



(19) **United States**

(12) **Patent Application Publication**  
**Sandbach**

(10) **Pub. No.: US 2002/0126101 A1**

(43) **Pub. Date: Sep. 12, 2002**

(54) **DETECTOR CONSTRUCTED FROM FABRIC HAVING PLANES WITH DIFFERING CONDUCTANCE**

Sep. 26, 1998 (GB) ..... 9820906.7  
Sep. 26, 1998 (GB) ..... 9820908.3  
Sep. 26, 1998 (GB) ..... 9820909.1  
Sep. 26, 1998 (GB) ..... 9820910.9

(75) Inventor: **David L. Sandbach**, London (GB)

Correspondence Address:  
**NIXON & VANDERHYE P.C.**  
1100 North Glebe Road, 8th Floor  
Arlington, VA 22201-4714 (US)

**Publication Classification**

(51) **Int. Cl.<sup>7</sup> ..... G09G 5/00**  
(52) **U.S. Cl. .... 345/173**

(73) Assignee: **ELECTROTEXILES COMPANY LIMITED**

(21) Appl. No.: **09/907,901**

(57) **ABSTRACT**

(22) Filed: **Jul. 19, 2001**

**Related U.S. Application Data**

(62) Division of application No. 09/298,172, filed on Apr. 23, 1999, now Pat. No. 6,369,804.

**Foreign Application Priority Data**

Sep. 26, 1998 (GB) ..... 9820902.6  
Sep. 26, 1998 (GB) ..... 9820905.9

A position detector is constructed from fabric having electrically conductive elements. The detector has at least two electrically conductive planes. An electrical potential is applied across one of the planes to determine the position to a mechanical interaction. In addition, second electrical property is determined to identify additional properties of the mechanical interactions.

