US 20150124601A1

(19) United States

(12) Patent Application Publication

Li et al.

(10) Pub. No.: US 2015/0124601 A1

(43) Pub. Date: May 7, 2015

(54) METHOD AND APPARATUS FOR NETWORK TRAFFIC OFFLOADING

(71) Applicant: **Nokia Corporation**, Espoo (FI)

(72) Inventors: **Zexian Li**, Espoo (FI); **Eng Hwee Ong**, Singapore (SG)

(73) Assignee: **Nokia Corporation**, Espoo (FI)

(21) Appl. No.: **14/400,705**

(22) PCT Filed: **Apr. 23, 2013**

(86) PCT No.: **PCT/FI2013/050449**

§ 371 (c)(1),
(2) Date: **Nov. 12, 2014**

Related U.S. Application Data

(60) Provisional application No. 61/647,782, filed on May 16, 2012.

Publication Classification

(51) **Int. Cl.**
H04W 36/22 (2006.01)
H04W 28/02 (2006.01)

(52) **U.S. Cl.**
CPC *H04W 36/22* (2013.01); *H04W 28/0268* (2013.01)

(57) **ABSTRACT**

A method, apparatus and computer program product are provided for managing network traffic offloading. In the context of a method, a method is provided that includes determining, based at least in part on a QoS (Quality of Service) mapping scheme, whether a data flow should be offloaded from a first access point to a second access point. The method may further include, if it is determined that the offload should be performed, causing the data flow to be offloaded to the second access point according to the QoS mapping scheme and causing a perceived QoS of the data flow to be monitored. The method may further include, in an instance in which the perceived QoS does not satisfy a predetermined desired QoS threshold, causing a remedial action to be performed.