

10. The image display of claim 9, wherein the ball bearing provides touch sensitivity for the image display.

11. The image display of claim 9, wherein the image display is a touch sensitive display.

12. An image display configured to provide a motion of an object at the surface of said image display comprising:

a hole layer (3-19) comprising a plurality of air holes; and an air hole (3-11) of the plurality of air holes tilted at an oblique angle with respect to the surface in one of four directions, such that air blown through said hole creates directed air pressure at the surface in the direction toward which the hole is tilted,

wherein said air hole is configured to be selectively opened and closed according to a movement signal received for moving an object at a surface of said image display in the direction of the directed air pressure.

13. The image display of claim 12, further comprising a control layer (3-59) comprised of a plurality of row electrodes and a plurality of column electrodes, and a foil arranged such that the foil closes the hole responsive to an electric current passed through a row of electrodes.

14. The image display of claim 12, wherein the plurality of air holes is comprised of sets of four holes, such that each hole of a set of four holes is located at a corner of an imaginary figure substantially resembling a rectangle with no intervening holes as viewed from the surface, wherein each hole of the set of four holes is tilted in one of the four directions.

15. The image display of claim 12, further comprising an air inlet channel (3-5) between holes of the plurality of holes.

16. The image display of claim 12, wherein holes of the plurality of holes are arranged between pixels of the image display.

17. The image display of claim 12, wherein the holes provide touch sensitivity for the image display.

18. An image display configured to cause a haptic sensation at a surface of the image display, said image display comprising:

a rod assembly (2-1) including a rod;

a set of driving magnets (2-20) arranged to be activated for a first activation by a first movement signal received and to be activated for a second activation by a second movement signal received; and

the rod (2-10) of said rod assembly arranged to move to an extended position with respect to the surface (2-50) of the image display responsive to the first activation, and to move to a retracted position with respect to the surface of the image display responsive to the second activation; wherein the haptic sensation is caused at the surface by the rod in the extended position.

19. The image display of claim 18, wherein at most one rod is provided between pixels.

20. The image display of claim 18, wherein the rod provides touch sensitivity for the image display.

* * * * *