



US 20090109007A1

(19) **United States**

(12) **Patent Application Publication**

Makinen et al.

(10) **Pub. No.: US 2009/0109007 A1**

(43) **Pub. Date: Apr. 30, 2009**

(54) **METHOD AND APPARATUS FOR SENSORY STIMULATION**

May 19, 2008 (FI) 20085472

(75) Inventors: **Ville Makinen, Espoo (FI); Petro Suvanto, Vantaa (FI); Jukka Linjama, Espoo (FI)**

Correspondence Address:
**BIRCH STEWART KOLASCH & BIRCH
PO BOX 747
FALLS CHURCH, VA 22040-0747 (US)**

(73) Assignee: **Senseg OY, Espoo (FI)**

(21) Appl. No.: **12/232,536**

(22) Filed: **Sep. 18, 2008**

Related U.S. Application Data

(60) Provisional application No. 60/960,899, filed on Oct. 18, 2007.

(30) **Foreign Application Priority Data**

Sep. 18, 2007 (FI) 20075651
Mar. 14, 2008 (FI) 20080213
May 19, 2008 (FI) 2008-5475

Publication Classification

(51) **Int. Cl.**
G08B 6/00 (2006.01)
G06F 3/01 (2006.01)
(52) **U.S. Cl.** **340/407.2; 340/407.1**
(57) **ABSTRACT**

An apparatus for producing an electrosensory sensation to a body member (120). The apparatus comprises one or more conducting electrodes (106), each of which is provided with an insulator (108). When the body member (120) is proximate to the conducting electrode, the insulator prevents flow of direct current from the conducting electrode to the body member. A capacitive coupling over the insulator (108) is formed between the conducting electrode (106) and the body member (120). The conducting electrodes are driven by an electrical input which comprises a low-frequency component (114) in a frequency range between 10 Hz and 500 Hz. The capacitive coupling and electrical input are dimensioned to produce an electrosensory sensation. The apparatus is capable of producing the electrosensory sensation independently of any mechanical vibration of the one or more conducting electrodes (106) or insulators (108).

