trolling C2, for instance by coupling the reference potential of the apparatus back to the user, as shown in FIG. 12.

[0085] Further analysis of the actual value of capacitance C1 shows that it can be treated as a capacitance consisting of three series-coupled partial capacitances: C_i of the insulator material, C_a of the air gap between insulator and finger, and C_s formed by the outmost skin layer that is electrically insulating the inner, conducting tissue from the environment. Each partial capacitance is given by:

$$C = \varepsilon\frac{S}{d}$$

[0086] Herein, ϵ is the permittivity (dielectric constant) of the insulating material, S is the (effective) surface area and d is the distance between the surfaces of the capacitor. In a series arrangement of capacitances, the smallest one of the individual capacitances dominates the overall value of the total capacitance C1. When the body member does not touch the surface of the insulated electrode but only approaches it, the capacitive coupling is weak. Thus the value of C1 is small and mainly determined by the air gap, C_a. When the body member touches the surface, the effective air gap is small (approximately the height ridges of the fingerprint profile on the skin surface). As capacitance is inversely proportional to the distance of the conducting surfaces forming the capacitor, corresponding C_a obtains a high value, and the value of C1 is determined by C_i and C_s. Thus the effectiveness of the electrosensory stimulus generation can be enhanced by appropriate selection of insulator material, particularly in terms of thickness and dielectric properties. For instance, selecting a material with a relatively high dielectric constant for the insulator reduces the electric field in the material but increases the electric field strength in the air gap and skin.

[0087] Furthermore, in applications where the surface is likely to be touched while the electrosensory stimulation or response is given, the effectiveness of the electrosensory stimulus generation can be enhanced by optimal selection of the material that will be touched by the body member. This is particularly significant in connection with insulators which are good volume insulators (insulators in the direction of the surface's normal) but less so in the direction along the surface.

[0088] An insulator's insulation capability along the surface may be negatively affected by surface impurities or moisture which have a negative effect on the apparent strength of the sensation felt by the body member to be stimulated. For instance, glass is generally considered a good insulator, but its surface tends to collect a thin sheet of moisture from the air. If the electrode of the CEI is insulated with glass, the electrosensory effect is felt in close proximity (when there is still an air gap between body member and the glass surface). However, when the glass surface is touched, even lightly, the electrosensory tends to weaken or disappear altogether. Coating the outer insulating surface with a material having a low surface conductance remedies such problems. The inventors speculate that if the surface having some surface conductivity is touched, it is the conductive layer on the surface that experiences the coulomb force rather than the body member touching the surface. Instead the touching body member acts as a kind of grounding for the conductive surface layer, for example via the stray capacitance of the body.

[0089] Instead of the measures described in connection with FIGS. 10 through 12, or in addition to such measures, stray capacitances can be controlled by arrangements in which several electrodes are used to generate potential differences among different areas of the touch screen surface. By way of example, this technique can be implemented by arranging the touch-sensitive surface of a hand-held device (eg the top side of the device) to a first potential, while the opposite side is arranged to a second potential, wherein the two different potentials can be the positive and negative poles of the device. Alternatively, a first surface area can be the electric ground (reference potential), while a second surface area is charged to a high potential.

[0090] Moreover, within the constraints imposed by the insulator layer(s), it is possible to form minuscule areas of different potentials, such as potentials with opposite signs or widely different magnitudes, wherein the areas are small enough that the user's body member, such as finger, is simultaneously subjected to the electric fields from several areas with different potentials.

[0091] FIG. 13 shows an embodiment in which the capacitive coupling is utilized to detect touching or approaching by the user's body member, such as finger. A detected touching or approaching by the user's body member can be passed as an input to a data processing device. In the embodiment shown in FIG. 13, the voltage source is floating. A floating voltage source can be implemented, via inductive or capacitive coupling and/or with break-before-make switches. A secondary winding of a transformer is an example of a simple yet effective floating voltage source. By measuring the voltage U4, it is possible to detect a change in the value(s) of capacitance(s) C1 and/or C2. Assuming that the floating voltage source is a secondary winding of a transformer, the change in capacitance(s) can be detected on the primary side as well, for example as a change in load impedance. Such a change in capacitance(s) serves as an indication of a touching or approaching body member.

[0092] In one implementation, the apparatus is arranged to utilize such indication of the touching or approaching body member such that the apparatus uses a first (lower) voltage to detect the touching or approaching by the body member and a second (higher) voltage to provide feedback to the user. For instance, such feedback can indicate any of the following: the outline of the/each touch-sensitive area, a detection of the touching or approaching body member by the apparatus, the significance of (the act to be initiated by) the touch-sensitive area, or any other information processed by the application program and which is potentially useful to the user.

[0093] FIG. 14 schematically illustrates an embodiment in which a single electrode and temporal variations in the intensity of the electrosensory stimulus can be used to create illusions of a textured touch screen surface. Reference numeral 1400 denotes a touch-sensitive screen which, for the purposes of describing the present embodiment, comprises three touch-sensitive areas A_1, A_2 and A_3. The approaching or touching by the touch-sensitive areas A_1, A_2 and A_3 of a user's finger 120 is detected by a controller 1406.

[0094] According to an embodiment of the invention, a conventional touch-sensitive screen 1400 can be complemented by an interface device according to the invention. Reference numeral 1404 denotes an electrode which is an implementation of the electrodes described in connection with previously-described embodiments, such as the electrode 106 described in connection with FIGS. 1 and 2. A supplemental insulator 1402 may be positioned between the