8. The handheld electronic device of claim **7**, wherein the input portion is movable relative to the housing between a first position and a second position, wherein the input portion lies on the flexible display in the first position, and wherein a top of the input portion is adjacent to a bottom of the housing in the second position.

9. The handheld electronic device of claim **8**, wherein the device is configured such that, when the input portion is in the first position, the input portion at least partially covers the flexible display.

10. The handheld electronic device of claim **8**, wherein the device is configured such that, when the input portion is in the second position, the input portion and the housing have a substantially planar arrangement.

11. The handheld electronic device of claim **7**, wherein the housing includes a first housing portion and a second housing portion movable relative to the first housing portion to transition the flexible display to a substantially planar arrangement.

12. The handheld electronic device of claim **11**, wherein the housing further includes a flexible housing portion connected to the first housing portion and the second housing portion to permit the second housing portion to move relative to the first housing portion.

13. The handheld electronic device of claim **7**, wherein the flexible display is configured to define a maximum angle of rotation of 180° when the flexible display is folded about the bendable portion.

14. The handheld electronic device of claim **7**, wherein, when the flexible display is folded about the bendable portion, the input portion is configured to limit movement of the second portion of the flexible display in a direction of the first portion of the flexible display.

15. A handheld electronic device, comprising:

a first housing portion;

a second housing portion rotatably arranged relative to the first housing portion such that the handheld electronic device is movable between an open configuration and a closed configuration;

a flexible display supported by the first housing portion and the second housing portion; and

an input portion linked to the section housing portion, wherein the device is configured such that the input portion is disposed in-between the first housing portion and the second housing portion adjacent the flexible display in the closed configuration.

16. The handheld electronic device of claim **15**, wherein the flexible display defines a folded arrangement when the device is in the closed configuration, and wherein the flexible display defines a substantially planar arrangement when the device is in the open configuration.

17. The handheld electronic device of claim **16**, wherein the input portion is movable relative to the housing between a first position and a second position when the device is in the open configuration, wherein the input portion lies on the flexible display in the first position, and wherein a top of the input portion is adjacent to a bottom of the housing in the second position.

18. The handheld electronic device of claim **17**, wherein the input portion at least partially covers the flexible display in the first position.

19. The handheld electronic device of claim **17**, wherein the flexible display is fully viewable when the input portion is in the second position.

20. The handheld electronic device of claim **15**, further including a flexible housing portion connecting the first housing portion and the second housing portion, wherein the second housing portion rotates about the flexible housing portion relative to the first housing portion.

* * * * *