

with a 50 ohm impedance, the current is small, it is therefore preferable to use the method described herein.

[0310] Among the inventions disclosed above is an arrangement for obtaining and conveying information about occupancy of a passenger compartment of a vehicle which comprises at least one wave-receiving sensor for receiving waves from the passenger compartment, generating means coupled to the wave-receiving sensor(s) for generating information about the occupancy of the passenger compartment based on the waves received by the wave-receiving sensor(s) and communications means coupled to the generating means for transmitting the information about the occupancy of the passenger compartment. As such, response personnel can receive the information about the occupancy of the passenger compartment and respond appropriately, if necessary. There may be several wave-receiving sensors and they may be, e.g., ultrasonic wave-receiving sensors, electromagnetic wave-receiving sensors, electric, magnetic or electromagnetic field sensors, antenna near field modification sensing sensors, energy absorption sensors, capacitance sensors, or combinations thereof. The information about the occupancy of the passenger compartment can include the number of occupants in the passenger compartment, as well as whether each occupant is moving non-reflexively and breathing. A transmitter may be provided for transmitting waves into the passenger compartment such that each wave-receiving sensor receives waves transmitted from the transmitter and modified by passing into and at least partially through the passenger compartment. Waves may also be from natural sources such as the sun, from lights on a vehicle or roadway, or radiation naturally emitted from the occupant or other object in the vehicle.

[0311] One or more memory units may be coupled to the generating means for storing the information about the occupancy of the passenger compartment and to the communications means. The communications means then can interrogate the memory unit(s) upon a crash of the vehicle to thereby obtain the information about the occupancy of the passenger compartment. In one particularly useful embodiment, means for determining the health state of at least one occupant are provided, e.g., a heartbeat sensor, a motion sensor such as a micropower impulse radar sensor for detecting motion of the at least one occupant and motion sensor for determining whether the occupant(s) is/are breathing, and coupled to the communications means. The communications means can interrogate the health state determining means upon a crash of the vehicle, or some other event or even continuously, to thereby obtain and transmit the health state of the occupant(s). The health state determining means can also comprise a chemical sensor for analyzing the amount of carbon dioxide in the passenger compartment or around the at least one occupant or for detecting the presence of blood in the passenger compartment. Movement of the occupant can be determined by monitoring the weight distribution of the occupant(s), or an analysis of waves from the space occupied by the occupant(s). Each wave-receiving sensor generates a signal representative of the waves received thereby and the generating means may comprise a processor for receiving and analyzing the signal from the wave-receiving sensor in order to generate the information about the occupancy of the passenger compartment. The processor can comprise pattern recognition means for classifying an occupant of the seat so that the information about the occupancy of the passenger

compartment includes the classification of the occupant. The wave-receiving sensor may be a micropower impulse radar sensor adapted to detect motion of an occupant whereby the motion of the occupant or absence of motion of the occupant is indicative of whether the occupant is breathing. As such, the information about the occupancy of the passenger compartment generated by the generating means is an indication of whether the occupant is breathing. Also, the wave-receiving sensor may generate a signal representative of the waves received thereby and the generating means receive this signal over time and determine whether any occupants in the passenger compartment are moving. As such, the information about the occupancy of the passenger compartment generated by the generating means includes the number of moving and non-moving occupants in the passenger compartment.

[0312] A related method for obtaining and conveying information about occupancy of a passenger compartment of a vehicle comprises the steps of receiving waves from the passenger compartment, generating information about the occupancy of the passenger compartment based on the received waves, and transmitting the information about the occupancy of the passenger compartment whereby response personnel can receive the information about the occupancy of the passenger compartment. Waves may be transmitted into the passenger compartment whereby the transmitted waves are modified by passing into and at least partially through the passenger compartment and then received. The information about the occupancy of the passenger compartment may be stored in at least one memory unit which is subsequently interrogated upon a crash of the vehicle to thereby obtain the information about the occupancy of the passenger compartment and thereafter the information with or without pictures of the passenger compartment before, during and/or after a crash or other event can be sent to a remote location such as an emergency services personnel station. A signal representative of the received waves can be generated by sensors and analyzed in order to generate the information about the state of health of at least one occupant of the passenger compartment and/or to generate the information about the occupancy of the passenger compartment (i.e., determine non-reflexive movement and/or breathing indicating life). Pattern recognition techniques, e.g., a trained neural network, can be applied to analyze the signal and thereby recognize and identify any occupants of the passenger compartment. In this case, the identification of the occupants of the passenger compartment can be included into the information about the occupancy of the passenger compartment.

[0313] Other embodiments disclosed above are directed to methods and arrangements for controlling deployment of an airbag. One exemplifying embodiment of an arrangement for controlling deployment of an airbag from an airbag module to protect an occupant in a seat of a vehicle in a crash comprises determining means for determining the position of the occupant or a part thereof, and control means coupled to the determining means for controlling deployment of the airbag based on the determined position of the occupant or part thereof. The determining means may comprise receiver means, e.g., a wave-receiving transducer such as an electromagnetic wave receiver (such as a SAW, CCD, CMOS, capacitor plate or antenna) or an ultrasonic transducer, for receiving waves from a space above a seat portion of the seat and processor means coupled to the receiver means for