

- 30.** The computer-readable medium of claim 29, wherein: determining the initial characteristics of the composite display includes determining particular ones of a plurality of portions of the application display to overlay with the virtual input device display.
- 31.** The computer-readable medium of claim 30, wherein: determining the particular ones of the plurality of portions include processing an indication of significance of the plurality of portions.
- 32.** The computer-readable medium of claim 28, wherein: determining the initial characteristics of the composite display includes determining a modification to the application display to accommodate the virtual input device display on the composite display.
- 33.** The computer readable medium of claim 32, wherein: determining a modification to the application display includes determining a modification to the spatial aspect of the application display.
- 34.** The computer readable medium of claim 33, wherein: determining a modification to the spatial aspect of the application display includes determining a portion of the application display to compress.
- 35.** The computer-readable medium of claim 34, wherein determining a portion of the application display to compress includes determining a portion of the application display to compress that includes an active input field and determining not to compress the portion of the application that includes the active input field.
- 36.** The computer-readable medium of claim 18, wherein the virtual input device initiation event is caused by a user gesture with respect to the touch screen.
- 37.** The computer-readable medium of claim 36, wherein the user gesture with respect to the touch screen comprises a user touching multiple points of the touch screen in a position having predetermined characteristics.
- 38.** The computer-readable medium of claim 36, wherein a position having predetermined characteristics includes a position having characteristics predetermined to be characteristic of fingers on a input device.
- 39.** The computer-readable medium of claim 36, wherein the user gesture with respect to the touch screen includes a user gesture with respect to an input field of an application display on the touch screen.
- 40.** The computer-readable medium of claim 36, wherein the user gesture with respect to the touch screen includes a user gesture with respect to a particular user interface item displayed on the touch screen.
- 41.** The computer-readable medium of claim 40, wherein the particular user interface item is associated with the application display.
- 42.** The computer-readable medium of claim 41, wherein the user interface item associated with the application display is an input field associated with the application display.
- 43.** The computer-readable medium of claim 42, wherein the user gesture includes at least one tap on a portion of the touch screen associated with the input field.
- 44.** The computer-readable medium of claim 43, wherein the particular user interface item is associated with a desktop portion of the touch screen associated with an operating system of the computer.
- 45.** The computer-readable medium of claim 28, the computer program further comprising:
in response to a virtual input device deactivation event, causing display of the composite image, including the virtual input device display, to be discontinued.
- 46.** The computer-readable medium of claim 35, wherein the virtual input device deactivation event is triggered by a particular gesture of the user with respect to the virtual input device display.
- 47.** The computer-readable medium of claim 35, wherein the virtual input device deactivation event is triggered by a particular gesture of the user with respect to the composite display, that is inconsistent with input via the virtual input device.
- 48.** The computer-readable medium of claim 35, wherein the virtual input device deactivation event is triggered by passing of a particular amount of time since a last input via the virtual input device.
- 49.** The computer-readable medium of claim 28, wherein: the composite display includes a visual indicator visually associating the virtual input device display with an input field of the application display.
- 50.** The computer-readable medium of claim 49, wherein the visual indicator is an arrow from a portion of the virtual input device display to the input field of the application display.
- 51.** The computer-readable medium of claim 50, wherein the portion of the virtual input device display is an input display of the virtual input device.
- 52.** The computer-readable medium of claim 49, wherein the visual indicator is a differentiated display of the input field of the application display.
- 53.** The computer-readable medium of claim 28, wherein the virtual input device display includes an input buffer display.
- 54.** The computer-readable medium of claim 53, the computer program further comprising:
transferring input from the input buffer display of the virtual input device display to an input field of the application display.

* * * * *