[0047] Haptic layer **612**, in one embodiment, includes a grid of MEMS pumps **602**, which further includes at least one pocket **604**. Each MEMS pump **602** includes a pressurized valve **608** and a depressurized valve **610**. Pressurized valve **608** is coupled to an inlet tube **614** while depressurized valve **610** is coupled to an outlet tube **616**. In one embodiment, inlet tube **614**, which is under high liquid pressure, is used to pump liquid through pressurized valve **608** to expand pocket **604**. Similarly, outlet tube **616**, which is under low pressure, is used to release the liquid through depressurized valve **610** to release the pressure from pocket **604**. It should be noted that MEMS pumps **602** can be coupled to the same pressurized liquid reservoir. It should be further noted that pressurized valve **608** and depressurized valve **610** can be combined into one single valve for both inlet tube **614** and outlet tube **616**. It should be further noted that inlet tube **614** and outlet tube **616** can also be combined into one tube.

[0048] A grid of MEMS pumps **602** includes an array of pressurized valves **608** and depressurized valves **610**, wherein pressurized valves **608** are coupled with a rear or a side mounted liquid reservoir under pressure while depressurized vales **610** are coupled to a rear or a side mounted depressurized liquid reservoir with low pressure. Valves 608-610 control the filling and emptying the liquid pockets **604** in MEMS pumps **602** to produce localized strain. An advantage of using pressurized liquid reservoir is to quickly deform the surface of insulated layer **606** and to maintain the deformation with minimal or no energy consumption (or expenditure). It should be noted that MEMS pump **602** can also use pressurized air or other gases to achieve similar results as liquid.

[0049] Device **600** further includes a set of control wires **617-618**, which can be used to control pressurized valve **608** and depressurized valve **610**, respectively. It should be noted that each valve in haptic layer **612** is addressable using electrical signals transmitted from wires or wireless network.

[0050] FIG. **6**(*b*) illustrates two diagrams of an interface device **620** and **650** having an array of MEMS pumps **604** in accordance with one embodiment of the present invention. Device **620** illustrates an activated pocket **623**, which includes an activated inlet valve **630** and a deactivated outlet valve **632**. During an operation, pocket **623** increases its physical volume (or size) from its original state **624** to its expanded pocket **623** when inlet valve **630** is activated. When inlet valve **630** is activated (or open) in response to electrical signal from wire **628**, inlet tube **625** pumps liquid **626** from pressurized reservoir to pocket **623**. Due to the expansion of pocket **623**, a localized strain **622** of insulated layer **606** is created.

[0051] Device **650** illustrates an activated MEMS pump returns from its expanded state of pocket **623** to the original state of pocket **653**. When depressurized valve **660** is activated, depressurized valve **660** releases liquid **656** from pocket **653** to low pressurized outlet **654**. It should be noted that depressurized valve **660** is controlled by at least one control signal via wire **658**. The changing in volume between original size of pocket **604** and expanded size of pocket **623** generates haptic effects.

[0052] FIG. **7** illustrates a side view diagram for an interface device **700** having an array of haptic cells **702** using variable porosity membrane **710** in accordance with one embodiment of the present invention. Device **700** includes an insulated layer **706** and a haptic layer **712**. While the top surface of insulated layer **706** is configured to receive inputs from a user, the bottom surface of insulated layer **706** is placed adjacent to the top surface of haptic layer **712**. The bottom surface of haptic layer **712** is, in one embodiment, placed adjacent to a display (not shown in FIG. **7**), wherein haptic layer **712** and insulated layer **706** may be substantially transparent thereby objects or images displayed in the display can be seen through haptic layer **712** and insulated layer **706**. It should be noted that display is not a necessary component in order for the interface device to function.

[0053] Haptic layer **712**, in one embodiment, includes a grid of haptic cells **702**, inlet valves **703**, and outlet valves **704**. Haptic cells **702**, in one embodiment, are pockets capable of containing fluid. Haptic layer **712** is similar to haptic layer **612** as shown in FIG. **6**(*a*) except that haptic layer **712** employs porosity membranes. While each inlet valve **703** is controlled by control signal(s) transmitted by wire **713**, each outlet valve **704** is controlled by electrical signals transmitted over a wire **714**. Every inlet valve **703** or outlet valve **704** employs at least one porosity membrane **710**. Porosity membranes **710** are coupled (or face) to a liquid reservoir wherein each membrane **710** is configured to control how much liquid should enter and/or pass through membrane **710**. An advantage of using porosity membranes is to maintain the deformation of insulated layer **706** with minimal or no energy consumption.

[0054] FIG. **8** is a side view of an interface device **800** having an array of haptic cells **802** using various resonant devices in accordance with one embodiment of the present invention. Device **800** includes an insulated layer **806** and a haptic layer **812**. While the top surface of insulated layer **806** is configured to receive an input from a user, the bottom surface of insulated layer **806** is placed adjacent to the top surface of haptic layer **812**. The bottom surface of haptic layer **812** is, in one embodiment, placed adjacent to a display (not shown in FIG. **8**), wherein haptic layer **812** and insulated layer **806** may be substantially transparent thereby objects or images displayed in the display can be seen through haptic layer **812** and insulated layer **806**. It should be noted that display is not a necessary component in order for the interface device to function.

[0055] Haptic layer **812**, in one embodiment, includes a grid of haptic cells **802**, wherein each cell **802** further includes a permanent magnet **804**, an electro magnet **810**, and two springs **808**. Haptic layer **812** is similar to haptic layer **612** shown in FIG. **6**(*a*) except that haptic layer **812** employs resonant devices while haptic layer **612** uses MEMS pumps. Haptic cell **802**, in one embodiment, uses a resonant mechanical retractable device to generate haptic effects. The resonant mechanical retractable device vibrates in response to a unique frequency, which could be generated by a side mounted resonant stimulator **816** or a rear mounted resonant stimulator **814**. A resonant grid, in one embodiment, is used to form a haptic layer **812**. Each cell **802** is constructed using resonant mechanical elements such as Linear Resonant Actuator ("LRA") or MEMS springs. Each cell **802**, however, is configured to have a slightly different resonant frequency and a high Q (high amplification at resonance and a narrow resonant frequency band). As such, each cell **802** can be stimulated using mechanical pressure waves originating at the edges of the sheet. The haptic effects can also be generated by a piezoelectric or other high bandwidth actuator that induces acoustic waves.

[0056] Cell **802**, in another embodiment, includes one spring **808**. In yet another embodiment, cell **802** includes more than two springs **808**. Each spring **808** is configured to