

structively or destructively depending on the position of the movable reflective layer, producing either an overall reflective or non-reflective state for each pixel.

[0036] The depicted portion of the pixel array in FIG. 1 includes two adjacent interferometric modulators **12a** and **12b**. In the interferometric modulator **12a** on the left, a movable reflective layer **14a** is illustrated in a relaxed position at a predetermined distance from an optical stack **16a**, which includes a partially reflective layer. In the interferometric modulator **12b** on the right, the movable reflective layer **14b** is illustrated in an actuated position adjacent to the optical stack **16b**.

[0037] The optical stacks **16a** and **16b** (collectively referred to as optical stack **16**), as referenced herein, typically comprise of several fused layers, which can include an electrode layer, such as indium tin oxide (ITO), a partially reflective layer, such as chromium, and a transparent dielectric. The optical stack **16** is thus electrically conductive, partially transparent and partially reflective, and may be fabricated, for example, by depositing one or more of the above layers onto a transparent substrate **20**. The partially reflective layer can be formed from a variety of materials that are partially reflective such as various metals, semiconductors, and dielectrics. The partially reflective layer can be formed of one or more layers of materials, and each of the layers can be formed of a single material or a combination of materials.

[0038] In some embodiments, the layers of the optical stack are patterned into parallel strips, and may form row electrodes in a display device as described further below. The movable reflective layers **14a**, **14b** may be formed as a series of parallel strips of a deposited metal layer or layers (orthogonal to the row electrodes of **16a**, **16b**) deposited on top of posts **18** and an intervening sacrificial material deposited between the posts **18**. When the sacrificial material is etched away, the movable reflective layers **14a**, **14b** are separated from the optical stacks **16a**, **16b** by a defined gap **19**. A highly conductive and reflective material such as aluminum may be used for the reflective layers **14**, and these strips may form column electrodes in a display device.

[0039] With no applied voltage, the cavity **19** remains between the movable reflective layer **14a** and optical stack **16a**, with the movable reflective layer **14a** in a mechanically relaxed state, as illustrated by the pixel **12a** in FIG. 1. However, when a potential difference is applied to a selected row and column, the capacitor formed at the intersection of the row and column electrodes at the corresponding pixel becomes charged, and electrostatic forces pull the electrodes together. If the voltage is high enough, the movable reflective layer **14** is deformed and is forced against the optical stack **16**. A dielectric layer (not illustrated in this Figure) within the optical stack **16** may prevent shorting and control the separation distance between layers **14** and **16**, as illustrated by pixel **12b** on the right in FIG. 1. The behavior is the same regardless of the polarity of the applied potential difference. In this way, row/column actuation that can control the reflective vs. non-reflective pixel states is analogous in many ways to that used in conventional LCD and other display technologies.

[0040] FIGS. 2 through 5B illustrate one exemplary process and system for using an array of interferometric modulators in a display application.

[0041] FIG. 2 is a system block diagram illustrating one embodiment of an electronic device that may incorporate

aspects of the invention. In the exemplary embodiment, the electronic device includes a processor **21** which may be any general purpose single- or multi-chip microprocessor such as an ARM, Pentium®, Pentium II®, Pentium III®, Pentium IV®, Pentium® Pro, an 8051, a MIPS®, a Power PC®, an ALPHA®, or any special purpose microprocessor such as a digital signal processor, microcontroller, or a programmable gate array. As is conventional in the art, the processor **21** may be configured to execute one or more software modules. In addition to executing an operating system, the processor may be configured to execute one or more software applications, including a web browser, a telephone application, an email program, or any other software application.

[0042] In one embodiment, the processor **21** is also configured to communicate with an array driver **22**. In one embodiment, the array driver **22** includes a row driver circuit **24** and a column driver circuit **26** that provide signals to a display array or panel **30**. The cross section of the array illustrated in FIG. 1 is shown by the lines 1-1 in FIG. 2. For MEMS interferometric modulators, the row/column actuation protocol may take advantage of a hysteresis property of these devices illustrated in FIG. 3. It may require, for example, a 10 volt potential difference to cause a movable layer to deform from the relaxed state to the actuated state. However, when the voltage is reduced from that value, the movable layer maintains its state as the voltage drops back below 10 volts. In the exemplary embodiment of FIG. 3, the movable layer does not relax completely until the voltage drops below 2 volts. There is thus a range of voltage, about 3 to 7 V in the example illustrated in FIG. 3, where there exists a window of applied voltage within which the device is stable in either the relaxed or actuated state. This is referred to herein as the “hysteresis window” or “stability window.” For a display array having the hysteresis characteristics of FIG. 3, the row/column actuation protocol can be designed such that during row strobing, pixels in the strobed row that are to be actuated are exposed to a voltage difference of about 10 volts, and pixels that are to be relaxed are exposed to a voltage difference of close to zero volts. After the strobe, the pixels are exposed to a steady state voltage difference of about 5 volts such that they remain in whatever state the row strobe put them in. After being written, each pixel sees a potential difference within the “stability window” of 3-7 volts in this example. This feature makes the pixel design illustrated in FIG. 1 stable under the same applied voltage conditions in either an actuated or relaxed pre-existing state. Since each pixel of the interferometric modulator, whether in the actuated or relaxed state, is essentially a capacitor formed by the fixed and moving reflective layers, this stable state can be held at a voltage within the hysteresis window with almost no power dissipation. Essentially no current flows into the pixel if the applied potential is fixed.

[0043] In typical applications, a display frame may be created by asserting the set of column electrodes in accordance with the desired set of actuated pixels in the first row. A row pulse is then applied to the row 1 electrode, actuating the pixels corresponding to the asserted column lines. The asserted set of column electrodes is then changed to correspond to the desired set of actuated pixels in the second row. A pulse is then applied to the row 2 electrode, actuating the appropriate pixels in row 2 in accordance with the asserted column electrodes. The row 1 pixels are unaffected by the row 2 pulse, and remain in the state they were set to during