



US 20090315830A1

(19) **United States**  
(12) **Patent Application Publication**  
**WESTERMAN**

(10) **Pub. No.: US 2009/0315830 A1**  
(43) **Pub. Date: Dec. 24, 2009**

(54) **KEYSTROKE TACTILITY ARRANGEMENT ON A SMOOTH TOUCH SURFACE**

(76) Inventor: **Wayne Carl WESTERMAN**, San Francisco, CA (US)

Correspondence Address:  
**APPLE C/O MORRISON AND FOERSTER, LLP**  
**LOS ANGELES**  
**555 WEST FIFTH STREET SUITE 3500**  
**LOS ANGELES, CA 90013-1024 (US)**

(21) Appl. No.: **12/550,280**

(22) Filed: **Aug. 28, 2009**

**Related U.S. Application Data**

(62) Division of application No. 11/380,109, filed on Apr. 25, 2006.

**Publication Classification**

(51) **Int. Cl.**  
**G06F 3/041** (2006.01)  
**G06F 3/02** (2006.01)  
**G08B 6/00** (2006.01)  
(52) **U.S. Cl.** ..... **345/168; 340/407.2; 345/173**

(57) **ABSTRACT**  
Disclosed are four arrangements for providing tactility on a touch surface keyboard. One approach is to provide tactile feedback mechanisms, such as dots, bars, or other shapes on all or many keys. In another embodiment, an articulating frame may be provided that extends when the surface is being used in a typing mode and retracts when the surface is used in some other mode, e.g., a pointing mode. The articulating frame may provide key edge ridges that define the boundaries of the key regions or may provide tactile feedback mechanisms within the key regions. The articulating frame may also be configured to cause concave depressions similar to mechanical key caps in the surface. In another embodiment, a rigid, non-articulating frame may be provided beneath the surface. A user will then feel higher resistance when pressing away from the key centers, but will feel a softer resistance at the key center.

