



US 20050280635A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2005/0280635 A1**

Hinata

(43) **Pub. Date: Dec. 22, 2005**

(54) **INPUT DEVICE, ELECTRO-OPTICAL DEVICE, ELECTRONIC APPARATUS, METHOD OF MANUFACTURING INPUT DEVICE, AND METHOD OF MANUFACTURING ELECTRO-OPTICAL DEVICE**

(30) **Foreign Application Priority Data**

Jun. 22, 2004 (JP) 2004-183601

Publication Classification

(51) **Int. Cl.⁷** **G02F 1/1333; G09G 5/00**

(52) **U.S. Cl.** **345/173; 349/40; 345/104**

(76) **Inventor: Shoji Hinata, Matsumoto (JP)**

(57) **ABSTRACT**

Correspondence Address:
HARNES, DICKEY & PIERCE, P.L.C.
P.O. BOX 828
BLOOMFIELD HILLS, MI 48303 (US)

An input device includes a first substrate that has a coordinate input surface, and a second substrate that faces the first substrate. In the input device, a position on the coordinate input surface of the first substrate is directly indicated, such that coordinate information at the indicated position is input. The first substrate and the second substrates are made of glass substrates. According to the coordinate input surface of the first substrate, a thin-plate region having a thinner thickness than the periphery of the coordinate input surface is formed.

(21) **Appl. No.: 11/143,292**

(22) **Filed: Jun. 2, 2005**

