

120 to expand the cavity 125 from the retracted volume setting to the extended volume setting and, ultimately, deforming a particular region 113 of the surface 115. The displacement device 130 preferably modifies the volume of the fluid 120 by (1) modifying the volume of the existing fluid in the cavity 125, or (2) adding and removing fluid to and from the cavity 125. The displacement device 130 may, however, influence the volume of the fluid 120 by any suitable device or method. Modifying the volume of the existing fluid in the cavity 125 most likely has an advantage of lesser complexity, while adding and removing fluid to and from the cavity 125 most likely has an advantage of maintaining the deformation of the surface 115 without the need for additional energy (if valves or other lockable mechanisms are used). When used with a mobile phone device, the displacement device 130 preferably increases the volume of the fluid 120 within the cavity 125 by approximately 0.003-0.1 ml. When used with this or other applications, however, the volume of the fluid may be increased (or possibly decreased) by any suitable amount.

[0031] Modifying the existing fluid in the cavity 125 may be accomplished in several ways. In a first example, as shown in FIGS. 5a and 5b, the fluid may be an expandable fluid and the displacement device 130 may include a heating element that heats the expandable fluid, thereby expanding the volume of the existing fluid in the cavity 125 (according to the ideal gas law,  $PV=nRT$ ). The heating element, which may be located within, adjacent the cavity 125, or any other location suitable to providing heat to the fluid, is preferably a resistive heater (made of a material such as TaN or Nichrome). In a second example, the fluid may include an expandable substance, such as plastic expandable microspheres. In a third example, the fluid may include paraffin. While these are three examples, the displacement device 130 can be any other suitable device or method that ultimately expands the cavity 125 from the retracted volume setting to the extended volume setting by modifying the existing fluid in the cavity 125.

[0032] Adding and removing fluid to and from the cavity 125 may also be accomplished in several ways. In a first example, as shown in FIG. 6, the displacement device 130 includes a reservoir 132 to hold additional fluid and a pump 134 to displace fluid from the reservoir 132 to the cavity 125. The reservoir 132 is preferably remote from the cavity 125 (and connected by a channel 138 or other suitable device), but may alternatively be located adjacent the cavity 125 and connected directly to the cavity 125. A portion of the channel 138 is preferably a micro-fluidic channel (having cross-sectional dimensions in the range of 1 micrometer to 1000 micrometers), but depending on the size and costs constraints of the user interface system 100, the channel 138 may have any suitable dimensions. The pump 134 is preferably a micro-pump (such as pump #MDP2205 from ThinXXS Microtechnology AG of Zweibrucken, Germany or pump #mp5 from Bartels Mikrotechnik GmbH of Dortmund, Germany), but may be any suitable device to pump fluid from one location to another. The pump 134 is preferably located at a distance from the cavity 125, and is preferably connected to the cavity 125 by a channel 138. To extend the cavity 125 from a retracted volume setting to the extended volume setting, the pump 134 displaces fluid from a reservoir 132, through the channel 138, and into the cavity 125. To retract the cavity 125 from the extended volume setting to the retracted volume setting, the pump 134 preferably “vents” or pumps in a reverse direction from the cavity 125 to the reservoir 132. In

a second example, as shown in FIG. 7, the displacement device 130 includes a reservoir 132 to hold additional fluid, a first pump 134 to displace fluid from the reservoir 132 to the cavity 125, a second pump 136 to displace fluid from the cavity 125 to the reservoir 132, a first valve located between the first pump 134 and the cavity 125, and a second valve located between the cavity 125 and the second pump 136. To extend the cavity 125 from the retracted volume setting to the extended volume setting, the first valve is opened, the second valve is closed, and the first pump 134 displaces fluid from the reservoir 132, through the channel 138, and into the cavity 125. To retract the cavity 125 from the extended position to the retracted position, the first valve is closed, the second valve is opened, and the second pump 136 displaces fluid from the cavity 125, through the channel 138, and into the reservoir 132. In other respects, the second example is similar to the first example above. The user interface system 100 may omit the second pump 136 and simply retract the cavity 125 from the extended volume setting to the retracted volume setting by opening the second valve and allowing the cavity 125 to vent or “drain” into the reservoir 132 (potentially assisted by the elasticity of the sheet 110 returning to an un-deformed state). In a third example, as shown in FIGS. 8a and 8b, the displacement device 130 includes an actuator, such as a linear actuator, that displaces fluid into and out of the cavity 125. To extend the cavity 125 from a retracted volume setting to the extended volume setting, as shown in FIG. 8a, the linear actuator displaces fluid through the channel 138 and into the cavity 125. To retract the cavity 125 from the extended volume setting to the retracted volume setting, as shown in FIG. 8b, the linear actuator draws fluid in a reverse direction from the cavity 125 to the reservoir 132. In other respects, the third example is similar to the second example above. While these are three examples, the displacement device 130 can be any other suitable device or method that ultimately expands the cavity 125 from the retracted volume setting to the extended volume setting by adding and removing fluid to and from the cavity 125.

[0033] Although the cause of the deformation of a particular region 113 of the surface 115 has been described as a modification of the volume of the fluid in the cavity 125, it is possible to describe the cause of the deformation as an increase in the pressure below the surface 115 relative to the pressure above the surface 115. When used with a mobile phone device, an increase of approximately 0.1-10.0 psi between the pressure below the sheet 110 relative to the pressure above the sheet no, is preferably enough to deform a particular region 113 of the surface 115. When used with this or other applications, however, the modification of the pressure may be increased (or possibly decreased) by any suitable amount.

### 3. The Deformation of the Surface And the Sensor

[0034] The deformation of the particular region 113 functions to provide tactile feedback and tactile guidance on the surface 115 for the user. The deformation of the particular region 113 also preferably functions to inform the user of the type of input the deformation represents. For example, the deformation of the particular region 113 may be of a shape that indicates the type of input that the deformation represents. For example, a circular deformation may indicate to the user that they are to select an area along the circular deformation. Alternatively, the sheet 110 may include tactile instructions, for example, a pattern of beads on the particular