

haptic feedback provided by the interface. Buttons may present raised surfaces and may unlabeled allowing for a uniform display to be presented across all of display 510 including the raised surfaces of one or more buttons.

[0033] In the preceding specification, various preferred embodiments have been described with reference to the accompanying drawings. It will, however, be evident that various modifications and changes may be made thereto, and additional embodiments may be implemented, without departing from the broader scope of the specification and the claims as set forth below. The specification and drawings are accordingly to be regarded in an illustrative rather than restrictive sense.

1. A system comprising:
 - a touch screen display panel; and
 - a tactile panel wherein the touch screen display panel is positioned on top of the tactile panel and the tactile panel creates one or more tactile surfaces on the touch screen display panel providing tactile information to a user of the touch screen display panel, wherein at least one of the one or more tactile surfaces provides different outputs according to different levels of pressure applied by the user.
2. The system of claim 1 wherein the touch screen display panel is an organic light emitting diode display panel.
3. The system of claim 1 wherein the tactile surfaces respond to a force applied by a user and return to a prior position when the force is removed.
4. The system of claim 1 wherein the tactile surfaces are raised.
5. The system of claim 1 wherein the tactile surfaces are recessed.
6. The system of claim 1 wherein the tactile panel is comprised of a flexible membrane layer allowing a user to depress one or more of the tactile surfaces.
7. The system of claim 1 wherein the one or more tactile surfaces approximate a keyboard.
8. The system of claim 1 wherein the one or more tactile surfaces approximate a keypad.
9. The system of claim 1 wherein the number of tactile surfaces on the touch screen display panel is variable.
10. The system of claim 9 wherein the number of tactile surfaces is varied according to the use of the touch screen display panel.

11. A method, comprising:
 providing a touch screen display panel; and
 providing a tactile panel wherein the touch screen display panel is positioned on top of the tactile panel and the tactile panel creates one or more tactile surfaces on the touch screen display panel providing tactile information to a user of the touch screen display panel, wherein at least one of the one or more tactile surfaces provides different outputs according to different levels of pressure applied by the user.

12. The method of claim 11 wherein the touch screen display panel is an organic light emitting diode display panel.

13. The method of claim 11 wherein the tactile surfaces recess in response to a force applied by a user and return to a prior position when the force is removed.

14. The method of claim 11 wherein the tactile surfaces are raised.

15. The method of claim 11 wherein the tactile surfaces are recessed.

16. The method of claim 11 wherein the tactile panel is comprised of a flexible membrane layer allowing a user to depress one or more of the tactile surfaces.

17. The method of claim 11 wherein the one or more tactile surfaces approximate a keyboard.

18. The method of claim 11 wherein the one or more tactile surfaces approximate a keypad.

19. The method of claim 11 the number of tactile surfaces on the touch screen display panel is variable.

20. The method of claim 19 wherein the number of tactile surfaces is varied according to the use of the touch screen display panel.

21. A system comprising:
 a touch screen display panel; and
 one or more push button switches wherein the touch screen display panel is positioned on top of the one or more push button switches and the one or more push button switches create one or more tactile surfaces on the touch screen display panel providing tactile information to a user of the touch screen display panel, wherein at least one of the one or more tactile surfaces provides different outputs according to different levels of pressure applied by the user.

* * * * *