

[0072] In one embodiment of a device **80**, a display screen **82** typically covers a large portion of the surface of the computer device **80**. Screen **82** is preferably a flat-panel display as is well known to those skilled in the art and can display text, images, animations, etc.; in some embodiments screen **80** is as functional as any personal computer screen. Display screen **82** is preferably a "touch screen" that includes sensors which allow the user to input information to the computer device **80** by physically contacting the screen **80** (i.e. it is another form of planar "touch device" similar to the touchpad **16**). For example, a transparent sensor film can be overlaid on the screen **80**, where the film can detect pressure from an object contacting the film. The sensor devices for implementing touch screens are well known to those skilled in the art.

[0073] The user can select graphically-displayed buttons or other graphical objects by pressing a finger or a stylus to the screen **82** at the exact location where the graphical object is displayed. Furthermore, some embodiments allow the user to "draw" or "write" on the screen by displaying graphical "ink" images **85** at locations where the user has pressed a tip of a stylus, finger, or other object. Handwritten characters can be recognized by software running on the device microprocessor as commands, data, or other input. In other embodiments, the user can provide input additionally or alternatively through voice recognition, where a microphone on the device inputs the user's voice which is translated to appropriate commands or data by software running on the device. Physical buttons **84** can also be included in the housing of the device **80** to provide particular commands to the device **80** when the buttons are pressed. Many PDA's are characterized by the lack of a standard keyboard for character input from the user; rather, an alternative input mode is used, such as using a stylus to draw characters on the screen, voice recognition, etc. However, some PDA's also include a fully-functional keyboard as well as a touch screen, where the keyboard is typically much smaller than a standard-sized keyboard. In yet other embodiments, standard-size laptop computers with standard keyboards may include flat-panel touch-input display screens, and such screens (similar to screen **12** of FIG. **1**) can be provided with haptic feedback according to the present invention.

[0074] In the present invention, the touch screen **82** provides haptic feedback to the user similarly to the touchpad **16** described in previous embodiments. One or more actuators **86** can be coupled to the underside of the touch screen **82** to provide haptic feedback such as pulses, vibrations, and textures; for example, an actuator **86** can be positioned near each corner of the screen **82**, as shown in FIG. **8a**. Other configurations of actuators can also be used. The user can experience the haptic feedback through a finger or a held object such as a stylus **87** that is contacting the screen **82**.

[0075] As shown in FIG. **8b**, the touch screen **82** is preferably coupled to the housing **88** of the device **80** by one or more spring or compliant elements **90**, such as helical springs, leaf springs, flexures, or compliant material (foam, rubber, etc.) The compliant element allows the touch screen **82** to move approximately along the z-axis, thereby providing haptic feedback similarly to the touchpad embodiments described above. Actuators **86** can be piezo-electric actuators, voice coil actuators, or any of the other types of actuators described above for the touchpad embodiments. As shown in FIG. **8b**, the actuators **86** are directly coupled to

the touch screen **82** similarly to the touchpad embodiment of FIG. **3**; alternatively, an inertial mass can be moved to provide inertial feedback in the z-axis of the touch screen, similarly to the touchpad embodiment of FIG. **6**. Other features described above for the touchpad are equally applicable to the touch screen embodiment **80**.

[0076] In the embodiments of touch input devices (touchpad and touch screen) described herein, it is also advantageous that contact of the user is detected by the touch input device. Since haptic feedback need only be output when the user is contacting the touch device, this detection allows haptic feedback to be stopped (actuators "turned off") when no objects are contacting the touch input device. This feature can conserve battery power for portable devices. If a local touch device microprocessor (or similar circuitry) is being used in the computer, such a microprocessor can turn off actuator output when no user contact is sensed, thus alleviating the host processor of additional computational burden.

[0077] While this invention has been described in terms of several preferred embodiments, it is contemplated that alterations, permutations, and equivalents thereof will become apparent to those skilled in the art upon a reading of the specification and study of the drawings. For example, many different types of actuators can be used to output tactile sensations to the user. Furthermore, many of the features described in one embodiment can be used interchangeably with other embodiments. Furthermore, certain terminology has been used for the purposes of descriptive clarity, and not to limit the present invention.

What is claim is:

1. A haptic feedback touch control for inputting signals to a computer and for outputting forces to a user of the touch control, the touch control comprising:

a touch input device including an approximately planar touch surface operative to input a position signal to a processor of said computer based on a location on said touch surface which said user contacts, said position signal representing a location in two dimensions, wherein said computer positions a cursor in a graphical environment displayed on a display device based at least in part on said position signal; and

at least one actuator coupled to said touch input device, said actuator outputting a force on said touch input device to provide a haptic sensation to said user contacting said touch surface, wherein said actuator outputs said force based on force information output by said processor, said actuator outputting a force directly on said touch input device.

2. A haptic feedback touch control as recited in claim 1 wherein said touch input device is a touchpad, said touchpad being separate from a display screen of said computer.

3. A haptic feedback touch control as recited in claim 1 wherein said touch input device is included in a display screen of said computer as a touch screen.

4. A haptic feedback touch control as recited in claim 1 wherein said touch input device is integrated in a housing of said computer.

5. A haptic feedback touch control as recited in claim 4 wherein said computer is a portable computer.

6. A haptic feedback touch control as recited in claim 1 wherein said touch input device is provided in a housing that is separate from said computer.