



(19) **United States**

(12) **Patent Application Publication**  
**URAOKA et al.**

(10) **Pub. No.: US 2012/0267258 A1**

(43) **Pub. Date: Oct. 25, 2012**

(54) **METHOD FOR ELECTROCHEMICALLY  
DETECTING ANALYTE**

(30) **Foreign Application Priority Data**

Apr. 22, 2011	(JP)	2011-096319
Apr. 22, 2011	(JP)	2011-096341
Mar. 29, 2012	(JP)	2012-075914

(75) Inventors: **Yukiharu URAOKA**, Ikoma-shi (JP); **Bin Zheng**, Ikoma-shi (JP); **Seigo SUZUKI**, Ashiya-shi (JP); **Hiroya KIRIMURA**, Kobe-shi (JP); **Masayoshi SEIKE**, Kobe-shi (JP); **Shigeki IWANAGA**, Kobe-shi (JP); **Nobuyasu HORI**, Kobe-shi (JP)

**Publication Classification**

(51) **Int. Cl.**  
**G01N 27/26** (2006.01)

(52) **U.S. Cl.** ..... **205/780.5; 205/775**

(57) **ABSTRACT**

(73) Assignees: **NARA INSTITUTE OF  
SCIENCE AND TECHNOLOGY**,  
Ikoma-shi (JP); **SYSMEX  
CORPORATION**, Kobe-shi (JP)

In order to provide a method for electrochemically detecting an analyte which can detect an analyte with high detection sensitivity, when detecting an analyte S trapped on a working electrode, a label binding substance 90 in which a labeling substance 93 and a first binding substance 92 which traps the analyte S are at least retained on a support 91 composed of polypeptide is brought into contact with the analyte. Alternatively, a complex containing the analyte S and a label binding substance 290 in which a labeling substance 293 is retained on a binding substance 291 which binds to the analyte S via a modulator 292 is formed. Then, the labeling substance present on the working electrode is electrochemically detected.

(21) Appl. No.: **13/452,466**

(22) Filed: **Apr. 20, 2012**

