FIG. 16


(1) read by
(1) creates
(1) read by
J
Data Type
Name
Documentation
Parent Data Type
Operations
Operation<1>
Operation<2>
Operation<n>
Constraints
Constraints<1>
Constraints<2>
Constraints<n>
Tagged Values
Tagged Values<1>
Tagged Values<2>
Tagged Values<n>
(1a) handled by
(1b) handled by
(1c) handled by
(1d) handled by
(1e) handled by
(1f) handled by
Data Type Descriptor Handler
Name Handler
Documentation Handler
Parent Data Type Handler
Operations Handler
Constraints Handler
Tagged Values Handler
(2) maps to
(3) maps to
(4) maps to
(5) creates
(6) creates
(7) creates
Data Type Descriptor
Name
Description
Parent Type Name
Operation Descriptors
Operation Desc<1>
Operation Desc<2>
Operation Desc<n>
(2) read by
K
Constraint Descriptors
Constraint Desc<1>
Constraint Desc<2>
Constraint Desc<n>
(3) read by
L
Default Value Config
Model Name
Property Value<1>
Property Value<2>
Property Value<n>
(4) read by
M
Hint Instances
Hint Instance<1>
Hint Instance<2>
Hint Instance<n>
Role Instances
Role Instance<1>
Role Instance<2>
Role Instance<n>