FIG. 28


(1) read by
(1) creates
(1) read by
CC
Interface
Name
Documentation
Visibility
Root
Leaf
Attributes
Attribute<1>
Attribute<2>
Attribute<n>
Operations
Operation<1>
Operation<2>
Operation<n>
Constraints
Constraints<1>
Constraints<2>
Constraints<n>
Tagged Values
Tagged Values<1>
Tagged Values<2>
Tagged Values<n>
Code language
(1a) handled by
(1b) handled by
(1c) handled by
(1d) handled by
(1e) handled by
(1f) handled by
(1g) handled by
(1h) handled by
(1i) handled by
(1j) handled by
Interface Handler
Name Handler
Documentation Handler
Visibility Handler
Root Handler
Leaf Handler
Attributes Handler
Operations Handler
Constraints Handler
Tagged Values Handler
Language Handler
(11) lookup role
Metamodel Repository
(11a) lookup role
Language Role
(11b) creates
(2) maps to
(3) maps to
(4) maps to
(5) maps to
(6) maps to
(7) maps to
(8) maps to
(9) maps to
(10) maps to
Interface Descriptor
Name
Description
Visibility
Root
Leaf
Attribute Descriptors
Attribute Desc<1>
Attribute Desc<2>
Attribute Desc<n>
Operation Descriptors
Operation Desc<1>
Operation Desc<2>
Operation Desc<n>
Constraint Descriptors
Constraint Desc<1>
Constraint Desc<2>
Constraint Desc<n>
Hint Instances
Hint Instance<1>
Hint Instance<2>
Hint Instance<n>
Role Instances
Role Instance<1>
Role Instance<2>
Role Instance<n>
(2) read by
DD
(3) read by
EE
(4) read by
FF