FIG. 30


(1) creates
(1) read by
(1) read by
GG
Model
Name
Documentation
Model Stereotype
Visibility
Active
Abstract
Root
Leaf
Attributes
Attribute<1>
Attribute<2>
Attribute<n>
Operations
Operation<1>
Operation<2>
Operation<n>
Template Parameters
Template Param<1>
Template Param<2>
Template Param<n>
Constraints
Constraints<1>
Constraints<2>
Constraints<n>
Tagged Values
Tagged Values<1>
Tagged Values<2>
Tagged Values<n>
Code language
(1a) handled by
(1b) handled by
(1c) handled by
(1d) handled by
(1e) handled by
(1f) handled by
(1g) handled by
(1h) handled by
(1i) handled by
(1j) handled by
(1k) handled by
(1l) handled by
(1m) handled by
(1n) handled by
Model Handler
Name Handler
Documentation Handler
Stereotype Handler
Visibility Handler
Active Handler
Abstract Handler
Root Handler
Leaf Handler
Attributes Handler
Operations Handler
Template Params Handler
Constraints Handler
Tagged Values Handler
Language Handler
(11) lookup role
Metamodel Repository
(11a) lookup role
Language Role
(11b) creates
(2) maps to
(3) maps to
(4) maps to
(5) maps to
(6) maps to
(7) maps to
(8) maps to
(9) maps to
(10) maps to
(11) maps to
(12) maps to
(13) maps to
(14) maps to
Model Descriptor
Name
Description
Stereotype
Visibility
Active
Abstract
Root
Leaf
ace Descriptors
Interface Desc<1>
Interface Desc<n>
Attribute Descriptors
Attribute Desc<1>
Attribute Desc<n>
Operation Descriptors
Operation Desc<1>
Operation Desc<n>
Template Descriptors
Template Desc<1>
Template Desc<2>
Template Desc<n>
Constraint Descriptors
Constraint Desc<1>
Constraint Desc<n>
Hint Instances
Hint Instance<1>
Hint Instance<n>
Role Instances
Role Instance<1>
Role Instance<n>
(2) read by
HH
(3) read by
II
(4) read by
JJ
(5) read by
KK