



(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2004/0110562 A1**
Kajino et al. (43) **Pub. Date: Jun. 10, 2004**

(54) **TACTILE PIN HOLDING APPARATUS,
TACTILE PIN DISPLAY APPARATUS AND
BRAILLE DISPLAY MEMBER**

Publication Classification

(51) **Int. Cl.⁷** **A63F 13/00**
(52) **U.S. Cl.** **463/36**

(76) **Inventors: Jiro Kajino, Osaka (JP); Michinori Hashizume, Yawata (JP); Kaoru Shimizu, Osaka (JP); Tomohiro Asao, Osaka (JP)**

(57) **ABSTRACT**

Rotational member (310) with plural tactile pins (301) movable up-and-down for displaying characters is rotated by rotation driving means. Elastic O-rings (370) are provided in the rotational member (310) for pressing and holding the pins (301). Actuators (320) brought to contact the pins (301) are provided nearby the rotational member (310) for positioning the pins (301) at desired heights from a tactile surface. Cam (330) brought to contact with the pins (301) is provided also nearby the rotational member (310) for positioning the pins (301) at the reset position or height. Furthermore, selectively actuating means is provided for selectively actuating the actuators (320). Owing to such arrangement, a continuous tactile pin display apparatus can be reduced in size, weight and cost.

Correspondence Address:
WENDEROTH, LIND & PONACK, L.L.P.
2033 K STREET N. W.
SUITE 800
WASHINGTON, DC 20006-1021 (US)

By providing at least the pins (301) or the rotational member (310) with a photocatalyst, it becomes possible to decompose contaminants, such as bacteria, sweat, oil of the hand and food particles, deposited on the pins or their peripheral portions.

(21) **Appl. No.: 10/720,241**

(22) **Filed: Nov. 25, 2003**

(30) **Foreign Application Priority Data**

Dec. 10, 2002	(JP)	2002-357444
Jan. 29, 2003	(JP)	2003-019613
Feb. 17, 2003	(JP)	2003-037541
Feb. 27, 2003	(JP)	2003-050257
Apr. 9, 2003	(JP)	2003-105248
May 23, 2003	(JP)	2003-145704

