



US 20060055663A1

(19) **United States**

(12) **Patent Application Publication**

(10) **Pub. No.: US 2006/0055663 A1**

**Ohtsuka**

(43) **Pub. Date:**

**Mar. 16, 2006**

(54) **DISPLAYING APPARATUS AND CONTROL METHOD**

(52) **U.S. Cl. .... 345/156**

(75) **Inventor: Shuichi Ohtsuka, Kanagawa (JP)**

(57) **ABSTRACT**

Correspondence Address:  
**BIRCH STEWART KOLASCH & BIRCH  
PO BOX 747  
FALLS CHURCH, VA 22040-0747 (US)**

(73) **Assignee: Fuji Photo Film Co., Ltd., Minami-Ashigara-Shi (JP)**

The displaying apparatus **100** displays a plurality of display data sequentially by updating its display. On a surface of the frame **100a**, the displaying apparatus 100 includes a display panel **110**, a bend member **120a**, and a bend member **120b** and both the bend member **120a** and the bend member **120b** have elasticity. Each of the bend member **120a** and the bend member **120b** is provided at an edge of the surface of the frame **100a**. The user bends each of the bend member **120a** and the bend member **120b** when he wants to update the display of the display panel **110**. The displaying apparatus **100** updates the display in the display panel **110** based on the deformation volume in the bend member **120**.

(21) **Appl. No.: 10/939,391**

(22) **Filed: Sep. 14, 2004**

**Publication Classification**

(51) **Int. Cl. G09G 5/00 (2006.01)**

