



US 20070229464A1

(19) **United States**

(12) **Patent Application Publication**  
**Hotelling et al.**

(10) **Pub. No.: US 2007/0229464 A1**

(43) **Pub. Date: Oct. 4, 2007**

(54) **FORCE IMAGING INPUT DEVICE AND SYSTEM**

**Publication Classification**

(51) **Int. Cl.**  
**G06F 3/041** (2006.01)

(52) **U.S. Cl.** ..... **345/173**

(57) **ABSTRACT**

(75) Inventors: **Steven P. Hotelling**, San Jose, CA (US); **Brian Q. Huppi**, San Francisco, CA (US)

A force imaging touch pad includes first and second sets of conductive traces separated by a spring membrane. When a force is applied, the spring membrane deforms moving the two sets of traces closer together. The resulting change in mutual capacitance is used to generate an image indicative of the amount or intensity of the applied force. A combined location and force imaging touch pad includes two sets of drive traces, one set of sense traces and a spring membrane. In operation, one of the drive traces is used in combination with the set of sense traces to generate an image of where one or more objects touch the touch pad. The second set of drive traces is used in combination with the sense traces and spring membrane to generate an image of the applied force's strength or intensity.

Correspondence Address:

**WONG, CABELLO, LUTSCH, RUTHERFORD & BRUCCULERI LLP**  
**20333 SH 249**  
**SUITE 600**  
**HOUSTON, TX 77070 (US)**

(73) Assignee: **Apple Computer, Inc.**, Cupertino, CA (US)

(21) Appl. No.: **11/278,080**

(22) Filed: **Mar. 30, 2006**

