

predetermined angle. At the front center of the frontward projection portion 4 and the right side of the start lever 10, three stop buttons 11L, 11C, 11R (game result leading means operable by the player), which is operated to stop rotation of the reels 3L, 3C, 3R, respectively, are arranged. At the upper left and right sides of the cabinet 2, speakers 12L, 12R are arranged. Between the speakers 12L, 12R, a payout table panel 13 which shows winning combinations of the symbols and the number of medals paid out as awards, is provided.

[0041] With reference to FIG. 2, the panel display unit 2a, the liquid crystal display unit 2b and the fixed display unit 2c will be explained.

[0042] The panel display unit 2a comprises a bonus game information display part 16, BET lamps 17a-17c, a payout display part 18 and a credit display part 19. Here, the bonus display part 16 is constructed from 7-segment LEDs and displays the game information during the bonus game. The 1-BET lamp 17a, 2-BET lamp 17b and MAX-BET lamp 17c are turned on according to the medal number betted to conduct the game. The 1-BET lamp 17a is turned on when the betted medal number is "1". The 2-BET lamp 17b is turned on when the betted medal number is "2". And the MAX-BET lamp 17c is turned on when the betted medal number is "3". The payout display part 18 and the credit display part 19 are constructed from 7-segment LEDs respectively. The payout display part 18 displays the payout medal number when the winning is materialized. The credit display part 19 displays the medal number accumulated (credited).

[0043] The liquid crystal display unit 2b comprises the symbol display areas 21L, 21C, 21R, window frame display areas 22L, 22C, 22R and effect display area 23. The display contents displayed on the liquid crystal display 2b are variably changed according to the variable symbol display mode of the reels 3L, 3C, 3R, stop display mode of the symbols and operation of a liquid crystal display device 31 mentioned hereinafter.

[0044] The symbol display areas 21L, 21C, 21R are provided corresponding to the reels 3L, 3C, 3R, respectively, and display the symbols arranged on the outer periphery of the reels 3L, 3C, 3R and various effects thereon. Here, in a case that the reels 3L, 3C, 3R corresponding to the symbol display areas 21L, 21C, 21R are rotating or the stop buttons 11L, 11C, 11R corresponding to the symbol display areas 21L, 21C, 21R are in an operable state for stop operation of the reels 3L, 3C, 3R, each symbol display area 21L, 21C, 21R is transparently displayed so as to be able to easily recognize the symbols arranged on the outer peripheries of the reels 3L, 3C, 3R, and effect effected through still images or moving images by, for example, symbols, letters, figures, marks, characters is not conducted.

[0045] The window frame display areas 22L, 22C, 22R are formed so as to enclose each symbol display area 21L, 21C, 21R and represents the frames of the symbols arranged on the outer peripheries of the reels 3L, 3C, 3R.

[0046] The effect display area 23 is formed in an area other than the symbol display areas 21L, 21C, 21R and the window frame display areas 22L, 22C, 22R in the liquid crystal display unit 2b. This effect display area 23 displays the image (representing so-called "WIN LAMP") conclusively indicating that bonus winning is realizable, the effect

to increase interest for games and the information necessary for the player to beneficially advance the game.

[0047] The fixed display unit 2c is an area to display the images determined beforehand. Concretely, the fixed display unit 2c displays "a part of row houses" which is described on a display plate 33 mentioned hereinafter. By combining the image displayed on the fixed display unit 2c and the image displayed on the effect display area 23, one still image or moving image can be displayed. In the embodiment, one complete image of the row houses can be displayed.

[0048] Further, with reference to FIGS. 3 and 4, LED lamps 29 arranged in the reels 3L, 3C, 3R will be described. The LED lamps 29 function as illumination means for illuminate the symbols arranged on the outer peripheries of the reels 3L, 3C, 3R and one of illumination means for illuminating the areas mainly corresponding to the symbol display areas 21L, 21C, 21R within an area of a liquid crystal panel 34 (mentioned later). Thus, the LED lamps 29 function as common illumination means for commonly illuminating the above symbols and the areas. And the LED lamps 29 also function as rear illumination means for illuminating the first display means from the backside thereof.

[0049] As shown in FIG. 3, in the reels 3L, 3C, 3R, there are arranged LED receiving circuit boards 24 which are positioned behind the symbols of three symbol lines (totally nine symbols), each symbol line appearing in each of symbol display areas 21L, 21C, 21R when rotation of the reels 3L, 3C, 3R stops. Each LED receiving circuit board 24 has three LED receiving portions in each of which a plurality of LED lamps 29 are provided. Hereinafter, among nine LED receiving portions, the LED receiving portion is serially represented by Z1, Z2 and Z3 from the left portion in the horizontal upper line, the LED receiving portion is serially represented by Z4, Z5 and Z6 from the left portion in the horizontal center line and the LED receiving portion is serially represented by Z7, Z8 and Z9 from the left portion in the bottom horizontal line. The LED lamp 29 illuminates the rear side of the reel sheet by white light, the reel sheet being attached to the reel 3L, 3C, 3R along the outer periphery thereof. The reel sheet is made translucent, thus light emitted from the LED lamp 29 permeates to the front plane of the reel sheet.

[0050] As shown in FIG. 4, the reel 3L is constructed from a cylindrical frame construction in which two circular frames 25 and 26 with the same shapes are connected by a plurality of connecting members 27 while separating with a distance (corresponding to the reel width) therebetween, and transmitting members 28 for transmitting driving force of a stepping motor 53L (see FIG. 8) arranged in the center position of the frame construction to the circular frames 25 and 26. Here, the reel sheet attached to the outer periphery of the reel 3L is omitted.

[0051] The LED receiving circuit board 24 arranged within the reel 3L has three LED receiving portions Z1, Z4 and Z7, each receiving a plurality of LED lamps 29. The LED receiving circuit board 24 is arranged so that the LED receiving portions Z1, Z4, Z7 position at rear sides of the symbols (totally three symbols), respectively, the symbols being seen through the symbol display area 21L by the player. Here, though the reels 3C and 3R are not shown, both reels have the same construction and the LED receiving circuit board 24 is arranged within each reel.