

means. In this case, for example, in the turning on control of the fluorescent lamps, electric power may be provided so that the fluorescent lamps are always turned on during a period from power-on of the gaming machine till power-off thereof. Thereby, similar to the above, light emitted from the fluorescent lamps always illuminates each symbol display area even if abnormality occurs in the mentioned LED drive circuit. Thereby, the player can always see and recognize the symbols arranged on each of the reels through the each symbol display areas

**[0130]** Further, in the embodiment, though the above mentioned sub-CPU conducts display control of a plurality of the ornamental lamps arranged in the cabinet, sound output control and image display control of the liquid crystal display device, the present invention is not limited to this. Another sub-CPU separate from the above sub-CPU may conduct the above various controls. For example, in a case that another sub-CPU separate from the above sub-CPU conducts the control of a plurality of the ornamental lamps arranged in the cabinet and, for example, in a case that abnormality occurs in the display control, it is enough to exchange only the sub-CPU with abnormality occurrence or only the circuit construction including the sub-CPU with abnormality occurrence to the normal sub-CPU or circuit construction having the normal sub-CPU. Therefore, time and labor for removing the cause of the abnormality occurrence can be omitted and such construction is very preferable. And in a case that another sub-CPU other than the above sub-CPU conducts sound output control or image display control, or for example, in a case that abnormality occurs in the sound output control or the image display control, it is enough to exchange only the sub-CPU with abnormality occurrence or only circuit construction including the sub-CPU with abnormality occurrence.

**[0131]** Further, the liquid crystal display device described in the embodiment may have image enlarging means for enlarging the input images by a predetermined magnification. For example, the image enlarging means may convert the image data for 640×480 dots into the image data for 1024×768 dots and output the converted image data to the display part (above mentioned terminal part). Thereby, it can use the image data for small display area, the data quantity thereof being less in comparison with that for the factual display area. As a result, memory quantity of the ROM and image data forming time can be reduced.

**[0132]** And in the embodiment, though the symbol display area is divided corresponding to each of three reels **3L**, **3C**, **3R**, the present invention is not limited to this and the symbol display area may be formed so as not to be divided. For example, it may be conceivable that two or three of the reels **3L**, **3C**, **3R** can be seen and recognized through one symbol display area. And if the first display means and the third display means are arranged at the rear face or side of the second display means, it may be constructed that the player sees and recognizes through one symbol display area a part or whole of the first display means and a part or whole of the third display means. When the reflection means is produced, there may be a case that the reflection means can be easily produced in comparison with a case that a plurality of transparent portions are formed dividedly.

**[0133]** Further, the present invention can apply to Japanese Pachinko gaming machine, arrange ball gaming

machine, mah-jong ball gaming machine, video-slot machine, video poker machine and the other machines, in addition to the slot machine in the embodiment. And even in the game program imitatively executing operation of the above mentioned slot machine in a family gaming machine, the present invention can apply and execute the game. In this case, CD-ROM, FD (flexible disc) and the similar memory medium can be utilized for the memory medium for storing the game program.

**[0134]** Here, recently in the Japanese Pachinko gaming machine in the main current, the gaming machine, in which an electric display device such as the liquid crystal display device is arranged at the center of gaming plate, is popularized. In this electric display device, a plurality of symbols (abbreviated as “special symbols” hereinafter) represented by images are variably displayed, thereby three lines of reels in the slot machine are imitatively displayed. When variable display of the special symbols stops and a predetermined stop mode (in which the same special symbols stop such as 7-7-7 and this stop mode is generally called “big combination”), the game shifts to the special gaming state beneficial for the player. In general Japanese Pachinko gaming machine, the variable display of the special symbols is started on condition that balls shot within the gaming plate by operation of the shooting handle enter into a predetermined winning hole (so-called “variable display start hole”). After a predetermined time is elapsed the variable display of the special symbols stops.

**[0135]** In this kind of Japanese Pachinko gaming machine, it may be arranged the liquid crystal display device (the second display means) and the first display means (for example, drum-type reels) at a more rear side than the display area (display plane) of the liquid crystal display device when seeing the front side of the gaming machine. And the special symbols may be variably displayed on one or both of the first display means (for example, the liquid crystal display device) and the second display means (for example, drum-type reels).

**[0136]** The above mentioned game result display means may be constructed so as to include the first display means and the second display means provided at a more front side than the display area of the first display means when seeing the front surface of the gaming machine. And the game result display means may be constructed so as to include the first display means and the second display means provided at a more front side than the display area of the first display means when seeing the front side of the gaming machine.

**[0137]** The above mentioned rearward illumination means illuminates the second display means from the backside thereof. And the above mentioned front illumination means illuminates the second display means from the backside of thereof. And the front illumination means may illuminate the second display means from the side plane thereof.

**[0138]** The above mentioned first display means and/or the second display means may be formed in a curved shape. As for extent of the curvature, the first display means and the second display means may have substantially the same curvature. Thereby, there may be a case that design of the gaming machine is improved and the gaming machine is made attractive. Even if the first display means is curved with a small radius of curvature or with a large radius of curvature, the above same effect can be obtained.