



(19) **United States**

(12) **Patent Application Publication**  
**Johnson et al.**

(10) **Pub. No.: US 2008/0190773 A1**

(43) **Pub. Date: Aug. 14, 2008**

(54) **MICROFLUIDIC FLOW MANIPULATION DEVICE**

**Publication Classification**

(76) Inventors: **Timothy J. Johnson**, Charlestown, MA (US); **David J. Ross**, Silver Spring, MD (US); **Laurie E. Locascio**, North Potomac, MD (US)

(51) **Int. Cl.**  
**G01N 27/447** (2006.01)  
**B01F 13/00** (2006.01)  
(52) **U.S. Cl.** ..... **204/601; 137/833**

Correspondence Address:  
**COCHRAN FREUND & YOUNG LLC**  
**2026 CARIBOU DR, SUITE 201**  
**FORT COLLINS, CO 80525 (US)**

(57) **ABSTRACT**

Disclosed is an apparatus and method for the mixing of two microfluidic channels wherein several wells are oriented diagonally across the width of a mixing channel. The device effectively mixes the confluent streams with electrokinetic flow, and to a lesser degree, with pressure driven flow. The device and method may be further adapted to split a pair of confluent streams into two or more streams of equal or non-equal concentrations of reactants. Further, under electrokinetic flow, the surfaces of said wells may be specially coated so that the differing electroosmotic mobility between the surfaces of the wells and the surfaces of the channel may increase the mixing efficiency. The device and method are applicable to the steady state mixing as well as the dynamic application of mixing a plug of reagent with a confluent stream.

(21) Appl. No.: **12/106,990**

(22) Filed: **Apr. 21, 2008**

**Related U.S. Application Data**

(60) Continuation of application No. 11/131,145, filed on May 16, 2005, which is a division of application No. 10/188,664, filed on Jul. 1, 2002, now Pat. No. 6,907,895.

(60) Provisional application No. 60/323,509, filed on Sep. 19, 2001.

