

electronic device in response to the selected one or more of the classifications of the second information having one or more classifications.

[0273] An exemplary implementation of the operation 12071 may include one or more classification selection modules 374 of FIG. 12 directing selection such as selecting one or more of the classifications of the second information having one or more classifications (e.g. one or more of the sensors 614 (see FIG. 23) as exemplary implementations of the sensor 144 (see FIG. 4) may send sensing information (such as stress information, strain information, force information, optical fiber information, surface contact information, gyroscopic information, etc) regarding a conformation (see FIG. 24) of the exemplary implementation 602 of the e-paper 102 through the sensor interface 146 to the recognition unit 116 (see FIG. 5) through the recognition interface 158 whereby the recognition engine 156 (see FIG. 5) compares the sensing information with conformation information stored in the conformation memory 200 (see FIG. 8) as accessed by the recognition engine (see FIG. 5) through the recognition interface and the conformation interface 194 (see FIG. 8). Based upon the comparison, the recognition engine can send to the content unit 112 through the recognition interface 158 and the content interface 134 one or more indications of what one or more classifications of information should be provided to the display unit 124 (see FIG. 9) for display).

[0274] An exemplary implementation of the operation 12072 may include one or more selection display modules 375 directing display such as displaying on one or more portions in response to the selected one or more of the classifications of the second information having one or more classifications (e.g. the display control 202 (see FIG. 9) of the display unit 124 may direct display hardware 204 to display on the display surface 610 through the surface portion 608a (see FIG. 21) information 620 having a "private" classification (see FIG. 23) and to display on the display surface 612 through the surface portion 608c (see FIG. 21) information 622 having a "public" classification (see FIG. 23) in response to selecting based upon the comparisons of the recognition engine 156 (see FIG. 5).

[0275] FIG. 46

[0276] FIG. 46 illustrates an example implementation of the exemplary operation O12 of FIG. 34 where the operation O12 includes, for example, operation O1208, which may be executed generally by, in some instances, the display unit 114 of FIG. 9. For instance, in some implementations, the exemplary operation O12 may include the operation of O1208 that may include the operation O121081 for selecting other than one or more of the classifications of the second information having one or more classifications and the operation O12082 for displaying on one or more portions of the bendable display containing electronic device in response to the selected other than one or more of the classifications of the second information having one or more classifications.

[0277] An exemplary implementation of the operation 12081 may include one or more non-classification selection modules 376 of FIG. 12 directing selection such as selecting other than one or more of the classifications of the second information having one or more classifications (e.g. the selection 626 between TV, PDA, cell phone, notebook PC, and eBook functionality (see FIG. 24) may be obtained so that other than one or more of the classifications of the second information is selected as a consequence by having the recognition engine 156 (see FIG. 5) use sensor information from

one or more of the sensors 614 (see FIG. 24) in conjunction with predetermined configuration data stored in the conformation memory 200 (see FIG. 8) to recognize a predetermined conformation, which can then be used by the application control 166 (see FIG. 6) of the application unit 118 to select a functionality per data stored in the application memory 176) associated with one or more conformations of one or more portions of one or more regions of the electronic paper assembly or other bendable display containing electronic device (e.g. the conformation of the exemplary implementation 602 of the e-paper 102 including the region 604a and the region 604b as illustrated in FIG. 24).

[0278] An exemplary implementation of the operation 12082 may include one or more other display modules 377 of FIG. 12 directing display such as displaying on one or more portions in response to the selected other than one or more of the classifications of the second information having one or more classifications (e.g. the display control 202 (see FIG. 9) of the display unit 124 may direct display hardware 204 to display on the display surface 610 through the surface portion 608a (see FIG. 21) some information regarding the selection 626 in response to selecting based upon the comparisons of the recognition engine 156 (see FIG. 5) in which in some implementations the displayed information is unrelated to the "public" or "private" classification illustrated by FIG. 23).

[0279] Those skilled in the art will appreciate that the foregoing specific exemplary processes and/or devices and/or technologies are representative of more general processes and/or devices and/or technologies taught elsewhere herein, such as in the claims filed herewith and/or elsewhere in the present application.

[0280] A partial view of a system S100 is shown in FIG. 47 that includes a computer program S104 for executing a computer process on a computing device. An implementation of the system S100 is provided using a signal-bearing medium S102 bearing one or more instructions for obtaining information associated with one or more sequences of two or more conformations of one or more portions of one or more regions of a bendable display containing electronic device. An exemplary implementation may include obtaining information (e.g. obtaining may be performed through one or more of the sensors 614 (see FIG. 23) as exemplary implementations of the sensor 144 (see FIG. 4) regarding the angle of bend 624 and the angle of bend 624a (see FIG. 23) of the exemplary implementation 602 of the e-paper 102) associated with one or more sequences of two or more conformations (e.g. the one or more of the sensors 614 as exemplary implementations of the sensor 144 may relay the information about a sequence in which the angle of bend 624 and the angle of bend 624a occurs through the sensor interface 146 (see FIG. 4) to the recognition unit 166 (see FIG. 5) through the recognition interface 158 where the recognition engine 156 may determine that the angle of bend 624 and the angle of bend 624a is associated with one or more conformations as retrieved from the conformation memory 200 (see FIG. 8) through the conformation interface 194) of one or more portions of one or more regions (e.g. the region 604a and the region 604b (see FIGS. 22 and 23) are angularly oriented with one another along the border 606a) of the electronic paper assembly or other bendable display containing electronic device (e.g. of the implementation 602 (see FIGS. 22 and 23) of the e-paper 102).

[0281] The implementation of the system S100 is also provided using a signal-bearing medium S102 bearing one or