

4. The computer according to claim 1, wherein a first distance between said first pivot and said third pivot and a second distance between said second pivot and said fourth pivot are substantially equal, and a third distance between said first pivot and said second pivot and a fourth distance between said third pivot and said fourth pivot are substantially equal.

5. A computer comprising:

display means for displaying an image to a user;

control means for controlling the image displayed by said display means;

accommodation means for accommodating said control means;

connection means connecting said accommodation means and said display means to each other and capable of freely setting the distance between said display means and a viewing point of the user within a predetermined range; and

load means for imposing a load such that a force necessary for moving said display means away from said viewing point is larger than a force necessary for bringing said display means closer to said viewing point when said distance is adjusted.

6. The computer according to claim 5, wherein said connection maintains the angle of said display means with respect to said viewing point even when said distance is changed.

7. The computer according to claim 5, wherein said connection means is accommodated in a recessed portion provided in a surface of said accommodation means.

8. A monitor unit connected to a computer, said monitor unit comprising:

a monitor having a display screen,

an arm extending from said monitor,

a fixing portion on which said monitor and said arm are supported,

a first hinge portion which rotatably connects said fixing portion and said arm to each other,

a second hinge portion which rotatably connects said monitor and said arm to each other, and

a resilient component for applying a rotating force in such a direction that said arm is moved away from said fixing portion.

9. The monitor unit according to claim 8, wherein said arm has a front plate which extends from a front portion of said first hinge portion to a front portion of said second hinge portion, and a rear plate which extends from a rear portion of said first hinge portion to a rear portion of said second hinge portion.

10. The monitor unit according to claim 9, wherein said front plate and said rear plate are connected to the front portion of said first hinge portion and the rear portion of said first hinge portion with a predetermined spacing set therebetween.

11. A support structure for supporting a front face unit facing a user, wherein said support structure is capable of holding said front face unit at a predetermined angle, said support structure comprising:

an arm configurably connected to said front face unit to be rotatable on an axis in a lateral direction perpendicular to a longitudinal direction from a front portion to a rear portion of said front face unit,

a base unit configurably connected to said arm to be rotatable along the lateral axis by a predetermined external force in order to support said front face unit, and

a signal processing portion for performing transmitting and receiving of signals between said front face unit and a computer connectable to said front face unit,

wherein said arm further comprises:

a first supporting member which extends from the front portion of said front face unit and is connected to said base unit,

a second supporting member which extends from the rear portion of said front face unit, is connected to said base unit, and is linked to said first supporting member, and

a resilient component which applies a rotating force in such a direction that said second supporting member is moved away from said base unit.

12. The support structure according to claim 11, wherein said first supporting member is connected to a front portion of said base unit, and said second supporting member is connected to a rear portion of said base unit.

13. The support structure according to claim 11, wherein an arrangement approximating a parallelogram is formed by a first connecting portion in said base unit to which said first supporting member is connected, a second connecting portion in said front face unit to which said first supporting member is connected, a third connecting portion in said base unit to which said second supporting member is connected, and a fourth connecting portion in said front face unit to which said second supporting member is connected.

15. The support structure according to claim 11, wherein said support structure being mounted on a portable computer.

* * * * *