

8. The device as claimed in one of claims 1 to 7, characterized in that the support sheet (1) is clamped as a continuous band in a circulating manner between two deflecting rollers (7) that are spaced apart from one another.

9. The device as claimed in one of claims 1 to 7, characterized in that a multiplicity of support sheets (7) are clamped as continuous bands in a circulating manner respectively between two deflecting rollers (7) that are spaced apart from one another, the axes of the deflecting rollers (7) being in line with one another and the continuous bands extending parallel to one another.

10. The device as claimed in one of claims 1 to 9, characterized in that the at least one actuator is formed for the mechanical, magnetic, piezoelectric or thermal activation of the touch points (2).

11. The device as claimed in one of claims 1 to 4, characterized in that the support band (1) is formed as a disk-shaped turntable (8).

12. The device as claimed in one of the preceding claims 1 to 11, characterized by a sensor for sensing the reading speed and a regulating unit for regulating the speed of the representation of continuous information.

13. The device as claimed in claim 12, characterized in that the sensor is a pressure sensor.

14. The device as claimed in one of the preceding claims 1 to 13, characterized by a voice output unit for the acoustic output of the information.

15. The device as claimed in one of claims 1 to 14, characterized by an interface for the transmission of the information from a terminal unit to the device.

16. The device as claimed in claim 15, characterized in that the interface is formed for radio transmission or infrared transmission.

17. The device as claimed in one of the preceding claims, characterized in that the touch points (2) have an unsymmetrical force distribution, so that it is more difficult for the touch points (2) to be pressed from the activated state into the deactivated state than vice versa.

18. A support sheet (1) for the punctiform representation of graphical information which can be read by touch, in particular for the representation of Braille script, with a multiplicity of systematically arranged touch points (2), the touch points (2) being formed integrally with the support sheet (1), characterized in that

the touch points (2) have a touch region (3), which, in the activated state of the touch points (2), protrudes beyond the plane formed by the touch surface of the support sheet (2), and a flexible boundary region (4) between the support sheet (1) and the touch region (3), the

boundary region (4) having a lower thickness and/or rigidity than the support sheet (1) and the touch region (3),

the touch regions (3) are able to spring back and [sic] or below the plane which is formed by the touch surface of the support sheet (1), by means of the associated boundary regions (4), in order to bring the touch points (2) into a deactivated state, and

the touch regions (3) have an actuating portion, protruding beyond the underside of the support sheet (1) that lies opposite from the touch surface of the support sheet (1).

19. The support sheet (1) as claimed in claim 18, characterized in that the support sheet (1) is formed with a plastic.

20. The support sheet (1) as claimed in claim 19, characterized in that the plastic is polyurethane.

21. The support sheet (1) as claimed in one of claims 18 to 20, characterized in that the support sheet (1) has a flexible, fiber-reinforced layer.

22. The support sheet (1) as claimed in one of claims 18 to 21, characterized in that the support sheet (1) is a continuous band.

23. The support sheet (1) as claimed in claim 22, characterized by tooth flanks (6) or tapers on the support sheet for engagement in deflecting rollers (7).

24. The support sheet (1) as claimed in claim 23, characterized in that the touch points (2) are respectively arranged in the regions between the tooth flanks (6) or tapers.

25. The support sheet (1) as claimed in one of claims 18 to 21, characterized in that the support sheet (1) is formed as a disk-shaped turntable (8).

26. The support sheet (1) as claimed in one of claims 18 to 25, characterized in that the touch points (2) are thermally activatable.

27. The support sheet (1) as claimed in one of claims 18 to 26, characterized in that the touch points (2) have an unsymmetrical force distribution, so that it is more difficult for the touch points (2) to be pressed from the activated state into the deactivated state than vice versa.

28. A method for producing a support sheet (1) as claimed in one of claims 18 to 27, characterized by heating the boundary region (4) for transforming the material of the support sheet (1) in the boundary region (4) into a flexible state.

\* \* \* \* \*