

of distractors present solely in the depth plane of the target was also investigated. The results showed a number of interesting features including the significant modification of the response time resulting from the target presence or absence. In the target absence trials, the reaction times of all the subjects displayed a direct correspondence to the number of distractors whilst the target present trials did not display any such dependency. Furthermore, it was found that the reaction times in instances where distractors were spread across multiple depths were faster than for distractors located in a single depth plane.

[0029] Consequently, the use of a plurality of depth/focal planes as a means of displaying information can enhance preattentive processing with enhanced reaction/assimilation times.

[0030] It is thus believed that a means of overcoming the above described drawbacks is available by harnessing the peripheral vision and subconscious perception of the reader (particularly in conjunction with multi focal plane displays) to assimilate additional information sources simultaneously with the process of conventional reading in order to enhance the speed and effectiveness of the whole reading/viewing process.

[0031] The benefits of the multi-layered viewing screens, in particular those utilising the technology described in the co-pending Patent Application Nos. NZ314566, NZ328074, NZ329130, PCT/NZ98/00098 and PCT/NZ99/00021 are especially germane to displays using liquid crystal displays (LCD).

[0032] There are two main types of Liquid Crystal Displays used in computer monitors, passive matrix and active matrix. Passive-matrix Liquid Crystal Displays use a simple grid to supply the charge to a particular pixel on the display. Creating the grid starts with two glass layers called substrates. One substrate is given columns and the other is given rows made from a transparent conductive material. This is usually indium tin oxide. The rows or columns are connected to integrated circuits that control when a charge is sent down a particular column or row. The liquid crystal material is sandwiched between the two glass substrates, and a polarizing film is added to the outer side of each substrate.

[0033] A pixel is defined as the smallest resolvable area of an image, either on a screen or stored in memory. Each pixel in a monochrome image has its own brightness, from 0 for black to the maximum value (e.g. 255 for an eight-bit pixel) for white. In a colour image, each pixel has its own brightness and colour, usually represented as a triple of red, green and blue intensities. To turn on a pixel, the integrated circuit sends a charge down the correct column of one substrate and a ground activated on the correct row of the other. The row and column intersect at the designated pixel and that delivers the voltage to untwist the liquid crystals at that pixel.

[0034] The passive matrix system has significant drawbacks, notably slow response time and imprecise voltage control. Response time refers to the Liquid Crystal Displays ability to refresh the image displayed. Imprecise voltage control hinders the passive matrix's ability to influence only one pixel at a time. When voltage is applied to untwist one pixel, the pixels around it also partially untwist, which makes images appear fuzzy and lacking in contrast.

[0035] Active-matrix Liquid Crystal Displays depend on thin film transistors (TFT). Thin film transistors are tiny

switching transistors and capacitors. They are arranged in a matrix on a glass substrate. To address a particular pixel, the proper row is switched on, and then a charge is sent down the correct column. Since all of the other rows that the column intersects are turned off, only the capacitor at the designated pixel receives a charge. The capacitor is able to hold the charge until the next refresh cycle. And if the amount of voltage supplied to the crystal is carefully controlled, it can be made to untwist only enough to allow some light through. By doing this in very exact, very small increments, Liquid Crystal Displays can create a grey scale. Most displays today offer 256 levels of brightness per pixel.

[0036] A Liquid Crystal Display that can show colours must have three subpixels with red, green and blue colour filters to create each colour pixel. Through the careful control and variation of the voltage applied, the intensity of each subpixel can range over 256 shades. Combining the subpixel produces a possible palette of 16.8 million colours (256 shades of red×256 shades of green×256 shades of blue).

[0037] Liquid Crystal Displays employ several variations of liquid crystal technology, including super twisted nematics, dual scan twisted nematics, ferroelectric liquid crystal and surface stabilized ferroelectric liquid crystal. They can be lit using ambient light in which case they are termed as reflective, backlit and termed Transmissive, or a combination of backlit and reflective and called transfective. There are also emissive technologies such as Organic Light Emitting Diodes, and technologies which project an image directly onto the back of the retina which are addressed in the same manner as Liquid Crystal Displays. These devices are described hereafter as LCD panels

[0038] All references, including any patents or patent applications cited in this specification are hereby incorporated by reference. No admission is made that any reference constitutes prior art. The discussion of the references states what their authors assert, and the applicants reserve the right to challenge the accuracy and pertinency of the cited documents. It will be clearly understood that, although a number of prior art publications are referred to herein, this reference does not constitute an admission that any of these documents form part of the common general knowledge in the art, in New Zealand or in any other country.

[0039] It is acknowledged that the term 'comprise' may, under varying jurisdictions, be attributed with either an exclusive or an inclusive meaning. For the purpose of this specification, and unless otherwise noted, the term 'comprise' shall have an inclusive meaning—i.e. that it will be taken to mean an inclusion of not only the listed components it directly references, but also other non-specified components or elements. This rationale will also be used when the term 'comprised' or 'comprising' is used in relation to one or more steps in a method or process.

[0040] It is an object of the present invention to address the foregoing problems or at least to provide the public with a useful choice.

[0041] Further aspects and advantages of the present invention will become apparent from the ensuing description which is given by way of example only.