```
<!ELEMENT rdb-db-pool (#PCDATA)>

<!--
The elements session and entity group the deployment parameters of
session and entity EJBs within an EJB-JAR module.
-->
<!ELEMENT session (ejb-name, display-name?, description?, env-entry*,
    resource-ref*)>
<!ELEMENT entity (ejb-name, display-name?, description?, env-entry*,
    resource-ref*, storage?)>

<!--
The ejb-name element specifies an enterprise bean's name.
-->
<!ELEMENT ejb-name (#PCDATA)>

<!--
See the DTDs of the standard J2EE deployment descriptors for more
information on the elements resource-ref, env-entry, context-param and
their subelements.
-->
<!ELEMENT resource-ref (description?, res-ref-name, res-type, res-
auth)>
<!ELEMENT res-ref-name (#PCDATA)>
<!ELEMENT res-type (#PCDATA)>
<!--
The possible values of the res-auth element are not unique among the
standard J2EE deployment descriptors. In an SDA deployment descriptor,
this element may have exactly one of the values application and
container.
-->
<!ELEMENT res-auth (#PCDATA)>
<!ELEMENT env-entry (description?, env-entry-name, env-entry-type,
    env-entry-value?)>
<!ELEMENT env-entry-name (#PCDATA)>
<!ELEMENT env-entry-type (#PCDATA)>
<!ELEMENT env-entry-value (#PCDATA)>
<!ELEMENT context-param (param-name, param-value, description?)>
```