

[0053] The aspects of the disclosed embodiments are also directed to providing a user interface comprising flexible display means and control means for detecting a bend of a corner of said display and executing a function associated with said corner. The user interface shares the advantages as discussed above.

[0054] The aspects of the disclosed embodiments are also directed to providing a device incorporating or configured to incorporate a user interface according to above.

[0055] The device shares the advantages as discussed above.

[0056] The aspects of the disclosed embodiments are also directed to providing a method for executing a function in a device comprising a flexible display, said method comprising detecting a bend, determine a resulting foldline and determine a graphical object intersected by said foldline and execute a function associated with said graphical object.

[0057] The method and the embodiments below share the advantages as discussed above.

[0058] In one embodiment the graphical object is displayed on the display.

[0059] In one embodiment the method further comprises detecting a release event and executing said function upon said release event.

[0060] In one embodiment the method further comprises determining said function based on a criterion related to a characteristic of said bend.

[0061] In one embodiment the method further comprises detecting a second bend, determining a resulting second foldline, determine a second graphical object being intersected by said second foldline and wherein said function is associated with or executed on said second graphical object.

[0062] In one embodiment the method further comprises determining a second graphical object being intersected by said first foldline and wherein said function is associated with or executed on said second graphical object.

[0063] In one embodiment the method further comprises detecting a variation in said first bend and determining a resulting second foldline and determining a second graphical object being intersected by said second foldline and wherein said function is associated with or executed on said second graphical object.

[0064] In one embodiment the method further comprises detecting a third graphical object being intersected by said first foldline and wherein said function is associated with or executed on said third graphical object.

[0065] In one embodiment the display is a touchdisplay and the method comprises detecting a touch input identifying a graphical object on said display wherein said function is associated with or executed on said second graphical object.

[0066] In one embodiment the method further comprises displaying a graphical indication of a foldline.

[0067] In one embodiment the method further comprises detecting a double bend.

[0068] In one embodiment the method further comprises detecting a release event and executing said function upon detection of said release event.

[0069] In one embodiment the method further comprises determining that a graphical object is intersected if a foldline intersects an area surrounding said graphical object.

[0070] The aspects of the disclosed embodiments are also directed to providing a method for executing a function in a device comprising a flexible display, said method comprising

detecting a bend of a corner of said display and executing a function associated with said corner.

[0071] The method shares the advantages as discussed above.

[0072] The aspects of the disclosed embodiments are also directed to providing a device implementing or configured to implement a method according to above.

[0073] The device shares the advantages as discussed above.

[0074] The aspects of the disclosed embodiments are also directed to providing a method for executing a function in a device comprising a flexible device, said method comprising detecting a bend, determining a resulting shape, determining a function associated with said shape and executing said function.

[0075] The method and the embodiments below share the advantages as discussed above.

[0076] In one embodiment the function is to search for an institution.

[0077] In one embodiment the function is to establish a connection with a device.

[0078] In one embodiment the method further comprises detecting a movement wherein said function is associated with said movement.

[0079] In one embodiment the method further comprises detecting a release event and thereupon arrest said execution of said function.

[0080] The aspects of the disclosed embodiments are also directed to providing a device implementing or configured to implement a method according to above.

[0081] The device shares the advantages as discussed above.

[0082] The aspects of the disclosed embodiments are also directed to providing a computer readable medium including at least computer program code for controlling a user interface comprising a flexible display, said computer readable medium comprising software code configured to detect a first bend and determine a resulting first foldline, software code configured to determine a graphical object being intersected by said first foldline and software code configured to execute a function associated with said graphical object.

[0083] The computer readable medium and the embodiments below share the advantages as discussed above.

[0084] In one embodiment the computer readable medium further comprises software code configured to display the graphical object.

[0085] In one embodiment the computer readable medium further comprises software code configured to detect a second bend and determine a resulting second foldline, determine a second graphical object being intersected by said second foldline and wherein said function is associated with or performed on said second graphical object.

[0086] In one embodiment the computer readable medium further comprises software code configured to determine a second graphical object being intersected by said first foldline and wherein said function is associated with or executed on said second graphical object.

[0087] In one embodiment the computer readable medium further comprises software code configured to detect a variation in said first bend and determine a resulting second foldline and determine a second graphical object being intersected by said second foldline and wherein said function is associated with or executed on said second graphical object.