

300 includes an input portion and an output display portion. The output display portion can be a display screen **322**, such as an LCD or other similar display devices.

[0050] An exemplary handheld electronic device **300** and its cooperation in a wireless network **319** is exemplified in the block diagram of FIG. **9**. This figure is exemplary only, and those persons skilled in the art will appreciate the additional elements and modifications necessary to make the device **300** work in particular network environments.

[0051] The block diagram of FIG. **9** representing the handheld device **300** interacting in the communication network **319** shows the device's **300** inclusion of a microprocessor **338** which controls the operation of the device **300**. The communication subsystem **311** performs all communication transmission and reception with the wireless network **319**. The microprocessor **338** further connects with an auxiliary input/output (I/O) subsystem **328**, a serial port (preferably a Universal Serial Bus port) **330**, a display screen **322**, a keyboard **332**, a speaker **334**, a microphone **336**, random access memory (RAM) **326**, and flash memory **324**. Other communication subsystems **340** and other device subsystems **342** are generally indicated as connected to the microprocessor **338** as well. An example of a communication subsystem **340** is that of a short range communication subsystem such as BLUE-TOOTH® communication module or an infrared device and associated circuits and components. Additionally, the microprocessor **338** is able to perform operating system functions and preferably enables execution of software applications on the handheld device **300**.

[0052] The above-described auxiliary I/O subsystem **328** can take a variety of different subsystems including the above described navigation tool. Other auxiliary I/O devices can include external display devices and externally connected keyboards (not shown). While the above examples have been provided in relation to the auxiliary I/O subsystem, other subsystems capable of providing input or receiving output from the handheld electronic device **300** are considered within the scope of this disclosure. Additionally, other keys may be placed along the side of the device **300** to function as escape keys, volume control keys, scrolling keys, power switches, or user programmable keys, which may be programmed accordingly.

[0053] In an exemplary embodiment, the flash memory **324** is enabled to provide a storage location for the operating system, device programs, and data. While the operating system in a preferred embodiment is stored in flash memory **324**, the operating system in other embodiments is stored in read-only memory (ROM) or similar storage element (not shown). As those skilled in the art will appreciate, the operating system, device application or parts thereof may be loaded in RAM **326** or other volatile memory.

[0054] In a preferred embodiment, the flash memory **324** contains programs/applications **358** for execution on the device **300** including an address book **352**, a personal information manager (PIM) **354**, and the device state **350**. Furthermore, programs **358** and other information **356** including data can be segregated upon storage in the flash memory **324** of the device **300**.

[0055] When the device **300** is enabled for two-way communication within the wireless communication network **319**, it can send and receive signals from a mobile communication service. Examples of communication systems enabled for two-way communication include, but are not limited to, the General Packet Radio Service (GPRS) network, the Universal

Mobile Telecommunication Service (UMTS) network, the Enhanced Data for Global Evolution (EDGE) network, and the Code Division Multiple Access (CDMA) network and those networks generally described as packet-switched, narrowband, data-only technologies mainly used for short burst wireless data transfer. For the systems listed above, the handheld device **300** must be properly enabled to transmit and receive signals from the communication network **319**. Other systems may not require such identifying information. GPRS, UMTS, and EDGE require the use of a Subscriber Identity Module (SIM) in order to allow communication with the communication network **319**. Likewise, most CDMA systems require the use of a Removable Identity Module (RUIM) in order to communicate with the CDMA network. The RUIM and SIM card can be used in multiple different handheld electronic devices **300**. The handheld device **300** may be able to operate some features without a SIM/RUIM card, but it will not be able to communicate with the network **319**. A SIM/RUIM interface **344** located within the device **300** allows for removal or insertion of a SIM/RUIM card (not shown). The SIM/RUIM card features memory and holds key configurations **351**, and other information **353** such as identification and subscriber related information. With a properly enabled handheld device **300**, two-way communication between the handheld device **300** and communication network **319** is possible.

[0056] If the handheld device **300** is enabled as described above or the communication network **319** does not require such enablement, the two-way communication enabled device **300** is able to both transmit and receive information from the communication network **319**. The transfer of communication can be from the device **300** or to the device **300**. In order to communicate with the communication network **319**, the device **300** in a preferred embodiment is equipped with an integral or internal antenna **318** for transmitting signals to the communication network **319**. Likewise the handheld device **300** in the preferred embodiment is equipped with another antenna **316** for receiving communication from the communication network **319**. These antennae (**316**, **318**) in another preferred embodiment are combined into a single antenna (not shown). As one skilled in the art would appreciate, the antenna or antennae (**316**, **318**) in another embodiment are externally mounted on the device **300**.

[0057] When equipped for two-way communication, the handheld device **300** features a communication subsystem **311**. As is well known in the art, this communication subsystem **311** is modified so that it can support the operational needs of the device **300**. The subsystem **311** includes a transmitter **314** and receiver **312** including the associated antenna or antennae (**316**, **318**) as described above, local oscillators (LOs) **313**, and a processing module **320** which in a preferred embodiment is a digital signal processor (DSP) **320**.

[0058] It is contemplated that communication by the device **300** with the wireless network **319** can be any type of communication that both the wireless network **319** and device **300** are enabled to transmit, receive and process. In general, these can be classified as voice and data. Voice communication is communication in which signals for audible sounds are transmitted by the device **300** through the communication network **319**. Data is all other types of communication that the device **300** is capable of performing within the constraints of the wireless network **319**.

[0059] Exemplary embodiments have been described hereinabove regarding both handheld electronic devices **300**, as