

[0024] FIG. 4 is a perspective view showing that the flexible display unit is entirely drawn and thus a display region is open.

[0025] FIG. 5 is a perspective view showing a process of opening a folder-type portable communication device according to an exemplary embodiment of the present invention.

[0026] FIG. 6 is a front view of FIG. 4.

[0027] FIG. 7 is a bottom view of FIG. 4.

[0028] FIG. 8 is a side view of FIG. 1.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

[0029] The invention is described more fully hereinafter with reference to the accompanying drawings, in which embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure is thorough, and will fully convey the scope of the invention to those skilled in the art. Like reference numerals in the drawings denote like elements.

[0030] As shown in FIG. 1, FIG. 2, FIG. 3, and FIG. 4, a portable communication device according to an exemplary embodiment of the present invention includes a main body housing 100, a folding housing 200 rotatably coupled to the main body housing 100 by a hinge unit 300 to rotate around a first hinge axis A1 and a second hinge axis A2, and a flexible display unit 400 that is drawn out from the main body housing 100 to open its display screen. The longitudinal direction of the main body housing 100 and the longitudinal direction of the folding housing 200 may be parallel to the first hinge axis A1 and the second hinge axis A2. The flexible display unit 400 may be implemented as a flexible Liquid Crystal Display (LCD) device, may be mounted in a rolled-up state, and may be opened by unrolling from the rolled-up state. The hinge unit 300 may be a dual-axis hinge and may provide the first hinge axis A1 and the second hinge axis A2. The first hinge axis A1 and the second hinge axis A2 may be parallel to each other.

[0031] The main body housing 100 includes a protrusion unit 110 extending along a side end. The protrusion unit 110 protrudes a predetermined height from the top face of the main body housing 100 in order to accommodate the rolled-up flexible display unit 400. The mounted state of the flexible display unit 400 is shown in FIG. 8.

[0032] As shown in FIG. 8, the flexible display unit 400 may be mounted in the main body housing 100, more specifically, the flexible display unit 400 may be rolled-up in the protrusion unit 110 and may be drawn out from the protrusion unit 110 when the folding housing 200 rotates. An end portion of the flexible display unit 400 may be fixed to the folding housing 200. In other words, the end of the flexible display unit 400 may be fixed to the end portion that moves the most when the folding housing 200 is rotated. When the folding housing 200 is closed, the rolled-up flexible display unit 400 may be automatically rewound into the protrusion unit 110 by a force of an elastic body 410 installed in a rotation axis of the flexible display unit 400.

[0033] FIG. 5 is a perspective view showing a process of drawing out the flexible display unit 400 according to the opening/closing operations of the folding housing 200. As shown in FIG. 5, the amount by which the flexible display unit 400 is drawn out may be proportional to the amount by which

the folding housing 200 is rotated. In other words, the flexible display unit 400 is not drawn out when the folding housing 200 is folded on the main body housing 100, and the flexible display unit 400 is completely drawn out when the folding housing 200 is fully rotated from the main body housing 100. The flexible display unit 400 is completely drawn out in FIG. 4, in which a wide display unit may be provided. As the amount by which the folding housing 200 rotates gradually increases, the amount by which the flexible display unit 400 is drawn out also gradually increases.

[0034] As shown in FIG. 1, a plurality of first keys 120 may be arranged on the top face of the protrusion unit 110 in a longitudinal direction. The first keys 120 are always exposed. A fixed display unit 210 and a plurality of second keys 220 that are adjacent to the fixed display unit 210 may be arranged on an external face 201 of the folding housing 200. The second keys 220 may be implemented as touch keys. An optical joystick sensor 222 may be disposed in the second keys 220.

[0035] As shown in FIG. 6, third keys 122 may be disposed in both side ends of the main body housing 100. As shown in FIG. 7, a camera lens 130 may be disposed on the bottom face of the main body housing 100.

[0036] As shown in FIG. 2 and FIG. 3, when the folding housing 200 rotates about 90°, the display screen of the flexible display unit 400 is held in an inclined state. As shown in FIG. 4, when the folding housing 200 rotates about 180°, the display screen of the flexible display unit 400 is opened to the maximum and thus faces the main body housing 100 and the folding housing 200. FIG. 1 shows a state used in a phone mode and FIG. 2, FIG. 3, and FIG. 4 show states that may be convenient for moving picture viewing.

[0037] As described above, according to exemplary embodiments of the present invention, a wide display screen may be provided in a small mounting space through a flexible display unit, and a structure in which a main body housing supports the flexible display unit may provide visual stability to users. Therefore, exemplary embodiments of the present invention may improve the visual interfacing environment in the future multimedia age and may provide various applications including e-book or navigation functions.

[0038] It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the spirit or scope of the invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A portable communication device, comprising:
 - a main housing;
 - a folding housing coupled to the main housing by a hinge unit to rotate about a hinge axis; and
 - a flexible display unit that is drawn out from the main housing to open its display screen when the folding housing unfolds.
2. The portable communication device of claim 1, wherein a longitudinal direction of the main housing is parallel to the hinge axis.
3. The portable communication device of claim 1, wherein the flexible display unit is stored in the main housing in a rolled-up state and unrolls when the folding housing unfolds, and an end of the flexible display unit is coupled to the folding housing.
4. A portable communication device, comprising:
 - a main housing;