

escape keys, volume control keys, scrolling keys, power switches, or user programmable keys, which may be programmed accordingly.

[0096] In an exemplary embodiment, the flash memory 324 is enabled to provide a storage location for the operating system, device programs, and data. While the operating system in a preferred embodiment is stored in flash memory 324, the operating system in other embodiments is stored in read-only memory (ROM) or similar storage element (not shown). As those skilled in the art will appreciate, the operating system, device application or parts thereof may be loaded in RAM 326 or other volatile memory.

[0097] In a preferred embodiment, the flash memory 324 contains programs/applications 358 for execution on the device 300 including an address book 352, a personal information manager (PIM) 354, and the device state 350. Furthermore, programs 358 and other information 356 including data can be segregated upon storage in the flash memory 324 of the device 300.

[0098] When the device 300 is enabled for two-way communication within the wireless communication network 319, it can send and receive signals from a mobile communication service. Examples of communication systems enabled for two-way communication include, but are not limited to, the General Packet Radio Service (GPRS) network, the Universal Mobile Telecommunication Service (UMTS) network, the Enhanced Data for Global Evolution (EDGE) network, and the Code Division Multiple Access (CDMA) network and those networks, generally described as packet-switched, narrowband, data-only technologies which are mainly used for short burst wireless data transfer. For the systems listed above, the communication device 300 must be properly enabled to transmit and receive signals from the communication network 319. Other systems may not require such identifying information. GPRS, UMTS, and EDGE require the use of a Subscriber Identity Module (SIM) in order to allow communication with the communication network 319. Likewise, most CDMA systems require the use of a Removable Identity Module (RUIM) in order to communicate with the CDMA network. The RUIM and SIM card can be used in multiple different communication devices 300. The communication device 300 may be able to operate some features without a SIM/RUIM card, but it will not be able to communicate with the network 319. A SIM/RUIM interface 344 located within the device 300 allows for removal or insertion of a SIM/RUIM card (not shown). The SIM/RUIM card features memory and holds key configurations 351, and other information 353 such as identification and subscriber related information. With a properly enabled communication device 300, two-way communication between the communication device 300 and communication network 319 is possible.

[0099] If the communication device 300 is enabled as described above or the communication network 319 does not require such enablement, the two-way communication enabled device 300 is able to both transmit and receive information from the communication network 319. The transfer of communication can be from the device 300 or to the device 300. In order to communicate with the communication network 319, the device 300 in the presently described embodiment is equipped with an integral or internal antenna 318 for transmitting signals to the communication network 319. Likewise the communication device 300 in the preferred embodiment is equipped with another antenna 316 for receiving communication from the communication network 319.

These antennae (316, 318) in another preferred embodiment are combined into a single antenna (not shown). As one skilled in the art would appreciate, the antenna or antennae (316, 318) in another embodiment are externally mounted on the device 300.

[0100] When equipped for two-way communication, the communication device 300 features a communication subsystem 311. As is well known in the art, this communication subsystem 311 is modified so that it can support the operational needs of the device 300. The subsystem 311 includes a transmitter 314 and receiver 312 including the associated antenna or antennae (316, 318) as described above, local oscillators (LOs) 313, and a processing module 320 which in a preferred embodiment is a digital signal processor (DSP) 320.

[0101] It is contemplated that communication by the device 300 with the wireless network 319 can be any type of communication that both the wireless network 319 and device 300 are enabled to transmit, receive and process. In general, these can be classified as voice and data. Voice communication is communication in which signals for audible sounds are transmitted by the device 300 through the communication network 319. Data is all other types of communication that the device 300 is capable of performing within the constraints of the wireless network 319.

[0102] Exemplary embodiments have been described hereinabove regarding both handheld electronic devices 300, as well as the communication networks within which they cooperate. It should be appreciated, however, that a focus of the present disclosure is the enablement of an adaptive display screen that is capable of changing the shape of an exposed upper surface in dependence upon a presented key arrangement.

What is claimed is:

1. An adaptive display screen with a shape-changing upper surface and which is configured for incorporation on a multi-mode, microprocessor-controlled wireless handheld communication device having capabilities for at least voice and email modes of communication, said adaptive display screen comprising:

a visual display that variously presents visibly different key arrangements to an operator of the device in dependence upon the mode of operation of the incorporating device; and

a shape changing, exposed upper surface presented to the operator for selective digital press-engagement, said exposed upper surface changing shape in dependence upon the presented key arrangement.

2. The adaptive display screen of claim 1, further comprising a display presented key arrangement taking the form of one of the following: a navigational key arrangement, a text entry key arrangement, a symbol entry key arrangement, and a numeric entry key arrangement.

3. The adaptive display screen of claim 1, wherein the variously presentable visibly different key arrangements comprise: a navigational key arrangement, a text entry key arrangement, a symbol entry key arrangement, and a numeric entry key arrangement.

4. The adaptive display screen of claim 1, wherein each visibly different key arrangement presents a plurality of discrete keys that each visibly define a two-dimensional signified key zone that establishes a target area for press-engagement and said shape changing, exposed upper surface