US 20200133478A1

(19) United States

(12) Patent Application Publication

Chaudhri et al.

(10) Pub. No.: US 2020/0133478 A1

(43) Pub. Date: Apr. 30, 2020

(54) **DEVICES, METHODS, AND GRAPHICAL USER INTERFACES FOR MESSAGING**

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

(72) Inventors: **Imran A. Chaudhri**, San Francisco, CA (US); **Freddy A. Anzures**, San Francisco, CA (US); **Chanaka G. Karunamuni**, San Jose, CA (US); **Nicholas V. King**, San Jose, CA (US); **Hoan Pham**, San Jose, CA (US); **Wan Si Wan**, Sunnyvale, CA (US); **Darin B. Adler**, Los Gatos, CA (US); **Bethany Bongiorno**, San Francisco, CA (US); **Justin N. Wood**, Los Altos, CA (US); **Roberto Garcia**, Santa Clara, CA (US); **Soin Shedlosky**, San Jose, CA (US); **Richard R. Dellinger**, San Jose, CA (US); **Daamun Mohseni**, San Jose, CA (US); **Giancarlo Yerkes**, Menlo Park, CA (US)

(21) Appl. No.: **16/732,184**

(22) Filed: **Dec. 31, 2019**

Related U.S. Application Data

(63) Continuation of application No. 16/544,787, filed on Aug. 19, 2019, which is a continuation of application No. 16/194,237, filed on Nov. 16, 2018, which is a continuation of application No. PCT/US2017/033396, filed on May 18, 2017.

(60) Provisional application No. 62/506,614, filed on May 16, 2017, provisional application No. 62/349,114, filed on Jun. 12, 2016, provisional application No. 62/349,116, filed on Jun. 12, 2016, provisional application No. 62/339,078, filed on May 19, 2016, provisional application No. 62/338,502, filed on May 18, 2016.

(30) **Foreign Application Priority Data**

Aug. 24, 2016 (DK) 201670636
Aug. 26, 2016 (DK) 201670655

Publication Classification

(51) **Int. Cl.**

G06F 3/0488	(2006.01)
G06F 3/0482	(2006.01)
G06Q 10/10	(2006.01)
H04N 5/232	(2006.01)
G06T 11/60	(2006.01)
H04L 12/58	(2006.01)
G06F 3/041	(2006.01)
G06F 3/0484	(2006.01)
G06F 3/0485	(2006.01)
G06F 3/0481	(2006.01)
G06T 13/00	(2006.01)
G06F 40/197	(2006.01)
H04M 1/725	(2006.01)

(52) **U.S. Cl.**

CPC ***G06F 3/04883*** (2013.01); *G06Q 10/02* (2013.01); ***G06Q 10/107*** (2013.01); ***H04N 5/23216*** (2013.01); ***G06T 11/60*** (2013.01); ***H04L 51/22*** (2013.01); ***H04L 51/046*** (2013.01); ***G06F 3/0412*** (2013.01); ***G06F 3/04847*** (2013.01); ***G06F 3/04886*** (2013.01); ***H04L 51/16*** (2013.01); ***G06F 3/0485*** (2013.01); ***G06F 3/04817*** (2013.01); ***G06F 3/04845*** (2013.01); ***G06F 3/0481*** (2013.01); ***G06T 13/00*** (2013.01); ***H04L 51/18*** (2013.01); ***G06F 40/197*** (2020.01); ***G06F 3/04842*** (2013.01); ***H04M 1/72547*** (2013.01); ***H04N 5/23293*** (2013.01); ***H04L 51/04*** (2013.01); ***G06F 3/0482*** (2013.01)

(57) **ABSTRACT**

An electronic device displays a messaging user interface of a message application, including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a message-input area, at least one avatar corresponding to a first other user included in the messaging session, and an application affordance. The device detects an input on the touch sensitive surface. In accordance with a determination that the input corresponds to selection of the at least one avatar displayed in the messaging user interface, the device displays a menu that contains a plurality of activatable menu items associated with the at least one avatar overlaid on the messaging user interface. In accordance with a determination that the input corresponds to selection of the application affordance, the device displays a plurality of application launch icons for a plurality of corresponding applications within the messaging user interface.


Portable Multifunction Device 100
104
Peripherals Interface 118
Controller 120
Processor(s) 122
103
Memory 102
Operating System 126
Communication Module 128
Contact/Motion Module 130
Graphics Module 132
Haptic Feedback Module 133
Text Input Module 134
GPS Module 135
Applications 136
Contacts Module 137
Telephone Module 138
Video Conference Module 139
E-mail Client Module 140
Instant Messaging Module 141
News Module 142
Camera Module 143
Image Management Module 144
Video & Music Player Module 152
Notes Module 153
Map Module 154
Browser Module 147
Calendar Module 148
Widget Modules 149
Weather Widget(s) 149-1
Stocks Widget 149-2
Calculator Widget 149-3
Alarm Clock Widget 149-4
Dictionary Widget 149-5
User-Created Widget(s) 149-6
Search Module 151
Online Video Module 155
Device/Global Internal State 157
Power System 162
RF Circuitry 108
External Port 124
Proximity Sensor 166
Audio Circuitry 110
111
113
Accelerometer(s) 168
103
I/O Subsystem 106
Touch-Sensitive Display System 112
Display Controller 156
Optical Sensor(s) 164
Optical sensor(s) Controller 158
Contact Intensity Sensor(s) 165
Intensity sensor(s) Controller 159
Tactile Output Generator(s) 167
Haptic Feedback Controller 161
Other Input Control Devices 116
Other Input Controller(s) 160

FIG. 1A


Event Sorter
170
Event Monitor
171
Hit View Determination Module
172
Active Event Recognizer Determination Module
173
Event Dispatcher Module
174
Application 136-1
Application
Application View 191
Application View 191
Event Handler 190
Data Updater 176
Object Updater 177
GUI Updater 178
Event Handler 190
Application Internal State 192
Event Recognizer 180
Event Recognizer 180
Event Data 179
Event Recognizer 180
Event Receiver 182
Event Comparator 184
Event Definitions 186
Event 1 187-1
Event 2 187-2
Metadata 183
Event Delivery 188

Figure 1B


Portable Multifunction Device 100
206
210
212
Speaker 111
Optical Sensor 164
Proximity Sensor 166
208
200
208
210 is SIM card slot
212 is headphone jack
202
Touch Screen 112
Contact Intensity Sensor(s) 165
Tactile Output Generator(s) 167
203
Microphone 113
Home 204
Accelerometer(s) 168
External Port 124

Figure 2


Memory 370
Operating System
126
Communication Module
128
Contact/Motion Module
130
Graphics Module
132
Haptic Feedback Module
133
Text Input Module
134
Applications
136
Contacts Module
137
Telephone Module
138
Video Conference Module
139
E-mail Client Module
140
Instant Messaging Module
141
News Module
142
Camera Module
143
Image Management Module
144
Browser Module
147
Calendar Module
148
Widget Modules
149
Weather Widget
149-1
Stocks Widget
149-2
Calculator Widget
149-3
Alarm Clock Widget
149-4
Dictionary Widget
149-5
User-Created Widget(s)
149-6
Widget Creator Module
150
Search Module
151
Video & Music Player Module
152
Drawing Module
380
Presentation Module
382
Word Processing Module
384
Website Creation Module
386
Disk Authoring Module
388
Spreadsheet Module
390
Device/Global Internal State
157
Device 300
310
CPU(s)
320
330
I/O Interface
Display
340
Keyboard/Mouse
350
Touchpad
355
Tactile Output Generator(s)
357
Sensor(s)
359
360
Network Communications Interface

Figure 3


Portable Multifunction Device
100
206
Speaker 111
Optical Sensor 164
Proximity Sensor 166
400
208
208
402
Current Time 404
405
406
Tuesday
30
Messages 424
Calendar 426
Photos 428
Camera 430
Online Video 432
Stocks 434
280
101
Maps 436
73°
Weather 438
Clock 440
News 442
Notes 444
Settings 446
App Store
iTunes
Voice Memos
Utilities
4
414
6
410
Phone 416
Mail 418
Browser 420
iPod 422
408
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 4A


450
468
470
453


451
460
462
Tactile Output Generator(s) 357
452
Contact Intensity Sensor(s) 359

Figure 4B



Figure 4C



Figure 4D



Figure 4E


9:26 PM
Genevive
5004
Interested in hiking Saturday?
Sure, where are you headed?
How about Point Reyes?
5006
5008-1
5010
5002

Figure 5A


9:26 PM
Genevive
Interested in hiking Saturday?
5004
Sure, where are you headed?
How about Point Reyes?
5006
5016
5014-6
5012
HA
5014-1
5014-2
5014-3
5014-4
5014-5
5002

Figure 5B


9:26 PM
Genevive
Interested in hiking Saturday?
5004
Sure, where are you headed?
How about Point Reyes?
5006
5022
5018-1
5014-2
5002

Figure 5C


9:26 PM
Interested in hiking Saturday?
5024
Sure, where are you headed?
5008
How about Point Reyes?
5006
5014-2
HA
!!
?
5028
Copy
5030
More ...

Figure 5D


9:26 PM
Interested in biking Saturday?
Sure, where are you heading?
5024
How about Point Reyes?
5006
5014-1
HA
!!
?
5026
Copy
More ...

Figure 5E


9:26 PM
Genevive
Interested in hiking Saturday?
5004
Sure, where are you headed?
How about Point Reyes?
5006
5018-2
5014-1
5002

Figure 5F


9:26 PM
Issac
Interested in hiking Saturday?
5004
Sure, where are you headed?
How about Point Reyes?
5006
5020
5002

Figure 5G


9:26 PM
Issac
5004
Interested in hiking Saturday?
Sure, where are you headed?
How about Point Reyes?
5006

Figure 5H


9:26 PM
Issac
CN
Chuck
Neil
Max
Genevive
About to order food. Pizza preferences?
5004
Mushrooms
CN
No olives please
5008-2
How about pepperoni and mushroom?
5036
5034
5002

Figure 5I


5041
CN
2
2
1
5040-1
5040-2
5040-3
HA
How about pepperoni and mushroom?
Copy
More ...
5038

Figure 5J


2
5042-1
5042-2
Mushrooms
HA
How about pepperoni and mushroom?
Copy
More ...
5038

Figure 5K


9:26 PM
Genevive
5002
Sure, where are you headed?
How about Point Reyes?
5004
5044
Can I get a ridiculous up with you?
5046-1
5048
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5L


9:26 PM
Sure, where are you headed?
How about Point Reyes?
Can I get a ridiculous up with you?
5046-1
Copy
Edit
5050
Delete
More ...
space
return

Figure 5M


9:26 PM
Genevive
5052
5057
5056
Can I get a ridiculous up
with you? 5046-1
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
5054 space
return

Figure 5N


9:26 PM
Genevive
5002
Sure, where are you headed?
How about Point Reyes?
5004
Can I get a ride up with you? 5046-2
5060
5058-1
Edited
5058-2
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5O


9:26 PM
Sure. Where are you headed?
How about Point Reyes?
5044
Can I get a ride up with you?
5046-2
5058-1
Edited
5058-2
5064
Copy
5066
Show Edits
5072
5068
Delete
5070
More ...
5062

Figure 5P


9:26 PM
Sure, where are you headed?
5074
Can I get a ride up with you? 5046-2
5076
Can I get a ridiculous up with you? 5046-1
5078
5080 Edit
5082 Done
123
space
return

Figure 5Q


9:26 PM
Issac
Sure, where are you headed?
How about Point Reyes?
Can I get a ride up with you? 5046-2
5084
5058-1
Edited
5058-2
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5R


9:20 PM
Sure, where are you headed?
Can I get a ride up with you?
5046-2
5058-1
Edited
5058-2
HA
Copy
Show Edits
5086
Delete
More ...
later
123
space
return

Figure 5S


9:26 PM
Sure, where are you headed?
Can I get a ride up with you? 5046-2
Can I get a ridiculous up with you? 5046-1
Ok
Thanks
Talk later
5082
Done
space
return

Figure 5T

9:26 PM
Max
We won the bout!
5004
5104
5106
5002
5100
5102
Congratulations!
I
The
To
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M X
123
space
return
ITD
ITL
ITH
ITO

Figure 5U

9:26 PM
Max
We won the bout!
Congratulations!
5008
5102
I
The
To
space
return
123
ITD
ITL
ITH
IT0

Figure 5V

9:26 PM
Wendy
We won the bout!
Congratulations!
5008
5102
I
The
To
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5W


9:26 PM
Max
We won the bout!
Congratulations!
5104
5108-1
I
The
To
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
ITD
ITL
ITH
ITO

Figure 5X


9:26 PM
Max
We won't the bout!
Congratulations!
I
The
To
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
5108-2
ITD
ITL
ITH
ITC

Figure 5Y


9:28 PM
We won the bout!
Congratulations!
5108-3
I
The
To
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M X
123
space
return
ITD
ITL
ITH
IT0

Figure 5Z


Send with effect
Bubble
5114
Screen
5116
5112-4
SLAM
5112-3
LOUD
5112-2
GENTLE
5112-1
INVISIBLE INK
5108-4
5102
Congratulations!
X
5008
5120
5110
ITD
ITL
ITH
IT0

Figure 5AA


Send with Effect
Bubble
5114
Screen
5116
5112-4
SLAM
5118
5008
Congratulations!
5102
5108-5
5112-2
GENTLE
5112-1
INVISIBLE INK
X
5120
5110
ITD
ITL
ITH
ITO

Figure 5AB


Send with Effect
Bubble
5114
Screen
5116
Congratulations!
5008
5102
5112-4
SLAM
5112-3
LOUD
5112-2
GENTLE
5112-1
INVISIBLE INK
5108-5
X
5120
5110
ITD
ITL
ITH
ITO

Figure 5AC


Send with Effect
Bubble
5114
Screen
5116
5112-4
SLAM
5102
Congratulations!
LOUD
5008
5108-5
GENTLE
INVISIBLE INK
X
5120
5110
ITD
ITL
ITH
IT0

Figure 5AD


Send with Effect
Bubble
5114
Screen
5116
5102
Congratulations!
5008
5108-6
LOUD
GENTLE
INVISIBLE INK
X
5120
5110
ITD
ITL
ITH
ITO

Figure 5AE


Send with Effect
Bubble
5114
Screen
5116
5102
Congratulations!
5008
5108-6
LOUD
GENTLE
INVISIBLE INK
X
5120
5110
ITD
ITL
ITH
ITO

Figure 5AF


Send with Effect
Bubble
5114
Screen
5116
5102
Congratulations!
5008
5108-7
LOUD
GENTLE
INVISIBLE INK
X
5120
5110
ITD
ITL
ITH
IT0

Figure 5AG


9:26 PM
Max
We won the bout!
5102
Congratulations!
5008
I
The
To
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
X
123
space
return

Figure 5AH

9:26 PM
Max
We won the bout!
5102
Congratulations!
5008
I
The
To
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5AI

9:26 PM
Max
We won the bout!
5102
Congratulations!
5008
I
The
To
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5AJ

9:26 PM
Wendy
We won't the bout!
5102
Congratulations!
5008
I
The
To
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5AK

9:26 PM
Wendy
We won the bout!
5102
Congratulations!
5008
I
The
To
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5AL

9:26 PM
Wendy
We won the bout!
5102
Congratulations!
5008
I
The
To
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5AM


9:41 AM
100%
Freddy
Today 9:38 AM
Pretty well, actually...
In fact, as of last night we're engaged!
5008
iMessage
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5AN

9:41 AM
100%
Freddy
Today 9:30 AM
Pretty well, actually...
In fact, as of last night we're engaged!
5008
5102
iMessage
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5AO

9:41 AM
100%
Freddy
How are things going with the one of you these days?
Pretty well, actually...
In fact, as of last night we're engaged!
CONGRATS
Message
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5AP

9:41 AM
100%
Freddy
How are things going with the photo you liked today?
Pretty well, actually...
In fact, as of last night we're engaged!
CONGRATS
Message
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5AQ

9:41 AM
100%
Freddy
Today 8:35 AM
How are things going with the
Pretty well, actually...
In fact, as of last night we're engaged!
CONGRATS
Message
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5AR


9:41 AM
100%
Freddy
thinking about a trip too.
Today 9:35 AM
How are things going with the two of you these days?
Pretty well, actually...
In fact, as of last night we're engaged!
5008
CONGRATS
5102
iMessage
I
The
I'm
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5AS


9:41 AM
100%
Freddy
Awesome. I'll count you in.
That's too bad... everyone was really looking forward to seeing you.
Message
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5AT


9:41 AM
100%
Freddy
Awesome. I'll count you in.
That's too bad... everyone was really looking forward to seeing you.
Message
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5AU


9:41 AM
100%
Freddy
Awesome. I'll count you in.
That's too bad... everyone was really looking forward to seeing you.
Message
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5AV

9:41 AM
100%
Freddy
Awesome. I'll count you in.
Hey, something has come up at work, and I'm not going to be able to join you guys tonight.
That's too bad... everyone was really looking forward to seeing you.
I'm sorry?
Message
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5AW


9:41 AM
100%
Freddy
Let's talk about it more in person.
Are you free this friday night?
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5AX


9:41 AM
100%
Let's talk about it more in person.
Are you free this friday night?
No!!
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5AY


9:41 AM
100%
Awesome. I'll count you in.
Let's talk about it more in person.
Are you free this friday night?
Love it! Can't wait!
Hell No!!
I
The
the
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5AZ


9:41 AM
100%
Let's talk about it more in person.
Are you free this friday night?
Cool, should I see if Imran
wants to come?
Hell No!!
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BA


9:41 AM
100%
Freddy
Awesome, I'll count you in.
Let's talk about it more in person.
Are you free this friday night?
Love it! Can't wait!
Cool, should I see if Imran
wants to come?
Hell No!!
iMessage
I
The
I'm
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BB

9:41 AM
100%
Freddy
Awesome, I'll count you in.
Let's talk about it more in person.
Are you free this friday night?
Love it! Can't wait!
Cool, should I see if Imran
wants to come?
Hell No!!
iMessage
I
The
I'm
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BC


9:41 AM
100%
Freddy
Let's talk about it more in person. Are you free this friday night?
Cool, should I see if Imran wants to come?
Message
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BD


9:41 AM
100%
Freddy
Let's talk about it more in person.
Are you free this friday night?
Cool, should I see if Imran
wants to come?
Message
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BE


9:41 AM
100%
Freddy
Let's talk about it more in person.
Are you free this friday night?
Cool, should I see if Imran
wants to come?
Message
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BF


Send with Effect
Bubble
5114
Screen
5116
5112-4
SLAM
5112-3
LOUD
5112-2
GENTLE
5118
5122
X
5120
5110

Figure 5BG


9:26 PM
Wendy
We won the bout!
5004
Congratulations!
5126
5124
I have
5008
5128-a
5002
I
The
To
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BH

9:26 PM
Wendy
We won the bout!
5004
Congratulations!
5126
5124
a surprise fo
5008
5128-b
5002
I
The
To
space
return

Figure 5BI


9:26 PM
Wendy
We won the bout!
5004
Congratulations!
5124
5126
a surprise fo
5008
5128-c
5002
I
The
To
space
return

Figure 5BJ


9:26 PM
Wendy
We won the bout!
5004
Congratulations!
5124
5126
r you
5008
5002
I
The
To
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BK

9:26 PM
Wendy
We won the bout!
5004
Congratulations!
5124
5008
5002
I
The
To
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BL

9:26 PM
Wendy
We won the bout!
5004
Congratulations!
5126
5124
ve a surprise for
5008
5130-a
5002
I
The
To
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BM


9:26 PM
Wendy
We won the bout!
5004
Congratulations!
5126
5124
have a surprise for y
5008
5002
5130-b
I
The
To
space
return

Figure 5BN


9:26 PM
Wendy
We won the bout!
Congratulations!
5126
I have a surprise for you
5008
5002
5130-c
I
The
To
space
return

Figure 5BO

9:26 PM
Wendy
We won the bout!
5004
Congratulations!
5124
5008
5002
I
The
To
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BP


9:41 AM
100%
Chan
Presentation went well
Calling you in 15 minutes when I get to the terminal.
Message
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BQ


9:41 AM
100%
Chan
Presentation went well
Calling you in 15 minutes when I get to the terminal.
iMessage
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BR


9:41 AM
100%
Chan
Presentation went well
Calling you in 15 minutes when I get to the terminal.
iMessage
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BS


9:41 AM
100%
Chan
Presentation went well
Calling you in 15 minutes when I get to the terminal.
iMessage
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BT


9:41 AM
100%
Chan
Presentation went well
Calling you in 15 minutes when I get to the terminal.
iMessage
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BU


9:41 AM
100%
Chan
Presentation went well
Calling you in 15 minutes when I get to the terminal.
iMessage
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BV


9:41 AM
100%
Chan
I'll call you later tonight
Message
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BW


9:41 AM
100%
Chan
I'll call you later tonight
iMessage
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BX


9:41 AM
100%
Chan
I'll call you later tonight
iMessage
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BY


9:41 AM
100%
Chan
I'll call you later tonight
Message
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5BZ


9:41 AM
100%
Chan
I'll call you later tonight
Message
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5CA


Send with effect
Bubble
5114
Screen
5116
5150
5152-1
SEND WITH BALLOONS
5118
Congratulations!
X
5120
5152-1
5154

Figure 5CB


Send with effect
Bubble
5114
Screen
5116
5156
5152-1
SEND WITH BALLOONS
Congratulations!
5154

Figure 5CC


Send with effect
Bubble
Screen
5152-2
SEND WITH CONFETTI
Congratulations!

Figure 5CD


Send with effect
Bubble
Screen
5152-2
SEND WITH CONFETTI
5158
Congratulations!
5118
X
5120

Figure 5CE


9:26 PM
Wendy
5160
We won the bout!
5004
Congratulations!
5146
5008
5160
5002

Figure 5CF



Figure 5CG

9:41 AM
100%
Freddy
Hi, How is it going?
Yesterday 10:23 AM
Sounds great! Let me see if Jen can go too.
iMessage

Figure 5CH

9:41 AM
100%
Freddy
Hi, How is it going?
Great! Went up to San Francisco this week.
That food was amazing!
Yesterday 10:29 AM
We want to take you out to dinner for your birthday tomorrow. Are you free?
Sounds great! Let me see if Jen can go too.
Perfect!
iMessage

Figure 5CI

9:41 AM
100%
Freddy
Hi, How is it going?
Yesterday 10:23 AM
Sounds great! Let me see if Jen can go too.
Perfect!
Today 9:23 AM
Happy Birthday!!!
Message

Figure 5CJ

9:41 AM
100%
Freddy
Hi, How is it going?
Great! I went up to San Francisco this week.
The food was amazing!
Yesterday 10:23 AM
We want to take you out to celebrate for your birthday tomorrow. Are you free?
Sounds great! Let me see if Jen can go too.
Perfect!
Today 9:23 AM
Happy Birthday!!!
Message

Figure 5CK


9:41 AM
100%
Freddy
Hi, How is it going?
Yesterday 10:23 AM
Sounds great! Let me see if Jen can go too.
Perfect!
Happy Birthday!!!
iMessage

Figure 5CL


9:41 AM
100%
Freddy
Hi, How is it going?
Great! I want us to San Francisco this week.
The food was amazing!
Yesterday 10:23 AM
We want to take you out to dinner for your birthday tomorrow - are you free?
Sounds great! Let me see if Jen can go too.
Today 9:2
Happy Birthday!!!!
iMessage

Figure 5CM


Sounds great! Let me see if Jen can go too.
Perfect!
Today 9:23 AM
Happy Birthday!!!!
iMessage

Figure 5CN


9:41 AM
100%
Freddy
Hi, How is it going?
Great. I went to the San Francisco this week.
This food was amazing!
Yesterday 10:23 AM
We want to take you out to brunch for your birthday tomorrow. Are you free?
Sounds great! Let me see if Jen can go too.
Perfect!
Today 9:23 AM
Happy Birthday!!!
iMessage

Figure 5CO

9:41 AM
100%
Freddy
Yesterday 10:33 AM
Brunch Tomorrow?
Sounds good. I want to hear more about your dinner at Boulevard. I've wanted to try that place for years! I'm jealous!!
Happy New Year!!
iMessage

Figure 5CP

Figure 5CQ



Figure 5CR



Figure 5CS



Figure 5CT

Peachy
Brunch Tomorrow?
Sounds good. I want to hear more about your dinner at Boulevard. I've wanted to try that place for years! I'm jealous!!
Happy New Year!!

Figure 5CU

9:41 AM
100%
Freddy
Brunch Tomorrow?
Sounds good. I want to hear more about your dinner at Boulevard. I've wanted to try that place for years! I'm jealous!!
Happy New Year!!
Message

Figure 5CV

9:41 AM
100%
Freddy
Yesterday 10:23 AM
Brunch Tomorrow?
Sounds good. I want to hear more about your dinner at Boulevard. I've wanted to try that place for years! I'm jealous!!
Today 9:23 AM
Happy New Year!!
Message

Figure 5CW


9:26 PM
Genevive
5008
5004
5170
5002
5100
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5CX


9:26 PM
Genevive
5008
5004
5170
5174
5100
5172
5118
5002
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5CY


9:26 PM
Genevive
5008
5004
5170
5008
5172
5002
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5CZ


9:26 PM
Genevive
5008
5004
5170
5008
5172
Cheers!
5176
5002
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M X
123
space
return

Figure 5DA

9:26 PM
Genevive
5008
Happy
5178
5182
5118
5100
5180
Birthday!
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5DB


9:26 PM
Genevive
5008
Happy
5178
5180
Birthday!
5008
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5DC

9:26 PM
Genevive
5002
Interested in hiking Saturday?
Sure, where are you headed?
How about Point Reyes?
5202
5204
5102
5200
Yes!
5100
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5DD


9:26 PM
Genevive
5002
Interested in hiking Saturday?
Sure, where are you headed?
How about Point Reyes?
5200
5102
Yes!
5100
Store
Bubbles
Wallet
Reviews
5206
5208
Activity
Videos
Games
More ...

Figure 5DE


9:26 PM
Genevive
5002
How about Point Reyes?
5102
Yes!
5210-1
5200
5100
5212
POP!

Figure 5DF


9:26 PM
Genevive
How about Point Reyes?
5002
5102
Yes!
5210-1
5200
5100
5214
POP!
YES

Figure 5DG


9:26 PM
Genevive
5002
How about Point Reyes?
5102
YES!
5210-2
5200
5100
POP!
SH

Figure 5DH


9:26 PM
Genevive
How about Point Reyes?
5002
5102
YES!
5210-3
5200
5100
5216
POP!
SH

Figure 5DI

9:41 AM
100%
Freddy
5002
Chan
Hey guys, remember we should keep this on the low
5004
Tiffany
ok! But what we should do for the party?
5100
5220
'What if we have everyone meet at Rintaro? She loves sushi. I can bring a nice bottle of wine and maybe we can all go bowling afterwards?
5200
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 5DJ


9:41 AM
100%
Freddy
5002
Chan
Hey guys, remember we should keep this on the low
5004
Tiffany
ok! But what we should do for the party?
5100
5222
'What if we have everyone meet at Rintaro? She loves sushi. I can bring a nice bottle of wine and maybe we can all go bowling afterwards?
5220
5200
FREQUENTLY USED
SMILEYS & PEOPLE

Figure 5DK


9:41 AM
100%
Freddy
5002
Chan
Hey guys, remember we should keep this on the low
5004
Tiffany
ok! But what we should do for the party?
5100
5222
'What if we have everyone meet at Rintaro? She loves sushi. I can bring a nice bottle of wine and maybe we can all go bowling afterwards?
5220
5200
FREQUENTLY USED
SMILEYS & PEOPLE

Figure 5DL


9:41 AM
100%
Freddy
5002
Chan
Hey guys, remember we should keep this on the low
5004
Tiffany
ok! But what we should do for the party?
5100
5222
5224
5220
5200
'What if we have everyone meet at Rintaro? She loves sushi. I can bring a nice bottle of wine and maybe we can all go bowling afterwards?
FREQUENTLY USED
SMILEYS & PEOPL

Figure 5DM


9:41 AM
100%
Freddy
5002
Chan
Hey guys, remember we should keep this on the low
5004
Tiffany
ok! But what we should do for the party?
5100
5222
5224
5220
5200
5226
'What if we have everyone meet at Rintaro? She loves sushi. I can bring a nice bottle of wine and maybe we can all go bowling afterwards?
FREQUENTLY USED
SMILEYS & PEOPLE

Figure 5DN


9:41 AM
100%
Freddy
5002
Chan
Hey guys, remember we should keep this on the low
5004
Tiffany
ok! But what we should do for the party?
5100
5222
5224
5220
5200
5226
What if we have everyone meet at Rintaro? She loves . I can bring a nice bottle of wine and maybe we can all go bowling afterwards?
FREQUENTLY USED
SMILEYS & PEOPL

Figure 5DO


9:41 AM
100%
Freddy
5002
Chan
Hey guys, remember we should keep this on the low
5004
Tiffany
ok! But what we should do for the party?
5100
5232
5234
5220
5200
5226
'What if we have everyone meet at Rintaro? She loves . I can bring a nice bottle of and maybe we can all go bowling afterwards?
FREQUENTLY USED
SMILEYS & PEOPLE

Figure 5DP


9:41 AM
100%
Freddy
5002
Chan
Hey guys, remember we should keep this on the low
5004
Tiffany
ok! But what we should do for the party?
5100
5232
5234
5220
5200
5236
'What if we have everyone meet at Rintaro? She loves . I can bring a nice bottle of and maybe we can all go afterwards?
FREQUENTLY USED
SMILEYS & PEOPL

Figure 5DQ


600
At an electronic device (e.g., a first electronic device) having one or more processors, memory, a touch-sensitive surface, and a display:
Display a messaging user interface on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user
602
Receive a first message within the messaging session from an electronic device (e.g., a second electronic device) that corresponds to another user included in the messaging session
604
In response to receiving the first message, displaying the first message in a first message region in the conversation transcript on the display
606
Detect a first input by a first contact at a location on the touch-sensitive surface that corresponds to a location of the first message region in the conversation transcript
608
In response to detecting the first input, displaying an acknowledgement selection affordance at a location in the messaging interface that corresponds to the first message region, wherein the acknowledgement selection affordance displays a plurality of acknowledgement options
610
The plurality of acknowledgement options include graphical icons that display at least one of a heart, a thumbs up, a thumbs down, a "HA!", a "!!", and/or a question mark
612
In response to detecting the first input, transmitting information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to display an acknowledgement-preparation indicator for a corresponding first message region in a conversation transcript that corresponds to the messaging session
614
A

Figure 6A


A
Detect a second input by a second contact at a location on the touch-sensitive surface that corresponds to a location of a first acknowledgement option in the acknowledgement selection affordance
616
In response to detecting the second input, applying the first acknowledgement option to the first message region
618
In response to detecting the second input, transmitting information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to apply the first acknowledgement option to a corresponding first message region in a conversation transcript that corresponds to the messaging session
620
Applying the first acknowledgement option to the first message region includes displaying the first acknowledgement option at a location adjacent to and/or partially overlapping the first message region
622
D
The first acknowledgement option is displayed in an acknowledgement region that has a different shape from the first message region
624
After applying the first acknowledgement option to the first message region:
630
Detecting a third input by a third contact at a location on the touch-sensitive surface that corresponds to a location of the first message region
632
B

Figure 6B


After applying the first acknowledgement option to the first message region:
630
B
In response to detecting the third input by the third contact at the location on the touch-sensitive surface that corresponds to the location of the first message region, displaying an acknowledgement editing interface
634
In response to detecting the third input by the third contact, ceasing to display the conversation transcript
636
In response to detecting the third input by the third contact, displaying the first message region in the acknowledgement editing interface
638
In response to detecting the third input by the third contact, displaying the acknowledgement selection affordance that includes the plurality of acknowledgement options in the acknowledgement editing interface, wherein the first acknowledgement option is visually distinguished from the other acknowledgement options in the plurality of acknowledgement options to indicate that the first acknowledgement option is currently selected
640
In response to detecting the third input by the third contact, displaying a menu in the acknowledgement editing interface that includes activatable editing options for the first message region
642
C

Figure 6C


After applying the first acknowledgement option to the first message region:
620
C
Detecting one or more inputs to the acknowledgement editing interface
650
Editing an acknowledgement option for the first message region in accordance with the detected one or more inputs
652
Ceasing to display the acknowledgement editing interface
654
Displaying the first message region in the conversation transcript with an edited acknowledgement
656
Transmitting information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to display a corresponding first message region with the edited acknowledgement in a conversation transcript that corresponds to the messaging session
658

Figure 6D


D
Concurrently displaying on the display:
a second message region in the conversation transcript, wherein
at least some of the users in the messaging session have selected the first acknowledgement option for the second message region and,
at least some of the users in the messaging session have selected a second acknowledgement option for the second message region, distinct from the first acknowledgement option; and
one or more indicia that users in the messaging session have selected a plurality of acknowledgements options for the second message region
660
Detecting an input by a contact at a location on the touch-sensitive surface that corresponds to a location of the second message region
662
In response to detecting the input by the contact at the location on the touch-sensitive surface that corresponds to the location of the second message region, displaying a user interface that includes a tally for each type of acknowledgement option selected by users in the messaging session
664
While displaying the tally for each type of acknowledgement option selected by users in the messaging session, detecting an input by a contact at a location on the touch-sensitive surface that corresponds to a tally for the first acknowledgement option for the second message region
666
In response to detecting the input by the contact at a location on the touch-sensitive surface that corresponds to the tally for the first acknowledgement option for the second message region, displaying icons (e.g., avatars) that represent users that selected the first acknowledgement option for the second message region
668

Figure 6E


700
Processing unit 706
Display unit 702
Detecting unit 708
Display enabling unit 710
Touch-sensitive surface unit 704
Ceasing unit 712
Transmitting unit 714
Receiving unit 716
Applying unit 718
Editing unit 720

Figure 7


800
802
Display a messaging user interface on a display, the messaging user interface including: a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a first message region that includes a first message in the messaging session that was sent from the electronic device of the user to the at least one other user in the messaging session
804
Detect a first input that corresponds to a request to edit the first message
806
In response to detecting the first input, display a message editing interface for the first message that includes the first message, a keyboard, and an update affordance
808
While displaying the message editing interface for the first message:
810
Detect one or more inputs that revise the first message
812
Detecting the one or more inputs that revise the first message include detecting an input at a location that corresponds to the first message in the message editing interface to select a position in the first message for text selection, text insertion, or the text deletion
814
Display a revised version of the first message
816
Detect an input that activates the update affordance
A

Figure 8A


800
A
818
In response to detecting the input that activates the update affordance:
820
Cease to display the message editing interface for the first message
822
Display the revised version of the first message in place of the first message in the conversation transcript
824
Display at least one indication of the revision of the first message in the conversation transcript
826
the at least one indication of the revision of the first message in the conversation transcript is not removable from the conversation transcript
828
The at least one indication of the revision of the first message includes a graphical element at a location of the first message region
830
The at least one indication of the revision of the first message includes text adjacent to the first message region
832
Transmit the revised version of the first message to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the revised version of the first message in place of the first message in a conversation transcript that corresponds to the messaging session, with at least one indication of the revision of the first message in the conversation transcript

Figure 8B

800

834

After editing the first message, detect an input that corresponds to a request to edit the revised version of the first message;

in response to detecting the input that corresponds to the request to edit the revised version of the first message, display a message editing interface for the revised version of the first message that includes the revised version of the first message, the keyboard, and the update affordance;

while displaying the message editing interface for the revised version of the first message:

detect one or more inputs that further revise the first message;

display a further revised version of the first message; and

detect an input that activates the update affordance; and,

in response to detecting the input that activates the update affordance:

cease to display the message editing interface for the revised version of the first message;

display the further revised version of the first message in place of the revised version of first message in the conversation transcript;

display at least one indication that the first message in the conversation transcript has been revised; and

transmit the further revised version of the first message to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the further revised version of the first message in place of the revised version of first message in a conversation transcript that corresponds to the messaging session, with at least one indication that the first message in the conversation transcript has been revised

836

After editing the first message, detect an input that corresponds to a request to see versions of the first message; and, in response to detecting the input that corresponds to the request to see versions of the first message, display a user interface that includes a current version of the first message and one or more prior versions of the first message

Figure 8C


900
Processing unit 906
Display unit 902
Detecting unit 908
Display enabling unit 910
Touch-sensitive surface unit 904
Ceasing unit 912
Transmitting unit 914

Figure 9


1000
1002
Display a messaging user interface on a display, the messaging user interface including: a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a first message region that includes a current version of a first message in the messaging session, wherein the conversation transcript includes an indication that the current version of the first message is a revised version of the first message in the conversation transcript
1004
Detect an input that corresponds to a request to see versions of the first message
1006
The input that corresponds to the request to see versions of the first message is detected while displaying
the current version of the first message and
a menu that includes an affordance, which when activated results in display of the user interface that includes the current version of the first message and one or more prior versions of the first message
1008
In response to detecting the input that corresponds to the request to see versions of the first message, display a versions user interface that includes the current version of the first message and one or more prior versions of the first message
1010
in the versions user interface, the current version of the first message is visually distinguished from other versions of the first message
1012
The versions user interface includes the current version of the first message, an original version of the first message, and at least one version of the first message that was revised prior to the current version of the first message
1014
The versions user interface includes an affordance, which when activated causes redisplay of the conversation transcript
1016
The versions user interface includes an affordance, which when activated causes display of a message editing interface for the current version of the first message that includes the current version of the first message, a keyboard, and an update affordance

Figure 10A

1000

1018

While displaying the versions user interface, detect an input on a respective version of the first message; and, in response to detecting an input on the respective version of the first message:

display a message editing interface for the respective version of the first message that includes the respective version of the first message, a keyboard, and an update affordance; and

cease to display the versions user interface

Figure 10B


1100
Processing unit 1106
Display unit 1102
Detecting unit 1108
Display enabling unit 1110
Touch-sensitive surface unit 1104
Ceasing unit 1112

Figure 11


1200
1202
Display a messaging user interface on a display, the messaging user interface including: a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a message-input area that includes a first message input
1204
While displaying the messaging user interface, detect a first input by a first contact at a location on the touch-sensitive surface that corresponds to a location in the message-input area
1206
In response to detecting the first input by the first contact, display an impact selection interface that includes a plurality of impact effect options
1208
The impact selection interface includes a region effect options affordance, which when activated causes display of impact effect options for a message containing the first message input, and a full-screen effect options affordance, which when activated causes display of a preview of one impact effect option that is applied to the entire displayed conversation transcript when a message containing the first message input is displayed in the messaging session
1210
The plurality of impact effect options includes at least one impact effect option that applies an image with an area that is larger than an area of a message region that contains the first message input to the message region that contains the first message input
1212
The plurality of impact effect options includes at least one impact effect option that increases or decreases a size of a message region that contains the first message input relative to a size of the message region that contains the first message input when no impact effect option is selected
A

Figure 12A


1200
A
1206
In response to detecting the first input by the first contact, display an impact selection interface that includes a plurality of impact effect options
1214
The plurality of impact effect options includes at least one impact effect option that is configured to have a message region that contains the first message input interact with other message regions in the displayed conversation transcript when the message region that contains the first message input is displayed
1216
The plurality of impact effect options includes at least one impact effect option that is configured to display an animation when a message region that contains the first message input is displayed in a conversation transcript that corresponds to the messaging session
1218
The plurality of impact effect options includes at least one impact effect option that is configured to display an animation when a message region that contains the first message input is displayed in a conversation transcript that corresponds to the messaging session, wherein the animation concurrently moves the message region that contains the first message input and other message regions in the conversation transcript
1220
The plurality of impact effect options includes at least one impact effect option that is configured to trigger one or more tactile outputs when a message region that contains the first message input is displayed in a conversation transcript that corresponds to the messaging session
A

Figure 12B


1200
A
1222
While displaying the impact selection interface, detect a second input by a second contact at a location on the touch-sensitive surface that corresponds to a location of a first impact effect option in the plurality of impact effect options
1224
In response to detecting the second user input by a second contact, display a preview that applies the first impact effect option to the first message input
1226
Wherein the preview that applies the first impact effect option to the first message input repeats periodically
B
1228
After displaying the preview, detect lift off of the second contact at a location on the touch-sensitive surface that corresponds to the first impact effect option; and, in response to detecting lift off of the second contact at the location on the touch-sensitive surface that corresponds to the first impact effect option: cease to display the impact selection interface; display a message region that contains the first message input in the conversation transcript; and transmit information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to display a message region that contains the first message input in a conversation transcript that corresponds to the messaging session, and apply the first impact effect option

Figure 12C

1200

B

1230

After displaying the preview, detect lift off of the second contact at a location on the touch-sensitive surface that corresponds to the first impact effect option; and, in response to detecting lift off of the second contact at a location on the touch-sensitive surface that corresponds to the first impact effect option: select the first impact effect option for a message that contains the first message input; cease to display the impact selection interface; and display the conversation transcript of the messaging session and the message-input area that includes a first message input; detect a third input; and in response to detecting the third input: display a message region that contains the first message input in the conversation transcript; and transmit information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to display a message region that contains the first message input in a conversation transcript that corresponds to the messaging session, and apply the first impact effect option

1232

After displaying the preview, detect a third input by a third contact at a location on the touch-sensitive surface that corresponds to the first impact effect option; and, in response to detecting the third input by the third contact at the location on the touch-sensitive surface that corresponds to the first impact effect option: cease to display the impact selection interface; display a message region that contains the first message input in the conversation transcript; and transmit information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to display a message region that contains the first message input in a conversation transcript that corresponds to the messaging session, and apply the first impact effect option

1234

After displaying the preview, detect a third input by a third contact at a location on the touch-sensitive surface that corresponds to the first impact effect option; and, in response to detecting the third input by the third contact at the location on the touch-sensitive surface that corresponds to the first impact effect option: select the first impact effect option for a message that contains the first message input; cease to display the impact selection interface; and display the conversation transcript of the messaging session and the message-input area that includes a first message input; detect a fourth input; and in response to detecting the fourth input: display a message region that contains the first message input in the conversation transcript; and transmit information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to display a message region that contains the first message input in a conversation transcript that corresponds to the messaging session, and apply the first impact effect option

Figure 12D

1200

1236
While the message-input area is empty, detect an input that enters text in the message-input area; and, in response to detecting the input that enters text in the message-input area, display an impact selection affordance, wherein activation of the impact selection affordance is configured to cause display of the impact selection interface

1238
While a preview of an impact effect option that is applied to the entire displayed conversation transcript is displayed, detect an input that activates display of a preview of another impact effect option that is applied to the entire displayed conversation transcript; and, in response to detecting the input that activates display of the preview of another impact effect option that is applied to the entire displayed conversation transcript, display the preview of the second impact effect option that is applied to the entire displayed conversation transcript

1240
While displaying the impact selection interface, detect an input by a contact at a location on the touch-sensitive surface that corresponds to a location of a second impact effect option in the plurality of impact effect options; and, in response to detecting the user input by the contact at the location on the touch-sensitive surface that corresponds to the location of a second impact effect option, display a preview that applies the second impact effect option to the first message input

1242
Determine whether an electronic device that corresponds to another user in the messaging session is capable of applying the first impact effect option to a message in the messaging session, and, in accordance with a determination that the electronic device that corresponds to another user in the messaging session is not capable of applying the first impact effect option to a message in the messaging session, display a notification on the display of the electronic device of the user about the first impact effect option

Figure 12E


1300
Processing unit 1306
Display unit 1302
Detecting unit 1308
Display enabling unit 1310
Touch-sensitive surface unit 1304
Ceasing unit 1312
Transmitting unit 1314
Selecting unit 1316
Determining unit 1318

Figure 13

1400

1402
Display a messaging user interface on a display, the messaging user interface including: a conversation transcript of a messaging session between a user of the electronic device and at least one other user, including a first other user, and a message region in the conversation transcript for a message received from the first other user, the message region including one or more screen elements that conceal the message received from the first other user

1404
The one or more screen elements that conceal the message are moving particles

1406
The message region with the concealed message has a message region outline that is distinct from an outline on message regions in the conversation transcript that do not have concealed messages

1408
Detect a first input by a contact at a location on a touch-sensitive surface that corresponds to the message region with the concealed message

1410
The first input is a drag gesture by the contact at a location that corresponds to the message region with the concealed message

1412
Detecting the first input by the contact includes detecting a drag gesture by the contact at a location that corresponds to the message region with the concealed message, and dynamically remove portions of the one or more screen elements that conceal the message, thereby revealing corresponding portions of the message, in accordance with the movement of the contact in the drag gesture

1414
The electronic device includes one or more sensors configured to detect intensities of contacts on the touch-sensitive surface, and the first input is a press input by the contact at a location that corresponds to the message region with the concealed message

A

Figure 14A

1400



Figure 14B


1500
Processing unit 1506
Display unit 1502
Detecting unit 1508
Display enabling unit 1510
Touch-sensitive surface unit 1504
Receiving unit 1512
Revealing unit 1514
Concealing unit 1516
Removing unit 1518
Deleting unit 1520

Figure 15


1600
1602
Display a messaging user interface on a display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, including a first other user
1604
Receive a first message within the messaging session from an electronic device that corresponds to the first other user included in the messaging session
1606
Determine whether the first message includes an enhanced message content trigger
1608
The determination whether the first message includes the enhanced message content trigger is performed in response to receiving the first message
1610
Determining whether the first message includes an enhanced message content trigger includes determining whether the first message includes predefined text
1612
Determining whether the first message includes an enhanced message content trigger includes determining whether the first message includes an embedded non-displayed value that indicates the enhanced message content to be displayed
1614
Determining whether the first message includes an enhanced message content trigger includes determining whether a time at which the first message was received corresponds to a predetermined time frame
A

Figure 16A


1600
A
1616
In accordance with a determination that the first message includes the enhanced message content trigger: display the first message in a first message region in the conversation transcript on the display, and display enhanced message content that corresponds to the trigger, wherein the enhanced message content includes content that applies an effect to at least one message region other than the first message region in the conversation transcript
1618
The enhanced message content includes content that applies an effect to the entire displayed conversation transcript
1620
Applying the effect to at least one message region other than the first message region includes accumulating animated objects on at least one message region other than the first message region
1622
Applying the effect to at least one message region other than the first message region includes animating at least one message region other than the first message region
1624
Applying the effect to at least one message region other than the first message region includes temporarily fading message regions other than the first message region without fading the first message region
1626
Applying the effect to at least one message region other than the first message region includes temporarily ceasing to display message regions other than the first message region while maintaining display of the first message region
1628
Displaying the enhanced message content that corresponds to the trigger includes displaying an image that temporarily replaces the entire messaging user interface
B

Figure 16B


1600
1616
In accordance with a determination that the first message includes the enhanced message content trigger: display the first message in a first message region in the conversation transcript on the display, and display enhanced message content that corresponds to the trigger, wherein the enhanced message content includes content that applies an effect to at least one message region other than the first message region in the conversation transcript
B
1630
Displaying the enhanced message content that corresponds to the trigger includes displaying an image that temporarily replaces the entire messaging user interface, except for the first message region
1632
Applying the effect to at least one message region other than the first message region includes temporarily highlighting the first message region without highlighting message regions other than the first message region
1634
The enhanced message content includes sound
1636
The enhanced message content includes tactile output
1638
Displaying the enhanced message content includes displaying an animation of the first message region
1640
Displaying the enhanced message content includes generating and displaying moving virtual objects in response to scrolling of the conversation transcript
1642
In accordance with a determination that the first message does not include the enhanced message content trigger, display the first message in a first message region in the conversation transcript on the display
1644
Cease to display the enhanced message content that corresponds to the trigger

Figure 16C


1700
Processing unit 1706
Display unit 1702
Display enabling unit 1708
Receiving unit 1710
Touch-sensitive surface unit 1704
Determining unit 1712
Applying unit 1714
Accumulating unit 1716
Animating unit 1718
Fading unit 1720
Ceasing unit 1722
Highlighting unit 1724
Generating unit 1726

Figure 17


1800
1802
Display a messaging user interface on a display, the messaging user interface including: a conversation transcript of a messaging session between a user of the electronic device and at least one other user, including a first other user, and a message input area
1804
Receive a first message within the messaging session from an electronic device that corresponds to the first other user included in the messaging session, wherein the first message includes first combinable content
1806
Combinable content includes an emoticon
1808
Combinable content includes an emoji
1810
Combinable content includes a sticker
1812
In response to receiving the first message, display the first message in a first message region in the conversation transcript on the display
1814
Receive input of a second message in the message-input area
1816
While the second message is displayed in the message-input area, detect an input to send the second message to the messaging session
A

Figure 18A

1800
A
1818
In response to detecting the input to send the second message to the messaging session
1820
In accordance with a determination that the second message contains second combinable content and the second combinable content and the first combinable content are parts of a predefined combination, display content that corresponds to the predefined combination in the conversation transcript on the display
1822
The determination that the second combinable content and the first combinable content are parts of a predefined combination is performed in response to detecting the input to send the second message to the messaging session
1824
The first combinable content and the second combinable content that are part of a predefined combination are the same content
1826
The first combinable content and the second combinable content that are part of a predefined combination are different content
1828
Respective first combinable content and respective second combinable content that are part of a respective predefined combination are defined by a user of the electronic device
1830
For a respective predefined combination, the content that corresponds to the predefined combination is defined by a user of the device
1832
The content that corresponds to the predefined combination includes animated content
1834
The content that corresponds to the predefined combination includes audio content

Figure 18B


1800
A
1818
In response to detecting the input to send the second message to the messaging session
1820
In accordance with a determination that the second message contains second combinable content and the second combinable content and the first combinable content are parts of a predefined combination, display content that corresponds to the predefined combination in the conversation transcript on the display
1836
The content that corresponds to the predefined combination includes haptic content
1838
The content that corresponds to the predefined combination includes animated content, audio content and/or haptic content
1840
The content that corresponds to the predefined combination includes automatically generated message text
1842
The content that corresponds to the predefined combination includes content that is applied to the entire displayed conversation transcript when the second message is initially displayed in the messaging session
1844
In accordance with a determination that the second message does not contain second combinable content that forms a predefined combination with the first combinable content, display the second message in a second message region in the conversation transcript on the display

Figure 18C


1900
Processing unit 1906
Display unit 1902
Display enabling unit 1908
Receiving unit 1910
Touch-sensitive surface unit 1904
Detecting unit 1912
Applying unit 1914

Figure 19


Portable Multifunction Device 100
Current Time
<
Alex
Tina
Want to watch a movie together tonight? Check out this trailer...
Sure!
Watch trailer for movie 123 with Alex (tap trailer to accept)?
2002
2001
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 20A


Portable Multifunction Device 100
Current Time
<
Alex
Tina
Want to watch a movie together tonight? Check out this trailer...
Sure!
Watch trailer for movie 123 with Alex (tap trailer to accept)?
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 20B


Portable Multifunction Device 100
Current Time
<
Alex
Tina
Want to watch a movie together tonight? Check out this trailer...
Sure!
You accepted Alex's invitation to watch trailer for Movie 123
Synchronized Viewing of Trailer for Movie 123
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 20C


Portable Multifunction Device 100
Current Time
Alex
Tina
Want to watch a movie together tonight? Check out this trailer...
Sure!
2010
You accepted Alex's invitation to watch trailer for Movie 123
Synchronized Viewing of Trailer for Movie 123
Playing the trailer now!
2012
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 20D


Portable Multifunction Device 100
Current Time
Alex
Tina
Want to watch a movie together tonight? Check out this trailer...
Sure!
2010
You accepted Alex's invitation to watch trailer for Movie 123
Synchronized Viewing of Trailer for Movie 123
Playing the trailer now!
2012
This is cool!
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 20E


Portable Multifunction Device 100
Current Time
<
Alex
Tina
Sure!
You accepted Alex's invitation to watch trailer for Movie 123
Synchronized Viewing of Trailer for Movie 123
Playing the trailer now!
This is cool!
I agree, movie looks good!
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
X
123
space
return

Figure 20F


Portable Multifunction Device 100
Current Time
<
Alex
Tina
You accepted Alex's invitation to watch trailer for Movie 123
Synchronized Viewing of Trailer for Movie 123
Playing the trailer now!
This is cool!
I agree, movie looks good!
Yea, great so far
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
X
123
space
return

Figure 20G


Portable Multifunction Device 100
Synchronized Viewing of Trailer for Movie "Z"
Playing the trailer now!
This is cool!
I agree, movie looks good!
Yea, great so far
Should we go see it tonight?
Maybe
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 20H


Portable Multifunction Device 100
Synchronized Viewing of Trailer for Movie 123
This is cool!
I agree, movie looks good!
Yea, great so far
Should we go see it tonight?
Maybe
This part is boring, I'm fast-forwarding!
2003
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 20I


Portable Multifunction Device 100
Synchronized Viewing of Trailer for Movie 123
Yea, great so far
Should we go see it tonight?
Maybe
This part is boring, I'm fast-forwarding!
You fast-forwarded trailer for movie 123
Hey! You skipped a great part, I'm rewinding
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 20J


Portable Multifunction Device 100
Synchronized Viewing of Trailer for Movie 123
Should we go see it tonight?
Maybe
This part is boring, I'm fast-forwarding!
You fast-forwarded trailer for movie 123
Hey! You skipped a great part, I'm rewinding
Alex rewound trailer for movie 123
2022
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 20K


Portable Multifunction Device 100
Current Time
Alex
Tina
Want to watch a movie together tonight? Check out this trailer...
2024
Sure!
2010
You accepted Alex's invitation to watch trailer for Movie 123
Synchronized Viewing of Trailer for Movie 123
Playing the trailer now!
2012
This is cool!
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 20L


Portable Multifunction Device 100
Synchronized Viewing of Trailer for Movie 123
Should we go see it tonight?
Maybe
This part is boring, I'm fast-forwarding!
You fast-forwarded trailer for movie 123
Hey! You skipped a great part, I'm rewinding
Alex rewound trailer for movie 123
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 20M


Portable Multifunction Device 100
Synchronized Viewing of Trailer for Movie 123
Should we go see it tonight?
Maybe
This part is boring, I'm fast-forwarding!
You fast-forwarded trailer for movie 123
Hey! You skipped a great part, I'm rewinding
Alex rewound trailer for movie 123
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 20N


Portable Multifunction Device 100
I agree, movie
Animation 2050
Yea, great so far
Should we go see it tonight?
Maybe
This part is boring, I'm fast-forwarding!
You fast-forwarded trailer for movie 123
Hey! You skipped a great part, I'm rewinding
Alex rewound trailer for movie 123
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 20O


Portable Multifunction Device 100
Current Time
<
Alex
Tina
Want to watch a movie together tonight? Check out this trailer...
Sure!
You accepted Alex's invitation to watch trailer for Movie 123
Playing the trailer now!
This is cool!
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 20P


2100
2102
Display, on a display of an electronic device, a messaging user interface, the messaging user interface including a conversation transcript of a messaging session between a user of the first electronic device and at least one other user
2104
The conversation transcript includes a representation of a media item that is displayed at a chronological position within the conversation transcript, and the messaging session is configured to allow synchronized viewing of the media item by the user at the first electronic device and the at least one other user at a second electronic device that is distinct from the first electronic device
2106
The representation of the media item is added to the conversation transcript by the user
2108
The representation of the media item is added to the conversation transcript by the at least one other user
2110
Receive a first request for synchronized viewing of the media item within the messaging user interface and, in response to receiving the first request, initiate playing of content corresponding to the media item while the representation of the media item is displayed at the chronological position within the conversation transcript
2112
The first request is received via the second electronic device
2114
The first request is received via the user at the first electronic device
A

Figure 21A


2100
A
2116
Display messages exchanged between the user and the at least one other user within the messaging user interface, including displaying the messages under the playing content corresponding to the media item, such that a position within the messaging user interface of the playing content corresponding to the media item moves towards a top portion of the messaging user interface
2118
in accordance with a determination that the chronological position is within a predetermined distance of the top portion of the messaging user interface, display the playing content corresponding to the media item at a fixed position within the messaging user interface
2120
After initiating playing of the content corresponding to the media item, display the playing content corresponding to the media item at the fixed position within the messaging user interface that is different than the chronological position
2122
Receive an indication that the at least one other user has manipulated the playing content corresponding to the media item; and, in response to receiving the indication, modify presentation of the playing content corresponding to the media item at the electronic device in accordance with the manipulations from the at least one other user
2124
The manipulations include fast-forwarding the playing content, rewinding the playing content, and/or pausing the playing content
2126
While displaying the playing content corresponding to the media item at the fixed position, detect an input;
in response to detecting the input, scroll the conversation transcript; and
while scrolling the conversation transcript, in accordance with a determination that the chronological position of the media item is within a predetermined distance of the fixed position, moving the playing content to the chronological position while continuing to play the playing content.
B

Figure 21B


2100
B
2128
While displaying the playing content corresponding to the media item at the fixed position:
(i) display messages exchanged between the user and the at least one other user below the playing content corresponding to the media item
(ii) detect an end of the content corresponding to the media item
2130
Detecting the end of the playing of the content corresponds to receiving a request to end playing of the content
2132
Detecting the end of the playing of the content corresponds to reaching an end of the playing of the content

Figure 21C


2200
Processing Unit 2208
Displaying Unit 2210
Display Unit 2202
Synchronized Viewing Request Receiving Unit 2212
Touch-Sensitive Surface Unit 2204
Play Initiation Unit 2214
Indication Receiving Unit 2216
Sensor Unit(s) 2206
Detecting Unit 2218
Presentation Modification Unit 2220
Scrolling Unit 2222

Figure 22


Portable Multifunction Device 100
Current Time
Alex
Tina
Maybe we can have a surprise party for him!! ☺
(thumbs up) Love it. Good idea!
Hey guys, remember we should keep this looooww...
Ok!
But I don't know what should we get him this year
Predictive
English (US)
Emoji
Handwriting
2302B
2303
Thanks
Talk later
T Y U I O P
F G H J K L
C V B N M X
123
space
return
2302A

Figure 23A


Portable Multifunction Device 100
Current Time
Alex
Tina
Maybe we can have a surprise party for him!! ☺
(thumbs up) Love it. Good idea!
Hey guys, remember we should keep this loooooww...
CONGRATS!!
2307
Thank you
Thank you for today
2305
Thank you + other
2303
Get well
Thank you
condolences
CONGRATS!!!
2304
Rotate to begin writing
2351

Figure 23B


Auto-replacing Handwritten Text in Input Portion 2303
2392A
Thank you
Thank you for helping to plan all of this! I think he is going to be really surprised!
2303
2306
2392B
Thank you
Thank you for helping to plan all of this! I think he is going to be really surprised!
2303
2306
Thank you for helping to plan all of this! I think he is going to be really surprised!
2303

Figure 23C


Portable Multifunction Device 100
Current Time
Alex
Tina
Maybe we can have a surprise party for him!! ☺
(thumbs up) Love it. Good idea!
Hey guys, remember we should keep this looooww...
Ok!
But I don't know what should we get him this year
2303
Get well
Thank you
condolences
CONGRATS!!!
Rotate to begin writing
2351

Figure 23D


Portable Multifunction Device 100
Done
2309
keyboard icon
CONGRATS!!!
Some text
2308

Figure 23E



Figure 23F


Portable Multifunction Device 100
2312
Done
2309
keyboard icon
CONGRATS!!!
thank you

Figure 23G


Portable Multifunction Device 100
2312
Label
Done
Thank you
2309
keyboard icon
CONGRATS!!!
Some text

Figure 23H

Portable Multifunction Device 100
2312
Label
Done
Thank you
2309
CONGRATS!!!
keyboard icon
Some text

Figure 23I

Portable Multifunction Device 100
2312
Label
Thank you
Done
2309
CONGRATS!!!
keyboard icon

Figure 23J


Portable Multifunction Device 100
2314
Cancel
Save
Thank you
Use this handwriting anytime by typing the label.
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
Space
Return
123
globe
Mic icon
Keyboard icon

Figure 23K


Portable Multifunction Device 100
2314
2316
Cancel
Save
Thank you
Thank you
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
Space
Return
123
globe
Mic icon

Figure 23L


100
2320
2312
2318
Delete
Label: thank you
Thank you
Done
Thank you
2309
Some text
CONGRATS!!!
keyboard icon

Figure 23M

Display of Second Electronic Device 2360
9:41 AM
100%
Tiffany
Sorry to ask for your help on such short notice, hope it wasn't too much trouble.
2322
iMessage
space
return

Figure 23N

Display of Second Electronic Device 2360
9:41 AM
100%
Tiffany
Sorry to ask for your help on such short notice, hope it wasn't too much trouble.
2322
iMessage
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 23O


Display of Second Electronic Device 2360
9:41 AM
100%
Tiffany
Sorry to ask for your help on such short notice, hope it wasn't too much trouble.
2322
iMessage
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 23P


Display of Second Electronic Device 2360
9:41 AM
100%
Tiffany
Sorry to ask for your help on such short notice, hope it wasn't too much trouble.
2324
Message
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 23Q


Display of Second Electronic Device 2360
9:41 AM
100%
Tiffany
Sorry to ask for your help on such short notice, hope it wasn't too much trouble.
No problem, I just dropped off Katie and Emily at school – they loved getting to ride in together.
2324
Thank
iMessage
I
The
I'm
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 23R


Display of Second Electronic Device 2360
9:41 AM
100%
Tiffany
Sorry to ask for your help on such short notice, hope it wasn't too much trouble.
2324
Thank You
iMessage
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 23S


Display of Second Electronic Device 2360
Close-up of 2324
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M

Figure 23T


Display of Second Electronic Device 2360
Close-up of 2324
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M

Figure 23U


Display of Second Electronic Device 2360
Close-up of 2324
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M

Figure 23V


Portable Multifunction Device 100
Current Time
Cancel
Create a handwriting keyboard
a
b
c
Continue
2326

Figure 23W


Portable Multifunction Device 100
Current Time
Cancel
THE QUICK BROWN FOX JUMPS
OVER THE LAZY DOG
2328
The quick brown fox jumps over the
lazy dog.
1234567890
,:?!"/([{<
-~$@#%&*
Tap a set of training characters to begin

Figure 23X


Current Time
Cancel
Save
THE QUICK BROWN FOX JUMPS
OVER THE LAZY DOG
2330
2332
Please Write Larger
Use the entire canvas to write.
You don't need to match the size of the guide letters.
Close
2330
Clear

Figure 23Y


Portable Multifunction Device 100
Current Time
Cancel
Save
THE QUICK BROWN FOX JUMPS
OVER THE LAZY DOG
2330
2332
T
H
Clear
>

Figure 23Z


Portable Multifunction Device 100
Current Time
Cancel
Save
THE QUICK BROWN FOX JUMPS
OVER THE LAZY DOG
2330
2334
2332
2336
T
H
E
Clear
>

Figure 23AA


Portable Multifunction Device 100
Current Time
THE QUICK BROWN FOX
JUMPS OVER THE LAZY DOG
the quick brown fox jumps over the
lazy dog.
1234567890
,:?!"/([{<
-~$@#%&*
You Completed All Handwriting Training Sets
– Enjoy Your New Handwritten Keyboard!
Clear
>

Figure 23AB

Portable Multifunction Device 100
Current Time
<
Alex
Tina
Maybe we can have a surprise party for him!! ☺
(thumbs up) Love it. Good idea!
Hey guys, remember we should keep this looooww...
CONGRATS!!
Ok
Thanks
Talk later
q w e r t y u i o p
a s d f g h j k l
z x c v b n m
123
space
return

Figure 23AC


Portable Multifunction Device 100
Edit
123-456-7890
Recent message 1
234-567-8901
Recent message 2
345-678-9012
Recent message 3
Alex
Tina
Maybe we can have a surprise party for him!! ☺
(thumbs up) Love it. Good idea!
Hey guys, remember we should keep this loooooww...
CONGRATS!!
Delete
Done
Some text
2309

Figure 23AD


Portable Multifunction Device 100
Edit
123-456-7890
Recent message 1
234-567-8901
Recent message 2
345-678-9012
Recent message 3
Alex
Tina
Maybe we can have a surprise party for him!! ☺
(thumbs up) Love it. Good idea!
Hey guys, remember we should keep this loooooww...
CONGRATS!!
Delete
thank you
thank you
Done
my bad...
condolences
goldfish
2351

Figure 23AE


2400
2402
While the electronic device is in a portrait orientation, displaying, on a display of an electronic device, a messaging user interface, the messaging user interface including a virtual keyboard
2404
Detect a change in the orientation of the electronic device from the portrait orientation to a landscape orientation
2406
In response to detecting the change in the orientation: cease to display the virtual keyboard an display, on the display, a handwriting input area that is configured to accept handwritten input from the user of the electronic device
2408
Ceasing to display the virtual keyboard includes ceasing to display a conversation transcript that is included in the messaging user interface while the orientation of the device is in the portrait orientation
A

Figure 24A


2400
A
2410
Receive handwritten inputs at the handwriting input area and, in response, display a preview of the handwritten inputs received at the handwriting input area, the preview including a user interface object in which the handwritten inputs will be displayed within the messaging user interface
2412
While receiving handwritten inputs in the handwriting input area, send instructions to display an indication that the user is currently handwriting a message
2414
While receiving handwritten inputs in the handwriting input area, determine that the handwritten inputs are within a predetermined distance of an edge of the handwriting input area and, in accordance with the determining, while continuing to display at least a portion of the handwritten inputs, shift a displayed portion of the handwriting input area to reveal additional space within the handwriting input area
2416
Receive a modification to at least a portion of the handwritten inputs and, in response, modify the portion of the handwritten inputs and the preview in accordance with the modification

Figure 24B


2400
A
2418
Display, within the handwriting input area, representations of pre-recorded handwritten inputs from the user of the electronic device
2420
Receive a selection of a first pre-recorded handwritten input
2422
Send the first pre-recorded handwritten input to a second device that is associated with another user in the messaging session
2424
Sending the first pre-recorded handwritten input to the second device includes instructing the second device to draw the first pre-recorded handwritten input at a predetermined pace at the second device
2426
Sending the first pre-recorded handwritten input to the second device includes instructing the second device to display the first pre-recorded handwritten input at the second device

Figure 24C


2500
Processing Unit 2508
Displaying Unit 2510
Display Unit 2502
Device Orientation Detecting Unit 2512
Touch-Sensitive Surface Unit 2504
Handwriting Modification Unit 2514
Sending Unit 2516
Sensor Unit(s) 2506
Handwritten Input Selection Unit 2518
Determining Unit 2522
Handwritten Input Area Shifting Unit 2524

Figure 25


2600
2602
Display, on a display of an electronic device: a messaging user interface, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a virtual keyboard, and a message-input area
2604
Receive, at the virtual keyboard, a plurality of typing inputs and, while receiving the plurality of typing inputs, determine whether one or more typing inputs match a stored sequence of characters that is associated with stored handwritten input from the user
2608
The stored sequence of characters corresponds to a label that the user provided for the stored handwritten input
2610
In accordance with a determination that the one or more typing inputs match the stored sequence of characters, display at a first location, proximate to a first set of characters that is displayed within the message-input area, a selectable representation of the stored handwritten input, and the first set of characters is displayed within the message-input area and includes characters that correspond to the one or more typing inputs that match the stored sequence of characters
2612
Detect, via a touch-sensitive surface of the electronic device, a selection of the selectable representation of the stored handwritten input and, in response to detecting the selection of the selectable representation of the stored handwritten input:
(i) ceasing to display the selectable representation of the stored handwritten input at the first location; and
(ii) replacing display, within the message-input area, of the first set of characters that correspond to the one or more typing inputs with display of a representation of the stored handwritten input.
A

Figure 26A


2600
A
2614
After replacing the first set of characters with the representation of the stored handwritten input, the message-input area includes both the representation of the stored handwritten input and at least a first typed input of the plurality of typed inputs
2616
Receive a request to send a message to the at least one other user and, in response:
(i) Display within the conversation transcript a user interface object that includes an animation that draws the stored handwritten input at a predetermined pace; and/ or
(ii) Send instructions to render a user interface object that includes the animation that draws the stored handwritten input at the predetermined pace
2618
The predetermined pace corresponds to a writing pace that was used by the user while providing the stored handwritten input
2620
The predetermined pace corresponds to a writing pace that is different from a pace that was used by the user while providing the handwritten input

Figure 26B


2700
Processing Unit 2708
Displaying Unit 2710
Typing Inputs Receiving Unit 2712
Determining Unit 2714
Detecting Unit 2716
Replacing Unit 2718
Sending Unit 2720
Request Receiving Unit 2722
Display Unit 2702
Touch-Sensitive Surface Unit 2704
Sensor Unit(s) 2706

Figure 27


2800
2802
Detect, via a touch-sensitive surface of an electronic device, a first input and, in response, present on a display of the electronic device, a keyboard preparation user interface
2804
The keyboard preparation user interface includes a first portion that displays the predefined set of training characters including a first emphasized character, and a second portion that displays one or more characters of the predefined set of training characters, the one or more characters included a second emphasized character
2806
Emphasized characters change as the handwritten inputs are received
2808
While presenting the keyboard preparation user interface, receive, via the touch-sensitive surface, handwritten inputs that correspond to a predefined set of training characters
2810
The predefined set of training characters correspond to characters displayed on a QWERTY keyboard
2812
After receiving the handwritten inputs, detect a second input that corresponds to a request to display a messaging user interface that includes a message-input area and a virtual keyboard with a plurality of keys, and a first key of the plurality of keys is associated with a first handwritten input of the received handwritten inputs
2814
The virtual keyboard is a QWERTY keyboard
2816
The virtual keyboard is a user-specific keyboard with keys, each key including a representation of one of the received handwritten inputs
A

Figure 28A


2800
A
2818
In response to detecting the second input, display the messaging user interface; receive, via the touch-sensitive surface, a selection of the first key and, in response to receiving the selection of the first key, output a representation of the first handwritten input within the message-input area
2820
Outputting the representation of the first handwritten input includes rendering the first handwritten input at a pace that was recorded while receiving the first handwritten input

Figure 28B



Table 4

Given two overlapping segments: (6A)
(6B) minus (6C) equals (6D)

```
DIFF = min(NEW_SEGMENT + PREVIOUS_SEGMENT, 1.0) - PREVIOUS_SEGMENT;
```

Table 5

(6E)

```
ALPHA = min(DIFF + PREVIOUS_ALPHA, 1.0);
```

Table 6

Figure 28C



Table 1



Table 7



Table 8

Figure 28D


2900
Processing Unit 2908
Input Detecting Unit 2910
Displaying Unit 2912
Selection Receiving Unit 2914
Handwriting Input Representation Outputting Unit 2916
Handwritten Input Receiving Unit 2918
Display Unit 2902
Touch-Sensitive Surface Unit 2904
Sensor Unit(s) 2906

Figure 29


112
Current Time
Alex
Tina
Want to watch a movie together tonight? Might be fun… ☺☺
3001
Sure!
Which theatre?
Dunno, I'm here right now:
3003
3005
Alex's Location
Gesture 3002
Okay, let me see what's close
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 30A


112
Current Time
Alex
Tina
Hey
What's going?
Want to watch a movie together tonight? Might be fun… ☺☺
3001
Sure!
Which theatre?
3003
Dunno, I'm here right now.
3005
Alex's Location
Gesture 3004
Okay, let me see what's close
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M X
123
space
return

Figure 30B


112
Current Time
Alex
Tina
Text with impact 3009
Want to watch a movie together tonight? Might be fun… ☺☺
3001
3003
Alex's Location
3005
Gesture 3006
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 30C


112
Current Time
Alex
Tina
Image 3011
Text with impact 3009
Want to watch a movie together tonight? Might be fun... ☺☺
3001
3003
Gesture 3008
Alex's Location
3005
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 30D


112
Current Time
Alex
Tina
Image 3011
3009
Text with impact
3001
Want to watch a movie together tonight? Might be fun... ☺☺
3003
Gesture 3010
3005
Alex's Location
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 30E


112
Current Time
Alex
Tina
Image
3011
3009
Text with impact
Want to watch a movie together tonight? Might be fun... ☺☺
3001
3003
Gesture
3012
3005
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 30F


112
Current Time
Alex
Tina
Want to watch a movie together tonight? Might be fun… ☺☺
3001
Sure!
Which theatre?
Dunno, I'm here right now:
3003
3005
Alex's Location
Okay, let me see what's close
Ok
Thanks
Talk later
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return

Figure 30G


3100
3102
Display, on a display of an electronic device, a messaging user interface that includes a plurality of content items. The plurality of content items includes content items having a first content type, the plurality of content items includes content items having a second content type that is distinct from the first content type, and a respective content item in the plurality of content items is displayed with a respective first size;
3104
While displaying the messaging user interface, detect a first input
3106
In response to detecting the first input, reduce a display size of at least some content items having the first content type while continuing to display content items having the second content type with their respective first size
3108
In conjunction with reducing the display size of at least some content items having the first content type, provide haptic feedback
3110
Reducing the display size includes reducing the display size in accordance with a determination that a characteristic of the first input satisfies first display-size-reduction criteria that are associated with the first content type
3112
After reducing the display size of at least some of the content items having the first content type, detect, via a touch-sensitive surface of the electronic device, a second input that corresponds to a request to scroll the messaging user interface and, in response to detecting the second input, scroll the messaging user interface while continuing to display: at least some of the content items having the first content type with the reduced display size, and content items having the second content type with their respective first sizes.
A

Figure 31A


3100
A
3114
Detect a third input and, in response, reduce a display size of content items having the second content type
3116
After reducing display size of the at least some of the content items having the first and second content types, detect a fourth input and, in response, reduce a display size of at least some of the content items having the third content type.
3118
After reducing display size of the at least some of the content items having the first, second, and third content types, detect a fifth input and, in response, reduce a display size of at least some of the content items having the fourth content type
3120
Reducing display size for the at least some content items having each of the first, second, third, and fourth content types is performed based on a hierarchical order assigned to each of the content types
3122
Receive a new input and, in response, revert display size of the at least some content items having the first content type back to the respective first size

Figure 31B


3200
Processing Unit 3208
Displaying Unit 3210
Input Detecting Unit 3212
Display Size Reducing Unit 3214
Haptic Feedback Providing Unit 3216
Display Size Reverting Unit 3218
Display Unit 3202
Touch-Sensitive Surface Unit 3204
Sensor Unit(s) 3206

Figure 32


3300
3302
Display, on a display of an electronic device, a messaging user interface that includes a plurality of content items. The plurality of content items includes content items having a first content type, the plurality of content items includes content items having a second content type that is distinct from the first content type, and a respective content item in the plurality of content items is displayed with a respective first size
3304
While displaying the messaging user interface, detect a first input
3306
In response to detecting the first input: reduce a display size of at least some content items having the first content type, such that a first content item having the first content type is reduced to a respective second size that is smaller than the respective first size by a predefined first display-size-reduction factor and reduce a display size of at least some content items having the second content type, such that a second content item having the second content type is reduced to a respective third size that is smaller than the respective first size by a predefined second display-size-reduction factor, and the predefined second display-size-reduction factor is less than the predefined first display-size-reduction factor
3308
In conjunction with reducing the display size of at least some content items having the first content type, provide haptic feedback
3310
Reducing the display size includes reducing the display size in accordance with a determination that a characteristic of the first input satisfies first display-size-reduction criteria that are associated with the first content type
3312
After reducing the display size of at least some of the content items having the first content type and at least some of the content items having the second content type, detect, via a touch-sensitive surface of the electronic device, a second input that corresponds to a request to scroll the messaging user interface and, in response to detecting the second input, scroll the messaging user interface while maintaining displayed sizes of content items having the first content type a the respective second size and content items having the second content type at the respective third size
A

Figure 33A


3300
A
3314
Detect a third input and, in response, further reduce a display size of content items having the second content type
3316
After reducing display size of the at least some of the content items having the first and second content types, detect a fourth input and, in response, reduce a display size of at least some of the content items having the third content type.
3318
After reducing display size of the at least some of the content items having the first, second, and third content types, detect a fifth input and, in response, reduce a display size of at least some of the content items having the fourth content type
3320
Reducing display size for the at least some content items having each of the first, second, third, and fourth content types is performed based on a hierarchical order assigned to each of the content types
3322
Receive a new input and, in response, revert display size of the at least some content items having the first content type back to the respective first size

Figure 33B


3400
Processing Unit 3408
Displaying Unit 3410
Input Detecting Unit 3412
Display Size Reducing Unit 3414
Haptic Feedback Providing Unit 3416
Display Size Reverting Unit 3218
Display Unit 3402
Touch-Sensitive Surface Unit 3404
Sensor Unit(s) 3406

Figure 34


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
4002
3510
Abe
Pretty slick, connecting a crank to the wheel hub
3503
Will they ship more of them across the pond?
3504
3506
3508
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35A


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3512
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35B


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3505
3518-1
3518-3
3806
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35C


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3518-1
3518-3
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
3512
204
ITD
ITL
ITH
IT0
Intensity of Contact 3512

Figure 35D


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
crank to the wheel hub
Will they ship more of them across the pond?
3502
3518-5
3702
3520
3518-1
3518-3
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
IT0
Intensity of Contact 3512

Figure 35E


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
crank to the wheel hub
Will they ship more of them across the pond?
3502
3518-5
3702
3520
3518-1
3518-3
3522
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35F


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
Abe
Will they ship more of them across the pond?
3518-5
3503
3702
3502
3518-1
3518-3
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35G


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3502
3516
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
3524
204
ITD
ITL
ITH
IT0
Intensity of Contact 3524

Figure 35H


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Will they ship more of them across the pond?
3518-5
3503
3502
3518-1
3518-3
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
3524
204
ITD
ITL
ITH
IT0
Intensity of Contact 3524

Figure 35I


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3502
3518-1
3518-3
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
3526
204

Figure 35J


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
crank to the wheel hub
Will they ship more of them across the pond?
3502
3518-5
3702
3520
3518-1
3518-3
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35K


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
crank to the wheel hub
Will they ship more of them across the pond?
3502
3518-5
3702
3520
3528
3518-1
3518-3
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35L


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Will they ship more of them across the pond?
3502
3518-5
3702
3530
3842
3520
Big hit by Jr.!
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35M


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Will they ship more of them across the pond?
3502
3518-5
3702
3530
3520
Big hit by Jr.!
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3532
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35N


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
them across the pond?
3518-5
3503
3534
Big hit by Jr.!
3702
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35O


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3518-1
3518-3
3516
3538
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
3536-a

Figure 35P


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3518-1
3518-3
3518-6
3516
3518-2
3518-4
3518-7
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
3536-b

Figure 35Q


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3518-1
3518-3
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 3540
204
ITD
ITL
ITH
IT0
Intensity of Contact 3540

Figure 35R


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
3503
3507
3518-2
3518-4
Touch Screen 112
Microphone 113
Accelerometer(s) 3540
204
ITD
ITL
ITH
IT0
Intensity of Contact 3540

Figure 35S


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3518-1
3518-3
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 3540
204
ITD
ITL
ITH
IT0
Intensity of Contact 3540

Figure 35T


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
Abe
Pretty slick, connecting a crank to the wheel hub
3503
3507
3518-2
3518-4
Touch Screen 112
Microphone 113
Accelerometer(s) 3544
204
ITD
ITL
ITH
IT0
Intensity of Contact 3544

Figure 35U


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
crank to the wheel hub
Will they ship more of them across the pond?
3502
3702
3520
3518-4
3518-1
3518-3
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 3544
204
ITD
ITL
ITH
IT0
Intensity of Contact 3544

Figure 35V


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
crank to the wheel hub
Will they ship more of them across the pond?
3502
3702
3520
3518-4
3546
3518-1
3518-3
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35W


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3509
208
402
9:26 AM 404
42%
406
Cancel
Markup
Save
3549
3551
3548-2
3518-4a
3550
3552
3554
T
3556
3558
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35X


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3509
208
402
9:26 AM 404
42%
406
Cancel
Markup
Save
3518-4a
T
3552
Touch Screen 112
Microphone 113
Accelerometer(s) 168
3560
204

Figure 35Y


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3509
208
402
9:26 AM 404
42%
406
Cancel
Markup
Save
3562
3518-4a
T
3552
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35Z


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3509
208
402
9:26 AM 404
42%
406
Cancel
Markup
Save
3518-4a
T
3554
Touch Screen 112
Microphone 113
Accelerometer(s) 168
3564
204

Figure 35AA


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3509
208
402
9:26 AM 404
42%
406
Cancel
Markup
Save
3568
3566
3570
3518-4a
T
3554
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35AB


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3509
208
402
9:26 AM 404
42%
406
Cancel
Markup
Save
3568-a
3572
3566
3518-4a
T
3554
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35AC


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3509
208
402
9:26 AM 404
42%
406
Cancel
Markup
Save
3568-b
3566
3518-4a
T
3554
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35AD


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3509
208
402
9:26 AM 404
42%
406
Cancel
Markup
Save
3566
3570-a
3574
3518-4a
T
3554
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35AE


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3509
208
402
9:26 AM 404
42%
406
Cancel
Markup
Save
3566
3570-b
3518-4a
T
3554
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35AF


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3509
208
402
9:26 AM 404
42%
406
Cancel
Markup
Save
3518-4a
3556
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
3576

Figure 35AG


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3509
208
402
9:26 AM 404
42%
406
Cancel
Markup
Save
3578
Señor Snowman
3518-4a
3556
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35AH


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3509
208
402
9:26 AM 404
42%
406
Cancel
Markup
Save
Señor Snowman
3518-4a
T
3558
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
3580

Figure 35AI


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3509
208
402
9:26 AM 404
42%
406
Cancel
Markup
Save
3582
Señor Snowman
3518-4a
T
3558
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35AJ


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3509
208
402
9:26 AM 404
42%
406
Cancel
Markup
Sa
3551
3586
Señor Snowman
3518-4a
T
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35AK


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
crank to the wheel hub
Will they ship more of them across the pond?
3502
3702
3520
Señor Snowman
3518-4a
3518-1
3518-3
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35AL


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
crank to the wheel hub
Will they ship more of them across the pond?
3502
3702
Señor Snowman
3518-4a
3520
3518-1
3518-3
3588
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35AM


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
Abe
Will they ship more of them across the pond?
3503
Señor Snowman
3518-4a
3702
3518-1
3518-3
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 35AN


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
Abe
Pretty slick, connecting a crank to the wheel hub
3503
3507
3518-2
3518-4
Touch Screen 112
Microphone 113
Accelerometer(s) 3590
204
ITD
ITL
ITH
IT0
Intensity of Contact 3590

Figure 35AO


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Will they ship more of them across the pond?
3518-4
3502
3518-1
3518-3
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 3590
204
ITD
ITL
ITH
IT0
Intensity of Contact 3590

Figure 35AP


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
4002
3510
Abe
Pretty slick, connecting a crank to the wheel hub
3503
Will they ship more of them across the pond?
3504
3602
3508
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36A


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:25 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3602
3604
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36B


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:25 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3602
3612
A. Johnson
Jr. nearly hit for the cycle today. I suspect he is not the first, nor the last, to miss by a triple.
3629
Fidelio
6. Er erwacht!
3606
3608
Touch Screen 112
3610
Microphone 113
Accelerometer(s) 168
204

Figure 36C


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:25 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
A. Johnson
Jr. nearly hit for the cycle today. I suspect he is not the first, nor the last, to miss by a triple.
Fidelio
6. Er erwacht!
3606
3614
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36D


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:25 AM 404
42%
406
Abe
crank to the wheel hub
Will they ship more of them across the pond?
3616
3502
3702
3520
Fidelio - Beethoven
6. Er erwacht!
A. Johnson
Jr. nearly hit for the cycle today. I suspect he is not the first, nor the last, to miss by a triple.
Fidelio
6. Er erwacht!
3606
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36E


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:25 AM 404
42%
406
Abe
crank to the wheel hub
Will they ship more of them across the pond?
3616
3502
3702
3520
Fidelio - Beethoven
6. Er erwacht!
A. Johnson
Jr. nearly hit for the cycle today. I suspect he is not the first, nor the last, to miss by a triple.
3618
Fidelio
6. Er erwacht!
3606
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36F


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Will they ship more of them across the pond?
3616
3620
3503
Fidelio - Beethoven
6. Er erwacht!
3702
3502
A. Johnson
Jr. nearly hit for the cycle today. I suspect he is not the first, nor the last, to miss by a triple.
Fidelio
6. Er erwacht!
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36G


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:25 AM 404
42%
406
3511
Andrew
indoubitably
Without question
Have you seen the new dandy horse with petals?
3503
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36H


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Andrew
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3616
3620
Fidelio - Beethoven
6. Er erwacht!
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36I


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Andrew
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3616
3620
Fidelio - Be
en
6. Er erwacht!
3622
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36J


206
Portable Multifunction Device 100-2
3624
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Andrew
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3616
Fidelio - Beethoven
6. Er erwacht!
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36K


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Will they ship more of them across the pond?
Fidelio - Beethoven
6. Er erwacht!
3502
A. Johnson
Jr. nearly hit for
suspect he is not the first, nor the last, to miss by a
3628
Fidelio
6. Er erwacht!
3608
Touch Screen 112
3610-a
Microphone 113
Accelerometer(s) 168
204
3626-a

Figure 36L


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Will they ship more of them across the pond?
Fidelio - Beethoven
6. Er erwacht!
3502
3630
Washington Gazette
Viroqua, Wisconsin – Residents reported a giant fireball in the sky three days ago. Local authorities have now recovered pieces of a meteorite they are calling the "Claywater Meteorite"
3629
3610-b
Touch Screen 112
3608-b
Microphone 113
3628
Accelerometer(s) 168
3626-b
204

Figure 36M


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
Abe
Will they ship more of them across the pond?
Fidelio - Beethoven
6. Er erwacht!
3502
Washington Gazette
Viroqua, Wisconsin – Residents reported a giant fireball in the sky three days ag
authorities ha
recovered pie
meteorite they
the "Claywater Meteorite"
3628
Touch Screen 112
Microphone 113
3628
Accelerometer(s) 168
204
3632
ITD
ITL
ITH
IT0
Intensity of Contact 3632

Figure 36N


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
Abe
Fidelio - Beethoven
6. Er erwacht!
3634
3503
Washington Gazette
Fireball in Wisconsin
3502
Washington Gazette
Viroqua, Wisconsin –
Residents reported a
giant fireball in the sky
three days ag
authorities ha
recovered pie
meteorite they
the "Claywater Meteorite"
3628
Touch Screen 112
Microphone 113
3628
Accelerometer(s) 168
204
3632
ITD
ITL
ITH
IT0
Intensity of Contact 3632

Figure 36O


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Fidelio - Beethoven
6. Er erwacht!
3634
Washington Gazette
Fireball in Wisconsin
3502
3636
Washington Gazette
Viroqua, Wisconsin – Residents reported a giant fireball in the sky three days ago. Local authorities have now recovered pieces of a meteorite they are calling the "Claywater Meteorite"
3628
Touch Screen 112
Microphone 113
3628
Accelerometer(s) 168
204

Figure 36P


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
Abe
3638
Washington Gazette
Viroqua, Wisconsin – Residents reported a giant fireball in the sky three days ago. Local authorities have now recovered pieces of a meteorite they are calling the "Claywater Meteorite," weighing nearly three pounds in aggregate. Fortunately, no injuries or property damage were reported as a result of the meteorite strike. According to geologist, Dr. Ferdinand Vandeveer Hayden, the meteorite likely broke off of an asteroid from the belt between
3634
3503
3502
3629
meteorite they are calling the "Claywater Meteorite"
Touch Screen 112
Microphone 113
3628
Accelerometer(s) 168
204

Figure 36Q


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
3638
Washington Gazette
Viroqua, Wisconsin – Residents reported a giant fireball in the sky three days ago. Local authorities have now recovered pieces of a meteorite they are calling the "Claywater Meteorite," weighing nearly three pounds in aggregate. Fortunately, no injuries or property damage were reported as a result of the meteorite strike. According to geologist Dr. Ferdinand Vandeveer Hayden, the meteorite likely broke off of an asteroid from the belt between
3634
3503
3502
3642
meteorite they are calling the "Claywater Meteorite"
3640-a
Touch Screen 112
Microphone 113
3628
Accelerometer(s) 168
204

Figure 36R


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
3638
hree days ago. Local authorities have now recovered pieces of a meteorite they are calling the "Claywater Meteorite," weighing nearly three pounds in aggregate. Fortunately, no injuries or property damage were reported as a result of the m orite strike. According to geol Dr. Ferdinand Vandeveer Hayd he meteorite likely broke off of an a teroid from the belt located betwee the orbits of Mars and Jupiter. "It is a relatively common occurrence that meteorites enter Earth's atmosphere. Usually, however, the meteorite completely
3634
3502
son
meteorite they are calling the "Claywater Meteorite"
3640-b
Touch Screen 112
Microphone 113
3628
Accelerometer(s) 168
204

Figure 36S


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:25 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3612
A. Johnson
Jr. nearly hit for the cycle today. I suspect he is not the first, nor the last, to miss by a triple.
3644
Fidelio
6. Er erwacht!
3606
3608
Touch Screen 112
3610
Microphone 113
Accelerometer(s) 168
204

Figure 36T


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:25 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3602
3646
Meteorite
3612
3604
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36U


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:25 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3646
Meteorite
3612
ashington Gazette
Viroqua, Wisconsin – Residents reported a giant fireball in the sky three days ago. Local authorities have now recovered pieces of a meteorite they are calling the "Claywater Meteorite"
Meteorite
WikiSpace – Out of
Meteorites are al referred to as fall stars or shooting
A meteorite is a sc piece of debris from
3629
3628
3648
3650
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36V


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
3503
Will they ship more of them across the pond?
3504
3506
3508
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36W


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3508
3502
3652
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36X


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3508
3502
App Store 3601
Tic-tac-toe 3603
Reservations 3605
Search 3607
Stickers 3609
Periscope 3611
Pizza 3613
Music 3615
3627
3654
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36Y


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3502
App Store 3601
Tic-tac-toe 3603
Reservations 3605
Search 3607
3656
3627
Stickers 3609
Periscope 3611
Pizza 3613
Music 3615
3654
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36Z


206
Portable Multifunction Device 100
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3658
208
208
402
9:26 AM 404
42%
406
Abe
3660
My Location
Currently Viewing
Currently List
123 Main Street
Fireball in Wisconsin
Washington Gazette
Beethoven: Fidelio
James Monroe, John
3662
3664
3666
Recently Shared
Show More
Mungo Park Wins Open
British Daily
Pigs in Space – Trailer 1
YouVideo
3668
3670
3672
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36AA


206
Portable Multifunction Device 100
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3658
208
208
402
9:26 AM 404
42%
406
Abe
3660
My Location
Currently Viewing
Currently List
123 Main Street
Fireball in Wisconsin
Washington Gazette
Beethoven: Fidelio
James Monroe, John
3662
3664
3666
Recently Shared
Show More
Mungo Park Wins Open
British Daily
Pigs in Space Trailer 1
YouVideo
3668
3670
3672
3674
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36AB


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Will they ship more of them across the pond?
3670
3503
Pigs in Space – Trailer 1
YouVideo
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36AC


206
Portable Multifunction Device 100
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3658
208
208
402
9:26 AM 404
42%
406
Abe
3660
My Location
Currently Viewing
Currently List
3676
123 Main Street
3662
Fireball in Wisconsin
Washington Gazette
3664
Beethoven: Fidelio
James Monroe, John
3666
Recently Shared
Show More
Mungo Park Wins Open
British Daily
3668
Pigs in Space – Trailer 1
YouVideo
3670
3672
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36AD


206
Portable Multifunction Device 100
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3659
208
208
402
9:26 AM 404
42%
406
Abe
3660
Trending
3678
Bach: Cantatas - BWV 20...
Abraham Lincoln, George Wa...
3680
Beethoven: Pastoral-Sinf...
Andrew Jackson, Martin Van ...
3668
Mungo Park Wins Open
British Daily
3669
Walt Bond blanks Caps
Baltimore Press
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36AE


206
Portable Multifunction Device 100
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3661
208
208
402
9:26 AM 404
42%
406
Abe
3660
Meteorites
All
Image
Music
Video
Sticker
3617
3619
3621
3623
3625
Fireball in Wisconsin
Washington Gazette
3664
Meteorite Shower Today
Trenton Press
3678
Most Meteorit
Science Today
3680
Blow-up the Meteorite – ...
YouVideo
3670
Riding a Meteorite Hom...
iTunes Movie Trailers
3682
The Meteorite
MoviePreviews
3684
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36AF


206
Portable Multifunction Device 100
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3661
208
208
402
9:26 AM 404
42%
406
Abe
3660
Meteorites
All
Image
Music
Video
Sticker
Fireball in Wisconsin
Washington Gazette
3664
Meteorite Shower Today
Trenton Press
3678
Most Meteorit
Science Today
3680
Blow-up the Meteorite – ...
YouVideo
3670
3688
Riding a Meteorite Hom...
iTunes Movie Trailers
3682
The Meteorite
MoviePreviews
3684
3686-a
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36AG


206
Portable Multifunction Device 100
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3661
208
208
402
9:26 AM 404
42%
406
Abe
3660
Meteorites
All
Image
Music
Video
Sticker
Fireball in Wisconsin
Washington Gazette
Meteorite Shower Today
Trenton Press
Most Meteorit
Science Today
3664
3678
3680
Riding a Meteorite Hom...
iTunes Movie Trailers
The Meteorite Catcher – ...
MoviePreviews.com
The Mete
iTunes Mo
3682
3684
3688
3670
3686-b
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36AH


206
Portable Multifunction Device 100
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3661
208
208
402
9:26 AM 404
42%
406
Abe
3660
Meteorites
All
Image
Music
Video
Sticker
Fireball in Wisconsin
Washington Gazette
3664
Meteorite Shower Today
Trenton Press
3678
Most Meteorit
Science Today
3680
Riding a Meteorite Hom...
iTunes Movie Trailers
3682
The Meteorite C...
MoviePreviews.co
3684
The Mete
iTunes M
3688
3670
3690
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36AI


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Will they ship more of them across the pond?
3694
3684
The Meteorite Catcher – ...
MoviePreviews.com
3692
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36AJ


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Will they ship more of them across the pond?
3694
3684
The Meteorite Catcher – ...
MoviePreviews.com
3502
3520
3692
3696
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36AK


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Will they ship more of them across the pond?
3684
3503
The Meteorite Catcher – T...
MoviePreviews.com
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 36AL


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Will they ship more of them across the pond?
3684
3700
The Meteorite Catcher – MoviePreviews.com
3502
3702
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37A


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Will they ship more of them across the pond?
3684
3700
The Meteorite Catcher – MoviePreviews.com
3502
3702
3704
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37B


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Will they ship more of them across the pond?
3684
3700
The Meteorite Catcher – MoviePreviews.com
3502
3504
3506
3508
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37C


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Will they ship more of them across the pond?
3684
3700
The Meteorite Catcher – MoviePreviews.com
3502
3508
3706
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37D


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
Abe
Will they ship more of them across the pond?
3684
3700
The Meteorite Catcher – MoviePreviews.com
3502
3508
Reservations
3892
3627
A table when you need it
3708
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37E


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
Abe
Will they ship more of them across the pond?
3684
3700
The Meteorite Catcher – MoviePreviews.com
3502
3508
Reservations
3627
3710
A table when you need it
3708
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37F


206
Portable Multifunction Device 100
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3712
208
208
402
9:26 AM 404
42%
406
3510
Abe
3714
3718-1
3718
Map
Current Location
Filter
3720
Table for 2, tonight at 7:00 PM
3722-1
All Restaurants
3722-2
Joe's Bistro
3724-1
3724-2
3724-3
6:45 PM
7:00 PM
7:15 PM
The Cavalry Club
3508
3716
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37G


206
Portable Multifunction Device 100
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3712
208
208
402
9:27 AM 404
42%
406
3510
Abe
3714
3718-1
3718-2
Map
Current Location
Filter
3720
Table for 2, tonight at 7:00 PM
3722-1
All Restaurants
3722-2
Joe's Bistro
3724-1
3724-2
3724-3
7:00 PM
7:15 PM
The Cavalry Club
3508
3726
3716
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37H


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:27 AM 404
42%
406
Abe
3684
The Meteorite Catcher – T...
MoviePreviews.com
3728
Joe's Bistro
American Fare
6:45 PM
2 people
3700
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37I


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3511
Andrew
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3700
3684
The Meteorite Catcher – T...
MoviePreviews.com
3504
3506
3508
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37J


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:27 PM 404
42%
406
Andrew
crank to the wheel hub
Will they ship more of them across the pond?
3700
3684
The Meteorite Catcher – T...
MoviePreviews.com
3730
3728
Joe's Bistro
American Fare
6:45 PM
2 people
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37K


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:27 PM 404
42%
406
Andrew
crank to the wheel hub
Will they ship more of them across the pond?
3700
3684
The Meteorite Catcher – T...
MoviePreviews.com
3728
Joe's Bistro
American Fare
6:45 PM
2 people
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
3732

Figure 37L


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:27 AM 404
42%
406
Andrew
3684
The Meteorite Catcher – T...
MoviePreviews.com
3728
3700
Joe's Bistro
American Fare
3702
2 people
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37M


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:28 AM 404
42% 406
Andrew
3684
The Meteorite Catcher – T...
MoviePreviews.com
3728
3700
Joe's Bistro
American Fare
6:45 PM
2 people
3502
I have a meeting at 6:30.
Q W E R T Y U I O P
A S D F G H J K L
3734
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37N


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:28 AM 404
42%
406
Andrew
The Meteorite Catcher – T...
MoviePreviews.com
3684
3728
Joe's Bistro
American Fare
6:45 PM
2 people
3700
3736
I have a meeting at 6:30.
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37O


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:28 AM 404
42%
406
Andrew
The Meteorite Catcher – T...
MoviePreviews.com
3684
3728-a
Joe's Bistro
American Fa
6:45 PM
2 people
3700
3736
I have a meeting at 6:30.
3738
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37P


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3712
208
208
402
9:28 AM 404
42% 406
3511
Andrew
3714
Joe's Bistro
American Fare
6:45 PM
3740-1
2 people
3740-2
Pick a different restaurant
3742
3508
3716
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37Q


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3712
208
208
402
9:28 AM 404
42%
406
Andrew
3714
Joe's Bistro
American Fare
6:45 PM
3740-1
2 people
3740-2
Pick a different restaurant
3742
3508
3716
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
3744

Figure 37R


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3712
208
208
402
9:28 AM 404
42%
406
Andrew
3714
Joe's Bistro
American Fare
3508
3716
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37S


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3712
208
208
402
9:28 AM 404
42%
406
Andrew
3714
Joe's Bistro
American Fare
3508
3746
3716
How about 8:00?
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37T


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3712
208
208
402
9:29 AM 404
42%
406
Andrew
3714
Joe's Bistro
American Fare
3508
3746
3520
6
How about 8:00?
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3748
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37U


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3712
208
208
402
9:29 AM 404
42% 406
Andrew
3714
Joe's Bistro
American Fare
6:45 PM
3740-1
2 people
3740-2
Pick a different restaurant
3742
3508
3716
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37V


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3712
208
208
402
9:30 AM 404
42% 406
Andrew
3714
8:00 works for me. See you then!
3750
Joe's Bistro
American Fare
6:45 PM
3740-1
2 people
3740-2
Pick a different restaurant
3742
3508
3716
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37W


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3712
208
208
402
9:30 AM 404
42% 406
Andrew
3714
Joe's Bistro
American Fare
PM
3740-1
2 people
3740-2
Pick a different restaurant
3752
3742
3508
3716
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37X


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3712
208
208
402
9:30 AM 404
42% 406
Andrew
3714
Joe's Bistro
American Fare
6:45 PM
7:00 PM
7:15 PM
7:30 PM
7:45 PM
8:00 PM
3740-1
3508
3716
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37Y


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3712
208
208
402
9:30 AM 404
42%
406
Andrew
3714
Joe's Bistro
American Fare
6:45 PM
7:00 PM
7:15 PM
7:30 PM
7:45 PM
PM
3740-1
3508
3754
3716
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37Z


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3712
208
208
402
9:30 AM 404
42% 406
Andrew
3714
Joe's Bistro
American Fare
8:00 PM
3740-1
2 people
3740-2
Pick a different restaurant
3742
3508
3716
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AA


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3712
208
208
402
9:31 AM 404
42% 406
Andrew
3714
3756
Joe's Bistro
American Fare
8:00 PM
3740-1
2 people
3740-2
Pick a different restaurant
3742
3508
3716
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AB


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:31 AM 404
42%
406
Andrew
3684
The Meteorite Catcher – T...
MoviePreviews.com
Reservation suggested for 6:45 PM today
3756
I have a meeting at 6:30.
3736
How about 8:00?
3746
3700
3750
8:00 works for me. See you then!
3728-b
Joe's Bistro
American Fare
8:00 PM
2 people
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AC


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:28 AM 404
42%
406
Abe
Will they ship more of them across the pond?
3700
3684
The Meteorite Catcher – T...
MoviePreviews.com
3728
Joe's Bistro
American Fare
6:45 PM
2 people
3736
I have a meeting at 6:30.
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AD


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:29 AM 404
42%
406
Abe
them across the pond?
3684
The Meteorite Catcher – T...
MoviePreviews.com
3700
3728
Joe's Bistro
American Fare
6:45 PM
2 people
3736
I have a meeting at 6:30.
3746
How about 8:00?
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AE


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:29 AM 404
42%
406
Abe
them across the pond?
3684
The Meteorite Catcher – T...
MoviePreviews.com
3700
3728
Joe's Bistro
American Fare
6:45 PM
2 people
3736
I have a meeting at 6:30.
3746
How about 8:00?
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
3758

Figure 37AF


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:29 AM 404
42% 406
Abe
3728
Joe's Bistro
American Fare
6:45 PM
2 people
3736
I have a meeting at 6:30.
3746
How about 8:00?
3700
3702
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AG


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:29 AM 404
42% 406
Abe
3728
Joe's Bistro
American Fare
6:45 PM
2 people
3736
I have a meeting at 6:30.
3746
How about 8:00?
3700
3702
3502
8:00 works for me. See you then!
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AH


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:30 AM 404
42%
406
Abe
3728
Joe's Bistro
American Fare
6:45 PM
2 people
3736
I have a meeting at 6:30.
3746
How about 8:00?
3700
3702
3502
8:00 works for me. See you then!
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3760
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AI


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:30 AM 404
42%
406
Abe
6:45 PM
2 people
3728
3736
I have a meeting at 6:30.
3746
How about 8:00?
3700
3750
8:00 works for me. See you then!
3762-a
3764
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AJ


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:30 AM 404
42% 406
Abe
3684
The Meteorite Catcher – T...
MoviePreviews.com
3700
3728-a
Joe's Bistro
American Fare
6:45 PM
2 people
3736
I have a meetir g at 6:30.
3746
How about 8:0(?
3750
8:00 works me. See you then!
3504
3506
3502
Touch Screen 112
Microphone 113
3762-b
Accelerometer(s) 168
204

Figure 37AK


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:31 AM 404
42%
406
Abe
3684
The Meteorite Catcher – T...
MoviePreviews.com
Reservation suggested for 6:45 PM today
3756
3736
I have a meeting at 6:30.
3746
How about 8:00?
3700
3750
8:00 works for me. See you then!
3728-b
Joe's Bistro
American Fare
8:00 PM
2 people
3504
3506
3508
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AL


206
Portable Multifunction Device 100
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3712
208
208
402
9:26 AM 404
42%
406
3510
3714
3718-1
3718
Map
Current Location
Filter
3720
Table for 2, to 3799 at 7:00 PM
3722-1
All Restaurants
3722-2
Joe's Bistro
3724-1
3724-2
3724-3
6:45 PM
7:00 PM
7:15 PM
The Cavalry Club
3508
3716
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
IT0
Intensity of Contact 3799

Figure 37AM


206
Portable Multifunction Device 100
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3712
208
208
402
9:26 AM 404
42% 406
3510
3714
3718-1
3718
Map
Filter
Call home
Video call home
3799
Message home
Mail home
Digital touch home
Payment
3884-1
3884-2
3722-1
3884-3
3722-2
3884-4
3884-5
3884-6
3882
3724-1
3724-2
3724-3
6:45 PM
7:00 PM
7:15 PM
The Cavalry Club
3508
3716
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
ITO
Intensity of Contact 3799

Figure 37AN


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:31 AM 404
42%
406
Abe
The Meteorite Catcher – T...
MoviePreviews.com
3684
Reservation suggested for 6:45 PM today
3756
3736
I have a meeting at 6:30.
3746
How about 8:00?
3700
3750
8:00 works for me. See you then!
3728
Joe's Bistro
American Fare
8:00 PM
2 people
3504
3506
3508
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
3768

Figure 37AO


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:31 AM 404
42% 406
Abe
3746
3750
8:00 works for me. See you then!
3728
Joe's Bistro
American Fare
8:00 PM
2 p
3700
3508
3502
Reservations
3892
3627
A table when you need it
3708
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AP


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:31 AM 404
42% 406
Abe
3746
3750
8:00 works for me. See you then!
3728
Joe's Bistro
American Fare
8:00 PM
2 p
3700
3508
3502
Reservations
3892
3772
3627
A table when you need it
3708
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
3770-a

Figure 37AQ


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:31 AM 404
42%
406
Abe
3746
3750
8:00 works for me. See you then!
3728
Joe's Bistro
American Fare
8:00 PM
2 p
3700
3508
3502
rvations
Tic-
3892
3627
Nought or cross
you need it
3708
Touch Screen 112
3774
Microphone 113
Accelerometer(s) 168
3770-b

Figure 37AR


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:31 AM 404
42%
406
Abe
3746
3750
8:00 works for me. See you then!
3728
Joe's Bistro
American Fare
8:00 PM
2 p
3700
3508
3502
Tic-tac-toe
X
O
3892
3627
Nought or cross your way to victory
3774
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AS


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:32 AM 404
42% 406
Abe
3746
3750
8:00 works for me. See you then!
3728
Joe's Bistro
American Fare
8:00 PM
2 p
3700
3508
3502
Tic-tac-toe
X
O
3892
3627
ought or cross your way to victory
3774
3776
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AT


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:32 AM 404
42%
406
Abe
3746
3750
8:00 works for me. See you then!
3728
Joe's Bistro
American Fare
8:00 PM
2 p
3508
3502
3700
Tic-tac-toe
X
3694
Play as O
3780-1
Play as X
3780-2
3778
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AU


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:32 AM 404
42%
406
Abe
3746
3750
8:00 works for me. See you then!
3728
Joe's Bistro
American Fare
8:00 PM
3700
3508
3502
Tic-tac-toe
X
3694
Play as O
3780-1
Play as X
3780-2
3782
3778
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AV


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:33 AM 404
42% 406
Abe
3736
I have a meeting at 6:30.
3746
Hov
3694
Abe
3750
en!
3728
3791
Joe's
Ameri
8:00 PM
3700
3786
X
It's your turn, O!
3716
3784
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AW


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:34 AM 404
42% 406
Abe
3736
I have a meeting at 6:30.
3746
Hov
3694
Abe
3750
en!
3728
3791
Joe's
Ameri
8:00 PM
3700
3786
X
It's your turn, O!
3788
3716
3784
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AX


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:34 AM 404
42% 406
Abe
3746
How
3694
Abe
3750
en!
3728
Joe's
Ameri
8:00 PM
3792
3791
3700
3786-a
X
Waiting for opponent
3716
oe
3790-a
3782
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AY


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:35 AM 404
42% 406
Abe
3746
How about 8:00?
3750
3694
Abe
3728
3794
3792
3791
3700
3796
3790-b
3786-b
It's your turn, O!
3716
Your turn
3782
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37AZ


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:36 AM 404
42% 406
Abe
3750
3728
3694
Abe
3798
I've got you now!
3794
X
3792
O
3791
It's your turn, O!
3716
3796
3786-b
3790-b
3700
3798
I've
3782
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BA


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:37 AM 404
42% 406
Abe
3750
3728
3694
Abe
Joe's
Ameri
8:00 PM
3701
3794
X
3796
3792
3790-b
3786-b
O
3791
3700
Your tu
It's your turn, O!
3716
3798
I've
3782
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BB


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:37 AM 404
42%
406
Abe
3750
3728
Joe's Bistro
American Fare
8:00 PM
2 people
3796
You played Tic-tac-toe
3790-b
Your opponent played Tic-tac-toe
3786-b
X
O
3700
Your turn
3798
I've got you now!
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BC


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:31 AM 404
42%
406
Andrew
3684
The Meteorite Catcher – T...
MoviePreviews.com
Reservation suggested for 6:45 PM today
3756
I have a meeting at 6:30.
3736
How about 8:00?
3746
3700
3750
8:00 works for me. See you then!
3728-b
Joe's Bistro
American Fare
8:00 PM
2 people
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BD


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:32 AM 404
42%
406
Andrew
The Meteorite Catcher – T...
MoviePreviews.com
Reservation suggested for 6:45 PM today
3756
I have a meeting at 6:30.
3736
3700
How about 8:00?
3746
3750
8:00 works for me. See you then!
3728-b
Joe's Bistro
American Fare
8:00 PM
2 people
3703
3793
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BE


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:34 AM 404
42%
406
Andrew
How about 8:00?
3746
3750
8:00 works for me. See you then!
3700
3728-b
Joe's Bistro
American Fare
8:00 PM
2 people
3703
Your opponent played Tic-tac-toe
3705-a
X
O
3795
Tap to download
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BF


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:34 AM 404
42%
406
Andrew
How about 8:00?
3746
3750
8:00 works for me. See you then!
3700
3728-b
Joe's Bistro
American Fare
8:00 PM
2 people
3703
Your opponent played Tic-tac-toe
3705-a
X
Tap to download
3707
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BG


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:34 AM 404
42%
406
Andrew
How about 8:00?
3746
3750
8:00 works for me. See you then!
3700
3728-b
Joe's Bistro
American Fare
8:00 PM
2 people
3703
Your opponent played Tic-tac-toe
3705-a
X
3709
Tap to download
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BH


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:34 AM 404
42%
406
Andrew
How about 8:00?
3746
3750
8:00 works for me. See you then!
3728-b
3700
Joe's Bistro
American Fare
8:00 PM
2 people
3703
Your opponent played Tic-tac-toe
3705-a
X
O
Your turn
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BI


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:34 AM 404
42%
406
Andrew
How about 8:00?
3746
3750
8:00 works for me. See you then!
3728-b
3700
Joe's Bistro
American Fare
8:00 PM
2 people
3703
Your opponent played Tic-tac-toe
3705-a
X
Your turn
3711
Microphone 113
Touch Screen 112
Accelerometer(s) 168
204

Figure 37BJ


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:34 AM 404
42% 406
Andrew
3746
3694
Abe
3750
3728-b
3700
3792
3791
3703
3705-a
people
It's your turn, X!
3716
Your turn
3782
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BK


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:35 AM 404
42% 406
Andrew
3746
3694
Abe
3750
3728-b
3700
3792
3791
3703
3705-a
3713
people
It's your turn, X!
3716
Your turn
3782
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BL


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:35 AM 404
42% 406
Andrew
How about 8:00?
3746
3750
3694
Abe
3728-b
3794
3792
3703
3791
people
3715
3705-b
3700
Waiting for opponent
3716
opponent
3782
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BM


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:35 AM 404
42%
406
Andrew
How about 8:00?
3746
3750
3694
Abe
3728-b
3717
3794
X
3792
3703
people
3791
O
3790-a
3705-b
3700
Waiting for opponent
3716
opponent
3782
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BN


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:35 AM 404
42%
406
Andrew
How about 8:00?
3746
3750
8:00 works for me. See you then!
3728-b
Joe's Bistro
American Fare
8:00 PM
2 people
3703
Your opponent played Tic-tac-toe
You played Tic-tac-toe
3790-a
3705-b
X
O
3700
Waiting for oppo
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
3719

Figure 37BO


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:35 AM 404
42%
406
Andrew
Your opponent played Tic-tac-toe
3703
You played Tic-tac-toe
3790-a
X
O
3705-b
3700
3702
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BP


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:36 AM 404
42%
406
Andrew
Your opponent played Tic-tac-toe
3703
You played Tic-tac-toe
3790-a
X
O
3705-b
3700
3702
3502
I've got you now!
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BQ


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:36 AM 404
42%
406
Andrew
Your opponent played Tic-tac-toe
3703
You played Tic-tac-toe
3790-a
X
O
3705-b
3700
3702
3502
I've got you now!
3721
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BR


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:36 AM 404
42%
406
Andrew
X
O
3705-b
Waiting for opponent
3700
I've got you now!
3798
3702
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BS


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:36 AM 404
42%
406
Andrew
X
O
3705-b
Waiting for opponent
3700
I've got you now!
3798
3502
3702
3723
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BT


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:36 AM 404
42%
406
Andrew
X
O
3705-b
Waiting for opponent
3700
I've got you now!
3798
3502
3504
3506
3508
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BU


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:36 AM 404
42%
406
Andrew
X
O
3705-b
Waiting for opponent
3700
I've got you now!
3798
3504
3506
3508
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3725
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BV


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:36 AM 404
42%
406
Andrew
X
O
3705-b
Waiting for opponent
3700
I've got you now!
3798
3504
3506
3508
3502
Tic-tac-toe
X
O
3892
3627
Nought or cross your way to victory
3774
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BW


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:36 AM 404
42%
406
Andrew
X
O
3705-b
Waiting for opponent
3700
3798
I've got you now!
3502
3504
3506
3508
Tic-tac-toe
X
O
3892
3627
Nought or cross your way to victory
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
3727

Figure 37BX


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:36 AM 404
42% 406
Andrew
X
O
3705-b
Waiting for opponent
3700
I've got you now!
3798
3502
3504
3506
3508
App Store 3601
Tic-tac-toe 3603
Reservations 3605
Search 3607
3627
Stickers 3609
Periscope 3611
Pizza 3613
Music 3615
3654
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37BY


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:37 AM 404
42%
406
Andrew
X
O
3705-b
Waiting for opponent
3700
I've got you now!
3798
3502
3504
3506
3508
App Store 3601
Tic-tac-toe 3603
Reservations 3605
Search 3607
3627
Stickers 3609
Periscope 3611
3613
Music 3615
3654
Touch Screen 112
Microphone 113
3729
Accelerometer(s) 168
204

Figure 37BZ


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:37 AM 404
42%
406
Andrew
Waiting for opponent
I've got you now!
3798
3735
3700
You started ordering a pizza
Pizza Builder
3694
Add Toppings
3733-1
Remove Toppings
3733-2
Order Pizza
3733-3
3731
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CA


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:37 AM 404
42%
406
Andrew
Waiting for opponent
I've got you now!
3798
3735
3700
You started ordering a pizza
Pizza Builder
3694
d Toppings
3733-1
Remove Toppings
3733-2
3737
Order Pizza
3733-3
3731
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CB


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:37 AM 404
42%
406
Andrew
Waiting for opponent
I've got you now!
3798
3735
3700
You started ordering a pizza
Pizza Builder
3694
Pepperoni
Mushrooms
Sausage
Bacon
Extra Cheese
Olives
Green peppers
3733-1
3731
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CC


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:38 AM 404
42%
406
Andrew
Waiting for opponent
I've got you now!
3798
3735
3700
You started ordering a pizza
Pizza Builder
3694
peroni
hrooms
Sausage
Bacon
ExtraCheese
Olives
Green peppers
3733-1
3739
3731
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CD


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:38 AM 404
42% 406
Andrew
Waiting for opponent
I've got you now!
3798
3735-a
3700
You added pepperoni
Pizza Builder
X
3694
Add Toppings
3733-1
Remove Toppings
3733-2
Order Pizza
3733-3
3731
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CE


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:39 AM 404
42%
406
Andrew
3735-b
3700
You added pepperoni
3741
Can we add a vegetable to the pie?
Pizza Builder
3694
Add Toppings
3733-1
Remove Toppings
3733-2
Order Pizza
3733-3
3731
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CF


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:39 AM 404
42% 406
Andrew
3735-b
3700
You added pepperoni
3741
Can we add a vegetable to the pie?
Pizza Builder
3694
Add Toppings
3743
3733-1
Remove Toppings
3733-2
Order Pizza
3733-3
3731
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CG


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:39 AM 404
42% 406
Andrew
3735-b
3700
You added pepperoni
3741
Can we add a vegetable to the pie?
3702
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CH


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:40 AM 404
42%
406
Andrew
3735-b
3700
You added pepperoni
3741
Can we add a vegetable to the pie?
3702
3502
How about mushrooms?
Q W E R T Y U I O P
A S D F G H J L
Z X C V B N M
123
space
return
3745
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CI


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:40 AM 404
42% 406
Andrew
3735-b
3700
3741
Can we add a vegetable to
You added pepperoni
How about mushrooms?
3747
3702
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CJ


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:41 AM 404
42% 406
Andrew
3741
Can we add a vegetable t
3735-b
3700
How about mu
3747
You added pepperoni
3749
Sounds good; I'll add to the pizza.
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CK


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:42 AM 404
42% 406
Andrew
3741
Can we add a vegetable t
3735-b
3700
How about mu
3747
Andrew added mushrooms
3749
Sounds good; I'll add to the pizza.
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CL

206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:43 AM 404
42%
406
Andrew
3741
Can we add a vegetable t
3735-b
3700
How about mu
3747
Andrew added mushrooms
3749
Sounds good; I'll add to the pizza.
It's your turn to pay.
Q W E R T Y U I O P
A S D F G H J L
Z X C V B N M
123
space
return
3751
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CM

206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:43 AM 404
42%
406
Andrew
3735-b
3747
How about mu
3749
Sounds good; I'll add to th
Andrew added mushrooms
It's your turn to pay.
3753
3700
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CN

206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:44 AM 404
42%
406
Andrew
3747
How about mushrooms?
3749
Sounds good; I'll add to the pizza.
3700
It's your turn to pay.
3753
3755
Andrew ordered a pizza
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CO

206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:44 AM 404
42%
406
Andrew
3747
How about mushrooms?
3749
Sounds good; I'll add to the pizza.
3700
It's your turn to pay.
3753
3755
Andrew ordered
3757-a
3759
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CP


206
Portable Multifunction Device 100-2
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:44 AM 404
42% 406
Andrew
3798
3735-a
3700
You started building a pizza
3741
Can we add a vegetable to the pie?
How about mushrooms?
3747
3749
Sounds good; I'll add to the pizza.
It's your turn to pay.
3753
3755
Andrew ordered
3502
Touch Screen 112
3757-b
Microphone 113
Accelerometer(s) 168
204

Figure 37CQ


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:37 AM 404
42%
406
Abe
8:00 PM
2 people
You played Tic-tac-toe
3790-b
3796
Your opponent played Tic-tac-toe
3786-b
X
O
Your turn
3798
I've got you now!
3700
3735
Abe wants to share a pizza
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CR


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:38 AM 404
42% 406
Abe
8:00 PM
2 people
3796
You played Tic-tac-toe
3790-b
Your opponent played Tic-tac-toe
3786-b
X
O
Your turn
3798
I've got you now!
3700
3735
3797
Abe added pepperoni
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CS


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:38 AM 404
42% 406
Abe
8:00 PM
2 people
You played Tic-tac-toe
3790-b
3796
Your opponent played Tic-tac-toe
3786-b
X
O
Your turn
3798
I've got you now!
3700
3735
Abe added pepperoni
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
3759

Figure 37CT


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:39 AM 404
42%
406
Abe
3798
I've got you now!
3735
3700
Abe added pepperoni
3502
Can we add a vegetable to the pie?
Q W E R T Y U I O P
A S D F G H J 3761 L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CU


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:39 AM 404
42% 406
Abe
3735
Abe added pepperoni
3700
3741
Can we add a vegetable to the pie?
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CV


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:40 AM 404
42%
406
Abe
3735
3700
3741
add a vegetable to the pie?
Abe added pepperoni
3747
How about mushrooms?
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CW


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:41 AM 404
42%
406
Abe
3735
3700
3741
add a vegetable to the pie?
Abe added pepperoni
3747
How about mushrooms?
3502
Sounds good; I'll add to the pizza.
Q W E R T Y U I O P
A S D F G H J L
Z X C V B N M
123
space
return
3763
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CX

206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:41 AM 404
42%
406
Abe
3735
3741
dd a vegetable to the pie?
3700
3747
mushrooms?
Abe added pepperoni
3749
Sounds good; I'll add to the pizza
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CY

206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:41 AM 404
42%
406
Abe
3735
3741
dd a vegetable to the pie?
3700
3747
mushrooms?
Abe added pepperoni
3749
3765
Sounds good; I'll add to the pizza
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37CZ

206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:41 AM 404
42% 406
Abe
3735
3741
dd a vegetable to the pie?
3700
3747
mushrooms?
Abe added pepperoni
3749
Sounds good; I'll add to the pizza
3502
Pizza Builder
3694
Add Toppings
3733-1
Remove Toppings
3733-2
Order Pizza
3733-3
3731
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37DA


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:41 AM 404
42%
406
Abe
3735
3741
dd a vegetable to the pie?
3700
3747
mushrooms?
Abe added pepperoni
3749
Sounds good; I'll add to the pizza
3502
Pizza Builder
3694
d Toppings
3733-1
Remove Toppings
3733-2
3767
Order Pizza
3733-3
3731
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37DB


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:41 AM 404
42% 406
Abe
3735
3741
dd a vegetable to the pie?
3700
3747
mushrooms?
Abe added pepperoni
3749
Sounds good; I'll add to the pizza
3502
Pizza Builder
3694
Pepperoni
Mushrooms
Sausage
Bacon
ExtraCheese
Olives
Green peppers
3733-1
3731
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37DC


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:42 AM 404
42%
406
Abe
3735
3741
dd a vegetable to the pie?
3700
3747
mushrooms?
Abe added pepperoni
3749
Sounds good; I'll add to the pizza
3502
Pizza Builder
3694
epperoni
shrooms
ausage
Bacon
ExtraCheese
Olives
Green peppers
3733-1
3769
3731
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37DD


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:42 AM 404
42% 406
Abe
3735
3741
dd a vegetable to the pie?
3700
3747
mushrooms?
You added mushrooms
3749
Sounds good; I'll add to the pizza
3502
Pizza Builder
3694
Add Toppings
3733-1
Remove Toppings
3733-2
Order Pizza
3733-3
3731
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37DE

206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:43 AM 404
42% 406
Abe
3735
3741
mushrooms?
3747
3749
good; I'll add to the pizza.
You added mushrooms
3753
It's your turn to pay.
3502
3700
Pizza Builder
3694
Add Toppings
3733-1
Remove Toppings
3733-2
Order Pizza
3733-3
3731
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37DF

206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:43 AM 404
42% 406
Abe
3735
3741
mushrooms?
3747
3749
good; I'll add to the pizza.
You added mushrooms
3753
It's your turn to pay.
3502
3700
Pizza Builder
3694
Add Toppings
3733-1
Remove Toppings
3733-2
der Pizza
3733-3
3731
Touch Screen 112
Microphone 113
Accelerometer(s) 168
3771
204

Figure 37DG


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:43 AM 404
42% 406
Abe
3735
3741
mushrooms?
3747
3749
good; I'll add to the pizza.
You added mushrooms
3753
It's your turn to pay.
3502
3700
Pizza Builder
Payment options
Pay
3773-1
Delivery address
1600 Pennsylva...
3773-2
Place Order
3773-3
3731
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37DH


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:44 AM 404
42% 406
Abe
3735
3741
mushrooms?
3747
3749
good; I'll add to the pizza.
You added mushrooms
3753
It's your turn to pay.
3502
3700
Pizza Builder
Payment options
Pay
3773-1
Delivery address
1600 Pennsylva...
3773-2
3773-3
3731
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
3775

Figure 37DI


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:44 AM 404
42% 406
Abe
3798
3735
3700
Abe started building a pizza
Can we add a vegetable to the pie?
3741
How about mushrooms?
3747
3749
Sounds good; I'll add to the pizza.
3753
It's your turn to pay.
3755
3502
You ordered a pizza
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 37DJ


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
4002
3510
Abe
I agree with you
indoubitably
Without question
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
3503
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 38A


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
I agree with you
indoubitably
Without question
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
3804

Figure 38B


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
3505
3518-1
3518-3
3806
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 38C


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
3518-1
3518-3
3806
3516
3810
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
3808-a

Figure 38D


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
3518-1
3518-3
3518-6
3806
3516
3518-2
3518-4
3518-7
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
3808-b

Figure 38E


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
3518-1
3814
3518-3
3518-6
3806
3516
3812-a
3518-2
3518-4
3518-7
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38F


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
3816
Camera
3818
Photo Library
3806
3518-1
3516
3812-b
3518-2
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38G


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
3816
3818
3820
Photo Library
3806
3518-1
3516
3518-2
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38H


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3822
208
208
402
9:26 AM 404
42%
406
HDR
3514
SLO-MO
VIDEO
PHOTO
SQUARE
PANO
3822
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38I


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3822
208
208
402
9:26 AM 404
42%
406
HDR
3514
SLO-MO
VIDEO
PHOTO
SQUARE
PANO
3822
Touch Screen 112
Microphone 113
3824
Accelerometer(s) 168
204

Figure 38J


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
3510
Abe
crank to the wheel hub
Will they ship more of them across the pond?
3502
3518-5
3702
3520
3518-1
3518-3
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38K


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
3510
Abe
crank to the wheel hub
Will they ship more of them across the pond?
3502
3518-5
3702
3520
3518-1
3518-3
3826
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38L


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
3510
Abe
Will they ship more of them across the pond?
3518-5
3702
3502
3518-1
3518-3
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38M


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
3510
Abe
Will they ship more of them across the pond?
3518-5
3702
3502
3816
Camera
3818
Photo Library
3806
3518-1
3516
3828-b
3518-2
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38N


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Will they ship more of them across the pond?
3518-5
3702
3502
3816
Camera
3818
3518-1
3516
3518-2
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
3830
204

Figure 38O


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3832
208
208
402
9:26 AM 404
42%
406
3836
Photo Library
Cancel
3834-1
Moments
3834-2
Camera Roll
3834-3
Favorites
3834-4
Selfies
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38P


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3832
208
208
402
9:26 AM 404
42%
406
3836
Photo Library
Cancel
3834-1
Moments
3838
3834-2
Camera Roll
3834-3
Favorites
3834-4
Selfies
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38Q


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
3510
Abe
Will they ship more of them across the pond?
3518-5
3504
3506
3508
3502
3840
3518-1
3518-3
3806
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38R


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Will they ship more of them across the pond?
3518-5
3702
3842
3802
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38S


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Will they ship more of them across the pond?
3518-5
3520
3502
3702
Big hit by Jr.!
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38T


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Will they ship more of them across the pond?
3518-5
3520
3502
3702
Big hit by Jr.!
Q W E R T Y U I O P
A S D F G H J 3844 L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38U


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
them across the pond?
3518-5
3503
3846
Big hit by Jr.!
3702
3502
3848
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38V


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
them across the pond?
3518-5
3846
Big hit by Jr.!
3504
3506
3508
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38W


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
them across the pond?
3518-5
3846
Big hit by Jr.!
3504
3506
3508
3502
3850
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38X


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
them across the pond?
3518-5
3846
Big hit by Jr.!
3504
3506
3508
3502
3518-1
3518-3
3806
3516
3518-2
3518-4
3514
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38Y


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
I agree with you
indoubitably
Without question
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 38Z


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
I agree with you
indoubitably
Without question
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
3852

Figure 38AA


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
3858
3856-1
SKETCH
3860-1
HEARTBEAT
3860-2
TAP
3860-3
3854
Microphone 113
Touch Screen 112
Accelerometer(s) 168

Figure 38AB


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
3858
3856-1
3862
SKETCH
3860-1
HEARTBEAT
3860-2
TAP
3860-3
3854
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 38AC


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3702
3842
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38AD


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3702
3842
3502
3864
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38AE


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38AF


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
3866
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38AG


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
3858
3856-1
SKETCH
3860-1
HEARTBEAT
3860-2
TAP
3860-3
3854
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 38AH


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
I agree with you
indoubitably
Without question
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 38AI


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
I agree with you
indoubitably
Without question
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
3868

Figure 38AJ


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
Reservations
3892
3627
A table when you need it
3708
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 38AK


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
Reservations
3892
3627
A table when you need it
Touch Screen 112
Microphone 113
Accelerometer(s) 168
3870

Figure 38AL


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
App Store 3601
Tic-tac-toe 3603
Reservations 3605
Search 3607
Stickers 3609
Periscope 3611
Pizza 3613
Music 3615
3627
3654
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 38AM


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
App Store 3601
Tic-tac-toe 3603
Reservations 3605
Search 3607
3872
3627
Stickers 3609
Periscope 3611
Pizza 3613
Music 3615
3654
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 38AN


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3702
3842
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38AO


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3702
3842
3502
3874
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38AP


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38AQ


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
Q W E R T Y U I O P
3876
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38AR


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3502
App Store 3601
Tic-tac-toe 3603
Reservations 3605
Search 3607
3627
Stickers 3609
Periscope 3611
Pizza 3613
Music 3615
3654
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 38AS


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
I agree with you
indoubitably
Without question
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 38AT


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
I agree with you
indoubitably
Without question
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
3503
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
3878

Figure 38AU


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
3510
Abe
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3702
3842
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38AV


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:44 AM 404
42% 406
3510
Pretty slick, connecting a cra 3880 the wheel hub
3503
Will they ship more of them across the pond?
3702
3842
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38AW


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:44 AM 404
42%
406
3510
Abe
Call home
Video call home
Message home
Mail home
Digital touch home
Payment
3884-1
3884-2
3884-3
3884-4
3884-5
3884-6
3503
3702
3502
3882
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38AX


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:44 AM 404
42%
406
3510
Abe
Call home
Video call home
Message home
Mail home
Digital touch home
Payment
3884-1
3884-2
3884-3
3884-4
3884-5
3884-6
3503
3702
3886
3882
3502
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3501
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38AY


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:44 AM 404
42%
406
3510
Abe
3798
3735
Abe started building a pizza
3700
Can we add a vegetable to the pie?
3741
How about mushrooms?
3747
3749
Sounds good; I'll add to the pizza.
3753
It's your turn to pay.
3755
3502
You ordered a pizza
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 38AZ


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:44 AM 404
42%
406
Abe
3798
3735
Abe started building a pizza
3700
Can we add a vegetable to the pie?
3741
How about mushrooms?
3747
3749
Sounds good; I'll add to the pizza.
3753
It's your turn to pay.
3755
You ordered a pizza
3504
3506
3508
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39A


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:44 AM 404
42%
406
Abe
3798
3735
Abe started building a pizza
3700
Can we add a vegetable to the pie?
3741
How about mushrooms?
3747
3749
Sounds good; I'll add to the pizza.
3753
It's your turn to pay.
3755
You ordered a pizza
3504
3506
3508
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
3902

Figure 39B


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:44 AM 404
42%
406
Abe
How about mushrooms?
3747
Sounds good; I'll add to the pizza.
3749
3753
It's your turn to pay.
3755
You ordered a pizza
3504
3506
3508
3502
Cold Weather Stickers
3892
3906
3908
3910
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39C


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:44 AM 404
42%
406
Abe
How about mushrooms?
3747
3749
Sounds good; I'll add to the pizza.
3753
It's your turn to pay.
3755
You ordered a pizza
3504
3506
3508
3502
Cold Weather Stickers
3906
3908
3910
3627
Winter is approaching
3912
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39D


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:44 AM 404
42% 406
Abe
3747
3749
Sounds good; I'll add to the pizza.
3753
It's your turn to pay.
3755
3502
You ordered a pizza
3702
3842
3520
Cold Weather Stickers
3908
3906
3908
3910
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39E


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:45 AM 404
42% 406
Abe
3747
3749
Sounds good; I'll add to the pizza.
3753
It's your turn to pay.
3755
3502
You ordered a pizza
3702
3842
3520
3908
Cold Weather Stickers
3914
3906
3908
3910
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39F


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:45 AM 404
42%
406
Abe
Sounds good; I'll add to the pizza.
3749
3753
It's your turn to pay.
3755
You ordered a pizza
3908-a
3700
3702
3842
3502
Cold Weather Stickers
3906
3908
3910
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39G


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:45 AM 404
42%
406
Abe
Sounds good; I'll add to the pizza.
3749
3753
It's your turn to pay.
3755
You ordered a pizza
3918
3908-a
3700
3702
3842
3502
Cold Weather Stickers
3906
3908
3910
3627
Winter is approaching
3916-a
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39H


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:46 AM 404
42%
406
Abe
Sounds good; I'll add to the pizza.
3749
3906-b
3753
It's your turn to pay
3755
You ordered a pizza
3908-a
3916-b
3700
3702
3842
3502
Cold Weather Stickers
3908
3910
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39I


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:46 AM 404
42%
406
Abe
Sounds good; I'll add to the pizza.
3749
3906-b
3753
It's your turn to pay
3755
You ordered a pizza
3908-a
3700
3702
3842
3502
Cold Weather Stickers
3906
3908
3910
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39J


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:46 AM 404
42%
406
Abe
Sounds good; I'll add to the pizza.
3749
3906-b
3753
It's your turn to pay.
3755
You ordered a pizza
3908-a
3700
3702
3842
3502
Cold Weather Stickers
3922
3906
3908
3910-a
3627
Winter is approaching
3920-a
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39K


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:46 AM 404
42%
406
Abe
Sounds good; I'll add to the pizza.
3749
3906-b
3753
It's your turn to pay.
3755
You ordered a pizza
3908-a
3700
3702
3842
3502
Cold We ers
3910-b
3920-b
3906
3908
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39L


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:46 AM 404
42%
406
Abe
Sounds good; I'll add to the pizza.
3749
3906-b
3753
It's your turn to pay.
3755
You ordered a pizza
3908-a
3700
3702
3842
3502
Cold Weather Stickers
3627
3906
3908
3910-a
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39M


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:46 AM 404
42%
406
Abe
Sounds good; I'll add to the pizza.
3749
3906-b
3753
It's your turn to pay.
3926
3755
You ordered a pizza
3908-b
3700
3702
3842
3502
Cold Weather Stickers
3906
3908-a
3910-a
3627
Winter is approaching
3924-a
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39N


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:47 AM 404
42% 406
Abe
Sounds good; I'll add to the pizza.
3749
3906-b
3753
It's your turn to pay.
3908-c
3755
You ordered a pizza
3908-b
3924-b
3700
3702
3842
3502
Cold Weather Stickers
3910-a
3627
3906
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39O


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:47 AM 404
42% 406
Abe
Sounds good; I'll add to the pizza.
3749
3906-b
3908-d
3753
It's your turn to pay.
3755
You ordered a pizza
3908-b
3700
3702
3842
3502
Cold Weather Stickers
3906
3908
3910-a
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39P


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:47 AM 404
42% 406
Abe
Sounds good; I'll add to the pizza.
3749
3906-b
3908-d
3753
It's your tu
3930-a
ay.
3755
You ordered a pizza
3908-b
3700
3702
3842
3502
Cold Weather Stickers
3906
3908
3910-a
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39Q


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:47 AM 404
42% 406
Abe
Sounds good; I'll add to the pizza.
3749
3906-b
3908-d
3753
It's your tu
3930-b
ay.
3755
You ordered a pizza
3908-b
3700
3702
3842
3502
Cold Weather Stickers
3906
3908
3910-a
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39R


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:47 AM 404
42% 406
Abe
Sounds good; I'll add to the pizza.
3749
3906-b
3908-d
3753
It's your tu
3930-c
ay.
3755
You ordered a pizza
3908-b
3700
3702
3842
3502
Cold Weather Stickers
3906
3908
3910-a
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39S


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:48 AM 404
42%
406
Abe
Sounds good; I'll add to the pizza.
3749
3906-b
3908-d
3753
It's your tu
3930-b
ay.
3755
You ordered a pizza
3908-b
3700
3702
3842
3502
Cold Weather Stickers
3906
3908
3910-a
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39T


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:48 AM 404
42%
406
Abe
Sounds good; I'll add to the pizza.
3749
3906-b
3908-d
3753
It's your turn to pay.
3755
You ordered a pizza
3908-b
3700
3702
3842
3502
Cold Weather Stickers
3627
3906
3908
3910-a
Winter is approaching
3928
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
IT0
Intensity of Contact 3928

Figure 39U


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:48 AM 404
42%
406
Abe
Sounds good; I'll add to the pizza.
3749
3906-b
3908-d
3753
It's your turn to pay.
3755
You ordered a pizza
3908-b
3700
3702
3842
3502
Cold Weather Stickers
3930-a
3627
3906
3908
3910-a
Winter is approaching
3928
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
IT0
Intensity of Contact 3928

Figure 39V


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:48 AM 404
42%
406
Abe
Sounds good; I'll add to the pizza.
3749
3906-b
3908-d
3753
It's your turn to pay.
3755
You ordered a pizza
3908-b
3700
3702
3842
3502
Cold Weather Stickers
3930-b
3627
3906
3908
3910-a
Winter is approaching
3928
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
IT0
Intensity of Contact 3928

Figure 39W


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:48 AM 404
42%
406
Abe
Sounds good; I'll add to the pizza.
3749
3906-b
3908-d
3753
It's your turn to pay.
3755
You ordered a pizza
3908-b
3700
3702
3842
3502
Cold Weather Stickers
3930-c
3627
3906
3908
3910-a
Winter is approaching
3928
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
IT0
Intensity of Contact 3928

Figure 39X


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:49 AM 404
42%
406
Abe
Sounds good; I'll add to the pizza.
3749
3906-b
3908-d
3753
It's your turn to pay.
3755
You ordered a pizza
3908-b
3700
3702
3842
3502
Cold Weather Stickers
3627
3906
3908
3910-a
Winter is approaching
3932
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
IT0
Intensity of Contact 3928

Figure 39Y


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:49 AM 404
42%
406
Abe
Sounds good; I'll add to the pizza.
3749
3906-b
3908-d
3753
It's your turn to pay.
3755
You ordered a pizza
3908-b
3700
3702
3842
3502
Cold Weather Stickers
3627
3906
3908
3910-a
Winter is approaching
3932
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
IT0
Intensity of Contact 3928

Figure 39Z


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:49 AM 404
42%
406
Abe
3755
3906-b
You ordered a pizza
3908-b
3906-c
3700
3702
3842
3502
Cold Weather Stickers
3627
3906
3908
3910-a
Winter is approaching
3904
3932
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
IT0
Intensity of Contact 3928

Figure 39AA


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:52 AM 404
42%
406
Abe
Can we add a vegetable to the pie?
3741
3747
How about mushrooms?
Sounds good; I'll add to the pizza.
3749
3906-b
3908-d
3753
It's your turn to pay.
3755
You ordered a pizza
3908-b
3700
3906-c
3504
3506
3508
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
3934

Figure 39AB


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:52 AM 404
42%
406
Abe
3755
3906-b
You ordered a pizza
3908-b
3906-c
3700
3504
3506
3508
3502
Reservations
3892
3627
A table when you need it
3708
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 39AC


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:52 AM 404
42% 406
Abe
3755
3906-b
You ordered a pizza
3908-b
3906-c
3700
3504
3506
3508
3502
Reservations
3892
3938
3627
A table when you need it
3708
Touch Screen 112
Microphone 113
Accelerometer(s) 168
3936-a

Figure 39AD


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:52 AM 404
42% 406
Abe
3755
3906-b
You ordered a pizza
3908-b
3906-c
3700
3504
3506
3508
3502
rvations
Cold Wea
3892
3627
3906
390
Winter is
n you need it
3708
Touch Screen 112
3904
Microphone 113
Accelerometer(s) 168
3936-b

Figure 39AE


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:52 AM 404
42% 406
Abe
3755
3906-b
You ordered a pizza
3908-b
3906-c
3700
3504
3506
3508
3502
Cold Weather Stickers
3892
3906
3908
3910-a
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39AF


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:52 AM 404
42% 406
Abe
3755
3906-b
You ordered a pizza
3908-b
3906-c
3700
3504
3506
3508
3502
3942
Cold Weather Stickers
3627
3906-a
3908
3910-a
Winter is approaching
3940-a
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
ITO
Intensity of Contact 3940

Figure 39AG


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:52 AM 404
42%
406
Abe
3755
3906-b
You ordered a pizza
3908-b
3700
3942
3906-c
3504
3508
3502
3906-d
Cold Weather Stickers
3940-b
3908
3910-a
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
IT0
Intensity of Contact 3940

Figure 39AH


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:52 AM 404
42% 406
Abe
3755
You ordered a pizza
3906-b
3908-b
3906-c
3906-e
3940-c
3700
3504
3506
3508
3502
Cold Weather Stickers
3908
3910-a
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
ITO
Intensity of Contact 3940

Figure 39AI


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:53 AM 404
42%
406
Abe
3755
3906-b
You ordered a pizza
3908-b
3906-e
3940-c
3906-c
3700
3504
3506
3508
3502
Cold Weather Stickers
3908
3910-a
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
ITO
Intensity of Contact 3940

Figure 39AJ


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:53 AM 404
42%
406
Abe
3755
3906-b
You ordered a pizza
3908-b
3944
3906-e
3940-c
3906-c
3700
3504
3506
3508
3502
Cold Weather Stickers
3908
3910-a
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
ITO
Intensity of Contact 3940

Figure 39AK


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:53 AM 404
42% 406
Abe
3755
3906-b
You ordered a pizza
3908-b
3944
3906-f
3940-d
3906-c
3700
3504
3506
3508
3502
Cold Weather Stickers
3908
3910-a
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
ITO
Intensity of Contact 3940

Figure 39AL


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:54 AM 404
42%
406
Abe
3755
3906-b
You ordered a pizza
3908-b
3906-f
3906-c
3700
3504
3506
3508
3502
Cold Weather Stickers
3906
3908
3910-a
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
IT0
Intensity of Contact 3940

Figure 39AM


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:54 AM 404
42%
406
Abe
3755
3906-b
You ordered a pizza
3908-b
3906-f
3948
3906-c
3946-a
3700
3504
3506
3508
3502
Cold Weather Stickers
3906
3908
3910-a
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
ITO
Intensity of Contact 3946

Figure 39AN


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:54 AM 404
42%
406
Abe
3755
3906-b
You ordered a pizza
3908-b
3906-g
3906-c
3946-b
3700
3504
3506
3508
3502
Cold Weather Stickers
3906
3908
3910-a
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
IT0
Intensity of Contact 3946

Figure 39AO


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:54 AM 404
42% 406
Abe
3755
You ordered a pizza
3906-b
3908-b
3906-c
3906-g
3946-b
3502
3700
3504
3506
3508
Cold Weather Stickers
3906
3908
3910-a
Winter is approaching
3627
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
IT0
Intensity of Contact 3946

Figure 39AP


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:54 AM 404
42% 406
Abe
3755
You ordered a pizza
3906-b
3908-b
3950
3906-c
3906-g
3946-b
3502
3700
3504
3506
3508
Cold Weather Stickers
3906
3908
3910-a
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
ITO
Intensity of Contact 3946

Figure 39AQ


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:54 AM 404
42%
406
Abe
3755
3906-b
You ordered a pizza
3908-b
3906-h
3950
3906-c
3946-c
3502
3700
3504
3508
Cold Weather Stickers
3906
3908
3910-a
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
IT0
Intensity of Contact 3946

Figure 39AR


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:55 AM 404
42%
406
Abe
3755
3906-b
You ordered a pizza
3908-b
3906-h
3906-c
3700
3504
3502
Cold Weather Stickers
3906
3908
3910-a
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
ITD
ITL
ITH
IT0
Intensity of Contact 3946

Figure 39AS


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:56 AM 404
42%
406
Abe
3755
3906-b
You ordered a pizza
3908-b
3906-i
3906-c
3700
3504
3506
3508
3502
Cold Weather Stickers
3906
3908
3910-a
3627
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39AT


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:58 AM 404
42%
406
Abe
Can we add a vegetable to the pie?
3741
3747
How about mushrooms?
Sounds good; I'll add to the pizza.
3749
3906-b
3908-d
3753
It's your turn to pay.
3755
You ordered a pizza
3908-b
3700
3906-i
3906-c
3504
3506
3508
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204
3952

Figure 39AU


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:58 AM 404
42%
406
Abe
3755
3906-b
You ordered a pizza
3908-b
3906-i
3906-c
3700
3504
3506
3508
3502
App Store 3601
Tic-tac-toe 3603
Reservations 3605
Search 3607
3627
Periscope 3611
Pizza 3613
Music 3615
3654
Touch Screen 112
Microphone 113
Accelerometer(s) 168
3954
204

Figure 39AV


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:58 AM 404
42%
406
Abe
3755
3906-b
You ordered a pizza
3908-b
3906-i
3906-c
3700
3504
3506
3508
3502
Cold Weather Stickers
3627
3906
3908
3910-a
Winter is approaching
3904
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 39AW


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
4002
3510
Abe
I agree with you
indoubitably
Without question
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
3503
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 40A


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
4002
3510
I agree with you
4004
indoubitably
Without question
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
3503
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
ITD
ITL
ITH
IT0
Intensity of Contact 4004

Figure 40B


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
4002
3510
Abe
Call home
Video call home
Message home
Mail home
Digital touch home
Payment
3884-1
3884-2
3884-3
3884-4
3884-5
3884-6
3502
3882
Pretty slick, connecting a crank to the wheel hub
3503
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
ITD
ITL
ITH
IT0
Intensity of Contact 4004

Figure 40C


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
4002
3510
I agree with you
4006
indoubitably
Without question
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
3503
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
ITD
ITL
ITH
IT0
Intensity of Contact 4006

Figure 40D


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
4002
4008
I agree with you
4006
indoubitably
Without question
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
3503
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
ITD
ITL
ITH
IT0
Intensity of Contact 4006

Figure 40E


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
4002
4008
Mary Todd
I agree with you
indoubitably
Without question
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
3503
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
ITD
ITL
ITH
IT0
Intensity of Contact 4006

Figure 40F


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
4002
4008
I agree with you
4010
indoubitably
Without question
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
3503
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
ITD
ITL
ITH
IT0
Intensity of Contact 4010

Figure 40G


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
4002
4008
Call home
Video call home
4010
Message home
Mail home
Digital touch home
Payment
3884-1
3884-2
3884-3
3884-4
3884-5
3884-6
3882
3503
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
ITD
ITL
ITH
IT0
Intensity of Contact 4010

Figure 40H


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
4002
4008
Mary Todd
Call home
Video call home
Message home
Mail home
Digital touch home
Payment
3884-1
3884-2
3884-3
3884-4
3884-5
3884-6
3882
3503
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3802
3602
Touch Screen 112
Microphone 113
Accelerometer(s) 168
ITD
ITL
ITH
IT0
Intensity of Contact 4010

Figure 40I


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
4002
4008
Mary Todd
Call home
Video call home
Message home
Mail home
Digital touch home
Payment
3884-1
3884-2
3884-3
3884-4
3884-5
3884-6
3882
3503
crank to the wheel hub
4012
Will they ship more of them across the pond?
3504
3506
3508
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 40J


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
4002
4008
Mary Todd
I agree with you
X
4016
Mary Todd
Done
4018
pay
$0
For:
1
2
3
4015
4
5
6
7
8
9
.
0
3503
3504
4014
3502
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 40K


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
4002
4008
Mary Todd
I agree with you
X
4016
Mary Todd
Done
4018
pay
$60
For:
4019
4015
1
2
3
4
5
6
7
8
9
.
0
3503
4020
3504
4014
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 40L


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
4002
4008
Mary Todd
I agree with you
X
4016
Mary Todd
Done
4018
pay
$60
For:
4019
4017
3503
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
4014
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 40M


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
4002
4008
Mary Todd
I agree with you
X
4016
Mary Todd
Done
4018
pay
$60
4019
For: Dinner and drinks
4019
4017
3503
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
3504
4014
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 40N


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
4002
4008
Mary Todd
I agree with you
4016
Mary Todd
4018
4022
pay
$60
4019
For: Dinner and drinks
4019
4017
3503
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
4014
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 40O


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
4002
4008
Mary Todd
I agree with you
indubitably
$60
Touch ID
Enter password
Cancel
4024
3503
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 40P


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
4002
4008
Mary Todd
I agree with you
indoubitably
$60
Enter password
Cancel
4024
4026
3503
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 40Q


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
4002
4008
Mary Todd
Without question
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
pay
Andrew paid Mary Todd
$60
Dinner and drinks
4028
3503
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 40R


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42%
406
4002
3510
I agree with you
4030
indoubitably
Without question
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
3503
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
ITD
ITL
ITH
IT0
Intensity of Contact 4030

Figure 40S


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
3510
4008
4032
4034
4036
402
9:26 AM
404
42%
406
Abe
Mary Todd
Chuck
Issac
Edwin
I agree with you
indoubitably
Without question
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
3503
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
ITD
ITL
ITH
ITO
Intensity of Contact 4030

Figure 40T


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
3510
4008
4032
4034
4036
402
9:26 AM
404
42%
406
Abe
Chuck
Issac
Edwin
I agree with you
4038
indoubitably
Without question
Have you seen the new dandy horse with petals?
Pretty slick, connecting a crank to the wheel hub
3503
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
ITD
ITL
ITH
IT0
Intensity of Contact 4038

Figure 40U


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
3510
4008
4032
4034
4036
402
9:26 AM
404
42%
406
Abe
Chuck
Issac
Edwin
Call home
Video call home
4038
Message home
Mail home
Digital touch home
Payment
3884-1
3884-2
3884-3
3884-4
3884-5
3884-6
3882
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
ITD
ITL
ITH
IT0
Intensity of Contact 4038

Figure 40V


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:26 AM 404
42% 406
4002
4008
Mary Todd
Call home
Video call home
Message home
Mail home
Digital touch home
Payment
3884-1
3884-2
3884-3
3884-4
3884-5
3884-6
3882
Pretty slick, connecting a crank to the wheel hub
3508
Will they ship more of them across the pond?
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168
ITD
ITL
ITH
IT0
Intensity of Contact 4038

Figure 40W


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:27 AM 404
42%
406
4002
4008
Mary Todd
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
pay
Andrew paid Mary Todd
$60
Dinner and drinks
3503
We should go see the Meteorite Catcher.
4102
4104
See movie info
4101
3504
3506
3508
3802
3502
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 41A


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:27 AM 404
42%
406
4002
4008
Mary Todd
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
pay
Andrew paid Mary Todd
$60
Dinner and drinks
3503
We should go see the Meteorite Catcher.
4102
4104
info
4106
Microphone 113
Touch Screen 112
Accelerometer(s) 168

Figure 41B


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:28 AM 404
42% 406
4002
4008
Mary Todd
them across the pond?
pay
Andrew paid Mary Todd
$60
Dinner and drinks
We should go see the Meteorite Catcher.
4102
4104
I found The Meteorite Catcher
Directed by
Andromeda Moon
4110
Starring
Astron Omer
Cassiopeia Libra
The Meteorite Catcher
His dreams fell from the sky
4112
Showing nearby
National Mall 14
4108
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 41C


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:28 AM 404
42%
406
4002
4008
Mary Todd
Andrew paid Mary Todd
$60
Dinner and drinks
3503
We should go see the Meteorite Catcher.
4102
4104
I found The Meteorite Catcher
You want to see every movie Astron Omer is in
4114
4116
4103
Directed by
Andromeda Moon
4110
Starring
Astron Omer
Cassiopeia Libra
The Meteorite Catcher
His dreams fell from the sky
Showing nearby
National Mall 14
4112
4108
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 41D


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:28 AM 404
42% 406
4002
4008
Mary Todd
Andrew paid Mary Todd
$60
Dinner and drinks
We should go see the Meteorite Catcher.
4102
4104
I found The Meteorite Catcher
You want to see every movie Astron Omer is in
4114
4116
4103
Directed by
Andromeda Moon
4110
4118
The Meteorite Catcher
His dreams fell from the sky
Starring
Astron Omer
Cassiopeia Libra
4112
Showing nearby
National Mall 14
4108
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 41E


206
Portable Multifunction Device 100
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3661
208
208
402
9:26 AM 404
42%
406
Abe
3660
Astron Omer
4103
All
Movies
News
Websites
Omer says threat is real
Scientists dismiss claim
3664
"Perseids inspired me"
Hollywood tomorrow
3678
Most Meteorit
Science Today
3680
Blow-up the Meteorite – ...
YouVideo
3670
Riding a Meteorite Hom...
iTunes Movie Trailers
3682
The Meteorite
MoviePreviews
3684
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 41F


206
Portable Multifunction Device 100
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3661
208
208
402
9:26 AM 404
42%
406
Abe
3660
Astron Omer
4103
All
Movies
News
Websites
Omer says threat is real
Scientists dismiss claim ...
3664
"Perseids inspired me"
Hollywood tomorrow
3678
Most Meteorit
Science Today
3680
Blow-up th teorite – ...
YouVideo
3670
4120
Riding a Meteorite Hom...
iTunes Movie Trailers
3682
The Meteorite
MoviePreviews
3684
Touch Screen 112
Microphone 113
Accelerometer(s) 168
204

Figure 41G


206
Portable Multifunction Device 100-1
Speaker 111
Optical Sensor 164
Proximity Sensor 166
3500
208
208
402
9:28 AM 404
42%
406
4002
4008
Mary Todd
Andrew paid Mary Todd
$60
Dinner and drinks
3503
We should go see the Meteorite Catcher.
4102
4104
I found The Meteorite Catcher
4114
You want to see every movie Astron Omer is in
4116
4103
3670
Blow-up the Meteorite – ...
YouVideo
Touch Screen 112
Microphone 113
Accelerometer(s) 168

Figure 41H


4202
Display a messaging user interface on a display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a keyboard, a message-input area, and a digital image affordance
4204
While displaying the messaging user interface, detect an input that activates the digital image affordance
4206
In response to detecting the input that activates the digital image affordance, replace display of the keyboard with display of a plurality of digital images, the plurality of digital images including one or more digital images stored in the memory and a live preview image from the digital camera
4208
The one or more digital images stored in the memory, and displayed in response to detecting the input that activates the digital image affordance, consist of digital images captured during the messaging session
4210
Detect an input that selects the live image displayed within the plurality of digital images
4212
In response to detecting that input that selects the live image, capture a digital image with the digital camera, while maintaining display of the conversation transcript
4214
After capturing the digital image: display the digital image captured by the digital camera in the conversation transcript, and transmit a representation of the captured digital image to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the captured digital image in a conversation transcript that corresponds to the messaging session

Figure 42A

4200

4216

Prior to displaying the digital image captured by the digital camera in the conversation transcript and transmitting a representation of the captured image: display the digital image captured by the digital camera in the message input area; while displaying the digital image captured by the digital camera in the message input area, detect an input that activates an image editing mode; in response to detecting the input that activates the image editing mode, replace display of the messaging user interface with display of a digital photo editing user interface, wherein the digital image captured by the digital camera is displayed in the digital photo editing user interface; while displaying the digital photo editing mode, detect an input that edits the digital photo captured by the digital camera; in response to detecting the input that edits the digital photo captured by the digital camera, edit the digital image captured by the digital camera; after editing the digital image captured by the digital camera, detect an input terminating the digital image editing mode; and in response to detecting the input terminating the digital image editing mode, display the edited digital image captured by the digital camera in the message input area

4218

In response to detecting the input that selects the live preview image, and after capturing the digital image, display the digital image in the message-input area; while displaying the digital image in the message-input area, detect input of a message in the message input area; after detecting input of the message in the message-input area, detect an input that corresponds to a request to post contents of the message-input area to the messaging session, the contents including the digital image and the message; and in response to detecting the input that corresponds to the request to post the contents of the message-input area to the messaging session: display the digital image in the conversation transcript, display the message in the conversation transcript, wherein the message partially overlaps the digital image in the conversation transcript, and transmit a representation of the digital image and the message to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the digital image and the message in a conversation transcript corresponding to the messaging session, wherein the message partially overlaps the representation of the digital image in the conversation transcript corresponding to the messaging session

Figure 42B

4200

4220
In response to detecting the input that selects the live image: in accordance with a determination that the input that selects the live image meets one or more input-area-display criteria, display the digital image captured by the digital camera in the message input area, and in accordance with a determination that the input that selects the live image meets one or more transcript-area-display criteria: display the digital image captured by the digital camera in the conversation transcript, and send instructions, to one or more electronic devices that correspond to the at least one other user included in the messaging session, to display the digital image captured by the digital camera in a conversation transcript corresponding to the messaging session

4222
The electronic device includes one or more sensors configured to detect intensities of contacts on the touch-sensitive surface; detecting the input that selects the live image displayed within the plurality of digital images includes detecting a first contact at a location on the touch-sensitive surface that corresponds to display of the live image on the display; the one or more transcript-area-display criteria require that a characteristic intensity of the first contact on the touch-sensitive surface meet a respective intensity threshold in order for the transcript-area-display criteria to be met; and the one or more input-area-display criteria do not require that the characteristic intensity of the contact on the touch-sensitive surface meet the respective intensity threshold in order for the selection criteria to be met

4224
The one or more input-area-display criteria are met upon detection of a tap gesture on the touch-sensitive surface

4226
Prior to detecting the input that selects the live image displayed within the plurality of digital images: detect a first portion of a second input that includes detecting an increase in a characteristic intensity of a second contact, at a location that corresponds to display of a first digital image within the plurality of digital images, above a preview intensity threshold; in response to detecting the first portion of the second input, increase the size of the first digital image; after increasing the size of the first digital image, detect a second portion of the second input that includes detecting a decrease in the characteristic intensity of the second contact below the preview intensity threshold; and in response to detecting the second portion of the second input, decrease the size of the first digital image

Figure 42C

4200

4228
Detect a user input including a first swipe gesture that starts while a focus selector is at a first location in the messaging user interface that corresponds to a first digital image in the plurality of digital images, the first swipe gesture moving the focus selector in a first direction; in response to detecting the first swipe gesture, scroll display of the plurality of digital images in the first direction on the display, wherein the scrolling display includes ceasing to display digital images in the plurality of digital images that are scrolled off a first edge of the display and displaying new digital images in the plurality of digital images from a second edge of the display

4230
Detect a user input including a second swipe gesture that starts while a focus selector is at a first location in the messaging user interface that corresponds to a first digital image in the plurality of digital images, the first swipe gesture moving the focus selector in a second direction; in response to detecting the second swipe gesture, display a first affordance for the digital camera and a second affordance for a photo library

4232
While displaying the first affordance for the digital camera:
detect an input that activates the first affordance for the digital camera; and
in response to detecting the input that activates the first affordance for the digital camera, display a user interface for the digital camera over at least a portion of the messaging user interface

4234
While displaying the second affordance for the photo library:
detect an input that activates the second affordance for the photo library; and
in response to detecting the input that activates the second affordance for the photo library: cease to display the plurality of digital images including one or more digital images stored in the memory and a live preview image from the digital camera and display a plurality of digital images from a digital photo library; and while displaying the plurality of digital images from the digital photo library: detect an input that selects a digital image in the plurality of digital images from the digital photo library; and in response to detecting the input that selects the digital image from the digital photo library: display the digital image from the digital photo library in the conversation transcript, and transmitting a representation of the digital image from the digital photo library to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the digital image from the digital photo library in a conversation transcript that corresponds to the messaging session

Figure 42D


4300
Display unit 4302
Touch-sensitive surface unit 4304
Sensor unit(s) 4306
Digital camera unit 4308
Memory 4310
Processing unit 4312
Display enabling unit 4314
Detecting unit 4316
Image capturing unit 4318
Transmitting unit 4320
Editing unit 4322
Scrolling unit 4324

Figure 43


4400
4402
Display a messaging user interface on a display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a search affordance
4404
The search affordance is a search application launch icon that is displayed with a plurality of launch icons for interactive applications within the messaging application
4406
Prior to displaying the plurality of launch icons for interactive applications in the messaging user interface, the messaging user interface included the conversation transcript of the messaging session between a user of the electronic device and at least one other user, a keyboard, a message-input area, and an application affordance: detecting a user input that activates the application affordance; and in response to detecting the user input that activates the application affordance, replacing display of the keyboard with display of the plurality of launch icons for interactive applications
4408
While displaying the messaging user interface, detect an input that activates the search affordance
4410
In response to detecting the input that activates the search affordance: cease to display the messaging user interface, and display a search user interface, the search user interface including a search field and a plurality of categorized content items, wherein the plurality of categorized content items includes at least a content item stored on the electronic device and a content item from the Internet
4412
While displaying the search user interface, detect an input that selects a first content item in the plurality of categorized content items
A

Figure 44A


4400
A
4414
After detecting the input that selects the first content item in the plurality of categorized content items: cease to display the searching user interface, display the first content item in the conversation transcript within the messaging user interface
4416
Transmitting the first content item to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the first content item in a conversation transcript that corresponds to the messaging session
4418
While displaying the search user interface, and prior to detecting the input that selects the first content item in the plurality of categorized content items: receive input of a query in the search field; and, in response to receiving input of the query in the search field, update the displayed plurality of categorized content items to display content items that satisfy the query
4420
In response to detecting the input that selects the first content item, display the first content item in the message-input area; while displaying the first content item in the message-input area, receive input of a message in the message input area; after receiving input of the message in the message-input area, detect an input that corresponds to a request to post the contents of the message-input area to the messaging session, the contents including the first content item and the message; and in response to detecting the input that corresponds to the request to post the contents of the message-input area to the messaging session: display the first content item in the conversation transcript, display the message in the conversation transcript, wherein the message partially overlaps the first content item in the conversation transcript, and transmit the first content item and the message to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the first content item and the message in a conversation transcript corresponding to the messaging session, wherein the message partially overlaps the first content item in the conversation transcript corresponding to the messaging session

Figure 44B

4400

4422
In response to detecting the input that selects the first content item: in accordance with a determination that the input that selects the first content item meets one or more input-area-display criteria, display the first content item in the message input area, and in accordance with a determination that the input that selects the first content item meets one or more transcript-area-display criteria: display the first content item in the conversation transcript, and transmit the first content item to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the first content item in a conversation transcript corresponding to the messaging session

4424
The electronic device includes one or more sensors configured to detect intensities of contacts on the touch-sensitive surface; detecting the input that selects the first content item in the plurality of content items includes detecting a first contact at a location on the touch-sensitive surface that corresponds to display of the first content item on the display; the one or more transcript-area-display criteria require that a characteristic intensity of the first contact on the touch-sensitive surface meet a respective intensity threshold in order for the transcript-area-display criteria to be met; and the one or more input-area-display criteria do not require that the characteristic intensity of the contact on the touch-sensitive surface meet the respective intensity threshold in order for the selection criteria to be met

4426
The one or more input-area-display criteria are met upon detection of a tap gesture on the touch-sensitive surface

4428
While displaying the first content item in the conversation transcript within the messaging user interface: detect a first input by a first contact at a location that corresponds to the first content item; and, in response to detecting the first input, in accordance with a determination that the first contact meets one or more expansion criteria, display an expanded version of content associated with the first content item

4430
Detect, in the conversation transcript, a word or phrase associated with additional content stored on the electronic device and additional content available on the Internet, wherein the plurality of categorized content items displayed in the search user interface includes a content item stored on the electronic device associated with the word or phrase detected in the conversation transcript

Figure 44C

4400

4432

Detect, in the conversation transcript, a word or phrase associated with additional content stored on the electronic device and additional content available on the Internet, wherein the plurality of categorized content items displayed in the search user interface includes content item from the Internet associated with the word or phrase detected in the conversation transcript

Figure 44D


4500
Display unit 4502
Touch-sensitive surface unit 4504
Processing unit 4506
Display enabling unit 4508
Detecting unit 4510
Transmitting unit 4512
Selecting unit 4514
Updating unit 4516
Receiving input unit 4518

Figure 45


4600
4602
Display a messaging user interface of a messaging application on a display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and an application affordance
4604
While displaying the messaging user interface, detect an input that activates the application affordance
4606
In response to detecting the input that activates the application affordance, concurrently displaying a launch icon for an application store and a plurality of launch icons for interactive applications, wherein activation of a respective launch icon for an interactive application launches a corresponding application that is displayed within the messaging application
4608
The interactive application is configured to perform a subset (e.g., less than all) of the functions of a corresponding application operated separate from the messaging application
4610
The interactive application launch icon displays an identifier for a corresponding application operated separate from the messaging application
4612
The interactive application displays a portion (e.g., less than all) of the content displayed by a corresponding application operated separate from the messaging application
4614
The interactive application causes the device to launch a corresponding application operated separate from the messaging application upon detection of a predefined input
4616
The interactive application is operated separately from a corresponding application operated separate from the messaging application
4618
The interactive application is operated in conjunction with a corresponding application operated separate from the messaging application

Figure 46A


4600
4606
In response to detecting the input that activates the application affordance, concurrently displaying a launch icon for an application store and a plurality of launch icons for interactive applications, wherein activation of a respective launch icon for an interactive application launches a corresponding application that is displayed within the messaging application
4620
The interactive application has a dedicated portion of the memory for temporary storage that is different from a dedicated portion of the memory for temporary storage for a corresponding application operated separate from the messaging application
4622
The corresponding application operated separate from the messaging application is configured to access the dedicated portion of memory for temporary storage for the interactive application
4624
Detect an input that activates the launch icon for the application store
4626
In response to detecting the input that activates the launch icon for the application store: cease to display the messaging user interface, and display an application store user interface, including display of at least one interactive application available for download to the electronic device
4628
While displaying the application store user interface, detecting an input that corresponds to a request to download a first interactive application that is not stored in the memory of the electronic device
A

Figure 46B


4600
A
4630
In response to detecting the input that corresponds to the request to download the first interactive application: download the first interactive application to the memory of the electronic device; replace display of the application store user interface with display of the messaging user interface, the messaging user interface including the conversation transcript and at least some of the plurality of launch icons for interactive applications; and add a launch icon that corresponds to the first interactive application to the display of the plurality of launch icons for interactive applications
4632
Adding an launch icon that corresponds to the first interactive application to the display of the plurality of launch icons for interactive applications includes displaying an indicia that the first interactive application is being downloaded
4634
The indicia indicates the progress of the download of the first interactive application

Figure 46C


4700
Processing unit 4706
Display unit 4702
Detecting unit 4708
Display enabling unit 4710
Touch-sensitive surface unit 4704
Ceasing unit 4712
Downloading unit 4714
Display replacing unit 4716
Adding unit 4718

Figure 47


4800
4802
Display a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a first message-input area, and a launch icon for an interactive application
4804
The launch icon for the interactive application is concurrently displayed with a plurality of launch icons for other interactive applications in the messaging user interface
4806
The interactive application launch icon displays an identifier for a corresponding application operated separate from the messaging application
4808
While displaying the messaging user interface, detect an input that activates the launch icon for the interactive application
4810
Detecting the input that activates the launch icon for the interactive application includes: detecting a first input by a first contact at a location corresponding to the launch icon for the interactive application; in response to detecting the first input, displaying a menu that includes a plurality of options for how to run the interactive application; and detecting a second input that selects a first option in the plurality of options for how to run the interactive application
A

Figure 48A


4800
A
4812
In response to detecting the input that activates the launch icon for the interactive application, display a user interface for the interactive application, the interactive application user interface including a second message-input area that is distinct from the first message-input area
4814
The user interface for the interactive application includes at least one avatar, each respective avatar in the at least one avatar corresponding to a user in the at least one other user included in the messaging session
4816
The user interface for the interactive application includes a plurality of avatars displayed as a stack of avatars
4818
While displaying the interactive application user interface:
detect a third input by a third contact at a location corresponding to an avatar within the user interface for the interactive application; and,
in response to detecting the third input, display a menu of actions, that are associated with the avatar
4820
The interactive application is configured to perform a subset (e.g., less than all) of the functions of a corresponding application operated separate from the messaging application
4822
The interactive application displays a portion (e.g., less than all) of the content displayed by a corresponding application operated separate from the messaging application
4824
The interactive application causes the device to launch a corresponding application operated separate from the messaging application upon detection of a predefined input
4826
The interactive application is operated separately from a corresponding application operated separate from the messaging application

Figure 48B


4800
A
4812
In response to detecting the input that activates the launch icon for the interactive application, display a user interface for the interactive application, the interactive application user interface including a second message-input area that is distinct from the first message-input area
4828
The interactive application is operated in conjunction with a corresponding application operated separate from the messaging application
4830
The interactive application has a dedicated portion of the memory for temporary storage that is different from a dedicated portion of the memory for temporary storage for a corresponding application operated separate from the messaging application
4832
The corresponding application operated separate from the messaging application is configured to access the dedicated portion of memory for temporary storage for the interactive application
4834
While displaying the interactive application user interface, detect input of a first message in the second message-input area
4836
In response to detecting the input of the first message in the second message-input area, display the first message in the second message-input area
4838
While displaying the first message in the second message-input area, detect an input that corresponds to a request to post the contents of the second message-input area to the messaging session
B

Figure 48C


4800
B
4840
In response to detecting the input that corresponds to the request to post the contents of the second message-input area to the messaging session, transmit the first message to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the first message in a conversation transcript corresponding to the messaging session
4842
After detecting the input that corresponds to the request to post the contents of the second message-input area to the messaging session, and while displaying the user interface for the interactive application, detecting an input terminating the interactive application; and, in response to detecting the input terminating the interactive application: cease to display the user interface for the interactive application, and display the messaging user interface, the messaging user interface including display of the first message in the conversation transcript
4844
While displaying the user interface for the interactive application:
receive a message associated with the messaging session; and,
in response to receiving the message associated with the messaging session, transiently display the message overlaid on top of the user interface for the interactive application

Figure 48D


4900
Processing unit 4906
Display unit 4902
Detecting unit 4908
Display enabling unit 4910
Touch-sensitive surface unit 4904
Ceasing unit 4912
Transmitting unit 4914
Receiving unit 4916

Figure 49


50000
50002
Display a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a message-input area, and an icon for an interactive application that is displayed within the conversation transcript
50004
The interactive application launch icon displays an identifier for a corresponding application operated separate from the messaging application
50006
While displaying the messaging user interface, detect an input that activates the icon for the interactive application
50008
In response to detecting the input that activates the icon for the interactive application, display a user interface for the interactive application in a first state
50010
The interactive application displays a portion (e.g., less than all) of the content displayed by a corresponding application operated separate from the messaging application
50012
The interactive application causes the device to launch a corresponding application operated separate from the messaging application upon detection of a predefined input
50014
The interactive application is operated separately from a corresponding application operated separate from the messaging application
50016
The interactive application is operated in conjunction with a corresponding application operated separate from the messaging application

Figure 50A


50000
50008
In response to detecting the input that activates the icon for the interactive application, display a user interface for the interactive application in a first state
50018
The interactive application has a dedicated portion of the memory for temporary storage that is different from a dedicated portion of the memory for temporary storage for a corresponding application operated separate from the messaging application
50020
The corresponding application operated separate from the messaging application is configured to access the dedicated portion of memory for temporary storage for the interactive application
50022
While displaying the user interface for the interactive application, detect a first user input within the user interface for the interactive application
50023
In response to detecting the first user input within the user interface for the interactive application: change display of the user interface for the interactive application from the first state to a second state, and send information, to the one or more electronic devices that correspond to the at least one other user included in the messaging session, indicating that the first user input was made in the user interface for the interactive application, wherein the one or more electronic devices display an indicia of the first user input
50024
The information indicating that the first user input was made in the user interface for the interactive application includes information that causes movement of a corresponding icon for the interactive application within a conversation transcript corresponding to the messaging session
50026
The information indicating that the first user input was made in the user interface for the interactive application includes information that causes movement of a corresponding icon for the interactive application from a first side of a conversation transcript corresponding to the messaging session to a second side of the conversation transcript

Figure 50B

50000

50023
In response to detecting the first user input within the user interface for the interactive application: change display of the user interface for the interactive application from the first state to a second state, and send information, to the one or more electronic devices that correspond to the at least one other user included in the messaging session, indicating that the first user input was made in the user interface for the interactive application, wherein the one or more electronic devices display an indicia of the first user input

50028
The information indicating that the first user input was made in the user interface for the interactive application includes information that causes display of text, indicating the first user input was made, below a corresponding icon for the interactive application within a conversation transcript corresponding to the messaging session

50030
The information indicating that the first user input was made in the user interface for the interactive application includes information that causes change of the appearance of a corresponding icon for the interactive application

50032
The information indicating that the first user input was made in the user interface for the interactive application includes information that causes change of display of a corresponding user interface for the interactive application from a first state to a second state

50034
The interactive application is configured to perform a subset (e.g., less than all) of the functions of a corresponding application operated separate from the messaging application

Figure 50C


51000
Processing unit 51006
Display unit 51002
Detecting unit 51008
Display enabling unit 51010
Touch-sensitive surface unit 51004
Display changing unit 51012
Sending unit 51014

Figure 51


52000
52002
Display a messaging user interface of a messaging application on a display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a message-input area
52004
While displaying the messaging user interface, receive information, from an electronic device that corresponds to another user included in the messaging session, that causes display of an icon for an interactive application in the conversation transcript
52006
The interactive application launch icon displays an identifier for a corresponding application operated separate from the messaging application
52008
In response to receiving the instructions, display the icon for the interactive application in the conversation transcript
52010
While displaying the icon for the interactive application in the conversation transcript, detect an input that activates the icon for the interactive application
52012
In response to detecting the input that activates the icon for the interactive application displayed in the conversation transcript
52014
In accordance with a determination that an interactive application that corresponds to the icon for the interactive application is stored in the memory of the electronic device, display a user interface for the interactive application
52016
The interactive application is configured to perform a subset of the functions of a corresponding application operated separate from the messaging application
52018
The interactive application displays a portion of the content displayed by a corresponding application operated separate from the messaging application

Figure 52A

52000

52012
In response to detecting the input that activates the icon for the interactive application displayed in the conversation transcript

52014
In accordance with a determination that an interactive application that corresponds to the icon for the interactive application is stored in the memory of the electronic device, display a user interface for the interactive application

52020
The interactive application causes the device to launch a corresponding application operated separate from the messaging application upon detection of a predefined input

52022
The interactive application is operated separately from a corresponding application operated separate from the messaging application

52024
The interactive application is operated in conjunction with a corresponding application operated separate from the messaging application

52026
The interactive application has a dedicated portion of the memory for temporary storage that is different from a dedicated portion of the memory for temporary storage for a corresponding application operated separate from the messaging application

52028
The corresponding application operated separate from the messaging application is configured to access the dedicated portion of memory for temporary storage for the interactive application

Figure 52B

52000

52012
In response to detecting the input that activates the icon for the interactive application displayed in the conversation transcript

52030
In accordance with a determination that the interactive application that corresponds to the icon for the interactive application is not stored in the memory of the electronic device: download the interactive application, from a remote server, to the memory of the electronic device, and after downloading the interactive application from the remote server, display the user interface for the interactive application

52032
In accordance with a determination that the interactive application is not stored in the memory of the electronic device, the icon for the interactive application has a first appearance; and in accordance with a determination that the interactive application is stored in the memory of the electronic device, the icon for the interactive application has a second appearance that is different from the first appearance

52034
Detect termination of the interactive application, and, in response to detecting termination of the interactive application: cease to display the user interface for the interactive application; and display the messaging user interface including the conversation transcript, wherein the icon for the interactive application is displayed at a position within the conversation transcript

Figure 52C


5300
Processing unit 5306
Display unit 5302
Detecting unit 5308
Display enabling unit 5310
Touch-sensitive surface unit 5304
Ceasing unit 5312
Downloading unit 5314
Receiving unit 5316

Figure 53

5400

5402
Display a messaging user interface of a messaging application on a display, the messaging user interface including: a conversation transcript, displayed in a first area of the display, of a messaging session between a user of the electronic device and at least one other user, a first interactive application object displayed within the conversation transcript that corresponds to a first interactive application, a message input area, and an input area for the first interactive application, distinct from the message input area, displayed in a second area of the display, the input area for the first interactive application including one or more input affordances

5404
Content posted to the messaging session is displayed within the conversation transcript according to a temporal order in which the content was posted, and the interactive application object is displayed at a position within the conversation transcript associated with the temporal order in which a session of the interactive application was initiated

5406
Display synchronous movement of content displayed in a temporal order within the conversation transcript towards an edge of the conversation transcript, the displayed content including the first interactive application object; in accordance with a determination that the first interactive application object is within a predetermined distance from the edge of the conversation transcript, display the first interactive application object at a fixed location on the display

5408
While displaying the first interactive application object at the fixed location on the display, continue to display synchronous movement of other content displayed in a temporal order within the conversation transcript

5410
Continuing to display synchronous movement of other content displayed in a temporal order with the conversation transcript includes animating other content such that the other content appears to move behind the first interactive application object

Figure 54A

5400

5412
Display a messaging user interface of a messaging application on a display, the messaging user interface including: a conversation transcript, displayed in a first area of the display, of a messaging session between a user of the electronic device and at least one other user, a first interactive application object displayed within the conversation transcript that corresponds to a first interactive application, a message input area, and an input area for the first interactive application, distinct from the message input area, displayed in a second area of the display, the input area for the first interactive application including one or more input affordances

5414
Content posted to the messaging session is displayed within the conversation transcript according to a temporal order in which the content was posted, and the interactive application object is displayed at a position within the conversation transcript associated with the temporal order in which a session of the interactive application was initiated

5416
Display synchronous movement of content displayed in a temporal order within the conversation transcript towards an edge of the conversation transcript, the displayed content including the first interactive application object; in accordance with a determination that the first interactive application object is within a predetermined distance from the edge of the conversation transcript, display the first interactive application object at a fixed location on the display

5418
While displaying the first interactive application object at the fixed location on the display: detect a request to close the first interactive application; and, in response to detecting the request to close the first interactive application: cease to display the first interactive application object at the fixed location on the display; and display the first interactive application object at a position within the conversation transcript associated with the temporal order in which the session of the interactive application was initiated

5420
Detect an input that activates a first input affordance in the input area for the interactive application

5422
After detecting the input that activates the first input affordance: update the first interactive application object that corresponds to the first interactive application in accordance with the input that activates the first input affordance; and send information, to one or more electronic devices that correspond to the at least one other user included in the messaging session, that causes update of a corresponding interactive application object that corresponds to the first interactive application displayed within a corresponding conversation transcript of the messaging session

Figure 54B

5400

5426

Prior to displaying the first interactive application object within the conversation transcript: display the messaging user interface including the conversation transcript of the messaging session between the user of the electronic device and the at least one other user and an application affordance; while displaying the messaging user interface, detect an input that activates the application affordance; in response to detecting the input that activates the application affordance: maintain display of at least a portion of the conversation transcript in a first area of the display, and display a second interactive application icon, which is one of a plurality of interactive application icons, in a second area of the display; while displaying the second interactive application icon in the second area of the display, detect a first swipe gesture that includes horizontal movement of a first contact at a location that corresponds to the second area of the display; in accordance with a determination that the first swipe gesture satisfies one or more interactive application icon switching criteria, replace display of the second interactive application icon with display of a first interactive application icon that corresponds to the first interactive application in the second area of the display; while displaying the first interactive application icon in the second area of the display, detect an input that activates the first interactive application icon; and, in response to detecting the input that activates the first interactive application icon: display a user interface for the first interactive application within the conversation transcript; and cease to display the first interactive application icon

5428

Prior to displaying the first interactive application object within the conversation transcript: display the messaging user interface including the conversation transcript of the messaging session between the user of the electronic device and the at least one other user and an application affordance; while displaying the messaging user interface, detect an input that activates the application affordance; in response to detecting the input that activates the application affordance: maintain display of at least a portion of the conversation transcript in a first area of the display, and display, in a second area of the display that includes a plurality of launch icons for interactive applications, a launch icon for the first interactive application; while displaying the plurality of launch icons for interactive applications, detect an input that activates the launch icon for the first interactive application; and, in response to detecting the input that activates the launch icon for the first interactive application: display a user interface for the first interactive application within the conversation transcript

5426

In response to detecting the input that activates the launch icon for the first interactive application, replace display of the plurality of launch icons for interactive applications with display of an input area for the first interactive application in the second area of the display

Figure 54C


5500
Processing unit 5510
Display enabling unit 5512
Detecting unit 5514
Updating unit 5516
Sending unit 5518
Maintaining unit 5520
Replacing unit 5522
Display unit 5502
Touch-sensitive surface unit 5504

Figure 55


5600
5602
Display a messaging user interface of a messaging application on a display, the messaging user interface including: a conversation transcript, displayed in a first area of the display, of a messaging session between a user of the electronic device and at least one other user, a first interactive application object displayed within the conversation transcript that corresponds to a first interactive application, a message input area, and an input area for the first interactive application, distinct from the message input area, displayed in a second area of the display, the input area for the first interactive application including one or more input affordances
5604
Detect a first input while a focus selector is at a location on the touch-sensitive surface that corresponds to the first interactive application object displayed within the conversation transcript
5606
In response to detecting the first input, display an input area for the first interactive application that is distinct from the message input area, the input area for the first interactive application including one or more input affordances
5608
Display of the input area for the first interactive application in response to detecting the first input replaces display of the conversation transcript, the first interactive application object, and/or the message input area
5610
While displaying an input area for the first interactive application, detect one or more inputs on the one or more input affordances
A

Figure 56A


5600
A
5612
After detecting the one or more inputs on the one or more input affordances: update the first interactive application; send information to one or more electronic devices that correspond to the at least one other user included in the messaging session that causes updating of a corresponding user interface for the first interactive application displayed within a corresponding conversation transcript of the messaging session; and cease display of the input area for the first interactive application
5614
Updating the first interactive application occurs in response to detecting an input on one of the input affordances
5616
Updating the first interactive application occurs in response to detecting an input that corresponds to a request to cease displaying the input area for the first interactive application
5618
Sending information to one or more electronic devices that correspond to the at least one other user included in the messaging session that causes updating of a corresponding user interface for the first interactive application occurs in response to detecting an input on one of the input affordances
5620
Sending information to one or more electronic devices that correspond to the at least one other user included in the messaging session that causes updating of a corresponding user interface for the first interactive application occurs in response to detecting an input that corresponds to a request to cease displaying the input area for the first interactive application
5622
Ceasing display of the input area for the first interactive application occurs in response to detecting an input on one of the input affordances
5624
Ceasing display of the input area for the first interactive application occurs in response to detecting an input on an exit affordance

Figure 56B


5700
Processing unit 5710
Display enabling unit 5712
Display unit 5702
Detecting unit 5714
Touch-sensitive surface unit 5704
Updating unit 5716
Sending unit 5718
Replacing unit 5720

Figure 57


5800
5802
Display a plurality of toggle affordances, wherein: a respective toggle affordance in the plurality of toggle affordances has a corresponding application in a plurality of other applications stored in a memory; the respective toggle affordance has a first state that enables display of a respective launch icon, within a messaging application, for operation of the corresponding application in an embedded mode within the messaging application; the respective toggle affordance has a second state that prevents display of the respective launch icon, within the messaging application, to prevent operation of the corresponding application in the embedded mode within the messaging application; the plurality of toggle affordances include a first toggle affordance for a first application that is displayed in the first state and a second toggle affordance for a second application that is displayed in the second state
5804
While displaying the plurality of toggle affordances, detect a first user input at a first location that corresponds to the first toggle affordance
5806
In response to detecting the first user input at the first location that corresponds to the first toggle affordance: change the first toggle affordance from the first state to the second state, and prevent display of a corresponding launch icon for the first application in the messaging application while displaying the plurality of toggle affordances, detect a first user input at a first location that corresponds to the first toggle affordance
5808
While displaying the plurality of toggle affordances, detect a second user input at a second location that corresponds to the second toggle affordance; and, in response to detecting the second user input at the second location that corresponds to the second toggle affordance: change the second toggle affordance from the second state to the first state, and enable display of a corresponding launch icon for the second application in the messaging application

Figure 58


5900
Processing unit 5910
Display enabling unit 5912
Detecting unit 5914
Changing unit 5916
Display unit 5902
Touch-sensitive surface unit 5904

Figure 59


6000
6002 Display a messaging user interface on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a message-input area, a digital image affordance, a digital touch affordance, and an application affordance
6004 The messaging user interface also includes a microphone affordance, configured to enable sound recording on the electronic device upon activation
6006 The messaging user interface also includes at least one avatar corresponding to a first other user included in the messaging session, configured to enable the electronic device to display a menu that contains activatable menu items associated with the at least one avatar overlaid on the messaging user interface when activated
6008 The menu that contains activatable menu items associated with the at least one avatar includes: a menu item that when activated initiates a digital touch action with the first other user, a menu item that when activated initiates messaging with only the first other user, a menu item that when activated initiates an email with the first other user, a menu item that when activated initiates a call with the first other user, a menu item that when activated initiates a video conference with the first other user, and/or a menu item that when activated initiates a payment action with the first other user While displaying the first interactive application object at the fixed location on the display, continue to display synchronous movement of other content displayed in a temporal order within the conversation transcript
6010 While displaying the messaging user interface, detect a first input on the touch sensitive surface
A

Figure 60A

6000

A

6012 In response to detecting the first input: in accordance with a determination that the first input is made while a focus selector is at a location in the messaging user interface that corresponds to the digital image affordance, display a plurality of digital images within the messaging user interface; in accordance with a determination that the first input is made while a focus selector is at a location in the messaging user interface that corresponds to the digital canvas affordance, display a digital drawing canvas within the messaging user interface; and in accordance with a determination that the first input is made while a focus selector is at a location in the messaging user interface that corresponds to the application affordance, display one or more launch icons for an application within the messaging user interface

6014 Displaying the plurality of digital images within the messaging user interface includes: in accordance with a determination that the messaging user interface included display of a keyboard at the time the first input was detected, replacing display of the keyboard with the display of the plurality of digital images, the plurality of digital images including a live preview image from the digital camera; and in accordance with a determination that the messaging user interface did not include display of a keyboard at the time the first input was detected, displaying the conversation transcript in a first area of the display and displaying the plurality of digital images in a second area of the display, the plurality of digital images including a live preview image from the digital camera

6016 While displaying the plurality of digital images, detect an input that selects a digital image in the plurality of digital images; and after detecting the input that selects a digital image in the plurality of digital images: display the selected digital image in the conversation transcript; and transmit a representation of the selected digital image to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the selected digital image in a conversation transcript that corresponds to the messaging session

6018 Detect an input that selects the live image displayed within the plurality of digital images; and, in response to detecting that input that selects the live image, capture a digital image with the digital camera, while maintaining display of the conversation transcript

6020 After capturing the digital image: display the digital image captured by the digital camera in the conversation transcript, and transmit a representation of the captured digital image to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the captured digital image in a conversation transcript that corresponds to the messaging session

Figure 60B

6000

6012 In response to detecting the first input: in accordance with a determination that the first input is made while a focus selector is at a location in the messaging user interface that corresponds to the digital image affordance, display a plurality of digital images within the messaging user interface; in accordance with a determination that the first input is made while a focus selector is at a location in the messaging user interface that corresponds to the digital canvas affordance, display a digital drawing canvas within the messaging user interface; and In accordance with a determination that the first input is made while a focus selector is at a location in the messaging user interface that corresponds to the application affordance, display one or more launch icons for an application within the messaging user interface

6022 Displaying the digital drawing canvas within the messaging user interface includes: in accordance with a determination that the messaging user interface included display of a keyboard at the time the first input was detected, replacing display of the keyboard with the display of the digital drawing canvas; and in accordance with a determination that the messaging user interface did not include display of a keyboard at the time the first input was detected, displaying the conversation transcript in a first area of the display and displaying the plurality of digital touch actions in a second area of the display

6024 Displaying the one or more launch icons for an application within the messaging user interface includes: in accordance with a determination that the messaging user interface included display of a keyboard at the time the first input was detected, replacing display of the keyboard with the display of the one or more launch icons for an application; and in accordance with a determination that the messaging user interface did not include display of a keyboard at the time the first input was detected, displaying the conversation transcript in a first area of the display and displaying the one or more launch icons for an application in a second area of the display

6026 While displaying the one or more launch icons for an application, detect an input that activates a launch icon in the one or more launch icons for an application; and after detecting the input that activates the launch icon in the one or more launch icons for an application: display a first input area for an application corresponding to the activated launch icon the application that is distinct from the message input area, the input area for the first interactive application including one or more input affordances; display a first application object within the conversation transcript that corresponds to the application corresponding to the activated launch icon; and transmit a representation of a second application object that corresponds to the application corresponding to the activated launch icon to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the second application object in a conversation transcript that corresponds to the messaging session

Figure 60C

6000

6028 While displaying the message-input area, detect a second input that activates the message-input area; and in response to detecting the input that activates the message-input area: in accordance with a determination that the messaging user interface included display of a keyboard and did not include display of the three activatable affordances at the time the second input was detected, display a prompt within the message-input area; in accordance with a determination that the messaging user interface included display of a keyboard and the three activatable affordances at the time the second input was detected: cease to display the three activatable affordances, display the application expansion affordance, expand display of the message input-area, and display a prompt within the message-input area; in accordance with a determination that the messaging user interface did not include display of a keyboard and included display of the three activatable affordances at the time the second input was detected: cease to display the three activatable affordances, display the application expansion affordance, expand display of the message input-area, display a prompt within the message-input area, and display a keyboard; and in accordance with a determination that the messaging user interface did not include display of a keyboard and did not include display of the three activatable affordances at the time the second input was detected: display a prompt within the message-input area, and display a keyboard

Figure 60D


6100
Processing unit 6110
Display enabling unit 6112
Detecting unit 6114
Replacing unit 6116
Transmitting unit 6118
Capturing unit 6120
Expanding unit 6122
Display unit 6102
Touch-sensitive surface unit 6104
Digital camera unit 6106

Figure 61


6200
6202
Display a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a plurality of electronic stickers, and a message-input area
6204
While displaying the messaging user interface, detect a first drag gesture that starts while a focus selector is at a first location in the messaging user interface that corresponds to a first electronic sticker in the plurality of electronic stickers, the first drag gesture moving the focus selector in a first direction
6206
Move the first electronic sticker in the first direction in accordance with the movement of the first drag gesture
6208
The plurality of electronic stickers is a plurality of objects contained within a digital image, wherein: the first electronic sticker corresponds to an object displayed at the first location at the start of the first drag gesture; and moving the first electronic sticker includes displaying an animation of peeling the first electronic sticker from the digital image
6210
Detect termination of the first drag gesture while the focus selector is at a second location in the messaging user interface
6212
In response to detecting termination of the first drag gesture:
in accordance with a determination that the second location is within the conversation transcript, place the electronic sticker in the conversation transcript at a location based on the second location, and in accordance with a determination that the second location in not within the conversation transcript, cease to display the electronic sticker at the second location on the display
6214
The location based on the second location is the second location
6216
The conversation transcript includes display of one or more objects posted to the messaging session, the location based on the second location is a nearest position in a plurality of positions that are defined by the positions of the one or more objects posted to the messaging session

Figure 62A

6200

6218
In response to detecting termination of the first drag gesture, in accordance with a determination that the second location is within the conversation transcript: transmit information that represents the electronic sticker to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display a corresponding representation of the electronic sticker in a corresponding location within a corresponding conversation transcript

6220
Detect a user input while the focus selector is at a third position that corresponds to a second electronic sticker in the plurality of electronic stickers; in response to detecting the user input while the focus selector is at the third position: in accordance with a determination that the user input satisfies one or more sticker-selection-criteria, display the second electronic sticker in the message-input area; and in accordance with a determination that the user input satisfies one or more sticker-posting-criteria, display the sticker in the conversation transcript at a location that corresponds to a next message insertion point

6222
Detect a user input while the focus selector is at a fourth position that corresponds to a third electronic sticker in the plurality of electronic stickers, wherein the third electronic sticker is associated with a sticker animation;
in response to detecting the user input while the focus selector is at the fourth position, in accordance with a determination that the user input satisfies one or more animation preview criteria, preview the sticker animation associated with the third electronic sticker

6224
Prior to displaying the plurality of electronic stickers: display the messaging user interface including the conversation transcript of the messaging session between the user of the electronic device and the at least one other user and an application affordance; while displaying the messaging user interface, detect an input that activates the application affordance; in response to detecting the input that activates the application affordance: maintain display of at least a portion of the conversation transcript in a first area of the display, and display the plurality of electronic stickers in a second area of the display

Figure 62B

6200

6226

Prior to displaying the plurality of electronic stickers: display the messaging user interface including the conversation transcript of the messaging session between the user of the electronic device and the at least one other user and an application affordance; while displaying the messaging user interface, detect an input that activates the application affordance; in response to detecting the input that activates the application affordance: maintain display of at least a portion of the conversation transcript in a first area of the display, and display a first interactive application icon, which is one of a plurality of interactive application icons, in a second area of the display; while displaying the first interactive application icon in the second area of the display, detect a first swipe gesture that includes horizontal movement of a first contact at a location that corresponds to the second area of the display; and in accordance with a determination that the first swipe gesture satisfies one or more interactive application icon switching criteria, replace display of the first interactive application icon with display of the plurality of electronic stickers in the second area of the display

6228

Prior to displaying the plurality of electronic stickers: display the messaging user interface including the conversation transcript of the messaging session between the user of the electronic device and the at least one other user and an application affordance; while displaying the messaging user interface, detect an input that activates the application affordance; in response to detecting the input that activates the application affordance: maintain display of at least a portion of the conversation transcript in a first area of the display, and display, in a second area of the display that includes a plurality of application launch icons, an application launch icon for a sticker pack; while displaying the plurality of application launch icons, detect an input that activates the application launch icon for the sticker pack; and, in response to a detecting the input that activates the application launch icon for the sticker pack, replace display of the plurality of application launch icons with display of the plurality of electronic stickers in the second area of the display

Figure 62C


6300
Processing Unit 6306
Enabling Unit 6308
Display Unit 6302
Detecting Unit 6310
Touch-Sensitive Surface Unit 6304
Moving Unit 6312
Placing Unit 6314
Ceasing Unit 6316
Transmitting Unit 6317
Previewing Unit 6318
Maintaining Unit 6320
Replacing Unit 6322

Figure 63


6400
6402
Display a messaging user interface of a messaging application on a display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a plurality of electronic stickers, and a message-input area
6404
While displaying the messaging user interface, detect a first user input while a focus selector is at a first location in the messaging user interface that corresponds to a first electronic sticker in the plurality of electronic stickers
6406
In response to detecting the first user input, place and display the first electronic sticker in the conversation transcript
6408
While the first electronic sticker is displayed in the conversation transcript: detect a second user input while a focus selector is at a second location in the messaging user interface that corresponds to the first electronic sticker in the conversation transcript; and, in response to detecting the second user input, change the position, size, and/or rotation of the first electronic sticker in the conversation transcript
6410
The size of the first electronic sticker is reduced in response to detecting a pinch gesture that includes movement of a first contact towards a second contact, wherein the pinch gesture started while a focus selector was at a location in the messaging user interface that corresponds to the first electronic sticker
6412
The size of the first electronic sticker is increased in response to detecting a depinch gesture that includes movement of a first contact away from a second contact, wherein the depinch gesture started while a focus selector was at a location in the messaging user interface that corresponds to the first electronic sticker
6414
The size of the first electronic sticker is increased in accordance with a characteristic intensity of a contact made while a focus selector was at a location in the messaging user interface that corresponds to the first electronic sticker

Figure 64A

6400

6408
While the first electronic sticker is displayed in the conversation transcript: detect a second user input while a focus selector is at a second location in the messaging user interface that corresponds to the first electronic sticker in the conversation transcript; and, in response to detecting the second user input, change the position, size, and/or rotation of the first electronic sticker in the conversation transcript

6416
The orientation of the first electronic sticker is changed in response to detecting a rotation gesture that started while a focus selector was at a location in the messaging user interface that corresponds to the first electronic sticker

6418
After detecting the first user input: transmit information that represents the first electronic sticker to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display a corresponding representation of the first electronic sticker in a corresponding location within a corresponding conversation transcript

6420
After transmitting the information that represents the first electronic sticker to the one or more electronic devices: detect a third user input while a focus selector is at a third location in the messaging user interface that corresponds to the first electronic sticker in the conversation transcript; and, in response to detecting the third user input: change the position of the first electronic sticker in the conversation transcript for a second time; and send information to the one or more electronic devices that correspond to the at least one other user included in the messaging session that the position of the first electronic sticker was changed in the conversation transcript, wherein the one or more electronic devices make corresponding changes to the position of the first electronic sticker within the corresponding conversation transcript

6422
After transmitting the information that represents the first electronic sticker to the one or more electronic devices: detect a third user input while a focus selector is at a third location in the messaging user interface that corresponds to the first electronic sticker in the conversation transcript; and, in response to detecting the third user input: change the rotation of the first electronic sticker in the conversation transcript for a second time; and send information to the one or more electronic devices that correspond to the at least one other user included in the messaging session that the rotation of the first electronic sticker was changed in the conversation transcript, wherein the one or more electronic devices make corresponding changes to the rotation of the first electronic sticker within the corresponding conversation transcript

Figure 64B

6400

6418
After detecting the first user input: transmit information that represents the first electronic sticker to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display a corresponding representation of the first electronic sticker in a corresponding location within a corresponding conversation transcript

6424
After transmitting information that represents the first electronic sticker to the one or more electronic devices: detect a third user input while a focus selector is at a third location in the messaging user interface that corresponds to the first electronic sticker in the conversation transcript; and, in response to detecting the third user input: change the size of the first electronic sticker in the conversation transcript for a second time; and send information to the one or more electronic devices that correspond to the at least one other user included in the messaging session that the size of the first electronic sticker was changed in the conversation transcript, wherein the one or more electronic devices make corresponding changes to the size of the first electronic sticker within the corresponding conversation transcript

6426
In response to detecting the first user input, change the position, of the first electronic sticker

6428
In response to detecting the first user input, change the size of the first electronic sticker

6430
In response to detecting the first user input, change the rotation of the first electronic sticker

Figure 64C


6500
Processing Unit 6506
Enabling Unit 6508
Display Unit 6502
Detecting Unit 6510
Touch-Sensitive Surface Unit 6504
Placing Unit 6512
Changing Unit 6514
Transmitting Unit 6516
Sending Unit 6518

Figure 65


6600
6602
Display a messaging user interface of a messaging application on a display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user and a message-input area, wherein each of the other users included in the messaging session has a corresponding avatar
6604
While displaying the messaging user interface, detect a first user input while a focus selector is at a first location in the messaging user interface that corresponds to an avatar of a first other user included in the messaging session
6606
In response to detecting the first user input, display a menu that contains activatable menu items associated with the first other user overlaid on the messaging user interface, the displayed menu including an activatable menu item for initiating a payment action with the first other user
6608
While displaying the menu that contains activatable menu items associated with the first other user, detect a second user input while a focus selector is at a second location in the messaging user interface that corresponds to the activatable menu item for initiating a payment action with the first other user
6610
In response to detecting the second user input, display a user interface configured to initiate sending of a payment to, and/or requesting a payment from, the first other user

Figure 66


6700
Processing Unit 6706
Display Unit 6702
Enabling Unit 6708
Touch-Sensitive Surface Unit 6704
Detecting Unit 6710

Figure 67

6800

6802
Display a messaging user interface of a messaging application on a display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and a plurality of other users, a message-input area, and a plurality of avatars, each respective avatar in the plurality of avatars corresponding to a respective other user in the plurality of other users included in the messaging session, wherein the plurality of avatars are displayed as a stack of avatars, with a first avatar in the plurality of avatars displayed on the top of the stack of avatars

6804
While displaying the messaging user interface, detect an input by a first contact on the touch-sensitive surface while a focus selector is at a first location in the messaging user interface that corresponds to the first avatar

6806
In response to detecting the input by the first contact: in accordance with a determination that the input meets menu-activation-criteria, wherein the menu-activation-criteria require that a characteristic intensity of the contact on the touch-sensitive surface meet a respective intensity threshold in order for the menu-activation criteria to be met, display a menu that contains activatable menu items associated with the first avatar overlaid on the messaging user interface; and in accordance with a determination that the input meets avatar-spreading-criteria, wherein the avatar-spreading-criteria do not require that a characteristic intensity of the contact on the touchscreen meet the respective intensity threshold in order for the selection criteria to be met, display the plurality of avatars in an array

6810
The avatar-spreading-criteria are met upon detection of a tap gesture on the touch-sensitive surface

6812
The menu that contains activatable menu items associated with the first avatar includes a menu item that when activated initiates a canvas for sharing digital drawings with the other user

6814
The menu that contains activatable menu items associated with the first avatar includes a menu item that when activated initiates messaging with only the first other user

6814
The menu that contains activatable menu items associated with the first avatar includes a menu item that when activated initiates an email with the first other user

Figure 68A

6800

6806
In response to detecting the input by the first contact: in accordance with a determination that the input meets menu-activation-criteria, wherein the menu-activation-criteria require that a characteristic intensity of the contact on the touch-sensitive surface meet a respective intensity threshold in order for the menu-activation criteria to be met, display a menu that contains activatable menu items associated with the first avatar overlaid on the messaging user interface; and in accordance with a determination that the input meets avatar-spreading-criteria, wherein the avatar-spreading-criteria do not require that a characteristic intensity of the contact on the touchscreen meet the respective intensity threshold in order for the selection criteria to be met, display the plurality of avatars in an array

6816
The menu that contains activatable menu items associated with the first avatar includes a menu item that when activated initiates a call with the first other user

6818
The menu that contains activatable menu items associated with the first avatar includes a menu item that when activated initiates a video conference with the first other user

6820
The menu that contains activatable menu items associated with the first avatar includes a menu item that when activated initiates a payment action with the first other user

Figure 68B


6900
Processing Unit 6906
Display Unit 6902
Enabling Unit 6908
Touch-Sensitive Surface Unit 6904
Detecting Unit 6910

Figure 69


7000
7002
Display a messaging user interface of a messaging application on a display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a message-input area
7004
While displaying the messaging user interface, receive a first message within the messaging session from an electronic device that corresponds to another user included in the messaging session
7006
In response to receiving the first message: display the first message within a first message region in the conversation transcript on the display; detect, in the first message, a word or phrase associated with additional content available on the Internet; and in response to detecting the word or phrase associated with additional content available on the internet, display, proximate to the first message region, a selectable indication that additional content associated with the word or phrase is available
7008
The word or phrase associated with additional content available is associated with a movie, and the additional content includes biographical data about the movie, information on local performances of the movie, ratings information for the movie, and/or multi-media content about the movie
7010
The word or phrase associated with additional content available is associated with a television show, and the additional content includes biographical data about the show, ratings information about the show, and/or multi-media content about the show
7012
The word or phrase associated with additional content available is associated with a song or album, and the additional content includes biographical data about the song or album, ratings information about the song or album, and/or multi-media content about the song or album
7014
The word or phrase associated with additional content available is associated with a business, and the additional content includes biographical data about the business, ratings information about the business, and/or interactive content about the business

Figure 70A

7000

7016
Detect an input that activates the selectable indication;
in response to detecting the input that activates the selectable indication, display additional content within the conversation transcript

Figure 70B


7100
Processing Unit 7106
Display Unit 7102
Enabling Unit 7108
Touch-Sensitive Surface Unit 7104
Receiving Unit 7110
Detecting Unit 7112

Figure 71


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
7218
Abe
7214
7202
Have you seen the new dandy horse with pedals?
7216
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
They have, and there was a huge line at the store to get them. Apparently everyone wanted to be the first to get the latest model.
7204
7208
7206
7210
7212
space
return
Touch Screen 112

Figure 72A


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
Have you seen the new dandy horse with pedals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
They have, and there was a huge line at the store to get them. Apparently everyone wanted to be the first to get the latest model.
7220
7208
7210
7212
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112

Figure 72B


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
7202
Have you seen the new dandy horse with pedals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
They have, and there was a huge line at the store to get them. Apparently everyone wanted to be the first to get the latest model.
7204
7208
7206
7222
MUSIC
Unicycle Race
The Royalty
I've got a Trike
Mauve Lloyd
7210
7234
7238
Wild Velocipedes
Moss Gatherers
Pennyfarthing Nadir
Old Steel
7236
7240
7224
7232
7230
7228
Touch Screen 112
7226

Figure 72C


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
Have you seen the new dandy horse with pedals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
They have, and there was a huge line at the store to get them. Apparently everyone wanted to be the first to get the latest model.
MUSIC
Unicycle Race
The Royalty
I've got a Trike
Mauve Lloyd
Wild Velocipedes
Moss Gatherers
Pennyfarthing Nadir
Old Steel
7224
7232
7242
7230
7244
7228
Touch Screen 112
7226

Figure 72D


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
Have you seen the new dandy horse with pedals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
They have, and there was a huge line at the store to get them. Apparently everyone wanted to be the first to get the latest model.
MUSIC
Unicycle Race
The Royalty
I've got a Trike
Mauve Lloyd
Wild Velocipedes
Moss Gatherers
Pennyfarthing Nadir
Old Steel
7224
7232
7242
7230
Touch Screen 112
7228

Figure 72E


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
Have you seen the new dandy horse with pedals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
They have, and there was a huge line at the store to get them. Apparently everyone wanted to be the first to get the latest model.
MUSIC
Unicycle Race
The Royalty
I've got a Trike
Mauve Lloyd
Wild Velocipedes
Moss Gatherers
Pennyfarthing Nadir
Old Steel
7242
7224
Touch Screen 112
7246
7232
7230

Figure 72F


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
Have you seen the new dandy horse with pedals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
They have, and there was a huge line at the store to get them. Apparently everyone wanted to be the first to get the latest model.
MUSIC
Unicycle Race
The Royalty
I've got a Trike
Mauve Lloyd
Wild Velocipedes
Moss Gatherers
Pennyfarthing Nadin
Old Steel
7224
7248
7246
7232
Touch Screen 112
7230

Figure 72G


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
Have you seen the new dandy horse with pedals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
They have, and there was a huge line at the store to get them. Apparently everyone wanted to be the first to get the latest model.
7222
MUSIC
Unicycle Race
The Royalty
I've got a Trike
Mauve Lloyd
7234
7238
Wild Velocipedes
Moss Gatherers
Pennyfarthing Nadir
Old Steel
7236
7240
7224
7246
7250
Touch Screen 112

Figure 72H


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
Have you seen the new dandy horse with pedals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
They have, and there was a huge line at the store to get them. Apparently everyone wanted to be the first to get the latest model.
7222
Reservations
Recently Viewed
Joe's Bistro
Details
7252
Springfield Tavern
Details
7254
Touch Screen 112

Figure 72I


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
7202
Have you seen the new dandy horse with pedals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
They have, and there was a huge line at the store to get them. Apparently everyone wanted to be the first to get the latest model.
7258
7256
7222
7260
Reservations
Recently Viewed
Joe's Bistro
Details
Springfield Tavern
Details
Touch Screen 112

Figure 72J


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
7202
Have you seen the new dandy horse with pedals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
7256
They have, and there was a
7260
7222
Reservations
Recently Viewed
Joe's Bistro
Details
Springfield Tavern
Details
Dakota Engravers
Details
Touch Screen 112

Figure 72K


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
7222
Recently Viewed
Joe's Bistro
Details
Springfield Tavern
Details
Dakota Engravers
Details
The Cavalry Club
Details
Capitol Hatter
Details
Herndon Inn
Details
Touch Screen 112

Figure 72L


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
7260
7262
Recently Viewed
Joe's Bistro
Details
Springfield Tavern
Details
Dakota Engravers
Details
The Cavalry Club
Details
Capitol Hatter
Details
Herndon Inn
Details
Touch Screen 112

Figure 72M


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
Have you seen the new dandy horse with pedals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
They have, and there was a huge line at the store to get them. Apparently everyone wanted to be the first to get the latest model.
Reservations
Recently Viewed
Joe's Bistro
Details
Springfield Tavern
Details
Touch Screen 112

Figure 72N


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
Have you seen the new dandy horse with pedals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
They have, and there was a huge line at the store to get them. Apparently everyone wanted to be the first to get the latest model.
7264
7208
7204
7222
Reservations
Recently Viewed
Joe's Bistro
Details
Springfield Tavern
Details
7210
7224
7248
7246
7232
Touch Screen 112
7230

Figure 72O


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
Have you seen the new dandy horse with pedals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
They have, and there was a huge line at the store to get them. Apparently everyone wanted to be the first to get the latest model.
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
7210
7212
Touch Screen 112

Figure 72P


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
Have you seen the new dandy horse with pedals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
They have, and there was a huge line at the store to get them. Apparently everyone wanted to be the first to get the latest model.
7266
7208
7210
7212
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112

Figure 72Q


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
Have you seen the new dandy horse with pedals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
They have, and there was a huge line at the store to get them. Apparently everyone wanted to be the first to get the latest model.
7222
Reservations
Recently Viewed
Joe's Bistro
Details
Springfield Tavern
Details
7210
7224
7232
7230
7228
Touch Screen 112
7226

Figure 72R


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
Have you seen the new dandy horse with pedals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
They have, and there was a huge line at the store to get them. Apparently everyone wanted to be the first to get the latest model.
Reservations
Recently Viewed
Joe's Bistro
Details
Springfield Tavern
Details
7268
7226
Touch Screen 112

Figure 72S


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
7270
Done
Edit
72112
Tic-tac-toe
7272
7273
Music
7274
7275
Stickers
7276
7277
Reservations
7278
7279
Pizza Builder
7280
7281
Live video
7282
7283
Activity
7284
7285
Touch Screen 112

Figure 72T


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Done
Edit
Tic-tac-toe
7272
7288
7273
Music
Stickers
Reservations
Pizza Builder
Live video
Activity
Touch Screen 112

Figure 72U


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Done
Edit
Music
Stickers
Reservations
Pizza Builder
Live video
Activity
Touch Screen 112

Figure 72V


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
7270
7292
Done
Edit
7290
Music
Stickers
Reservations
Pizza Builder
Live video
Activity
Touch Screen 112

Figure 72W


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
7270
7294
Cancel
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
Search
7212
Touch Screen 112

Figure 72X


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
7296
7294
transit
Cancel
7290
city transit map
transit arrival times
transit stickers
tiny transit
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
Search
7212
7298
72100
Touch Screen 112

Figure 72Y


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
7294
transit
Cancel
Tiny Transit
GET
72108
72102
72106
Transit Maps
GET
72104
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
Search
Touch Screen 112

Figure 72Z


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
7270
Done
Edit
Music
Stickers
Reservations
Pizza Builder
Live video
Activity
Tiny Transit
72110
Touch Screen 112

Figure 72AA


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
72114
Done
Edit
72112
Music
Stickers
Reservations
Pizza Builder
Live video
Activity
Tiny Transit
Touch Screen 112

Figure 72AB


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Done
72116
72117
Music
7274
72118
Stickers
7276
72119
Reservations
7278
72121
Pizza Builder
7280
72123
Live video
7282
72125
Activity
7284
72124
Tiny Transit
72127
72110
Touch Screen 112

Figure 72AC


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Done
Music
Stickers
72118
72122
7276
Reservations
Pizza Builder
Live video
Activity
Tiny Transit
Touch Screen 112

Figure 72AD


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Done
Music
Stickers
72118
7276
Reservations
Pizza Builder
Live video
Activity
Tiny Transit
Touch Screen 112

Figure 72AE


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Done
Music
Stickers
Reservations
Pizza Builder
Live video
Activity
Tiny Transit
72131
7278
72120
72124
72110
Touch Screen 112

Figure 72AF


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Done
Music
Stickers
Reservations
Pizza Builder
Live video
Activity
Tiny Transit
Touch Screen 112

Figure 72AG


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Done
Music
Stickers
Reservations
Pizza Builder
Live video
Tiny Transit
Activity
Touch Screen 112

Figure 72AH


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Done
Music
Stickers
Reservations
Tiny Transit
Pizza Builder
Live video
Activity
Touch Screen 112

Figure 72AI


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Done
Music
Tiny Transit
Stickers
Reservations
Pizza Builder
Live video
Activity
Touch Screen 112

Figure 72AJ


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Done
Music
Tiny Transit
Stickers
Reservations
Pizza Builder
Live video
Activity
Touch Screen 112

Figure 72AK


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
72132
Done
72116
72130
Music
Tiny Transit
Stickers
Reservations
Pizza Builder
Live video
Activity
Touch Screen 112

Figure 72AL


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
7270
Done
Edit
Music
Tiny Transit
Stickers
Reservations
Pizza Builder
Live video
Activity
Touch Screen 112

Figure 72AM


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
72136
7270
Done
Edit
72134
Music
Tiny Transit
Stickers
Reservations
Pizza Builder
Live video
Activity
Touch Screen 112

Figure 72AN


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Abe
7202
Have you seen the new dandy horse with pedals?
Pretty slick, connecting a crank to the wheel hub
Will they ship more of them across the pond?
They have, and there was a huge line at the store to get them. Apparently everyone wanted to be the first to get the latest model.
Reservations
7210
Recently Viewed
Joe's Bistro
Details
Springfield Tavern
Details
7224
Touch Screen 112
72128
72126
7230
7226

Figure 72AO


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
7202
72140
Was the test ride a success?
72138
Oui, le voyage s'est bien passé.
72142
72146
This time, I made it all the way to New Haven.
Will there be another demonstration?
72144
ITD
ITL
ITH
IT0
Touch Screen 112
Intensity of Contact 72155

Figure 72AP


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
72140
Was the test ride a success?
Oui, le voyage s'est bien passé.
72148
72146
This time, I made it all the way to New Haven.
Will there be another demonstration?
Touch Screen 112
ITD
ITL
ITH
ITO
Intensity of Contact 72155

Figure 72AQ


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
72140
Was the test ride a success?
Yes, the trip went well.
72150
This time, I made it all the way to New Haven.
Will there be another demonstration?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72AR


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
72140
Was the test ride a success?
Yes, the trip went well.
This time, I made it all the way to New Haven.
72152
Will there be another demonstration?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72AS


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
72140
Was the test ride a success?
Oui, le voyage s'est bien passé.
72146
This time, I made it all the way to New Haven.
Will there be another demonstration?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72AT


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
72140
Was the test ride a success?
Oui, le voyage s'est bien passé.
72154
72146
This time, I made it all the way to New Haven.
Will there be another demonstration?
Touch Screen 112
ITD
ITL
ITH
ITO
Intensity of Contact 72155

Figure 72AU


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Here
HA
72140
Oui, le voyage s'est bien passé.
72154
This time, I made it all the way to New Haven.
Will there be another demonstration?
72156
Translate
72158
Copy
Speak
More...
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72AV


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
HA
Oui, le voyage s'est bien passé.
This time I made it all the way to New Haven.
Will there be another demonstration?
72156
Translate
Copy
Speak
More...
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72AW


Portable Multifunction Device 100
UI 7200
164
111
72140
HA
Oui, le voyage s'est bien passé.
72156
72158
Translate
Copy
Speak
More...
72160
ITD
ITL
ITH
IT0
Touch Screen 112
Intensity of Contact 72155

Figure 72AX


Portable Multifunction Device 100
UI 7200
164
111
72140
HA
Yes, the trip went well.
72156
Undo Translate
72158
Copy
Speak
More...
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72AY


Portable Multifunction Device 100
UI 7200
164
111
HA
Yes, the trip went well.
72162
Undo Translate
Copy
Speak
More...
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72AZ


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
Yes, the trip went well.
This time, I made it all the way to New Haven.
Will there be another demonstration?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BA


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
72140
Was the test ride a success?
Yes, the trip went well.
72164
This time, I made it all the way to New Haven.
Will there be another demonstration?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BB


Portable Multifunction Device 100
UI 7200
164
111
72140
HA
Yes, the trip went well.
72164
72150
72156
Undo Translate
72158
Copy
Speak
More...
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BC


Portable Multifunction Device 100
UI 7200
164
111
HA
Yes, the trip went well.
72156
Undo Translate
Copy
Speak
More...
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BD


Portable Multifunction Device 100
UI 7200
164
111
HA
Yes, the trip went well.
72156
Undo Translate
Copy
Speak
More...
72158
72166
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BE


Portable Multifunction Device 100
UI 7200
164
111
72140
HA
Oui, le voyage s'est bien passé.
72146
72156
Translate
72158
Copy
Speak
More...
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BF


Portable Multifunction Device 100
UI 7200
164
111
HA
Oui, le voyage s'est bien passé.
72168
Translate
Copy
Speak
More...
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BG


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
Oui, le voyage s'est bien passé.
This time, I made it all the way to New Haven.
Will there be another demonstration?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BH


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
Oui, le voyage s'est bien passé.
72142
This time, I made it all the way to New Haven.
72170
Will there be another demonstration?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BI


Portable Multifunction Device 100
UI 7200
164
111
72142
This time, I made it all the way to New Haven.
72170
72172
72156
Copy
Speak
More...
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BJ


Portable Multifunction Device 100
UI 7200
164
111
72142
This time, I made it all the way to New Haven.
Copy
Speak
More...
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BK


Portable Multifunction Device 100
UI 7200
164
111
72142
This time, I made it all the way to New Haven.
72174
Copy
Speak
More...
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BL


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
Oui, le voyage s'est bien passé.
This time, I made it all the way to New Haven.
Will there be another demonstration?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BM


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
72140
Was the test ride a success?
Oui, le voyage s'est bien passé.
72176
This time, I made it all the way to New Haven.
Will there be another demonstration?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BN


Portable Multifunction Device 100
UI 7200
164
111
72180
72140
HA
72178
Oui, le voyage s'est bien passé.
72176
Copy
Speak
More...
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BO


Portable Multifunction Device 100
UI 7200
164
111
HA
Oui, le voyage s'est bien passé.
Copy
Speak
More...
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BP


Portable Multifunction Device 100
UI 7200
72182
72180
72140
164
111
HA
72178
Oui, le voyage s'est bien passé.
72146
Copy
Speak
More...
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BQ


Portable Multifunction Device 100
UI 7200
164
111
HA
Yes, the trip went well.
72150
Copy
Speak
More...
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BR


Portable Multifunction Device 100
UI 7200
164
111
HA
Yes, the trip went well.
72184
Copy
Speak
More...
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BS


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
Oui, le voyage s'est bien passé.
This time, I made it all the way to New Haven.
Will there be another demonstration?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BT



t<0

Figure 72BU-1



t=0

Figure 72BU-2



$t=t_{tap}$

Figure 72BU-3



$t>t_{tap}$

Figure 72BU-4



t<0

Figure 72BV-1



t=0

Figure 72BV-2



$t=t_{tap}$

Figure 72BV-3



$t=t_{long}$, $t_{long} > t_{tap}$

Figure 72BV-4



$t>t_{long}$

Figure 72BV-5


4:26 PM
Portable Multifunction Device 100
Pierre
Was the test ride a success?
72140
Oui, le voyage s'est bien passé.
72190
72146
This time, I made it all the way to New Haven.
Will there be another demonstration?
Touch Screen 112
72192
Threshold hover distance
Distance 72194
Touch Screen 112

Figure 72BW


Portable Multifunction Device 100
4:26 PM
Pierre
Was the test ride a success?
Yes, the trip went well.
72162
72150
This time, I made it all the way to New Haven.
Will there be another demonstration?
Touch Screen 112
Threshold hover distance
72192
Distance 72194
Touch Screen 112

Figure 72BX


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
Oui, le voyage s'est bien passé.
This time, I made it all the way to New Haven.
Will there be another demonstration?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BY


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
72140
Was the test ride a success?
Oui, le voyage s'est bien passé.
This time, I made it all the way to New Haven.
Will there be another demonstration?
72198
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72BZ


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
72140
Was the test ride a success?
Oui, le voyage s'est bien passé.
This time, I made it all the way to New Haven.
Will there be another demonstration?
72198
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72CA


Portable Multifunction Device 100
UI 7200
164
111
Was the test ride a success?
Oui, le voyage s'est bien passé.
This time, I made it all the way to New Haven.
Will there be another
HA
72198
Peut-être. Do you want to give pedaling a go?
72156
Translate
Translate All
Copy
Speak
More...
72158
72196
Touch Screen 112
ITD
ITL
ITH
ITO
Intensity of Contact 72155

Figure 72CB


Portable Multifunction Device 100
UI 7200
164
111
Was the test ride a success?
Oui, le voyage s'est bien passé
This time, I made it all the way to New Haven
Will there be another
HA
72198
Peut-être. Do you want to give pedaling a go?
72156
Translate
Translate All
Copy
Speak
More...
72158
72196
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72CC


Portable Multifunction Device 100
UI 7200
164
111
Was the test ride a success?
Oui, le voyage s'est bien passé.
This time, I made it all the way to New Haven.
Will there be another
HA
72198
Peut-être. Do you want to give pedaling a go?
72156
Translate
Translate All
Copy
Speak
More...
72158
72196
Touch Screen 112
ITD
ITL
ITH
ITO
Intensity of Contact 72155

Figure 72CD


Portable Multifunction Device 100
UI 7200
164
111
72140
Yes, the trip went well.
72198
Perhaps. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72CE


Portable Multifunction Device 100
UI 7200
164
111
72140
Yes, the trip went well.
72198
Perhaps. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72CF


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
72140
Was the test ride a success?
Yes, the trip went well.
This time, I made it all the way to New Haven.
Will there be another demonstration?
72198
Perhaps. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72CG


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
72140
Was the test ride a success?
Yes, the trip went well.
This time, I made it all the way to New Haven.
Will there be another demonstration?
72198
Perhaps. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72CH


Portable Multifunction Device 100
UI 7200
164
111
72140
HA
Yes, the trip went well.
72156
Undo Translate
Undo Translate All
Copy
Speak
More...
72158
72196
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72CI


Portable Multifunction Device 100
UI 7200
164
111
Siri
72140
Yes, the trip went well.
72156
Undo Translate
Undo Translate All
Copy
Speak
More...
72158
72196
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72CJ


Portable Multifunction Device 100
UI 7200
164
111
72140
Yes, the trip went well.
72156
Undo Translate
Undo Translate All
Copy
Speak
More...
72158
72196
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72CK


Portable Multifunction Device 100
UI 7200
164
111
72140
Oui, le voyage s'est bien passé.
72198
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72CL


Portable Multifunction Device 100
UI 7200
164
111
72140
Oui, le voyage s'est bien passé.
72198
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72CM


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
Oui, le voyage s'est bien passé.
This time, I made it all the way to New Haven.
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
72146
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72CN


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
72200
72140
Was the test ride a success?
Oui, le voyage s'est bien passé.
This time, I made it all the way to New Haven.
72146
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
ITO
Intensity of Contact 72155

Figure 72CO


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
72200
72140
Was the test ride a success?
le voyage s'est bien passé.
This time, I made it all the way to New Haven.
72146
72202
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
ITO
Intensity of Contact 72155

Figure 72CP


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
72200
72140
Was the test ride a success?
Oui, le voyage s'est bien passé.
This time, I made it all the way to New Haven.
72146
72202
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
ITO
Intensity of Contact 72155

Figure 72CQ


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
72200
72140
Was the test ride a success?
Oui, le voyage s'est bien passé.
This time, I made it all the way to New Haven.
72146
72202
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
ITO
Intensity of Contact 72155

Figure 72CR


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
72140
Was the test ride a success?
Yes, the trip was bien passé.
This time, I made it all the way to New Haven.
72146
72204
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72CS


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
Oui, le voyage s'est bien passé.
This time, I made it all the way to New Haven.
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
72146
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72CT


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
72206
72140
Was the test ride a success?
Oui, le voyage s'est bien passé.
This time, I made it all the way to New Haven.
72146
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
ITO
Intensity of Contact 72155

Figure 72CU


Portable Multifunction Device 100
UI 7200
164
111
72210
72206
72140
Yes
le voyage s'est bien passé.
72146
72208
Touch Screen 112
ITD
ITL
ITH
ITO
Intensity of Contact 72155

Figure 72CV


Portable Multifunction Device 100
UI 7200
164
111
72210
72206
72140
Yes, the
Oui, le voyage s'est bien passé.
72146
72208
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72CW


Portable Multifunction Device 100
UI 7200
164
111
72210
Yes, the trip
72206
72140
Oui, le voyage s'est bien passé.
72146
72208
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72CX


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
Oui, le voyage s'est bien passé.
This time, I made it all the way to New Haven.
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72CY


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
72140
Oui, le voyage s'est bien passé.
72190
72146
This time, I made it all the way to New Haven.
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72CZ


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
72140
Oui, le voyage s'est bien passé.
72190
72146
This time, I made it all the way to New Haven.
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DA


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
72140
Yes, the trip went well.
72190
72150
This time, I made it all the way to New Haven.
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DB


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
72140
Oui, le voyage s'est bien passé.
72190
72146
This time, I made it all the way to New Haven.
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DC


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
Oui, le voyage s'est bien passé.
This time, I made it all the way to New Haven.
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DD


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
72140
Oui, le voyage s'est bien passé.
72214
72146
This time, I made it all the way to New Haven.
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DE


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
72140
Oui, le voyage s'est bien passé.
72214
72146
This time, I made it all the way to New Haven.
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DF


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
72140
Yes, the trip went well.
72214
72150
This time, I made it all the way to New Haven.
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DG


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
72140
Yes, the trip went well.
72214
72150
This time, I made it all the way to New Haven.
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DH


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Pierre
Was the test ride a success?
72140
Yes, the trip went well.
72214
72150
This time, I made it all the way to New Haven.
Will there be another demonstration?
Peut-être. Do you want to give pedaling a go?
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DI


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
72216
Ray
72218
7202
We're at the café in the village
The one next to the skating rink
How's it going on the mountain?
Perfect conditions.
How long will you stay there?
72224
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DJ


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
72220
The one next to the skating rink
How's it going on the mountain?
Perfect conditions.
How long will you stay there?
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DK


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
72220
The one next to the skating rink
How's it going on the mountain?
Perfect conditions.
How long will you stay there?
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DL


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
72220
The one next to the skating rink
How's it going on the mountain?
Perfect conditions.
How long will you stay there?
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DM


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
The one next to the skating rink
How's it going on the mountain?
Perfect conditions.
How long will you stay there?
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DN


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
72222
The one next to the skating rink
How's it going on the mountain?
Perfect conditions.
How long will you stay there?
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DO


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
72222
The one next to the skating rink
How's it going on the mountain?
Perfect conditions.
How long will you stay there?
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DP


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
72222
The one next to the skating rink
How's it going on the mountain?
Perfect conditions.
How long will you stay there?
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DQ


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
The one next to the skating rink
How's it going on the mountain?
Perfect conditions.
How long will you stay there?
72224
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DR


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
We're at the café in the village
The one next to the skating rink
How's it going on the mountain?
Perfect conditions.
How long will you stay there?
72224
72226
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DS


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
We're at the café in the village
The one next to the skating rink
How's it going on the mountain?
Perfect conditions.
How long will you stay there?
72224
72226
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DT


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
We're at the café in the village
The one next to the skating rink
How's it going on the mountain?
Perfect conditions.
How long will you stay there?
72224
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DU


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
We're at the café in the village
The one next to the skating rink
How's it going on the mountain?
Perfect conditions.
How long will you stay there?
72224
72228
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DV


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
We're at the café in the village
The one next to the skating rink
How's it going on the mountain?
Perfect conditions.
How long will you stay there?
72224
72228
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DW


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
We're at the café in the village
The one next to the skating rink
How's it going on the mountain?
Perfect conditions.
How long will you stay there?
72224
72228
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DX


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
The one next to the skating rink
How's it going on the mountain?
72230
Perfect conditions.
How long will you stay there?
72224
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DY


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
The one next to the skating rink
How's it going on the mountain?
Perfect conditions.
How long will you stay there?
72224
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72DZ


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
72232
The one next to the skating rink
How's it going on the mountain?
Perfect conditions.
How long will you stay there?
72224
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EA


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
The one next to the skating rink
72234
How's it going on the mountain?
Perfect conditions.
How long will you stay there?
72224
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EB


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
The one next to the skating rink
How's it going on the mountain?
72234
Perfect conditions.
How long will you stay there?
72224
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EC


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
The one next to the skating rink
How's it going on the mountain?
72236
Perfect conditions.
How long will you stay there?
72224
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72ED


Portable Multifunction Device 100-B
UI 7200
4:26 PM
164
111
Riley
72218
7202
We're at the café in the village
72236
The one next to the skating rink
How's it going on the mountain?
Perfect conditions
72236
How long will you stay there?
72224
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EE


Portable Multifunction Device 100-B
UI 7200
4:26 PM
164
111
Riley
We're at the café in the village
The one next to the skating rink
How's it going on the mountain?
Perfect conditions
How long will you stay there?
72238
72240
72244
72242
At least a half hour
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EF


Portable Multifunction Device 100-B
UI 7200
4:26 PM
164
111
Riley
72218
7202
We're at the café in the village
72232
The one next to the skating rink
How's it going on the mountain?
Perfect conditions
How long will you stay there?
72224
At least a half hour
72246
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EG


Portable Multifunction Device 100-B
UI 7200
4:26 PM
164
111
Riley
72218
We're at the café in the village
The one next to the skating rink
72232
How's it going on the mountain?
Perfect conditions
How long will you stay there?
72224
At least a half hour
72246
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EH


Portable Multifunction Device 100-B
UI 7200
4:26 PM
164
111
Riley
We're at the café in the village
The one next to the skating rink
How's it going on the mountain?
Perfect conditions
How long will you stay there?
At least a half hour
72248
72246
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EI


Portable Multifunction Device 100-B
UI 7200
4:26 PM
164
111
Riley
We're at the café in the village
The one next to the skating rink
How's it going on the mountain?
Perfect conditions
How long will you stay there?
At least a half hour
72248
72246
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EJ


Portable Multifunction Device 100-B
UI 7200
4:26 PM
164
111
Riley
We're at the café in the village
The one next to the skating rink
How's it going on the mountain?
Perfect conditions
How long will you stay there?
At least a half hour
72248
72246
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EK


Portable Multifunction Device 100-B
UI 7200
4:26 PM
164
111
Riley
72218
We're at the café in the village
The one next to the skating rink
72236
How's it going on the mountain?
Perfect conditions
How long will you stay there?
72224
At least a half hour
72246
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EL


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
72236
72258
72260
72262
How long will you stay there?
72224
At least a half hour
72246
7204
72250
Great, we'll meet you there in 20
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EM


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
72236
How long will you stay there?
72224
At least a half hour
72246
72256
Great, we'll meet you there in 20
72254
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EN


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
72236
How long will you stay there?
72224
72246
72256
72264
Great, we'll meet you there in 20
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EO


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
72236
How long will you stay there?
72224
72246
72264
Great, we'll meet you there in 20
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EP


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
72236
How long will you stay there?
72224
72246
Great, we'll meet you there in 20
72264
72266
72254
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EQ


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
72236
How long will you stay there?
72224
72246
At least a half hour
72264
Great, we'll meet you there in 20
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72ER


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
72236
72268
How long will you stay there?
72224
72246
At least a half hour
72264
Great, we'll meet you there in 20
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72ES


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
rink
72258
How's it going on the mountain?
72260
Perfect conditions.
72262
How long will you stay there?
72224
At least a half hour
72246
Great, we'll meet you there in 20
72264
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72ET


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
rink
72258
How's it going on the mountain?
72260
72270
Perfect conditions.
72262
How long will you stay there?
72224
72236
At least a half hour
72246
Great, we'll meet you there in 20
72264
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EU


Portable Multifunction Device 100-A
UI 7200
4:26 PM
164
111
Ray
72218
We're at the café in the village
72236
How long will you stay there?
72224
72246
At least a half hour
72264
Great, we'll meet you there in 20
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EV


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Ray
7202
I am headed to the meeting now
72272
If you get a look at the device, can you let me know whether the feature we discussed is still part of the design?
OK
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EW


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Ray
7202
I am headed to the meeting now
72272
If you get a look at the device, can you let me know whether the feature we discussed is still part of the design?
72274
OK
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EX


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Ray
7202
I am headed to the meeting now
72272
If you get a look at the device, can you let me know whether the feature we discussed is still part of the design?
72274
OK
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EY


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Ray
7202
I am headed to the meeting now
72272
If you get a look at the device, can you let me know whether the feature we discussed is still part of the design?
72274
OK
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72EZ


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Ray
7202
I am headed to the meeting now
72272
If you get a look at the device, can you let me know whether the feature we discussed is still part of the design?
OK
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72FA


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Ray
7202
I am headed to the meeting now
72272
If you get a look at the device, can you let me know whether the feature we discussed is still part of the design?
72276
OK
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72FB


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Ray
7202
I am headed to the
If you get a look at the device, can you let me know whether the feature we discussed is still part of the design?
72218
72276
72278
OK
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72FC


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Ray
7202
If you get a look at the device, can you let me know whether the feature we discussed is still part of the design?
72276
72218
72278
OK
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72FD


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Ray
72280
If you get a look at the device, can you let me know whether the feature we discussed is still part of the design?
0:00
72276
I am headed to the meeting now
OK
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72FE


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Ray
72280
72272
If you get a look at the device, can you let me know whether the feature we discussed is still part of the design?
7202
0:05
72282
I am headed to the meeting now
72278
OK
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72FF


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Ray
72280
72272
If you get a look at the device, can you let me know whether the feature we discussed is still part of the design?
55:42
72282
I am headed to the meeting now
7204
OK
72284
Yes, it's in
72290
72286
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72FG


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Ray
7202
I am headed to the meeting now
If you get a look at the device, can you let me know whether the feature we discussed is still part of the design?
OK
72284
Yes, it's in
72292
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72FH


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Ray
If you get a look at the device, can you let me know whether the feature we discussed is still part of the design?
0:15
72272
72294
I am headed to the meeting now
72278
OK
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72FI


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Ray
72272
If you get a look at the device, can you let me know whether the feature we discussed is still part of the design?
0:15
72294
I am headed to the meeting now
72278
OK
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72FJ


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Ray
72272
If you get a look at the device, can you let me know whether the feature we discussed is still part of the design?
72294
72278
OK
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72FK


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Ray
72272
If you get a look at the device, can you let me know whether the feature we discussed is still part of the design?
72294
72278
OK
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72FL


Portable Multifunction Device 100
UI 7200
4:26 PM
164
111
Ray
I am headed to the meeting now
72272
If you get a look at the device, can you let me know whether the feature we discussed is still part of the design?
OK
Q W E R T Y U I O P
A S D F G H J K L
Z X C V B N M
123
space
return
Touch Screen 112
ITD
ITL
ITH
IT0
Intensity of Contact 72155

Figure 72FM


7300
7302 Display a messaging user interface on the display, the messaging user interface including:
a conversation transcript of a messaging session between a user of the electronic device and at least one other user;
a message-input area;
an application area; and
an application-area-display affordance
7304 While displaying the messaging user interface, detect a first input that activates the application-area-display affordance
7306 In response to detecting the first input that activates the application-area-display affordance, in accordance with a determination that the application area is displaying a keyboard at the time the first input is detected, replace display of the keyboard in the application area with concurrent display of:
an application-selection area that displays a plurality of scrollable application-selection affordances, wherein:
the plurality of scrollable application-selection affordances includes a first application-selection affordance that corresponds to a first application that is currently selected; and
a respective application-selection affordance has a respective first size; and
an application-input area that displays one or more activatable objects of the first application
7308 While concurrently displaying the application-selection area and the application-input area, detect a second input that includes a movement of a contact on the touch-sensitive surface that corresponds to movement of a focus selector in a first direction in the application-selection area on the display;
A

Figure 73A


7300
A
7310 In response to detecting the second input:
scroll the plurality of application-selection affordances in the first direction, and
display a second application-selection affordance
7312 While displaying the second application-selection affordance and the one or more activatable objects of the first application in the messaging user interface, detect a third input that activates the second application-selection affordance
7314 In response to detecting the third input that activates the second application-selection affordance:
cease to display the one or more activatable objects of the first application; and
display, in the application-input area, one or more activatable objects of a second application that corresponds to the second application-selection affordance
7316 While scrolling the plurality of application-selection affordances in the first direction, for at least some of the scrolling application-selection affordances, increase the size of a respective application-selection affordance from the respective first size to a respective second size, larger than the respective first size
7318 After scrolling the plurality of application-selection affordances in the first direction, decrease the size of the respective application-selection affordance from the respective second size to the respective first size
B

Figure 73B

7300

B

7320 While scrolling the plurality of application-selection affordances in the first direction, reduce a number of application-selection affordances shown in the application-input area from a first number of application-selection affordances to a second number of application-selection affordances that is less than the first number of application-selection affordances

7322 After scrolling the plurality of application-selection affordances in the first direction, cease to display at least one application-selection affordance of the plurality of scrollable application-selection affordances that was displayed prior to scrolling the plurality of application-selection affordances in the first direction

7324 While the application-input area is displayed at a first size:

display, in the application-input area, an application-input area expansion affordance; and

detect a fourth input that activates the application-input area expansion affordance; and

in response to detecting the fourth input, increase a size of the application-input area from the first size to a second size that is larger than the first size

7326 In response to detecting the first input that activates the application-area-display affordance, in accordance with a determination that the application area is displaying the application-selection area and the application-input area in the application area at the time the first input is detected, replace display of the application-selection area and the application-input area in the application area with display of the keyboard

C

Figure 73C

7300

C

7328 While displaying, in the application-input area, the one or more activatable objects of the second application, detect a fifth input that activates the application-area-display affordance;

in response to detecting the fifth input that activates the application-area-display affordance, replace concurrent display of the application-selection area and the application-input area with display of the keyboard;

while displaying the keyboard in the application area, detect a sixth input that activates the application-area-display affordance;

in response to detecting the sixth input that activates the application area-display affordance:

cease to display the keyboard in the application area, and

concurrently display the application-selection area and the application-input area, wherein the application-selection area concurrently displays a pre-selected set of application-selection affordances that includes the first application-selection affordance

Figure 73D


7400
7402 Display a messaging user interface of a messaging application on the display, the messaging user interface including:
a conversation transcript of a messaging session between a user of the electronic device and at least one other user;
a message-input area; and
an application area that includes:
an application-input area that displays one or more activatable objects of a first application; and
an application-selection area that includes:
a plurality of scrollable application-selection affordances that correspond to a plurality of applications that operate within the messaging user interface, and
a first application-configuration affordance
7404 While displaying the application-configuration affordance in the application-selection area, detect a first input that activates the first application-configuration affordance
7406 In response to detecting the first input, display a first application-management interface for the messaging application that includes:
a plurality of installed-application affordances that correspond to the plurality of applications that operate within the messaging user interface of the messaging application, and
a second application-configuration affordance, that is distinct from the first application-configuration affordance
7408 While displaying the first application-management interface, detect a second input at a location that corresponds to a first installed-application affordance of the plurality of installed-application affordances, wherein the first installed-application affordance corresponds to a first installed application on the electronic device
A

Figure 74A


7400
A
7410 In response to detecting the second input, initiate a process to uninstall at least a component of the first installed application on the mobile device
7412 While displaying the first application-management interface, detect a third input at a location that corresponds to the second application-configuration affordance
7414 In response to detecting the third input, display a second application-management interface for the messaging application that includes:
a plurality of toggles that correspond to the plurality of applications that operate within the messaging user interface of the messaging application, wherein activation of a respective toggle causes a corresponding application to toggle between a hidden state and a revealed state in the messaging user interface of the messaging application
7416 The first application-configuration affordance is located in a fixed position relative to the plurality of application-selection affordances that correspond to the plurality of applications
7418 Display, in the first application-management interface, a search-input area;
receive input for the search-input area; and
perform a search, using the input in the search-input area, for a plurality of applications that are operable within the messaging user interface
B

Figure 74B

7400

B

7420 While displaying the second application-management interface, detect a fourth input at a location that corresponds to a first toggle of the plurality of toggles, wherein the first toggle corresponds to a second application of the plurality of applications that operate within the messaging user interface of the messaging application;

in response to detecting the fourth input:

in accordance with a determination that a current state of the second application is a revealed state, toggle the state of second application from the revealed state to the hidden state; and

in accordance with a determination that the current state of the second application is a hidden state, toggle the second application from the hidden state to the revealed state;

after toggling the first toggle, redisplay the application-selection area that includes the plurality of scrollable application-selection affordances, wherein:

in accordance with a determination that the second application is in the revealed state, display a first application-selection affordance that corresponds to the second application in the redisplayed application-selection area; and

in accordance with a determination that the second application is in the hidden state, forgo displaying the first application-selection affordance that corresponds to the second application in the redisplayed application-selection area

C

Figure 74C

7400

C

7422 Display, in the second application-management interface, a plurality of arrangement indicia that correspond to the plurality of applications that operate within the messaging user interface of the messaging application, wherein the plurality of arrangement indicia include:

a first arrangement indicator that corresponds to a third application that operates within the messaging interface, and

a second arrangement indicator that corresponds to a fourth application that operates within the messaging interface;

while displaying the second application-management interface, detect a fifth input that includes a movement of a contact on the touch-sensitive surface from a first location that corresponds to the first arrangement indicator; and

in response to detecting the fifth input:

in accordance with a determination that movement of the contact on the touch-sensitive surface meets rearrangement criteria, change an order of the first arrangement indicator relative to the second arrangement indicator

7424 After changing the order of the first arrangement indicator relative to the second arrangement indicator, redisplay the application-selection area that includes the plurality of scrollable application-selection affordances; and display, in the application-selection area:

a second application-selection affordance of the plurality of scrollable application-selection affordances, wherein the second application-selection affordance corresponds to the third application that operates within the messaging interface, and

a third application-selection affordance of the plurality of scrollable application-selection affordances, wherein the third application-selection affordance corresponds to the fourth application that operates within the messaging user interface,

wherein an order of the second application-selection affordance relative to the third application-selection affordance corresponds to the order of the first arrangement indicator relative to the second arrangement indicator

Figure 74D

7500

7502 Display a messaging user interface on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user

↓

7504 Receive a first message within the messaging session from an electronic device that corresponds to another user included in the messaging session, wherein the first message includes foreign language text

↓

7506 In response to receiving the first message, display the first message in the conversation transcript

↓

7508 Detect a first input at a first location that corresponds to the foreign language text in the first message

↓

7510 In response to detecting the first input at the first location that corresponds to the foreign language text:

in accordance with a determination that the first input meets translation criteria, display a translation of the foreign language text; and

in accordance with a determination that the first input meets option-display criteria, display a plurality of activatable indicia

7512 The electronic device includes a touch-sensitive surface and one or more sensors configured to detect intensities of contacts with the touch-sensitive surface;

detecting the input at the first location that corresponds to the foreign language text includes detecting a contact on the touch-sensitive surface;

the determination that the first input meets translation criteria includes a determination that a characteristic intensity of the contact on the touch-sensitive surface meets translation intensity criteria; and

the determination that the first input meets option-display criteria includes a determination that the characteristic intensity of the contact with the touch-sensitive surface meets option-display intensity criteria

A

Figure 75A

7500

A

7514 The electronic device includes a touch-sensitive surface;
detecting the input at the first location that corresponds to the foreign language text includes detecting a contact on the touch-sensitive surface;
the determination that the first input meets translation criteria includes a determination that a duration of the contact on the touch-sensitive surface meets translation duration criteria; and
the determination that the first input meets option-display criteria includes a determination that a duration of the contact on the touch-sensitive surface meets option display duration criteria

7516 The electronic device includes a touch-sensitive surface and one or more sensors configured to detect proximity of an input object above the touch-sensitive surface;
detecting the input at the first location that corresponds to the foreign language text includes detecting input by the input object; and
the determination that the first input meets translation criteria includes a determination that the input by the input object meets hover proximity criteria

7518 The determination that the first input meets translation criteria includes a determination that a focus selector that corresponds to the first input moved to the first location that corresponds to the foreign language text from a second location that corresponds to another part of the foreign language text in the first message

7520 Displaying the translation of the foreign language text in accordance with the determination that the first input meets translation criteria includes
displaying a translation of a first portion of the foreign language text;
while displaying the translation of the first portion of the foreign language text, detecting movement of a focus selector that corresponds to the first input to a second location that corresponds to another part of the foreign language text; and,
in response to detecting the movement of the focus selector to the second location, displaying a translation of a second portion of the foreign language text

B

Figure 75B

7500

B

7522 Receive a second message within the messaging session;
in accordance with a determination that the second message includes foreign language text and in accordance with a determination that the option-display criteria are met, display, in a plurality of activatable indicia, an activatable indicator which, when activated, causes display of a translation of the foreign language text in the second message; and
in accordance with a determination that the second message does not include foreign language text and in accordance with a determination that the option-display criteria are met, display a plurality of activatable indicia, without displaying the activatable indicator

7524 While displaying the translation of the foreign language text, determine whether the translation of the foreign language text meets translation-display-cessation criteria;
in accordance with a determination that the displayed translation of the foreign language text meets the translation-display-cessation criteria, cease to display the translation of the foreign language text and re-displaying the corresponding foreign language text; and
in accordance with a determination that the displayed translation of the foreign language text does not meet the translation-display-cessation criteria, continue to display the translation of the foreign language text

7526 While displaying the translation of the foreign language text, detecting a second input at a third location that corresponds to the translation of the foreign language text; and,
in response to detecting the second input at the third location that corresponds to the translated foreign language text, in accordance with a determination that the second input meets re-display criteria, ceasing to display the translation of the foreign language text and re-displaying the corresponding foreign language text

C

Figure 75C

7500

C

7528 While displaying the translation of the foreign language text, detect a third input at a fourth location that corresponds to the translation of the foreign language text; and,

in response to detecting the third input at the fourth location that corresponds to the translation of the foreign language text, in accordance with a determination that the third input meets the option-display criteria, display a plurality of activatable indicia, wherein the plurality of activatable indicia include an activatable indicator which, when activated, causes re-display of the original, un-translated foreign language text

Figure 75D


7600
7602 Display a messaging user interface on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user
7604 Receive a first message within the messaging session from an electronic device that corresponds to another user included in the messaging session, wherein the first message includes foreign language text
7606 In response to receiving the first message, display the first message in the conversation transcript
7608 Detect a first input at a location that corresponds to the foreign language text in the first message
7610 In response to detecting the first input at the location that corresponds to the foreign language text:
in accordance with a determination that the first input meets translation criteria, perform a foreign-language-text-translation action; and
in accordance with a determination that the first input does not meet the translation criteria, forgo performance of the foreign-language-text-translation action
7612 The electronic device includes a touch-sensitive surface and one or more sensors configured to detect intensities of contacts with the touch-sensitive surface;
detecting the first input at the first location that corresponds to the foreign language text includes detecting a contact on the touch-sensitive surface; and
in accordance with a determination that the first input meets temporary-translation-display criteria, performing the foreign-language-text-translation action includes temporarily displaying a translation of the foreign language text
B
A

Figure 76A

7600

A

7614 In accordance with a determination that the first input meets fixed-translation-display criteria, perform the foreign-language-text-translation action includes fixedly replacing display of the foreign language text with the translation of the foreign language text

7616 The determination that the first input meets the fixed-translation-display criteria includes a determination that a characteristic intensity of the contact on the touch-sensitive surface meets fixed translation intensity criteria

7618 The determination that the first input meets the fixed-translation-display criteria includes a determination that the duration of the contact on the touch-sensitive surface meets fixed translation duration criteria

7612

B

7620 Performing the foreign-language-text-translation action includes:

displaying a translation of the foreign language text;

determining whether lift-off of the contact from the touch-sensitive surface has occurred; and,

in response to detecting lift-off of the contact from the touch-sensitive surface, ceasing to display the translation of the foreign language text

7622 Performing the foreign-language-text-translation action includes displaying, over the conversation transcript, a platter that includes a plurality of activatable indicia, wherein the plurality of activatable indicia includes a translation indicator which, when activated, causes display of a translation for at least a portion of the foreign language text

C

Figure 76B

7600

C

7624 The electronic device includes a touch-sensitive surface and one or more sensors configured to detect proximity of an input object above the touch-sensitive surface;
detecting the input at the first location that corresponds to the foreign language text includes detecting input by the input object; and
the determination that the first input meets translation criteria includes a determination that the input by the input object meets hover proximity criteria

7626 The determination that the first input meets translation criteria includes a determination that a focus selector that corresponds to the first input moved to the first location that corresponds to the foreign language text from a second location that corresponds to another part of the foreign language text

7628 Displaying the translation of the foreign language text in accordance with the determination that the first input meets translation criteria includes
displaying a translation of a first portion of the foreign language text;
while displaying the translation of the first portion of the foreign language text, detecting movement of a focus selector that corresponds to the first input to a second location that corresponds to another part of the foreign language text; and,
in response to detecting the movement of the focus selector to the second location, displaying a translation of a second portion of the foreign language text

Figure 76C

DEVICES, METHODS, AND GRAPHICAL USER INTERFACES FOR MESSAGING

RELATED APPLICATIONS

[0001] This application is a continuation of U.S. patent application Ser. No. 16/544,787, filed Aug. 19, 2019, which is a continuation of U.S. patent application Ser. No. 16/194,237, filed Nov. 16, 2018, which is a continuation of PCT International Application Serial No. PCT/US2017/033396, filed May 18, 2017, which claims priority to: (1) Denmark Application No. 201670655, filed Aug. 26, 2016; (2) Denmark Application No. 201670636, filed Aug. 24, 2016; (3) U.S. Provisional Application Ser. No. 62/506,614, filed May 16, 2017; (4) U.S. Provisional Application Ser. No. 62/349,114, filed Jun. 12, 2016; (5) U.S. Provisional Application Ser. No. 62/349,116, filed Jun. 12, 2016; (6) U.S. Provisional Application Ser. No. 62/339,078, filed May 19, 2016; and (7) U.S. Provisional Application Ser. No. 62/338,502, filed May 18, 2016, entitled "Devices, Methods, and Graphical User Interfaces for Messaging," which are all incorporated by reference herein in their entireties.

TECHNICAL FIELD

[0002] This relates generally to electronic devices with touch-sensitive surfaces, including but not limited to electronic devices with touch-sensitive surfaces that send and receive messages, such as instant messages.

BACKGROUND

[0003] The use of touch-sensitive surfaces as input devices for computers and other electronic computing devices has increased significantly in recent years. Exemplary touch-sensitive surfaces include touchpads and touch-screen displays. Such devices are often used to send messages, such as instant messages, between users using messaging applications.

[0004] But current messaging applications have numerous drawbacks and limitations. For example, they are limited in their ability to easily: acknowledge messages; edit previously sent messages; express what a user is trying to communicate; display private messages; synchronize viewing of content between users; incorporate handwritten inputs; quickly locate content in a message transcript; integrate a camera; integrate search and sharing; integrate interactive applications; integrate stickers; make payments; interact with avatars; make suggestions; navigate among interactive applications; manage interactive applications; translate foreign language text; combine messages into a group; and flag messages.

SUMMARY

[0005] Accordingly, there is a need for electronic devices with improved methods and interfaces for messaging. Such methods and interfaces optionally complement or replace conventional methods for messaging. Such methods and interfaces change the number, extent, and/or nature of the inputs from a user and produce a more efficient human-machine interface. For battery-operated devices, such methods and interfaces conserve power and increase the time between battery charges.

[0006] The above deficiencies and other problems associated with user interfaces for electronic devices with touch-sensitive surfaces are reduced or eliminated by the disclosed devices. In some embodiments, the device is a desktop computer. In some embodiments, the device is portable (e.g., a notebook computer, tablet computer, or handheld device). In some embodiments, the device is a personal electronic device (e.g., a wearable electronic device, such as a watch). In some embodiments, the device has a touchpad. In some embodiments, the device has a touch-sensitive display (also known as a "touch screen" or "touch-screen display"). In some embodiments, the device has a graphical user interface (GUI), one or more processors, memory and one or more modules, programs or sets of instructions stored in the memory for performing multiple functions. In some embodiments, the user interacts with the GUI primarily through stylus and/or finger contacts and gestures on the touch-sensitive surface. In some embodiments, the functions optionally include image editing, drawing, presenting, word processing, spreadsheet making, game playing, telephoning, video conferencing, e-mailing, instant messaging, workout support, digital photographing, digital videoing, web browsing, digital music playing, note taking, and/or digital video playing. Executable instructions for performing these functions are, optionally, included in a non-transitory computer readable storage medium or other computer program product configured for execution by one or more processors.

[0007] There is a need for electronic devices with improved methods and interfaces for applying an acknowledgement to a message region in a conversation transcript. Such methods and interfaces may complement or replace conventional methods for applying an acknowledgement to a message region in a conversation transcript. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0008] In accordance with some embodiments, a method of applying an acknowledgement to a message region in a conversation transcript displayed on a display of an electronic device includes, displaying a messaging user interface (e.g., of a messaging application) on the display, where the messaging user interface includes a conversation transcript of a messaging session between a user of the electronic device and at least one other user (e.g., of another electronic device). The method further includes receiving a first message within the messaging session from an electronic device (e.g., a second electronic device) that corresponds to another user included in the messaging session, and in response to receiving the first message, displaying the first message in a first message region in the conversation transcript on the display. The electronic device detects a first input by a first contact at a location on the touch-sensitive surface that corresponds to a location of the first message region in the conversation transcript, and in response to detecting the first input, displays an acknowledgement selection affordance at a location in the messaging interface that corresponds to the first message region, where the acknowledgement selection affordance displays a plurality of acknowledgement options. Next, the method includes detecting a second input by a second contact at a location on the touch-sensitive surface that corresponds to a location of a first acknowledgement option in the acknowledgement selection affordance, and in response to detecting the second input, applying the first acknowledgement option to the first message region.

[0009] In accordance with some embodiments, an electronic device includes a display unit configured to display a messaging user interface on the display unit, the messaging

user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a touch-sensitive surface unit configured to detect contacts; and a processing unit coupled with the display unit and the touch-sensitive surface unit. The processing unit configured to: receive a first message within the messaging session from an electronic device that corresponds to another user included in the messaging session; and in response to receiving the first message, display the first message in a first message region in the conversation transcript on the display unit. The processing unit is further configured to detect a first input by a first contact at a location on the touch-sensitive surface unit that corresponds to a location of the first message region in the conversation transcript; and in response to detecting the first input, display an acknowledgement selection affordance at a location in the messaging interface that corresponds to the first message region, wherein the acknowledgement selection affordance displays a plurality of acknowledgement options. The processing unit is further configured to detect a second input by a second contact at a location on the touch-sensitive surface unit that corresponds to a location of a first acknowledgement option in the acknowledgement selection affordance; and, in response to detecting the second input, apply the first acknowledgement option to the first message region.

[0010] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for applying an acknowledgement to a message region in a conversation transcript, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for applying an acknowledgement to a message region in a conversation transcript.

[0011] There is a need for electronic devices with improved methods and interfaces for editing sent messages. Such methods and interfaces may complement or replace conventional methods for editing sent messages. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0012] In accordance with some embodiments, a method of editing messages, performed at an electronic device (e.g., a first electronic device) having one or more processors, memory, a touch-sensitive surface, and a display, includes displaying a messaging user interface on the display. The messaging user interface includes a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a first message region that includes a first message in the messaging session that was sent from the electronic device of the user to the at least one other user in the messaging session. The method further includes detecting a first input that corresponds to a request to edit the first message, and in response to detecting the first input, displaying a message editing interface for the first message that includes the first message, a keyboard, and an update affordance, and while displaying the message editing interface for the first message, detecting one or more inputs that revise the first message, displaying a revised version of the first message; and detecting an input that activates the update affordance.

[0013] The method further includes, in response to detecting the input that activates the update affordance: ceasing to display the message editing interface for the first message; displaying the revised version of the first message in place of the first message in the conversation transcript; displaying at least one indication of the revision of the first message in the conversation transcript; and transmitting the revised version of the first message to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the revised version of the first message in place of the first message in a conversation transcript that corresponds to the messaging session, with at least one indication of the revision of the first message in the conversation transcript.

[0014] In accordance with some embodiments, an electronic device includes a display unit configured to display a messaging user interface on the display unit, a touch-sensitive surface unit configured to detect contacts, and a processing unit coupled with the display unit and the touch-sensitive surface unit. The messaging user interface includes a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a first message region that includes a first message in the messaging session that was sent from the electronic device of the user to the at least one other user in the messaging session. The processing unit is configured to: detect a first input that corresponds to a request to edit the first message; and in response to detecting the first input, display a message editing interface for the first message that includes the first message, a keyboard, and an update affordance. The processing unit is further configured, while displaying the message editing interface for the first message, to detect one or more inputs that revise the first message; display a revised version of the first message; and detect an input that activates the update affordance; and, in response to detecting the input that activates the update affordance: cease to display the message editing interface for the first message; display the revised version of the first message in place of the first message in the conversation transcript; display at least one indication of the revision of the first message in the conversation transcript; and transmit the revised version of the first message to one or more electronic devices that correspond to the at least one other user included in the messaging session. The one or more electronic devices display the revised version of the first message in place of the first message in a conversation transcript that corresponds to the messaging session, with at least one indication of the revision of the first message in the conversation transcript.

[0015] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for editing sent messages, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for editing sent messages in a messaging application.

[0016] There is a need for electronic devices with improved methods and interfaces for displaying versions of a sent message. Such methods and interfaces may complement or replace conventional methods for displaying versions of a sent message. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0017] In accordance with some embodiments, a method, performed at an electronic device having one or more processors, memory, a touch-sensitive surface, and a display, includes displaying a messaging user interface on the display, the messaging user interface including: a conversation

transcript of a messaging session between a user of the electronic device and at least one other user, and a first message region that includes a current version of a first message in the messaging session, wherein the conversation transcript includes an indication that the current version of the first message is a revised version of the first message in the conversation transcript. The method further includes detecting an input that corresponds to a request to see versions of the first message; and, in response to detecting the input that corresponds to the request to see versions of the first message, displaying a versions user interface that includes the current version of the first message and one or more prior versions of the first message.

[0018] In accordance with some embodiments, an electronic device includes a display unit configured to display a messaging user interface on the display unit, a touch-sensitive surface unit configured to detect contacts, and a processing unit coupled with the display unit and the touch-sensitive surface unit. The messaging user interface includes a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a first message region that includes a current version of a first message in the messaging session, wherein the conversation transcript includes an indication that the current version of the first message is a revised version of the first message in the conversation transcript. The processing unit is configured to detect an input that corresponds to a request to see versions of the first message; and, in response to detecting the input that corresponds to the request to see versions of the first message, display a versions user interface that includes the current version of the first message and one or more prior versions of the first message.

[0019] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for displaying versions of a sent message, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for displaying versions of a sent message in a messaging application.

[0020] There is a need for electronic devices with improved methods and interfaces for selecting an impact effect for a message. Such methods and interfaces may complement or replace conventional methods for selecting an impact effect for a message. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0021] In accordance with some embodiments, a method, performed at an electronic device having one or more processors, memory, a touch-sensitive surface, and a display, includes displaying a messaging user interface on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a message-input area that includes a first message input. The method further includes, while displaying the messaging user interface, detecting a first input by a first contact at a location on the touch-sensitive surface that corresponds to a location in the message-input area; in response to detecting the first input by the first contact, displaying an impact selection interface that includes a plurality of impact effect options; while displaying the impact selection interface, detecting a second input by a second contact at a location on the touch-sensitive surface that corresponds to a location of a first impact effect option in the plurality of impact effect options; and, in response to detecting the second user input by a second contact, displaying a preview that applies the first impact effect option to the first message input.

[0022] In accordance with some embodiments, an electronic device includes a display unit configured to display a messaging user interface on the display unit, a touch-sensitive surface unit configured to detect contacts, and a processing unit coupled with the display unit and the touch-sensitive surface unit. The messaging user interface includes a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a message-input area that includes a first message input. The processing unit is configured to: while displaying the messaging user interface, detect a first input by a first contact at a location on the touch-sensitive surface unit that corresponds to a location in the message-input area; and in response to detecting the first input by the first contact, display an impact selection interface that includes a plurality of impact effect options. The processing unit is further configured to: while displaying the impact selection interface, detect a second input by a second contact at a location on the touch-sensitive surface unit that corresponds to a location of a first impact effect option in the plurality of impact effect options; and, in response to detecting the second user input by a second contact, display a preview that applies the first impact effect option to the first message input.

[0023] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for selecting an impact effect for a message, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for selecting an impact effect for a message in a messaging application.

[0024] There is a need for electronic devices with improved methods and interfaces for concealing and revealing a message. Such methods and interfaces may complement or replace conventional methods for concealing and revealing a message. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0025] In accordance with some embodiments, a method, performed at an electronic device having one or more processors, memory, a touch-sensitive surface, and a display, includes displaying a messaging user interface on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, including a first other user, and a message region in the conversation transcript for a message received from the first other user, the message region including one or more screen elements that conceal the message received from the first other user. The method further includes detecting a first input by a contact at a location on the touch-sensitive surface that corresponds to the message region with the concealed message; and, in response to detecting the first input by the contact, revealing the concealed message in the message region.

[0026] In accordance with some embodiments, an electronic device includes a display unit configured to display a messaging user interface on the display unit, a touch-sensitive surface unit configured to detect contacts, and a processing unit coupled with the display unit and the touch-

sensitive surface unit. The messaging user interface includes a conversation transcript of a messaging session between a user of the electronic device and at least one other user, including a first other user, and a message region in the conversation transcript for a message received from the first other user, the message region including one or more screen elements that conceal the message received from the first other user. The processing unit is further configured to: detect a first input by a contact at a location on the touch-sensitive surface unit that corresponds to the message region with the concealed message; and, reveal the concealed message in the message region in response to detecting the first input by the contact.

[0027] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for concealing and revealing a message, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for concealing and revealing a message in a messaging application.

[0028] There is a need for electronic devices with improved methods and interfaces for displaying enhanced message content in a messaging application. Such methods and interfaces may complement or replace conventional methods for displaying enhanced message content in a messaging application. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0029] In accordance with some embodiments, a method, performed at an electronic device having one or more processors, memory, a touch-sensitive surface, and a display, includes displaying a messaging user interface on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, including a first other user, receiving a first message within the messaging session from an electronic device that corresponds to the first other user included in the messaging session, and determining whether the first message includes an enhanced message content trigger. The method further includes, in accordance with a determination that the first message includes the enhanced message content trigger, displaying the first message in a first message region in the conversation transcript on the display, and displaying enhanced message content that corresponds to the trigger, wherein the enhanced message content includes content that applies an effect to at least one message region other than the first message region in the conversation transcript. The method also includes, in accordance with a determination that the first message does not include the enhanced message content trigger, displaying the first message in a first message region in the conversation transcript on the display (e.g., without the enhanced message content).

[0030] In accordance with some embodiments, an electronic device includes a display unit configured to display a messaging user interface on the display unit, a touch-sensitive surface unit configured to detect contacts, and a processing unit coupled with the display unit and the touch-sensitive surface unit. The messaging user interface includes a conversation transcript of a messaging session between a user of the electronic device and at least one other user, including a first other user. The processing unit is configured to receive a first message within the messaging session from an electronic device that corresponds to the first other user included in the messaging session, and determine whether the first message includes an enhanced message content trigger. The processing unit is further configured to, in accordance with a determination that the first message includes the enhanced message content trigger, display the first message in a first message region in the conversation transcript on the display unit, and display enhanced message content that corresponds to the trigger, wherein the enhanced message content includes content that applies an effect to at least one message region other than the first message region in the conversation transcript. In addition, the processing unit is configure to, in accordance with a determination that the first message does not include the enhanced message content trigger, display the first message in a first message region in the conversation transcript on the display unit.

[0031] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for displaying enhanced message content in a messaging application, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for displaying enhanced message content in a messaging application.

[0032] There is a need for electronic devices with improved methods and interfaces for displaying combinable content in a messaging application. Such methods and interfaces may complement or replace conventional methods for displaying combinable content in a messaging application. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0033] In accordance with some embodiments, a method, performed at an electronic device having one or more processors, memory, a touch-sensitive surface, and a display, includes displaying a messaging user interface on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, including a first other user, and a message input area. The method further includes receiving a first message within the messaging session from an electronic device that corresponds to the first other user included in the messaging session, wherein the first message includes first combinable content, in response to receiving the first message, displaying the first message in a first message region in the conversation transcript on the display, receiving input of a second message in the message-input area, and while the second message is displayed in the message-input area, detecting an input to send the second message to the messaging session. The method further includes, in response to detecting the input to send the second message to the messaging session: in accordance with a determination that the second message contains second combinable content and the second combinable content and the first combinable content are parts of a predefined combination, displaying content that corresponds to the predefined combination in the conversation transcript on the display; and in accordance with a determination that the second message does not contain second combinable content that forms a predefined combination with the first combinable content, displaying the second message in a second message region in the conversation transcript on the display (e.g., without displaying content that corresponds to a predefined combination in the conversation transcript on the display).

[0034] In accordance with some embodiments, an electronic device includes a display unit configured to display a messaging user interface on the display unit, a touch-sensitive surface unit configured to detect contacts, and a processing unit coupled with the display unit and the touch-sensitive surface unit. The messaging user interface includes a conversation transcript of a messaging session between a user of the electronic device and at least one other user, including a first other user, and a message input area. The processing unit is configured to: receive a first message within the messaging session from an electronic device that corresponds to the first other user included in the messaging session, wherein the first message includes first combinable content; in response to receiving the first message, display the first message in a first message region in the conversation transcript on the display unit; receive input of a second message in the message-input area; and while the second message is displayed in the message-input area, detect an input to send the second message to the messaging session. The processing unit is further configured to, in response to detecting the input to send the second message to the messaging session: in accordance with a determination that the second message contains second combinable content and the second combinable content and the first combinable content are parts of a predefined combination, display content that corresponds to the predefined combination in the conversation transcript on the display unit; and in accordance with a determination that the second message does not contain second combinable content that forms a predefined combination with the first combinable content, display the second message in a second message region in the conversation transcript on the display unit (i.e., without displaying content that corresponds to a predefined combination in the conversation transcript on the display).

[0035] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for displaying combinable content in a messaging application, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for displaying combinable content in a messaging application.

[0036] There is a need for electronic devices with improved methods and interfaces for synchronizing media presentation in a messaging application. Such methods and interfaces optionally complement or replace conventional methods for synchronizing media presentation in a messaging application. Such methods and interfaces produce more efficient human-machine interfaces by allowing users to easily view media content in a synchronized fashion directly within a messaging application (and without having to be co-located with another user viewing the media content and without having to use inefficient techniques to enable synchronized viewing). For battery-operated devices, such methods and interfaces increase user satisfaction with their devices, conserve power, and increase the time between battery charges. Furthermore, allowing users to easily view media content in a synchronized fashion directly within a messaging application enhances the operability of the device and makes the user-device interface (e.g., in the messaging application) more efficient (e.g., by allowing for efficient synchronized viewing of media items) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

[0037] In accordance with some embodiments, a method is performed at an electronic device with a display and a touch-sensitive surface. The method includes: displaying, on the display, a messaging user interface, the messaging user interface including a conversation transcript of a messaging session between a user of the first electronic device and at least one other user. In some embodiments, the conversation transcript includes a representation of a media item that is displayed at a chronological position within the conversation transcript, and the messaging session is configured to allow synchronized viewing of the media item by the user at the first electronic device and the at least one other user at a second electronic device that is distinct from the first electronic device. The method also includes: receiving a first request for synchronized viewing of the media item within the messaging user interface. In response to receiving the first request, the method includes: initiating playing of content corresponding to the media item while the representation of the media item is displayed at the chronological position within the conversation transcript. After initiating playing of the content corresponding to the media item, the method includes: displaying the playing content corresponding to the media item at a fixed position within the messaging user interface that is different than the chronological position. While displaying the playing content corresponding to the media item at the fixed position, the method includes: displaying messages exchanged between the user and the at least one other user below the playing content corresponding to the media item; and detecting an end of the content corresponding to the media item. In response to detecting the end of the content corresponding to the media item, the method includes: ceasing to display the content corresponding to the media item at the fixed position.

[0038] In accordance with some embodiments, an electronic device (e.g., electronic device **2200**, FIG. **22**) includes a display unit configured to display a user interface, a touch-sensitive surface unit to receive contacts, one or more sensor units to detect intensities of contacts with the touch-sensitive surface unit; and a processing unit coupled with the display unit, the touch-sensitive surface unit, and the one or more sensor units. The processing unit is configured to (or one or more components thereof, such as the units **2210-2216** shown in FIG. **22** are configured to) display, on the display, a messaging user interface, the messaging user interface including a conversation transcript of a messaging session between a user of the first electronic device and at least one other user. In some embodiments, the conversation transcript includes a representation of a media item that is displayed at a chronological position within the conversation transcript, and the messaging session is configured to allow synchronized viewing of the media item by the user at the first electronic device and the at least one other user at a second electronic device that is distinct from the first electronic device. The processing unit is also configured to: receive a first request for synchronized viewing of the media item within the messaging user interface and, in response to receiving the first request, initiate playing of content corresponding to the media item while the representation of the media item is displayed at the chronological position within the conversation transcript. After initiating playing of the content corresponding to the media item, the processing unit

is configured to: display the playing content corresponding to the media item at a fixed position within the messaging user interface that is different than the chronological position. While displaying the playing content corresponding to the media item at the fixed position, the processing unit is configured to: display messages exchanged between the user and the at least one other user below the playing content corresponding to the media item and detect an end of the content corresponding to the media item. In response to detecting the end of the content corresponding to the media item, the processing unit is configured to: cease to display the content corresponding to the media item at the fixed position.

[0039] Thus, electronic devices with displays and touch-sensitive surfaces are provided with faster, more efficient methods and interfaces for viewing media content in a synchronized fashion within a messaging application, thereby increasing the effectiveness, efficiency, operability, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for viewing media in a messaging application.

[0040] There is a need for electronic devices with improved methods and interfaces for using handwriting inputs in a messaging application. Such methods and interfaces optionally complement or replace conventional methods for entering messages in a messaging application. Such methods and interfaces help improve user satisfaction with their devices and produce more efficient human-machine interfaces by allowing users, e.g., to simply rotate their device in order to begin entering handwritten inputs. Such methods and interfaces also produce more efficient human-machine interfaces by allowing for auto-replacing of typed inputs with handwritten inputs and by allowing users to intuitively create keyboards with handwritten characters as keys, thus improving operability of the devices. For battery-operated devices, such methods and interfaces conserve power and increase the time between battery charges. Furthermore, allowing users to simply rotate their devices in order to begin entering handwritten inputs, auto-replacing typed inputs, and creating keyboards with handwritten characters as keys all contribute to enhancing the operability of the devices and making the user-device interfaces (e.g., in the messaging application) more efficient (e.g., by allowing users to easily customize their message content with handwritten inputs) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently. For example, the user need not leave the messaging application, open and use a different application to input or locate handwritten inputs, and then return to use those inputs in the messaging application. Instead, the user simple provides and/or selects custom handwritten inputs directly within the messaging application.

[0041] In accordance with some embodiments, a method is performed at an electronic device with a display and a touch-sensitive surface. The method includes: while the electronic device is in a portrait orientation, displaying, on the display, a messaging user interface, the messaging user interface including a virtual keyboard. The method also includes: detecting a change in the orientation of the electronic device from the portrait orientation to a landscape orientation; and, in response to detecting the change in the orientation of the electronic device: ceasing to display the virtual keyboard and displaying, on the display, a handwriting input area that is configured to accept handwritten input from a user of the electronic device.

[0042] In accordance with some embodiments, an electronic device includes a display unit configured to display a user interface, a touch-sensitive surface unit to receive contacts, one or more sensor units to detect intensities of contacts with the touch-sensitive surface unit; and a processing unit coupled with the display unit, the touch-sensitive surface unit, and the one or more sensor units. The processing unit is configured to: while the electronic device is in a portrait orientation, display, on the display, a messaging user interface, the messaging user interface including a virtual keyboard; detect a change in the orientation of the electronic device from the portrait orientation to a landscape orientation; and, in response to detecting the change in the orientation of the electronic device: cease to display the virtual keyboard; and display, on the display, a handwriting input area that is configured to accept handwritten input from a user of the electronic device.

[0043] In accordance with some embodiments, a method is performed at an electronic device with a display and a touch-sensitive surface. The method includes: displaying, on the display: a messaging user interface, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a virtual keyboard, and a message-input area. The method also includes: receiving, at the virtual keyboard, a plurality of typing inputs. While receiving the plurality of typing inputs, the method includes: determining whether one or more typing inputs of the plurality of typing inputs match a stored sequence of characters that is associated with stored handwritten input from the user. In accordance with a determination that the one or more typing inputs match the stored sequence of characters, the method includes: displaying at a first location, proximate to a first set of characters that is displayed within the message-input area, a selectable representation of the stored handwritten input. In some embodiments, the first set of characters is displayed within the message-input area and includes characters that correspond to the one or more typing inputs that match the stored sequence of characters. The method also includes: detecting, via the touch-sensitive surface, a selection of the selectable representation of the stored handwritten input; and, in response to detecting the selection of the selectable representation of the stored handwritten input: ceasing to display the selectable representation of the stored handwritten input at the first location; and replacing display, within the message-input area, of the first set of characters that correspond to the one or more typing inputs with display of a representation of the stored handwritten input.

[0044] In accordance with some embodiments, an electronic device includes a display unit configured to display a user interface, a touch-sensitive surface unit to receive contacts, one or more sensor units to detect intensities of contacts with the touch-sensitive surface unit; and a processing unit coupled with the display unit, the touch-sensitive surface unit, and the one or more sensor units. The processing unit is configured to: display, on the display: a messaging user interface, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a virtual keyboard, and a message-input area. The processing unit is configured to: receive, at the virtual keyboard, a plurality of typing inputs; while receiving the

plurality of typing inputs, determine whether one or more typing inputs of the plurality of typing inputs match a stored sequence of characters that is associated with stored handwritten input from the user; in accordance with a determination that the one or more typing inputs match the stored sequence of characters, display at a first location, proximate to a first set of characters that is displayed within the message-input area, a selectable representation of the stored handwritten input, and the first set of characters is displayed within the message-input area and includes characters that correspond to the one or more typing inputs that match the stored sequence of characters; detect, via the touch-sensitive surface, a selection of the selectable representation of the stored handwritten input; and, in response to detecting the selection of the selectable representation of the stored handwritten input: cease to display the selectable representation of the stored handwritten input at the first location; and replace display, within the message-input area, of the first set of characters that correspond to the one or more typing inputs with display of a representation of the stored handwritten input.

[0045] In accordance with some embodiments, a method is performed at an electronic device with a display and a touch-sensitive surface. The method includes: detecting, via the touch-sensitive surface, a first input; in response to detecting the first input, presenting, on the display, a keyboard preparation user interface; while presenting the keyboard preparation user interface, receiving, via the touch-sensitive surface, handwritten inputs that correspond to a predefined set of training characters; after receiving the handwritten inputs, detecting a second input that corresponds to a request to display a messaging user interface that includes a message-input area and a virtual keyboard with a plurality of keys, wherein a first key of the plurality of keys is associated with a first handwritten input of the received handwritten inputs; in response to detecting the second input, displaying the messaging user interface that includes the message-input area and the virtual keyboard with the plurality of keys; receiving, via the touch-sensitive surface, a selection of the first key; and in response to receiving the selection of the first key, outputting a representation of the first handwritten input within the message-input area.

[0046] In accordance with some embodiments, an electronic device includes a display unit configured to display a user interface, a touch-sensitive surface unit to receive contacts, one or more sensor units to detect intensities of contacts with the touch-sensitive surface unit; and a processing unit coupled with the display unit, the touch-sensitive surface unit, and the one or more sensor units. The processing unit is configured to: detect, via the touch-sensitive surface, a first input; in response to detecting the first input, present, on the display, a keyboard preparation user interface; while presenting the keyboard preparation user interface, receive, via the touch-sensitive surface, handwritten inputs that correspond to a predefined set of training characters; after receiving the handwritten inputs, detect a second input that corresponds to a request to display a messaging user interface that includes a message-input area and a virtual keyboard with a plurality of keys, wherein a first key of the plurality of keys is associated with a first handwritten input of the received handwritten inputs; in response to detecting the second input, display the messaging user interface that includes the message-input area and the virtual keyboard with the plurality of keys; receive, via the touch-sensitive surface, a selection of the first key; and in response to receiving the selection of the first key, output a representation of the first handwritten input within the message-input area.

[0047] Thus, electronic devices with displays, touch-sensitive surfaces and optionally one or more sensors to detect intensities of contacts with the touch-sensitive surface are provided with faster, more efficient methods and interfaces for handwriting messages, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for composing and submitting messages.

[0048] There is a need for electronic devices with improved methods and interfaces for quickly locating different types of content in a messaging application. Such methods and interfaces optionally complement or replace conventional methods. Such methods and interfaces produce more efficient human-machine interfaces by allowing users to simply utilize a simple gesture in order to quickly scale down display sizes for content in a messaging application, so that users are able to quickly locate desired content (e.g., users can scale down all text-only content in order to quickly locate emojis, photos, videos, or other types of content that may have been received a long time ago). For battery-operated devices, such methods and interfaces conserve power and increase the time between battery charges (e.g., by allowing users to quickly locate desired content). Furthermore, allowing users to quickly locate desired content enhances the operability of the devices and makes user-device interfaces (e.g., in the messaging application) more efficient (e.g., by allowing users to easily locate desired content in a potentially large and difficult to search conversation transcript) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently (e.g., the user need not scroll through pages and pages of content in the conversation transcript and can instead simply provide intuitive gestures to easily scale down content so that desired content is easily located).

[0049] In accordance with some embodiments, a method is performed at an electronic device with a display and a touch-sensitive surface. The method includes: displaying, on the display, a messaging user interface that includes a plurality of content items. In some embodiments, the plurality of content items includes content items having a first content type, the plurality of content items includes content items having a second content type that is distinct from the first content type, and a respective content item in the plurality of content items is displayed with a respective first size. While displaying the messaging user interface, the method includes: detecting, via the touch-sensitive surface, a first input. In response to detecting the first input, the method includes: reducing a display size of at least some content items having the first content type while continuing to display content items having the second content type with their respective first size.

[0050] In accordance with some embodiments, an electronic device includes a display unit configured to display a user interface, a touch-sensitive surface unit to receive contacts, one or more sensor units to detect intensities of contacts with the touch-sensitive surface unit; and a processing unit coupled with the display unit, the touch-sensitive surface unit, and the one or more sensor units. The

processing unit is configured to: display, on the display, a messaging user interface that includes a plurality of content items. In some embodiments, the plurality of content items at least includes content items having a first content type, the plurality of content items at least includes content items having a second content type that is distinct from the first content type, and a respective content item in the plurality of content items is displayed with a respective first size. While displaying the messaging user interface, the processing unit is configured to: detect, via the touch-sensitive surface, a first input and, in response to detecting the first input, reduce a display size of at least some content items having the first content type while continuing to display content items having the second content type with their respective first size.

[0051] In accordance with some embodiments, a method is performed at an electronic device with a display and a touch-sensitive surface. The method includes: displaying, on the display, a messaging user interface that includes a plurality of content items. In some embodiments, the plurality of content items includes content items having a first content type, the plurality of content items includes content items having a second content type that is distinct from the first content type, and a respective content item in the plurality of content items is displayed with a respective first size. While displaying the messaging user interface, the method includes: detecting, via the touch-sensitive surface, a first input and, in response to detecting the first input, the method includes: reducing a display size of at least some content items having the first content type, such that a first content item having the first content type is reduced to a respective second size that is smaller than the respective first size by a predefined first display-size-reduction factor; and reducing a display size of at least some content items having the second content type, such that a second content item having the second content type is reduced to a respective third size that is smaller than the respective first size by a predefined second display-size-reduction factor. In some embodiments, the predefined second display-size-reduction factor is less than the predefined first display-size-reduction factor.

[0052] In accordance with some embodiments, an electronic device includes a display unit configured to display a user interface and a touch-sensitive surface unit to receive contacts, one or more sensor units to detect intensities of contacts with the touch-sensitive surface unit; and a processing unit coupled with the display unit, the touch-sensitive surface unit, and the one or more sensor units. The processing unit is configured to: display, on the display, a messaging user interface that includes a plurality of content items. In some embodiments, the plurality of content items includes content items having a first content type, the plurality of content items includes content items having a second content type that is distinct from the first content type, and a respective content item in the plurality of content items is displayed with a respective first size. While displaying the messaging user interface, the processing unit is configured to: detect, via the touch-sensitive surface, a first input. In response to detecting the first input, the processing unit is configured to: reduce a display size of at least some content items having the first content type, such that a first content item having the first content type is reduced to a respective second size that is smaller than the respective first size by a predefined first display-size-reduction factor; and reduce a display size of at least some content items having the second content type, such that a second content item having the second content type is reduced to a respective third size that is smaller than the respective first size by a predefined second display-size-reduction factor. In some embodiments, the predefined second display-size-reduction factor is less than the predefined first display-size-reduction factor.

[0053] Thus, electronic devices with displays, touch-sensitive surfaces and optionally one or more sensors to detect intensities of contacts with the touch-sensitive surface are provided with fast and efficient methods and interfaces for quickly locating different types of content in a messaging application, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices.

[0054] There is a need for electronic devices with improved methods and interfaces for sharing images (e.g., photos) in message conversations. Such methods and interfaces may complement or replace conventional methods for sharing images (e.g., photos) in message conversations. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0055] In accordance with some embodiments, a method is performed at an electronic device with a display, a digital camera, a touch-sensitive surface and memory. The method includes displaying a messaging user interface on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a keyboard, a message-input area, and a digital image affordance. The method further includes, while displaying the messaging user interface, detecting an input that activates the digital image affordance. The method further includes in response to detecting the input that activates the digital image affordance, replacing display of the keyboard with display of a plurality of digital images, the plurality of digital images including one or more digital images stored in the memory and a live preview image from the digital camera. The method further includes detecting an input that selects the live image displayed within the plurality of digital images. The method further includes, in response to detecting that input that selects the live image, capturing a digital image with the digital camera, while maintaining display of the conversation transcript.

[0056] In accordance with some embodiments, an electronic device includes a display unit configured to display user interfaces, a digital camera unit configured to capture images, a touch-sensitive surface unit, a memory unit, and a processing unit coupled to the display unit, the digital camera unit, the touch-sensitive surface unit and the memory unit. The processing unit is configured to: display a messaging user interface on the display unit, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a keyboard, a message-input area, and a digital image affordance. The processing unit is further configured to, while displaying the messaging user interface, detect an input that activates the digital image affordance. The processing unit is further configured to, in response to detecting the input that activates the digital image affordance, replace display of the keyboard with display of a plurality of digital images, the plurality of digital images including one or more digital images stored in the memory

unit and a live preview image from the digital camera unit. The processing unit is further configured to detect an input that selects the live image displayed within the plurality of digital images. The processing unit is further configured to, in response to detecting that input that selects the live image, capture a digital image with the digital camera unit, while maintaining display of the conversation transcript.

[0057] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for sharing images (e.g., photos) in message conversations, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for sharing images (e.g., photos) in message conversations.

[0058] There is a need for electronic devices with improved methods and interfaces for searching and sharing content (e.g., content from the Internet and locally stored content) in message conversations. Such methods and interfaces may complement or replace conventional methods for searching and sharing content in message conversations. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0059] In accordance with some embodiments, a method is performed at an electronic device with a display and a touch-sensitive surface. The method includes displaying a messaging user interface on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a search affordance. The method further includes, while displaying the messaging user interface, detecting an input that activates the search affordance. The method further includes, in response to detecting the input that activates the search affordance: ceasing to display the messaging user interface, and displaying a search user interface, the search user interface including a search field and a plurality of categorized content items, wherein the plurality of categorized content items includes at least a content item stored on the electronic device and a content item from the Internet. The method further includes, while displaying the search user interface, detecting an input that selects a first content item in the plurality of categorized content items. The method further includes, after detecting the input that selects the first content item in the plurality of categorized content items: ceasing to display the searching user interface, displaying the first content item in the conversation transcript within the messaging user interface, and transmitting the first content item to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the first content item in a conversation transcript that corresponds to the messaging session.

[0060] In accordance with some embodiments, an electronic device includes a display unit configured to display user interfaces, a touch-sensitive surface unit, a memory unit, and a processing unit coupled to the display unit, the touch-sensitive surface unit, and the memory unit. The processing unit is configured to: display a messaging user interface on the display unit, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a search affordance. The processing unit is further configured to, while displaying the messaging user interface, detect an input that activates the search affordance. The processing unit is further configured to, in response to detecting the input that activates the search affordance: cease to display the messaging user interface, and display a search user interface, the search user interface including a search field and a plurality of categorized content items, wherein the plurality of categorized content items includes at least a content item stored on the electronic device and a content item from the Internet. The processing unit is further configured to, while displaying the search user interface, detect an input that selects a first content item in the plurality of categorized content items. The processing unit is further configured to, after detecting the input that selects the first content item in the plurality of categorized content items: cease to display the searching user interface, display the first content item in the conversation transcript within the messaging user interface, and transmit the first content item to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the first content item in a conversation transcript that corresponds to the messaging session.

[0061] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for searching sharing content in message conversations, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for sharing content in conversations.

[0062] There is a need for electronic devices with improved methods and interfaces for adding an interactive application to a messaging application. Such methods and interfaces may complement or replace conventional methods for adding an interactive application to a messaging application. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0063] In accordance with some embodiments, a method is performed at an electronic device having one or more processors, memory, a touch-sensitive surface, and a display. The method includes: displaying a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and an application affordance; while displaying the messaging user interface, detecting an input that activates the application affordance; in response to detecting the input that activates the application affordance, concurrently displaying a launch icon for an application store and a plurality of launch icons for interactive applications, wherein activation of a respective launch icon for an interactive application launches a corresponding application that is displayed within the messaging application; detecting an input that activates the launch icon for the application store; in response to detecting the input that activates the launch icon for the application store: ceasing to display the messaging user interface, and displaying an application store user interface, including display of at least one interactive application available for download to the electronic device; while displaying the application store user interface, detecting an input that corresponds to a request to download a first interactive application that is not stored in the memory of the electronic device; and, in response to detecting the input that corresponds to the request to download the first interactive

application: downloading the first interactive application to the memory of the electronic device; replacing display of the application store user interface with display of the messaging user interface, the messaging user interface including the conversation transcript and at least some of the plurality of launch icons for interactive applications; and adding a launch icon that corresponds to the first interactive application to the display of the plurality of launch icons for interactive applications.

[0064] In accordance with some embodiments, an electronic device includes a display unit configured to display user interfaces; a touch-sensitive surface unit configured to detect contacts; and a processing unit coupled with the display unit and the touch-sensitive surface unit. The processing unit is configured to: enable display of a messaging user interface of a messaging application on the display unit, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and an application affordance; while displaying the messaging user interface, detect an input that activates the application affordance; in response to detecting the input that activates the application affordance, concurrently enable display of a launch icon for an application store and a plurality of launch icons for interactive applications, wherein activation of a respective launch icon for an interactive application launches a corresponding application that is displayed within the messaging application; detect an input that activates the launch icon for the application store; in response to detecting the input that activates the launch icon for the application store: cease to display the messaging user interface, and enable display of an application store user interface, including display of at least one interactive application available for download to the electronic device; while displaying the application store user interface, detect an input that corresponds to a request to download a first interactive application that is not stored in the memory of the electronic device; and, in response to detecting the input that corresponds to the request to download the first interactive application: download the first interactive application to the memory of the electronic device; replace display of the application store user interface with display of the messaging user interface, the messaging user interface including the conversation transcript and at least some of the plurality of launch icons for interactive applications; and add a launch icon that corresponds to the first interactive application to the display of the plurality of launch icons for interactive applications.

[0065] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for adding an interactive application to a messaging application, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for adding an interactive application to a messaging application.

[0066] There is a need for electronic devices with improved methods and interfaces for posting messages. Such methods and interfaces may complement or replace conventional methods for posting messages. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0067] In accordance with some embodiments, a method is performed at an electronic device having one or more processors, memory, a touch-sensitive surface, and a display. The method includes: displaying a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a first message-input area, and a launch icon for an interactive application; while displaying the messaging user interface, detecting an input that activates the launch icon for the interactive application; in response to detecting the input that activates the launch icon for the interactive application, displaying a user interface for the interactive application, the interactive application user interface including a second message-input area that is distinct from the first message-input area; while displaying the interactive application user interface, detecting input of a first message in the second message-input area; in response to detecting the input of the first message in the second message-input area, displaying the first message in the second message-input area; while displaying the first message in the second message-input area, detecting an input that corresponds to a request to post the contents of the second message-input area to the messaging session; and, in response to detecting the input that corresponds to the request to post the contents of the second message-input area to the messaging session, transmitting the first message to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the first message in a conversation transcript corresponding to the messaging session.

[0068] In accordance with some embodiments, an electronic device includes a display unit configured to display user interfaces; a touch-sensitive surface unit configured to detect contacts; and a processing unit coupled with the display unit and the touch-sensitive surface unit. The processing unit is configured to: enable display of a messaging user interface of a messaging application on the display unit, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a first message-input area, and a launch icon for an interactive application; while displaying the messaging user interface, detect an input that activates the launch icon for the interactive application; in response to detecting the input that activates the launch icon for the interactive application, enable display of a user interface for the interactive application, the interactive application user interface including a second message-input area that is distinct from the first message-input area; while displaying the interactive application user interface, detect input of a first message in the second message-input area; in response to detecting the input of the first message in the second message-input area, enable display of the first message in the second message-input area; while displaying the first message in the second message-input area, detect an input that corresponds to a request to post the contents of the second message-input area to the messaging session; and, in response to detecting the input that corresponds to the request to post the contents of the second message-input area to the messaging session, transmit the first message to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the first message in a conversation transcript corresponding to the messaging session.

[0069] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for posting messages, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for posting messages.

[0070] There is a need for electronic devices with improved methods and interfaces for using an interactive application within a messaging application. Such methods and interfaces may complement or replace conventional methods for using an interactive application within a messaging application. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0071] In accordance with some embodiments, a method is performed at an electronic device having one or more processors, memory, a touch-sensitive surface, and a display. The method includes: displaying a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a message-input area, and an icon for an interactive application that is displayed within the conversation transcript; while displaying the messaging user interface, detecting an input that activates the icon for the interactive application; in response to detecting the input that activates the icon for the interactive application, displaying a user interface for the interactive application in a first state; while displaying the user interface for the interactive application, detecting a first user input within the user interface for the interactive application; and, in response to detecting the first user input within the user interface for the interactive application: changing display of the user interface for the interactive application from the first state to a second state, and sending information, to the one or more electronic devices that correspond to the at least one other user included in the messaging session, indicating that the first user input was made in the user interface for the interactive application, wherein the one or more electronic devices display an indicia of the first user input.

[0072] In accordance with some embodiments, an electronic device includes a display unit configured to display user interfaces; a touch-sensitive surface unit configured to detect contacts; and a processing unit coupled with the display unit and the touch-sensitive surface unit. The processing unit is configured to: enable display of a messaging user interface of a messaging application on the display unit, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a message-input area, and an icon for an interactive application that is displayed within the conversation transcript; while displaying the messaging user interface, detect an input that activates the icon for the interactive application; in response to detecting the input that activates the icon for the interactive application, enable display of a user interface for the interactive application in a first state; while displaying the user interface for the interactive application, detect a first user input within the user interface for the interactive application; and, in response to detecting the first user input within the user interface for the interactive application: change display of the user interface for the interactive application from the first state to a second state, and send information, to the one or more electronic devices that correspond to the at least one other user included in the messaging session, indicating that the first user input was made in the user interface for the interactive application, wherein the one or more electronic devices display an indicia of the first user input.

[0073] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for using an interactive application within a messaging application, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for using an interactive application in a messaging application.

[0074] There is a need for electronic devices with improved methods and interfaces for using an interactive application in a messaging application. Such methods and interfaces may complement or replace conventional methods for using an interactive application in a messaging application. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0075] In accordance with some embodiments, a method is performed at an electronic device having one or more processors, memory, a touch-sensitive surface, and a display. The method includes: displaying a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a message-input area; while displaying the messaging user interface, receiving instructions, from an electronic device that corresponds to another user included in the messaging session, to display an icon for an interactive application in the conversation transcript; in response to receiving the instructions, displaying the icon for the interactive application in the conversation transcript; while displaying the icon for the interactive application in the conversation transcript, detecting an input that activates the icon for the interactive application; and, in response to detecting the input that activates the icon for the interactive application displayed in the conversation transcript: in accordance with a determination that an interactive application that corresponds to the icon for the interactive application is stored in the memory of the electronic device, displaying a user interface for the interactive application, and in accordance with a determination that the interactive application that corresponds to the icon for the interactive application is not stored in the memory of the electronic device: downloading the interactive application, from a remote server, to the memory of the electronic device, and after downloading the interactive application from the remote server, displaying the user interface for the interactive application.

[0076] In accordance with some embodiments, an electronic device includes a display unit configured to display user interfaces; a touch-sensitive surface unit configured to detect contacts; and a processing unit coupled with the display unit and the touch-sensitive surface unit. The processing unit is configured to: enable display of a messaging user interface of a messaging application on the display unit, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a message-input area; while displaying the messaging user interface, receive instructions, from an electronic device that corresponds to another user included in the messaging session, to display an

icon for an interactive application in the conversation transcript; in response to receiving the instructions, enable display of the icon for the interactive application in the conversation transcript; while displaying the icon for the interactive application in the conversation transcript, detect an input that activates the icon for the interactive application; and, in response to detecting the input that activates the icon for the interactive application displayed in the conversation transcript: in accordance with a determination that an interactive application that corresponds to the icon for the interactive application is stored in the memory of the electronic device, enable display of a user interface for the interactive application, and in accordance with a determination that the interactive application that corresponds to the icon for the interactive application is not stored in the memory of the electronic device: download the interactive application, from a remote server, to the memory of the electronic device, and after downloading the interactive application from the remote server, enable display of the user interface for the interactive application.

[0077] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for using an interactive application in a messaging application, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for using an interactive application in a messaging application.

[0078] There is a need for electronic devices with improved methods and interfaces for using an interactive application in a messaging application. Such methods and interfaces may complement or replace conventional methods for using an interactive application in a messaging application. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0079] In accordance with some embodiments, a method is performed at an electronic device with a display and a touch-sensitive surface. The method includes, displaying a messaging user interface of a messaging application on the display, the messaging user interface including: a conversation transcript, displayed in a first area of the display, of a messaging session between a user of the electronic device and at least one other user, a first interactive application object displayed within the conversation transcript that corresponds to a first interactive application, a message input area, and an input area for the first interactive application, distinct from the message input area, displayed in a second area of the display, the input area for the first interactive application including one or more input affordances; and; detecting an input that activates a first input affordance in the input area for the interactive application.

[0080] In accordance with some embodiments, an electronic device includes a display unit and a touch-sensitive surface unit, and a processing unit coupled with the display unit and the touch-sensitive surface unit. The processing unit is configured to: enable display of a messaging user interface of a messaging application on the display unit, the messaging user interface including: a conversation transcript, displayed in a first area of the display, of a messaging session between a user of the electronic device and at least one other user, a first interactive application object displayed within the conversation transcript that corresponds to a first interactive application, a message input area, and an input area for the first interactive application, distinct from the message input area, displayed in a second area of the display, the input area for the first interactive application including one or more input affordances; and; detect an input that activates a first input affordance in the input area for the interactive application.

[0081] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for using an interactive application in a messaging application, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for using an interactive application in a messaging application.

[0082] There is a need for electronic devices with improved methods and interfaces for using an interactive application in a messaging application. Such methods and interfaces may complement or replace conventional methods for using an interactive application in a messaging application. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0083] In accordance with some embodiments, a method is performed at an electronic device with a display and a touch-sensitive surface. The method includes, displaying a messaging user interface of a messaging application on the display, the messaging user interface including: a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a first interactive application object displayed within the conversation transcript that corresponds to a first interactive application, and a message input area. The method further includes detecting a first input while a focus selector is at a location on the touch-sensitive surface that corresponds to the first interactive application object displayed within the conversation transcript; in response to detecting the first input, displaying an input area for the first interactive application that is distinct from the message input area, the input area for the first interactive application including one or more input affordances; while displaying an input area for the first interactive application, detecting one or more inputs on the one or more input affordances; after detecting the one or more inputs on the one or more input affordances: updating the first interactive application; sending information to one or more electronic devices that correspond to the at least one other user included in the messaging session that causes updating of a corresponding user interface for the first interactive application displayed within a corresponding conversation transcript of the messaging session; and ceasing display of the input area for the first interactive application.

[0084] In accordance with some embodiments, an electronic device includes a display unit and a touch-sensitive surface unit, and a processing unit coupled with the display unit and the touch-sensitive surface unit. The processing unit is configured to: enable display of a messaging user interface of a messaging application on the display unit, the messaging user interface including: a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a first interactive application object displayed within the conversation transcript that corresponds to a first interactive application, and a message input area. The processing unit is further configured to: detect a first input while a focus selector is at a location on

the touch-sensitive surface unit that corresponds to the first interactive application object displayed within the conversation transcript; in response to detecting the first input, enable display of an input area for the first interactive application that is distinct from the message input area, the input area for the first interactive application including one or more input affordances; while displaying an input area for the first interactive application, detect one or more inputs on the one or more input affordances; after detecting the one or more inputs on the one or more input affordances: update the first interactive application; send information to one or more electronic devices that correspond to the at least one other user included in the messaging session that causes updating of a corresponding user interface for the first interactive application displayed within a corresponding conversation transcript of the messaging session; and cease display of the input area for the first interactive application.

[0085] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for using an interactive application in a messaging application, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for using an interactive application in a messaging application.

[0086] There is a need for electronic devices with improved methods and interfaces for enabling use of an interactive application in a messaging application. Such methods and interfaces may complement or replace conventional methods for enabling use of an interactive application in a messaging application. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0087] In accordance with some embodiments, a method is performed at an electronic device with a display and a touch-sensitive surface, where a messaging application and a plurality of other applications are stored in the memory, and a respective application in the plurality of other applications has a normal mode for normal operation on the electronic device and an embedded mode for operation within the messaging application on the electronic device. The method includes: displaying a plurality of toggle affordances, where a respective toggle affordance in the plurality of toggle affordances has a corresponding application in the plurality of other applications stored in the memory; the respective toggle affordance has a first state that enables display of a respective launch icon, within the messaging application, for operation of the corresponding application in the embedded mode within the messaging application; the respective toggle affordance has a second state that prevents display of the respective launch icon, within the messaging application, to prevent operation of the corresponding application in the embedded mode within the messaging application; the plurality of toggle affordances include a first toggle affordance for a first application that is displayed in the first state and a second toggle affordance for a second application that is displayed in the second state. While displaying the plurality of toggle affordances, the method further includes: detecting a first user input at a first location that corresponds to the first toggle affordance; and, in response to detecting the first user input at the first location that corresponds to the first toggle affordance: changing the first toggle affordance from the first state to the second state, and preventing display of a corresponding launch icon for the first application in the messaging application.

[0088] In accordance with some embodiments, an electronic device includes a display unit and a touch-sensitive surface unit, and a processing unit coupled with the display unit and the touch-sensitive surface unit, where a messaging application and a plurality of other applications are stored in memory of the electronic device, and a respective application in the plurality of other applications has a normal mode for normal operation on the electronic device and an embedded mode for operation within the messaging application on the electronic device. The processing unit is configured to: enable display of a plurality of toggle affordances, where a respective toggle affordance in the plurality of toggle affordances has a corresponding application in the plurality of other applications stored in the memory, the respective toggle affordance has a first state that enables display of a respective launch icon, within the messaging application, for operation of the corresponding application in the embedded mode within the messaging application; the respective toggle affordance has a second state that prevents display of the respective launch icon, within the messaging application, to prevent operation of the corresponding application in the embedded mode within the messaging application; the plurality of toggle affordances include a first toggle affordance for a first application that is displayed in the first state and a second toggle affordance for a second application that is displayed in the second state. The processing unit is further configured to: while displaying the plurality of toggle affordances, detect a first user input at a first location that corresponds to the first toggle affordance; and, in response to detecting the first user input at the first location that corresponds to the first toggle affordance: change the first toggle affordance from the first state to the second state, and prevent display of a corresponding launch icon for the first application in the messaging application.

[0089] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for enabling use of an interactive application in a messaging application, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for enabling use of an interactive application in a messaging application.

[0090] There is a need for electronic devices with improved methods and interfaces for navigating within a messaging application. Such methods and interfaces may complement or replace conventional methods for navigating within a messaging application. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0091] In accordance with some embodiments, a method is performed at an electronic device with a display, a touch-sensitive surface, and a digital camera. The method includes: displaying a messaging user interface on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a message-input area, a digital image affordance, a digital touch affordance, and an application affordance; while displaying the messaging user interface, detecting a first input on the touch sensitive surface; in response to detecting the first input: in accordance with a determination that the first input is made

while a focus selector is at a location in the messaging user interface that corresponds to the digital image affordance, displaying a plurality of digital images within the messaging user interface; in accordance with a determination that the first input is made while a focus selector is at a location in the messaging user interface that corresponds to the digital canvas affordance, displaying a digital drawing canvas within the messaging user interface; and in accordance with a determination that the first input is made while a focus selector is at a location in the messaging user interface that corresponds to the application affordance, displaying one or more launch icons for an application within the messaging user interface.

[0092] In accordance with some embodiments, an electronic device includes a display unit, a touch-sensitive surface unit, a digital camera unit, and a processing unit coupled with the display unit, the touch-sensitive surface unit, and the digital camera unit. The processing unit is configured to: enable display of a messaging user interface on the display unit, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a message-input area, a digital image affordance, a digital touch affordance, and an application affordance. The processing unit is further configured to: while displaying the messaging user interface, detect a first input on the touch sensitive surface; in response to detecting the first input: in accordance with a determination that the first input is made while a focus selector is at a location in the messaging user interface that corresponds to the digital image affordance, enable display of a plurality of digital images within the messaging user interface; in accordance with a determination that the first input is made while a focus selector is at a location in the messaging user interface that corresponds to the digital canvas affordance, enable display of a digital drawing canvas within the messaging user interface; and in accordance with a determination that the first input is made while a focus selector is at a location in the messaging user interface that corresponds to the application affordance, enable display of one or more launch icons for an application within the messaging user interface.

[0093] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for navigating within a messaging application, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for navigating within a messaging application.

[0094] There is a need for electronic devices with improved methods and interfaces for placing an electronic sticker in a conversation transcript. Such methods and interfaces may complement or replace conventional methods for placing an electronic sticker in a conversation transcript. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0095] In accordance with some embodiments, a method is performed at an electronic device with at an electronic device having one or more processors, memory, a touch-sensitive surface, and a display. The device displays a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a plurality of electronic stickers, and a message-input area. While displaying the messaging user interface, the device detects a first drag gesture that starts while a focus selector is at a first location in the messaging user interface that corresponds to a first electronic sticker in the plurality of electronic stickers, the first drag gesture moving the focus selector in a first direction. The device moves the first electronic sticker in the first direction in accordance with the movement of the first drag gesture. The device detects termination of the first drag gesture while the focus selector is at a second location in the messaging user interface. In response to detecting termination of the first drag gesture: in accordance with a determination that the second location is within the conversation transcript, the device places the electronic sticker in the conversation transcript at a location based on the second location. In accordance with a determination that the second location in not within the conversation transcript, the device ceases to display the electronic sticker at the second location on the display.

[0096] In accordance with some embodiments, an electronic device includes a display unit configured to display user interfaces; a touch-sensitive surface unit configured to detect contacts; and a processing unit coupled with the display unit and the touch-sensitive surface unit. The processing unit is configured to: enable display of a messaging user interface of a messaging application on the display unit, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a plurality of electronic stickers, and a message-input area. While displaying the messaging user interface, the processing unit is configured to detect a first drag gesture that starts while a focus selector is at a first location in the messaging user interface that corresponds to a first electronic sticker in the plurality of electronic stickers, the first drag gesture move the focus selector in a first direction. The processing unit is configured to move the first electronic sticker in the first direction in accordance with the movement of the first drag gesture. The processing unit is configured to detect termination of the first drag gesture while the focus selector is at a second location in the messaging user interface. In response to detecting termination of the first drag gesture: in accordance with a determination that the second location is within the conversation transcript, the processing unit is configured to place the electronic sticker in the conversation transcript at a location based on the second location, and in accordance with a determination that the second location in not within the conversation transcript, the processing unit is configured to cease to display the electronic sticker at the second location on the display unit.

[0097] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for placing an electronic sticker in a conversation transcript, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for placing an electronic sticker in a conversation transcript.

[0098] There is a need for electronic devices with improved methods and interfaces for changing characteristics of an electronic sticker in a conversation transcript for a messaging user interface. Such methods and interfaces may complement or replace conventional methods for changing characteristics of an electronic sticker in a con-

versation transcript for a messaging user interface. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0099] In accordance with some embodiments, a method is performed at an electronic device with one or more processors, memory, a touch-sensitive surface, and a display. The device displays a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a plurality of electronic stickers, and a message-input area. While displaying the messaging user interface, the device detects a first user input while a focus selector is at a first location in the messaging user interface that corresponds to a first electronic sticker in the plurality of electronic stickers. In response to detecting the first user input, the device places and displays the first electronic sticker in the conversation transcript. While the first electronic sticker is displayed in the conversation transcript: the device detects a second user input while a focus selector is at a second location in the messaging user interface that corresponds to the first electronic sticker in the conversation transcript. In response to detecting the second user input, the device changes the position, size, and/or rotation of the first electronic sticker in the conversation transcript.

[0100] In accordance with some embodiments, there is an electronic device with a display unit configured to display user interfaces; a touch-sensitive surface unit configured to detect contacts; and a processing unit coupled with the display unit and the touch-sensitive surface unit. The processing unit enables display of a messaging user interface of a messaging application on the display unit, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a plurality of electronic stickers, and a message-input area. While displaying the messaging user interface, the processing unit detects a first user input while a focus selector is at a first location in the messaging user interface that corresponds to a first electronic sticker in the plurality of electronic stickers. In response to detecting the first user input, the processing unit places and enables display of the first electronic sticker in the conversation transcript. While the first electronic sticker is displayed in the conversation transcript, the processing unit detects a second user input while a focus selector is at a second location in the messaging user interface that corresponds to the first electronic sticker in the conversation transcript. In response to detecting the second user input, the device changes the position, size, and/or rotation of the first electronic sticker in the conversation transcript.

[0101] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for changing characteristics of an electronic sticker in a conversation transcript for a messaging user interface, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for changing characteristics of an electronic sticker in a conversation transcript for a messaging user interface.

[0102] There is a need for electronic devices with improved methods and interfaces for initiating payments through a messaging application. Such methods and interfaces may complement or replace conventional methods for initiating payments through a messaging application. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0103] In accordance with some embodiments, a method is performed at an electronic device with one or more processors, memory, a touch-sensitive surface, and a display. The device displays a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user and a message-input area, wherein each of the other users included in the messaging session has a corresponding avatar. While displaying the messaging user interface, the device detects a first user input while a focus selector is at a first location in the messaging user interface that corresponds to an avatar of a first other user included in the messaging session. In response to detecting the first user input, the device displays a menu that contains activatable menu items associated with the first other user overlaid on the messaging user interface, the displayed menu including an activatable menu item for initiating a payment action with the first other user. While displaying the menu that contains activatable menu items associated with the first other user, the device detects a second user input while a focus selector is at a second location in the messaging user interface that corresponds to the activatable menu item for initiating a payment action with the first other user. In response to detecting the second user input, the device displays a user interface configured to initiate sending of a payment to, and/or requesting a payment from, the first other user.

[0104] In some embodiments, there is an electronic device, with a display unit configured to display user interfaces; a touch-sensitive surface unit configured to detect contacts; and a processing unit coupled with the display unit and the touch-sensitive surface unit. The processing unit enables display of a messaging user interface of a messaging application on the display unit, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user and a message-input area, wherein each of the other users included in the messaging session has a corresponding avatar. While displaying the messaging user interface, the processing unit detects a first user input while a focus selector is at a first location in the messaging user interface that corresponds to an avatar of a first other user included in the messaging session. In response to detecting the first user input, the processing unit enables display of a menu that contains activatable menu items associated with the first other user overlaid on the messaging user interface, the displayed menu including an activatable menu item for initiating a payment action with the first other user. While displaying the menu that contains activatable menu items associated with the first other user, the processing unit detects a second user input while a focus selector is at a second location in the messaging user interface that corresponds to the activatable menu item for initiating a payment action with the first other user. In response to detecting the second user input, the processing unit enables display of a user interface configured to initiate sending of a payment to, and/or requesting a payment from, the first other user.

[0105] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for initiating payments through a messaging appli-

cation, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for initiating payments through messaging applications.

[0106] There is a need for electronic devices with improved methods and interfaces for selectively activating menus in a messaging session. Such methods and interfaces may complement or replace conventional methods for selectively activating menus in a messaging session. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0107] In accordance with some embodiments, a method is performed at an electronic device with one or more processors, memory, a touch-sensitive surface, one or more sensors to detect intensities of contacts with the touch-sensitive surface, and a display. The device displays a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and a plurality of other users, a message-input area, and a plurality of avatars, each respective avatar in the plurality of avatars corresponding to a respective other user in the plurality of other users included in the messaging session, wherein the plurality of avatars are displayed as a stack of avatars, with a first avatar in the plurality of avatars displayed on the top of the stack of avatars. While displaying the messaging user interface, the device detects an input by a first contact on the touch-sensitive surface while a focus selector is at a first location in the messaging user interface that corresponds to the first avatar. In response to detecting the input by the first contact: in accordance with a determination that the input meets menu-activation-criteria, wherein the menu-activation-criteria require that a characteristic intensity of the contact on the touch-sensitive surface meet a respective intensity threshold in order for the menu-activation criteria to be met, the device displays a menu that contains activatable menu items associated with the first avatar overlaid on the messaging user interface. In accordance with a determination that the input meets avatar-spreading-criteria, wherein the avatar-spreading-criteria do not require that a characteristic intensity of the contact on the touchscreen meet the respective intensity threshold in order for the selection criteria to be met, the device displays the plurality of avatars in an array.

[0108] In accordance with some embodiments, there is an electronic device, including a display unit configured to display user interfaces; a touch-sensitive surface unit configured to detect contacts; and a processing unit coupled with the display unit and the touch-sensitive surface unit. The processing unit enables display of a messaging user interface of a messaging application on the display unit, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and a plurality of other users, a message-input area, and a plurality of avatars, each respective avatar in the plurality of avatars corresponding to a respective other user in the plurality of other users included in the messaging session, wherein the plurality of avatars are displayed as a stack of avatars, with a first avatar in the plurality of avatars displayed on the top of the stack of avatars. While displaying the messaging user interface, the processing unit detects an input by a first contact on the touch-sensitive surface unit while a focus selector is at a first location in the messaging user interface that corresponds to the first avatar. In response to detecting the input by the first contact: in accordance with a determination that the input meets menu-activation-criteria, wherein the menu-activation-criteria require that a characteristic intensity of the contact on the touch-sensitive surface unit meet a respective intensity threshold in order for the menu-activation criteria to be met, the processing unit enables display of a menu that contains activatable menu items associated with the first avatar overlaid on the messaging user interface. In accordance with a determination that the input meets avatar-spreading-criteria, wherein the avatar-spreading-criteria do not require that a characteristic intensity of the contact on the touchscreen meet the respective intensity threshold in order for the selection criteria to be met, the processing unit enables display of the plurality of avatars in an array.

[0109] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for selectively activating menus in a messaging session, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for selectively activating menus in a messaging session.

[0110] There is a need for electronic devices with improved methods and interfaces for providing a selectable link to access additional content for a word or phrase in a message. Such methods and interfaces may complement or replace conventional methods for providing a selectable link to access additional content for a word or phrase in a message. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0111] In accordance with some embodiments, a method is performed at an electronic device with one or more processors, memory, a touch-sensitive surface, and a display. The device displays a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a message-input area. While displaying the messaging user interface, the device receives a first message within the messaging session from an electronic device that corresponds to another user included in the messaging session. In response to receiving the first message, the device displays the first message within a first message region in the conversation transcript on the display. The device detects, in the first message, a word or phrase associated with additional content available on the Internet; and in response to detecting the word or phrase associated with additional content available on the internet, the device displays, proximate to the first message region, a selectable indication that additional content associated with the word or phrase is available.

[0112] In some embodiments, there is an electronic device, including a display unit configured to display user interfaces; a touch-sensitive surface unit configured to detect contacts; and a processing unit coupled with the display unit and the touch-sensitive surface unit. The processing unit enables display of a messaging user interface of a messaging application on the display unit, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a message-input area. While displaying the messaging user interface, the processing unit receives a first

message within the messaging session from an electronic device that corresponds to another user included in the messaging session. In response to receiving the first message: the processing unit enables display of the first message within a first message region in the conversation transcript on the display unit. The processing unit detects, in the first message, a word or phrase associated with additional content available on the Internet. In response to detecting the word or phrase associated with additional content available on the internet, the processing unit enables display of, proximate to the first message region, a selectable indication that additional content associated with the word or phrase is available.

[0113] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for providing a selectable link to access additional content for a word or phrase in a message, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for providing a selectable link to access additional content on the word or phrase in a message.

[0114] There is a need for electronic devices with improved methods and interfaces for navigating between applications in a messaging user interface. Such methods and interfaces may complement or replace conventional methods for navigating between applications in a messaging user interface. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0115] In accordance with some embodiments, a method is performed at an electronic device having a display and a touch-sensitive surface. The method includes: displaying a messaging user interface on the display, the messaging user interface including: a conversation transcript of a messaging session between a user of the electronic device and at least one other user; a message-input area; an application area; and an application-area-display affordance; while displaying the messaging user interface, detecting a first input that activates the application-area-display affordance; in response to detecting the first input that activates the application-area-display affordance, in accordance with a determination that the application area is displaying a keyboard at the time the first input is detected, replacing display of the keyboard in the application area with concurrent display of: an application-selection area that displays a plurality of scrollable application-selection affordances, wherein: the plurality of scrollable application-selection affordances includes a first application-selection affordance that corresponds to a first application that is currently selected; and a respective application-selection affordance has a respective first size; and an application-input area that displays one or more activatable objects of the first application; while concurrently displaying the application-selection area and the application-input area, detecting a second input that includes a movement of a contact on the touch-sensitive surface that corresponds to movement of a focus selector in a first direction in the application-selection area on the display; in response to detecting the second input: scrolling the plurality of application-selection affordances in the first direction, and displaying a second application-selection affordance; while displaying the second application-selection affordance and the one or more activatable objects of the first application in the messaging user interface, detecting a third input that activates the second application-selection affordance; and, in response to detecting the third input that activates the second application-selection affordance: ceasing to display the one or more activatable objects of the first application; and displaying, in the application-input area, one or more activatable objects of a second application that corresponds to the second application-selection affordance.

[0116] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for navigating between applications in a messaging user interface, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for navigating between applications in a messaging user interface.

[0117] There is a need for electronic devices with improved methods and interfaces for managing applications used within a messaging application. Such methods and interfaces may complement or replace conventional methods for managing applications used within a messaging application. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0118] In accordance with some embodiments, a method is performed at a device having a display and a touch-sensitive surface. The method includes: displaying a messaging user interface of a messaging application on the display, the messaging user interface including: a conversation transcript of a messaging session between a user of the electronic device and at least one other user; a message-input area; and an application area that includes: an application-input area that displays one or more activatable objects of a first application; and an application-selection area that includes: a plurality of scrollable application-selection affordances that correspond to a plurality of applications that operate within the messaging user interface, and a first application-configuration affordance; while displaying the application-configuration affordance in the application-selection area, detecting a first input that activates the first application-configuration affordance; in response to detecting the first input, displaying a first application-management interface for the messaging application that includes: a plurality of installed-application affordances that correspond to the plurality of applications that operate within the messaging user interface of the messaging application, and a second application-configuration affordance, that is distinct from the first application-configuration affordance; while displaying the first application-management interface, detecting a second input at a location that corresponds to a first installed-application affordance of the plurality of installed-application affordances, wherein the first installed-application affordance corresponds to a first installed application on the electronic device; and in response to detecting the second input, initiating a process to uninstall at least a component of the first installed application on the mobile device; while displaying the first application-management interface, detecting a third input at a location that corresponds to the second application-configuration affordance; and, in response to detecting the third input, displaying a second application-management interface for the messaging application that includes: a plurality of toggles that correspond to the plurality of applications that operate within the messaging user interface of the messaging application, wherein activation of a respective toggle causes a corresponding

application to toggle between a hidden state and a revealed state in the messaging user interface of the messaging application.

[0119] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for managing applications used within a messaging application, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for managing applications used within a messaging application.

[0120] There is a need for electronic devices with improved methods and interfaces for translating message content in a messaging application. Such methods and interfaces may complement or replace conventional methods for translating message content in a messaging application. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-machine interface.

[0121] In accordance with some embodiments, a method is performed at a device having a display and one or more input devices. The method includes: displaying a messaging user interface on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user; receiving a first message within the messaging session from an electronic device that corresponds to another user included in the messaging session, wherein the first message includes foreign language text; in response to receiving the first message, displaying the first message in the conversation transcript; detecting a first input at a first location that corresponds to the foreign language text in the first message; in response to detecting the first input at the first location that corresponds to the foreign language text: in accordance with a determination that the first input meets translation criteria, displaying a translation of the foreign language text; and in accordance with a determination that the first input meets option-display criteria, displaying a plurality of activatable indicia.

[0122] In accordance with some embodiments, a method is performed at a device having a display and one or more input devices. The method includes: displaying a messaging user interface on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user; receiving a first message within the messaging session from an electronic device that corresponds to another user included in the messaging session, wherein the first message includes foreign language text; in response to receiving the first message, displaying the first message in the conversation transcript; detecting a first input at a location that corresponds to the foreign language text in the first message; in response to detecting the first input at the location that corresponds to the foreign language text: in accordance with a determination that the first input meets translation criteria, performing a foreign-language-text-translation action; and in accordance with a determination that the first input does not meet the translation criteria, forgoing performance of the foreign-language-text-translation action.

[0123] Thus, electronic devices with displays and touch-sensitive surfaces are provided with improved methods and interfaces for translating message content in a messaging application, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for translating message content in a messaging application.

[0124] In accordance with some embodiments, an electronic device includes a display, a touch-sensitive surface, optionally one or more sensors to detect intensities of contacts with the touch-sensitive surface, one or more processors, memory, and one or more programs; the one or more programs are stored in the memory and configured to be executed by the one or more processors and the one or more programs include instructions for performing or causing performance of the operations of any of the methods described herein. In accordance with some embodiments, a computer readable storage medium has stored therein instructions which when executed by an electronic device with a display, a touch-sensitive surface, and optionally one or more sensors to detect intensities of contacts with the touch-sensitive surface, cause the device to perform or cause performance of the operations of any of the methods described herein. In accordance with some embodiments, a graphical user interface on an electronic device with a display, a touch-sensitive surface, optionally one or more sensors to detect intensities of contacts with the touch-sensitive surface, a memory, and one or more processors to execute one or more programs stored in the memory includes one or more of the elements displayed in any of the methods described herein, which are updated in response to inputs, as described in any of the methods described herein. In accordance with some embodiments, an electronic device includes: a display, a touch-sensitive surface, and optionally one or more sensors to detect intensities of contacts with the touch-sensitive surface; and means for performing or causing performance of the operations of any of the methods described herein. In accordance with some embodiments, an information processing apparatus, for use in an electronic device with a display and a touch-sensitive surface, and optionally one or more sensors to detect intensities of contacts with the touch-sensitive surface, includes means for performing or causing performance of the operations of any of the methods described herein.

[0125] Thus, electronic devices with displays, touch-sensitive surfaces and optionally one or more sensors to detect intensities of contacts with the touch-sensitive surface are provided with faster, more efficient methods and interfaces for messaging, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for messaging.

BRIEF DESCRIPTION OF THE DRAWINGS

[0126] For a better understanding of the various described embodiments, reference should be made to the Description of Embodiments below, in conjunction with the following drawings in which like reference numerals refer to corresponding parts throughout the figures.

[0127] FIG. **1**A is a block diagram illustrating a portable multifunction device with a touch-sensitive display in accordance with some embodiments.

[0128] FIG. **1**B is a block diagram illustrating example components for event handling in accordance with some embodiments.

[0129] FIG. **2** illustrates a portable multifunction device having a touch screen in accordance with some embodiments.

[0130] FIG. **3** is a block diagram of an example multifunction device with a display and a touch-sensitive surface in accordance with some embodiments.

[0131] FIG. **4**A illustrates an example user interface for a menu of applications on a portable multifunction device in accordance with some embodiments.

[0132] FIG. **4**B illustrates an example user interface for a multifunction device with a touch-sensitive surface that is separate from the display in accordance with some embodiments.

[0133] FIGS. **4**C-**4**E illustrate examples of dynamic intensity thresholds in accordance with some embodiments.

[0134] FIGS. **5**A-**5**K illustrate exemplary user interfaces for displaying message transcripts and message acknowledgments.

[0135] FIGS. **5**L-**5**T illustrate exemplary user interfaces for editing previously sent messages while displaying a message transcript.

[0136] FIGS. **5**U-**5**BF illustrate exemplary user interfaces for applying an impact effect option to a message input or message region.

[0137] FIGS. **5**BG-**5**CA illustrate exemplary user interfaces for interacting with concealed messages.

[0138] FIGS. **5**CB-**5**CW illustrate exemplary user interfaces for triggering enhanced message content and applying an effect to a messaging user interface when a message includes an enhanced message content trigger.

[0139] FIGS. **5**CX-**5**DC illustrate exemplary user interfaces for detecting and responding to combinable content in separate messages.

[0140] FIGS. **5**DD-**5**DI illustrate exemplary user interfaces for selecting a message region type or shape.

[0141] FIGS. **5**DJ-**5**DQ illustrate exemplary user interfaces for displaying and selecting automatically suggested emoji while composing a message.

[0142] FIGS. **6**A-**6**E are flow diagrams of a process for applying an acknowledgement to a message region in a conversation transcript, in accordance with some embodiments.

[0143] FIG. **7** is a functional block diagram of an electronic device in accordance with some embodiments.

[0144] FIGS. **8**A-**8**C are flow diagrams of a process for editing a previously sent message in a messaging session, in accordance with some embodiments.

[0145] FIG. **9** is a functional block diagram of an electronic device in accordance with some embodiments.

[0146] FIGS. **10**A-**10**B are flow diagrams of a process for editing a previously sent message in a messaging session, in accordance with some embodiments.

[0147] FIG. **11** is a functional block diagram of an electronic device in accordance with some embodiments.

[0148] FIGS. **12**A-**12**E are flow diagrams of a process for applying an impact effect option to a message input, in accordance with some embodiments.

[0149] FIG. **13** is a functional block diagram of an electronic device in accordance with some embodiments.

[0150] FIGS. **14**A-**14**B are flow diagrams of a process for interacting with concealed messages, in accordance with some embodiments.

[0151] FIG. **15** is a functional block diagram of an electronic device in accordance with some embodiments.

[0152] FIGS. **16**A-**16**C are flow diagrams of a process for applying an effect to a messaging user interface when a message includes an enhanced message content trigger, in accordance with some embodiments.

[0153] FIG. **17** is a functional block diagram of an electronic device in accordance with some embodiments.

[0154] FIG. **18**A-**18**C are flow diagrams of a process for detecting combinable content in a messaging user interface and displaying content corresponding to a predetermined combination when the combinable content is detected, in accordance with some embodiments.

[0155] FIG. **19** is a functional block diagram of an electronic device in accordance with some embodiments.

[0156] FIGS. **20**A-**20**P illustrate example user interfaces for presenting synchronized media content (e.g., audio content and/or video content) in a messaging application, in accordance with some embodiments.

[0157] FIGS. **21**A-**21**C are flow diagrams illustrating a method of presenting synchronized media content in a messaging application, in accordance with some embodiments.

[0158] FIG. **22** is a functional block diagram of an electronic device in accordance with some embodiments.

[0159] FIGS. **23**A-**23**AE illustrate example user interfaces for providing and presenting user-specific handwritten inputs in a messaging application, in accordance with some embodiments.

[0160] FIGS. **24**A-**24**C are flow diagrams illustrating a method of providing and presenting user-specific handwritten inputs in a messaging application, in accordance with some embodiments.

[0161] FIG. **25** is a functional block diagram of an electronic device in accordance with some embodiments.

[0162] FIGS. **26**A-**26**B are flow diagrams illustrating a method of providing and presenting user-specific handwritten inputs in a messaging application, in accordance with some embodiments.

[0163] FIG. **27** is a functional block diagram of an electronic device in accordance with some embodiments.

[0164] FIGS. **28**A-**28**B are flow diagrams illustrating a method of providing and presenting user-specific handwritten inputs in a messaging application, in accordance with some embodiments.

[0165] FIGS. **28**C-**28**D contain Tables 1, and 4-8 which include an illustration of handwriting rendering using two interdependent rendering pipelines (Table 1), an illustration of Specular Wetness techniques (Table 4), overlapping line segments providing in conjunction with particular handwritten inputs (Table 5), an equation showing consistent alpha coverage along edges (Table 6), an equation used to help with the blending techniques (Table 7) and an example of a final composite (Table 8), in accordance with some embodiments.

[0166] FIG. **29** is a functional block diagram of an electronic device in accordance with some embodiments.

[0167] FIGS. **30**A-**30**G illustrate example user interfaces for quickly locating different types of content in a messaging application, in accordance with some embodiments.

[0168] FIGS. **31**A-**31**B are flow diagrams illustrating a method of quickly locating different types of content in a messaging application, in accordance with some embodiments.

[0169] FIG. **32** is a functional block diagram of an electronic device, in accordance with some embodiments.

[0170] FIGS. **33**A-**33**B are flow diagrams illustrating a method of quickly locating different types of content in a messaging application, in accordance with some embodiments.

[0171] FIG. **34** is a functional block diagram of an electronic device, in accordance with some embodiments.

[0172] FIGS. **35**A-**35**AP illustrate exemplary user interfaces for integrating a digital camera into a messaging application in accordance with some embodiments.

[0173] FIGS. **36**A-**36**AL illustrate exemplary user interfaces for integrating search functionality, and posting rich content, in a messaging application, in accordance with some embodiments.

[0174] FIGS. **37**A-**37**DJ illustrate exemplary user interfaces for integrating interactive applications in a messaging application in accordance with some embodiments.

[0175] FIGS. **38**A-**38**AZ illustrate exemplary user interfaces for integrating applications in a messaging application in accordance with some embodiments.

[0176] FIGS. **39**A-**39**AW illustrate exemplary user interfaces for integrating electronic stickers in a messaging application in accordance with some embodiments.

[0177] FIGS. **40**A-**40**W illustrate exemplary user interfaces for interacting with other users of a messaging transcript through an avatar in accordance with some embodiments.

[0178] FIGS. **41**A-**41**H illustrate exemplary user interfaces for integrating data detectors into a messaging application in accordance with some embodiments.

[0179] FIGS. **42**A-**42**D are flow diagrams illustrating a method of capturing and posting digital images within a messaging application in accordance with some embodiments.

[0180] FIG. **43** is a functional block diagram of an electronic device in accordance with some embodiments.

[0181] FIGS. **44**A-**44**D are flow diagrams illustrating a method of searching for and sharing multimedia content within a messaging application in accordance with some embodiments.

[0182] FIG. **45** is a functional block diagram of an electronic device in accordance with some embodiments.

[0183] FIGS. **46**A-**46**C are flow diagrams illustrating a method **4600** of adding an interactive application to a messaging application in accordance with some embodiments.

[0184] FIG. **47** is a functional block diagram of an electronic device in accordance with some embodiments.

[0185] FIGS. **48**A-**48**D are flow diagrams illustrating a method of posting messages to a messaging session from a user interface other than the user interface for the messaging application in accordance with some embodiments.

[0186] FIG. **49** is a functional block diagram of an electronic device in accordance with some embodiments.

[0187] FIGS. **50**A-**50**C are flow diagrams illustrating a method of using an interactive application in a messaging application in accordance with some embodiments.

[0188] FIG. **51** is a functional block diagram of an electronic device in accordance with some embodiments.

[0189] FIGS. **52**A-**52**C are flow diagrams illustrating a method of using an interactive application in a messaging application in accordance with some embodiments.

[0190] FIG. **53** is a functional block diagram of an electronic device in accordance with some embodiments.

[0191] FIGS. **54**A-**54**C are flow diagrams illustrating a method of using an interactive application in a messaging application in accordance with some embodiments.

[0192] FIG. **55** is a functional block diagram of an electronic device in accordance with some embodiments.

[0193] FIGS. **56**A-**56**B are flow diagrams illustrating a method of using an interactive application in a messaging application in accordance with some embodiments.

[0194] FIG. **57** is a functional block diagram of an electronic device in accordance with some embodiments.

[0195] FIG. **58** is a flow diagram illustrating a method of enabling use of an interactive application in a messaging application in accordance with some embodiments.

[0196] FIG. **59** is a functional block diagram of an electronic device in accordance with some embodiments.

[0197] FIGS. **60**A-**60**D are flow diagrams illustrating a method of navigating within a messaging application having associated applications in accordance with some embodiments.

[0198] FIG. **61** is a functional block diagram of an electronic device in accordance with some embodiments.

[0199] FIGS. **62**A-**62**C are flow diagrams illustrating a method of adding a sticker to a messaging transcript in accordance with some embodiments.

[0200] FIG. **63** is a functional block diagram of an electronic device in accordance with some embodiments.

[0201] FIGS. **64**A-**64**C are flow diagrams illustrating a method **6400** of modifying display of electronic stickers in a messaging application in accordance with some embodiments.

[0202] FIG. **65** is a functional block diagram of an electronic device in accordance with some embodiments.

[0203] FIG. **66** is a flow diagram illustrating a method of making payments from a messaging application in accordance with some embodiments.

[0204] FIG. **67** is a functional block diagram of an electronic device in accordance with some embodiments.

[0205] FIGS. **68**A-**68**B are flow diagrams illustrating a method **6800** of interacting with a single user included in a group messaging session in accordance with some embodiments.

[0206] FIG. **69** is a functional block diagram of an electronic device in accordance with some embodiments.

[0207] FIGS. **70**A-**70**B are flow diagrams illustrating a method **7000** of displaying additional information in a messaging session in accordance with some embodiments.

[0208] FIG. **71** is a functional block diagram of an electronic device in accordance with some embodiments.

[0209] FIGS. **72**A-**72**R illustrate exemplary user interfaces for navigating between applications using an application user interface displayed in a messaging user interface, in accordance with some embodiments.

[0210] FIGS. **72**S-**72**AO illustrate exemplary user interfaces for managing applications used within a messaging application, in accordance with some embodiments.

[0211] FIGS. **72**AP-**72**DI illustrate exemplary user interfaces for translating message content in a messaging application, in accordance with some embodiments.

[0212] FIGS. **72**DJ-**72**EV illustrate exemplary user interfaces for connecting message bubbles in a messaging application, in accordance with some embodiments.

[0213] FIGS. **72**EW-**72**FM illustrate exemplary user interfaces for flagging a message bubble, in accordance with some embodiments.

[0214] FIGS. **73**A-**73**D are flow diagrams illustrating a method of navigating between applications using an application user interface displayed in a messaging user interface, in accordance with some embodiments.

[0215] FIGS. **74**A-**74**D are flow diagrams illustrating a method for managing applications used within a messaging application, in accordance with some embodiments.

[0216] FIGS. **75**A-**75**D are flow diagrams illustrating a method for translating message content in a messaging application, in accordance with some embodiments in accordance with some embodiments.

[0217] FIGS. **76**A-**76**C are flow diagrams illustrating a method for translating message content in a messaging application, in accordance with some embodiments.

DESCRIPTION OF EMBODIMENTS

[0218] The methods, devices, and GUIs described herein improve messaging in multiple ways. For example, they make it easier to: acknowledge messages; edit previously sent messages; express what a user is trying to communicate; display private messages; synchronize viewing of content between users; incorporate handwritten inputs; quickly locate content in a message transcript; integrate a camera; integrate search and sharing; integrate interactive applications; integrate stickers; make payments; interact with avatars; make suggestions; navigate among interactive applications; manage interactive applications; translate foreign language text; combine messages into a group; and flag messages.

EXAMPLE DEVICES

[0219] Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings. In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the various described embodiments. However, it will be apparent to one of ordinary skill in the art that the various described embodiments may be practiced without these specific details. In other instances, well-known methods, procedures, components, circuits, and networks have not been described in detail so as not to unnecessarily obscure aspects of the embodiments.

[0220] It will also be understood that, although the terms first, second, etc. are, in some instances, used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first contact could be termed a second contact, and, similarly, a second contact could be termed a first contact, without departing from the scope of the various described embodiments. The first contact and the second contact are both contacts, but they are not the same contact, unless the context clearly indicates otherwise.

[0221] The terminology used in the description of the various described embodiments herein is for the purpose of describing particular embodiments only and is not intended to be limiting. As used in the description of the various described embodiments and the appended claims, the singular forms "a," "an," and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term "and/or" as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms "includes," "including," "comprises," and/or "comprising," when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

[0222] As used herein, the term "if" is, optionally, construed to mean "when" or "upon" or "in response to determining" or "in response to detecting," depending on the context. Similarly, the phrase "if it is determined" or "if [a stated condition or event] is detected" is, optionally, construed to mean "upon determining" or "in response to determining" or "upon detecting [the stated condition or event]" or "in response to detecting [the stated condition or event]," depending on the context.

[0223] Embodiments of electronic devices, user interfaces for such devices, and associated processes for using such devices are described. In some embodiments, the device is a portable communications device, such as a mobile telephone, that also contains other functions, such as PDA and/or music player functions. Example embodiments of portable multifunction devices include, without limitation, the iPhone®, iPod Touch®, and iPad® devices from Apple Inc. of Cupertino, Calif. Other portable electronic devices, such as laptops or tablet computers with touch-sensitive surfaces (e.g., touch-screen displays and/or touchpads), are, optionally, used. It should also be understood that, in some embodiments, the device is not a portable communications device, but is a desktop computer with a touch-sensitive surface (e.g., a touch-screen display and/or a touchpad).

[0224] In the discussion that follows, an electronic device that includes a display and a touch-sensitive surface is described. It should be understood, however, that the electronic device optionally includes one or more other physical user-interface devices, such as a physical keyboard, a mouse and/or a joystick.

[0225] In addition to a messaging application, the device typically supports a variety of other applications, such as one or more of the following: a note taking application, a drawing application, a presentation application, a word processing application, a website creation application, a disk authoring application, a spreadsheet application, a gaming application, a telephone application, a video conferencing application, an e-mail application, a workout support application, a photo management application, a digital camera application, a digital video camera application, a web browsing application, a digital music player application, and/or a digital video player application.

[0226] The various applications that are executed on the device optionally use at least one common physical user-interface device, such as the touch-sensitive surface. One or more functions of the touch-sensitive surface as well as corresponding information displayed on the device are, optionally, adjusted and/or varied from one application to the next and/or within a respective application. In this way, a common physical architecture (such as the touch-sensitive surface) of the device optionally supports the variety of applications with user interfaces that are intuitive and transparent to the user.

[0227] Attention is now directed toward embodiments of portable devices with touch-sensitive displays. FIG. **1**A is a block diagram illustrating portable multifunction device **100** with touch-sensitive display system **112** in accordance with

some embodiments. Touch-sensitive display system **112** is sometimes called a "touch screen" for convenience, and is sometimes simply called a touch-sensitive display. Device **100** includes memory **102** (which optionally includes one or more computer readable storage mediums), memory controller **120**, one or more processing units (CPUs) **122**, peripherals interface **118**, RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, input/output (I/O) subsystem **106**, other input or control devices **116**, and external port **124**. Device **100** optionally includes one or more optical sensors **164**. Device **100** optionally includes one or more intensity sensors **165** for detecting intensities of contacts on device **100** (e.g., a touch-sensitive surface such as touch-sensitive display system **112** of device **100**). Device **100** optionally includes one or more tactile output generators **167** for generating tactile outputs on device **100** (e.g., generating tactile outputs on a touch-sensitive surface such as touch-sensitive display system **112** of device **100** or touchpad **355** of device **300**). These components optionally communicate over one or more communication buses or signal lines **103**.

[0228] As used in the specification and claims, the term "tactile output" refers to physical displacement of a device relative to a previous position of the device, physical displacement of a component (e.g., a touch-sensitive surface) of a device relative to another component (e.g., housing) of the device, or displacement of the component relative to a center of mass of the device that will be detected by a user with the user's sense of touch. For example, in situations where the device or the component of the device is in contact with a surface of a user that is sensitive to touch (e.g., a finger, palm, or other part of a user's hand), the tactile output generated by the physical displacement will be interpreted by the user as a tactile sensation corresponding to a perceived change in physical characteristics of the device or the component of the device. For example, movement of a touch-sensitive surface (e.g., a touch-sensitive display or trackpad) is, optionally, interpreted by the user as a "down click" or "up click" of a physical actuator button. In some cases, a user will feel a tactile sensation such as an "down click" or "up click" even when there is no movement of a physical actuator button associated with the touch-sensitive surface that is physically pressed (e.g., displaced) by the user's movements. As another example, movement of the touch-sensitive surface is, optionally, interpreted or sensed by the user as "roughness" of the touch-sensitive surface, even when there is no change in smoothness of the touch-sensitive surface. While such interpretations of touch by a user will be subject to the individualized sensory perceptions of the user, there are many sensory perceptions of touch that are common to a large majority of users. Thus, when a tactile output is described as corresponding to a particular sensory perception of a user (e.g., an "up click," a "down click," "roughness"), unless otherwise stated, the generated tactile output corresponds to physical displacement of the device or a component thereof that will generate the described sensory perception for a typical (or average) user. Using tactile outputs to provide haptic feedback to a user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

[0229] It should be appreciated that device **100** is only one example of a portable multifunction device, and that device **100** optionally has more or fewer components than shown, optionally combines two or more components, or optionally has a different configuration or arrangement of the components. The various components shown in FIG. **1**A are implemented in hardware, software, firmware, or a combination thereof, including one or more signal processing and/or application specific integrated circuits.

[0230] Memory **102** optionally includes high-speed random access memory and optionally also includes non-volatile memory, such as one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices. Access to memory **102** by other components of device **100**, such as CPU(s) **122** and the peripherals interface **118**, is, optionally, controlled by memory controller **120**.

[0231] Peripherals interface **118** can be used to couple input and output peripherals of the device to CPU(s) **122** and memory **102**. The one or more processors **122** run or execute various software programs and/or sets of instructions stored in memory **102** to perform various functions for device **100** and to process data.

[0232] In some embodiments, peripherals interface **118**, CPU(s) **122**, and memory controller **120** are, optionally, implemented on a single chip, such as chip **104**. In some other embodiments, they are, optionally, implemented on separate chips.

[0233] RF (radio frequency) circuitry **108** receives and sends RF signals, also called electromagnetic signals. RF circuitry **108** converts electrical signals to/from electromagnetic signals and communicates with communications networks and other communications devices via the electromagnetic signals. RF circuitry **108** optionally includes well-known circuitry for performing these functions, including but not limited to an antenna system, an RF transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a CODEC chipset, a subscriber identity module (SIM) card, memory, and so forth. RF circuitry **108** optionally communicates with networks, such as the Internet, also referred to as the World Wide Web (WWW), an intranet and/or a wireless network, such as a cellular telephone network, a wireless local area network (LAN) and/or a metropolitan area network (MAN), and other devices by wireless communication. The wireless communication optionally uses any of a plurality of communications standards, protocols and technologies, including but not limited to Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), high-speed downlink packet access (HSDPA), high-speed uplink packet access (HSDPA), Evolution, Data-Only (EV-DO), HSPA, HSPA+, Dual-Cell HSPA (DC-HSPDA), long term evolution (LTE), near field communication (NFC), wideband code division multiple access (W-CDMA), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Wireless Fidelity (Wi-Fi) (e.g., IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g and/or IEEE 802.11n), voice over Internet Protocol (VoIP), Wi-MAX, a protocol for e-mail (e.g., Internet message access protocol (IMAP) and/or post office protocol (POP)), instant messaging (e.g., extensible messaging and presence protocol (XMPP), Session Initiation Protocol for Instant Messaging and Presence Leveraging Extensions (SIMPLE), Instant Messaging and Presence Service

(IMPS)), and/or Short Message Service (SMS), or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

[0234] Audio circuitry **110**, speaker **111**, and microphone **113** provide an audio interface between a user and device **100**. Audio circuitry **110** receives audio data from peripherals interface **118**, converts the audio data to an electrical signal, and transmits the electrical signal to speaker **111**. Speaker **111** converts the electrical signal to human-audible sound waves. Audio circuitry **110** also receives electrical signals converted by microphone **113** from sound waves. Audio circuitry **110** converts the electrical signal to audio data and transmits the audio data to peripherals interface **118** for processing. Audio data is, optionally, retrieved from and/or transmitted to memory **102** and/or RF circuitry **108** by peripherals interface **118**. In some embodiments, audio circuitry **110** also includes a headset jack (e.g., **212**, FIG. **2**). The headset jack provides an interface between audio circuitry **110** and removable audio input/output peripherals, such as output-only headphones or a headset with both output (e.g., a headphone for one or both ears) and input (e.g., a microphone).

[0235] I/O subsystem **106** couples input/output peripherals on device **100**, such as touch-sensitive display system **112** and other input or control devices **116**, with peripherals interface **118**. I/O subsystem **106** optionally includes display controller **156**, optical sensor controller **158**, intensity sensor controller **159**, haptic feedback controller **161**, and one or more input controllers **160** for other input or control devices. The one or more input controllers **160** receive/send electrical signals from/to other input or control devices **116**. The other input or control devices **116** optionally include physical buttons (e.g., push buttons, rocker buttons, etc.), dials, slider switches, joysticks, click wheels, and so forth. In some alternate embodiments, input controller(s) **160** are, optionally, coupled with any (or none) of the following: a keyboard, infrared port, USB port, stylus, and/or a pointer device such as a mouse. The one or more buttons (e.g., **208**, FIG. **2**) optionally include an up/down button for volume control of speaker **111** and/or microphone **113**. The one or more buttons optionally include a push button (e.g., **206**, FIG. **2**).

[0236] Touch-sensitive display system **112** provides an input interface and an output interface between the device and a user. Display controller **156** receives and/or sends electrical signals from/to touch-sensitive di splay system **112**. Touch-sensitive display system **112** displays visual output to the user. The visual output optionally includes graphics, text, icons, video, and any combination thereof (collectively termed "graphics"). In some embodiments, some or all of the visual output corresponds to user interface objects. As used herein, the term "affordance" refers to a user-interactive graphical user interface object (e.g., a graphical user interface object that is configured to respond to inputs directed toward the graphical user interface object). Examples of user-interactive graphical user interface objects include, without limitation, a button, slider, icon, selectable menu item, switch, hyperlink, or other user interface control.

[0237] Touch-sensitive display system **112** has a touch-sensitive surface, sensor or set of sensors that accepts input from the user based on haptic and/or tactile contact. Touch-sensitive display system **112** and display controller **156** (along with any associated modules and/or sets of instructions in memory **102**) detect contact (and any movement or breaking of the contact) on touch-sensitive display system **112** and converts the detected contact into interaction with user-interface objects (e.g., one or more soft keys, icons, web pages or images) that are displayed on touch-sensitive display system **112**. In an example embodiment, a point of contact between touch-sensitive display system **112** and the user corresponds to a finger of the user or a stylus.

[0238] Touch-sensitive display system **112** optionally uses LCD (liquid crystal display) technology, LPD (light emitting polymer display) technology, or LED (light emitting diode) technology, although other display technologies are used in other embodiments. Touch-sensitive display system **112** and display controller **156** optionally detect contact and any movement or breaking thereof using any of a plurality of touch sensing technologies now known or later developed, including but not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with touch-sensitive display system **112**. In an example embodiment, projected mutual capacitance sensing technology is used, such as that found in the iPhone®, iPod Touch®, and iPad® from Apple Inc. of Cupertino, Calif.

[0239] Touch-sensitive display system **112** optionally has a video resolution in excess of 100 dpi. In some embodiments, the touch screen video resolution is in excess of 400 dpi (e.g., 500 dpi, 800 dpi, or greater). The user optionally makes contact with touch-sensitive display system **112** using any suitable object or appendage, such as a stylus, a finger, and so forth. In some embodiments, the user interface is designed to work with finger-based contacts and gestures, which can be less precise than stylus-based input due to the larger area of contact of a finger on the touch screen. In some embodiments, the device translates the rough finger-based input into a precise pointer/cursor position or command for performing the actions desired by the user.

[0240] In some embodiments, in addition to the touch screen, device **100** optionally includes a touchpad (not shown) for activating or deactivating particular functions. In some embodiments, the touchpad is a touch-sensitive area of the device that, unlike the touch screen, does not display visual output. The touchpad is, optionally, a touch-sensitive surface that is separate from touch-sensitive display system **112** or an extension of the touch-sensitive surface formed by the touch screen.

[0241] Device **100** also includes power system **162** for powering the various components. Power system **162** optionally includes a power management system, one or more power sources (e.g., battery, alternating current (AC)), a recharging system, a power failure detection circuit, a power converter or inverter, a power status indicator (e.g., a light-emitting diode (LED)) and any other components associated with the generation, management and distribution of power in portable devices.

[0242] Device **100** optionally also includes one or more optical sensors **164**. FIG. **1**A shows an optical sensor coupled with optical sensor controller **158** in I/O subsystem **106**. Optical sensor(s) **164** optionally include charge-coupled device (CCD) or complementary metal-oxide semiconductor (CMOS) phototransistors. Optical sensor(s) **164** receive light from the environment, projected through one or more lens, and converts the light to data representing an image. In conjunction with imaging module **143** (also called

a camera module), optical sensor(s) **164** optionally capture still images and/or video. In some embodiments, an optical sensor is located on the back of device **100**, opposite touch-sensitive display system **112** on the front of the device, so that the touch screen is enabled for use as a viewfinder for still and/or video image acquisition. In some embodiments, another optical sensor is located on the front of the device so that the user's image is obtained (e.g., for selfies, for videoconferencing while the user views the other video conference participants on the touch screen, etc.).

[0243] Device **100** optionally also includes one or more contact intensity sensors **165**. FIG. **1**A shows a contact intensity sensor coupled with intensity sensor controller **159** in I/O subsystem **106**. Contact intensity sensor(s) **165** optionally include one or more piezoresistive strain gauges, capacitive force sensors, electric force sensors, piezoelectric force sensors, optical force sensors, capacitive touch-sensitive surfaces, or other intensity sensors (e.g., sensors used to measure the force (or pressure) of a contact on a touch-sensitive surface). Contact intensity sensor(s) **165** receive contact intensity information (e.g., pressure information or a proxy for pressure information) from the environment. In some embodiments, at least one contact intensity sensor is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system **112**). In some embodiments, at least one contact intensity sensor is located on the back of device **100**, opposite touch-screen display system **112** which is located on the front of device **100**.

[0244] Device **100** optionally also includes one or more proximity sensors **166**. FIG. **1**A shows proximity sensor **166** coupled with peripherals interface **118**. Alternately, proximity sensor **166** is coupled with input controller **160** in I/O subsystem **106**. In some embodiments, the proximity sensor turns off and disables touch-sensitive display system **112** when the multifunction device is placed near the user's ear (e.g., when the user is making a phone call).

[0245] Device **100** optionally also includes one or more tactile output generators **167**. FIG. **1**A shows a tactile output generator coupled with haptic feedback controller **161** in I/O subsystem **106**. Tactile output generator(s) **167** optionally include one or more electroacoustic devices such as speakers or other audio components and/or electromechanical devices that convert energy into linear motion such as a motor, solenoid, electroactive polymer, piezoelectric actuator, electrostatic actuator, or other tactile output generating component (e.g., a component that converts electrical signals into tactile outputs on the device). Tactile output generator(s) **167** receive tactile feedback generation instructions from haptic feedback module **133** and generates tactile outputs on device **100** that are capable of being sensed by a user of device **100**. In some embodiments, at least one tactile output generator is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system **112**) and, optionally, generates a tactile output by moving the touch-sensitive surface vertically (e.g., in/out of a surface of device **100**) or laterally (e.g., back and forth in the same plane as a surface of device **100**). In some embodiments, at least one tactile output generator sensor is located on the back of device **100**, opposite touch-sensitive display system **112**, which is located on the front of device **100**.

[0246] Device **100** optionally also includes one or more accelerometers **168**. FIG. **1**A shows accelerometer **168** coupled with peripherals interface **118**. Alternately, accelerometer **168** is, optionally, coupled with an input controller **160** in I/O subsystem **106**. In some embodiments, information is displayed on the touch-screen display in a portrait view or a landscape view based on an analysis of data received from the one or more accelerometers. Device **100** optionally includes, in addition to accelerometer(s) **168**, a magnetometer (not shown) and a GPS (or GLONASS or other global navigation system) receiver (not shown) for obtaining information concerning the location and orientation (e.g., portrait or landscape) of device **100**.

[0247] In some embodiments, the software components stored in memory **102** include operating system **126**, communication module (or set of instructions) **128**, contact/motion module (or set of instructions) **130**, graphics module (or set of instructions) **132**, haptic feedback module (or set of instructions) **133**, text input module (or set of instructions) **134**, Global Positioning System (GPS) module (or set of instructions) **135**, and applications (or sets of instructions) **136**. Furthermore, in some embodiments, memory **102** stores device/global internal state **157**, as shown in FIGS. **1**A and **3**. Device/global internal state **157** includes one or more of: active application state, indicating which applications, if any, are currently active; display state, indicating what applications, views or other information occupy various regions of touch-sensitive display system **112**; sensor state, including information obtained from the device's various sensors and other input or control devices **116**; and location and/or positional information concerning the device's location and/or attitude.

[0248] Operating system **126** (e.g., iOS, Darwin, RTXC, LINUX, UNIX, OS X, WINDOWS, or an embedded operating system such as VxWorks) includes various software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device control, power management, etc.) and facilitates communication between various hardware and software components.

[0249] Communication module **128** facilitates communication with other devices over one or more external ports **124** and also includes various software components for handling data received by RF circuitry **108** and/or external port **124**. External port **124** (e.g., Universal Serial Bus (USB), FIREWIRE, etc.) is adapted for coupling directly to other devices or indirectly over a network (e.g., the Internet, wireless LAN, etc.). In some embodiments, the external port is a multi-pin (e.g., 30-pin) connector that is the same as, or similar to and/or compatible with the 30-pin connector used in some iPhone®, iPod Touch®, and iPad® devices from Apple Inc. of Cupertino, Calif. In some embodiments, the external port is a Lightning connector that is the same as, or similar to and/or compatible with the Lightning connector used in some iPhone®, iPod Touch®, and iPad® devices from Apple Inc. of Cupertino, Calif.

[0250] Contact/motion module **130** optionally detects contact with touch-sensitive display system **112** (in conjunction with display controller **156**) and other touch-sensitive devices (e.g., a touchpad or physical click wheel). Contact/motion module **130** includes various software components for performing various operations related to detection of contact (e.g., by a finger or by a stylus), such as determining if contact has occurred (e.g., detecting a finger-down event), determining an intensity of the contact (e.g., the force or pressure of the contact or a substitute for the force or pressure of the contact), determining if there is movement of the contact and tracking the movement across the touch-

sensitive surface (e.g., detecting one or more finger-dragging events), and determining if the contact has ceased (e.g., detecting a finger-up event or a break in contact). Contact/motion module **130** receives contact data from the touch-sensitive surface. Determining movement of the point of contact, which is represented by a series of contact data, optionally includes determining speed (magnitude), velocity (magnitude and direction), and/or an acceleration (a change in magnitude and/or direction) of the point of contact. These operations are, optionally, applied to single contacts (e.g., one finger contacts or stylus contacts) or to multiple simultaneous contacts (e.g., "multitouch"/multiple finger contacts). In some embodiments, contact/motion module **130** and display controller **156** detect contact on a touchpad.

[0251] Contact/motion module **130** optionally detects a gesture input by a user. Different gestures on the touch-sensitive surface have different contact patterns (e.g., different motions, timings, and/or intensities of detected contacts). Thus, a gesture is, optionally, detected by detecting a particular contact pattern. For example, detecting a finger tap gesture includes detecting a finger-down event followed by detecting a finger-up (lift off) event at the same position (or substantially the same position) as the finger-down event (e.g., at the position of an icon). As another example, detecting a finger swipe gesture on the touch-sensitive surface includes detecting a finger-down event followed by detecting one or more finger-dragging events, and subsequently followed by detecting a finger-up (lift off) event. Similarly, tap, swipe, drag, and other gestures are optionally detected for a stylus by detecting a particular contact pattern for the stylus.

[0252] In some embodiments, detecting a finger tap gesture depends on the length of time between detecting the finger-down event and the finger-up event, but is independent of the intensity of the finger contact between detecting the finger-down event and the finger-up event. In some embodiments, a tap gesture is detected in accordance with a determination that the length of time between the finger-down event and the finger-up event is less than a predetermined value (e.g., less than 0.1, 0.2, 0.3, 0.4 or 0.5 seconds), independent of whether the intensity of the finger contact during the tap meets a given intensity threshold (greater than a nominal contact-detection intensity threshold), such as a light press or deep press intensity threshold. Thus, a finger tap gesture can satisfy particular input criteria that do not require that the characteristic intensity of a contact satisfy a given intensity threshold in order for the particular input criteria to be met. For clarity, the finger contact in a tap gesture typically needs to satisfy a nominal contact-detection intensity threshold, below which the contact is not detected, in order for the finger-down event to be detected. A similar analysis applies to detecting a tap gesture by a stylus or other contact. In cases where the device is capable of detecting a finger or stylus contact hovering over a touch sensitive surface, the nominal contact-detection intensity threshold optionally does not correspond to physical contact between the finger or stylus and the touch sensitive surface.

[0253] The same concepts apply in an analogous manner to other types of gestures. For example, a swipe gesture, a pinch gesture, a depinch gesture, and/or a long press gesture are optionally detected based on the satisfaction of criteria that are either independent of intensities of contacts included in the gesture, or do not require that contact(s) that perform the gesture reach intensity thresholds in order to be recognized. For example., a swipe gesture is detected based on an amount of movement of one or more contacts; a pinch gesture is detected based on movement of two or more contacts towards each other; a depinch gesture is detected based on movement of two or more contacts away from each other; and a long press gesture is detected based on a duration of the contact on the touch-sensitive surface with less than a threshold amount of movement. As such, the statement that particular gesture recognition criteria do not require that the intensity of the contact(s) meet a respective intensity threshold in order for the particular gesture recognition criteria to be met means that the particular gesture recognition criteria are capable of being satisfied if the contact(s) in the gesture do not reach the respective intensity threshold, and are also capable of being satisfied in circumstances where one or more of the contacts in the gesture do reach or exceed the respective intensity threshold. In some embodiments, a tap gesture is detected based on a determination that the finger-down and finger-up event are detected within a predefined time period, without regard to whether the contact is above or below the respective intensity threshold during the predefined time period, and a swipe gesture is detected based on a determination that the contact movement is greater than a predefined magnitude, even if the contact is above the respective intensity threshold at the end of the contact movement. Even in implementations where detection of a gesture is influenced by the intensities of contacts performing the gesture (e.g., the device detects a long press more quickly when the intensity of the contact is above an intensity threshold or delays detection of a tap input when the intensity of the contact is higher), the detection of those gestures does not require that the contacts reach a particular intensity threshold so long as the criteria for recognizing the gesture can be met in circumstances where the contact does not reach the particular intensity threshold (e.g., even if the amount of time that it takes to recognize the gesture changes).

[0254] Contact intensity thresholds, duration thresholds, and movement thresholds are, in some circumstances, combined in a variety of different combinations in order to create heuristics for distinguishing two or more different gestures directed to the same input element or region so that multiple different interactions with the same input element are enabled to provide a richer set of user interactions and responses. The statement that a particular set of gesture recognition criteria do not require that the intensity of the contact(s) meet a respective intensity threshold in order for the particular gesture recognition criteria to be met does not preclude the concurrent evaluation of other intensity-dependent gesture recognition criteria to identify other gestures that do have a criteria that is met when a gesture includes a contact with an intensity above the respective intensity threshold. For example, in some circumstances, first gesture recognition criteria for a first gesture—which do not require that the intensity of the contact(s) meet a respective intensity threshold in order for the first gesture recognition criteria to be met—are in competition with second gesture recognition criteria for a second gesture—which are dependent on the contact(s) reaching the respective intensity threshold. In such competitions, the gesture is, optionally, not recognized as meeting the first gesture recognition criteria for the first gesture if the second gesture recognition criteria for the second gesture are met first. For example, if a contact reaches the respective intensity threshold before the contact

moves by a predefined amount of movement, a deep press gesture is detected rather than a swipe gesture. Conversely, if the contact moves by the predefined amount of movement before the contact reaches the respective intensity threshold, a swipe gesture is detected rather than a deep press gesture. Even in such circumstances, the first gesture recognition criteria for the first gesture still do not require that the intensity of the contact(s) meet a respective intensity threshold in order for the first gesture recognition criteria to be met because if the contact stayed below the respective intensity threshold until an end of the gesture (e.g., a swipe gesture with a contact that does not increase to an intensity above the respective intensity threshold), the gesture would have been recognized by the first gesture recognition criteria as a swipe gesture. As such, particular gesture recognition criteria that do not require that the intensity of the contact(s) meet a respective intensity threshold in order for the particular gesture recognition criteria to be met will (A) in some circumstances ignore the intensity of the contact with respect to the intensity threshold (e.g. for a tap gesture) and/or (B) in some circumstances still be dependent on the intensity of the contact with respect to the intensity threshold in the sense that the particular gesture recognition criteria (e.g., for a long press gesture) will fail if a competing set of intensity-dependent gesture recognition criteria (e.g., for a deep press gesture) recognize an input as corresponding to an intensity-dependent gesture before the particular gesture recognition criteria recognize a gesture corresponding to the input (e.g., for a long press gesture that is competing with a deep press gesture for recognition).

[0255] Graphics module **132** includes various known software components for rendering and displaying graphics on touch-sensitive display system **112** or other display, including components for changing the visual impact (e.g., brightness, transparency, saturation, contrast or other visual property) of graphics that are displayed. As used herein, the term "graphics" includes any object that can be displayed to a user, including without limitation text, web pages, icons (such as user-interface objects including soft keys), digital images, videos, animations and the like.

[0256] In some embodiments, graphics module **132** stores data representing graphics to be used. Each graphic is, optionally, assigned a corresponding code. Graphics module **132** receives, from applications etc., one or more codes specifying graphics to be displayed along with, if necessary, coordinate data and other graphic property data, and then generates screen image data to output to display controller **156**.

[0257] Haptic feedback module **133** includes various software components for generating instructions used by tactile output generator(s) **167** to produce tactile outputs at one or more locations on device **100** in response to user interactions with device **100**.

[0258] Text input module **134**, which is, optionally, a component of graphics module **132**, provides soft keyboards for entering text in various applications (e.g., contacts **137**, e-mail **140**, IM **141**, browser **147**, and any other application that needs text input).

[0259] GPS module **135** determines the location of the device and provides this information for use in various applications (e.g., to telephone **138** for use in location-based dialing, to camera **143** as picture/video metadata, and to applications that provide location-based services such as weather widgets, local yellow page widgets, and map/navigation widgets).

[0260] Applications **136** optionally include the following modules (or sets of instructions), or a subset or superset thereof:

[0261] contacts module **137** (sometimes called an address book or contact list);

[0262] telephone module **138**;

[0263] video conferencing module **139**;

[0264] e-mail client module **140**;

[0265] instant messaging (IM) module **141**;

[0266] news module **142**;

[0267] camera module **143** for still and/or video images;

[0268] image management module **144**;

[0269] browser module **147**;

[0270] calendar module **148**;

[0271] widget modules **149**, which optionally include one or more of: weather widget **149-1**, stocks widget **149-2**, calculator widget **149-3**, alarm clock widget **149-4**, dictionary widget **149-5**, and other widgets obtained by the user, as well as user-created widgets **149-6**;

[0272] widget creator module **150** for making user-created widgets **149-6**;

[0273] search module **151**;

[0274] video and music player module **152**, which is, optionally, made up of a video player module and a music player module;

[0275] notes module **153**;

[0276] map module **154**; and/or

[0277] online video module **155**.

[0278] Examples of other applications **136** that are, optionally, stored in memory **102** include other word processing applications, other image editing applications, drawing applications, presentation applications, JAVA-enabled applications, encryption, digital rights management, voice recognition, and voice replication.

[0279] In conjunction with touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, contacts module **137** includes executable instructions to manage an address book or contact list (e.g., stored in application internal state **192** of contacts module **137** in memory **102** or memory **370**), including: adding name(s) to the address book; deleting name(s) from the address book; associating telephone number(s), e-mail address(es), physical address(es) or other information with a name; associating an image with a name; categorizing and sorting names; providing telephone numbers and/or e-mail addresses to initiate and/or facilitate communications by telephone **138**, video conference **139**, e-mail **140**, or IM **141**; and so forth.

[0280] In conjunction with RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, telephone module **138** includes executable instructions to enter a sequence of characters corresponding to a telephone number, access one or more telephone numbers in address book **137**, modify a telephone number that has been entered, dial a respective telephone number, conduct a conversation and disconnect or hang up when the conversation is com-

pleted. As noted above, the wireless communication optionally uses any of a plurality of communications standards, protocols and technologies.

[0281] In conjunction with RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, touch-sensitive display system **112**, display controller **156**, optical sensor(s) **164**, optical sensor controller **158**, contact module **130**, graphics module **132**, text input module **134**, contact list **137**, and telephone module **138**, videoconferencing module **139** includes executable instructions to initiate, conduct, and terminate a video conference between a user and one or more other participants in accordance with user instructions.

[0282] In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, e-mail client module **140** includes executable instructions to create, send, receive, and manage e-mail in response to user instructions. In conjunction with image management module **144**, e-mail client module **140** makes it very easy to create and send e-mails with still or video images taken with camera module **143**.

[0283] In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, the instant messaging module **141** includes executable instructions to enter a sequence of characters corresponding to an instant message, to modify previously entered characters, to transmit a respective instant message (for example, using a Short Message Service (SMS) or Multimedia Message Service (MMS) protocol for telephony-based instant messages or using XMPP, SIMPLE, Apple Push Notification Service (APNs) or IMPS for Internet-based instant messages), to receive instant messages, to view received instant messages, and to perform the functions of the messaging application described in greater detail below. In some embodiments, transmitted and/or received instant messages optionally include graphics, photos, audio files, video files and/or other attachments as are supported in a MMS and/or an Enhanced Messaging Service (EMS). As used herein, "instant messaging" refers to both telephony-based messages (e.g., messages sent using SMS or MMS) and Internet-based messages (e.g., messages sent using XMPP, SIMPLE, APNs, or IMPS).

[0284] In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, text input module **134**, GPS module **135**, map module **154**, and music player module **146**, news module **142** includes executable instructions to create workouts (e.g., with time, distance, and/or calorie burning goals); communicate with workout sensors (in sports devices and smart watches); receive workout sensor data; calibrate sensors used to monitor a workout; select and play music for a workout; and display, store and transmit workout data.

[0285] In conjunction with touch-sensitive display system **112**, display controller **156**, optical sensor(s) **164**, optical sensor controller **158**, contact module **130**, graphics module **132**, and image management module **144**, camera module **143** includes executable instructions to capture still images or video (including a video stream) and store them into memory **102**, modify characteristics of a still image or video, and/or delete a still image or video from memory **102**.

[0286] In conjunction with touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, text input module **134**, and camera module **143**, image management module **144** includes executable instructions to arrange, modify (e.g., edit), or otherwise manipulate, label, delete, present (e.g., in a digital slide show or album), and store still and/or video images.

[0287] In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display system controller **156**, contact module **130**, graphics module **132**, and text input module **134**, browser module **147** includes executable instructions to browse the Internet in accordance with user instructions, including searching, linking to, receiving, and displaying web pages or portions thereof, as well as attachments and other files linked to web pages.

[0288] In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display system controller **156**, contact module **130**, graphics module **132**, text input module **134**, e-mail client module **140**, and browser module **147**, calendar module **148** includes executable instructions to create, display, modify, and store calendars and data associated with calendars (e.g., calendar entries, to do lists, etc.) in accordance with user instructions.

[0289] In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display system controller **156**, contact module **130**, graphics module **132**, text input module **134**, and browser module **147**, widget modules **149** are mini-applications that are, optionally, downloaded and used by a user (e.g., weather widget **149-1**, stocks widget **149-2**, calculator widget **149-3**, alarm clock widget **149-4**, and dictionary widget **149-5**) or created by the user (e.g., user-created widget **149-6**). In some embodiments, a widget includes an HTML (Hypertext Markup Language) file, a CSS (Cascading Style Sheets) file, and a JavaScript file. In some embodiments, a widget includes an XML (Extensible Markup Language) file and a JavaScript file (e.g., Yahoo! Widgets).

[0290] In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display system controller **156**, contact module **130**, graphics module **132**, text input module **134**, and browser module **147**, the widget creator module **150** includes executable instructions to create widgets (e.g., turning a user-specified portion of a web page into a widget).

[0291] In conjunction with touch-sensitive display system **112**, display system controller **156**, contact module **130**, graphics module **132**, and text input module **134**, search module **151** includes executable instructions to search for text, music, sound, image, video, and/or other files in memory **102** that match one or more search criteria (e.g., one or more user-specified search terms) in accordance with user instructions.

[0292] In conjunction with touch-sensitive display system **112**, display system controller **156**, contact module **130**, graphics module **132**, audio circuitry **110**, speaker **111**, RF circuitry **108**, and browser module **147**, video and music player module **152** includes executable instructions that allow the user to download and play back recorded music and other sound files stored in one or more file formats, such as MP3 or AAC files, and executable instructions to display, present or otherwise play back videos (e.g., on touch-sensitive display system **112**, or on an external display connected wirelessly or via external port **124**). In some embodiments, device **100** optionally includes the functionality of an MP3 player, such as an iPod (trademark of Apple Inc.).

[0293] In conjunction with touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, notes module **153** includes executable instructions to create and manage notes, to do lists, and the like in accordance with user instructions.

[0294] In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display system controller **156**, contact module **130**, graphics module **132**, text input module **134**, GPS module **135**, and browser module **147**, map module **154** includes executable instructions to receive, display, modify, and store maps and data associated with maps (e.g., driving directions; data on stores and other points of interest at or near a particular location; and other location-based data) in accordance with user instructions.

[0295] In conjunction with touch-sensitive display system **112**, display system controller **156**, contact module **130**, graphics module **132**, audio circuitry **110**, speaker **111**, RF circuitry **108**, text input module **134**, e-mail client module **140**, and browser module **147**, online video module **155** includes executable instructions that allow the user to access, browse, receive (e.g., by streaming and/or download), play back (e.g., on the touch screen **112**, or on an external display connected wirelessly or via external port **124**), send an e-mail with a link to a particular online video, and otherwise manage online videos in one or more file formats, such as H.264. In some embodiments, instant messaging module **141**, rather than e-mail client module **140**, is used to send a link to a particular online video.

[0296] Each of the above identified modules and applications correspond to a set of executable instructions for performing one or more functions described above and the methods described in this application (e.g., the computer-implemented methods and other information processing methods described herein). These modules (i.e., sets of instructions) need not be implemented as separate software programs, procedures or modules, and thus various subsets of these modules are, optionally, combined or otherwise re-arranged in various embodiments. In some embodiments, memory **102** optionally stores a subset of the modules and data structures identified above. Furthermore, memory **102** optionally stores additional modules and data structures not described above.

[0297] In some embodiments, device **100** is a device where operation of a predefined set of functions on the device is performed exclusively through a touch screen and/or a touchpad. By using a touch screen and/or a touchpad as the primary input control device for operation of device **100**, the number of physical input control devices (such as push buttons, dials, and the like) on device **100** is, optionally, reduced.

[0298] The predefined set of functions that are performed exclusively through a touch screen and/or a touchpad optionally include navigation between user interfaces. In some embodiments, the touchpad, when touched by the user, navigates device **100** to a main, home, or root menu from any user interface that is displayed on device **100**. In such embodiments, a "menu button" is implemented using a touchpad. In some other embodiments, the menu button is a physical push button or other physical input control device instead of a touchpad.

[0299] FIG. **1**B is a block diagram illustrating example components for event handling in accordance with some embodiments. In some embodiments, memory **102** (in FIG. **1**A) or **370** (FIG. **3**) includes event sorter **170** (e.g., in operating system **126**) and a respective application **136-1** (e.g., any of the aforementioned applications **136**, **137-155**, **380-390**).

[0300] Event sorter **170** receives event information and determines the application **136-1** and application view **191** of application **136-1** to which to deliver the event information. Event sorter **170** includes event monitor **171** and event dispatcher module **174**. In some embodiments, application **136-1** includes application internal state **192**, which indicates the current application view(s) displayed on touch-sensitive display system **112** when the application is active or executing. In some embodiments, device/global internal state **157** is used by event sorter **170** to determine which application(s) is (are) currently active, and application internal state **192** is used by event sorter **170** to determine application views **191** to which to deliver event information.

[0301] In some embodiments, application internal state **192** includes additional information, such as one or more of: resume information to be used when application **136-1** resumes execution, user interface state information that indicates information being displayed or that is ready for display by application **136-1**, a state queue for enabling the user to go back to a prior state or view of application **136-1**, and a redo/undo queue of previous actions taken by the user.

[0302] Event monitor **171** receives event information from peripherals interface **118**. Event information includes information about a sub-event (e.g., a user touch on touch-sensitive display system **112**, as part of a multi-touch gesture). Peripherals interface **118** transmits information it receives from I/O subsystem **106** or a sensor, such as proximity sensor **166**, accelerometer(s) **168**, and/or microphone **113** (through audio circuitry **110**). Information that peripherals interface **118** receives from I/O subsystem **106** includes information from touch-sensitive display system **112** or a touch-sensitive surface.

[0303] In some embodiments, event monitor **171** sends requests to the peripherals interface **118** at predetermined intervals. In response, peripherals interface **118** transmits event information. In other embodiments, peripheral interface **118** transmits event information only when there is a significant event (e.g., receiving an input above a predetermined noise threshold and/or for more than a predetermined duration).

[0304] In some embodiments, event sorter **170** also includes a hit view determination module **172** and/or an active event recognizer determination module **173**.

[0305] Hit view determination module **172** provides software procedures for determining where a sub-event has taken place within one or more views, when touch-sensitive display system **112** displays more than one view. Views are made up of controls and other elements that a user can see on the display.

[0306] Another aspect of the user interface associated with an application is a set of views, sometimes herein called application views or user interface windows, in which information is displayed and touch-based gestures occur. The application views (of a respective application) in which a touch is detected optionally correspond to programmatic levels within a programmatic or view hierarchy of the application. For example, the lowest level view in which a touch is detected is, optionally, called the hit view, and the set of events that are recognized as proper inputs are, optionally, determined based, at least in part, on the hit view of the initial touch that begins a touch-based gesture.

[0307] Hit view determination module **172** receives information related to sub-events of a touch-based gesture. When an application has multiple views organized in a hierarchy, hit view determination module **172** identifies a hit view as the lowest view in the hierarchy which should handle the sub-event. In most circumstances, the hit view is the lowest level view in which an initiating sub-event occurs (i.e., the first sub-event in the sequence of sub-events that form an event or potential event). Once the hit view is identified by the hit view determination module, the hit view typically receives all sub-events related to the same touch or input source for which it was identified as the hit view.

[0308] Active event recognizer determination module **173** determines which view or views within a view hierarchy should receive a particular sequence of sub-events. In some embodiments, active event recognizer determination module **173** determines that only the hit view should receive a particular sequence of sub-events. In other embodiments, active event recognizer determination module **173** determines that all views that include the physical location of a sub-event are actively involved views, and therefore determines that all actively involved views should receive a particular sequence of sub-events. In other embodiments, even if touch sub-events were entirely confined to the area associated with one particular view, views higher in the hierarchy would still remain as actively involved views.

[0309] Event dispatcher module **174** dispatches the event information to an event recognizer (e.g., event recognizer **180**). In embodiments including active event recognizer determination module **173**, event dispatcher module **174** delivers the event information to an event recognizer determined by active event recognizer determination module **173**. In some embodiments, event dispatcher module **174** stores in an event queue the event information, which is retrieved by a respective event receiver module **182**.

[0310] In some embodiments, operating system **126** includes event sorter **170**. Alternatively, application **136-1** includes event sorter **170**. In yet other embodiments, event sorter **170** is a stand-alone module, or a part of another module stored in memory **102**, such as contact/motion module **130**.

[0311] In some embodiments, application **136-1** includes a plurality of event handlers **190** and one or more application views **191**, each of which includes instructions for handling touch events that occur within a respective view of the application's user interface. Each application view **191** of the application **136-1** includes one or more event recognizers **180**. Typically, a respective application view **191** includes a plurality of event recognizers **180**. In other embodiments, one or more of event recognizers **180** are part of a separate module, such as a user interface kit (not shown) or a higher level object from which application **136-1** inherits methods and other properties. In some embodiments, a respective event handler **190** includes one or more of: data updater **176**, object updater **177**, GUI updater **178**, and/or event data **179** received from event sorter **170**. Event handler **190** optionally utilizes or calls data updater **176**, object updater **177** or GUI updater **178** to update the application internal state **192**. Alternatively, one or more of the application views **191** includes one or more respective event handlers **190**. Also, in some embodiments, one or more of data updater **176**, object updater **177**, and GUI updater **178** are included in a respective application view **191**.

[0312] A respective event recognizer **180** receives event information (e.g., event data **179**) from event sorter **170**, and identifies an event from the event information. Event recognizer **180** includes event receiver **182** and event comparator **184**. In some embodiments, event recognizer **180** also includes at least a subset of: metadata **183**, and event delivery instructions **188** (which optionally include sub-event delivery instructions).

[0313] Event receiver **182** receives event information from event sorter **170**. The event information includes information about a sub-event, for example, a touch or a touch movement. Depending on the sub-event, the event information also includes additional information, such as location of the sub-event. When the sub-event concerns motion of a touch, the event information optionally also includes speed and direction of the sub-event. In some embodiments, events include rotation of the device from one orientation to another (e.g., from a portrait orientation to a landscape orientation, or vice versa), and the event information includes corresponding information about the current orientation (also called device attitude) of the device.

[0314] Event comparator **184** compares the event information to predefined event or sub-event definitions and, based on the comparison, determines an event or sub-event, or determines or updates the state of an event or sub-event. In some embodiments, event comparator **184** includes event definitions **186**. Event definitions **186** contain definitions of events (e.g., predefined sequences of sub-events), for example, event **1** (**187-1**), event **2** (**187-2**), and others. In some embodiments, sub-events in an event **187** include, for example, touch begin, touch end, touch movement, touch cancellation, and multiple touching. In one example, the definition for event **1** (**187-1**) is a double tap on a displayed object. The double tap, for example, comprises a first touch (touch begin) on the displayed object for a predetermined phase, a first lift-off (touch end) for a predetermined phase, a second touch (touch begin) on the displayed object for a predetermined phase, and a second lift-off (touch end) for a predetermined phase. In another example, the definition for event **2** (**187-2**) is a dragging on a displayed object. The dragging, for example, comprises a touch (or contact) on the displayed object for a predetermined phase, a movement of the touch across touch-sensitive display system **112**, and lift-off of the touch (touch end). In some embodiments, the event also includes information for one or more associated event handlers **190**.

[0315] In some embodiments, event definition **187** includes a definition of an event for a respective user-interface object. In some embodiments, event comparator **184** performs a hit test to determine which user-interface object is associated with a sub-event. For example, in an application view in which three user-interface objects are displayed on touch-sensitive display system **112**, when a touch is detected on touch-sensitive display system **112**, event comparator **184** performs a hit test to determine which of the three user-interface objects is associated with the touch (sub-event). If each displayed object is associated with a respective event handler **190**, the event comparator uses the result of the hit test to determine which event handler **190** should be activated. For example, event comparator **184** selects an event handler associated with the sub-event and the object triggering the hit test.

[0316] In some embodiments, the definition for a respective event **187** also includes delayed actions that delay

delivery of the event information until after it has been determined whether the sequence of sub-events does or does not correspond to the event recognizer's event type.

[0317] When a respective event recognizer **180** determines that the series of sub-events do not match any of the events in event definitions **186**, the respective event recognizer **180** enters an event impossible, event failed, or event ended state, after which it disregards subsequent sub-events of the touch-based gesture. In this situation, other event recognizers, if any, that remain active for the hit view continue to track and process sub-events of an ongoing touch-based gesture.

[0318] In some embodiments, a respective event recognizer **180** includes metadata **183** with configurable properties, flags, and/or lists that indicate how the event delivery system should perform sub-event delivery to actively involved event recognizers. In some embodiments, metadata **183** includes configurable properties, flags, and/or lists that indicate how event recognizers interact, or are enabled to interact, with one another. In some embodiments, metadata **183** includes configurable properties, flags, and/or lists that indicate whether sub-events are delivered to varying levels in the view or programmatic hierarchy.

[0319] In some embodiments, a respective event recognizer **180** activates event handler **190** associated with an event when one or more particular sub-events of an event are recognized. In some embodiments, a respective event recognizer **180** delivers event information associated with the event to event handler **190**. Activating an event handler **190** is distinct from sending (and deferred sending) sub-events to a respective hit view. In some embodiments, event recognizer **180** throws a flag associated with the recognized event, and event handler **190** associated with the flag catches the flag and performs a predefined process.

[0320] In some embodiments, event delivery instructions **188** include sub-event delivery instructions that deliver event information about a sub-event without activating an event handler. Instead, the sub-event delivery instructions deliver event information to event handlers associated with the series of sub-events or to actively involved views. Event handlers associated with the series of sub-events or with actively involved views receive the event information and perform a predetermined process.

[0321] In some embodiments, data updater **176** creates and updates data used in application **136-1**. For example, data updater **176** updates the telephone number used in contacts module **137**, or stores a video file used in video and music player module **152**. In some embodiments, object updater **177** creates and updates objects used in application **136-1**. For example, object updater **177** creates a new user-interface object or updates the position of a user-interface object. GUI updater **178** updates the GUI. For example, GUI updater **178** prepares display information and sends it to graphics module **132** for display on a touch-sensitive display.

[0322] In some embodiments, event handler(s) **190** includes or has access to data updater **176**, object updater **177**, and GUI updater **178**. In some embodiments, data updater **176**, object updater **177**, and GUI updater **178** are included in a single module of a respective application **136-1** or application view **191**. In other embodiments, they are included in two or more software modules.

[0323] It shall be understood that the foregoing discussion regarding event handling of user touches on touch-sensitive displays also applies to other forms of user inputs to operate multifunction devices **100** with input-devices, not all of which are initiated on touch screens. For example, mouse movement and mouse button presses, optionally coordinated with single or multiple keyboard presses or holds; contact movements such as taps, drags, scrolls, etc., on touch-pads; pen stylus inputs; movement of the device; oral instructions; detected eye movements; biometric inputs; and/or any combination thereof are optionally utilized as inputs corresponding to sub-events which define an event to be recognized.

[0324] FIG. **2** illustrates a portable multifunction device **100** having a touch screen (e.g., touch-sensitive display system **112**, FIG. **1**A) in accordance with some embodiments. The touch screen optionally displays one or more graphics within user interface (UI) **200**. In this embodiment, as well as others described below, a user is enabled to select one or more of the graphics by making a gesture on the graphics, for example, with one or more fingers **202** (not drawn to scale in the figure) or one or more styluses **203** (not drawn to scale in the figure). In some embodiments, selection of one or more graphics occurs when the user breaks contact with the one or more graphics. In some embodiments, the gesture optionally includes one or more taps, one or more swipes (from left to right, right to left, upward and/or downward) and/or a rolling of a finger (from right to left, left to right, upward and/or downward) that has made contact with device **100**. In some implementations or circumstances, inadvertent contact with a graphic does not select the graphic. For example, a swipe gesture that sweeps over an application icon optionally does not select the corresponding application when the gesture corresponding to selection is a tap.

[0325] Device **100** optionally also includes one or more physical buttons, such as "home" or menu button **204**. As described previously, menu button **204** is, optionally, used to navigate to any application **136** in a set of applications that are, optionally executed on device **100**. Alternatively, in some embodiments, the menu button is implemented as a soft key in a GUI displayed on the touch-screen display.

[0326] In some embodiments, device **100** includes the touch-screen display, menu button **204**, push button **206** for powering the device on/off and locking the device, volume adjustment button(s) **208**, Subscriber Identity Module (SIM) card slot **210**, head set jack **212**, and docking/charging external port **124**. Push button **206** is, optionally, used to turn the power on/off on the device by depressing the button and holding the button in the depressed state for a predefined time interval; to lock the device by depressing the button and releasing the button before the predefined time interval has elapsed; and/or to unlock the device or initiate an unlock process. In some embodiments, device **100** also accepts verbal input for activation or deactivation of some functions through microphone **113**. Device **100** also, optionally, includes one or more contact intensity sensors **165** for detecting intensities of contacts on touch-sensitive display system **112** and/or one or more tactile output generators **167** for generating tactile outputs for a user of device **100**.

[0327] FIG. **3** is a block diagram of an example multifunction device with a display and a touch-sensitive surface in accordance with some embodiments. Device **300** need not be portable. In some embodiments, device **300** is a laptop computer, a desktop computer, a tablet computer, a multimedia player device, a navigation device, an educational device (such as a child's learning toy), a gaming system, or

a control device (e.g., a home or industrial controller). Device **300** typically includes one or more processing units (CPU's) **310**, one or more network or other communications interfaces **360**, memory **370**, and one or more communication buses **320** for interconnecting these components. Communication buses **320** optionally include circuitry (sometimes called a chipset) that interconnects and controls communications between system components. Device **300** includes input/output (I/O) interface **330** comprising display **340**, which is typically a touch-screen display. I/O interface **330** also optionally includes a keyboard and/or mouse (or other pointing device) **350** and touchpad **355**, tactile output generator **357** for generating tactile outputs on device **300** (e.g., similar to tactile output generator(s) **167** described above with reference to FIG. **1**A), sensors **359** (e.g., optical, acceleration, proximity, touch-sensitive, and/or contact intensity sensors similar to contact intensity sensor(s) **165** described above with reference to FIG. **1**A). Memory **370** includes high-speed random access memory, such as DRAM, SRAM, DDR RAM or other random access solid state memory devices; and optionally includes non-volatile memory, such as one or more magnetic disk storage devices, optical disk storage devices, flash memory devices, or other non-volatile solid state storage devices. Memory **370** optionally includes one or more storage devices remotely located from CPU(s) **310**. In some embodiments, memory **370** stores programs, modules, and data structures analogous to the programs, modules, and data structures stored in memory **102** of portable multifunction device **100** (FIG. **1**A), or a subset thereof. Furthermore, memory **370** optionally stores additional programs, modules, and data structures not present in memory **102** of portable multifunction device **100**. For example, memory **370** of device **300** optionally stores drawing module **380**, presentation module **382**, word processing module **384**, website creation module **386**, disk authoring module **388**, and/or spreadsheet module **390**, while memory **102** of portable multifunction device **100** (FIG. **1**A) optionally does not store these modules.

[0328] Each of the above identified elements in FIG. **3** are, optionally, stored in one or more of the previously mentioned memory devices. Each of the above identified modules corresponds to a set of instructions for performing a function described above. The above identified modules or programs (i.e., sets of instructions) need not be implemented as separate software programs, procedures or modules, and thus various subsets of these modules are, optionally, combined or otherwise re-arranged in various embodiments. In some embodiments, memory **370** optionally stores a subset of the modules and data structures identified above. Furthermore, memory **370** optionally stores additional modules and data structures not described above.

[0329] Attention is now directed towards embodiments of user interfaces ("UI") that are, optionally, implemented on portable multifunction device **100**.

[0330] FIG. **4**A illustrates an example user interface for a menu of applications on portable multifunction device **100** in accordance with some embodiments. Similar user interfaces are, optionally, implemented on device **300**. In some embodiments, user interface **400** includes the following elements, or a subset or superset thereof:

[0331] Signal strength indicator(s) **402** for wireless communication(s), such as cellular and Wi-Fi signals;

[0332] Time **404**;

[0333] Bluetooth indicator **405**;

[0334] Battery status indicator **406**;

[0335] Tray **408** with icons for frequently used applications, such as:

- **[0336]** Icon **416** for telephone module **138**, labeled "Phone," which optionally includes an indicator **414** of the number of missed calls or voicemail messages;
- **[0337]** Icon **418** for e-mail client module **140**, labeled "Mail," which optionally includes an indicator **410** of the number of unread e-mails;
- **[0338]** Icon **420** for browser module **147**, labeled "Browser;" and
- **[0339]** Icon **422** for video and music player module **152**, also referred to as iPod (trademark of Apple Inc.) module **152**, labeled "iPod;" and

[0340] Icons for other applications, such as:

- **[0341]** Icon **424** for IM module **141**, labeled "Messages;"
- **[0342]** Icon **426** for calendar module **148**, labeled "Calendar;"
- **[0343]** Icon **428** for image management module **144**, labeled "Photos;"
- **[0344]** Icon **430** for camera module **143**, labeled "Camera;"
- **[0345]** Icon **432** for online video module **155**, labeled "Online Video;"
- **[0346]** Icon **434** for stocks widget **149-2**, labeled "Stocks;"
- **[0347]** Icon **436** for map module **154**, labeled "Map;"
- **[0348]** Icon **438** for weather widget **149-1**, labeled "Weather;"
- **[0349]** Icon **440** for alarm clock widget **149-4**, labeled "Clock;"
- **[0350]** Icon **442** for news module **142**, labeled "News;"
- **[0351]** Icon **444** for notes module **153**, labeled "Notes;" and
- **[0352]** Icon **446** for a settings application or module, which provides access to settings for device **100** and its various applications **136**.

[0353] It should be noted that the icon labels illustrated in FIG. **4**A are merely examples. For example, in some embodiments, icon **422** for video and music player module **152** is labeled "Music" or "Music Player." Other labels are, optionally, used for various application icons. In some embodiments, a label for a respective application icon includes a name of an application corresponding to the respective application icon. In some embodiments, a label for a particular application icon is distinct from a name of an application corresponding to the particular application icon.

[0354] FIG. **4**B illustrates an example user interface on a device (e.g., device **300**, FIG. **3**) with a touch-sensitive surface **451** (e.g., a tablet or touchpad **355**, FIG. **3**) that is separate from the display **450**. Device **300** also, optionally, includes one or more contact intensity sensors (e.g., one or more of sensors **359**) for detecting intensities of contacts on touch-sensitive surface **451** and/or one or more tactile output generators **357** for generating tactile outputs for a user of device **300**.

[0355] FIG. **4**B illustrates an example user interface on a device (e.g., device **300**, FIG. **3**) with a touch-sensitive

surface **451** (e.g., a tablet or touchpad **355**, FIG. **3**) that is separate from the display **450**. Although many of the examples that follow will be given with reference to inputs on touch screen display **112** (where the touch sensitive surface and the display are combined), in some embodiments, the device detects inputs on a touch-sensitive surface that is separate from the display, as shown in FIG. **4**B. In some embodiments, the touch-sensitive surface (e.g., **451** in FIG. **4**B) has a primary axis (e.g., **452** in FIG. **4**B) that corresponds to a primary axis (e.g., **453** in FIG. **4**B) on the display (e.g., **450**). In accordance with these embodiments, the device detects contacts (e.g., **460** and **462** in FIG. **4**B) with the touch-sensitive surface **451** at locations that correspond to respective locations on the display (e.g., in FIG. **4**B, **460** corresponds to **468** and **462** corresponds to **470**). In this way, user inputs (e.g., contacts **460** and **462**, and movements thereof) detected by the device on the touch-sensitive surface (e.g., **451** in FIG. **4**B) are used by the device to manipulate the user interface on the display (e.g., **450** in FIG. **4**B) of the multifunction device when the touch-sensitive surface is separate from the display. It should be understood that similar methods are, optionally, used for other user interfaces described herein.

[0356] Additionally, while the following examples are given primarily with reference to finger inputs (e.g., finger contacts, finger tap gestures, finger swipe gestures, etc.), it should be understood that, in some embodiments, one or more of the finger inputs are replaced with input from another input device (e.g., a mouse based input or a stylus input). For example, a swipe gesture is, optionally, replaced with a mouse click (e.g., instead of a contact) followed by movement of the cursor along the path of the swipe (e.g., instead of movement of the contact). As another example, a tap gesture is, optionally, replaced with a mouse click while the cursor is located over the location of the tap gesture (e.g., instead of detection of the contact followed by ceasing to detect the contact). Similarly, when multiple user inputs are simultaneously detected, it should be understood that multiple computer mice are, optionally, used simultaneously, or a mouse and finger contacts are, optionally, used simultaneously.

[0357] As used herein, the term "focus selector" is an input element that indicates a current part of a user interface with which a user is interacting. In some implementations that include a cursor or other location marker, the cursor acts as a "focus selector," so that when an input (e.g., a press input) is detected on a touch-sensitive surface (e.g., touchpad **355** in FIG. **3** or touch-sensitive surface **451** in FIG. **4**B) while the cursor is over a particular user interface element (e.g., a button, window, slider or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations that include a touch-screen display (e.g., touch-sensitive display system **112** in FIG. **1**A or the touch screen in FIG. **4**A) that enables direct interaction with user interface elements on the touch-screen display, a detected contact on the touch-screen acts as a "focus selector," so that when an input (e.g., a press input by the contact) is detected on the touch-screen display at a location of a particular user interface element (e.g., a button, window, slider or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations, focus is moved from one region of a user interface to another region of the user interface without corresponding movement of a cursor or movement of a contact on a touch-screen display (e.g., by using a tab key or arrow keys to move focus from one button to another button); in these implementations, the focus selector moves in accordance with movement of focus between different regions of the user interface. Without regard to the specific form taken by the focus selector, the focus selector is generally the user interface element (or contact on a touch-screen display) that is controlled by the user so as to communicate the user's intended interaction with the user interface (e.g., by indicating, to the device, the element of the user interface with which the user is intending to interact). For example, the location of a focus selector (e.g., a cursor, a contact, or a selection box) over a respective button while a press input is detected on the touch-sensitive surface (e.g., a touchpad or touch screen) will indicate that the user is intending to activate the respective button (as opposed to other user interface elements shown on a display of the device).

[0358] As used in the specification and claims, the term "intensity" of a contact on a touch-sensitive surface refers to the force or pressure (force per unit area) of a contact (e.g., a finger contact or a stylus contact) on the touch-sensitive surface, or to a substitute (proxy) for the force or pressure of a contact on the touch-sensitive surface. The intensity of a contact has a range of values that includes at least four distinct values and more typically includes hundreds of distinct values (e.g., at least 256). Intensity of a contact is, optionally, determined (or measured) using various approaches and various sensors or combinations of sensors. For example, one or more force sensors underneath or adjacent to the touch-sensitive surface are, optionally, used to measure force at various points on the touch-sensitive surface. In some implementations, force measurements from multiple force sensors are combined (e.g., a weighted average or a sum) to determine an estimated force of a contact. Similarly, a pressure-sensitive tip of a stylus is, optionally, used to determine a pressure of the stylus on the touch-sensitive surface. Alternatively, the size of the contact area detected on the touch-sensitive surface and/or changes thereto, the capacitance of the touch-sensitive surface proximate to the contact and/or changes thereto, and/or the resistance of the touch-sensitive surface proximate to the contact and/or changes thereto are, optionally, used as a substitute for the force or pressure of the contact on the touch-sensitive surface. In some implementations, the substitute measurements for contact force or pressure are used directly to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is described in units corresponding to the substitute measurements). In some implementations, the substitute measurements for contact force or pressure are converted to an estimated force or pressure and the estimated force or pressure is used to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is a pressure threshold measured in units of pressure). Using the intensity of a contact as an attribute of a user input allows for user access to additional device functionality that may otherwise not be readily accessible by the user on a reduced-size device with limited real estate for displaying affordances (e.g., on a touch-sensitive display) and/or receiving user input (e.g., via a touch-sensitive display, a touch-sensitive surface, or a physical/mechanical control such as a knob or a button).

[0359] In some embodiments, contact/motion module **130** uses a set of one or more intensity thresholds to determine whether an operation has been performed by a user (e.g., to determine whether a user has "clicked" on an icon). In some embodiments, at least a subset of the intensity thresholds are determined in accordance with software parameters (e.g., the intensity thresholds are not determined by the activation thresholds of particular physical actuators and can be adjusted without changing the physical hardware of device **100**). For example, a mouse "click" threshold of a trackpad or touch-screen display can be set to any of a large range of predefined thresholds values without changing the trackpad or touch-screen display hardware. Additionally, in some implementations a user of the device is provided with software settings for adjusting one or more of the set of intensity thresholds (e.g., by adjusting individual intensity thresholds and/or by adjusting a plurality of intensity thresholds at once with a system-level click "intensity" parameter).

[0360] As used in the specification and claims, the term "characteristic intensity" of a contact is a characteristic of the contact based on one or more intensities of the contact. In some embodiments, the characteristic intensity is based on multiple intensity samples. The characteristic intensity is, optionally, based on a predefined number of intensity samples, or a set of intensity samples collected during a predetermined time period (e.g., 0.05, 0.1, 0.2, 0.5, 1, 2, 5, 10 seconds) relative to a predefined event (e.g., after detecting the contact, prior to detecting liftoff of the contact, before or after detecting a start of movement of the contact, prior to detecting an end of the contact, before or after detecting an increase in intensity of the contact, and/or before or after detecting a decrease in intensity of the contact). A characteristic intensity of a contact is, optionally based on one or more of: a maximum value of the intensities of the contact, a mean value of the intensities of the contact, an average value of the intensities of the contact, a top 10 percentile value of the intensities of the contact, a value at the half maximum of the intensities of the contact, a value at the 90 percent maximum of the intensities of the contact, or the like. In some embodiments, the duration of the contact is used in determining the characteristic intensity (e.g., when the characteristic intensity is an average of the intensity of the contact over time). In some embodiments, the characteristic intensity is compared to a set of one or more intensity thresholds to determine whether an operation has been performed by a user. For example, the set of one or more intensity thresholds may include a first intensity threshold and a second intensity threshold. In this example, a contact with a characteristic intensity that does not exceed the first threshold results in a first operation, a contact with a characteristic intensity that exceeds the first intensity threshold and does not exceed the second intensity threshold results in a second operation, and a contact with a characteristic intensity that exceeds the second intensity threshold results in a third operation. In some embodiments, a comparison between the characteristic intensity and one or more intensity thresholds is used to determine whether or not to perform one or more operations (e.g., whether to perform a respective option or forgo performing the respective operation) rather than being used to determine whether to perform a first operation or a second operation.

[0361] In some embodiments, a portion of a gesture is identified for purposes of determining a characteristic intensity. For example, a touch-sensitive surface may receive a continuous swipe contact transitioning from a start location and reaching an end location (e.g., a drag gesture), at which point the intensity of the contact increases. In this example, the characteristic intensity of the contact at the end location may be based on only a portion of the continuous swipe contact, and not the entire swipe contact (e.g., only the portion of the swipe contact at the end location). In some embodiments, a smoothing algorithm may be applied to the intensities of the swipe contact prior to determining the characteristic intensity of the contact. For example, the smoothing algorithm optionally includes one or more of: an unweighted sliding-average smoothing algorithm, a triangular smoothing algorithm, a median filter smoothing algorithm, and/or an exponential smoothing algorithm. In some circumstances, these smoothing algorithms eliminate narrow spikes or dips in the intensities of the swipe contact for purposes of determining a characteristic intensity.

[0362] The user interface figures described herein optionally include various intensity diagrams that show the current intensity of the contact on the touch-sensitive surface relative to one or more intensity thresholds (e.g., a contact detection intensity threshold IT_0, a light press intensity threshold IT_L, a deep press intensity threshold IT_D (e.g., that is at least initially higher than I_L), and/or one or more other intensity thresholds (e.g., an intensity threshold I_H that is lower than I_L)). This intensity diagram is typically not part of the displayed user interface, but is provided to aid in the interpretation of the figures. In some embodiments, the light press intensity threshold corresponds to an intensity at which the device will perform operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, the deep press intensity threshold corresponds to an intensity at which the device will perform operations that are different from operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, when a contact is detected with a characteristic intensity below the light press intensity threshold (e.g., and above a nominal contact-detection intensity threshold IT_0 below which the contact is no longer detected), the device will move a focus selector in accordance with movement of the contact on the touch-sensitive surface without performing an operation associated with the light press intensity threshold or the deep press intensity threshold. Generally, unless otherwise stated, these intensity thresholds are consistent between different sets of user interface figures.

[0363] In some embodiments, the response of the device to inputs detected by the device depends on criteria based on the contact intensity during the input. For example, for some "light press" inputs, the intensity of a contact exceeding a first intensity threshold during the input triggers a first response. In some embodiments, the response of the device to inputs detected by the device depends on criteria that include both the contact intensity during the input and time-based criteria. For example, for some "deep press" inputs, the intensity of a contact exceeding a second intensity threshold during the input, greater than the first intensity threshold for a light press, triggers a second response only if a delay time has elapsed between meeting the first intensity threshold and meeting the second intensity threshold. This delay time is typically less than 200 ms in duration (e.g., 40, 100, or 120 ms, depending on the magnitude of the second intensity threshold, with the delay time increasing as the second intensity threshold increases). This delay time helps to avoid accidental deep press inputs. As another

example, for some "deep press" inputs, there is a reduced-sensitivity time period that occurs after the time at which the first intensity threshold is met. During the reduced-sensitivity time period, the second intensity threshold is increased. This temporary increase in the second intensity threshold also helps to avoid accidental deep press inputs. For other deep press inputs, the response to detection of a deep press input does not depend on time-based criteria.

[0364] In some embodiments, one or more of the input intensity thresholds and/or the corresponding outputs vary based on one or more factors, such as user settings, contact motion, input timing, application running, rate at which the intensity is applied, number of concurrent inputs, user history, environmental factors (e.g., ambient noise), focus selector position, and the like. Example factors are described in U.S. patent application Ser. Nos. 14/399,606 and 14/624,296, which are incorporated by reference herein in their entireties.

[0365] For example, FIG. **4**C illustrates a dynamic intensity threshold **480** that changes over time based in part on the intensity of touch input **476** over time. Dynamic intensity threshold **480** is a sum of two components, first component **474** that decays over time after a predefined delay time p**1** from when touch input **476** is initially detected, and second component **478** that trails the intensity of touch input **476** over time. The initial high intensity threshold of first component **474** reduces accidental triggering of a "deep press" response, while still allowing an immediate "deep press" response if touch input **476** provides sufficient intensity. Second component **478** reduces unintentional triggering of a "deep press" response by gradual intensity fluctuations of in a touch input. In some embodiments, when touch input **476** satisfies dynamic intensity threshold **480** (e.g., at point **481** in FIG. **4**C), the "deep press" response is triggered.

[0366] FIG. **4**D illustrates another dynamic intensity threshold **486** (e.g., intensity threshold I_D). FIG. **4**D also illustrates two other intensity thresholds: a first intensity threshold I_H and a second intensity threshold I_L. In FIG. **4**D, although touch input **484** satisfies the first intensity threshold I_H and the second intensity threshold I_L prior to time p**2**, no response is provided until delay time p**2** has elapsed at time **482**. Also in FIG. **4**D, dynamic intensity threshold **486** decays over time, with the decay starting at time **488** after a predefined delay time p**1** has elapsed from time **482** (when the response associated with the second intensity threshold I_L was triggered). This type of dynamic intensity threshold reduces accidental triggering of a response associated with the dynamic intensity threshold ID immediately after, or concurrently with, triggering a response associated with a lower intensity threshold, such as the first intensity threshold I_H or the second intensity threshold I_L.

[0367] FIG. **4**E illustrate yet another dynamic intensity threshold **492** (e.g., intensity threshold ID). In FIG. **4**E, a response associated with the intensity threshold I_L is triggered after the delay time p**2** has elapsed from when touch input **490** is initially detected. Concurrently, dynamic intensity threshold **492** decays after the predefined delay time p**1** has elapsed from when touch input **490** is initially detected. So a decrease in intensity of touch input **490** after triggering the response associated with the intensity threshold I_L, followed by an increase in the intensity of touch input **490**, without releasing touch input **490**, can trigger a response associated with the intensity threshold I_D (e.g., at time **494**) even when the intensity of touch input **490** is below another intensity threshold, for example, the intensity threshold I_L.

[0368] An increase of characteristic intensity of the contact from an intensity below the light press intensity threshold IT_L to an intensity between the light press intensity threshold IT_L and the deep press intensity threshold IT_D is sometimes referred to as a "light press" input. An increase of characteristic intensity of the contact from an intensity below the deep press intensity threshold IT_D to an intensity above the deep press intensity threshold IT_D S is sometimes referred to as a "deep press" input. An increase of characteristic intensity of the contact from an intensity below the contact-detection intensity threshold IT_0 to an intensity between the contact-detection intensity threshold IT_0 and the light press intensity threshold IT_L is sometimes referred to as detecting the contact on the touch-surface. A decrease of characteristic intensity of the contact from an intensity above the contact-detection intensity threshold IT_0 to an intensity below the contact-detection intensity threshold IT_0 is sometimes referred to as detecting liftoff of the contact from the touch-surface. In some embodiments IT_0 is zero. In some embodiments, IT_0 is greater than zero. In some illustrations a shaded circle or oval is used to represent intensity of a contact on the touch-sensitive surface. In some illustrations, a circle or oval without shading is used represent a respective contact on the touch-sensitive surface without specifying the intensity of the respective contact.

[0369] In some embodiments, described herein, one or more operations are performed in response to detecting a gesture that includes a respective press input or in response to detecting the respective press input performed with a respective contact (or a plurality of contacts), where the respective press input is detected based at least in part on detecting an increase in intensity of the contact (or plurality of contacts) above a press-input intensity threshold. In some embodiments, the respective operation is performed in response to detecting the increase in intensity of the respective contact above the press-input intensity threshold (e.g., the respective operation is performed on a "down stroke" of the respective press input). In some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent decrease in intensity of the respective contact below the press-input threshold (e.g., the respective operation is performed on an "up stroke" of the respective press input).

[0370] In some embodiments, the device employs intensity hysteresis to avoid accidental inputs sometimes termed "jitter," where the device defines or selects a hysteresis intensity threshold with a predefined relationship to the press-input intensity threshold (e.g., the hysteresis intensity threshold is X intensity units lower than the press-input intensity threshold or the hysteresis intensity threshold is 75%, 90%, or some reasonable proportion of the press-input intensity threshold). Thus, in some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the hysteresis intensity threshold that corresponds to the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent decrease in intensity of the respective contact below the hysteresis

intensity threshold (e.g., the respective operation is performed on an "up stroke" of the respective press input). Similarly, in some embodiments, the press input is detected only when the device detects an increase in intensity of the contact from an intensity at or below the hysteresis intensity threshold to an intensity at or above the press-input intensity threshold and, optionally, a subsequent decrease in intensity of the contact to an intensity at or below the hysteresis intensity, and the respective operation is performed in response to detecting the press input (e.g., the increase in intensity of the contact or the decrease in intensity of the contact, depending on the circumstances).

[0371] For ease of explanation, the description of operations performed in response to a press input associated with a press-input intensity threshold or in response to a gesture including the press input are, optionally, triggered in response to detecting: an increase in intensity of a contact above the press-input intensity threshold, an increase in intensity of a contact from an intensity below the hysteresis intensity threshold to an intensity above the press-input intensity threshold, a decrease in intensity of the contact below the press-input intensity threshold, or a decrease in intensity of the contact below the hysteresis intensity threshold corresponding to the press-input intensity threshold. Additionally, in examples where an operation is described as being performed in response to detecting a decrease in intensity of a contact below the press-input intensity threshold, the operation is, optionally, performed in response to detecting a decrease in intensity of the contact below a hysteresis intensity threshold corresponding to, and lower than, the press-input intensity threshold. As described above, in some embodiments, the triggering of these responses also depends on time-based criteria being met (e.g., a delay time has elapsed between a first intensity threshold being met and a second intensity threshold being met).

User Interfaces and Associated Processes

[0372] Attention is now directed towards embodiments of user interfaces ("UI") and associated processes that may be implemented on an electronic device, such as portable multifunction device **100** or device **300**, with a display, a touch-sensitive surface, and (optionally) one or more sensors to detect intensities of contacts with the touch-sensitive surface.

[0373] These user interfaces and associated processes provide new, improved ways to:

[0374] acknowledge messages;

[0375] edit previously sent messages;

[0376] display an edit history for a previously sent message;

[0377] apply impact effect options to a message (e.g., to express what a user is trying to communicate);

[0378] display private messages using "invisible ink";

[0379] display enhanced message interface content (e.g., "full screen moments");

[0380] display content (e.g., "magic moments") that corresponds to particular combinations of content in two separate messages;

[0381] build message bubbles;

[0382] suggest emojis

[0383] synchronize viewing of content between users;

[0384] incorporate handwritten inputs;

[0385] selectively scrunch content in a message transcript;

[0386] integrate a camera;

[0387] integrate search and sharing;

[0388] integrate interactive applications;

[0389] integrate stickers;

[0390] make payments;

[0391] interact with avatars; and

[0392] make suggestions.

[0393] FIGS. **5A-5K** illustrate exemplary user interfaces for displaying message transcripts and message acknowledgments in accordance with some embodiments. In particular, FIG. **5A** illustrates a messaging user interface **5002** of a messaging application, displayed on the display of an electronic device, sometimes called the first electronic device to help distinguish it from other electronic devices in communication with the first electronic device. The first electronic device also includes a touch-sensitive surface and one or more sensors, such as in a touch-screen display or trackpad, configured to detect intensities of contacts on the touch-sensitive surface.

[0394] The messaging user interface **5002**, as shown in FIG. **5A**, includes an exemplary conversation transcript **5004** (also referred to as "conversation transcript **5004**") of a messaging session between a user (e.g., Genevive) of the electronic device and at least one other user (e.g., Isaac) of another electronic device). The conversation transcript **5004** in this example includes multiple messages, each in a respective message region **5008**. A first input with a first contact **5010** at the location on the touch-sensitive surface corresponding to a first message **5006**. In response to detecting the first input **5010**, the electronic device displays an acknowledgement selection affordance **5012**, FIG. **5B**, at a location in the messaging interface that corresponds to the first message region. In this example, the acknowledgement selection affordance displays a plurality of acknowledgement options: **5014-1** (heart), **5014-2** (thumbs up), **5014-3** (thumbs down), **5014-4** ("HA"), **5014-5** ("!!") and **5014-6** ("?"). Other embodiments may include fewer, additional or different acknowledgment options. The electronic device responds to receiving a second input **5106** by a second contact (e.g., a tap gesture, light press gesture, deep press gesture, or lift off) on a respective acknowledgment option (or a hit region corresponding to the respective acknowledgment option), such as option **5014-2** (thumbs up), to select respective acknowledgment option and apply it to the first message **5006** or first message region **5008-1**, as shown in FIG. **5C**. The selected acknowledgment option, in this example option **5014-2**, is displayed in a respective acknowledgement region **5018**. As shown in FIG. **5H**, the electronic device(s) of other user(s) (in this example, Isaac) participating in the messaging session (sometimes called a conversation) display the same selected acknowledgment option proximate for the first message region.

[0395] To edit the selected acknowledgement option, the user make a third input by a third contact **5022**, as shown in FIG. **5C**. Upon detecting the third input by the third contact, the electronic device displays an acknowledgement editing interface **5024**, as shown in FIG. **5D**. Optionally, the acknowledgement editing interface is displayed on top of and/or in place of the conversation transcript. Optionally the currently selected acknowledgment option, in this example option **5014-2**, is visually distinguished from the other available acknowledgement options in the acknowledgement editing interface **5024**, as shown in FIG. **5D**.

[0396] FIG. **5**E shows an input, contact **5026**, selecting a different, second acknowledgement option **5014-1**, and FIG. **5**F shows a message region in a conversation transcript with the edited acknowledgment (i.e., with second acknowledgement option **5014-1** displayed instead of first acknowledgement option **5014-2**).

[0397] In some embodiments, while the user of the first electronic device is using the acknowledgement editing interface **5024** to edit a previously selected acknowledgment option for the first message region, the electronic device of another user in the messaging session displays an acknowledgement-preparation indicator **5020**, as shown in FIG. **5**G, proximate (e.g., near, adjacent or partially overlapping) the first message region in the conversation transcript **5004** displayed by that electronic device.

[0398] Different users in the same messaging session may select different acknowledgment options for the same message or message region. In some embodiments, as shown in FIG. **5**I, the electronic device displays, in the conversation transcript, an indicia **5036**, that users in the messaging session have selected a plurality of acknowledgements options for the second message region. In the example shown in FIG. **5**I, indicia **5036** is a stack of overlapping acknowledgement option icons, but could alternatively be a plurality of individual acknowledgement option icons. As shown in FIG. **5**I, indicia **5036** is optionally adjacent to and/or partially overlapping the second message region **5008-02**.

[0399] FIG. **5**J shows an example of a user interface that includes a tally for each type of acknowledgement option selected by the users in the messaging session. For example, as shown in FIG. **5**J, the user interface includes tallies **5040-1**, **5040-2**, **5040-3** for three distinct acknowledgement options selected by users in the messaging session. In some embodiments, the user messaging interface shown in FIG. **5**J is displayed by the electronic device in response to detecting an input by a contact (e.g., contact **5034**, FIG. **5**I) at a location on the touch-sensitive surface that corresponds to a location of the message region having indicia **5036**, which indicates that multiple user in the messaging session have selected acknowledgement options for the same message (or corresponding message region).

[0400] By selecting one of the tallies **5040**, a user can see the users who selected any particular acknowledgement option. The electronic device, in response to an input by a contact (e.g., contact **5041**, as shown in FIG. **5**J) at a location on the touch-sensitive surface that corresponds to the tally **5040** for a particular acknowledgement option for a respective message region, displays icons **5042** (e.g., avatars) that represent users that selected the particular acknowledgement option for the respective message region, as shown in FIG. **5**K.

[0401] FIGS. **5**L-**5**T illustrate exemplary user interfaces for editing previously sent messages while displaying a message transcript. FIG. **5**L shows a messaging user interface **5002** of a messaging application on the display of an electronic device. The messaging user interface **5002** includes a conversation transcript **5004** of a messaging session between a user of the electronic device and at least one other user, and a first message region **5044** that includes a first message **5046-1** that was sent from the electronic device of the user to the at least one other user in the messaging session.

[0402] The first message **5046-1** can be edited, despite the fact that it has already been sent. To initiate the editing of the first message, the user selects the first message with a predefined touch input **5048** (e.g., a tap gesture, long press gesture, light press gesture, or deep press gesture) on the first message or the message region for the first message. In some embodiments, the electronic device, in response to detecting the input **5048**, displays a menu interface, such as the one shown in FIG. **5**M. Alternatively, the electronic device, in response to detecting the input **5048**, displays a message editing interface **5022**, as shown in FIG. **5**N. In some embodiments, a first input gesture (e.g., a tap gesture) on the first message is used to transition to the menu interface (e.g., as shown in FIG. **5**M), while a second input gesture (e.g., a deep press) is used to transition to the message editing interface **5052**, FIG. **5**N. From the menu interface, as shown in FIG. **5**M, a user can transition the messaging application to the message editing interface **5022**, shown in FIG. **5**N, by a touch input **5050** (FIG. **5**M) that selects an edit option in the menu interface.

[0403] The message editing interface **5052**, FIG. **5**N, for editing a respective message, such as first message **5046-1**, includes a keyboard **5054**, and an update affordance **5056**. While displaying the message editing interface **5052** for the respective message, the electronic device detects one or more inputs, such as input **5057** shown in FIG. **5**N, that revise the respective message, displays a revised version of the message, and detects an input that activates the update affordance (e.g., for sending the updated message to the one or more other electronic devices of the one or more other participants in the messaging session.

[0404] FIG. **5**O shows the conversation transcript **5004** after message **5046** has been updated. Because the conversation transcript **5004** includes an edited message, the edited message includes one or more indications **5058** that a particular message was revised after the original version of the message was sent to the other participant(s) in the messaging session. In FIG. **5**O, there are two such indications of revision: indication **5058-1** is a shadow region behind the message region; indication **5058-2** is text (e.g., "Edited") displayed below the message region that contains the revised version of the message.

[0405] An edited or revised message can be edited yet again. The electronic device, in response to an input (e.g., input **5060**, FIG. **5**O) that corresponds to a request to edit the revised version **5046-2**) of a message, displays a message editing interface for the revised version of the message, as shown in FIG. **5**R. The message editing interface, as shown in FIG. **5**R, includes the message **5046-2** to be edited, a keyboard, and an update affordance (which is optionally not shown until at least one revision has been made to the message).

[0406] A participant in the messaging session can request to see all version, or two or more versions, of an edited message. For example, in response to a predefined input **5060**, FIG. **5**O, on an edited message, the electronic device displays the user interface shown in FIG. **5**P, in which display of the conversation transcript is suppressed except for the revised version of the first message **5046-2**, and a menu **5062** or list of editing options. In this example, the displayed menu **5062** includes a copy affordance **5064** (for copying the message selected by input **5060**), a show edits affordance **5066** (for showing edits to the message selected by input **5060**), a delete affordance **5068** (for deleting the

message selected by input **5060**, or alternatively for undoing all edits made to the message selected by input **5060**), and a display more options affordance **5070**. In the example shown in FIG. **5**P, input **5072** (e.g., a tap gesture) is detected at the location on the touch-sensitive surface that corresponds to the location of the "show edits" affordance **5066**, which when activated, displays a user interface **5074** (FIG. **5**Q) that includes current version **5046-1** of the first message as well as a prior version **5046-2**, as shown in FIG. **5**Q. A further input, **5076** or **5078**, in the user interface of FIG. **5**Q, selects a version of the message to edit. For example, the selected version is highlighted, and then a touch input on Edit (**5080**) would initiate editing of the selected version of the message. Alternatively, a touch input on Done (**5082**) terminates the editing of the selected version of the message.

[0407] An alternative to the edit menu interface shown in FIG. **5**P is the edit menu interface shown in FIG. **5**S, which includes the selected message (selected in response to input **5060**, FIG. **5**O), and a menu that includes an affordance (e.g., a "show edits" option, **5086**), which when activated results in display of the user interface shown in FIG. **5**T, which includes the current version **5046-2** of the selected message and one or more prior versions of the selected message (e.g., version **5046-1**).

[0408] FIGS. **5**U-**5**BF illustrate exemplary user interfaces for applying an impact effect option to a message input or message region. FIG. **5**U illustrates a messaging user interface **5002** having a conversation transcript **5004** of a messaging session between a user (Wendy, in this example) of the electronic device and at least one other user (e.g., Max, in this example, a user of another electronic device), and a message-input area **5100** that includes first message input **5102** (e.g., text, stickers, images, and/or other graphics entered by a user of the electronic device in the message-input area, but not yet sent to the at least one other user in the messaging session). In FIG. **5**U, first message input **5102** has not yet been sent.

[0409] In some embodiments, to trigger the activation of an impact selection interface **5110**, FIG. **5**AA, first input **5102**, by a first contact at a location on the touch-sensitive surface that corresponds to a location in the message-input area **5100**, includes a particular gesture (e.g., a swipe gesture) received at the message-input area **5100**. In this example, the message-input area includes an impact selection affordance **5104** and the location of the contact **5106** of the first input corresponds to the impact selection affordance. In some embodiments, impact selection affordance **5104** is a multipurpose affordance, and a second gesture (e.g., a tap) on the same affordance **5104** is used to send the message **5102** in message input area **5100**. The electronic device, upon detecting an input that includes the second gesture on affordance **5104**, sends message **5102** and transitions to the user interface shown in FIG. **5**V. Similarly, after message **5102** is sent, the electronic device of the other user receives that message and shows the user interface shown in FIG. **5**W.

[0410] In some alternative embodiments, illustrated in FIGS. **5**X, **5**Y and **5**Z, a deep press input **5108-1**, **5108-2**, **5108-3**, as shown in FIGS. **5**X, **5**Y and **5**Z, when detected by the electronic device, causes the messaging application to display an impact selection interface **5110**, FIG. **5**AA, that includes a plurality of impact effect options (e.g., impact effect options **5112-1** through **5112-4**. The increasing intensity of the deep press input is represented by the intensity diagrams in FIGS. **5**X, **5**Y and **5**Z. Further, the deep press input **5108-1**, **5108-2**, **5108-3**, on impact selection affordance **5104**, as shown in FIGS. **5**X, **5**Y and **5**Z, followed by a drag to the first impact effect option (e.g., input **5108-4** on impact effect option **5112-1**, FIG. **5**AA) and then pausing while over the affordance for a respective impact effect option **5112**, selects that impact effect option.

[0411] The impact selection interface **5110**, FIG. **5**AA, includes a "bubble" affordance **5114** for displaying a selecting message region impact effect options, and a "screen" affordance **5116** for selecting full screen impact effect options.

[0412] In some embodiments, the impact selection interface **5110**, shows an animated preview of the currently selected impact effect option. For example, the sequence of FIGS. **5**AB-**5**AD show an animated preview of the "loud" impact effect option, which is a message region impact effect option, being applied to first message input ("Congratulations!") in response to an input **5108-5** at a location on the touch-sensitive surface that corresponds to a location of the "loud" impact effect option. In this example, the preview of the "loud" impact effect option shows the font size of the message and the size of a message region at first increasing and then decreasing.

[0413] In another example, the, sequence of FIGS. **5**AE-**5**AG show an animated preview of the "slam" impact effect option, which is a message region impact effect option, being applied to first message input ("Congratulations!") in response to a second input **5108-6** at a location on the touch-sensitive surface that corresponds to a location of the "slam" impact effect option. In this example, the preview of the "slam" impact effect option shows the font size of the message and the size of a message region at first increasing and then decreasing, and at the same time changing the tilt or rotation state of the message region, and optionally changing the shade or color of a background region surrounding the message region. Optionally, the application of a respective impact effect option may change additional characteristics of the message region to which the impact effect option is applied, such as font color, background shade or color within the message region, etc.

[0414] FIG. **5**AG also shows a third input **5108-7** on a send affordance, at a location corresponding to a user-selected impact effect option, in this case the "slam" option. In response, the electronic device of the user composing the message ceases to display the impact selection interface and displays a message region that contains the first message input in the conversation transcript, and in some embodiments, applies the selected impact effect option to the message region, as shown in FIG. **5**AH, or to the entire conversation transcript, as shown in the FIG. **5**AI (enlarging the message region to which the impact effect option was applied and decreasing the size of one or more other message regions in the conversation transcript), and then transitioning to a final or static display of the conversation transcript that includes the sent message, as shown in FIG. **5**AJ. Similarly, the sent message is displayed at the electronic device of one or more other users in the messaging session, such as Wendy, with the selected impact effect option applied to the either message region of the sent message or the entire conversation transcript, depending on which impact effect option was selected by the sending user, one example of which is shown in the sequence of FIGS. **5**AK, **5**AL, **5**AM.

[0415] The sequence of FIGS. **5**AN-**5**AS show an example of the "loud" impact effect option applied to a respective sent message ("congrats"). The sequence of FIGS. **5**AT-**5**AW show an example of the "gentle" impact effect option applied to a respective sent message ("I'm sorry.").

[0416] In some embodiments, the selected impact effect option is applied to all (or substantially all) of the display screen of an electronic device that sends or receives the message, which includes the message region with the sent message, for a full-screen effect, an example of which is shown by the sequence of user interface images in FIGS. **5**AX through **5**BF. FIGS. **5**AX through **5**BF show the progression of the "slam" effect of a first message input ("Hell No!!"), starting with the first message input displayed shown enlarged, rotated and with a dark background (FIG. **5**AX), then displayed even larger and with a somewhat lighter background (FIG. **5**AY), then less enlarged and rotated at a different angle than before (FIG. **5**AZ), then shown with further reduced enlargement and with blurry borders (FIG. **5**BA), then shown with reduced size a different background and a different rotation (FIG. **5**BB) and then with a sequence of different shadows around the message region (FIGS. **5**BC, **5**BD, **5**BE) until the first message input is shown at normal (default) size, not rotated, and with a normal (default) background (FIG. **5**BF).

[0417] FIGS. **5**BG-**5**CA illustrate exemplary user interfaces for interacting with concealed messages. An impact selection interface **5110**, shown in FIG. **5**BG, includes a plurality of impact effect options (e.g., impact effect options **5112-1** through **5112-4**, described elsewhere in this document with respect to FIG. **5**AA). In this example, the impact selection interface **5110** also includes a "bubble" affordance **5114** for displaying a selecting message region impact effect options, and a "screen" affordance **5116** for selecting full screen impact effect options.

[0418] In some embodiments, the displayed impact effect options include an option that conceals the content of a message in the conversation transcript ("invisible ink" option **5112-1**, FIG. **5**AA, indicated in FIG. **5**BG by an empty message region). In the example shown in FIG. **5**BG, the invisible ink option includes a send affordance **5118** for sending a message (with user-specified message input) with the respective impact effect option. In the example shown in FIG. **5**BG, impact selection interface **5110** includes a cancel affordance **5120** for canceling the selection of any impact effect options and returning the messaging application to either a prior user interface of the messaging application or a predefined user interface of the messaging application.

[0419] Once a message (hereinafter called the "concealed message" for ease of reference) has been sent with the invisible ink option, the concealed message is not displayed or is obscured, for example by screen elements **5124** that conceal the message, as shown in FIG. **5**BH, until the user of the electronic device displaying a conversation transcript that includes the concealed message performs a respective gesture, such as sliding a touch input **5128**-*a,* **5128**-*b,* **5128**-*c* over the message region containing the concealed message, as shown in the sequence of FIGS. **5**BH through **5**BL, which temporarily reveals a portion of the message corresponding to the position of the touch input **5128-1**, **5128**-*b,* **5128**-*c*; or performing a deep press gesture on the message region containing the concealed message, as shown in the sequence of FIGS. **5**BM-**5**BP, in which the portion of the concealed message that is revealed corresponding to the intensity of the deep press input **5130**-*a,* **5130**-*b,* **5130**-*c,* and optionally also corresponding to the position of the deep press input **5130**-*a,* **5130**-*b,* **5130**-*c.* In these examples, the concealed message is concealed again in response to detecting termination of the input by the contact that caused the concealed message, or portions thereof, to be temporarily revealed.

[0420] In another example, the sequence of FIGS. **5**BQ-**5**BV, show a concealed message being gradually revealed, as shown in FIGS. **5**BQ to **5**BT, and then gradually concealed, as shown in FIGS. **5**BT to **5**BV. In yet another example, the sequence of FIGS. **5**BW-**5**CA, show a concealed message that contains a picture of photograph being gradually revealed.

[0421] FIGS. **5**CB-**5**CW illustrate exemplary user interfaces for triggering enhanced message content and applying an effect to a messaging user interface when a message includes an enhanced message content trigger. More particularly, a respective message in a messaging session can be sent with an enhanced message content trigger, and when an electronic device with a compatible messaging application receives that message with the enhanced message content trigger, the electronic device displays a conversation transcript with the received message and with enhanced message content. In some embodiments, the particular enhanced message content to be displayed is indicated by one or more parameters in the enhanced message content trigger.

[0422] FIGS. **5**CB and **5**CC show an example of a user interface displaying a preview of a full screen impact effect, in this case a full screen impact effect that includes moving or animated balloons **5152-1**. As shown in FIG. **5**CB, the user of the electronic device composing the message "Congratulations!" has selected the "screen" affordance **5116**, for selecting full screen impact effect options. Similarly, the sequence of FIGS. **5**CD-**5**CF show an example of a user interface displaying a preview of a full screen impact effect, in this case a full screen impact effect that includes moving or animated confetti **5152-2**. In the example shown here, the user navigates through the available full screen impact effects using swipe gestures, such as swipe gesture **5156** shown in FIG. **5**CC, which cause the electronic device to moves from a preview of the balloon full screen impact effect shown in FIG. **5**CC to the confetti full screen impact effect shown in FIG. **5**CD. As shown in FIGS. **5**CB and **5**CC, the user interface may include an effect option indicator **5154** (sometimes called page dots) to indicate which full screen effect option is currently selected or is currently being previewed, and also to indicate how many full screen effect options are available and which one of those options in a sequence of the full screen effect options is currently being viewed.

[0423] FIG. **5**CG is an example of a user interface having a conversation transcript in which none of the messages include an enhanced message content trigger, and thus the messages in the transcript are displayed without displaying enhanced message content corresponding to a trigger.

[0424] The sequence of FIGS. **5**CH-**5**CO shows an example of a balloons full screen effect being displayed when a message ("Happy Birthday!!!!!") containing a corresponding enhanced message content trigger is received. Similarly, the sequence of FIGS. **5**CP-**5**CW shows an example of a fireworks full screen effect being displayed when a message ("Happy New Year!!!") containing a corresponding enhanced message content trigger is received.

[0425] FIGS. **5**CX-**5**DC illustrate exemplary user interfaces for detecting and responding to combinable content in separate messages. In FIG. **5**CX, a messaging user interface **5002** includes a conversation transcript **5004** a messaging session between a user of the electronic device and at least one other user (e.g., a user of another electronic device) including a first other user, and a message input area **5100**. A received first message **5170** in a first message region **5008** is shown in the conversation transcript **5004**. The first message **5170**, for example a beer glass, has first combinable content (e.g., an emoticon or an image such as an emoji or a sticker). In FIG. **5**CY, the user of the electronic device inputs a second message **5172** in message input area **5100** of the messaging user interface **5002**, and sends the second message **5172** by an input **5174** that selects a send affordance **5118**. This results in the display of the messaging user interface shown in FIG. **5**CZ.

[0426] If the second message **5172** contains second combinable content that forms a predefined combination with the first combinable content in the first message **5170**, content **5176**, the electronic device displays content that corresponds to the predefined combination, such as an animation of two beer glasses being clicked together (as shown in FIG. **5**DA) and/or display of the word "Cheers!" (as shown in FIG. **5**DA). Similarly, the electronic devices of the one or more other users in the messaging session would display the first message, the second message, and the content that corresponds to the predefined combination. It is noted that the content **5176** that corresponds to the predefined combination may be an animation that is briefly displayed after the second message is sent. Optionally, display of the content that corresponds to the predefined combination is repeated periodically while both the first and second messages with the combinable content are displayed in the conversation transcript **5004**, or when other predefined criteria are satisfied (e.g., both the first and second messages with the combinable content are displayed in the conversation transcript **5004** and there has been no new activity in the messaging session for at least N seconds, when N is a predefined value between 1 and 60 seconds).

[0427] The sequence of FIGS. **5**DB and **5**DC show another example of combinable content, in which a first user has sent a first message **5178**, "Happy," and the second user inputs a second message **5180**, "Birthday!" If the first message and second message both include combinable content corresponding to a predefined combination, then content corresponding to the predefined combination would be displayed in the message transcript of the messaging user interface displayed by either the sender's electronic device, or a recipient's electronic device, or (typically) both. For example, the content that corresponds to the predefined combination in this example might be balloons, similar to those shown in FIGS. **5**CH-**5**CO.

[0428] FIGS. **5**DD-**5**DI illustrate exemplary user interfaces for selecting a message region type or shape, in accordance with some embodiments. FIG. **5**DD shows a messaging user interface **5002** with a message input region **5100** having a first message input **5102** ("Yes!") already entered in the message input region. Messaging user interface **5002** includes a send affordance **5200** in or near message input region **5100**, for sending the message that has been input in that region. In addition, FIG. **5**DD shows a input with a contact **5202** on an options affordance **5204**.

[0429] The messaging user interface shown in FIG. **5**DE is displayed in response to input with contact **5202** on options affordance **5204**, which includes affordances for a number of message processing options, including a message region type/shape selection affordance **5208**, labeled the "bubbles" affordance in FIG. **5**DE. While displaying this messaging user interface, the electronic device receives an input with contact **5206** on the "bubbles" option affordance **5208**.

[0430] The messaging user interface shown in FIG. **5**DF is displayed in response to input with contact **5206** on "bubbles" affordance **5208**. FIG. **5**DF also shows a preview message region **5210-1** that includes the first message input **5102**, and that has a default, or previously selected, message region type. In these embodiments, the messaging application has a plurality of message region types or options, each having a corresponding shape, and typically having a corresponding font size, and optionally having one or more of: a font color, border color, and/or background color. In the example shown in FIG. **5**DF, the send affordance **5200** is displayed near the preview message region **5210-1** instead of in message input region **5100**. To select a different message region type for the first message **5172**, or to view other available message region types, the user inputs a swipe gesture **5212**. In response to swipe gesture **5212**, a scrolling set of message region type icons is scrolled, as shown in the progression from FIG. **5**DF to FIG. **5**DG.

[0431] In the example of the messaging user interface shown in FIG. **5**DG, an input with contact **5214** is received, which causes the electronic device to change the message region type for the message region to be used with message input **5102**, as shown in FIG. **5**DH. In FIG. **5**DH, message input **5102** is now shown in a message region **5210-2** having a message region type corresponding to the message region type selected by input with contact **5214** (shown in FIG. **5**DG). The user can continue to select different message region types. For example, in FIG. **5**DI, message input **5102** is now shown in a message region **5210-3** having a message region type corresponding to the message region type selected by input with contact **5216**.

[0432] FIGS. **5**DJ-**5**DQ illustrate exemplary user interfaces for displaying and selecting automatically suggested emoji while composing a message. In FIG. **5**DJ, a messaging user interface **5002** having a conversation transcript **5004** with an input, but not yet sent, message **5220** in message input region **5100** is shown. In this example, the messaging using interface **5002** includes a send affordance **5200** in or near message input region **5100** for sending the input message.

[0433] As shown in FIGS. **5**DK-**5**DN, the electronic device begins to automatically make suggestions of emoji to replace one or more words or terms in the message input region **5100**. In the example shown, the electronic device highlights word or terms, in sequence in the message, that are candidates for being replaced by emoji, first highlighting the term "sushi" **5222** in the input message **5220**, as shown in FIGS. **5**DK and **5**DL, then highlighting the term "wine" **5224** in the input message **5220**, as shown in FIG. **5**DM, and then highlighting the term "bowling" **5226** in the input message **5220**, as shown in FIG. **5**DN. In response to the user of the electronic device selecting one of the highlight terms (e.g., by an input with a contact on a highlighted term), such as "sushi" **5222** in the input message **5220**, that term is replaced by a corresponding emoji **5232** corresponding to

that term, as shown in FIG. **5**DO. Similarly, in FIG. **5**DP, the term "wine" in the input message **5220** has been replaced by an emoji **5234** (e.g., a wine glass emoji) corresponding to that term in response to a user selection of the highlighted term "wine" in the input message **5220**. In a third example, the term "bowling" in the input message **5220** has been replaced by an emoji **5236** (e.g., a bowling emoji) corresponding to that term in response to a user selection of the highlighted term "bowling" in the input message **5220**.

Message Acknowledgements

[0434] FIGS. **6**A-**6**E are flow diagrams of a process for applying an acknowledgement to a message region in a conversation transcript, in accordance with some embodiments. More specifically, these methods relate to displaying an acknowledgement selection affordance that includes a plurality of acknowledgement options and applying a selected acknowledgement option to a received message. In some embodiments, an indication of the applied acknowledgement option is transmitted to a remote device (e.g., for display within a conversation transcript of the remote device). The acknowledgement allows a user to quickly communicate a sentiment without having to type multiple words. It saves user time by saving keystrokes and, therefore, creates a more efficient man-machine interaction.

[0435] One or more examples of an electronic device (e.g., portable multifunction device **100** or device **300**) implementing these methods are shown in FIGS. **5**A-**5**K.

[0436] FIGS. **6**A-**6**E are flow diagrams illustrating a method **600**, performed by an electronic device, sometimes herein called a first electronic device, having one or more processors, memory, a touch-sensitive surface, and a display. In some embodiments, the electronic device includes one or more sensors (e.g., sensors in a touch-screen display or trackpad) configured to detect intensities of contacts on the touch-sensitive surface.

[0437] While performing method **600**, the electronic device displays (**602**) a messaging user interface (e.g., of a messaging application) on the display. The messaging user interface includes a conversation transcript of a messaging session between a user of the electronic device and at least one other user (e.g., of another electronic device). See for example, FIG. **5**A, conversation transcript **5004** in messaging user interface **5002**. The electronic device receives (**604**) a first message within the messaging session from an electronic device (e.g., a second electronic device) that corresponds to another user included in the messaging session. For example, in FIG. **5**A, message **5006** is a first message.

[0438] In response to receiving the first message, the electronic device displays (**606**) the first message (e.g., message **5006**, FIG. **5**A) in a first message region (e.g., message region **5008-1**, FIG. **5**A) in the conversation transcript (e.g., conversation transcript **5004**, FIG. **5**A) on the display. As used herein, a message region is a message region, bubble, platter, or other container for a message in a conversation transcript of a messaging session. The electronic device furthermore detects (**608**) a first input by a first contact (e.g., contact **5010**, FIG. **5**A) at a location on the touch-sensitive surface that corresponds to a location of the first message region in the conversation transcript. For example, the first contact may be a tap gesture, long press gesture, light press gesture, or deep press gesture on the first message region or on a hidden hit region for the first message region.

[0439] Next, in response to detecting the first input, the electronic device displays (**610**) displaying an acknowledgement selection affordance (e.g., acknowledgement selection affordance **5012**, FIG. **5**B) at a location in the messaging interface that corresponds to the first message region. The acknowledgement selection affordance displays a plurality of acknowledgement options. For example, see acknowledgement options **5014-1** to **5014-6** in FIG. **5**B. In some embodiments, the acknowledgement selection affordance is an acknowledgement selection platter displayed proximate to and/or overlapping the first message region. In some embodiments, in accordance with a determination that a characteristic intensity of the contact is above a first intensity threshold, the acknowledgement selection affordance is displayed. In some embodiments, a user can reveal additional acknowledgement options, in addition to an initially displayed set of acknowledgement options **5014**, by performing a predefined input gesture, such as a gesture that includes repeated deep presses, a drag gesture, etc.

[0440] In some embodiments, the plurality of acknowledgement options include (**612**) graphical icons that display at least one of a heart, a thumbs up, a thumbs down, a "HA!", a "!!", and/or a question mark. (See, for example, acknowledgement options **5014-1** to **5014-6** shown in FIG. **5**B).

[0441] In some embodiments, method **600** includes, in response to detecting the first input, transmitting (**614**) information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to display an acknowledgement-preparation indicator for a corresponding first message region in a conversation transcript that corresponds to the messaging session (e.g., causing the other devices in the messaging session to display an acknowledgement region with animated ellipses marks adjacent to and/or partially overlapping the corresponding first message region in the conversation transcript of the at least one other user's device, analogous to what is shown in FIG. **5**G).

[0442] After detecting and responding to the first input, the electronic device detects (**616**) a second input by a second contact (e.g., contact **5016**, FIG. **5**B) at a location on the touch-sensitive surface that corresponds to a location of a first acknowledgement option (e.g., acknowledgement option **5014-2**, FIG. **5**B) in the acknowledgement selection affordance (e.g., acknowledgement selection affordance **5012**, FIG. **5**B). Optionally, detecting the second contact is accomplished by, for example, detecting a tap gesture, light press gesture, deep press gesture, or lift off on the first acknowledgement option or on a hidden hit region for the first acknowledgement option. In some embodiments, the first contact and the second contact are distinct contacts, such as contacts in two different tap gestures made by the same finger. In some embodiments, the first contact and the second contact are different parts of the same continuous contact with the touch-sensitive surface, such as a long press, light press, or deep press on the first message region followed by a drag to the first acknowledgement option and lift off at the first acknowledgement option.

[0443] In response to detecting the second input, the electronic device applies (**618**) the first acknowledgement option to the first message region. For example, FIG. **5**C shows a first acknowledgment option **5014-2** applied to a first message region. In some embodiments, the electronic device also ceases to display the acknowledgement selection affordance in response to detecting the second input.

[0444] In some embodiments, applying (**618**) the first acknowledgement option to the first message region includes displaying (**620**) the first acknowledgement option at a location adjacent to and/or partially overlapping the first message region. See, for example, FIG. **5**C, which shows first acknowledgement option **5014-2** applied to, and in this case, partially overlapping, a corresponding first message region.

[0445] Optionally, in some embodiments, in response to detecting the second input, the electronic device transmits (**622**) information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to apply the first acknowledgement option to a corresponding first message region in a conversation transcript that corresponds to the messaging session. In some embodiments, this is accomplished by transmitting information that causes the other devices in the messaging session to display the first acknowledgement option adjacent to and/or partially overlapping the corresponding first message region in the conversation transcript of the at least one other user's device. See, for example, FIG. **5**H, which shows the conversation transcript as displayed on one of the other devices in the messaging session, including first acknowledgement option **5014-2** applied to (and in this case, partially overlapping) a corresponding first message region. In some embodiments, the first acknowledgement option (e.g., first acknowledgement option **5014-2**) replaces an acknowledgement-preparation indicator (e.g., acknowledgement-preparation indicator **5020**, FIG. **5**G) for a corresponding first message region (e.g., via an animated transition).

[0446] In some embodiments, the first acknowledgement option is displayed in an acknowledgement region that has a different shape from the first message region (e.g., as shown in FIG. **5**C, a respective message region **5008-1** for a message from another user is rectangular and/or includes a first indicator that the first message is from the other user (e.g., a tail section "<" pointing towards a first side of the display), whereas a respective acknowledgement region **5018** is circular and/or includes a second indicator that the acknowledgement is from the user (e.g., a tail section "Oo" pointing towards a second side of the display, opposite the first side)).

[0447] In some embodiments, method **600** includes, after applying the first acknowledgement option to the first message region (and, in some embodiments, ceasing to display the acknowledgement selection affordance), performing a sequence of operations (**632-658**) that includes detecting (**632**) a third input by a third contact (e.g., contact **5022**, FIG. **5**C) at a location on the touch-sensitive surface that corresponds to a location of the first message region (or, in some embodiments, the first acknowledgement option). In some embodiments, detecting (**632**) the third input includes detecting a tap gesture, long press gesture, light press gesture, or deep press gesture on the first message region (or the first acknowledgement option) or on a hidden hit region for the first message region (or the first acknowledgement option).

[0448] In such embodiments, method **600** further includes, in response to detecting (**632**) the third input by the third contact at the location on the touch-sensitive surface that corresponds to the location of the first message region (or, in some embodiments, the first acknowledgement option), displaying (**634**) an acknowledgement editing interface (e.g., acknowledgement editing interface **5024**, FIG. **5**D). Optionally, the acknowledgement editing interface is displayed on top of and/or in place of the conversation transcript.

[0449] In such embodiments, method **600** further includes detecting (**650**) one or more inputs to the acknowledgement editing interface (e.g., detecting contact **5026**, FIG. **5**E), editing (**652**) (e.g., changing or deleting) an acknowledgement option for the first message region in accordance with the detected one or more inputs; ceasing (**654**) to display the acknowledgement editing interface; displaying (**656**) the first message region in the conversation transcript with an edited acknowledgement; and transmitting (**658**) information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to display a corresponding first message region with the edited acknowledgement in a conversation transcript that corresponds to the messaging session. For example, FIG. **5**D shows an acknowledgement editing interface **5024**, with an indication (e.g., highlighting or greying out) that acknowledgement option **5014-2** was previously selected. FIG. **5**E shows an input, contact **5026**, selecting a different, second acknowledgement option **5014-1**, and FIG. **5**F shows a message region in a conversation transcript with the edited acknowledgment (i.e., with second acknowledgement option **5014-1** displayed instead of first acknowledgement option **5014-2**).

[0450] In some embodiments, in addition to displaying (**634**) the acknowledgement editing interface in response to detecting (**632**) the third input by the third contact, method **600** includes, in response to detecting the third input by the third contact, ceasing (**636**) to display (or dimming) the conversation transcript, an example of which is shown in FIG. **5**E.

[0451] Furthermore, in some embodiments, in response to detecting the third input by the third contact, method **600** includes displaying (**638**) the first message region in the acknowledgement editing interface. For example, FIG. **5**E shows an example in which the first message region is displayed in the acknowledgement editing interface, without displaying any other message regions in the conversation transcript in the acknowledgement editing interface. In some embodiments, the first message region is initially displayed in the acknowledgement editing interface at a same location as the first message region was displayed in the conversation transcript immediately prior to detecting the third input.

[0452] In some embodiments, in addition to displaying (**634**) the acknowledgement editing interface in response to detecting (**632**) the third input by the third contact, method **600** includes, in response to detecting the third input by the third contact, displaying the acknowledgement selection affordance that includes the plurality of acknowledgement options in the acknowledgement editing interface, wherein the first acknowledgement option is visually distinguished (e.g., highlighted) from the other acknowledgement options in the plurality of acknowledgement options to indicate that the first acknowledgement option is currently selected. For example, FIG. **5**D shows that acknowledgement editing interface **5024** includes the acknowledgement selection affordance (similar to affordance **5012**, FIG. **5**B), which includes a plurality of acknowledgement options **5014**).

[0453] In some embodiments in addition to displaying (**634**) the acknowledgement editing interface in response to detecting (**632**) the third input by the third contact, method **600** includes, in response to detecting the third input by the third contact, displaying (**642**) a menu in the acknowledge-

ment editing interface that includes activatable editing options for the first message region. For example, FIG. **5**D shows an edit menu **5028** which includes a "Copy" icon **530** to copy content of the first message region. While not shown in FIG. **5**D, edit menu **5028** optionally include additional activatable editing options, such as a "Delete" icon to delete the currently applied acknowledgement option.

[0454] In some embodiments, method **600** includes, while displaying the messaging user interface as described above, concurrently displaying (**660**) on the display (A) a second message region (e.g., message region **5008-2**, FIG. **5**I) in the conversation transcript, wherein (1) at least some of the users in the messaging session have selected the first acknowledgement option for the second message region, and (2) at least some of the users in the messaging session have selected a second acknowledgement option for the second message region, distinct from the first acknowledgement option; and (B) one or more indicia (e.g., indicia **5036**) that users in the messaging session have selected a plurality of acknowledgements options for the second message region. In the example shown in FIG. **5**I, indicia **5036** is a stack of overlapping acknowledgement option icons, but could alternatively be a plurality of individual acknowledgement option icons. As shown in FIG. **5**I, indicia **5036** is optionally adjacent to and/or partially overlapping the second message region **5008-02**. In some embodiments, for a given acknowledgement option that was selected, the selections are stacked if the acknowledgement option was selected by more than a threshold number of user users in the messaging session (e.g., by more than 2, 3, or 4 users).

[0455] In such embodiments (i.e., showing a second message region and the indicia that users in the messaging session have selected a plurality of acknowledgements options for the second message region), method **600** includes detecting (**662**) an input by a contact at a location on the touch-sensitive surface that corresponds to a location of the second message region (e.g., contact **5034** on second message region **5008-2**, FIG. **5**I). Alternatively, the detected input corresponds to a location of the one or more indicia that users in the messaging session have selected a plurality of acknowledgements options for the second message region. In some embodiments, detecting (**662**) the input includes detecting a tap gesture, long press gesture, light press gesture, or deep press gesture on the second message region or on a hidden hit region for the second message region.

[0456] In response to detecting the input by the contact at the location on the touch-sensitive surface that corresponds to the location of the second message region, method **600** includes displaying (**664**) a user interface that includes a tally for each type of acknowledgement option selected by users in the messaging session. For example, as shown in FIG. **5***j*, the user interface includes tallies **5040-1**, **5040-2**, **5040-3** for three distinct acknowledgement options selected by users in the messaging session. Alternatively, in some embodiments, in response to detecting the input by the contact at the location on the touch-sensitive surface that corresponds to the location of the second message region, the device displays a user interface that includes a tally affordance (e.g., as a menu option), which when activated, displays the tally for each type of acknowledgement option selected by users in the messaging session.

[0457] In some embodiments, method **600** includes, while displaying the tally for each type of acknowledgement option selected by users in the messaging session, detecting (**666**) an input by a contact at a location on the touch-sensitive surface that corresponds to a tally for the first acknowledgement option for the second message region. For example, referring to FIG. **5**J, the input may select tally **5040-1**. In some embodiments, detecting (**666**) the input at a location on the touch-sensitive surface that corresponds to a tally includes detecting a tap gesture, long press gesture, light press gesture, or deep press gesture on the tally for the first acknowledgement option, or on a stack of icons (e.g., avatars) that correspond to users in the messaging session that selected the first acknowledgement option, or on a hidden hit region for this tally or this stack of icons.

[0458] In such embodiments, method **600** further includes, in response to detecting (**666**) the input by the contact at a location on the touch-sensitive surface that corresponds to the tally for the first acknowledgement option for the second message region, displaying (**668**) icons (e.g., avatars) that represent users that selected the first acknowledgement option for the second message region. For example, as shown in FIG. **5**K, the user interface displayed by the device in response to an input selecting tally **5040-1** (FIG. **5**J), includes a display of the icons (e.g., avatars) that represent users that selected the first acknowledgement option for the second message region, which replaces display of the tally for each type of acknowledgement option selected by users in the messaging session (shown in FIG. **5**J).

[0459] It should be understood that the particular order in which the operations in FIGS. **6**A-**6**E have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **800**, **1000**, **1200**, **1400**, **1600**, **1800**) are also applicable in an analogous manner to method **600** described above with respect to FIGS. **6**A-**6**E. For example, the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described above with reference to method **600** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein. For brevity, these details are not repeated here.

[0460] In accordance with some embodiments, FIG. **7** shows a functional block diagram of an electronic device **700** configured in accordance with the principles of the invention as described above. The functional blocks of the device may be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the invention. It is understood by persons of skill in the art that the functional blocks described in FIG. **7** may be combined or separated into sub-blocks to implement the principles of the invention as described above. Therefore, the description herein may support any possible combination or separation or further definition of the functional blocks described herein.

[0461] As shown in FIG. **7**, an electronic device **700** includes a display unit **702** configured to display a messaging user interface on the display unit, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least

one other user; a touch-sensitive surface unit **704** configured to detect contacts; and a processing unit **706** coupled with the display unit **702** and the touch-sensitive surface unit **704**. In some embodiments, the processing unit **706** includes a detecting unit **708**, a display enabling unit **710**, a ceasing unit **712**, a transmitting unit **714**, a receiving unit **716**, an applying unit **718**, and an editing unit **720**.

[0462] The processing unit **706** is configured to: receive a first message within the messaging session from an electronic device that corresponds to another user included in the messaging session (e.g., with the receiving unit **716**); in response to receiving the first message, enable display of the first message in a first message region in the conversation transcript on the display unit **702** (e.g., with the display enabling unit **710**); detect a first input by a first contact at a location on the touch-sensitive surface unit **704** that corresponds to a location of the first message region in the conversation transcript (e.g., with the detecting unit **708**); in response to detecting the first input, enable display of an acknowledgement selection affordance at a location in the messaging interface that corresponds to the first message region (e.g., with the display enabling unit **710**), wherein the acknowledgement selection affordance displays a plurality of acknowledgement options; detect a second input by a second contact at a location on the touch-sensitive surface unit **704** that corresponds to a location of a first acknowledgement option in the acknowledgement selection affordance (e.g., with the detecting unit **708**); and, in response to detecting the second input, apply the first acknowledgement option to the first message region (e.g., with the applying unit **718**).

[0463] In some embodiments, applying the first acknowledgement option to the first message region includes displaying the first acknowledgement option at a location adjacent to and/or partially overlapping the first message region.

[0464] In some embodiments, the first acknowledgement option is displayed in an acknowledgement region that has a different shape from the first message region.

[0465] In some embodiments, the processing unit **706** is further configured to: in response to detecting the first input, transmit information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to display an acknowledgement-preparation indicator for a corresponding first message region in a conversation transcript that corresponds to the messaging session (e.g., with the transmitting unit **714**).

[0466] In some embodiments, the processing unit **706** is further configured to: in response to detecting the second input, transmit information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to apply the first acknowledgement option to a corresponding first message region in a conversation transcript that corresponds to the messaging session (e.g., with the transmitting unit **714**).

[0467] In some embodiments, the processing unit **706** is further configured to: after applying the first acknowledgement option to the first message region: detect a third input by a third contact at a location on the touch-sensitive surface unit **704** that corresponds to a location of the first message region (e.g., with the detecting unit **708**); in response to detecting the third input by the third contact at the location on the touch-sensitive surface unit **704** that corresponds to the location of the first message region, enable display of an acknowledgement edit interface (e.g., with the display enabling unit **710**); detect one or more inputs to the acknowledgement editing interface (e.g., with the detecting unit **708**); edit an acknowledgement option for the first message region in accordance with the detected one or more inputs (e.g., with the editing unit **720**); cease to display the acknowledgement editing interface (e.g., with the ceasing unit **712**); enable display of the first message region in the conversation transcript with an edited acknowledgement (e.g., with the display enabling unit **710**); and transmit information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to display a corresponding first message region with the edited acknowledgement in a conversation transcript that corresponds to the messaging session (e.g., with the transmitting unit **714**).

[0468] In some embodiments, the processing unit **706** is further configured to: in response to detecting the third input by the third contact, cease to display the conversation transcript (e.g., with the ceasing unit **712**).

[0469] In some embodiments, the processing unit **706** is further configured to: in response to detecting the third input by the third contact, enable display of the first message region in the acknowledgement editing interface (e.g., with the display enabling unit **710**).

[0470] In some embodiments, the processing unit **706** is further configured to: in response to detecting the third input by the third contact, enable display of the acknowledgement selection affordance that includes the plurality of acknowledgement options in the acknowledgement editing interface (e.g., with the display enabling unit **710**), wherein the first acknowledgement option is visually distinguished from the other acknowledgement options in the plurality of acknowledgement options to indicate that the first acknowledgement option is currently selected.

[0471] In some embodiments, the processing unit **706** is further configured to: in response to detecting the third input by the third contact, enable display of a menu in the acknowledgement editing interface that includes activatable editing options for the first message region (e.g., with the display enabling unit **710**).

[0472] In some embodiments, the plurality of acknowledgement options include graphical icons that display at least one of a heart, a thumbs up, a thumbs down, a "HA!", a "!!", and/or a question mark.

[0473] In some embodiments, the processing unit **706** is further configured to: concurrently enable display on the display unit **702** (e.g., with the display enabling unit **710**) of: a second message region in the conversation transcript, wherein at least some of the users in the messaging session have selected the first acknowledgement option for the second message region and at least some of the users in the messaging session have selected a second acknowledgement option for the second message region, distinct from the first acknowledgement option; and one or more indicia that users in the messaging session have selected a plurality of acknowledgements options for the second message region; and detect an input by a contact at a location on the touch-sensitive surface unit **704** that corresponds to a location of the second message region (e.g., with the detecting unit **708**); and, in response to detecting the input by the contact at the location on the touch-sensitive surface unit **704** that corresponds to the location of the second message

region, enable display of a user interface that includes a tally for each type of acknowledgement option selected by users in the messaging session (e.g., with the display enabling unit **710**).

[0474] In some embodiments, the processing unit **706** is further configured to: while the tally for each type of acknowledgement option selected by users in the messaging session is displayed, detect an input by a contact at a location on the touch-sensitive surface unit **704** that corresponds to a tally for the first acknowledgement option for the second message region (e.g., with the detecting unit **708**); and in response to detecting the input by the contact at a location on the touch-sensitive surface unit **704** that corresponds to the tally for the first acknowledgement option for the second message region, enable display of icons that represent users that selected the first acknowledgement option for the second message region (e.g., with the display enabling unit **710**).

[0475] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[0476] The operations described above with reference to FIGS. **6**A-**6**E are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **7**. For example, detection operations **606** and **616** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as selection of an object on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally utilizes or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

Editing Previously Sent Messages

[0477] FIGS. **8**A-**8**C are flow diagrams of a process for editing a previously sent messages in a messaging session, in accordance with some embodiments. More specifically, the methods relate to displaying an interface for editing a message, displaying a revised version of the message, ceasing to display the pre-revision version of the message, and/or displaying at least one indication of the revision.

[0478] Message transcripts can become cluttered with messages containing typographical errors followed by messages correcting the previous errors. By allowing editing of previously transmitted messages, the conversational flow of the transcript is better preserved and makes it easier for conversation participants to follow the conversation.

[0479] One or more examples of an electronic device (e.g., portable multifunction device **100** or device **300**) implementing these methods are shown in FIGS. **5**L-**5**T.

[0480] FIGS. **8**A-**8**C are flow diagrams illustrating a method **800**, performed by an electronic device, sometimes herein called a first electronic device, having one or more processors, memory, a touch-sensitive surface, and a display. In some embodiments, the electronic device includes one or more sensors (e.g., sensors in a touch-screen display or trackpad) configured to detect intensities of contacts on the touch-sensitive surface.

[0481] In accordance with some embodiments, method **800** includes displaying (**802**) a messaging user interface (e.g., user interface **5002**, FIG. **5**L, of a messaging application) on the display. The messaging user interface includes a conversation transcript (e.g., conversation transcript **5004** in user interface **5002**, FIG. **5**L) of a messaging session between a user of the electronic device and at least one other user, and a first message region (e.g., message region **5044**, FIG. **5**L) that includes a first message (e.g., message **5046-1**, FIG. **5**L) in the messaging session that was sent from the electronic device of the user to the at least one other user in the messaging session.

[0482] The method further includes detecting (**804**) a first input (e.g., input **5048**) that corresponds to a request to edit the first message. In some embodiments, the device detects the first input by detecting a tap gesture, long press gesture, light press gesture, or deep press gesture on the first message region (e.g., message region **5044**, FIG. **5**L) or on a hidden hit region for the first message region that results in display of a message editing interface for the first message (e.g., message editing interface **5052**, FIG. **5**N). In some embodiments, the device detects a tap gesture, light press gesture, or deep press gesture on an editing affordance in the messaging user interface or on a hidden hit region for the editing affordance that results in display of a message editing interface for the first message (e.g., as shown in FIG. **5**N). In some embodiments, if the first message is the most recently sent message by the user, the device detects a tap gesture, long press gesture, light press gesture, or deep press gesture on a message-input area (or on an editing affordance in the message-input area) that results in display of a message editing interface for the first message (e.g., as shown in FIG. **5**N).

[0483] In some embodiments, in response to detecting an input by the contact at the location on the touch-sensitive surface that corresponds to the location of the first message region (e.g., first message region **5044**, FIG. **5**L), the device displays a user interface that includes an edit affordance (e.g., an edit affordance, displayed as a menu option, as shown in FIG. **5**M), which when activated, displays the message editing interface for the first message (e.g., message editing interface **5052**, FIG. **5**N). In some embodiments, while the first message region is displayed with a list of activatable options for the first message (FIG. **5**M), the device detects an input (e.g., input **5050**, FIG. **5**M) that activates an edit option, such as a tap gesture on the edit option, that results in display of a message editing interface for the first message.

[0484] Method **800** includes, in response to detecting the first input (e.g., input **5048**, FIG. **5**L, or input **5050**, FIG. **5**M), displaying (**806**) a message editing interface (e.g., message editing interface **5052**, FIG. **5**N) for the first message that includes the first message (e.g., message **5046-**

1, FIG. **5**N), a keyboard (e.g., keyboard **5054**, FIG. **5**N), and an update affordance (e.g., update affordance **5056**, FIG. **5**N), and while displaying (**808**) the message editing interface for the first message, detecting (**810**) one or more inputs that revise the first message, displaying (**814**) a revised version of the first message; and detecting (**816**) an input that activates the update affordance.

[0485] In some embodiments, displaying (**806**) the editing interface replaces display of the conversation transcript (e.g., compare FIGS. **5**L and **5**N). In some embodiments, display of the editing interface (e.g., as shown in FIG. **5**N) replaces display of a user interface that includes a list of activatable options for the first message (e.g., as shown in FIG. **5**M).

[0486] In some embodiments, detecting (**810**) one or more inputs that revise the first message includes detecting inputs on the keyboard that add and/or delete text in the first message, and/or detecting inputs that select, cut, copy, and or paste text. For example, in FIGS. **5**N and **5**O, the editing replaces the term "ridiculous" with "ride". In some embodiments, detecting (**816**) an input that activates the update affordance includes detecting a tap gesture at a location that corresponds to the update affordance. In some embodiments, the update affordance is adjacent to the revised version of the first message in the message editing interface (rather than in the keyboard or in a new message input area).

[0487] Method **800** further includes, in response (**818**) to detecting the input that activates the update affordance: ceasing (**820**) to display the message editing interface for the first message; displaying (**822**) the revised version of the first message in place of the first message in the conversation transcript; displaying (**824**) at least one indication of the revision of the first message in the conversation transcript; and transmitting (**832**) the revised version of the first message to one or more electronic devices (e.g., a second electronic device) that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the revised version of the first message in place of the first message in a conversation transcript that corresponds to the messaging session, with at least one indication of the revision of the first message in the conversation transcript. For example, activating update affordance **5056**, shown in FIG. **5**N, causes the device to cease the display of message editing interface **5052**, for example returning to the display of messaging user interface **5002**, including conversation transcript **5004**, as shown in FIG. **5**O. Further, as shown in FIG. **5**O, the revised version of the first message **5046-2** is now displayed, along with an indication **5058-1** (e.g., a shadow, indicating the existence of an earlier version of the first message) of the revision of the first message in the conversation transcript. FIG. **5**O also shows a second example of an indication **5058-2** of the revision of the first message in the conversation transcript, which in this example is the displayed term "Edited". As shown in FIG. **5**R, the revised version **5046-2** of the first message is transmitted to and displayed by at least one electronic device corresponding to at least one other user included in the messaging session, and includes a first indication **5058-1** (e.g., a message region shadow) of the revision of the first message as well as a second indication **5058-2** (e.g., the displayed term "Edited") of the revision of the first message.

[0488] In some embodiments of method **800**, detecting (**810**) the one or more inputs that revise the first message includes detecting (**812**) an input at a location (e.g., location **5057**, FIG. **5**N) that corresponds to the first message in the message editing interface (e.g., a tap on the first message in the first message region) to select a position in the first message for text selection, text insertion, or the text deletion. The insertion point or location **5057** shown in FIG. **5**N is adjacent the term "ridiculous", which, as shown in FIG. **5**O, the user edits so as to replace that term with the term "ride."

[0489] In some embodiments, the at least one indication (e.g., indication **5058-1** and/or indication **5058-2**, FIG. **5**O) of the revision of the first message in the conversation transcript is not removable from the conversation transcript (**826**). Making such indications not removable may be important for giving users confidence that the conversation transcript accurately reflects the messages sent by the participants.

[0490] In some embodiments, the at least one indication of the revision of the first message includes a graphical element at a location of the first message region (**828**). For example, as shown in FIG. **5**O, indication **5058-1** is a shadow region behind the first message region; alternatively state, indication **5058-1** is a shadow region that is partially overlapped by the first message region.

[0491] In some embodiments, the at least one indication of the revision of the first message includes text adjacent to the first message region (**830**). For example, as shown in FIG. **5**O, indication **5058-1** is text (e.g., "Edited") displayed below the first message region that contains the revised version of the first message.

[0492] In some embodiments, method **800** includes, after editing the first message, detecting (**834**) an input (e.g., input **5060**, FIG. **5**O) that corresponds to a request to edit the revised version (e.g., version **5046-2**) of the first message, and in response to detecting the input that corresponds to the request to edit the revised version of the first message, performing a set of operations, including displaying a message editing interface (e.g., the interface shown in FIG. **5**R) for the revised version of the first message that includes the revised version of the first message, the keyboard, and the update affordance, an example of which is shown in FIG. **5**R. In such embodiments, method **800** further includes, while displaying the message editing interface for the revised version of the first message: detecting one or more inputs that further revise the first message; displaying a further revised version of the first message; and detecting an input that activates the update affordance. In such embodiments, method **800** further includes, in response to detecting the input that activates the update affordance: ceasing to display the message editing interface for the revised version of the first message; displaying the further revised version of the first message in place of the revised version of first message in the conversation transcript; displaying at least one indication that the first message in the conversation transcript has been revised (e.g., in some embodiment, two shadow regions are displayed behind the first message region, which are partially overlapped by the first message region, to indicate that the first message has been revised twice); and transmitting the further revised version of the first message to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the further revised version of the first message in place of the revised version of first message in a conversation transcript

that corresponds to the messaging session, with at least one indication that the first message in the conversation transcript has been revised.

[0493] In some embodiments, method **800** includes, after editing the first message, detecting (**836**) an input that corresponds to a request to see versions of the first message, and in response to detecting the input that corresponds to the request to see versions of the first message, displaying a user interface that includes a current version of the first message and one or more prior versions of the first message. For example, in response to input **5060** in FIG. **5**O, the device may display the user interface shown in FIG. **5**P, in which display of the conversation transcript is suppressed except for the revised version of the first message **5046-2**, and a menu **5062** or list of editing options. In this example, the displayed menu **5062** or list of editing options includes a copy affordance **5064**, a show edits affordance **5066**, a delete affordance **5068** and a display more options affordance **5070**. In the example shown in FIG. **5**P, input **5072** (e.g., a tap gesture) is detected at the location on the touch-sensitive surface that corresponds to the location of the "show edits" affordance **5066**, which when activated, displays a user interface **5074** (FIG. **5**Q) that includes current version **5046-1** of the first message as well as a prior version **5046-2**, as shown in FIG. **5**Q.

[0494] It should be understood that the particular order in which the operations in FIGS. **8**A-**8**C have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **1000**, **1200**, **1400**, **1600**, **1800**) are also applicable in an analogous manner to method **800** described above with respect to FIGS. **8**A-**8**C. For example, the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described above with reference to method **800** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein. For brevity, these details are not repeated here.

[0495] In accordance with some embodiments, FIG. **9** shows a functional block diagram of an electronic device **900** configured in accordance with the principles of the invention as described above. The functional blocks of the device may be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the invention. It is understood by persons of skill in the art that the functional blocks described in FIG. **9** may be combined or separated into sub-blocks to implement the principles of the invention as described above. Therefore, the description herein may support any possible combination or separation or further definition of the functional blocks described herein.

[0496] As shown in FIG. **9**, an electronic device **900** includes a display unit **902** configured to display a messaging user interface on the display **902**, the messaging user interface including: a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a first message region that includes a first message in the messaging session that was sent from the electronic device of the user to the at least one other user in the messaging session; a touch-sensitive surface unit **904** configured to detect contacts; and a processing unit **906** coupled with the display unit **902** and the touch-sensitive surface unit **904**. In some embodiments, the processing unit **906** includes a detecting unit **908**, a display enabling unit **910**, a ceasing unit **912**, and a transmitting unit **914**.

[0497] The processing unit **906** is configured to: detect a first input that corresponds to a request to edit the first message (e.g., with the detecting unit **908**); in response to detecting the first input, enable display of a message editing interface for the first message that includes the first message, a keyboard, and an update affordances (e.g., with the display enabling unit **910**); while the message editing interface for the first message is displayed: detect one or more inputs that revise the first message (e.g., with the detecting unit **908**); enable display of a revised version of the first message (e.g., with the display enabling unit **910**); and detect an input that activates the update affordance (e.g., with the detecting unit **908**); and, in response to detecting the input that activates the update affordance: cease to display the message editing interface for the first message (e.g., with the ceasing unit **912**); enable display of the revised version of the first message in place of the first message in the conversation transcript (e.g., with the display enabling unit **910**); enable display of at least one indication of the revision of the first message in the conversation transcript (e.g., with the display enabling unit **910**); and transmit the revised version of the first message to one or more electronic devices that correspond to the at least one other user included in the messaging session (e.g., with the transmitting unit **914**), wherein the one or more electronic devices display the revised version of the first message in place of the first message in a conversation transcript that corresponds to the messaging session, with at least one indication of the revision of the first message in the conversation transcript.

[0498] In some embodiments, the at least one indication of the revision of the first message in the conversation transcript is not removable from the conversation transcript.

[0499] In some embodiments, the at least one indication of the revision of the first message includes a graphical element at a location of the first message region.

[0500] In some embodiments, the at least one indication of the revision of the first message includes text adjacent to the first message region.

[0501] In some embodiments, detecting the one or more inputs that revise the first message include detecting an input at a location that corresponds to the first message in the message editing interface to select a position in the first message for text selection, text insertion, or the text deletion.

[0502] In some embodiments, the processing unit **906** is further configured to: after editing the first message, detect an input that corresponds to a request to edit the revised version of the first message (e.g., with the detecting unit **908**); in response to detecting the input that corresponds to the request to edit the revised version of the first message, enable display of a message editing interface for the revised version of the first message that includes the revised version of the first message, the keyboard, and the update affordance (e.g., with the display enabling unit **910**); while the message editing interface for the revised version of the first message is displayed: detect one or more inputs that further revise the first message (e.g., with the detecting unit **908**); enable display of a further revised version of the first message (e.g.,

with the display enabling unit **910**); and detect an input that activates the update affordance (e.g., with the detecting unit **908**); and, in response to detecting the input that activates the update affordance: cease to display the message editing interface for the revised version of the first message (e.g., with the ceasing unit **912**); enable display of the further revised version of the first message in place of the revised version of first message in the conversation transcript (e.g., with the display enabling unit **910**); enable display of at least one indication that the first message in the conversation transcript has been revised (e.g., with the display enabling unit **910**); and transmit the further revised version of the first message to one or more electronic devices that correspond to the at least one other user included in the messaging session (e.g., with the transmitting unit **914**), wherein the one or more electronic devices display the further revised version of the first message in place of the revised version of first message in a conversation transcript that corresponds to the messaging session, with at least one indication that the first message in the conversation transcript has been revised.

[0503] In some embodiments, the processing unit **906** is further configured to: after editing the first message, detect an input that corresponds to a request to see versions of the first message (e.g., with the detecting unit **908**); and, in response to detecting the input that corresponds to the request to see versions of the first message, enable display of a user interface that includes a current version of the first message and one or more prior versions of the first message (e.g., with the display enabling unit **910**).

[0504] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[0505] The operations described above with reference to FIGS. **8**A-**8**C are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **9**. For example, detection operations **804** and **810** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as selection of an object on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally utilizes or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

[0506] FIGS. **10**A-**10**B are flow diagrams of a process for editing a previously sent message in a messaging session, in accordance with some embodiments. One or more examples of an electronic device (e.g., portable multifunction device **100** or device **300**) implementing these methods are shown in FIGS. **5**L-**5**T.

[0507] FIGS. **10**A-**10**B are flow diagrams illustrating a method **1000**, performed by an electronic device, sometimes herein called a first electronic device, having one or more processors, memory, a touch-sensitive surface, and a display. In some embodiments, the electronic device includes one or more sensors (e.g., sensors in a touch-screen display or trackpad) configured to detect intensities of contacts on the touch-sensitive surface.

[0508] In accordance with some embodiments, method **1000** includes displaying (**1002**) a messaging user interface (e.g., user interface **5002**, as shown in FIG. **5**L or **5**O, of a messaging application) on the display. The messaging user interface includes a conversation transcript (e.g., conversation transcript **5004** in user interface **5002**, FIG. **5**L or **5**O) of a messaging session between a user of the electronic device and at least one other user (e.g., a user of another electronic device), and a first message region (e.g., message region **5044**, FIG. **5**O) that includes a current version of a first message (e.g., message version **5046-2**, FIG. **5**O) in the messaging session, wherein the conversation transcript includes an indication (e.g., indication **5058-1**, or **5058-2**, as describe above) that the current version of the first message is a revised version of the first message in the conversation transcript. The original version of the first message is, for example, a previously transmitted message or a previously received message.

[0509] Method **1000** further includes detecting (**1004**) an input that corresponds to a request to see versions of the first message (e.g., input **5060**, as shown in FIG. **5**O), and in response to detecting the input that corresponds to the request to see versions of the first message, displaying (**1008**) a versions user interface (e.g., user interface **5074**, FIG. **5**Q) that includes the current version of the first message (e.g., version **5046-1**) and one or more prior versions of the first message (e.g., version **5046-2**).

[0510] In some embodiments, detecting (**1004**) the input includes the device detecting a tap gesture, long press gesture, light press gesture, or deep press gesture on the first message region or on a hidden hit region for the first message region that results in display of a user interface with current and prior versions of the first message (e.g., user interface **5074**, FIG. **5**Q).

[0511] In some embodiments, in response to detecting an input by the contact at the location on the touch-sensitive surface that corresponds to the location of the first message region (input **5060**, FIG. **5**O), the device displays a user interface that includes an affordance (e.g., "show edits" menu option, FIG. **5**P), which when activated, displays current and prior versions of the first message (e.g., FIG. **5**Q). In some embodiments, while the first message region is displayed with a list of activatable options for the revised version of the first message (as shown in FIG. **5**P), the device detects an input that activates a "show edits" option (e.g., input **5072** on show edits option **5066**, FIG. **5**P), such as a tap gesture on the "show edits" option, that results in display of a user interface with current and prior versions of the first message (e.g., FIG. **5**Q).

[0512] In some embodiments, the input that corresponds to the request to see versions of the first message is detected (**1006**) while displaying the current version of the first message (e.g., without displaying other messages in the

conversation transcript, as shown in FIG. **5**S) and a menu that includes an affordance (e.g., a "show edits" option, FIG. **5**S), which when activated results in display of the user interface (e.g., as shown in FIG. **5**T) that includes the current version (e.g., version **5046-2**, FIG. **5**T) of the first message and one or more prior versions of the first message (e.g., version **5046-1**, FIG. **5**T). In some embodiments, the menu includes an affordance (e.g., a "edit" option), which when activated results in display of a message editing interface for the current version of the first message that includes the current version of the first message, a keyboard, and an update affordance.

[0513] In some embodiments, in the versions user interface (e.g., **5074**, FIG. **5**Q), the current version of the first message (e.g., **5046-1**) is visually distinguished (**1010**) from other versions of the first message. For example, in various embodiments the current version of the first message is visually distinguished from other versions of the first message by different shading, background color, background pattern, font color, and/or region boundary color, or the like.

[0514] In some embodiments, the versions user interface (e.g., **5074**, FIG. **5**Q) includes (**1012**) the current version of the first message (e.g., **5046-1**), an original version of the first message (e.g., **5046-2**), and at least one version of the first message that was revised prior to the current version of the first message (not shown in the figures).

[0515] In some embodiments, the versions user interface (e.g., **5074**, FIG. **5**Q) includes (**1014**) an affordance (e.g., a "Done" option **5082**, FIG. **5**Q), which when activated causes redisplay of the conversation transcript in the user interface (e.g., as shown in FIG. **5**R). Typically, activation of this affordance also causes display of the versions user interface to cease.

[0516] In some embodiments, the versions user interface includes (**1016**) an affordance (e.g., Edit icon **5080**, FIG. **5**Q), which when activated causes display of a message editing interface (e.g., as shown in FIG. **5**R) for the current version of the first message that includes the current version of the first message (**5046-2**), a keyboard (**5054**), and an update affordance (**5056**). Typically, activation of this affordance also causes display of the versions user interface to cease.

[0517] It should be understood that the particular order in which the operations in FIGS. **10**A-**10**B have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1200**, **1400**, **1600**, **1800**) are also applicable in an analogous manner to method **1000** described above with respect to FIGS. **10**A-**10**B. For example, the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described above with reference to method **1000** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein. For brevity, these details are not repeated here.

[0518] In some embodiments, method **1000** includes, while displaying the versions user interface (e.g., **5074**, FIG. **5**Q), detecting (**1018**) an input (e.g., input **5076** or **5078**, FIG. **5**Q, to edit either the current version **5046-1** or the original version **5046-2**) on a respective version of the first message (e.g., detecting a tap gesture, long press gesture, light press gesture, or deep press gesture on the current version, an intermediate version, or the original version of the first message); and, in response to detecting an input on the respective version of the first message: displaying a message editing interface (e.g., a message editing interface as shown in FIG. **5**N) for the respective version of the first message that includes the respective version (**5046**) of the first message, a keyboard (**5054**), and an update affordance (**5056**); and ceasing to display the versions user interface.

[0519] In accordance with some embodiments, FIG. **11** shows a functional block diagram of an electronic device **1100** configured in accordance with the principles of the invention as described above. The functional blocks of the device may be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the invention. It is understood by persons of skill in the art that the functional blocks described in FIG. **11** may be combined or separated into sub-blocks to implement the principles of the invention as described above. Therefore, the description herein may support any possible combination or separation or further definition of the functional blocks described herein.

[0520] As shown in FIG. **11**, an electronic device **1100** includes a display unit **1102** configured to display a messaging user interface on the display unit, the messaging user interface including: a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a first message region that includes a current version of a first message in the messaging session, wherein the conversation transcript includes an indication that the current version of the first message is a revised version of the first message in the conversation transcript; a touch-sensitive surface unit **1104** configured to detect contacts; and a processing unit **1106** coupled with the display unit **1102** and the touch-sensitive surface unit **1104**. In some embodiments, the processing unit **1106** includes a detecting unit **1108**, a display enabling unit **1110**, and a ceasing unit **1112**.

[0521] The processing unit **1106** is configured to: detect an input that corresponds to a request to see versions of the first message (e.g., with the detecting unit **1108**); and, in response to detecting the input that corresponds to the request to see versions of the first message, enable display of a versions user interface that includes the current version of the first message and one or more prior versions of the first message (e.g., with the display enabling unit **1110**).

[0522] In some embodiments, the input that corresponds to the request to see versions of the first message is detected while displaying the current version of the first message and a menu that includes an affordance, which when activated results in display of the user interface that includes the current version of the first message and one or more prior versions of the first message.

[0523] In some embodiments, in the versions user interface, the current version of the first message is visually distinguished from other versions of the first message.

[0524] In some embodiments, the versions user interface includes the current version of the first message, an original version of the first message, and at least one version of the first message that was revised prior to the current version of the first message.

[0525] In some embodiments, the versions user interface includes an affordance, which when activated causes redisplay of the conversation transcript.

[0526] In some embodiments, the versions user interface includes an affordance, which when activated causes display of a message editing interface for the current version of the first message that includes the current version of the first message, a keyboard, and an update affordance.

[0527] In some embodiments, the processing unit **1106** is further configured to: while the versions user interface is displayed, detect an input on a respective version of the first message (e.g., with the detecting unit **1108**); and, in response to detecting an input on the respective version of the first message: enable display of a message editing interface for the respective version of the first message that includes the respective version of the first message, a keyboard, and an update affordance (e.g., with the display enabling unit **1110**); and cease to display the versions user interface (e.g., with the ceasing unit **1112**).

[0528] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[0529] The operations described above with reference to FIGS. **10**A-**10**B are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **11**. For example, detection operations **1004** and **1018** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as selection of an object on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally utilizes or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

Message Impact Effects

[0530] FIGS. **12**A-**12**E, described in more detail below, relate generally to methods for applying an impact effect option to a message input. More specifically, these figures relate to methods of displaying an interface that includes multiple impact effect options in response to input received in a message input area of a messaging user interface. A preview that applies an impact effect option to the message input is displayed. Information including the message input and the applied impact effect option is transmitted to at least one remote electronic device (e.g., a device of at least one other user). Oftentimes, additional information that could be conveyed with verbal tone or facial expressions is lost when only the text of a conversation is available to determine the intent of the speaker. The methods described here with respect to FIGS. **12**A-**12**E allow additional information to be added to the transcript to convey additional sentiment that might be missing otherwise.

[0531] One or more examples of an electronic device (e.g., portable multifunction device **100** or device **300**) implementing these methods are shown in FIGS. **5**U-**5**AM and **5**AN-**5**BF.

[0532] FIGS. **12**A-**12**E are flow diagrams illustrating a method **1200**, performed by an electronic device, sometimes herein called a first electronic device, having one or more processors, memory, a touch-sensitive surface, and a display. In some embodiments, the electronic device includes one or more sensors (e.g., sensors in a touch-screen display or trackpad) configured to detect intensities of contacts on the touch-sensitive surface.

[0533] In accordance with some embodiments, method **1200** includes displaying (**1202**) a messaging user interface (e.g., user interface **5002**, as shown in FIG. **5**U, of a messaging application) on the display. The messaging user interface includes a conversation transcript (e.g., conversation transcript **5004** in user interface **5002**, FIG. **5**U) of a messaging session between a user of the electronic device and at least one other user (e.g., a user of another electronic device), and a message-input area (e.g., **5100**, FIG. **5**U) that includes a first message input (e.g., text, stickers, images, and/or other graphics entered by a user of the electronic device in the message-input area, but not yet sent to the at least one other user in the messaging session). Method **1200** includes, while displaying the messaging user interface, detecting a first input by a first contact (e.g., input **5102**, FIG. **5**U) at a location on the touch-sensitive surface that corresponds to a location in the message-input area. In some embodiments, the first input includes a gesture (e.g., a swipe gesture) received at the message-input area. In some embodiments, the message-input area includes an impact selection affordance (e.g., **5104**, FIG. **5**U) and the location of the contact corresponds to the impact selection affordance. In some embodiments, detecting the first input includes the device detecting a tap gesture, long press gesture, light press gesture, or deep press gesture by the contact at a location that corresponds to the impact selection affordance. Furthermore, in some embodiments, different inputs (e.g., a tap gesture, and a deep press gesture) on the impact selection affordance cause the user interface to transition to different subsequent user interfaces. For example, in some embodiments, a tap gesture on affordance **5104**, FIG. **5**U or **5**X, sends the message input **5102** in message input area **5100** as a message, while a deep press input **5108-1**, **5108-2**, **5108-3**, as shown in FIGS. **5**X, **5**Y and **5**Z, when detected by the electronic device, causes the messaging application to display an impact selection interface **5110**, FIG. **5**AA.

[0534] Thus, method **1200** further includes, in response to detecting the first input by the first contact, displaying (**1206**) an impact selection interface (e.g., impact selection interface **5110**, FIG. **5**AA) that includes a plurality of impact effect options (e.g., impact effect options **5112-1** through **5112-4** are displayed in place of the messaging user interface or on top of the messaging user interface). In some embodiments, the displayed plurality of impact effect options (e.g., **5112-1** to **5112-4**, FIG. **5**AA) are a subset, less than all, of a set of impact effect options. In some embodiments, the set of impact effect options includes options that are applied to

an individual message region (e.g., "region effect" options) and options that are applied to the entire displayed conversation transcript when a message is initially displayed in the messaging session (e.g., "full-screen effect" options). In some embodiments, the displayed plurality of impact effect options includes at least some of the region effect options and none of the full-screen effect options. In some embodiments, the region effect options include: an option that slams down a message in the conversation transcript when the message is initially displayed (e.g., "slam" option **5112-4**, FIG. **5**AA); an option that increases the size of the message in the conversation transcript, at least when the message is initially displayed (e.g., "loud" option **5112-3**, FIG. **5**AA); an option that decreases the size of the message in the conversation transcript, at least when the message is initially displayed (e.g., "gentle" option **5112-2**, FIG. **5**AA, and FIGS. **5**AT through **5**AW); and an option that conceals the content of a message in the conversation transcript ("invisible ink" option **5112-1**, FIG. **5**AA).

[0535] In some embodiments, the full-screen effect options include two or more of the following options: an option that displays balloons in the conversation transcript when the message is initially displayed ("balloons"); an option that displays confetti in the conversation transcript when the message is initially displayed ("confetti"); an option that displays fireworks in the conversation transcript when the message is initially displayed ("fireworks"); an option that displays the message in focus and blurs the rest of the conversation transcript when the message is initially displayed ("focus"); an option that displays one or more spotlight beams moving in the conversation transcript when the message is initially displayed ("spotlight" or "drop the mic"); an option that displays multiple copies of the message over the conversation transcript when the message is initially displayed ("echo"); an option that displays a shooting star in the conversation transcript when the message is initially displayed ("shooting star"); an option that displays multiple laser beams (e.g., as shown in FIGS. **5**CR through **5**CT) moving in the conversation transcript when the message is initially displayed ("lasers"); and an option that displays a heart inflating from the message when the message is initially displayed ("metallic heart").

[0536] Method **1200** further includes, while displaying the impact selection interface, detecting (**1222**) a second input by a second contact at a location on the touch-sensitive surface that corresponds to a location of a first impact effect option in the plurality of impact effect options. Examples of the second input are input **5108-4**, FIG. **5**AA, input **5108-5**, FIGS. **5**AB-**5**AD, and input **5108-6**, FIGS. **5**AE-**5**AF. In some embodiments, the first contact and the second contact are distinct contacts, such as contacts in two different tap gestures made by the same finger, or a deep press gesture on a send affordance followed by a tap gesture on a first impact effect option. In some embodiments, the first contact and the second contact are different parts of the same continuous contact with the touch-sensitive surface, such as a long press, light press, or deep press on the impact selection affordance (e.g., deep press input **5108-1**, **5108-2**, **5108-3**, on impact selection affordance **5104**, as shown in FIGS. **5**X, **5**Y and **5**Z) followed by a drag to the first impact effect option (e.g., input **5108-4** on impact effect option **5112-1**, FIG. **5**AA) and then pausing or deep pressing on the first impact effect option.

[0537] Method **1200** also includes, in response to detecting the second user input by a second contact (e.g., second input **5108-6**, FIG. **5**AE) displaying (**1224**) a preview (e.g., in the impact selection interface, **5110**, FIG. **5**AE) that applies the first impact effect option to the first message input. FIG. **5**AE shows a preview of the slam option being applied to first message input ("Congratulations!") in response to a second input **5108-6** respective by a second contact at a location on the touch-sensitive surface that corresponds to a location of a first impact effect option (i.e., the slam option). In some embodiments, the preview applies the first impact effect to a message region that includes the first message input (e.g., as shown in FIG. **5**AE). In some embodiments, the preview applies the first impact effect to all (or substantially all) of the display screen, which includes a message region with the first message, for a full-screen effect, an example of which is shown by the sequence of user interface images in FIGS. **5**AX through **5**BF. FIGS. **5**AX through **5**BF show the progression of the "slam" effect of a first message input ("Hell No!!"), starting with the first message input displayed shown enlarged, rotated and with a dark background (FIG. **5**AX), then displayed even larger and with a somewhat lighter background (FIG. **5**AY), then less enlarged and rotated at a different angle than before (FIG. **5**AZ), then shown with further reduced enlargement and with blurry borders (FIG. **5**BA), then shown with reduced size a different background and a different rotation (FIG. **5**BB) and then with a sequence of different shadows around the message region (FIGS. **5**BC, **5**BD, **5**BE) until the first message input is shown at normal (default) size, not rotated, and with a normal (default) background (FIG. **5**BF).

[0538] In some embodiments, while the preview of a respective impact effect option is displayed, the location in the impact selection interface that corresponds to the respective impact effect option includes an affordance (e.g., send affordance **5118**, FIG. **5**AB) for sending a message (with the first message input) with the respective impact effect option.

[0539] With regard to displaying (**1206**) an impact selection interface that includes a plurality of impact effect options, discussed above, in some embodiments, the impact selection interface includes (**1208**) both a region effect options affordance (e.g., affordance **5114**, FIG. **5**AA), which when activated causes display of impact effect options for a message containing the first message input, and a full-screen effect options affordance (e.g., affordance **5116**, FIG. **5**AA), which when activated causes display of a preview of one impact effect option that is applied to the entire displayed conversation transcript when a message containing the first message input is displayed in the messaging session. Typically, there will be a plurality of full-screen effect options, but only one of them is previewed at any one time, in response to activation of a full-screen effect options affordance.

[0540] In some embodiments, with regard to displaying (**1206**) an impact selection interface that includes a plurality of impact effect options, discussed above, the plurality of impact effect options includes (**1210**) at least one impact effect option that applies an image (e.g., a shaded oval or cloud) with an area that is larger than an area of a message region that contains the first message input to the message region that contains the first message input (e.g., displaying the image behind the message region that contains the first message input). Examples of this effect are shown in FIGS. **5**AE, and **5**AF.

[0541] In some embodiments, with regard to displaying (**1206**) an impact selection interface that includes a plurality of impact effect options, discussed above, the plurality of impact effect options includes (**1212**) at least one impact effect option that increases or decreases a size of a message region that contains the first message input relative to a size (e.g., a default size) of the message region that contains the first message input when no impact effect option is selected. For example, FIG. **5**AB shows an example in which an impact effect option is displayed with a message region that contains the first message input having a decreased size relative to a default size of the message region, while FIG. **5**AC shows an example in which an impact effect option is displayed with the message region that contains the first message input having an increased size relative to a default size of the message region.

[0542] In some embodiments, with regard to displaying (**1206**) an impact selection interface that includes a plurality of impact effect options, discussed above, the plurality of impact effect options includes (**1214**) at least one impact effect option that is configured to have a message region that contains the first message input interact with other message regions in the displayed conversation transcript when the message region that contains the first message input is displayed (e.g., the other message regions shake and/or bounce upon display of the message region that contains the first message input in the conversation transcript, to increase the impact of the arriving message). For example, the sequence of user interfaces illustrated in FIGS. **5**BB-**5**BE show message regions other than the message region with the first message input (e.g., "Hell No!!) being moved (e.g., moved closer together, and caused to partially overlap) to increase the visual impact of the arriving message.

[0543] In some embodiments, with regard to displaying (**1206**) an impact selection interface that includes a plurality of impact effect options, discussed above, the plurality of impact effect options includes (**1216**) at least one impact effect option that is configured to display an animation when a message region that contains the first message input is displayed in a conversation transcript that corresponds to the messaging session. In some embodiments, the animation is a "shake" animation (e.g., as shown in FIGS. **5**AH-**5**AI) that moves the message region between two or more locations, such as side-to-side and/or up-and-down animation. In some embodiments, the animation increases a size of the message region from an initially displayed size in the conversation transcript (e.g., as shown in the sequence of FIGS. **5**AK, **5**AL, **5**AM, and in the sequence of FIGS. **5**AN-**5**AS).

[0544] In some embodiments, the animation increases the size of the message region beyond a final size that is displayed at the end of the animation (thereby overshooting the final size) and then reduces the size of the message region to the final size (e.g., as shown in the sequence of FIGS. **5**AN-**5**AS). In some embodiments, the final size of the message region is larger or smaller than a (default) size of the message region that contains the first message input when no impact effect option is selected. In some embodiments, an impact effect option that conceals the content of a message region displays an animation that includes moving particles (e.g., virtual sand particles) within the message region to indicate that the content of the message is concealed (e.g., as shown in FIG. **5**BQ-**5**BR).

[0545] In some embodiments, with regard to displaying (**1206**) an impact selection interface that includes a plurality of impact effect options, discussed above, the plurality of impact effect options includes (**1218**) at least one impact effect option that is configured to display an animation when a message region that contains the first message input is displayed in a conversation transcript that corresponds to the messaging session, wherein the animation concurrently moves the message region that contains the first message input and other message regions in the conversation transcript. For example, the other message regions shake and/or bounce upon display of the message region that contains the first message input in the conversation transcript, to increase the impact of the arriving message. The sequence of user interfaces illustrated in FIGS. **5**BB-**5**BF show such an example in which both the message region with the first message input and other message regions are moved in the conversation transcript in accordance with the "slam" effect option (**5112-4** in FIGS. **5**AA, **5**AC).

[0546] In some embodiments, with regard to displaying (**1206**) an impact selection interface that includes a plurality of impact effect options, discussed above, the plurality of impact effect options includes (**1220**) at least one impact effect option that is configured to trigger one or more tactile outputs (e.g., to provide haptic feedback) when a message region that contains the first message input is displayed in a conversation transcript that corresponds to the messaging session. For example, In some embodiments, a first impact effect option (e.g., the "slam" option **5112-4**, FIG. **5**AA) has a smaller amplitude tactile output than a second impact effect option (e.g., the "loud" option **5112-3**, FIG. **5**AA).

[0547] In some embodiments, with regard to displaying (**1224**) a preview (e.g., in the impact selection interface, **5110**, FIG. **5**AE), the preview (e.g., in the impact selection interface **5110**, FIG. **5**AE) that applies the first impact effect option to the first message input repeats periodically (**1226**). For example, an animation shown in the preview is repeated every N (e.g., 2, 3, or 4) seconds, until a subsequent user input is detected.

[0548] In some embodiments, after displaying the preview, method **1200** includes detecting (**1228**) lift off of the second contact at a location on the touch-sensitive surface that corresponds to the first impact effect option; and, in response to detecting lift off of the second contact at the location on the touch-sensitive surface that corresponds to the first impact effect option: ceasing to display the impact selection interface (e.g., impact selection interface, **5110**, FIG. **5**AE); displaying a message region that contains the first message input in the conversation transcript (and, in some embodiments, applying the first impact effect option to the message region and/or the conversation transcript, as shown in FIG. **5**AH); and transmitting information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to (A) display a message region that contains the first message input in a conversation transcript that corresponds to the messaging session, and (B) apply the first impact effect option (e.g., as shown in FIG. **5**AK). The first impact effect is optionally applied to the message region that contains the first message input and/or to the displayed conversation transcript.

[0549] In some embodiments, after displaying the preview, method **1200** includes detecting (**1230**) detecting a third input by a third contact at a location on the touch-sensitive surface that corresponds to the first impact effect option (e.g., detecting a tap gesture, long press gesture, light

press gesture, or deep press gesture by the contact at a location that corresponds to the first impact effect option, such as at a send affordance for the first impact option). For example, FIG. **5**AG shows a third input **5108-7** on a send affordance, at a location corresponding to a user-selected impact effect option, in this case the "slam" option.

[0550] In such embodiments, method **1200** includes, in response to detecting the third input by the third contact at the location on the touch-sensitive surface that corresponds to the first impact effect option: ceasing to display the impact selection interface; displaying a message region that contains the first message input in the conversation transcript (and, in some embodiments, applying the first impact effect option to the message region and/or the conversation transcript, as shown in FIG. **5**AH); and transmitting information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to (A) display a message region that contains the first message input in a conversation transcript that corresponds to the messaging session, and (B) apply the first impact effect option (e.g., as shown in FIG. **5**AK). The first impact effect is optionally applied to the message region that contains the first message input and/or to the displayed conversation transcript.

[0551] In some embodiments, after displaying the preview, method **1200** includes detecting (**1232**) lift off of the second contact (e.g., lift-off of second input **5108-6**, as shown in FIG. **5**AE or **5**AF) at a location on the touch-sensitive surface that corresponds to the first impact effect option; and, in response to detecting lift off of the second contact at a location on the touch-sensitive surface that corresponds to the first impact effect option: selecting the first impact effect option for a message that contains the first message input; ceasing to display the impact selection interface; and displaying (e.g., as shown in FIG. **5**AH) the conversation transcript of the messaging session and the message-input area that includes a first message input.

[0552] In such embodiments, method **1200** includes, detecting a third input (e.g., a tap gesture at a location that corresponds to a send affordance, such as third input **5108-7**, FIG. **5**AG); and in response to detecting the third input: displaying a message region (e.g., as shown in FIG. **5**AH) that contains the first message input in the conversation transcript (and, in some embodiments, applying the first impact effect option to the message region and/or the conversation transcript); and transmitting information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to (A) display a message region that contains the first message input in a conversation transcript that corresponds to the messaging session, and (B) apply the first impact effect option (e.g., as shown in FIG. **5**AK). The first impact effect is optionally applied to the message region that contains the first message input and/or to the displayed conversation transcript.

[0553] In some embodiments, after displaying the preview, method **1200** includes detecting (**1234**) a third input by a third contact at a location on the touch-sensitive surface that corresponds to the first impact effect option (e.g., detecting a tap gesture, long press gesture, light press gesture, or deep press gesture by the contact at a location that corresponds to the first impact effect option, such as at a send affordance for the first impact option). For example, FIG. **5**AG shows a third input **5108-7** on a affordance, at a location corresponding to a user-selected impact effect option, in this case the "slam" option.

[0554] In such embodiments (**1234**), method **1200** includes, in response to detecting the third input by the third contact at the location on the touch-sensitive surface that corresponds to the first impact effect option: selecting the first impact effect option for a message that contains the first message input; ceasing to display the impact selection interface; and displaying the conversation transcript of the messaging session and the message-input area that includes a first message input (e.g., first message input **5102** in message-input area **5008**, as shown in FIG. **5**AH). Further, method **1200** includes detecting a fourth input (e.g., a tap gesture at a location that corresponds to a send affordance, which optionally may be the same affordance as the impact option select affordance, or alternatively may a distinct affordance from the impact option select affordance); and in response to detecting the fourth input: (A) displaying a message region that contains the first message input in the conversation transcript (and, in some embodiments, applying the first impact effect option to the message region and/or the conversation transcript); and transmitting information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to (A) display a message region that contains the first message input in a conversation transcript that corresponds to the messaging session, and (B) apply the first impact effect option (e.g., as shown in FIG. **5**AK). The first impact effect is optionally applied to the message region that contains the first message input and/or to the displayed conversation transcript.

[0555] Optionally, a user of the messaging application can preview more than one impact effect option that is applied to the entire displayed conversation transcript before making a final selection of an impact effect option. In some embodiments, method **1200** includes, while the message-input area is empty (**1236**), detecting an input that enters text in the message-input area (e.g., message input area **5100**, FIG. **5**U); and, in response to detecting the input that enters text in the message-input area, displaying an impact selection affordance (e.g., impact selection affordance **5104**, in message-input area **5100**), wherein activation of the impact selection affordance is configured to cause display of the impact selection interface.

[0556] In some embodiments, method **1200** includes, while a preview of an impact effect option that is applied to the entire displayed conversation transcript is displayed (e.g., a preview of a first full screen effect option, such as displaying balloons (e.g., balloons **5152-1**, as shown in FIG. **5**CB) floating upwards in the conversation transcript for a birthday message, as shown in FIG. **5**CC, and FIGS. **5**CH-**5**CO), detecting (**1238**) an input (e.g., swipe gesture **5156**, FIG. **5**CC) that activates display of a preview of another impact effect option that is applied to the entire displayed conversation transcript; and, in response to detecting the input that activates display of the preview of another impact effect option that is applied to the entire displayed conversation transcript, displaying the preview of the second impact effect option that is applied to the entire displayed conversation transcript (e.g., displaying a preview of a second full screen effect option, such as a display of confetti for a "Congratulations!" message, as shown in FIGS. **5**CD-SCE, or fireworks exploding in the conversation transcript for a "Happy New Year" message, as shown in FIGS.

5CP-5CW). As shown in FIGS. 5CB and 5CC, the user interface may include an effect option indicator **5154** (sometimes called page dots) to indicate which full screen effect option is currently selected or is currently being previewed, and also to indicate how many full screen effect options are available and which one of those options in a sequence of the full screen effect options is currently being viewed.

[0557] Optionally, a user of the messaging application can preview more than one impact effect option before making a final selection of an impact effect option. In some embodiments, method **1200** includes, while displaying the impact selection interface (e.g., impact selection interface **5110**, as shown in FIG. 5AA), detecting (**1240**) an input by a contact (e.g., input **5108-4**) at a location on the touch-sensitive surface that corresponds to a location of a second impact effect option in the plurality of impact effect options; and, in response to detecting the user input by the contact at the location on the touch-sensitive surface that corresponds to the location of a second impact effect option, displaying a preview (e.g., in the impact selection interface) that applies the second impact effect option to the first message input. In some embodiments, the preview applies the second impact effect to a message region that includes the first message input.

[0558] The sequence of FIGS. 5CH-5CO shows an example of a balloons full screen effect being displayed when a message ("Happy Birthday!!!!!") containing a corresponding enhanced message content trigger is received. Similarly, the sequence of FIGS. 5CP-5CW shows an example of a fireworks full screen effect being displayed when a message ("Happy New Year!!!") containing a corresponding enhanced message content trigger is received.

[0559] In some embodiments, method **1200** includes determining (**1242**) whether an electronic device that corresponds to another user in the messaging session is capable of applying the first impact effect option (or, more generally, capable of applying any of the plurality of impact effect options) to a message in the messaging session, and, in accordance with a determination that the electronic device that corresponds to another user in the messaging session is not capable of applying the first impact effect option to a message in the messaging session, displaying a notification on the display of the electronic device of the user about the first impact effect option (e.g., a notification that the electronic device that corresponds to the other user in the messaging session is not capable of applying the first impact effect option, or any impact effect option, to a message in the messaging session). Optionally, in accordance with a determination that the electronic device that corresponds to another user in the messaging session is capable of applying the first impact effect option to a message in the messaging session, method **1200** includes forgoing displaying the notification.

[0560] In some embodiments, prior to transmitting information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to display a message region that contains the first message input, the electronic device of the user determines whether the electronic device corresponding to the at least one other user is capable of applying the first impact effect option to the message region. If not, the electronic device of the user displays a notification indicating that the other user will not see the effect.

[0561] It should be understood that the particular order in which the operations in FIGS. **12**A-**12**E have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1000**, **1400**, **1600**, **1800**) are also applicable in an analogous manner to method **1200** described above with respect to FIGS. **12**A-**12**E. For example, the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described above with reference to method **1200** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein. For brevity, these details are not repeated here.

[0562] In accordance with some embodiments, FIG. **13** shows a functional block diagram of an electronic device **1300** configured in accordance with the principles of the invention as described above. The functional blocks of the device may be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the invention. It is understood by persons of skill in the art that the functional blocks described in FIG. **13** may be combined or separated into sub-blocks to implement the principles of the invention as described above. Therefore, the description herein may support any possible combination or separation or further definition of the functional blocks described herein.

[0563] As shown in FIG. **13**, an electronic device **1300** includes a display unit **1302** configured to display a messaging user interface on the display unit, the messaging user interface including: a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a message-input area that includes a first message input; a touch-sensitive surface unit **1304** configured to detect contacts; and a processing unit **1306** coupled with the display unit and the touch-sensitive surface unit. In some embodiments, the processing unit **1306** includes a detecting unit **1308**, a display enabling unit **1310**, a ceasing unit **1312**, a transmitting unit **1314**, a selecting unit **1316**, and a determining unit **1318**.

[0564] The processing unit **1306** is configured to: while displaying the messaging user interface, detect a first input by a first contact at a location on the touch-sensitive surface unit **1304** that corresponds to a location in the message-input area (e.g., with the detecting unit **1308**); in response to detecting the first input by the first contact, enable display of an impact selection interface that includes a plurality of impact effect options (e.g., with the display enabling unit **1310**); while displaying the impact selection interface, detect a second input by a second contact at a location on the touch-sensitive surface unit **1304** that corresponds to a location of a first impact effect option in the plurality of impact effect options (e.g., with the detecting unit **1308**); and, in response to detecting the second user input by a second contact, enable display of a preview that applies the first impact effect option to the first message input (e.g., with the display enabling unit **1310**).

[0565] In some embodiments, the processing unit **1306** is further configured to: after displaying the preview, detect lift

off of the second contact at a location on the touch-sensitive surface unit **1304** that corresponds to the first impact effect option (e.g., with the detecting unit **1308**); and, in response to detecting lift off of the second contact at the location on the touch-sensitive surface unit **1304** that corresponds to the first impact effect option: cease to display the impact selection interface (e.g., with the ceasing unit **1312**); enable display of a message region that contains the first message input in the conversation transcript (e.g., with the display enabling unit **1310**); and transmit information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to enable display of a message region that contains the first message input in a conversation transcript that corresponds to the messaging session, and apply the first impact effect option (e.g., with the transmitting unit **1314**).

[0566] In some embodiments, the processing unit **1306** is further configured to: after displaying the preview, detect lift off of the second contact at a location on the touch-sensitive surface unit **1304** that corresponds to the first impact effect option (e.g., with the detecting unit **1308**); and, in response to detecting lift off of the second contact at a location on the touch-sensitive surface unit **1304** that corresponds to the first impact effect option: select the first impact effect option for a message that contains the first message input (e.g., with the selecting unit **1316**); cease to display the impact selection interface (e.g., with the ceasing unit **1312**); and enable display of the conversation transcript of the messaging session and the message-input area that includes a first message input (e.g., with the display enabling unit **1310**); detect a third input (e.g., with the detecting unit **1308**); and in response to detecting the third input: enable display of a message region that contains the first message input in the conversation transcript (e.g., with the display enabling unit **1310**); and transmit information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to enable display of a message region that contains the first message input in a conversation transcript that corresponds to the messaging session, and apply the first impact effect option (e.g., with the transmitting unit **1314**).

[0567] In some embodiments, the processing unit **1306** is further configured to: after displaying the preview, detect a third input by a third contact at a location on the touch-sensitive surface unit **1304** that corresponds to the first impact effect option (e.g., with the detecting unit **1308**); and, in response to detecting the third input by the third contact at the location on the touch-sensitive surface unit **1304** that corresponds to the first impact effect option: cease to display the impact selection interface (e.g., with the ceasing unit **1312**); enable display of a message region that contains the first message input in the conversation transcript (e.g., with the display enabling unit **1310**); and transmit information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to enable display of a message region that contains the first message input in a conversation transcript that corresponds to the messaging session, and apply the first impact effect option (e.g., with the transmitting unit **1314**).

[0568] In some embodiments, the processing unit **1306** is further configured to: after displaying the preview, detect a third input by a third contact at a location on the touch-sensitive surface unit **1304** that corresponds to the first impact effect option (e.g., with the detecting unit **1308**); and, in response to detecting the third input by the third contact at the location on the touch-sensitive surface unit **1304** that corresponds to the first impact effect option: select the first impact effect option for a message that contains the first message input (e.g., with the selecting unit **1316**); cease to display the impact selection interface (e.g., with the ceasing unit **1312**); and enable display of the conversation transcript of the messaging session and the message-input area that includes a first message input (e.g., with the display enabling unit **1310**); detect a fourth input (e.g., with the detecting unit **1308**); and in response to detecting the fourth input: enable display of a message region that contains the first message input in the conversation transcript (e.g., with the display enabling unit **1310**); and transmit information that causes one or more electronic devices that correspond to the at least one other user included in the messaging session to enable display of a message region that contains the first message input in a conversation transcript that corresponds to the messaging session, and apply the first impact effect option (e.g., with the transmitting unit **1314**).

[0569] In some embodiments, the processing unit **1306** is further configured to: while the message-input area is empty, detect an input that enters text in the message-input area (e.g., with the detecting unit **1308**); and, in response to detecting the input that enters text in the message-input area, enable display of an impact selection affordance (e.g., with the display enabling unit **1310**), wherein activation of the impact selection affordance is configured to cause display of the impact selection interface.

[0570] In some embodiments, the impact selection interface includes a region effect options affordance, which when activated causes display of impact effect options for a message containing the first message input, and a full-screen effect options affordance, which when activated causes display of a preview of one impact effect option that is applied to the entire displayed conversation transcript when a message containing the first message input is displayed in the messaging session.

[0571] In some embodiments, the processing unit **1306** is further configured to: while a preview of an impact effect option that is applied to the entire displayed conversation transcript is displayed, detect an input that activates display of a preview of another impact effect option that is applied to the entire displayed conversation transcript (e.g., with the detecting unit **1308**); and, in response to detecting the input that activates display of the preview of another impact effect option that is applied to the entire displayed conversation transcript, enable display of the preview of the second impact effect option that is applied to the entire displayed conversation transcript (e.g., with the display enabling unit **1310**).

[0572] In some embodiments, the processing unit **1306** is further configured to: while displaying the impact selection interface, detect an input by a contact at a location on the touch-sensitive surface unit **1304** that corresponds to a location of a second impact effect option in the plurality of impact effect options (e.g., with the detecting unit **1308**); and, in response to detecting the user input by the contact at the location on the touch-sensitive surface unit **1304** that corresponds to the location of a second impact effect option, enable display of a preview that applies the second impact effect option to the first message input (e.g., with the display enabling unit **1310**).

[0573] In some embodiments, the plurality of impact effect options includes at least one impact effect option that applies an image with an area that is larger than an area of a message region that contains the first message input to the message region that contains the first message input.

[0574] In some embodiments, the plurality of impact effect options includes at least one impact effect option that increases or decreases a size of a message region that contains the first message input relative to a size of the message region that contains the first message input when no impact effect option is selected.

[0575] In some embodiments, the plurality of impact effect options includes at least one impact effect option that is configured to have a message region that contains the first message input interact with other message regions in the displayed conversation transcript when the message region that contains the first message input is displayed.

[0576] In some embodiments, the plurality of impact effect options includes at least one impact effect option that is configured to display an animation when a message region that contains the first message input is displayed in a conversation transcript that corresponds to the messaging session.

[0577] In some embodiments, the plurality of impact effect options includes at least one impact effect option that is configured to display an animation when a message region that contains the first message input is displayed in a conversation transcript that corresponds to the messaging session, wherein the animation concurrently moves the message region that contains the first message input and other message regions in the conversation transcript.

[0578] In some embodiments, the plurality of impact effect options includes at least one impact effect option that is configured to trigger one or more tactile outputs when a message region that contains the first message input is displayed in a conversation transcript that corresponds to the messaging session.

[0579] In some embodiments, the preview that applies the first impact effect option to the first message input repeats periodically.

[0580] In some embodiments, the processing unit **1306** is further configured to: determine whether an electronic device that corresponds to another user in the messaging session is capable of applying the first impact effect option to a message in the messaging session (e.g., with the determining unit **1318**), and, in accordance with a determination that the electronic device that corresponds to another user in the messaging session is not capable of applying the first impact effect option to a message in the messaging session, enable display of a notification on the display unit **1302** of the electronic device of the user about the first impact effect option (e.g., with the display enabling unit **1310**).

[0581] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[0582] The operations described above with reference to FIGS. **12**A-**12**E are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **13**. For example, detection operations **1204** and **1222** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as selection of an object on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally utilizes or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

Concealed Message Interaction

[0583] FIGS. **14**A-**14**B are flow diagrams of a process for interacting with concealed messages, in accordance with some embodiments. More specifically, these figures relate to methods of displaying an interface that includes one or more screen elements to conceal received message text within the message region. In response to input received at a location corresponding to the message region, the received message is at least partially revealed. This allows messages to be transmitted and viewed privately where messages may be viewed in a crowded location, etc. By requiring an additional action to view the message text, inadvertent disclosure of the contents is avoided.

[0584] One or more examples of an electronic device (e.g., portable multifunction device **100** or device **300**) implementing these methods are shown in FIGS. **5**BG-**5**BP and **5**BQ-**5**CA.

[0585] FIGS. **14**A-**14**B are flow diagrams illustrating a method **1400**, performed by an electronic device, sometimes herein called a first electronic device, having one or more processors, memory, a touch-sensitive surface, and a display. In some embodiments, the electronic device includes one or more sensors (e.g., sensors in a touch-screen display or trackpad) configured to detect intensities of contacts on the touch-sensitive surface.

[0586] In accordance with some embodiments, method **1400** includes displaying (**1402**) a messaging user interface (e.g., user interface **5002**, as shown in FIG. **5**BH, of a messaging application) on the display. The messaging user interface includes a conversation transcript (e.g., conversation transcript **5004** in user interface **5002**, FIG. **5**BH) of a messaging session between a user of the electronic device and at least one other user (e.g., a user of another electronic device) including a first other user, and a message region (**5008**, FIG. **5**BH) in the conversation transcript for a message (e.g., message **5126**) received from the first other user, the message region including one or more screen elements (e.g., screen elements **5124**, FIG. **5**BH) that conceal the message received from the first other user.

[0587] In some embodiments, the received message is sent by another device, a user of which has applied an "invisible ink" effect to the message. In some embodiments, that is accomplished using an impact selection interface **5110**, FIG. **5**BG, that includes a plurality of impact effect options (e.g.,

impact effect options **5112-1** through **5112-4**, described above with respect to FIG. **5**AA). In some embodiments, the set of impact effect options includes options that are applied to an individual message region (e.g., "region effect" options) and options that are applied to the entire displayed conversation transcript when a message is initially displayed in the messaging session (e.g., "full-screen effect" options). In some embodiments, the displayed plurality of impact effect options includes an option that conceals the content of a message in the conversation transcript ("invisible ink" option **5112-1**, FIG. **5**AA, indicated in FIG. **5**BG by an empty message region). In some embodiments, the invisible ink option includes an affordance (e.g., send affordance **5118**, FIG. **5**BG) for sending a message (with user-specified message input) with the respective impact effect option. In some embodiments, impact selection interface **5110**, FIG. **5**BG, includes a cancel affordance **5120** for canceling the selection of any impact effect options and returning the messaging application to either a prior user interface of the messaging application or a predefined user interface of the messaging application.

[0588] In some embodiments, the one or more screen elements (**5124**) that conceal the message are (**1404**) moving particles (e.g., displayed images of moving particles). In some embodiments, the device displays an animation that includes moving particles (e.g., virtual sand particles) within the message region to conceal the content of the message.

[0589] In some embodiments, the message region (**5008**, FIG. **5**BH) with the concealed message has (**1406**) a message region outline that is distinct from an outline on message regions in the conversation transcript that do not have concealed messages. In one example, the message region with the concealed message has a dotted line outline, whereas conventional message regions (e.g., message regions that do not have impact effects applied to them, such as the invisible ink effect) in the conversation transcript have solid line outlines.

[0590] Method **1400** further includes detecting (**1408**) a first input by a contact (e.g., a swipe or drag gesture input **5128**-*a*, FIG. **5**BH) at a location on the touch-sensitive surface that corresponds to the message region with the concealed message; and, after detecting the first input by the contact, revealing (**1416**) the concealed message in the message region. For example, as shown in FIGS. **5**BH, **5**BI, **5**BJ and **5**BK, respective portions of the message **5126** are revealed in response to the drag gesture input **5128**-*a*, **5128**-*b*, **5128**-*c*, **5128**-*d* progressing from a first portion of the message region **5008** to another portion of the message region **5008**. Continuing with the example, as shown in FIG. **5**L, when the drag gesture **5128** is completed, or ends, or after the passage of a predefined time, the message in the message region **5008** is again concealed.

[0591] In some embodiments, the first input is a drag gesture (e.g., input **5128**-*a*) by the contact at a location that corresponds to the message region with the concealed message.

[0592] In some embodiments, detecting (**1408**) the first input by the contact includes detecting (**1412**) a drag gesture (e.g., input **5128**-*a*, FIG. **5**BH) by the contact at a location that corresponds to the message region with the concealed message, and method **1400** includes dynamically removing (**1412**) portions of the one or more screen elements that conceal the message, thereby revealing corresponding portions of the message, in accordance with the movement of the contact in the drag gesture. In some embodiments, portions of the one or more screen elements (e.g., screen elements **5124**) are removed that are within a predetermined distance of the contact in the drag gesture. In some embodiments, after a given portion of the message is revealed (e.g., after passage of a predetermined amount of time, such as 0.5, 1, 2, 3, 4, or 5 seconds), the given portion is concealed again (e.g., by applying one or more screen elements that conceal the given portion).

[0593] In some embodiments, the electronic device includes (**1414**) one or more sensors configured to detect intensities of contacts on the touch-sensitive surface, and the first input (e.g., input **5128**-*a*) is a press input (e.g., a light press or a deep press) by the contact at a location that corresponds to the message region with the concealed message.

[0594] In some embodiments, the electronic device includes (**1418**) one or more sensors configured to detect intensities of contacts on the touch-sensitive surface, and detecting the first input by the contact includes detecting an increase in intensity of the contact (e.g., input **5130**-*a*, **5130**-*b*, **5130**-*c*, with increasing intensity, as shown in FIGS. **5**BM, **5**BN and **5**BO) at a location that corresponds to the message region (**5008**, FIG. **5**BM) with the concealed message. In such embodiments, method **1400** includes: dynamically removing portions of the one or more screen elements (**5124**) that conceal the message (e.g., as shown in FIG. **5**BM), thereby revealing corresponding portions of the message, in accordance with the increase in intensity of the contact (e.g., as shown in the sequence of FIGS. **5**BM, **5**BN and **5**BO). In some embodiments, portions of the one or more screen elements (**5124**) are removed that are closest to the contact and then, as the intensity of the contact increases, portions that are farther and farther from the contact are removed, until the entire message is revealed, as shown in the sequence of FIGS. **5**BM, **5**BN and **5**BO. In some embodiments, in accordance with a decrease in intensity of the contact during the input, the device dynamically adds portions of one or more screen elements, thereby concealing corresponding portions of the message, as shown in the progression from FIG. **5**BO to FIG. **5**BP.

[0595] In some embodiments, method **1400** includes, in response to detecting the first input by the contact, displaying (**1420**) an authentication prompt (e.g., text that says "Please enter a fingerprint or passcode" or the like) and/or an authentication interface (e.g., a passcode screen). In such embodiments, method **1400** further includes receiving an authentication input (e.g., receiving a passcode or fingerprint input); in accordance with a determination that the authentication input satisfies authentication criteria, revealing the concealed message in the message region; and in accordance with a determination that the authentication input does not satisfy the authentication criteria, keeping the message in the message region concealed.

[0596] In some embodiments, the device determines whether the user is authorized to see the message, and, in accordance with a determination that the user is authorized to see the message, the message is revealed. In some embodiments, the determination is performed in response to detecting the first user input. In some embodiments, the determination is performed in response to receiving the concealed message. In some embodiments, the determination is performed when a messaging application is loaded or when the messaging application receives focus (e.g., when

a user interface of the messaging application is displayed and is enabled to received user inputs). In some embodiments, the determination is performed when the user provides authentication information to the device (e.g., authentication is performed when the user unlocks the device using a code, password, and/or fingerprint). In some embodiments (e.g., on a device with multiple users) authentication is performed each time a new user provides authentication information.

[0597] In some embodiments, determining whether the user is authorized to reveal the message includes performing a biometric authentication. In some embodiments, authentication is performed when user provides a fingerprint to unlock the device. In some embodiments, user is prompted to provide a fingerprint or passcode when the concealed message is received or when user attempts to access the concealed message.

[0598] In some embodiments, prior to sending a concealed message from a device, the device authenticates the sender (e.g., by checking sender authentication credentials). For example, prior to sending a concealed message (such as a message with an "invisible ink" impact effect option), the sending device checks whether a passcode or fingerprint provided by a user corresponds to an authorized user, such as the primary user of the device. In some embodiments, the sender is prompted to provide a passcode and/or biometric authentication (e.g., a fingerprint) just prior to sending the concealed message (e.g., in response to a user activating a send icon or selecting an option to conceal the message, like an "invisible ink" impact effect option). In some embodiments, if the device authenticates the sender, then the concealed message is sent or is enabled to be sent, whereas if the device does not authenticate the sender, then the concealed message is prevented from being sent.

[0599] In some embodiments, method **1400** includes, after revealing the concealed message in the message region, concealing (**1422**) the message received from the first other user. For example, after a concealed message in message region **5008** has been revealed, as shown in the sequence of FIGS. **5**BH-**5**BK, the message in message region is again concealed, as shown in FIG. **5**BL. In another example, the sequence of FIGS. **5**BQ-**5**BV, show a message being gradually revealed, as shown in FIGS. **5**BQ to **5**BT, and then gradually concealed, as shown in FIGS. **5**BT to **5**BV. In some embodiments, the message is concealed again in response to detecting termination of the first input by the contact. In some embodiments, the message is concealed again after a predetermined time (e.g., 2 seconds, 5 seconds, or a predetermined amount of time that between two and five seconds) has elapsed since the first input by the contact terminates. In some embodiments, the message is concealed again after a predetermined time (e.g., 2 seconds, 5 seconds, or a predetermined amount of time that between two and five seconds) has elapsed since the message was revealed.

[0600] It should be understood that the particular order in which the operations in FIGS. **14**A-**14**B have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1600**, **1800**) are also applicable in an analogous manner to method **1400** described above with respect to FIGS. **14**A-**14**B. For example, the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described above with reference to method **1400** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein. For brevity, these details are not repeated here.

[0601] In accordance with some embodiments, FIG. **15** shows a functional block diagram of an electronic device **1500** configured in accordance with the principles of the invention as described above. The functional blocks of the device may be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the invention. It is understood by persons of skill in the art that the functional blocks described in FIG. **15** may be combined or separated into sub-blocks to implement the principles of the invention as described above. Therefore, the description herein may support any possible combination or separation or further definition of the functional blocks described herein.

[0602] As shown in FIG. **15**, an electronic device **1500** includes a display unit **1502** configured to display a messaging user interface on the display unit **1502**, the messaging user interface including: a conversation transcript of a messaging session between a user of the electronic device and at least one other user, including a first other user, and a message region in the conversation transcript for a message received from the first other user, the message region including one or more screen elements that conceal the message received from the first other user; a touch-sensitive surface unit **1504** configured to detect contacts; and a processing unit **1506** coupled with the display unit **1502** and the touch-sensitive surface unit **1504**. In some embodiments, the processing unit **1506** includes a detecting unit **1508**, a display enabling unit **1510**, a receiving unit **1512**, a revealing unit **1514**, a concealing unit **1516**, a removing unit **1518**, and a deleting unit **1520**.

[0603] The processing unit **1506** is configured to: detect a first input by a contact at a location on the touch-sensitive surface unit **1504** that corresponds to the message region with the concealed message (e.g., with the detecting unit **1508**); and, reveal the concealed message in the message region in response to detecting the first input by the contact (e.g., with the revealing unit **1514**).

[0604] In some embodiments, the one or more screen elements that conceal the message are moving particles.

[0605] In some embodiments, the message region with the concealed message has a message region outline that is distinct from an outline on message regions in the conversation transcript that do not have concealed messages.

[0606] In some embodiments, the processing unit **1506** is further configured to: in response to detecting the first input by the contact, enable display of an authentication prompt and/or an authentication interface (e.g., with the display enabling unit **1510**); receive an authentication input (e.g., with the receiving unit **1512**); in accordance with a determination that the authentication input satisfies authentication criteria, reveal the concealed message in the message region (e.g., with the revealing unit **1514**); and in accordance with a determination that the authentication input does not

satisfy the authentication criteria, keep the message in the message region concealed (e.g., with the concealing unit **1516**).

[0607] In some embodiments, the first input is a drag gesture by the contact at a location that corresponds to the message region with the concealed message.

[0608] In some embodiments, detecting the first input by the contact includes detecting a drag gesture by the contact at a location that corresponds to the message region with the concealed message, and the processing unit **1506** is further configured to: dynamically remove portions of the one or more screen elements that conceal the message (e.g., with the removing unit **1518**), thereby revealing corresponding portions of the message, in accordance with the movement of the contact in the drag gesture.

[0609] In some embodiments, the electronic device includes one or more sensors configured to detect intensities of contacts on the touch-sensitive surface unit **1504**, and the first input is a press input by the contact at a location that corresponds to the message region with the concealed message.

[0610] In some embodiments, the electronic device includes one or more sensors configured to detect intensities of contacts on the touch-sensitive surface unit **1504**, and detecting the first input by the contact includes detecting an increase in intensity of the contact at a location that corresponds to the message region with the concealed message, and the processing unit **1506** is further configured to: dynamically remove portions of the one or more screen elements that conceal the message (e.g., with the removing unit **1518**), thereby revealing corresponding portions of the message, in accordance with the increase in intensity of the contact.

[0611] In some embodiments, the processing unit **1506** is further configured to: after revealing the concealed message in the message region, conceal the message received from the first other user (e.g., with the concealing unit **1516**).

[0612] In some embodiments, the processing unit **1506** is further configured to: after revealing the concealed message in the message region, automatically delete the message received from the first other user from the conversation transcript (e.g., with the deleting unit **1520**).

[0613] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[0614] The operations described above with reference to FIGS. **14**A-**14**B are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **15**. For example, detection operations **1408**, **1412**, and **1414** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as selection of an object on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally utilizes or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

Triggering Enhanced Message Content

[0615] FIGS. **16**A-**16**C are flow diagrams of a process for applying an effect to a messaging user interface when a message includes an enhanced message content trigger, in accordance with some embodiments. More specifically, these figures relates to methods for determining whether a message in a first message region includes an enhanced message content trigger (e.g., a word, phrase, set of emoji, or other content that triggers the effect, or an option selected by the sender). In response to determining that the message includes the enhanced message content trigger, the effect is applied to the messaging user interface. In some embodiments, the effect is applied to at least one message region other than the first message region. In some embodiments, the effect is applied to a chrome of the messaging user interface.

[0616] One or more examples of an electronic device (e.g., portable multifunction device **100** or device **300**) implementing this method are shown in FIGS. **5**CB-**5**CG and **5**CH-**5**CW.

[0617] FIGS. **16**A-**16**C are flow diagrams illustrating a method **1600**, performed by an electronic device, sometimes herein called a first electronic device, having one or more processors, memory, a touch-sensitive surface, and a display. In some embodiments, the electronic device includes one or more sensors (e.g., sensors in a touch-screen display or trackpad) configured to detect intensities of contacts on the touch-sensitive surface.

[0618] In accordance with some embodiments, method **1600** includes displaying (**1602**) a messaging user interface (e.g., user interface **5002**, as shown in FIG. **5**BH, of a messaging application) on the display. The messaging user interface includes a conversation transcript (e.g., conversation transcript **5004** in user interface **5002**, FIG. **5**CF) of a messaging session between a user of the electronic device and at least one other user (e.g., a user of another electronic device) including a first other user. Method **1600** further includes receiving (**1604**) a first message within the messaging session from an electronic device (e.g., a second electronic device) that corresponds to the first other user included in the messaging session; determining (**1606**) whether the first message includes an enhanced message content trigger; in accordance with a determination that the first message includes the enhanced message content trigger: displaying (**1616**) the first message in a first message region in the conversation transcript on the display, and displaying enhanced message content that corresponds to the trigger, wherein the enhanced message content includes content that applies an effect to at least one message region other than the first message region in the conversation transcript (for example as shown in FIG. **5**CF); and, in accordance with a determination that the first message does not include the enhanced message content trigger, displaying (**1642**) the first message in a first message region in the conversation transcript on the display (i.e., without displaying the

enhanced message content that corresponds to the trigger, for example as shown in FIG. **5**CG).

[0619] In some embodiments, the determination (**1606**) whether the first message includes the enhanced message content trigger is performed (**1608**) in response to receiving the first message.

[0620] In some embodiments, determining (**1606**) whether the first message includes an enhanced message content trigger includes determining (**1610**) whether the first message includes predefined text. For example, when the first message includes the words "happy birthday," the device displays enhanced message content that includes balloons, as shown in the sequence of FIGS. **5**CK to **5**CO. In some embodiments, determining whether the first message includes an enhanced message content trigger includes analyzing content of the first message to determine whether the first message includes predefined message content, such as a word, phrase, emoticon, emoticon string, emoji, emoji string, sticker, and/or sticker string.

[0621] In some embodiments, determining (**1606**) whether the first message includes an enhanced message content trigger includes determining (**1612**) whether the first message includes an embedded non-displayed value (e.g., as determined by a display option selected by the sender) that indicates the enhanced message content to be displayed. For example, the sender of the first message (the first other user) selects a full screen effect option to apply to the first message, and an embedded non-displayed value that corresponds to the full screen effect option selected by the sender is sent with the first message.

[0622] In some embodiments, determining (**1606**) whether the first message includes an enhanced message content trigger includes determining (**1614**) whether a time at which the first message was received corresponds to a predetermined time frame. For example, when the first message is received at or within a predetermined time after midnight on January 1, the device displays enhanced message content that includes fireworks and/or text that states "Happy New Year!"

[0623] In some embodiments, the enhanced message content includes (**1618**) content that applies an effect to the entire displayed conversation transcript. For example, the effect applied to the entire conversation transcript may be the animated display of balloons that move past the entire conversation transcript, the animated display of confetti (e.g., as shown in FIGS. **5**CD through **5**CF) that moves past the entire conversation transcript, or the like.

[0624] In some embodiments, applying (**1616**) the effect to at least one message region other than the first message region includes accumulating (**1620**) animated objects (e.g., virtual confetti) on at least one message region other than the first message region. In some embodiments, animated objects accumulate on user interface objects displayed outside the messaging user interface. In some embodiments, animated objects accumulate on a status bar or other portion of the display that is controlled by the operating system of the device.

[0625] In some embodiments, applying (**1616**) the effect to at least one message region other than the first message region includes animating (**1622**) at least one message region other than the first message region. In some embodiments, movement of the other message regions is triggered by movement of the first message region. In some embodiments, other user interface objects displayed outside the messaging user interface are animated.

[0626] In some embodiments, applying (**1616**) the effect to at least one message region other than the first message region includes temporarily fading (**1624**) message regions other than the first message region without fading the first message region, as shown in FIG. **5**CQ (as compared to the FIG. **5**CP).

[0627] In some embodiments, applying (**1616**) the effect to at least one message region other than the first message region includes temporarily ceasing to display (**1626**) message regions other than the first message region while maintaining display of the first message region.

[0628] In some embodiments, displaying (**1616**) the enhanced message content that corresponds to the trigger includes displaying (**1628**) an image (e.g., an animated image) that temporarily replaces the entire messaging user interface. In some other embodiments, displaying (**1616**) the enhanced message content that corresponds to the trigger includes displaying (**1630**) an image (e.g., an animated image) that temporarily replaces the entire messaging user interface, except for the first message region. For example, balloons or confetti would be displayed, replacing the entire messaging user interface, or replacing the entire messaging user interface other than the first message region.

[0629] In some embodiments, applying (**1616**) the effect to at least one message region other than the first message region includes temporarily highlighting (**1632**) the first message region without highlighting message regions other than the first message region. For example, in a "balloons" full screen effect, the first message region would be highlighted while the balloons are displayed, without highlighting (or fading) the other message regions in the displayed conversation transcript.

[0630] In some embodiments, the enhanced message content includes sound (**1634**). For example, in some embodiments, the sound is played in coordination with the displayed enhanced message content.

[0631] In some embodiments, the enhanced message content includes tactile output (**1636**). For example, the tactile output may be haptic effects output in coordination with the displayed enhanced message content.

[0632] In some embodiments, displaying (**1616**) the enhanced message content includes displaying (**1638**) an animation of the first message region. In some embodiments, when displaying the animation, the first message region disappears and subsequently reappears. In some embodiments, the first message region size and/or first message text size changes during the animation.

[0633] In some embodiments, displaying (**1616**) the enhanced message content includes generating and displaying (**1640**) moving virtual objects in response to scrolling of the conversation transcript. For example, this may be implemented by generating and displaying hearts or sparkles coming off of the first message region as the transcript moves.

[0634] In some embodiments, method **1600** includes ceasing (**1644**) to display the enhanced message content that corresponds to the trigger. For example, the ceasing to display the enhanced message content occurs in response to user input, or after the enhanced message content has been displayed for a predetermined period of time.

[0635] It should be understood that the particular order in which the operations in FIGS. **16**A-**16**C have been described

is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1800**) are also applicable in an analogous manner to method **1600** described above with respect to FIGS. **16**A-**16**C. For example, the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described above with reference to method **1600** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein. For brevity, these details are not repeated here.

[0636] In accordance with some embodiments, FIG. **17** shows a functional block diagram of an electronic device **1700** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. **17** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[0637] As shown in FIG. **17**, an electronic device **1700** includes a display unit **1702** configured to display a messaging user interface on the display unit, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, including a first other user; a touch-sensitive surface unit **1704** configured to detect contacts; and a processing unit **1706** coupled to the display unit **1702** and the touch-sensitive surface unit **1704**. In some embodiments, the processing unit includes display enabling unit **1708**, receiving unit **1710**, determining unit **1712**, applying unit **1714**, accumulating unit **1716**, animating unit **1718**, fading unit **1720**, ceasing unit **1722**, highlighting unit **1724**, and generating unit **1726**.

[0638] The processing unit **1706** is configured to: receive a first message within the messaging session from an electronic device that corresponds to the first other user included in the messaging session (e.g., with the receiving unit **1710**) and determine whether the first message includes an enhanced message content trigger (e.g., with the determining unit **1712**). The processing unit **1706** is further configured to, in accordance with a determination that the first message includes the enhanced message content trigger, display the first message in a first message region in the conversation transcript on the display unit **1702** (e.g., with the display enabling unit **1708**) and display enhanced message content that corresponds to the trigger, where the enhanced message content includes content that applies an effect to at least one message region other than the first message region in the conversation transcript (e.g., with the display enabling unit **1708**). The processing unit **1706** is further configured to, in accordance with a determination that the first message does not include the enhanced message content trigger, display the first message in a first message region in the conversation transcript on the display unit **1702** (e.g., with the display enabling unit **1708**).

[0639] In some embodiments, the determination whether the first message includes the enhanced message content trigger is performed in response to receiving the first message (e.g., with the determining unit **1712**).

[0640] In some embodiments, determining whether the first message includes an enhanced message content trigger includes determining whether the first message includes predefined text (e.g., with the determining unit **1712**).

[0641] In some embodiments, determining whether the first message includes an enhanced message content trigger includes determining whether the first message includes an embedded non-displayed value that indicates the enhanced message content to be displayed (e.g., with the determining unit **1712**).

[0642] In some embodiments, determining whether the first message includes an enhanced message content trigger includes determining whether a time at which the first message was received corresponds to a predetermined time frame (e.g., with the determining unit **1712**).

[0643] In some embodiments, the enhanced message content includes content that applies an effect to the entire displayed conversation transcript (e.g., with the applying unit **1714**).

[0644] In some embodiments, applying the effect to at least one message region other than the first message region includes accumulating animated objects on at least one message region other than the first message region (e.g., with the accumulating unit **1716**).

[0645] In some embodiments, applying the effect to at least one message region other than the first message region includes animating at least one message region other than the first message region (e.g., with animating unit **1718**).

[0646] In some embodiments, applying the effect to at least one message region other than the first message region includes temporarily fading message regions other than the first message region without fading the first message region (e.g., with the fading unit **1720**).

[0647] In some embodiments, applying the effect to at least one message region other than the first message region includes temporarily ceasing to display message regions other than the first message region while maintaining display of the first message region (e.g., with the ceasing unit **1722**).

[0648] In some embodiments, displaying the enhanced message content that corresponds to the trigger includes displaying an image that temporarily replaces the entire messaging user interface (e.g., with the display enabling unit **1708**).

[0649] In some embodiments, displaying the enhanced message content that corresponds to the trigger includes displaying an image that temporarily replaces the entire messaging user interface, except for the first message region (e.g., with the display enabling unit **1708**).

[0650] In some embodiments, applying the effect to at least one message region other than the first message region includes temporarily highlighting the first message region without highlighting message regions other than the first message region (e.g., with the highlighting unit **1724**).

[0651] In some embodiments, the enhanced message content includes sound.

[0652] In some embodiments, the enhanced message content includes tactile output.

[0653] In some embodiments, displaying the enhanced message content includes displaying an animation of the first message region (e.g., with the display enabling unit **1708**).

[0654] In some embodiments, displaying the enhanced message content includes generating and displaying moving virtual objects in response to scrolling of the conversation transcript (e.g., with the generating unit **1726** and the display enabling unit **1708**).

[0655] In some embodiments, the processing unit **1706** is further configured to cease to display the enhanced message content that corresponds to the trigger (e.g., with the ceasing unit.

[0656] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[0657] The operations described above with reference to FIGS. **16**A-**16**C are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **17**. For example, display operations **1602**, **1616**, **1618**, **1620**, **1622**, **1624**, **1626**, **1628**, **1630**, **1632**, **1638**, **1640**, **1642**, and **1644**, receiving operation **1604**, determining operations **1606**, **1608**, **1610**, **1612**, and **1614**, audio output operation **1634**, and tactile output operation **1636** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as selection of an object on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally utilizes or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

Detecting and Responding to Combinable Content in Separate Messages

[0658] FIGS. **18**A-**18**C, described in more detail below, relate generally to methods for detecting combinable content in a messaging user interface. More specifically, these figures relate to methods for displaying content corresponding to a predetermined combination when the detected combinable content form the predetermined combination.

[0659] One or more examples of an electronic device (e.g., portable multifunction device **100** or device **300**) implementing this method are shown in FIGS. **5**CX-**5**DC.

[0660] FIGS. **18**A-**18**C are flow diagrams illustrating a method **1800**, performed by an electronic device, sometimes herein called a first electronic device, having one or more processors, memory, a touch-sensitive surface, and a display. In some embodiments, the electronic device includes one or more sensors (e.g., sensors in a touch-screen display or trackpad) configured to detect intensities of contacts on the touch-sensitive surface.

[0661] In accordance with some embodiments, method **1800** includes displaying (**1802**) a messaging user interface (e.g., user interface **5002**, as shown in FIG. **5**BH, of a messaging application) on the display. The messaging user interface includes a conversation transcript (e.g., conversation transcript **5004** in user interface **5002**, FIG. **5**CX) of a messaging session between a user of the electronic device and at least one other user (e.g., a user of another electronic device) including a first other user, and a message input area (e.g., message input area **5100**, FIG. **5**CX).

[0662] Method **1800** further includes receiving (**1804**) a first message (e.g., message **5170**, in message region **5008**, FIG. **5**CX) within the messaging session from an electronic device (e.g., a second electronic device) that corresponds to the first other user included in the messaging session, wherein the first message includes first combinable content (e.g., an emoticon or an image such as an emoji or a sticker), and in response to receiving the first message, displaying (**1812**) the first message in a first message region in the conversation transcript on the display (for example, as shown in FIG. **5**CX). In some embodiments, the combinable content includes (**1806**) an emoticon. In some embodiments, the combinable content includes (**1808**) an emoji. In some embodiments, the combinable content includes (**1810**) a sticker.

[0663] Method **1800** continues with receiving (**1814**) input of a second message in the message-input area (e.g., second message **5172** in message input area **5100**, as shown in FIG. **5**CY), and while the second message is displayed in the message-input area, detecting (**1816**) an input (e.g., **5174**, FIG. **5**CY) to send the second message to the messaging session (e.g., detecting a tap gesture on a send icon, **5118**, FIG. **5**CY).

[0664] Further, method **1800** includes, in response (**1818**) to detecting the input to send the second message to the messaging session: in accordance with a determination that the second message contains second combinable content, and the second combinable content and the first combinable content are parts (e.g., complementary parts) of a predefined combination, displaying (**1820**) content that corresponds to the predefined combination in the conversation transcript on the display. For example, the content corresponding to the predefined combination is displayed in a second message region, or an area between message regions having messages from the user of the device and message regions with messages from the at least one other user. In some embodiments, content corresponding to the predefined combination is briefly applied to the entire displayed conversation transcript when the second message is initially displayed in the messaging session.

[0665] Further, in accordance with a determination that the second message does not contain second combinable content that forms a predefined combination with the first combinable content, displaying (**1844**) the second message in a second message region in the conversation transcript on the display (i.e., without displaying content that corresponds to a predefined combination).

[0666] In some embodiments, the determination (**1820**) that the second combinable content and the first combinable content are parts of a predefined combination is performed (**1822**) in response to detecting the input (e.g., **5174**, FIG.

5CY) to send the second message to the messaging session (e.g., in response to detecting a tap gesture on a send icon, **5118**, FIG. **5**CY).

[0667] In some embodiments, or in some circumstances, the first combinable content and the second combinable content that are part of a predefined combination are the same content (**1824**). For example, a first word or emoji for beer in a first message (**5170**, FIG. **5**CZ) and a second, same word or emoji for beer in a second message (**5172**, FIG. **5**CZ) result in display of content (e.g., content **5176**, FIG. **5**DA) that corresponds to the predefined combination, such as an animation of two beer glasses being clicked together (as shown in FIG. **5**DA) and/or display of the word "Cheers!" (as shown in FIG. **5**DA). In some embodiments, the content that corresponds to the predefined combination is displayed in a portion of the messaging user interface (e.g., messaging user interface **5002**) between the first and second messages (e.g., between message regions **5008** for first message **5170** and second message **5172**, FIG. **5**DA). In another example, a first fist emoji in the first message and a second fist emoji in the second message result in display of content that corresponds to the predefined combination, such as an animation of two fists bumping together.

[0668] In some embodiments, or in some circumstances, the first combinable content and the second combinable content that are part of a predefined combination are different content (**1826**). For example, a word or emoji for lightning and a word or emoji for key result in display of content that corresponds to a predefined combination, such as an emoji or sticker representing electricity, such as a light bulb. In another example, an emoji for an apple and the word or symbol (e.g., "π") for the number pi result in display of content that corresponds to a predefined combination, such as an emoji or sticker for an apple pie. In yet another example, the word "Happy" in a first message and the word "Birthday" in a second message result in a display of balloons in a portion of the messaging user interface between the first message and second message or in the entire messaging user interface, for example as shown in FIGS. **5**CB, **5**CC and **5**CJ-**5**CO.

[0669] Optionally, users can define combinations of content that are the aforementioned predefined combinations, and/or they can define the content that corresponds to any such combination. More specifically, in some embodiments, or in some circumstances, respective first combinable content and respective second combinable content that are part of a respective predefined combination are defined (**1828**) by a user of the electronic device. For example, in some embodiments, the predefined combinations are defined by a user of the device or by users in a messaging session. Similarly, in some embodiments, or in some circumstances, the content that corresponds to the predefined combination is defined by a user of the device (**1830**). For example, in some embodiments, the content that corresponds to the predefined combination is defined by a user of the device or by users in a messaging session.

[0670] A variety of content can be included in or used as the content that corresponds to the predefined combination. More specifically, in some embodiments, the content that corresponds to the predefined combination includes animated content (**1832**), examples of which are balloons or confetti that move through the messaging user interface or a portion of the messaging user interface. In some embodiments, the content that corresponds to the predefined combination includes audio content (**1834**), such as music, or one or more tones, or recorded or synthesized speech. In some embodiments, the content that corresponds to the predefined combination includes haptic content (**1836**), such as a vibration or vibration pattern. Thus, in some embodiments, the content that corresponds to the predefined combination includes animated content, audio content and/or haptic content (**1838**).

[0671] Further, in some embodiments, the content that corresponds to the predefined combination includes (**1840**) automatically generated message text. For example, in the above described example, with a first word or emoji for beer in a first message (**5170**, FIG. **5**CZ) and a second, same word or emoji for beer in a second message (**5172**, FIG. **5**CZ), the first electronic device automatically generates message text, such as "Cheers!", in a message region.

[0672] In some embodiments, the content that corresponds to the predefined combination includes (**1842**) content that is applied to the entire displayed conversation transcript when the second message is initially displayed in the messaging session. For example, content in a "full-screen moment," such as displaying a "fireworks" full screen effect in response to a first message, "Happy," and a second message, "New Year," as shown in FIGS. **5**CR-**5**CT, or displaying a "balloons" full screen effect in response to a first message, "Happy," and a second message, "Birthday," as shown in FIGS. **5**CJ-**5**CO.

[0673] In some embodiments, a predefined combination includes first combinable content, second combinable content, and third combinable content (e.g., three complementary parts). For example, when messages with first combinable content (e.g., a foot) and second combinable content (e.g., an Italian flag) are displayed in a conversation transcript, in response to an input to send a third message, in accordance with a determination that the third message contains third combinable content (e.g., a soccer ball), content that corresponds to the predefined combination is displayed in the conversation transcript on the display.

[0674] It should be understood that the particular order in which the operations in FIGS. **18**A-**18**C have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**) are also applicable in an analogous manner to method **1800** described above with respect to FIGS. **18**A-**18**C. For example, the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described above with reference to method **1800** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein. For brevity, these details are not repeated here.

[0675] In accordance with some embodiments, FIG. **19** shows a functional block diagram of an electronic device **1900** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described embodiments. It

is understood by persons of skill in the art that the functional blocks described in FIG. **19** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[0676] As shown in FIG. **19**, an electronic device **1900** includes a display unit **1902** configured to display a messaging user interface on the display unit, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, including a first other user, and a message input area; a touch-sensitive surface unit **1904** configured to detect contacts; and a processing unit **1906** coupled to the display unit **1902** and the touch-sensitive surface unit **1904**. In some embodiments, the processing unit includes display enabling unit **1908**, receiving unit **1910**, detecting unit **1912**, and applying unit **1914**,

[0677] The processing unit **1906** is configured to: receive a first message within the messaging session from an electronic device that corresponds to the first other user included in the messaging session, where the first message includes first combinable content (e.g., with the receiving unit **1910**) and in response to receiving the first message, display the first message in a first message region in the conversation transcript on the display unit **1902** (e.g., with the display enabling unit **1908**). Processing unit **1906** is further configured to receive input of a second message in the message-input area (e.g., with the receiving unit **1910**). Processing unit **1906** is further configured to, while the second message is displayed in the message-input area, detect an input to send the second message to the messaging session (e.g., with the detecting unit **1912**) and, in response to detecting the input to send the second message to the messaging session: in accordance with a determination that the second message contains second combinable content and the second combinable content and the first combinable content are parts of a predefined combination, display content that corresponds to the predefined combination in the conversation transcript on the display unit **1902** (e.g., with the display enabling unit **1908**) and, in accordance with a determination that the second message does not contain second combinable content that forms a predefined combination with the first combinable content, display the second message in a second message region in the conversation transcript on the display unit **1902** (e.g., with the display enabling unit **1908**).

[0678] In some embodiments, the determination that the second combinable content and the first combinable content are parts of a predefined combination is performed in response to detecting the input to send the second message to the messaging session (e.g., with the detecting unit **1912**).

[0679] In some embodiments, the combinable content includes an emoticon.

[0680] In some embodiments, the combinable content includes an emoji.

[0681] In some embodiments, the combinable content includes a sticker.

[0682] In some embodiments, the first combinable content and the second combinable content that are part of a predefined combination are the same content.

[0683] In some embodiments, the first combinable content and the second combinable content that are part of a predefined combination are different content.

[0684] In some embodiments, respective first combinable content and respective second combinable content that are part of a respective predefined combination are defined by a user of the electronic device **1900**.

[0685] In some embodiments, for a respective predefined combination, the content that corresponds to the predefined combination is defined by a user of the device **1900**.

[0686] In some embodiments, the content that corresponds to the predefined combination includes animated content.

[0687] In some embodiments, the content that corresponds to the predefined combination includes audio content.

[0688] In some embodiments, the content that corresponds to the predefined combination includes haptic content.

[0689] In some embodiments, the content that corresponds to the predefined combination includes animated content, audio content and/or haptic content.

[0690] In some embodiments, the content that corresponds to the predefined combination includes automatically generated message text.

[0691] In some embodiments, the content that corresponds to the predefined combination includes content that is applied to the entire displayed conversation transcript when the second message is initially displayed in the messaging session (e.g., with the applying unit **1914**).

[0692] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[0693] The operations described above with reference to FIGS. **18**A-**18**C are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **19**. For example, displaying operations **1802**, **1812**, **1822**, **1824**, **1826**, **1828**, **1830**, **1832**, **1834**, **1836**, **1838**, **1840**, **1842**, and **1844**, receiving operations **1804**, **1806**, **1808**, **1810**, and **1814**, detecting operation **1816**, and applying operation **1842** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as selection of an object on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally utilizes or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

Presenting Synchronized Media Content

[0694] FIGS. **20**A-**20**P illustrate example user interfaces for presenting synchronized media content in a messaging application, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the

processes described below. Although some of the examples which follow will be given with reference to inputs on a touch-screen display (where the touch-sensitive surface and the display are combined), in some embodiments, the device detects inputs on a touch-sensitive surface **451** that is separate from the display **450**, as shown in FIG. **4**B. For convenience of explanation, the embodiments described below will be discussed with reference to operations performed on a device with a touch-sensitive display system **112**. In such embodiments, a focus selector is, optionally: a respective finger or stylus contact, a representative point corresponding to a finger or stylus contact (e.g., a centroid of a respective contact or a point associated with a respective contact), or a centroid of two or more contacts detected on the touch-sensitive display system **112**. However, analogous operations are, optionally, performed on a device with a display **450** and a separate touch-sensitive surface **451** in response to detecting the contacts on the touch-sensitive surface **451** while displaying the user interfaces discussed below, along with a focus selector.

[0695] As shown in FIG. **20**A, a first user of a first electronic device (e.g., device **100**) receives an invitation from a second user of a second electronic device to synchronously watch a media item. As shown in FIG. **20**A, the first user receives a message that is displayed within a messaging user interface (i.e., a user interface that is displayed within a messaging application) that informs the first user that the second user would like to watch a "trailer for movie 123" together. In some embodiments, the first user accepts the invitation by tapping (e.g., tap **2001**) within a message region (e.g., the message bubble **2002** shown in FIG. **20**A) that includes the invitation and also optionally includes a representation (e.g., a thumbnail view) of the media item. In some embodiments or circumstances, a message region is a message bubble, platter, or other container for a message in a conversation transcript of a messaging session.

[0696] As shown in FIG. **20**B, in response to detecting that the first user has accepted the invitation (e.g., detecting the tap gesture **2001** over the representation of the media item), the electronic device **100** provides the user with an animation that indicates that the media item will be displayed at a larger size within the messaging user interface. For example, the representation of the media item increases in size within the message user interface and begins to expand so that at least a portion of the representation is displayed outside of the message region (e.g., the representation of the media item is shown as increasing in size and expanding outside of the message bubble **2002**, FIG. **20**B).

[0697] The animation continues with the representation continuing to increase in size and, as shown in FIG. **20**C, the representation of the media item is eventually shown as occupying a different part of the messaging user interface (e.g., a central region of the messaging user interface). In some embodiments, the initial location of the representation of the media item after the animation completes is referred to as the chronological position of the media item (i.e., the media item is shown in a chronological order relative to other messages that were received either before or after initiation of synchronized viewing of the media item). For example, as shown in FIG. **20**D, the representation of the media item is shown at its chronological position, which is between a position representing a message that was received before initiation of synchronized viewing of the media item (e.g., position for message region **2010**) and between a position for a message that was received after initiation of synchronized viewing of the media item (e.g., position for message region **2012**). Additionally, chronological positions of the media item and messages received before/after initiation of synchronized viewing are maintained as new messages are received (as shown in FIG. **20**E, receiving/displaying a new message moves content in the conversation transcript in a substantially vertical direction while maintaining respective chronological positions for each respective message region). As discussed in more detail below, in some circumstances, the media item also moves to a fixed position at a top portion of the messaging user interface (as shown in FIG. **20**H).

[0698] In some embodiments, the representation of the media item includes information that indicates that the media item is being viewed in synchrony with other users (e.g., "Synchronized Viewing of Trailer for Movie 123"), includes an affordance that, when selected, causes the messaging application to begin synchronized viewing of the media item (and causes remote devices associated with other users within the messaging session to concurrently begin synchronized viewing as well) (e.g., the play button affordance shown within the representation of the media item), and a play-head and progress bar. In some embodiments, after (and/or in conjunction with the animation discussed above) the representation of the media item is displayed in the central region, the message region that included the invitation from the second user is no longer displayed and an indication that the first user has accepted the second user's invitation is instead displayed. For example, the indication that the first user has accepted includes a textual description of "You accepted Alex's invitation to watch trailer for Movie 123" (as shown in FIG. **20**D).

[0699] As shown in FIG. **20**D, the users in the messaging session (e.g., the first and the second user) are able to continue exchanging messages while the representation of the media item is displayed (before and/or during initiation of playback of the media item). For example, the second user sends a message of "Playing the trailer now!" and that message moves all of the content within the conversation transcript in a substantially vertical (e.g., upward) direction. In this way, users are able to fluidly continue conversing before synchronized playback of the media item begins.

[0700] In response to receiving a request from any of the users in the messaging session to begin synchronized viewing of the media item (e.g., one of the users hits the play affordance shown with the representation of the media item, FIG. **20**D), the device (or the messaging application) initiates playing of content corresponding to the media item. As shown in FIG. **20**E, playing of content corresponding to the media item begins and users are able to continue exchanging messages during synchronized playback of the media item (e.g., the first user sends a message of "This is cool!" and that message moves the content within the conversation transcript in a substantially vertical direction, while continuing to play the content corresponding to the media item).

[0701] As shown in FIG. **20**F-**20**G, the users are able to continue exchanging messages while the synchronized viewing of the media item continues. In some embodiments, the newly exchanged messages continue to move content in the conversation transcript in a substantially vertical direction (while still maintaining a chronological ordering of each respective message region).

[0702] As shown in FIG. **20**H, once the representation of the media item is within a predetermined distance of a top portion of the messaging user interface (e.g., 1 px, 2 px, 3 px, 4 px, 5 px, or some other predetermined distance), the representation of the media item is then displayed at a fixed position within the messaging user interface (in other words, the representation of the media item is not displayed at its chronological position). In some embodiments, a representation of the media item does remain at the chronological position and the representation is also displayed at the fixed position (i.e., representations are shown in two places).

[0703] As shown in FIG. **20**I, while playing content corresponding to the media item and while displaying the representation of the media item at the fixed position, users are able to continue exchanging messages and those messages cause earlier messages to move underneath the playing content corresponding to the media item (in order to avoid obscuring viewing of the playing content). In some embodiments, users are also able to manipulate (e.g., fast-forward, rewind, pause, and the like) the playing content corresponding to the media item and those manipulations are communicated to devices for other users in the messaging session in order to continue synchronized viewing of the media item for all of the users in the messaging session. For example, as shown in FIG. **20**I, the first user is able to drag a play-head (e.g., gesture **2003**) to fast-forward the playing content and the fast-forward command is also communicated to devices for other users in the messaging session (techniques for transmitting this information are discussed in detail below in reference to FIGS. **21**A-**21**C). In some embodiments, the messaging user interface is also updated to indicate that the first user performed a respective manipulation of the playing content (e.g., "You fast-forwarded trailer for movie 123," FIGS. **20**J-**20**K).

[0704] As another example of user manipulations of the playing content, after the second user manipulates the playing content by providing a rewind command, the playing content is shown in the messaging user interface at the first electronic device in accordance with the second user's rewind command (e.g., as shown between FIGS. **20**J-**20**K, the play-head for the playing content has moved backwards due to the second user's rewind command). In some embodiments, the messaging user interface is also updated to indicate that the second user performed a respective manipulation of the playing content (e.g., "Alex rewound trailer for movie 123," FIG. **20**K).

[0705] As is also shown in FIG. **20**K, the first user is able to scroll the conversation transcript while the synchronized viewing of the media item is ongoing. For example, the first user provides gesture **2022** that, when detected, causes the device to scroll the conversation transcript in a substantially downward direction (FIG. **20**K). While scrolling the conversation transcript (and the content included therein), the device determines whether the playing content corresponding to the media item should be moved back to its chronological position (and no longer displayed at the fixed position). In accordance with a determination that the playing content corresponding to the media item should be moved back to its chronological position (e.g., chronological position is scrolled to within a predetermined distance of the fixed position, as discussed below in reference to FIGS. **21**A-**21**C), the playing content corresponding to the media item is moved to the chronological position and is no longer displayed at the fixed position. As shown in FIG. **20**L, the first user is also able to scroll in a substantially upward direction (e.g., by providing gesture **2024**) and, in response, the playing content corresponding to the media item moves back to the fixed position at an appropriate time (e.g., as shown in FIG. **20**M after scrolling in an upward direction, the playing content corresponding to the media item moves back to the fixed position). In this way, users are able to intuitively scroll through the conversation transcript without interrupting their viewing of the media item.

[0706] As shown in FIGS. **20**N-**20**O, an end of the playing content corresponding to the media item is detected (e.g., playing of the media item finishes, one of the users exits the messaging application, or one of the users provides a stop command) and, in response, the device provides an animation of the representation of the media item shrinking in size and returning to its chronological position within the conversation transcript (as shown in FIG. **20**O for animation **2050**, the representation shrinks in size and beings to move back towards its chronological position, as shown in FIG. **20**P).

[0707] FIGS. **21**A-**21**C are flow diagrams illustrating a method **2100** of presenting synchronized media content in a messaging application, in accordance with some embodiments. The method **2100** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display and a touch-sensitive surface. In some embodiments, the display is a touch screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **2100** are, optionally, combined and/or the order of some operations is, optionally, changed.

[0708] As described below, the method **2100** provides an intuitive way to present synchronized media content in a messaging application. The method produces more efficient human-machine interfaces by allowing users to easily view media content in a synchronized fashion directly within a messaging application (and without having to be co-located with another user viewing the media content and without having to use very inefficient techniques to enable synchronized viewing). For battery-operated devices, the method increases user satisfaction with their devices, conserves power (e.g., by requiring few inputs to enable synchronized viewing of media content), and increases the time between battery charges. Furthermore, allowing users to easily view media content in a synchronized fashion directly within a messaging application enhances the operability of the device and makes the user-device interface (e.g., in the messaging application) more efficient (e.g., by allowing for efficient synchronized viewing of media items).

[0709] As shown in FIG. **21**A, the device displays (**2102**), on the display, a messaging user interface, the messaging user interface including a conversation transcript of a messaging session between a user of the first electronic device and at least one other user. The conversation transcript includes (**2104**) a representation of a media item that is displayed at a chronological position within the conversation transcript. For example, the representation of the media item is an icon that shows a still image from the media item (such as a representation shown in FIG. **20**A within message container **2002**), or a link to the media item that when selected causes the device to display the icon that shows the still image from the media item (such as a link displayed within the message container **2002** that indicates "click here

to being synchronized viewing" or "click here to accept synchronized viewing invitation"). The messaging session is configured (**2104**) to allow synchronized viewing of the media item by the user at the first electronic device and the at least one other user at a second electronic device that is distinct (and remotely located) from the first electronic device. In some embodiments, the media item is specially configured to allow synchronized viewing. In some embodiments, the messaging session or a messaging application associated with the messaging session (and displaying the messaging user interface) is able to take any media item and allow synchronized viewing of the media item using a variety of synchronized viewing techniques that are discussed in more detail below.

[0710] In some embodiments, the representation of the media item is added to the conversation transcript by the user (**2106**). In some embodiments, the representation of the media item is added to the conversation transcript by the at least one other user (**2108**). In this way, any user in the messaging session is able to initiate synchronized viewing of the media item. Additional details regarding facilitating/transmitting messages between the user and the at least one other user in order to enable synchronous viewing of the media item are provided below.

[0711] In some embodiments, the device receives (**2110**) a first request for synchronized viewing of the media item within the messaging user interface (e.g., the first request is from the user or the at least one other user). In some embodiments, receiving the first request includes receiving a URL for the media item and when a respective user (e.g., the user or the at least one other user or some other user associated with the messaging session) activates a play button for the media item, the device sends a play command, via a messaging network (cellular, WiFi) to the second electronic device and an indication of a current time at the first electronic device. In some embodiments, if the at least one other user hits the play button first, then the first electronic device receives the play command and the indication of a current time at the second electronic device.

[0712] In response to receiving the first request, the device initiates playing (**2110**) of content corresponding to the media item while the representation of the media item is displayed at the chronological position within the conversation transcript. In some embodiments, the first request is received (**2112**) via the second electronic device (e.g., a request by the at least one other user at the second electronic device to synchronously view the media item is routed through a server or sent directly to the first electronic device). In some embodiments, the first request is received (**2114**) via the user at the first electronic device (e.g., the user selects the play button shown in the representation of the media item illustrated in FIG. **20**C). In some embodiments, playing includes playing the content in a synchronized fashion at both the electronic device and the second electronic device for synchronized viewing by the user and the at least one other user, respectively. In some embodiments, initiation of playback of the content corresponding to the media item is delayed when the user hits play (e.g., by 2 seconds to account for time it takes to send a message to the second electronic device and begin playback at the second electronic device). In other embodiments, sending/receiving the URL includes sending/receiving information to push playback on the second device ahead in time (e.g., jump by 1-2 seconds to sync playback on the devices).

[0713] Turning now to FIG. **21**B, the device (before displaying the playing content corresponding to the media item at the fixed position), displays (**2116**) messages exchanged between the user and the at least one other user within the messaging user interface, including displaying the messages under the playing content corresponding to the media item (as shown in FIGS. **20**D-**20**G, exchanged messages are displayed underneath the playing content and a position within the messaging user interface of the playing content corresponding to the media item is moved towards a top portion of the messaging user interface). In other words, displaying the messages includes moving the chronological position of the playing content towards the top portion of the messaging user interface, because as new messages are received and displayed in the messaging user interface, earlier messages continue to move (or be pushed) towards the top portion. In some embodiments, relative vertical positioning of messages with respect to other messages corresponds to an earlier chronological position.

[0714] In accordance with a determination that the chronological position is within a predetermined distance of the top portion of the messaging user interface, the device displays (**2118**) the playing content corresponding to the media item at the fixed position within the messaging user interface (e.g., a synchronized content position that is defined relative to the top portion of the messaging user interface, such that the content item is pinned at the top portion of the messaging user interface while exchanged messages appear below). As shown in FIGS. **20**H-**20**K, messages exchanged between the users continue to be displayed beneath the playing content while it is located at the fixed/pinned position.

[0715] After initiating playing of the content corresponding to the media item (and while continuing to play the content corresponding to the media item), the device displays (**2120**) (e.g., moves) the playing content corresponding to the media item at the fixed position within the messaging user interface that is different than the chronological position. In some embodiments, the content corresponding to the media item (or the representation of the media item) floats up to the fixed position sometime after initiating playback of the content corresponding to the media item. In some embodiments, the representation of the media item remains in the chronological position while the content is playing and messages exchanged between the user and the at least one other user push the chronological position towards a top portion of the messaging user interface. In some embodiments, in accordance with a determination that the content corresponding to the media item has moved to within a predetermined distance of the top portion, the electronic device displays the content corresponding to the media item at the fixed position (as also discussed above). In some embodiments, the representation of the media item is displayed at the chronological position (above the fold) while the playing content corresponding to the media item is displayed at the fixed position (in other words, representations of the media item are displayed at the fixed position and at the chronological position). By displaying the representation of the media item at the fixed position, users are able to continue viewing the media item in a substantially synchronous fashion with other users without having to interrupt their conversation. Therefore, users are able to quickly and conveniently watch a media item together and continue conversing normally, thereby enhancing operability of the device **100** and producing more efficient user-

device interfaces (e.g., users need not switch back and forth between a messaging application and some other media-sharing or watching application).

[0716] In some embodiments, while displaying the playing content corresponding to the media item, users are able to manipulate the playing content (**2122**) (e.g., fast-forward, rewind, pause) and users are also able to scroll the conversation transcript (**2126**).

[0717] With respect to operation **2122**, the device receives an indication that the at least one other user has manipulated the playing content (e.g., issued a fast-forward, rewind, or pause command) corresponding to the media item. In response to receiving the indication, the device modifies presentation of the playing content corresponding to the media item at the electronic device in accordance with the manipulations from the at least one other user (e.g., as shown in FIGS. **20**I-**20**J (fast-forward) and FIGS. **20**J-**20**K (rewind)). In this way, users are able to continue synchronous viewing of the media item while also being able to manipulate a position of the content corresponding to the media item and other users will seamlessly be provided with those manipulations as well.

[0718] In some embodiments, the manipulations include one or more of fast-forwarding the playing content, rewinding the playing content, and/or pausing the playing content. For example, the indication indicates that the at least one other user fast-forwarded the playing content and, in response to receiving the indication of the fast-forwarding, the presentation of the playing content is modified in accordance with the fast-forwarding (e.g., both the user's device and another device associated with the at least one other user both display the fast-forwarding in a substantially synchronous fashion). As another example, the indication indicates that the at least one other user rewound the playing content and, in response, the presentation of the playing content is modified in accordance with the rewinding. As one more example, the indication indicates that the at least one other user paused the playing content and, in response, the presentation of the playing content is paused.

[0719] As to operation **2126**, while displaying the playing content corresponding to the media item at the fixed position, the device detects an input (e.g., a drag gesture moving the conversation transcript in a downward direction, as shown for gesture **2022** in FIG. **20**K). In response to detecting the input, the device scrolls the conversation transcript (as shown in FIG. **20**L, the conversation transcript is scrolled in a downward direction in response to the gesture **2022**). While scrolling the conversation transcript, in accordance with a determination that the chronological position of the media item is within a predetermined distance of the fixed position (e.g., within 1 px, 2 px, 3 px, 4 px, or 5 px, or some other predefined distance), the device moves the playing content to the chronological position while continuing to play the playing content (as shown in FIG. **20**L, the representation of the media item is now shown at the chronological position in response to the scroll gesture **2022** and is no longer displayed at the fixed position. In this way, if the user scrolls far enough back in the conversation, then the playing content moves back to the chronological position instead of remaining at the fixed position, thus ensuring a smooth viewing experience of the content corresponding to the media item.

[0720] Turning now to FIG. **21**C, while displaying the playing content corresponding to the media item at the fixed position, the device: displays (**2128**) messages exchanged between the user and the at least one other user below the playing content corresponding to the media item (and passing behind the playing content corresponding to the media item, so that viewing of the media item is uninterrupted and so that the users are able to continue exchanging messages while synchronously viewing the media item).

[0721] While displaying the playing content corresponding to the media item at the fixed position, the device also detects (**2128**) an end of the content corresponding to the media item. In response to detecting the end of the content corresponding to the media item, the device ceases to display the content corresponding to the media item at the fixed position. In some embodiments, ceasing to display includes presenting an animation of the media item (or the representation of the media item) returning to the chronological position within the conversation transcript (e.g., the animation **2050** illustrated in FIGS. **20**N-**20**P). This animation effect provides users with a visual reminder of the chronological position for the media item, since many messages may have been exchanged and the user may no longer be able to locate the media item (or the representation thereof) within the conversation transcript. Providing this animation effect enhances the operability of the device **100** and makes the user-device interface more efficient (e.g., by ensuring that the user knows where the media is located within the conversation transcript, so that they can easily and efficiently locate the media item at a later point in time).

[0722] In some embodiments, detecting the end of the playing of the content corresponds (**2130**) to receiving a request to end playing of the content (e.g., the request is received from any user associated with the messaging session, such as when a user hits a stop button or when a user leaves the messaging application). In some embodiments, detecting the end of the playing of the content corresponds (**2132**) to reaching an end of the playing of the content (e.g., the playing content concludes after reaching an end point).

[0723] In some embodiments, the synchronous viewing of the content corresponding to the media item described above is facilitated by sending play-head information over a message channel (e.g., a meta-message) whenever either user (or any user in a messaging session that includes more than two users) manipulates a position of the playing content (as discussed above with respect to fast-forwarding, rewinding, and/or pausing). In some embodiments, time synchronization protocols are used to send messages back and forth whenever the play-head is manipulated and/or to verify that the content is being viewed synchronously (e.g., if a particular user's network connection slows down, this can be detected and used to also slow down viewing at an electronic device for a different user (who is part of the messaging session in which synchronized viewing of a media item is taking place) in order to ensure that viewing remains synchronous). In some embodiments, if a touch event is detected (at an electronic device associated with a user who is part of a messaging session that includes synchronized viewing of a media item) that manipulates the play-head of the media item, the electronic device actively tracks the touch event and keeps sending messages (including play-head information) to the second electronic device (or to a plurality of devices, including the second electronic device) in order to ensure that synchronized viewing continues with interruption.

[0724] The embodiments and techniques for enabling synchronous viewing of media items in a messaging application may also be applied to asynchronous games that are played within a messaging application (including checkers, chess, connect four, gin, tic-tac-toe, etc.), a shared shopping list (e.g., both users are able to synchronously view a shopping list within a messaging application and can each individually check off items while they are shopping at the same or remotely-located businesses), a shared to-do list, and collaborative drawings.

[0725] It should be understood that the particular order in which the operations in FIGS. **21**A-**21**C have been described is merely one example and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein are also applicable in an analogous manner to method **2100** described above. For example, the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described above with reference to method **2100** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein. For brevity, these details are not repeated here.

[0726] In accordance with some embodiments, FIG. **22** shows a functional block diagram of an electronic device **2200** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, firmware, or a combination thereof to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. **22** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[0727] As shown in FIG. **22**, an electronic device **2200** includes a display unit **2202** configured to display a user interface, a touch-sensitive surface unit **2204** configured to receive contacts, one or more sensor units **2206** for detecting intensities of contacts on the touch-sensitive surface unit **2204**; and a processing unit **2208** coupled with the display unit **2202**, the touch-sensitive surface unit **2204** and the one or more sensor units **2206**. In some embodiments, the processing unit **2208** includes a displaying unit **2210**, a synchronized viewing request receiving unit **2212**, a play initiation unit **2214**, an indication receiving unit **2216**, a detecting unit **2218**, and/or presentation modification unit **2220**, and/or a scrolling unit **2222**.

[0728] The processing unit **2208** is configured to display (e.g., with the displaying unit **2210**), on the display (e.g., the display unit **2202**), a messaging user interface, the messaging user interface including a conversation transcript of a messaging session between a user of the first electronic device and at least one other user. In some embodiments, the conversation transcript includes a representation of a media item that is displayed at a chronological position within the conversation transcript, and the messaging session is configured to allow synchronized viewing of the media item by the user at the first electronic device and the at least one other user at a second electronic device that is distinct from the first electronic device. The processing unit is also configured to: receive a first request for synchronized viewing of the media item within the messaging user interface (e.g., with the synchronized viewing request receiving unit **2212**) and, in response to receiving the first request, initiate playing of content corresponding to the media item (e.g., with the play initiation unit **2214**) while the representation of the media item is displayed at the chronological position within the conversation transcript. After initiating playing of the content corresponding to the media item, display the playing content corresponding to the media item at a fixed position (e.g., with the displaying unit **2210** in conjunction with the display unit **2202**) within the messaging user interface that is different than the chronological position. While displaying the playing content corresponding to the media item at the fixed position: (i) display (e.g., with the displaying unit **2210** in conjunction with the display unit **2202**) messages exchanged between the user and the at least one other user below the playing content corresponding to the media item and (ii) detect an end of the content corresponding to the media item (e.g., with the detecting unit **2218**). In response to detecting the end of the content corresponding to the media item, cease to display the content corresponding to the media item at the fixed position (e.g., with the displaying unit **2210** in conjunction with the display unit **2202**).

[0729] In accordance with some embodiments of the electronic device **2200**, the processing unit is further configured to: receive an indication that the at least one other user has manipulated the playing content corresponding to the media item (e.g., with the indication receiving unit **2216**); and, in response to receiving the indication, modify presentation of the playing content corresponding to the media item at the electronic device in accordance with the manipulations from the at least one other user (e.g., with the presentation modification unit **2220**).

[0730] In accordance with some embodiments of the electronic device **2200**, the manipulations include fast-forwarding the playing content, rewinding the playing content, and/or pausing the playing content.

[0731] In accordance with some embodiments of the electronic device **2200**, the representation of the media item is added to the conversation transcript by the user.

[0732] In accordance with some embodiments of the electronic device **2200**, the representation of the media item is added to the conversation transcript by the at least one other user.

[0733] In accordance with some embodiments of the electronic device **2200**, the first request is received via the second electronic device.

[0734] In accordance with some embodiments of the electronic device **2200**, the first request is received via the user at the first electronic device.

[0735] In accordance with some embodiments of the electronic device **2200**, the processing unit is further configured to: before displaying the playing content corresponding to the media item at the fixed position: (i) display (e.g., with the displaying unit **2210** in conjunction with the display unit **2202**) messages exchanged between the user and the at least one other user within the messaging user interface, and displaying the messages includes displaying the messages under the playing content corresponding to the media item,

such that a position within the messaging user interface of the playing content corresponding to the media item moves towards a top portion of the messaging user interface; and (ii) in accordance with a determination that the chronological position is within a predetermined distance of the top portion of the messaging user interface, display the playing content corresponding to the media item at the fixed position within the messaging user interface.

[0736] In accordance with some embodiments of the electronic device **2200**, the processing unit is further configured to: while displaying the playing content corresponding to the media item at the fixed position, detect an input; in response to detecting the input, scroll the conversation transcript (e.g., with the scrolling unit **2222**); and while scrolling the conversation transcript, in accordance with a determination that the chronological position of the media item is within a predetermined distance of the fixed position, move the playing content to the chronological position while continuing to play the playing content (e.g., with the displaying unit in conjunction with the display unit **2202**).

[0737] In accordance with some embodiments of the electronic device **2200**, detecting the end of the playing of the content corresponds to receiving a request to end playing of the content.

[0738] In accordance with some embodiments of the electronic device **2200**, detecting the end of the playing of the content corresponds to reaching an end of the playing of the content

[0739] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[0740] The operations described above with reference to FIGS. **21**A-**21**C are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **22**. For example, one or more of the operations are optionally implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

Incorporate Handwritten Inputs in Messages

[0741] FIGS. **23**A-**23**AE illustrate example user interfaces for providing and presenting user-specific handwritten inputs in a messaging application, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below. Although some of the examples which follow will be given with reference to inputs on a touch-screen display (where the touch-sensitive surface and the display are combined), in some embodiments, the device detects inputs on a touch-sensitive surface **451** that is separate from the display **450**, as shown in FIG. **4**B. For convenience of explanation, the embodiments described below will be discussed with reference to operations performed on a device with a touch-sensitive display system **112**. In such embodiments, a focus selector is, optionally: a respective finger or stylus contact, a representative point corresponding to a finger or stylus contact (e.g., a centroid of a respective contact or a point associated with a respective contact), or a centroid of two or more contacts detected on the touch-sensitive display system **112**. However, analogous operations are, optionally, performed on a device with a display **450** and a separate touch-sensitive surface **451** in response to detecting the contacts on the touch-sensitive surface **451** while displaying the user interfaces discussed below, along with a focus selector.

[0742] As shown in FIG. **23**A, the device displays a user interface for a messaging application (also referred to herein as a "messaging user interface") and a user of the device is able to activate handwriting features by providing either or both of gestures **2302**A and **2302**B. In some embodiments, in response to the gestures **2302**A and/or **2302**B and while the device is in a portrait orientation, the device displays selectable representations of handwritten inputs (as shown in FIG. **23**B for user interface region **2351**).

[0743] In some embodiments, in response to receiving a selection of one of the selectable representations shown in user interface region **2351** (e.g., in response to input **2304** over a first selectable representation), the device updates message-input region **2303** to include handwritten text that is associated with the first selectable representation (e.g., as shown in FIG. **23**B, the message-input area is updated to include handwritten text of "Thank you").

[0744] In some embodiments, users are also able to select handwritten text that is displayed in the message-input area **2303**. For example, in response to a tap over the handwritten text displayed in the message-input area **2303** (FIG. **23**B), the device may allow the user to then edit that handwritten text (e.g., by displaying a user interface such as that shown in FIG. **23**J that allows for editing handwritten text).

[0745] As shown in FIG. **23**C, in some embodiments, the device also provides suggestions to auto-replace typed text with handwritten text.

[0746] In addition to selecting handwritten text by selecting any of the selectable representations shown in user interface region **2351**, some embodiments also allow users to simply rotate the device in order to provide new handwritten inputs. For example, the user simply rotates the device from the portrait orientation (FIG. **23**D) to a landscape orientation (FIG. **23**E) and, in response to detecting this orientation change, the device displays a user interface that is configured to accept handwritten inputs from the user (e.g., user interface **2309**, FIG. **23**E).

[0747] In some embodiments, users may select background colors and/or patterns for the handwritten inputs (e.g., in response to user input **2308**, FIG. **23**E, the device displays a background selection user interface, FIG. **23**F). In response to a selection (e.g., tap **2310**, FIG. **23**F), the device

modifies a background for the user interface **2309** accordingly (as shown in FIG. **23**G).

[0748] FIGS. **23**H-**23**J illustrate that the user is able to provide the handwritten inputs at the user interface **2309** and, as the user is providing the handwritten inputs, the device presents a real-time preview **2312** of those handwritten inputs. The device may also allow the user to provide a label for a newly-provided handwritten input. For example, in response to a selection of "Label" shown in the upper left corner of FIG. **23**J, the device displays a user interface that allows the user to provide a label.

[0749] In some embodiments, the user is able to type the label into input region **2314** (as shown in FIGS. **23**K-**23**L). In some embodiments, the input region **2314** is auto-populated with a suggested label (e.g., by applying an optical character recognition algorithm to the newly provided handwritten inputs the device is able to suggest an appropriate label). In response to user selection (e.g., tap **2316**, FIG. **23**L) of a "Save" affordance, the device saves the label and associates the newly-provided handwritten input (e.g., handwritten strokes for the newly-provided "Thank you" text) therewith. As shown in FIG. **23**M, the device also provides an indication that the newly-provided handwritten input is associated with the label (e.g., indication **2318**).

[0750] In some embodiments, in response to selection of a "Done" link (e.g., tap **2320**) the device adds the newly-provided handwritten input to the message input-area **2303** and the user is then able to send the newly-provided handwritten input to other users. For example, as shown in FIGS. **23**N-**23**V, after the user sends the newly-provided handwritten input, devices associated with the other users are instructed to render the handwritten input at a predetermined pace (e.g., a second electronic device **2360** presents an indication that the user is provided a handwritten input (e.g., indication **2322**) and then the second device **2360** presents an animation of the handwritten input being drawn at the predetermined pace (as shown in FIGS. **23**Q-**23**V for animation **2324**)).

[0751] In some embodiments, line thickness for a particular handwritten stroke (e.g., strokes provided in conjunction with a particular handwritten input) is determined based on velocity and force applied by a user's finger (or stylus) during the particular handwritten stroke. In some embodiments, a number of ink-rendering techniques are utilized in order to accurately mimic the way that ink naturally swells on a surface (as discussed in more detail below).

[0752] In some embodiments, users are also able to train a custom user-specific handwriting keyboard via the user interfaces shown in FIGS. **23**W-**23**AB. In some embodiments, after successfully training the handwriting keyboard, the device is able to present the custom user-specific handwriting keyboard (as shown in FIG. **23**AC).

[0753] As shown in FIG. **23**AE, in some embodiments, in addition to providing handwritten text, users are also able to provide handwritten drawings (or a combination of handwritten text and handwritten drawings). Any of the techniques discussed herein with respect to handwritten text are also applicable to handwritten drawings (such as the goldfish sketch shown in FIG. **23**AE).

[0754] As shown in FIGS. **23**AD-**23**AE, in some embodiments, the user interfaces for providing and presenting handwritten inputs are different depending on certain physical characteristics of a display that is in communication with the electronic device (also discussed above). In some embodiments, FIG. **23**AD-**23**AE represent user interfaces shown on a device that is in communication with a display of approximately 9.4 inches (about **240** mm), such as an iPad Air (or a device with a larger display, such as an iPad Pro) from Apple Inc. of Cupertino, Calif. In order to utilize these larger display sizes, the handwriting input area is displayed at the same time as the conversation transcript (upper right corner) and a listing of current conversations that the user is part of (upper left corner). In some embodiments, any of the details provided herein in reference to handwriting input area **2309** are applicable to the handwriting input area shown in FIGS. **23**AD-**23**AE.

[0755] FIGS. **24**A-**24**C are flow diagrams illustrating a method **2400** of providing and presenting user-specific handwritten inputs in a messaging application, in accordance with some embodiments. The method **2400** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display and a touch-sensitive surface. In some embodiments, the display is a touch screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **2400** are, optionally, combined and/or the order of some operations is, optionally, changed.

[0756] As described below, the method **2400** provides an intuitive way to provide and present user-specific handwritten inputs in a messaging application. The method helps to improve user satisfaction with their devices and produces more efficient human-machine interfaces by allowing users, e.g., to simply rotate their device in order to begin entering handwritten inputs. Such methods and interfaces also produce more efficient human-machine interfaces by allowing to easily, efficiently, and quickly select handwritten inputs for inclusion in a conversation transcript of a messaging application. For battery-operated devices, such methods and interfaces conserve power and increase the time between battery charges. Furthermore, allowing users to simply rotate their devices in order to begin entering handwritten inputs and allowing users to easily, efficiently, and quickly select handwritten inputs enhances the operability of the devices and makes user-device interfaces (e.g., in the messaging application) more efficient (e.g., by allowing users to easily customize their message content with handwritten inputs) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently (e.g., the user need not leave the messaging application, open and use a different application to input or locate handwritten inputs, and then return to use those inputs in the messaging application, instead the user simple provides and/or selects custom handwritten inputs directly within the messaging application).

[0757] As shown in FIG. **24**A, while the electronic device is in a portrait orientation, the device displays (**2402**, on the display, a messaging user interface (e.g., a messaging user interface that includes a conversation transcript of a messaging session between a user of the electronic device and at least one other user), the messaging user interface including a virtual keyboard. An example messaging user interface is shown in FIG. **23**A. In some embodiments, the virtual keyboard is not configured to accept handwritten input. In some embodiments, the keyboard is a QWERTY, emoji, or

other type of virtual keyboard that does not accept handwritten input (such as the QWERTY keyboard shown in FIG. **23**A.

[0758] The device detects (**2404**) a change in the orientation of the electronic device from the portrait orientation to a landscape orientation (e.g., a user of the device physically rotates the device approximately **90** degrees along an axis). As an example, in FIG. **23**D, the device **100** is oriented in the portrait orientation and, in FIG. **23**E, the device is oriented in a landscape orientation.

[0759] In response to detecting the change in the orientation of the electronic device (e.g., between FIGS. **23**A and **23**E, and also between FIGS. **23**D and **23**E), the device ceases to display (**2406**) the virtual keyboard and displays, on the display, a handwriting input area (e.g., area **2309**, FIG. **23**E) that is configured to accept handwritten input from a user of the electronic device. As shown in FIGS. **23**D-**23**E, upon detecting the change in orientation from portrait to landscape, the device displays the handwriting input area **2309** and no longer displays the messaging user interface. In some embodiments, the handwriting input area is displayed in accordance with a determination that the user previously selected a handwriting input affordance (e.g., the user selects the affordance in order to ensure that when the device is oriented in landscape, the handwriting input area will be immediately displayed without requiring the user to manually choose to display the handwriting input area). In this way, by simply rotating the device **100**, the user is able to enter a handwriting input mode and begin providing handwritten inputs, thus, producing an efficient human-machine interface for providing handwritten inputs in a messaging application.

[0760] In some embodiments, ceasing to display the virtual keyboard includes (**2408**) ceasing to display a conversation transcript that is included in the messaging user interface while the orientation of the electronic device is in the portrait orientation (as shown between FIGS. **23**A and **23**E and between FIGS. **23**D and **23**E, after the device is rotated to the landscape orientation, the conversation transcript is no longer displayed). In this way, by displaying only the handwriting input area **2309** (i.e., the handwriting input area **2309** occupies substantially all of the display **112**) and ceasing to display the conversation transcript, the user is presented with a large canvas on which to provide handwritten inputs. Presenting a large canvas on which to provide handwritten inputs enhances the operability of the device **100** and makes the user-device interface more efficient (e.g., by providing the user with sufficient space to accurately provide handwritten inputs).

[0761] After displaying the handwriting input area **2309**, users are able to provide handwriting inputs (as discussed in reference to operations **2410**-**2416**, FIG. **24**B) and users are able to select representations pre-recorded handwritten inputs (as discussed in reference to operations **2418**-**2426**). Users may perform these operations in any order (e.g., provide handwritten inputs and then later select representations, or vice versa, and may repeat these operations as needed to produce desired handwritten text). In this way, users are able to easily and efficiently provide new handwritten inputs, provide typed inputs, and/or select pre-recorded handwritten inputs in order to produce varied messages to add to a conversation transcript in a messaging application.

[0762] Turning now to FIG. **24**B, in some embodiments, the device receives (**2410** handwritten inputs at the handwriting input area (e.g., the user begins to handwrite "Thank y" as shown in FIG. **23**H). In some embodiments, in response to receiving the handwritten inputs, the device displays a (real-time/constantly updating) preview (e.g., preview **2312**, FIG. **23**H) of the handwritten inputs, the preview including a user interface object (message region/bubble) in which the handwritten inputs will be displayed within the messaging user interface. As shown in FIGS. **23**H-**23**J, the preview of the handwritten inputs is shown in the upper right corner in a message bubble that will be used to display the handwritten inputs within the messaging user interface (e.g., after selecting and sending the handwritten inputs to another user, the handwritten inputs are shown within a messaging bubble in the messaging user interface). In some embodiments, handwritten inputs are not shown within message bubbles and are instead displayed as free-standing text within the messaging user interface. One example of a handwritten input within a messaging bubble is shown in FIG. **23**B (e.g., message bubble **2305**) and an example of a handwritten input outside of a messaging bubble is shown in FIG. **23**B (e.g., message bubble **2307**). By providing a live, real-time preview of the handwritten inputs, operability of the device **100** is enhanced and more efficient user-device interfaces are produced (e.g., by helping the user to provide proper inputs and reduce user mistakes when providing handwritten inputs).

[0763] In some embodiments, while receiving handwritten inputs in the handwriting input area, the device sends (**2412**) (e.g., to a server for routing to a second device of a second user who is in a messaging session with the user of the electronic device, or directly to the second device) instructions to display an indication that the user is currently handwriting a message (e.g., a message bubble with a simulated handwritten stroke and the message bubble is displayed within a conversation transcription of a messaging user interface at the second device, such as indication **2322** FIGS. **23**N-**23**P). In some embodiments, the indication (e.g., **2322**, FIGS. **23**N-**23**P) that that user is currently handwriting a message is different than an indication that is provided when a user is typing a message using an input mechanism other than the handwriting input area (e.g., a virtual QWERTY keyboard).

[0764] In some embodiments, while receiving handwritten inputs in the handwriting input area, the device determines (**2414**) that the handwritten inputs are within a predetermined distance of an edge of the handwriting input area (e.g., within 1 px, 2 px, 3 px, 4 px, 5 px, or some other predefined distance) and, in accordance with the determining, while continuing to display at least a portion of the handwritten inputs, the device shifts a displayed portion of the handwriting input area to reveal additional space within the handwriting input area. For example, as shown in FIGS. **23**H-**23**J, once the handwritten inputs approach within the predetermined distance of the edge, the handwriting input area is shifted to reveal additional space and to allow the user to continue fluidly providing the handwritten inputs. In some embodiments, by continuing to display at least a portion of the handwritten inputs, the user is still able to view some of the previously entered handwritten strokes in order to provide context as the user continues to provide additional handwritten inputs. By dynamically shifting a displayed region of the handwriting input area, operability

of the device **100** is enhanced and more efficient user-device interfaces are provided (e.g., by shifting the displayed region, users are able to continue providing handwritten inputs in an uninterrupted fashion, while still being able to view a portion of previously providing handwriting strokes).

[0765] In some embodiments, the user is able to manually cause the device to shift the displayed portion of the handwriting input area (e.g., by selecting the ">" affordance shown in FIGS. **23**H-**23**J). In some embodiments, the user is able to provide a two finger swipe gesture in a substantially horizontal direction in order to cause the device to shift the displayed portion of the handwriting input area as well (in order to allow the user to easily navigate to the left or right of a particular handwritten input that is currently displayed on the user interface **2309**).

[0766] In some embodiments, the device receives (**2416**) a modification to at least a portion of the handwritten inputs (e.g., an annotation or embellishment of some previously-completed handwriting strokes, or a request to undo a portion of the handwritten inputs.) and, in response to receiving the modification, the device modifies the portion of the handwritten inputs and the preview (e.g., **2312**) in accordance with the modification. For example, in response to an undo request (e.g., the user clicks an undo button (not pictured) displayed proximate to or within the handwriting input area **2309**), the device deletes a last handwritten stroke provided by the user and concurrently deletes the same stroke from the preview **2312**. In some embodiments, if the user taps over the undo button and keeps in contact with the undo button for a predetermined period of time (e.g., 2 seconds or more), the device clears the entire handwriting canvas (e.g., user interface/canvas **2309**).

[0767] Turning now to FIG. **24**C, the device displays (**2418**), within (or near/next to) the handwriting input area, representations of pre-recorded handwritten inputs from the user of the electronic device. In some embodiments, the pre-recorded handwritten inputs are displayed below the handwritten input area (e.g., as shown in FIG. **23**J, representations are shown for "my bad," "Happy Birthday", and "CONGRATS!!!") and each one is available for selection by the user. In some embodiments, after selecting a first of the pre-recorded handwritten inputs, the handwritten input area is updated to include the first pre-recorded handwritten input and the user is then able to modify the input or include it in the conversation transcript for sending to other users. In some embodiments, in addition to representations of pre-recorded handwritten inputs, the device also displays representations of default pre-stored handwritten inputs.

[0768] In some embodiments, in addition to being able to modify pre-recorded handwritten inputs, users are also able to select them for sending to other users (e.g., as shown in FIG. **23**B, input **2304** is provided for selecting a representation of the handwritten input "Thank you"). In some embodiments, the device receives (**2420**) a selection of a first pre-recorded handwritten input (e.g., input **2304**, FIG. **23**B) and sends (**2422**) the first pre-recorded handwritten input (or a representation thereof, or instructions for reproducing the first pre-recorded handwritten input) to a second device that is associated with another user in the messaging session, and sending the first pre-recorded handwritten input to the second device includes instructing the second device to draw the first pre-recorded handwritten input at a predetermined pace at the second device.

[0769] For example, as shown in FIGS. **23**Q-**23**V for region **2324** of a messaging application on a second electronic device **2360**, in response to user selection of a representation of a first pre-recorded handwritten input of "Thank you," a second device **2360** receives instructions to draw the first pre-recorded handwritten input at the predetermined pace. Additional details are provided below regarding ink-regarding techniques utilized to accurately simulate drawing on of the pre-recorded handwritten input.

[0770] In some embodiments, instead of drawing the first pre-recorded handwritten input, the second electronic device **2360** just displays (**2426**) the first pre-recorded handwritten input (i.e., without the drawing discussed above). For example, the second device **2360** just displays the message region **2324** as shown in FIG. **23**S, instead of rendering the drawing effects. Stated another way, in some embodiments, the first pre-recorded handwritten input is added to the messaging user interface at the second device **2360** and is displayed without an animation effect (e.g., without drawing the handwritten input at the predetermined pace).

[0771] In some embodiments, the predetermined pace corresponds (**2424**) to a writing pace that was used by the user while providing the first pre-recorded handwritten input. In some embodiments, the predetermined pace corresponds to a writing pace that is different than a pace that was used by the user while providing the first pre-recorded handwritten input (e.g., a default pace for presenting handwritten inputs).

[0772] In some embodiments, the handwriting input area is available while the device is in the portrait orientation (e.g., for devices with larger displays). In some embodiments, in order to access the handwriting input area while the device is in the portrait orientation, a handwritten input selection affordance is included in the messaging user interface (e.g., affordance shown as being selected by input **2302**A, FIG. **23**A, or the affordance shown as being selected by input **2302**B, FIG. **23**A). In response to detecting selection of the handwritten input selection affordance, the device ceases to display the virtual keyboard and displays the handwriting input area and representations of pre-recorded handwritten inputs from the user of the electronic device. In some embodiments, the handwritten input selection affordance is only available while in the portrait orientation if the device has a touch-sensitive display that is above a predefined size (e.g., a touch-sensitive display that is at least 7.9 inches, such as those available on iPad and iPad mini devices from APPLE of Cupertino, Calif.) or a touch-sensitive display that has a resolution that is above a predefined threshold (such as 2048×1536 pixels at 346 ppi, or better, such as those available on the aforementioned devices from APPLE). Stated another way, in some embodiments, smaller smart phones do not have a handwritten input selection affordance displayed at all while the orientation of the smaller device is the portrait orientation and, therefore, the handwritten input area is only available while these smaller devices are oriented in the landscape orientation.

[0773] It should be understood that the particular order in which the operations in FIGS. **24**A-**24**C have been described is merely one example and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods

described herein are also applicable in an analogous manner to method **2400** described above. For example, the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described above with reference to method **2400** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein. For brevity, these details are not repeated here.

[0774] In some embodiments, the method **2400** described above in reference to FIGS. **24**A-**24**C utilizes one or more of the techniques described below to render ink on the display in order to accurately simulate the way that ink is applied to a surface.

[0775] In accordance with some embodiments, FIG. **25** shows a functional block diagram of an electronic device **2500** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, firmware, or a combination thereof to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. **25** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[0776] As shown in FIG. **25**, an electronic device **2500** includes a display unit **2502** configured to display a user interface, a touch-sensitive surface unit **2504** configured to receive contacts, one or more sensor units **2506** for detecting intensities of contacts on the touch-sensitive surface unit **2504**; and a processing unit **2508** coupled with the display unit **2502**, the touch-sensitive surface unit **2504** and the one or more sensor units **2506**. In some embodiments, the processing unit **2508** includes a displaying unit **2510**, a device orientation detecting unit **2512**, a handwriting modification unit **2514**, a sending unit **2516**, a handwritten input selection unit **2518**, a determining unit **2520**, and/or a handwritten input area shifting unit **2524**.

[0777] The processing unit **2508** is configured to while the electronic device is in a portrait orientation, display (e.g., with the displaying unit **2510**), on the display (e.g., the display unit **2502**), a messaging user interface, the messaging user interface including a virtual keyboard; detect a change in the orientation of the electronic device from the portrait orientation to a landscape orientation (e.g., with the device orientation detecting unit **2512**); and, in response to detecting the change in the orientation of the electronic device: cease to display the virtual keyboard (e.g., with the displaying unit **2510**); and display, on the display, a handwriting input area that is configured to accept handwritten input from a user of the electronic device (e.g., with the displaying unit **2510**).

[0778] In accordance with some embodiments of the electronic device **2500**, the processing unit is configured to: receive handwritten inputs at the handwriting input area (e.g., with the handwritten modification unit **2514**); and in response to receiving the handwritten inputs, display a preview of the handwritten inputs, the preview including a user interface object in which the handwritten inputs will be displayed within the messaging user interface (e.g., with the displaying unit **2510**).

[0779] In accordance with some embodiments of the electronic device **2500**, the processing unit is further configured to: receive a modification to at least a portion of the handwritten inputs (e.g., with the handwritten modification unit **2514**) and, in response to receiving the modification, modify the portion of the handwritten inputs and the preview in accordance with the modification (e.g., with the handwritten modification unit **2514**).

[0780] In accordance with some embodiments of the electronic device **2500**, the processing unit is further configured to: while receiving handwritten inputs in the handwriting input area, send instructions to display an indication that the user is currently handwriting a message (e.g., with the sending unit **2516**).

[0781] In accordance with some embodiments of the electronic device **2500**, the processing unit is further configured to: display, within the handwriting input area, representations of pre-recorded handwritten inputs from the user of the electronic device (e.g., with the displaying unit **2510**).

[0782] In accordance with some embodiments of the electronic device **2500**, the processing unit is further configured to: receive a selection of a first pre-recorded handwritten input (e.g., with the handwritten input selection unit **2518**); and send the first pre-recorded handwritten input to a second device that is associated with another user in the messaging session (e.g., with the sending unit **2516**), and sending the first pre-recorded handwritten input to the second device includes instructing the second device to draw the first pre-recorded handwritten input at a predetermined pace at the second device.

[0783] In accordance with some embodiments of the electronic device **2500**, the predetermined pace corresponds to a writing pace that was used by the user while providing the first pre-recorded handwritten input.

[0784] In accordance with some embodiments of the electronic device **2500**, the predetermined pace corresponds to a writing pace that is different than a pace that was used by the user while providing the first pre-recorded handwritten input.

[0785] In accordance with some embodiments of the electronic device **2500**, the processing unit is further configured to: receive a selection of a first pre-recorded handwritten input (e.g., with the handwritten input selection unit **2518**); and send the first pre-recorded handwritten input to a second device that is associated with another user in the messaging session (e.g., with the sending unit **2516**), and sending the first pre-recorded handwritten input to the second device includes instructing the second device to display the first pre-recorded handwritten input at the second device.

[0786] In accordance with some embodiments of the electronic device **2500**, the processing unit is further configured to: while receiving handwritten inputs in the handwriting input area, determine that the handwriting inputs are within a predetermined distance of an edge of the handwriting input area (e.g., with the determining unit **2522**) and, in accordance with the determining, while continuing to display at least a portion of the handwritten inputs, shift a displayed portion of the handwriting input area to reveal additional space within the handwriting input area (e.g., with the handwritten input area shifting unit **2524**).

[0787] In accordance with some embodiments of the electronic device **2500**, ceasing to display the virtual keyboard includes ceasing to display a conversation transcript that is

included in the messaging user interface while the orientation of the electronic device is in the portrait orientation.

[0788] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[0789] The operations described above with reference to FIGS. **24**A-**24**C are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **25**. For example, some operations are optionally implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

[0790] FIGS. **26**A-**26**B are flow diagrams illustrating a method **2600** of providing and presenting user-specific handwritten inputs in a messaging application, in accordance with some embodiments. The method **2600** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display and a touch-sensitive surface. In some embodiments, the display is a touch screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **2600** are, optionally, combined and/or the order of some operations is, optionally, changed.

[0791] As described below, the method **2600** provides an intuitive way to provide and present user-specific handwritten inputs in a messaging application. The method helps to improve user satisfaction with their devices and produces more efficient human-machine interfaces by allowing users, e.g., to efficiently auto-replace typed inputs with handwritten inputs. For battery-operated devices, such methods and interfaces conserve power and increase the time between battery charges (e.g., by requiring only a single input to auto-replace a particular sequence of typed inputs with an associated handwritten input).

[0792] The device displays (**2602**), on the display: a messaging user interface, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user (e.g., including the message regions displaying messages exchanged between the user and the at least one other user, as shown in FIG. **23**A), a virtual keyboard (e.g., the virtual QWERTY keyboard shown in FIG. **23**A), and a message-input area (e.g., message-input area **2303**, FIG. **23**B).

[0793] The device also receives (**2604**), at the virtual keyboard, a plurality of typing inputs (the user types a plurality of keys on the display virtual QWERTY keyboard). For example, as shown in FIG. **23**C (showing close-ups of the message-input area **2303**) the user types (in other words, the plurality of typing inputs include the following inputs) "Thank you for helping to play all of this! I think he is going to be really surprised!" While receiving the plurality of typing inputs, the device determines whether one or more typing inputs of the plurality of typing inputs match a stored sequence of characters that is associated with stored handwritten input from the user. In some embodiments, the stored sequence of characters corresponds (**2608**) to a label that the user provided for the stored handwritten input. For example, the user inputs a variety of handwritten inputs and associates a label with each respective handwritten input (e.g., as shown in FIG. **23**K-**23**M, the user associates a label of thank you with recently-typed handwritten text for "Thank you").

[0794] In accordance with a determination that the one or more typing inputs match the stored sequence of characters (e.g., that the typed inputs "Thank you" match the stored label of "Thank you"), the device displays (**2610**) at a first location, proximate to a first set of characters that is displayed within the message-input area, a selectable representation of the stored handwritten input (e.g., selectable representation **2392**A and **2392**B shown in FIG. **23**C), and the first set of characters is displayed within the message-input area and includes characters that correspond to the one or more typing inputs that match the stored sequence of characters.

[0795] The device also detects (**2612**), via the touch-sensitive surface, a selection of the selectable representation of the stored handwritten input (e.g., detects one of the inputs **2306** shown in FIG. **23**C). In response to detecting the selection of the selectable representation of the stored handwritten input, the device: ceases to display the selectable representation of the stored handwritten input at the first location and replaces display, within the message-input area, of the first set of characters that correspond to the one or more typing inputs with display of a representation of the stored handwritten input. For example, as shown in FIG. **23**C, in response to input **2306**, the device ceases to display the selectable representations **2392**A/**2392**B and instead replaces the typed characters "Thank you" with a representation of the stored handwritten input that was displayed in the selectable representation. In this way, the user is able to provide a single input (just a selection of the selectable representation) in order to auto-replace typed text with handwritten text, thereby enhancing operability of the device **100** and making the user-device interface more efficient.

[0796] Turning now to FIG. **26**B, in some embodiments, after replacing the first set of characters with the representation of the stored handwritten input, the message-input area (e.g., area **2303**) includes (**2614**) both the representation of the stored handwritten input and at least a first typed input of the plurality of typed inputs. (In other words, the user's message includes both handwritten and typed text (as is shown in FIG. **23**C). In this way, the user is able to personalize particular phrases within a single message without having to send handwritten text for the full contents of

that single message, thereby enhancing operability of the device **100** and making the user-device interface more efficient.

[0797] In some embodiments, the device receives (**2616**) a request to send a message to the at least one other user and, in response to receiving the request, the device displays within the conversation transcript a user interface object that includes an animation that draws the stored handwritten input at a predetermined pace (as shown in FIGS. **23**Q-**23**V for a second electronic device **2360** and, in some embodiments, the same animation is drawn at the predetermined pace at the device **100**). In some embodiments, in response to receiving the request to send the message to the at least one other user, the device sends (through a server or directly to a second device **2360** that is associated with the at least one other user) instructions to render a user interface object that includes the animation that draws the stored handwritten input at the predetermined pace (as shown in FIGS. **23**Q-**23**V).

[0798] In some embodiments, the predetermined pace corresponds to a writing pace that was used by the user while providing the stored handwritten input (thus allowing users to provided highly customized handwritten messages that include both the user's handwritten text and the predetermined pace at which the user's handwritten text was previously written). In some embodiments, the predetermined pace corresponds to a writing pace that is different from a pace that was used by the user while providing the stored handwritten input.

[0799] It should be understood that the particular order in which the operations in FIGS. **26**A-**26**B have been described is merely one example and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein are also applicable in an analogous manner to method **2600** described above. For example, the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described above with reference to method **2600** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein. For brevity, these details are not repeated here.

[0800] In some embodiments, the method **2600** described above in reference to FIGS. **26**A-**26**B utilizes one or more of the techniques described below to render ink on the display in order to accurately simulate the way that ink is applied to a surface.

[0801] In accordance with some embodiments, FIG. **27** shows a functional block diagram of an electronic device **2700** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, firmware, or a combination thereof to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. **27** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[0802] As shown in FIG. **27**, an electronic device **2700** includes a display unit **2702** configured to display a user interface, a touch-sensitive surface unit **2704** configured to receive contacts, one or more sensor units **2706** for detecting intensities of contacts on the touch-sensitive surface unit **2704**; and a processing unit **2708** coupled with the display unit **2702**, the touch-sensitive surface unit **2704** and the one or more sensor units **2706**. In some embodiments, the processing unit **2708** includes a displaying unit **2710**, a typing inputs receiving unit **2712**, a determining unit **2714**, a detecting unit **2716**, a replacing unit **2718**, a second unit **2720**, and a request receiving unit **2722**.

[0803] The processing unit **2708** is configured to display, on the display (e.g., with the displaying unit **2710** in conjunction with the display unit **2702**), a messaging user interface, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a virtual keyboard, and a message-input area; receive, at the virtual keyboard, a plurality of typing inputs (e.g., with the typing inputs receiving unit **2712**); while receiving the plurality of typing inputs, determine whether one or more typing inputs of the plurality of typing inputs match a stored sequence of characters that is associated with stored handwritten input from the user (e.g., with the determining unit **2714**); in accordance with a determination that the one or more typing inputs match the stored sequence of characters, display (e.g., with the displaying unit **2710**) at a first location, proximate to a first set of characters that is displayed within the message-input area, a selectable representation of the stored handwritten input, and the first set of characters is displayed within the message-input area and includes characters that correspond to the one or more typing inputs that match the stored sequence of characters; detect (e.g., with the detecting unit **2716**)), via the touch-sensitive surface, a selection of the selectable representation of the stored handwritten input; and, in response to detecting the selection of the selectable representation of the stored handwritten input: cease to display (e.g., with the displaying unit **2710**) the selectable representation of the stored handwritten input at the first location; and replace display (e.g., with the replacing unit **2718**), within the message-input area, of the first set of characters that correspond to the one or more typing inputs with display of a representation of the stored handwritten input.

[0804] In accordance with some embodiments of the electronic device **2700**, the processing unit is configured to: receive a request (e.g., with the request receiving unit **2722**) to send a message to the at least one other user; and, in response to receiving the request, display (e.g., with the displaying unit **2710**) within the conversation transcript a user interface object that includes an animation that draws the stored handwritten input at a predetermined pace.

[0805] In accordance with some embodiments of the electronic device **2700**, the processing unit is further configured to: in response to receiving the request to send the message to the at least one other user, send instructions (e.g., with the sending unit **2720**) to render a user interface object that includes the animation that draws the stored handwritten input at the predetermined pace.

[0806] In accordance with some embodiments of the electronic device **2700**, the predetermined pace corresponds to a writing pace that was used by the user while providing the stored handwritten input.

[0807] In accordance with some embodiments of the electronic device **2700**, the predetermined pace corresponds to a writing pace that is different from a pace that was used by the user while providing the stored handwritten input.

[0808] In accordance with some embodiments of the electronic device **2700**, after replacing the first set of characters with the representation of the stored handwritten input, the message-input area includes both the representation of the stored handwritten input and at least a first typed input of the plurality of typed inputs.

[0809] In accordance with some embodiments of the electronic device **2700**, the stored sequence of characters corresponds to a label that the user provided for the stored handwritten input.

[0810] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[0811] The operations described above with reference to FIGS. **26**A-**26**B are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **27**. For example, some operations are optionally implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

[0812] FIGS. **28**A-**28**B are flow diagrams illustrating a method **2800** of providing and presenting user-specific handwritten inputs in a messaging application, in accordance with some embodiments. The method **2800** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display and a touch-sensitive surface. In some embodiments, the display is a touch screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **2800** are, optionally, combined and/or the order of some operations is, optionally, changed.

[0813] As described below, the method **2800** provides an intuitive way to provide and present user-specific handwritten inputs in a messaging application. The method helps to improve user satisfaction with their devices and produces more efficient human-machine interfaces by allowing users, e.g., to simply following a predefined training sequence in order to produce a custom keyboard with user-specific handwritten characters as keys on the custom keyboard. For battery-operated devices, such methods and interfaces conserve power and increase the time between battery charges. Furthermore, allowing users to easily, efficiently, and quickly produce custom keyboards with user-specific handwritten characters as keys enhances the operability of the devices and makes user-device interfaces (e.g., in the messaging application) more efficient (e.g., by allowing users to easily customize their message content with handwritten inputs selected from the custom keyboard) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently (e.g., the user need not leave the messaging application, open and use a different application to input or locate handwritten inputs, and then return to use those inputs in the messaging application, instead the user simple provides and/or selects custom handwritten inputs directly within the messaging application).

[0814] The device detects (**2802**), via the touch-sensitive surface, a first input (that corresponds to a request to prepare a custom keyboard with handwritten characters, such as input **2326** in order to activate a keyboard preparation mode and then input **2328** in order to display the keyboard preparation user interface for a respective set of training characters, FIGS. **23**W-**23**X). In response to detecting the first input (or multiple inputs, such as inputs **2326** and **2328**), the device presents, on the display, a keyboard preparation user interface (e.g., the user interface shown on FIG. **23**Y). In some embodiments, the keyboard preparation user interface includes (**2804**) a first portion that displays the predefined set of training characters including a first emphasized character (e.g., the portion of the user interface shown in FIG. **23**Y that displays "THE QUICK BROWN FOX JUMPS OVER THE LAZY DOG." In some embodiments, the first portion is a top portion that provides a preview of characters that will be typed by the user while preparing the custom keyboard and the emphasized character represents that next character to be handwritten by the user while preparing the custom keyboard (e.g., as shown in FIGS. **23**Y and **23**Z, the "T" character **2330** is emphasized in the first portion in order to indicate to the user that they should provide handwritten input for that character). In some embodiments, the keyboard preparation user interface also includes: a second portion that displays one or more characters of the predefined set of training characters, the one or more characters including a second emphasized character (e.g., emphasized character **2332**, FIGS. **23**Y-**23**Z). For example the second portion is a bottom portion that is displayed below the first/top portion and the second portion includes a limited number of characters (e.g., 1, 2, or 3) representing the next characters to be handwritten by the user. In some embodiments, the first and second emphasized characters correspond to the same character, but the second emphasized character is displayed with a larger font size that the first emphasized character, as shown in FIGS. **23**Y-**23**Z.

[0815] In some embodiments, emphasized characters in the first and second portions change as the handwritten inputs are received (**2806**). In some embodiments, in accordance with a determination that a respective handwritten

input satisfies acceptance criteria, the device emphasizes a next character in the set of training characters (as shown in FIGS. **23**Z-**23**AA, the emphasized characters change as the user continues to provide handwritten inputs that satisfy the acceptance criteria. In this way, users are provided with clear visual cues as to the characters they should be handwriting.

[0816] In some embodiments, in accordance with a determination that a respective handwritten input does not satisfy the acceptance criteria, the device provides an indication to the user as to how the handwritten input should be revised in order to satisfy the acceptance criteria. For example, as shown in FIG. **23**Y, the user provides a handwritten input for the letter "T" but that handwritten input does not satisfy the acceptance criteria and, as such, the device displays the indication **2330** instructing the user to provide a larger handwritten input.

[0817] While presenting the keyboard preparation user interface, the device receives (**2808**), via the touch-sensitive surface, handwritten inputs that correspond to a predefined set of training characters (as discussed above in reference to FIGS. **23**Y-**23**AA). For example, the predefined set of training characters correspond to those characters displayed on a QWERTY keyboard (**2810**).

[0818] After receiving the handwritten inputs, the device detects (**2812**) a second input that corresponds to a request to display a messaging user interface that includes a message-input area and a virtual keyboard with a plurality of keys (e.g., the virtual keyboard is a QWERTY keyboard (such as that shown in FIG. **23**A) or is the custom keyboard with handwritten characters that correspond to the handwritten inputs (such as that shown in FIG. **23**AC)). A first key of the plurality of keys is associated with a first handwritten input of the received handwritten inputs. In some embodiments, the virtual keyboard is a QWERTY keyboard (**2814**). For example, the keys on the QWERTY keyboard shown on FIG. **23**A are each associated with a respective handwritten input from the user. As another example, the virtual keyboard is a user-specific keyboard with keys, wherein each key includes a representation of one of the received handwritten inputs (such as that shown in FIG. **23**AC).

[0819] In response to detecting the second input, the device displays (**2818**) the messaging user interface that includes the message-input area and the virtual keyboard with the plurality of keys. For example the second input corresponds to a request to open a messaging application (e.g., by clicking an icon on a home screen page). The device receives (**2818**), via the touch-sensitive surface, a selection of the first key (e.g., the user taps over a representation of the "p" key shown on the QWERTY keyboard of FIG. **23**A or the user-specific handwritten keyboard of FIG. **23**AC. In response to receiving the selection of the first key, the device outputs a representation of the first handwritten input within the message-input area (e.g., extending the previous example after the user taps the "p" key on a displayed keyboard the device displays a user-specific handwritten input for the "p" key, such as one provided during the handwriting training exercise discussed above in reference to FIGS. **23**W-**23**AB)

[0820] In some embodiments, outputting the representation of the first handwritten input includes (**2820**) rendering the first handwritten input at a pace that was recorded while receiving the first handwritten input.

[0821] It should be understood that the particular order in which the operations in FIGS. **28**A-**28**B have been described is merely one example and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein are also applicable in an analogous manner to method **2800** described above. For example, the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described above with reference to method **2800** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein. For brevity, these details are not repeated here.

[0822] In some embodiments, the methods described above in reference to FIGS. **24**A-**24**C, **26**A-**26**B, and **28**A-**28**B utilize one or more of the techniques described below to render ink on the display in order to accurately simulate the way that ink is applied to a surface.

[0823] Handwriting GL Renderer

[0824] The handwriting renderer can be defined by two primary systems: wet and dry (as shown in Table 1 in FIG. **28**D). These are two interdependent rendering pipelines that present the lifecycle of the appearance of ink on screen. In some embodiments, the rendering pipelines work on all supported hardware (e.g., many different configurations of smart phones, laptops, smart watches, etc.).

[0825] In some embodiments, each state described above (e.g., in reference to Table 1 in FIG. **28**D) represents a frame buffer and contains its own shader pipeline. Wet Intermediate: off-screen, draw arrays using GL_POINTS, made of many overlapping dots using glBlendFunc(GL_ONE, GL_ONE_MINUS_SRC_ALPHA) resulting in the appearance of continuous line color in concert with Dynamic Circularization, time-based particle simulation for Bleed Behavior. Wet Composite: receives Self, Wet Intermediate and paper texture, fragment based normals determination for Specular Wetness, accumulatively fades to 0%, revealing Dry Composite. Dry Intermediate: off-screen, receives Self and Wet Intermediate, pre-processing for Segment Level Multiply Blending. Dry Composite: receives Dry Intermediate and paper texture, applies color from Dry Intermediate results.

[0826] In some embodiments, when presented to a screen (e.g., display **112** of device **100**), Wet Composite is alpha blended on top of Dry Composite.

[0827] Bleed Behavior

[0828] Example equations for rendering bleed behavior that accurately mimics the way ink is applied to a surface is shown in Table 2 below:

TABLE 2

life = clamp((time − birth) / lifespan, 0.0, 1.0);
final_size = max_size * 0.1 + (max_size * 0.36 + max_size * 0.09 * life) * speed + (max_size * 0.45 * life) * (force * 0.8 + speed * 0.2);

[0829] In some embodiments, the Bleed Behavior is a time-based effect that changes each vertex's point size over a normalized time-of-lifespan. In some embodiments, the size is determined by filtered (smoothed) and normalized values of user pressure (force) and velocity (baked down to speed).

[0830] In some embodiments, when the simulation has completed its phase for a given point, a channel designated exclusively for the Dry Pipeline to receive is written to (e.g., it is critical that this channel is written to only once per point to avoid alpha over-coverage within the Dry Pipeline).

[0831] Example equations used to implement a Dynamic Circularization technique are shown in Table 3 below:

TABLE 3

```
one_uv_pixel = 1.0 / point_size;
vector_from_center = (gl_PointCoord − 0.5) * 2.0;
dist_squared = dot(vector_from_center, vector_from_center);
value = 1.0 − linearstep(max(0.0, 1.0 − one_uv_pixel * 4.0), 1.0, dist_squared);
```

[0832] In some embodiments, during the fragment phase of the Wet Intermediate Pass, each GL POINT is processed. Based on the point-size and fragment-coordinate of the point, we can ensure that the circularization of the point maintains a consistent edge alpha falloff. This consistency provides a consistent line edge appearance without the expense of MSAA (multi-sampled anti-aliasing) and regardless of line-weight/point-size.

[0833] An example matrix that illustrates Specular Wetness techniques is shown in Table 4 (see FIG. **28**C).

[0834] In some embodiments, using a Laplacian Convolution Matrix for Wet Intermediate and Paper texture color, a two-dimensional vector is created based on adjacent pixel luminance (an example is shown in Table 4 in FIG. **28**C). This vector's direction and magnitude is used to compute a three-dimensional vector (normal). This vector is used just like a bump map to create the appearance of Phong shaded wetness based on a light's three dimensional position.

[0835] Multiply Blend Using Segment Separation

[0836] Intermediate

[0837] In some embodiments, overlapping line segments are provided in conjunction with particular handwritten inputs. An example is shown in Table 5 (see FIG. **28**C).

[0838] For the purposes of the example shown in Table 5 in FIG. **28**C, Element **5**B is referred to as a NEW_SEGMENT, Element **5**C as PREVIOUS_SEGMENT, and Element **5**D as DIFF. In some embodiments, when new data is written to the specified channel that the Dry Intermediate is designed to receive from the Wet Intermediate, that data is denoted as NEW_SEGMENT. In some embodiments, the equation shown in Table 5 in FIG. **28**C is utilized to ensure that DIFF can be added seamlessly to the previous state of a color attachment, providing the same consistent alpha coverage along edges (an example is shown in Table 6 in Table 28C.

[0839] In some embodiments, DIFF is added and clamped to a single channel of an intermediate frame buffer's color attachment to represent ALPHA (**5**E).

[0840] In some embodiments, the following equation is used to help with the bleeding techniques: BLEND=DIFF*TARGET MULTIPLIER+(1.0−DIFF* TARGET_MULTIPLIER) * PREVIOUS BLEND. In some embodiments, the diagonal component in Element **5**F of Table 7 in FIG. **28**D as DIFF and the grid component as PREVIOUS_BLEND. In some embodiments, DIFF is multiplied by a scalar (TARGET_MULTIPLIER) and added to the inverse of this product of the previous state. The result is written to a single channel representing the multiply blend state. Due to inherent alpha over coverage with this process, alpha is preserved in a separate channel.

[0841] Composite

[0842] In some embodiments, when a request is made to render a pass to the composite frame buffer to be presented to screen, this task is much more trivial than traditional blend mode operations since the work has been done in the intermediate pass and, notably preserves alpha precisely. Other methods take pre-multiplied alpha and do expensive, imprecise work to extract alpha using methods like unpremultiply.

[0843] RGB=mix(BASE_COLOR, BLACK, linearstep (TARGET_MULTIPLIER, 1.0, BLEND)).

[0844] A=ALPHA*PAPER_TEXTURE.

[0845] In some embodiments, the result from FIG. **5**F as BLEND, the result in FIG. **5**E as ALPHA. In some embodiments, these techniques of generating multiply blending more closely simulates how ink reacts to paper. It works continuously (per segment) within a single stroke and simultaneously with all other pixels in the color attachment.

[0846] Multiply Blend Using Segment Collation

[0847] In some embodiments, while the richness and complexity of segment separation blending may require one pass per segment in a live drawing setting, there are a few cases that require a more optimized method of rendering all non-live drawing data in as few passes as possible (e.g. Undo, Thumbnail, Recents). For these cases, it is ideal to collate as many segments as possible that are known to only overlap their previous segment.

[0848] Collision Detection to Determine Pass Endpoint

[0849] Element **6**A in Table 8 in FIG. **28**D illustrates an example final composite. Element **6**B in Table 8 in FIG. **28**D illustrates the series of passes needed to render **6**A.

[0850] In some embodiments, when all segments are known, fast-enumeration is used to go over each segment to determine two-dimensional vector intersection with all segments within the current pass (This includes detached segments from previous lines. This system is agnostic to beginning and end of complete strokes). When an intersection is determined, this group of vertices is denoted as a single pass by flagging the last segment as an endpoint. In some embodiments, in the second shape of FIG. **6**B, although the second shape appears to intersect with the first shape, these techniques do not determine intersection until an intersection is reached within vectors enumerated since the last intersection.

[0851] Additional details regarding techniques used in conjunction with the methods described above in reference to FIGS. **24**A-**24**C, **26**A-**26**B, and **28**A-**28**B are also provided in U.S. Provisional Application Ser. No. 62/349,116, filed Jun. 12, 2016, which is incorporated by reference

herein. The details provided in U.S. Provisional Application Ser. No. 62/349,116 thus serve as a supplement to the details provided herein and may be combined and interchanged with any of the details provided above in reference to FIGS. **24**A-**24**C, **26**A-**26**B, and **28**A-**28**B.

[0852] In accordance with some embodiments, FIG. **29** shows a functional block diagram of an electronic device **2900** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, firmware, or a combination thereof to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. **29** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[0853] As shown in FIG. **29**, an electronic device **2900** includes a display unit **2902** configured to display a user interface, a touch-sensitive surface unit **2904** configured to receive contacts, one or more sensor units **2906** for detecting intensities of contacts on the touch-sensitive surface unit **2904**; and a processing unit **2908** coupled with the display unit **2902**, the touch-sensitive surface unit **2904** and the one or more sensor units **2906**. In some embodiments, the processing unit **2908** includes an input detecting unit **2910**, a displaying unit **2912**, a selection receiving unit **2914**, a handwriting input representation outputting unit **2916**, and a handwritten input receiving unit **2918**.

[0854] The processing unit **2908** is configured to detect (e.g., with the input detecting unit **2910**), via the touch-sensitive surface, a first input; in response to detecting the first input, present, on the display (e.g., with the displaying unit **2912** in conjunction with the display unit **2902**), a keyboard preparation user interface; while presenting the keyboard preparation user interface, receive, via the touch-sensitive surface, handwritten inputs (e.g., with the handwritten input receiving unit **2918**) that correspond to a predefined set of training characters; after receiving the handwritten inputs, detect a second input (e.g., with the input detecting unit **2910**) that corresponds to a request to display a messaging user interface that includes a message-input area and a virtual keyboard with a plurality of keys, and a first key of the plurality of keys is associated with a first handwritten input of the received handwritten inputs; in response to detecting the second input, display the messaging user interface that includes the message-input area and the virtual keyboard with the plurality of keys (e.g., with the displaying unit **2912**); receive, via the touch-sensitive surface, a selection of the first key (e.g., with the selection receiving unit **2914**); and in response to receiving the selection of the first key, output a representation of the first handwritten input within the message-input area (e.g., with the handwriting input representation outputting unit **2916**).

[0855] In some embodiments, the predefined set of training characters corresponds to characters displayed on a QWERTY keyboard.

[0856] In some embodiments, the virtual keyboard is a QWERTY keyboard.

[0857] In some embodiments, the virtual keyboard is a user-specific keyboard with keys, wherein each key includes a representation of one of the received handwritten inputs.

[0858] In some embodiments, outputting the representation of the first handwritten input includes rendering the first handwritten input at a pace that was recorded while receiving the first handwritten input.

[0859] In some embodiments, the keyboard preparation user interface includes: a first portion that displays the predefined set of training characters including a first emphasized character, and a second portion that displays one or more characters of the predefined set of training characters, the one or more characters including a second emphasized character.

[0860] In some embodiments, emphasized characters change as the handwritten inputs are received.

[0861] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[0862] The operations described above with reference to FIGS. **28**A-**28**B are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **29**. For example, some operations are optionally implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

Selectively Scrunch Content in a Message Transcript

[0863] FIGS. **30**A-**30**G illustrate example user interfaces for quickly locating different types of content in a messaging application, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below. Although some of the examples which follow will be given with reference to inputs on a touch-screen display (where the touch-sensitive surface and the display are combined), in some embodiments, the device detects inputs on a touch-sensitive surface **451** that is separate from the display **450**, as shown in FIG. **4**B. For convenience of explanation, the embodiments described below will be discussed with reference to operations performed on a device with a touch-sensitive display system **112**. In such embodiments, a focus selector is, optionally: a respective finger or stylus contact, a representative point corresponding to a finger or stylus contact (e.g., a centroid of a respective contact or a point associated with a respective contact), or a centroid of two or more contacts detected on

the touch-sensitive display system **112**. However, analogous operations are, optionally, performed on a device with a display **450** and a separate touch-sensitive surface **451** in response to detecting the contacts on the touch-sensitive surface **451** while displaying the user interfaces discussed below, along with a focus selector.

[0864] As shown in FIG. **30**A, in some embodiments, users are able to quickly locate different types of content in a messaging application by scrunching down content in order to easily locate desired content. A user provides a gesture **3002** in FIG. **30**A and, in response, the device reduces a display size (i.e., scrunches/squishes down) message regions that include content having a first content type (e.g., message regions with text-only content are reduced in size, such as the content for message region **3003**, FIG. **30**B). In some embodiments, as a user continues to provide a gesture (e.g., gesture **3004** is a continuation of gesture **3002** but, in some embodiments, gesture **3004** is a distinct gesture from gesture **3002**), the message regions are further reduced in size (e.g., message region **3003** is further reduced in size, FIG. **30**C).

[0865] Users are able to intuitively provide additional gestures (or continue providing a single gesture) that reduce a display size for content types other than the first content type. As shown in FIG. **30**D, in response to gesture **3006** (FIG. **30**C), content items having a second content type (e.g., text with emojis) are displayed with a reduced display size (such as message region **3001**). As shown in FIG. **30**E, in response to gesture **3008** (FIG. **30**D), content items having a third content type (e.g., text that includes text-rendering effects) are displayed with a reduced display size (such as message region **3009**, FIG. **30**E). As shown in FIG. **30**F, in response to gesture **3010**, content items having a fourth content type (e.g., graphical content, such as images and maps objects) are displayed with a reduced display size (such as message region **3005** and **3011**, FIG. **30**F).

[0866] In some embodiments, users are also able to quickly expand portions of the messaging user interface in response to a de-pinch gesture (e.g., gesture **3012**). In response to detecting gesture **3012**, the device increases display sizes for all content types (FIGS. **30**F-**30**G), until the message regions return to their respective default sizes. In this way, users are easily able to search out desired content without having to aimlessly scroll through a long and confusing conversation transcript (instead users simply scrunch down content so that they can quickly see a high-level overview of content items in the conversation transcript and, once desired information is located, users can expand content items to view the desired information and message regions that are surrounding the desired information).

[0867] FIGS. **31**A-**31**B are flow diagrams illustrating a method **3100** of quickly locating different types of content in a messaging application, in accordance with some embodiments. The method **3100** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display and a touch-sensitive surface. In some embodiments, the display is a touch screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **3100** are, optionally, combined and/or the order of some operations is, optionally, changed.

[0868] As described below, the method **3100** provides an intuitive way to locate different types of content in a messaging application. The method produces more efficient human-machine interfaces by allowing users to use a simple gesture to quickly scale down display sizes for content in a messaging application, so that users are able to quickly locate desired content (e.g., users can scale down all text-only content in order to quickly locate emojis, photos, videos, or other types of content that may have been received a long time ago). For battery-operated devices, the method helps to conserve power and increase the time between battery charges (e.g., by allowing users to quickly locate desired content instead forcing users to employ inefficient and battery-draining techniques). Furthermore, allowing users to quickly locate desired content enhances the operability of the devices and makes user-device interfaces (e.g., in the messaging application) more efficient by allowing users to easily locate desired content in a potentially large and difficult to search conversation transcript. The user need not scroll through pages and pages of content in the conversation transcript and can instead simply provide intuitive gestures to easily scale down content so that desired content is easily located.

[0869] The device displays (**3102**), on the display, a messaging user interface that includes a plurality of content items. In some embodiments, the messaging user interface includes a conversation transcript of a messaging session between a user of the electronic device and at least one other user, as shown in FIG. **30**A. In some embodiments, the plurality of content items includes content items having a first content type. For example, each content item of the first content type is text-based and does not include any emojis or other text-rendering effects (such as making the text appear or disappear in response to a gesture over a content item, also referred to herein as an invisible ink effect or a private message). In some embodiments, the first content type includes text-only messages sent and received via the messaging user interface. In some embodiments, a content item corresponds to content included in a single user interface element displayed in the messaging user interface (e.g., a single message region or bubble). Message region **3003** is a one example shown in FIG. **30**A of a content item that includes content of the first content type.

[0870] In some embodiments, the plurality of content items includes content items having a second content type that is distinct from the first content type. For example, the second content type corresponds to messages containing content other than text-only content, such as emojis or graphical content sent and received via the message user interface, such as camera images, screenshots, maps objects, objects with text-rendering effects, and the like. In some embodiments, content items having the second content type include message regions that include text and emojis (e.g., message region **3001**, FIG. **30**A). As described in more detail below, the messaging user interface may include content items having a third content type (e.g., the content included in message region **3009**, FIG. **30**C) and a fourth content type (e.g., the content included in message region **3005** and image **3011**, FIGS. **30**A and **30**D) as well.

[0871] In some embodiments, a respective content item in the plurality of content items is displayed with a respective first size. In some embodiments, each content item is displayed with a respective default display size. In some embodiments, different default sizes are associated with the

content types (e.g., pictures and other graphical content have a different default display size than text-only content items).

[0872] While displaying the messaging user interface (and, in some embodiments, while a focus selector is over the messaging user interface), the device detects (**3104**), via the touch-sensitive surface, a first input. In some embodiments, the first input (e.g., a first portion of a pinch gesture, such as gesture **3002** shown in FIG. **30**A) corresponds to a first request to reduce a display size (or a magnification level) for at least a portion of the content items in the plurality of content items. In some embodiments, the first request is received while some textual-only content is displayed within the messaging user interface (e.g., the message regions that include text-only content including message region **3003**, as shown in FIG. **30**A).

[0873] In response to detecting the first input, the device reduces (**3106**) a display size of at least some content items having the first content type while continuing to display content items having the second content type with their respective first size. In some embodiments, reducing the display size includes reducing the display size for all content items having the first content type. In some embodiments, reducing the display size includes reducing the display size for only those content items having the first content type that are currently visible on the display (e.g., items of the first content type may or may not have a reduced display size while they are not currently visible within the portion of the messaging session that is visible within the messaging user interface on the display). As shown in FIG. **30**B, in response to the gesture **3002**, the device reduces a display size of the message region **3003** (and for other message regions that include text-only content).

[0874] In this way, users can easily scrunch or squish down content of a first type (e.g., text-only content) within a messaging user interface in order to quickly search for other content having a type other than the first type. For example, a user can quickly search for a desired photograph or video, without having to scroll through pages and pages of text-only content, thereby quickly, efficiently, and intuitively locating desired (non-textual) content. Additionally, in some embodiments, after content has been squished down, timestamps that are displayed in the conversation transcript are easily visible and, thus, users can quickly search through a lengthy conversation transcript to find a relevant time period. In other embodiments, any other user interface could employ the aforementioned features. For example, any user interface that includes content of a variety of content types, such as a web browser user interface (including images, text, videos, etc.), an electronic book user interface (including text, images associated with the text, etc.), and others.

[0875] In some embodiments, in conjunction with reducing the display size of at least some content items having the first content type, the device provides (**3108**) haptic feedback. In some embodiments, haptic feedback is provided whenever display sizes for any of the content items is reduced (to indicate either that the gesture was received or that the gesture/input was "legal.") (e.g., any type a messaging bubble is scrunched down, the device provides haptic feedback).

[0876] In some embodiments, reducing the display size includes (**3110**) reducing the display size in accordance with a determination that a characteristic (distance travelled, space between fingers in a pinch gesture, characteristic intensity of contact) of the first input satisfies first display-size-reduction criteria that are associated with the first content type.

[0877] In some embodiments, after reducing the display size of at least some of the content items having the first content type, the device detects (**3112**), via the touch-sensitive surface, a second input that corresponds to a request to scroll the messaging user interface. In response to detecting the second input, the device scrolls the messaging user interface while continuing to display: at least some of the content items having the first content type with the reduced display size, and content items having the second content type with their respective first sizes. In this way, users are easily able to scroll and search for desired content while keeping some content items at reduced display sizes (in order to assist in more easily locating desired content items).

[0878] In some embodiments, the user is able to provide a series of gestures or one continuous gesture in order to scrunch down display sizes for content within the messaging user interface. For example, in response to gesture **3004**, the device continues to reduced display sizes for content have the first content type (e.g., message region **3003** is further reduced in size as compared to its size in FIG. **30**B).

[0879] In some embodiments, the device detects (**3114**) a third input (e.g., a pinch gesture or a portion thereof, such as gesture **3006**, shown in FIG. **30**C). In response to detecting the third input, the device reduces a display size of content items having the second content type. For example, as shown in FIG. **30**D, in response to gesture **3006** shown in FIG. **30**C, the display size for content items having the second content type is reduced (e.g., message region **3001** is now displayed with a reduced display size in accordance with the gesture **3008**).

[0880] In some embodiments, the messaging user interface includes content items having a third content type (e.g., content included in message region **3009** includes text that is associated with a text-rendering effect). The device, after reducing display size of the at least some of the content items having the first and second content types, detects (**3116**) a fourth input (e.g., a pinch gesture or a portion thereof, such as gesture **3008** shown in FIG. **30**D). In response to detecting the fourth input, the device reduces a display size of at least some of the content items having the third content type. (e.g., as shown in FIG. **30**E, a display size for the message region **3009** is reduced).

[0881] In some embodiments, the messaging user interface includes content items having a fourth content type (e.g., message regions that include graphical content, such as images, maps objects, and other types of graphical content). After reducing display size of the at least some of the content items having the first, second, and third content types, the device detects a fifth input (e.g., a pinch gesture or a portion thereof, such as gesture **3010** shown in FIG. **30**E). In response to detecting the fifth input, the device reduces a display size of at least some of the content items having the fourth content type (e.g., as shown in FIG. **30**F, the device reduces a display size for content included in message region **3011** (an image) and message region **3005** (a maps object).

[0882] In some embodiments, reducing display sizes for the at least some content items having each of the first, second, third, and fourth content types is performed based on a hierarchical order (e.g., a predefined order of impor-

tance) assigned to each of the content types. In other words, some embodiments include at least four different content types that are scrunched down one after another in response to inputs (e.g., pinch gestures or portions of a single pinch gesture). For example, messaging bubbles with only text are scrunched down first, then messaging bubbles that include emojis are scrunched down, followed by messaging bubbles that are associated with a text-rendering effect (e.g., private messages), and then photos that are included in the conversation transcript are scrunched down (in some embodiments, the photos are not included in messaging bubbles).

[0883] In some embodiments, the device receives a new input (e.g., one or more de-pinch gestures, such as gesture **3012**, FIG. **30**F). In response to receiving the new input, the device reverts display size of the at least some content items having the first content type back to the respective first size (as shown in FIG. **30**G display sizes for message regions that include content items having first (**3003**), second (**3001**), and fourth (**3005**) content types are all returned to their respective first/default sizes. In some embodiments, the new input may be utilized to revert display sizes for any content items that have been scrunched down back to their respective first sizes (e.g., as shown in FIGS. **30**-F-**30**G, the de-pinch gesture **3012** is used to quickly increase display sizes for content items having a number of content types). In some embodiments, the user is able to gradually perform the de-pinch gesture **3012** and each content item have each respective content type will revert back to its respective first size at an appropriate time.

[0884] In some embodiments, at any point during method **3100** (or method **3300** below) if a new message is received (and then displayed within a new message region within the messaging user interface), the device displays that message bubble at its respective first size (instead of displaying it as being scrunched down). In this way, users are still able to view new messages.

[0885] It should be understood that the particular order in which the operations in FIGS. **31**A-**31**B have been described is merely one example and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein are also applicable in an analogous manner to method **3100** described above. For example, the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described above with reference to method **3100** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein. For brevity, these details are not repeated here.

[0886] In accordance with some embodiments, FIG. **32** shows a functional block diagram of an electronic device **3200** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, firmware, or a combination thereof to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. **32** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[0887] As shown in FIG. **32**, an electronic device **3200** includes a display unit **3202** configured to display a user interface, a touch-sensitive surface unit **3204** configured to receive contacts, one or more sensor units **3206** for detecting intensities of contacts on the touch-sensitive surface unit **3204**; and a processing unit **3208** coupled with the display unit **3202**, the touch-sensitive surface unit **3204** and the one or more sensor units **3206**. In some embodiments, the processing unit **3208** includes a displaying unit **3210**, an input detecting unit **3212**, a display size reduction unit **3214**, a haptic feedback providing unit **3216**, and a display size reverting unit **3218**.

[0888] The processing unit **3208** is configured to display (e.g., with the displaying unit **3210**), on the display (e.g., the display unit **3202**), a messaging user interface that includes a plurality of content items. In some embodiments, the plurality of content items includes content items having a first content type, the plurality of content items includes content items having a second content type that is distinct from the first content type, and a respective content item in the plurality of content items is displayed with a respective first size. While displaying the messaging user interface, the processing unit is configured to: detect, via the touch-sensitive surface, a first input and, in response to detecting the first input, reduce a display size of at least some content items having the first content type while continuing to display content items having the second content type with their respective first size.

[0889] In accordance with some embodiments of the electronic device **3200**, the processing unit is configured to: after reducing the display size of at least some of the content items having the first content type, detecting, via the touch-sensitive surface, a second input (e.g., with the input detecting unit **3212**) that corresponds to a request to scroll the messaging user interface; and, in response to detecting the second input, scrolling the messaging user interface while continuing to display: at least some of the content items having the first content type with the reduced display size, and content items having the second content type with their respective first sizes (e.g., with the displaying unit **3210**).

[0890] In accordance with some embodiments of the electronic device **3200**, the processing unit is further configured to: in conjunction with reducing the display size of at least some content items having the first content type, provide haptic feedback (e.g., with the haptic feedback providing unit **3216**).

[0891] In accordance with some embodiments of the electronic device **3200**, the processing unit is further configured to: receive a new input; and, in response to receiving the new input, revert display size (e.g., with the display size reverting unit **3218**) of the at least some content items having the first content type back to the respective first size.

[0892] In accordance with some embodiments of the electronic device **3200**, reducing the display size includes reducing the display size in accordance with a determination that a characteristic of the first input satisfies first display-size-reduction criteria that are associated with the first content type (e.g., with the display size reducing unit **3214**).

[0893] In accordance with some embodiments of the electronic device **3200**, the processing unit is further configured to: detect a third input (e.g., with the input detecting unit

3212) and, in response to detecting the third input, reduce a display size of content items having the second content type (e.g., with the display size reducing unit **3214**).

[0894] In accordance with some embodiments of the electronic device **3200**, the messaging user interface includes content items having a third content type, and the processing unit is further configured to: after reducing display size of the at least some of the content items having the first and second content types, detect a fourth input (e.g., with the input detecting unit **3212**) and, in response to detecting the fourth input, reduce a display size of at least some of the content items having the third content type (e.g., with the display size reducing unit **3214**).

[0895] In accordance with some embodiments of the electronic device **3200**, the messaging user interface includes content items having a fourth content type, and the processing unit is further configured to: after reducing display size of the at least some of the content items having the first, second, and third content types, detect a fifth input (e.g., with the input detecting unit **3212**); and, in response to detecting the fifth input, reduce a display size of at least some of the content items having the fourth content type (e.g., with the display size reducing unit **3214**).

[0896] In accordance with some embodiments of the electronic device **3200**, reducing display sizes for the at least some content items having each of the first, second, third, and fourth content types is performed based on a hierarchical order assigned to each of the content types.

[0897] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[0898] The operations described above with reference to FIGS. **31**A-**31**B are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **32**. For example, some operations are optionally implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

[0899] FIGS. **33**A-**33**B are flow diagrams illustrating a method **3300** of quickly locating different types of content in a messaging application, in accordance with some embodiments. The method **3300** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display and a touch-sensitive surface. In some embodiments, the display is a touch screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **3300** are, optionally, combined and/or the order of some operations is, optionally, changed.

[0900] As described below, the method **3300** provides an intuitive way to locate different types of content in a messaging application. The method produces more efficient human-machine interfaces by allowing users to use a simple gesture to quickly scale down display sizes for content in a messaging application, so that users are able to quickly locate desired content (e.g., users can scale down all text-only content in order to quickly locate emojis, photos, videos, or other types of content that may have been received a long time ago). For battery-operated devices, the method helps to conserve power and increase the time between battery charges (e.g., by allowing users to quickly locate desired content instead forcing users to employ inefficient and battery-draining techniques). Furthermore, allowing users to quickly locate desired content enhances the operability of the devices and makes user-device interfaces (e.g., in the messaging application) more efficient by allowing users to easily locate desired content in a potentially large and difficult to search conversation transcript. For example, the user need not scroll through pages and pages of content in the conversation transcript and can instead simply provide intuitive gestures to easily scale down content so that desired content is easily located.

[0901] The device displays (**3302**), on the display, a messaging user interface that includes a plurality of content items. In some embodiments, the messaging user interface includes a conversation transcript of a messaging session between a user of the electronic device and at least one other user, as shown in FIG. **30**A. In some embodiments, the plurality of content items includes content items having a first content type. For example, each content item of the first content type is text-based and does not include any emojis or other text-rendering effects (such as making the text appear or disappear in response to a gesture over a content item, also referred to herein as an invisible ink effect or a private message). In some embodiments, the first content type includes text-only messages sent and received via the messaging user interface. In some embodiments, a content item corresponds to content included in a single UI element displayed in the messaging user interface (e.g., a single message region or bubble). Message region **3003** is a one example shown in FIG. **30**A of a content item that includes content of the first content type.

[0902] In some embodiments, the plurality of content items includes content items having a second content type that is distinct from the first content type. For example, the second content type corresponds to messages containing content other than text-only content, such as emojis or graphical content sent and received via the message user interface, such as camera images, screenshots, maps objects, objects with text-rendering effects, and the like. In some embodiments, content items having the second content type include message regions that include text and emojis (e.g., message region **3001**, FIG. **30**A). As described in more detail below, the messaging user interface may include content items having a third content type (e.g., the content included in message region **3009**, FIG. **30**C) and a fourth

content type (e.g., the content included in message region **3005** and image **3011**, FIGS. **30**A and **30**D) as well.

[0903] In some embodiments, a respective content item in the plurality of content items is displayed with a respective first size. In some embodiments, each content item is displayed with a respective default display size. In some embodiments, different default sizes are associated with the content types (e.g., pictures and other graphical content have a different default display size than text-only content items).

[0904] While displaying the messaging user interface (and, in some embodiments, while a focus selector is over the messaging user interface), the device detects (**3304**), via the touch-sensitive surface, a first input. In some embodiments, the first input (e.g., a first portion of a pinch gesture, such as gesture **3002** shown in FIG. **30**A) corresponds to a first request to reduce a display size (or a magnification level) for at least a portion of the content items in the plurality of content items. In some embodiments, the first request is received while some textual-only content is displayed within the messaging user interface (e.g., the message regions that include text-only content including message region **3003**, as shown in FIG. **30**A).

[0905] In response to detecting the first input, the device reduces (**3306**) a display size of at least some content items having the first content type, such that a first content item having the first content type is reduced to a respective second size that is smaller than the respective first size by a predefined first display-size-reduction factor (e.g., content included in the message region **3003** is reduced from a first size, FIG. **30**A, and then to a second size, FIG. **30**B). In response to detecting the first input, the device also reduces (**3306**) a display size of at least some content items having the second content type, such that a second content item having the second content type is reduced to a respective third size that is smaller than the respective first size by a predefined second display-size-reduction factor (e.g., content included in the message region **3001** is reduced from a first size, FIG. **30**C, to a second size, FIG. **30**D). In some embodiments, the reduction in size for the message region **3001** is performed in response to gesture **3002** and/or **3004**. In some embodiments, the predefined second display-size-reduction factor is less than the predefined first display-size-reduction factor. Stated another way, the content items having the first content type are reduced to a smaller display size relative to the content items having the second content type (the content items have the first content type are scrunched down more than the content items having the second content type). In some embodiments, the content items having the second content type are only slightly reduced in size, so as to provide a visual cue to the user that the content items having the second content type can be further reduced in size by providing additional inputs (e.g., additional pinch gestures). For example, as shown in FIG. **30**D, message regions that include text-only content (e.g., message region **3003**, FIG. **30**D) are scrunched down more than message regions that include content in addition to text (e.g., message region **3001**, FIG. **30**D).

[0906] Operations **3308** and **3310** correspond to operations **3108** and **3110**, respectively, discussed above in reference to FIG. **31**A. As such, the descriptions above in reference to operations **3108** and **3110** are applicable to operations **3308** and **3310** as well.

[0907] In some embodiments, after reducing the display size of at least some of the content items having the first content type and at least some of the content items having the second content type, the device detects (**3312**), via the touch-sensitive surface, a second input that corresponds to a request to scroll the messaging user interface. In response to detecting the second input, the device scrolls the messaging user interface while maintaining displayed sizes of content items having the first content type at the respective second size and content items having the second content type at the respective third size.

[0908] In some embodiments, the device detects (**3314**) a third input and, in response, the device further reduces a display size of content items having the second content type (e.g., as shown in FIG. **30**E, the device further reduces message region **3001** and the contained included therein in response to a continuation of or new pinch gesture, such as gesture **3008**).

[0909] Operations **3316**, **3318**, **3320**, and **3322** correspond to operations **3116**, **3118**, **3120**, and **3122**, respectively, discussed above in reference to FIG. **31**A. As such, the descriptions above in reference to operations **3116**, **3118**, **3120**, and **3122** are applicable to operations **3316**, **3318**, **3320**, and **3322** as well.

[0910] It should be understood that the particular order in which the operations in FIGS. **33**A-**33**B have been described is merely one example and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein are also applicable in an analogous manner to method **3300** described above. For example, the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described above with reference to method **3300** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein. For brevity, these details are not repeated here.

[0911] In accordance with some embodiments, FIG. **34** shows a functional block diagram of an electronic device **3400** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, firmware, or a combination thereof to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. **34** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[0912] As shown in FIG. **34**, an electronic device **3400** includes a display unit **3402** configured to display a user interface, a touch-sensitive surface unit **3404** configured to receive contacts, one or more sensor units **3406** for detecting intensities of contacts on the touch-sensitive surface unit **3404**; and a processing unit **3408** coupled with the display unit **3402**, the touch-sensitive surface unit **3404** and the one or more sensor units **3406**. In some embodiments, the processing unit **3408** includes a displaying unit **3410**, an

input detecting unit **3412**, a display size reduction unit **3414**, a haptic feedback providing unit **3416**, and a display size reverting unit **3418**.

[0913] The processing unit **3408** is configured to display (e.g., with the displaying unit **3410**), on the display (e.g., display unit **3402**), a messaging user interface that includes a plurality of content items. In some embodiments, the plurality of content items includes content items having a first content type, the plurality of content items includes content items having a second content type that is distinct from the first content type, and a respective content item in the plurality of content items is displayed with a respective first size. While displaying the messaging user interface, detect (e.g., with the input detecting unit **3412**), via the touch-sensitive surface, a first input and, in response to detecting the first input: reduce a display size (e.g., with the display size reducing unit **3414**) of at least some content items having the first content type, such that a first content item having the first content type is reduced to a respective second size that is smaller than the respective first size by a predefined first display-size-reduction factor; and reduce a display size (e.g., with the display size reducing unit **3414**) of at least some content items having the second content type, such that a second content item having the second content type is reduced to a respective third size that is smaller than the respective first size by a predefined second display-size-reduction factor. In some embodiments, the predefined second display-size-reduction factor is less than the predefined first display-size-reduction factor.

[0914] In accordance with some embodiments of the electronic device **3400**, the processing unit is configured to: after reducing the display size of at least some of the content items having the first content type, detecting, via the touch-sensitive surface, a second input (e.g., with the input detecting unit **3412**) that corresponds to a request to scroll the messaging user interface; and, in response to detecting the second input, scrolling the messaging user interface while continuing to display: at least some of the content items having the first content type with the reduced display size, and content items having the second content type with their respective first sizes (e.g., with the displaying unit **3410**).

[0915] In accordance with some embodiments of the electronic device **3400**, the processing unit is configured to: detect a third input (e.g., with the input detecting unit **3412**) and, in response to detecting the third input, further reduce display size of each content item having the second content type (e.g., with the display size reducing unit **3414**).

[0916] In accordance with some embodiments of the electronic device **3400**, the processing unit is further configured to: in conjunction with reducing the display size of at least some content items having the first content type, provide haptic feedback (e.g., with the haptic feedback providing unit **3416**).

[0917] In accordance with some embodiments of the electronic device **3400**, the processing unit is further configured to: receive a new input; and, in response to receiving the new input, revert display size (e.g., with the display size reverting unit **3418**) of the at least some content items having the first content type back to the respective first size.

[0918] In accordance with some embodiments of the electronic device **3400**, reducing the display size includes reducing the display size in accordance with a determination that a characteristic of the first input satisfies first display-size-reduction criteria that are associated with the first content type (e.g., with the display size reducing unit **3414**).

[0919] In accordance with some embodiments of the electronic device **3400**, the processing unit is further configured to: detect a third input (e.g., with the input detecting unit **3412**) and, in response to detecting the third input, reduce a display size of content items having the second content type (e.g., with the display size reducing unit **3414**).

[0920] In accordance with some embodiments of the electronic device **3400**, the messaging user interface includes content items having a third content type, and the processing unit is further configured to: after reducing display size of the at least some of the content items having the first and second content types, detect a fourth input (e.g., with the input detecting unit **3412**) and, in response to detecting the fourth input, reduce a display size of at least some of the content items having the third content type (e.g., with the display size reducing unit **3414**).

[0921] In accordance with some embodiments of the electronic device **3400**, the messaging user interface includes content items having a fourth content type, and the processing unit is further configured to: after reducing display size of the at least some of the content items having the first, second, and third content types, detect a fifth input (e.g., with the input detecting unit **3412**); and, in response to detecting the fifth input, reduce a display size of at least some of the content items having the fourth content type (e.g., with the display size reducing unit **3414**).

[0922] In accordance with some embodiments of the electronic device **3400**, reducing display sizes for the at least some content items having each of the first, second, third, and fourth content types is performed based on a hierarchical order assigned to each of the content types.

[0923] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[0924] The operations described above with reference to FIGS. **33**A-**33**B are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **34**. For example, some operations are optionally implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

Integrated Messaging

[0925] FIGS. **35**A-**35**AP illustrate exemplary user interfaces for integrating a digital camera into a messaging application in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIGS. **42**A-**42**D. For convenience of explanation, some of the embodiments will be discussed with reference to operations performed on a device with a touch-sensitive display system **112**. In such embodiments, the focus selector is, optionally: a respective finger or stylus contact, a representative point corresponding to a finger or stylus contact (e.g., a centroid of a respective contact or a point associated with a respective contact), or a centroid of two or more contacts detected on the touch-sensitive display system **112**. However, analogous operations are, optionally, performed on a device with a display **450** and a separate touch-sensitive surface **451** in response to detecting the contacts on the touch-sensitive surface **451** while displaying the user interfaces shown in the figures on the display **450**, along with a focus selector.

[0926] FIGS. **35**A-**35**W and **35**AL-**35**AP illustrate exemplary user interface **3500** for a messaging application which includes secondary conversation transcript **3503** (also referred to as "conversation transcript **3503**"), message-input area **3502**, either of application expansion affordance **3702** or three activatable affordances—digital image affordance **3504**, digital canvas affordance **3506**, and application affordance **3508**—either of digital keyboard **3501** or digital image tray **3806**, which includes live preview image **3514** from an associated digital camera, including image capture affordance **3516** and camera switching affordance **3505** for switching the live preview image between two or more associated digital cameras, and previously captured digital images **3518**. Secondary conversation transcript **3503** includes messages from participants of a corresponding messaging session, including the user of portable multifunction device **100** and other users included in the messaging session. Each of the other users included in the messaging transcript are represented by an avatar (e.g., avatar **3510** for "Abe") displayed in stack of avatars **4002**.

[0927] FIGS. **35**X-**35**AK illustrate exemplary user interface **3509** for editing digital images, optionally operated within the messaging application, which includes display of digital image **3518-4**, editing affordances that enable different editing modes—pencil affordance **3552**, magnification loupe affordance **3554**, text affordance **3556**, and handwriting affordance **3558**—color selection affordances **3548** for setting a color for an editing affordance tool, size selection affordance **3550** for setting the size of a line, text, or handwriting made on the digital image, canceling affordance **3549** for canceling edits to the digital image, and saving affordance **3551** for saving edits to the digital image.

[0928] FIGS. **35**A-**35**I illustrate two exemplary embodiments for capturing a digital image and posting the captured image to the messaging transcript (e.g., the messaging session) without leaving the messaging application. In both embodiments, a digital camera is accessed in a messaging user interface displaying conversation transcript **3503** and keyboard **3501**, as illustrated in FIG. **35**A, by detecting activation of digital image affordance **3504** by contact **3512** in FIG. **35**B. In response, digital image tray **3806** replaces digital keyboard **3501** in FIGS. **35**C and **35**H.

[0929] In a first embodiment, device **100** detects a tap gesture including contact **3512** on image capture affordance **3516** in FIG. **35**D. In response, device **100** captures live preview image **3514**, creating digital image **3518-5**, and places the image (e.g., a representation of the image) in message-input area **3502**, which expands to accommodate the image, in FIG. **35**E. The device then detects a tap gesture including contact **3522** on message-content posting affordance **3520** in FIG. **35**F. In response, device **100** posts captured digital image **3518-5** to the messaging session, displaying the image in conversation transcript **3503** in FIG. **35**G.

[0930] In a second embodiment, device **100** detects a press gesture including contact **3524** on image capture affordance **3516** in FIG. **35**H. Device **100** then detects an increase in the intensity of contact **3524** above a predefined intensity threshold (e.g., IT_L or IT_D) and, in response, captures live preview image **3514**, creating digital image **3518-5** in FIG. **35**I. In contrast to the first embodiment—where the intensity of contact **3512** did not increase above the predefined intensity threshold—device **100** posts captured digital image **3518-5** directly to the messaging session, displaying the image in conversation transcript **3503** in FIG. **35**I, because the intensity of contact **3516** reached the predefined intensity threshold.

[0931] FIGS. **35**J-**350** illustrate an exemplary embodiment where a message is associated with a posted digital image. Device **100** detects a tap gesture including contact **3526** on image capture affordance **3516** in FIG. **35**J. In response, device **100** captures live preview image **3514**, creating digital image **3518-5**, and places the image (e.g., a representation of the image) in message-input area **3502**, which expanded to accommodate the image in FIG. **35**K. The device then detects a tap gesture including contact **3528** in message-input area **3502** in FIG. **35**L. In response, device **100** replaces display of digital image tray **3806** with digital keyboard **3501**, further expands message-input area **3502** to accommodate a message, and displays text cursor **3842** in FIG. **35**M. Device **100** also detects input of message **3530** and displays the message in message-input area **3502**, along with captured digital image **3518-5** in FIG. **35**M. The device then detects a tap gesture including contact **3532** on message-content posting affordance **3520** in FIG. **35**N. In response, device **100** posts captured digital image **3518-5** and message **3530** to the messaging session, displaying the image and message, in message region **3534**, within conversation transcript **3503** in FIG. **35**O. Because message **3530** was posted from message-input area **3502** at the same time as image **3518-5**, message region **3534** is displayed as overlapping with image **3518-5** in FIG. **35**O.

[0932] FIGS. **35**P-**35**Q illustrate an exemplary embodiment where a swipe gesture reveals additional digital images. Device **100** detects a swipe gesture including movement **3538** of contact **3536** to the left, from position **3536-*a*** in FIG. **35**P to position **3536-*b*** in FIG. **35**Q. In response, the device moves digital image tray **3806** to the left, in accordance with movement **3538**, creating the appearance that live preview image **3514** slides off of the left side of touch screen **112** and additional digital images **3518-6** and **3518-7** slide onto the display from the right side of touch screen **112**, in FIG. **35**Q.

[0933] FIGS. **35**R-**35**V illustrate two exemplary embodiments where a previously captured digital image is previewed and posted to the messaging session.

[0934] In a first embodiment, device **100** detects a press gesture including contact **3540** on previously captured digi-

tal image **3518-4** in FIG. **35**R. Device **100** then detects an increase in the intensity of contact **3540** above a first predefined intensity threshold (e.g., IT_L) and, in response, displays enlarged preview **3507** of image **3518-4** over portions of digital image tray **3806** and conversation transcript **3503** in FIG. **35**S. The device then detects a decrease in the intensity of contact **3540** and, in response, ceases display of enlarged preview **3507** in FIG. **35**T.

[0935] In a second embodiment, device **100** detects a press gesture including contact **3544** on previously captured digital image **3518-4**, and then an increase in the intensity of contact **3544** above a first predefined intensity threshold (e.g., IT_L), in FIG. **35**U. In response, the device displays enlarged preview **3507** of image **3518-4** over portions of digital image tray **3806** and conversation transcript **3503** in FIG. **35**U. The device then detects a further increase in the intensity of contact **3544** above a second predefined intensity threshold (e.g., IT_D) and, in response, and places the image in message-input area **3502** in FIG. **35**V. Previously captured digital image **3518-4** may now be posted to the messaging session upon detection of an input (e.g., tap gesture) activating message-content posting affordance **3520**.

[0936] FIGS. **35**W-**35**AN illustrate an exemplary embodiment where a digital image is edited prior to posting the image to the messaging session. Device **100** detects a tap gesture including contact **3546** on digital image **3518-4**, while the image is displayed in message-input area **3502**, in FIG. **35**W. In response, the device opens image-editing user interface **3509**, displaying editable representation **3518-4***a* of digital image **3518-4**, in FIG. **35**X.

[0937] The device detects activation (**3560**) of pencil affordance **3552**, in FIG. **35**Y, and drawing of mustache **3562**, in FIG. **35**Z. The device then detects activation (**3564**) of magnification loupe affordance **3554**, in FIG. **35**AA, and placement of magnification loupe **3566**, in FIG. **35**AB. The magnification of loupe **3566** is increased by movement **3572** of tab **3568** from position **3568-***a* in FIG. **35**AC to position **3568-***b* in FIG. **35**AD. The size of loupe **3566** is increased by movement **3574** of tab **3570** from position **3570-***a* in FIG. **35**AE to position **3570-***b* in FIG. **35**AF. The device then detects activation (**3576**) of text affordance **3556**, in FIG. **35**AG, and input of text **3578** in FIG. **35**AH. The device then detects activation (**3580**) of handwriting affordance **3558**, in FIG. **35**AI, and input of handwriting **3582** in FIG. **35**AJ.

[0938] The device then detects a tap gesture including contact **3586** on saving affordance **3551** in FIG. **35**AK. In response, the device returns to messaging user interface **3500** and displays edited digital image **3518-4***a* in message-input area **3502** in FIG. **35**AL. The device then detects a tap gesture including contact **3588** on message-content posting affordance **3520** in FIG. **35**AM. In response, device **100** posts edited digital image **3518-4***a* to the messaging session, displaying the image in conversation transcript **3503** in FIG. **35**AN.

[0939] FIGS. **35**A**0**-**35**AP illustrate a third exemplary embodiment where a previously captured digital image is previewed and posted to the messaging session. Device **100** detects a press gesture including contact **3590** on previously captured digital image **3518-4**, and then an increase in the intensity of contact **3590** above a first predefined intensity threshold (e.g., IT_L), in FIG. **35**AO. In response, the device displays enlarged preview **3507** of image **3518-4** over portions of digital image tray **3806** and conversation transcript **3503** in FIG. **35**AO. The device then detects a further increase in the intensity of contact **3590** above a second predefined intensity threshold (e.g., IT_D) and, in response, and posts previously captured digital image **3518-4** directly to the messaging session, displaying the image in conversation transcript **3503** in FIG. **35**AP.

[0940] FIGS. **36**A-**36**AL illustrate exemplary user interfaces for integrating search functionality, and posting rich content, in a messaging application, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIGS. **44**A-**44**D. For convenience of explanation, some of the embodiments will be discussed with reference to operations performed on a device with a touch-sensitive display system **112**. In such embodiments, the focus selector is, optionally: a respective finger or stylus contact, a representative point corresponding to a finger or stylus contact (e.g., a centroid of a respective contact or a point associated with a respective contact), or a centroid of two or more contacts detected on the touch-sensitive display system **112**. However, analogous operations are, optionally, performed on a device with a display **450** and a separate touch-sensitive surface **451** in response to detecting the contacts on the touch-sensitive surface **451** while displaying the user interfaces shown in the figures on the display **450**, along with a focus selector.

[0941] FIGS. **36**A-**36**V illustrate exemplary user interface **3500** for a messaging application which includes conversation transcript **3503**, message-input area **3502**, either of application expansion affordance **3702** or three activatable affordances—digital image affordance **3504**, search affordance **3602**, and application affordance **3508**—optionally, either of digital keyboard **3501** or search tray **3629**, which includes content (e.g., **3606**, **3608**, and **3610**) that can be posted to the messaging session corresponding to conversation transcript **3503**. Conversation transcript **3503** includes messages and content from participants of a corresponding messaging session, including the user of portable multifunction device **100** and other users included in the messaging session. Each of the other users included in the messaging transcript are represented by an avatar (e.g., avatar **3510** for "Abe") displayed in stack of avatars **4002**.

[0942] FIGS. **36**A-**36**S illustrate two exemplary embodiments for posting multimedia content stored on the electronic device and/or multimedia content recently accessed on the device, without leaving the messaging application. Multimedia content is accessed in a messaging user interface displaying conversation transcript **3503** and keyboard **3501**, as illustrated in FIG. **36**A, by detecting activation of search affordance **3602** by contact **3604** in FIG. **36**B. In response, search tray **3629**, including multimedia content that was recently accessed on the device—digital recording **3606**, social media entry **3608**, and digital image **3610**—replaces digital keyboard **3501** in FIG. **36**C.

[0943] In a first embodiment, device **100-1** places digital recording **3606** in message-input area **3520**, in FIG. **36**E, in response to detecting a tap gesture including contact **3614** on the digital recording in FIG. **36**D. Responsive to detecting a tap gesture including contact **3618** on message-content posting affordance **3520** in FIG. **36**F, device **100-1** posts the digital recording to the messaging session, displaying the recording in conversation transcript **3503** in FIG. **36**G.

[0944] Device **100-2**, corresponding to a second user included in the messaging session corresponding to conver-

sation transcript **3503**, as illustrated in FIG. **36**H, receives digital recording **3616** in FIG. **36**I. Responsive to detecting a tap gesture on digital recording **3616**, including contact **3622** in FIG. **36**J, device **100-2** plays the digital recording in FIG. **36**K, as illustrated by sound waves **3624**.

[0945] A second embodiment also illustrates an exemplary embodiment where a swipe gesture reveals additional multimedia content recently accessed by the device. Device **100-1** detects a swipe gesture including movement **3628** of contact **3626** to the left, from position **3626-*a*** in FIG. **36**L to position **3626-*b*** in FIG. **36**M. In response, the device moves search tray **3629** to the left, in accordance with movement **3628**, creating the appearance that digital image **3608** slides off the left side of touch screen **112** and additional multimedia content—news article **3628** and movie preview **3630**—slides onto the display from the right side of touch screen **112**, in FIG. **36**M.

[0946] Device **100-1** detects a press gesture including contact **3632** on news article **3628**, associated with a webpage previously accessed by device **100-1**, in FIG. **36**N. Device **100** then detects an increase in the intensity of contact **3632** above a predefined intensity threshold (e.g., IT_L or IT_D) and, in response, posts representation **3634** of the news article, including an image associated with the article, an organization associated with the website (the "Washington Gazette"), and a title of the news article ("Fireball in Wisconsin") directly to the messaging session, displaying representation **3634** in conversation transcript **3503** in FIG. **36**O.

[0947] FIGS. **36**P-**36**S illustrate an exemplary embodiment where content from the internet is accessed from within the messaging user interface. Device **100-1** detects a tap gesture, including contact **3636**, on news article **3634** displayed in conversation transcript **3503**, in FIG. **36**P. In response, device **100-1** accesses the web page associated with the news article in area **3638**, displayed over portions of search tray **3629** and conversation transcript **3503**, in FIG. **36**Q. Device **100-1** then displays more of the news article from the web site, in area **3638**, responsive to detecting a swipe gesture, including movement **3642** of contact **3640** from position **3640-*a*** in FIG. **36**R to position **3640-*b*** in FIG. **36**S.

[0948] FIGS. **36**T-**36**V illustrate an exemplary embodiment where multimedia content on the internet is searched from within the messaging user interface. Device **100-1** initiates a search in response to detecting a tap gesture, including contact **3612**, on search-input area **3612**, in FIG. **36**T. In response, the device replaces search tray **3629** with digital keyboard **3501** in FIG. **36**U. Device **100-1** then detects input of search term **3646** ("Meteorite") in FIG. **36**U. In response, digital keyboard **3501** is replaced by search tray **3629**, including content from the internet-news article **3628**, picture **3648**, and wiki page **3650**—in FIG. **36**V.

[0949] FIGS. **36**W-**36**AL illustrate two exemplary embodiments in which multimedia content is searched and posted to a messaging session from a search user interface run within the messaging application. FIG. **36**W illustrates an exemplary user interface **3500** for a messaging application which includes conversation transcript **3503**, message-input area **3502**, three activatable affordances-digital image affordance **3504**, digital canvas affordance **3506**, and application affordance **3508**, and digital keyboard **3501**.

[0950] Device **100-1** detects a tap gesture, including contact **3652**, on application affordance **3508** in FIG. **36**X. In response, digital keyboard **3501** is replaced with application selection tray **3654**, including launch icons **3601**, **3603**, **3605**, **3607**, **3609**, **3611**, **3613**, and **3615** for applications operable within the messaging application, in FIG. **36**Y. Responsive to activation of launch icon **3607** for a search application by a tap gesture including contact **3656**, in FIG. **36**Z, the device replaces display of messaging user interface **3500** with default search user interface **3658**, in FIGS. **36**AA and **36**AD.

[0951] In a first embodiment, default search user interface **3658** displays suggested content associated with device **100-1**-location **3662**, news article **3664** from an open web page, digital recording **3666**, recently shared news article **3668**, recently shared movie trailer **3670** from the internet, and recently shared digital image **3672**—in FIG. **36**AA. Responsive to selection of movie trailer **3670** by a tap gesture including contact **3674**, in FIG. **36**AB, the device switches back to messaging user interface **3500** and posts movie trailer **3670** to the messaging session, displaying the trailer in conversation transcript **3503**, in FIG. **36**AC.

[0952] In a second embodiment, content from the internet, accessed via a search within the messaging search user interface, is posted to the messaging session without leaving the messaging application. Device **100-1** detects a tap gesture including contact **3676** on search-input area **3660** of default search user interface **3658**, in FIG. **36**AD. In response, the device displays trending search user interface **3659**, including suggested content trending on the internet—digital recordings **3678** and **3680**, and news articles **3668** and **3669**—and digital keyboard **3501**, in FIG. **36**AE. Responsive to receiving input of search term "Meteorites," the device displays search result user interface **3661**, including multimedia content from the internet relating to meteorites-news articles **3664**, **3678**, and **3680**, and movie trailers **3670**, **3682**, and **3684** and category filter affordances **3617**, **3619**, **3621**, **3623**, and **3625** for filtering the search results for specific categories of search results, in FIG. **36**AF.

[0953] Additional search results are displayed in response to device **100-1** detecting a swipe gesture including movement **3688** of contact **3686** to the left, from position **3686-*a*** in FIG. **36**AG to position **3686-*b*** in FIG. **36**AH. In response, the device moves movie trailer search results **3670**, **3682**, and **3684** to the left, in accordance with movement **3688**, creating the appearance that movie trailer **3670** slides off of the left side of touch screen **112** and additional movie trailer **3688** slides onto the display from the right side of touch screen **112**, in FIG. **36**AH.

[0954] Responsive to selection of movie trailer **3690**, by detection of a tap gesture including contact **3690** in FIG. **36**AI, device **100-1** switches back to messaging user interface **3500** and places movie trailer **3684** in area **3692** of expanded message-input area **3502**, which includes cancel icon **3694** for canceling selection of movie trailer **3684**, in FIG. **36**AJ. Movie trailer **3684** is then posted to the messaging session in response to detecting a tap gesture, including contact **3696**, on message-content posting affordance **3520** in FIG. **36**AK. Movie trailer **3684** is then displayed in conversation transcript **3503**, in FIG. **36**AL.

[0955] FIGS. **37**A-**37**DJ illustrate exemplary user interfaces for integrating interactive applications in a messaging application in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIGS. **46**A-**46**C,

48A-**48**D, **50**A-**50**C, **52**A-**52**C, **54**A-**54**C, **56**A-**56**B, and **58**. For convenience of explanation, some of the embodiments will be discussed with reference to operations performed on a device with a touch-sensitive display system **112**. In such embodiments, the focus selector is, optionally: a respective finger or stylus contact, a representative point corresponding to a finger or stylus contact (e.g., a centroid of a respective contact or a point associated with a respective contact), or a centroid of two or more contacts detected on the touch-sensitive display system **112**. However, analogous operations are, optionally, performed on a device with a display **450** and a separate touch-sensitive surface **451** in response to detecting the contacts on the touch-sensitive surface **451** while displaying the user interfaces shown in the figures on the display **450**, along with a focus selector.

[0956] FIGS. **37**A-**37**DJ illustrate exemplary electronic devices **100-1**, operated by "Andrew," and **100-2**, operated by "Abe." The user interfaces on devices **100-1** and **100-2** include time stamp **404**, allowing inputs made at a particular time on one device to be matched with the effects of those inputs on the other device. For example, placement of 'O' **3792** in tic-tac-toe user interface **3782** at 9:34 AM on device **100-1**, in FIGS. **37**AX-**37**AY, corresponds to the display of tic-tac-toe notification **3703** and tic-tac-toe application object **3705** in third conversation transcript **3700** (also referred to as "conversation transcript **3700**" or "transcript **3700**") on device **100-2** at 9:34 AM in FIG. **37**BF.

[0957] FIGS. **37**A-**37**AM illustrate an exemplary embodiment of an interactive reservation application operated within a messaging application. Operation of the interactive application includes display of a full-screen application user interface that replaces display of the messenger user interface, and which is accessible to users included in the messaging session through an application object displayed in the conversation transcript.

[0958] FIGS. **37**A and **37**J illustrate exemplary user interface **3500** for a messaging application on devices **100-1** and **100-2**, respectively. User interface **3500** includes conversation transcript **3700**, message-input area **3502**, either of application expansion affordance **3702** or three activatable affordances—digital image affordance **3504**, digital canvas affordance **3506**, and application affordance **3508**—optionally, one of digital keyboard **3501** for inputting messages into message-input area **3502**, application selection tray **3654**, and application swipe tray **3892**. Conversation transcript **3700** includes messages from participants of a corresponding messaging session, including the user of the particular portable multifunction device and other users included in the messaging session. Each of the other users included in the messaging transcript are represented by an avatar (e.g., avatar **3510** for "Abe" and avatar **3511** for "Andrew").

[0959] FIGS. **37**A-**37**G illustrate activation of an interactive application for making a reservation. Application expansion affordance **3702** is expanded to display three activatable affordances—digital image affordance **3504**, digital canvas affordance **3506**, and application affordance **3508**—in FIG. **37**C, in response to device **100-1** detecting a tap gesture including contact **3702** on application expansion affordance **3702** in FIG. **37**B. The device then displays application swipe tray **3892** in FIG. **37**E, responsive to detecting a tap gesture including contact **3706** on application affordance **3508** in FIG. **37**D. Application swipe tray **3892** includes launch icon **3708** for an interactive reservations application and application menu toggle affordance **3627** for switching between application swipe tray **3892** and application selection tray **3654**.

[0960] The interactive reservation application is launched within the messaging application in FIG. **38**G when the device detects a tap gesture including contact **3710** on reservation launch icon **3708** in FIG. **37**F. Upon launch, the device displays user interface **3712** for the reservation application, including input affordances **3720** for selecting a location around which to search, **3722-1** and **3722-2** for setting parameters of a search, **3718** for executing a search, and **3724** for selecting a reservation. The user interface also includes canceling affordance **3714** for closing the user interface without selecting reservation.

[0961] FIGS. **37**H-**37**AC illustrate selection and modification of a reservation using the interactive reservation application. Device **100-1** detects selection of a reservation at "Joe's Bistro at 6:45 PM" by a tap gesture including contact **3726** on reservation affordance **3724-1** in FIG. **37**H at 9:27 AM. In response, the device replaces display of reservation application user interface **3712** with messaging user interface **3500**. Device **100-1** also displays reservation application object **3728**, which displays information on the reservation (e.g., that the reservation is for 2 people at 6:45 PM at Joe's Bistro), on the right-hand side of conversation transcript **3700**, indicating that the reservation was initially made by device **100-1**.

[0962] Device **100-1** also transmits information to device **100-2** that a reservation was made in the reservation application. In response to receiving the information transmitted from device **100-1**, device **100-2** displays a corresponding reservation application object **3728** on the left-hand side of corresponding conversation transcript **3700**, indicating that another device made the initial reservation. Reservation application object includes indication **3730** that the object is associated with a reservation application. Device **100-2** displays digital keyboard **3501** in FIG. **37**M, responsive to a tap gesture including contact **3732** on message-input area **3502** in FIG. **37**L. The device then posts message **3736**, indicating the reservation time is inconvenient for the Abe, to the messaging session, as displayed in conversation transcript **3700** in FIG. **370**, responsive to receiving input from digital keyboard **3501** and detecting a tap gesture including contact **3734** on message posting affordance **3502** in FIG. **37**N.

[0963] Device **100-2** then detects activation of the reservation application session by a tap gesture including contact **3738** on reservation application object **3728** displayed at location **3728**-*a* in conversation transcript **3700** in FIG. **37**P. Responsive to activation, the device displays reservation user interface **3712** in FIG. **37**Q. The user interface includes input affordances **3740-1**, **3740-2**, and **3742** for changing the time, number of patrons, or location of the reservation. Reservation user interface **3712** also includes message-input area **3716** that is separate from message-input area **3501** displayed in message user interface **3500**. Reservation user interface **3712** also includes Andrew's avatar **3511**, corresponding to the other user included in the messaging session. Reservation user interface **3712** also includes exit affordance **3714** to return to the messaging user interface.

[0964] Device **100-2** detects a tap gesture, including contact **3744** in FIG. **37**R, in message-input area **3716**, activating digital keyboard **3501** in FIG. **37**S. The device receives input of message **3746** in FIG. **37**T, asking whether an 8:00

reservation would be alright, and a request to post the message to the messaging session, via a tap gesture including contact **3748** in FIG. **37**U. In response, the device posts the message to the messaging session at 9:29 AM, and ceases to display digital keyboard **3501** in FIG. **37**V. Corresponding device **100-1** receives message **3746** and displays it in conversation transcript in FIG. **37**AE.

[0965] Device **100-1** displays digital keyboard **3501** in FIG. **37**AG in response to a tap gesture, including contact **3758** in FIG. **37**AF, on message-input area **3502**. The device then receives input of reply message **3750** in message input area **3502** in FIG. **37**AH, indicating that 8:00 is fine for the reservation. The message is posted to the messaging session at 9:30 AM via a tap gesture, including contact **3760** on message posting affordance **3520** in FIG. **37**AI, as displayed within conversation transcript **3700** in FIG. **37**AJ.

[0966] Device **100-2** receives reply message **3750** at 9:30 AM, and transiently displays it within reservation user interface **3712** in FIG. **37**W. The device then receives tap inputs changing the time of the reservation to 8:00 PM. The first tap input includes contact **3752** on input affordance **3740-1** in FIG. **37**X, causing the device to display a drop-down menu from input affordance **3740-1**, displaying alternate reservation times, in FIG. **37**Y. The second tap input selects an 8:00 reservation time by contact **3754** on '8:00 PM' in FIG. **37**Z. The updated reservation details are displayed in FIG. **37**AA. Device **100-2** returns to messaging user interface **3500**, in FIG. **37**AC, in response to a tap gesture on exit affordance **3714**, including contact **3756** in FIG. **37**AB. Reservation application object **3728** is updated in response to the change in the reservation time, and has moved in conversation transcript **3700** from position **3728-***a,* as displayed in FIG. **37**P, to position **3728-***b,* as displayed in FIG. **37**AC.

[0967] Movement of reservation application object **3728** from the left-hand side to the right-hand side of conversation transcript **3700** reflects that the user of device **100-2** made the last input in the application session. Movement of reservation application object **3728** down in conversation transcript reflects the temporal order in which the last input was made in the application session (e.g., the original reservation was made before message **3736** was posted to the messaging session, while the reservation update was made after message **3750** was posted to the messaging session). The temporal position of the original reservation (e.g., prior to posting of message **3736**) is archived by display of application archiving icon **3756**.

[0968] In some embodiments, selection of an application archiving icon (e.g., by a tap gesture) causes the device to display information about the particular event being archived (e.g., in some embodiments, tapping on application archiving icon **3756** would cause display of information on the original reservation (e.g., within the conversation transcript or after displaying the application user interface).

[0969] The display of reservation application object **3728** is also updated on device **100-1** in response to the changes to the reservation made by device **100-2**. Device **100-1** ceases to display digital keyboard **3501**, responsive to swipe gesture including movement **3764** of contact **3761** from location **3762-***a* in FIG. **37**AJ to location **3762-***b* in FIG. **37**AK. Device **100-1** then receives information transmitted from device **100-2** about the change to the reservation. In response, device **100-1** updates reservation application object **3728** by moving it from position **3728-***a,* as in FIG. **37**AK, down and left to position **3728-***b,* as in FIG. **37**AK, reflecting that the last input in the application session was made by device **100-2**, after message **3750** was posted to the messaging session. Application archiving icon **3756** is inserted in conversation transcript **3700** at the temporal location previously occupied by the reservation application object (e.g., position **3728-***a*) in FIG. **37**AL.

[0970] FIGS. **37**AO-**37**BS illustrate an exemplary embodiment of an interactive tic-tac-toe application operated within a messaging application. Operation of the interactive application includes display of an application user interface over a portion of the messenger user interface, and which is accessible to users included in the messaging session through an application object displayed in the conversation transcript.

[0971] FIGS. **37**AO and **37**BD illustrate exemplary user interface **3500** for a messaging application on devices **100-1** and **100-2**, respectively. User interface **3500** includes conversation transcript **3700**, message-input area **3502**, three activatable affordances—digital image affordance **3504**, digital canvas affordance **3506**, and application affordance **3508**—optionally, one of digital keyboard **3501** for inputting messages into message-input area **3502**, application selection tray **3654**, and application swipe tray **3892**. Conversation transcript **3700** includes messages from participants of a corresponding messaging session, including the user of the particular portable multifunction device and other users included in the messaging session. Each of the other users included in the messaging transcript are represented by an avatar (e.g., avatar **3510** for "Abe" and avatar **3511** for "Andrew").

[0972] FIGS. **37**AO-**37**AW illustrate activation of an interactive tic-tac-toe application. Responsive to detecting a tap gesture on application affordance **3508**, including contact **3768** in FIG. **37**AO, device **100-1** displays application swipe tray **3892** in FIG. **37**E. Application swipe tray **3892** includes launch icon **3708** for an interactive reservations application and application menu toggle affordance **3627** for switching between application swipe tray **3892** and application selection tray **3654**. The device then detects a swipe gesture to the left in application swipe tray **3892**, including movement **3772** of contact **3770** from position **3770-***a* in FIG. **37**AQ to position **3770-***b* in FIG. **37**AR. In response, the device moves application swipe tray **3892** to the left, in accordance with movement **3772**, creating the appearance that application launch icon **3708** slides off of the left side of touch screen **112** and application launch icon **3774** slides onto the display from the right side of touch screen **112**, in FIG. **37**AR. After completion of the swipe gesture, the device displays application launch icon **3774** for an interactive tic-tac-toe application within application slide tray **3892**, in FIG. **37**AS.

[0973] The interactive tic-tac-toe application is launched within the messaging application in FIG. **37**AU when the device detects a tap gesture on tic-tac-toe launch icon **3774**, including contact **3710** in FIG. **37**F. In response to launching the application, application slide tray is replaced by menu **3778** including options **3780-1** and **3780-2** for playing the game as O or X, respectively. Responsive to detecting selection of 'O' via a tap gesture on affordance **3780-1**, including contact **3782** in FIG. **37**AV, device **100-1** displays tic-tac-toe user interface **3784** over a portion of messaging user interface **3500** in FIG. **37**AW. User interface **3784** includes tic-tac-toe board **3791**, exit affordance **3694** for

closing the user interface, and message-input area **3716**, separate from message-input area **3716**. Device **100-1** also places tic-tac-toe application object **3786** into conversation transcript **3700** responsive to initiation of the tic-tac-toe session.

[0974] Device **100-1** then detects placement of 'O' **3792** in the center square of tic-tac-toe board **3791** in FIG. **37**AY, by a tap gesture including contact **3788** in FIG. **37**AX. Responsive to placing 'O' **3792** on tic-tac-toe board **3791**, device **100-1** places application archiving icon **3790** in conversation transcript **3700**, in FIG. **37**AY, memorializing the temporal location of the move in the transcript. In some embodiments, selecting the application archiving icon **3790** (e.g., by tapping on it) opens tic-tac-toe user interface **3782** in a state that shows the play associated with the temporal location of the archiving icon.

[0975] While device **100-1** is initiating the tic-tac-toe session, device **100-2** displays activity region **3703** including tic-tac-toe icon **3793** in conversation transcript **3700** indicating that the user of another device is contemporaneously initiating a session of an interactive application within the messaging session, as in FIG. **37**BE. Responsive to receiving information that 'O' **3792** was placed on tic-tac-toe board **3791** on device **100-1**, device **100-2** displays application archiving icon **3703** and tic-tac-toe application object **3705** in transcript **3700** in FIG. **37**BF.

[0976] Responsive to detecting a tap gesture on tic-tac-toe application object **3705**, including contact **3707** in FIG. **37**BG, device **100-2** downloads the tic-tac-toe application because it was not already stored on the device, as indicated below tic-tac-toe application object **3705** ("tap to download"). Indicia **3709** of the ongoing download is displayed over tic-tac-toe application object **3705** in FIG. **37**BH. Upon completion of the download, device **100-2** indicates that it the user's turn to move by displaying "your turn" below tic-tac-toe application object **3705** in FIG. **37**BI. The device opens tic-tac-toe user interface partially over transcript **3700** in FIG. **37**BK upon detecting a tap gesture on tic-tac-toe application object **3705**, including contact **3711** in FIG. **37**BJ.

[0977] Device **100-2** then detects placement of 'X' **3794** in the upper right square of tic-tac-toe board **3791** in FIG. **37**BM, by a tap gesture including contact **3713** in FIG. **37**BL. Responsive to placing 'X' **3794** on tic-tac-toe board **3791**, device **100-2** places application archiving icon **3715** in conversation transcript **3700**, in FIG. **37**BM, memorializing the temporal location of the move in the transcript. Device **100-2** also moves the location of tic-tac-toe application object **3705** from position **3705**-*a* in FIG. **37**BL to position **3705**-*b* in FIG. **37**BM, reflecting that the last tic-tac-toe move was made by device **100-2** at a new temporal position in the messaging session.

[0978] Device **100-2** then closes tic-tac-toe user interface **3782** in FIG. **37**BO responsive to a tap gesture on exit affordance **3694**, including contact **3717** in FIG. **37**BN. Device **100-2** displays digital keyboard **3501** in FIG. **37**BP upon detecting a tap gesture on message-input area **3502**, including contact **3719** in FIG. **37**BO. Device **100-2** then posts message **3798** to the messaging session in FIG. **37**BS after receiving input of the message in FIG. **37**BQ and detecting a tap gesture including contact **3721** in FIG. **37**BR.

[0979] Responsive to receiving information that 'X' **3794** was placed on tic-tac-toe board **3791** on device **100-2**, device **100-1** updates display of tic-tac-toe user interface, which was open when the information was received, to display 'X' **3794** on board **3791** in FIG. **37**AZ. Device **100-1** also displays tic-tac-toe archiving icon **3796** at the next temporal position in conversation transcript **3700** in FIG. **37**AZ, and moves tic-tac-toe application object **3786** from position **3786**-*a* in FIG. **37**AY to position **3786**-*b* in FIG. **37**AZ reflecting that the last tic-tac-toe move was made by device **100-2** at a new temporal position in the messaging session.

[0980] Device **100-1** receives message **3798** from device **100-2**, while tic-tac-toe user interface **3782** remains open over messaging user interface **3500**, in FIG. **37**BA. In response, the device transiently displays message **3798** within tic-tac-toe user interface **3782** and places the message in conversation transcript **3700**, shown behind tic-tac-toe user interface **3798** in FIG. **37**BA. Device **100-1** then closes tic-tac-toe user interface **3782** in FIG. **37**BC after detecting a tap gesture on exit affordance **3694**, including contact **3701** in FIG. **37**BB. This reveals conversation transcript **3700**, which includes tic-tac-toe application archiving icons **3790** and **3796**—memorializing moves made in the application by device **100-1** and **100-2**, respectively—tic-tac-toe application object **3786**, indicating by its position on the left-hand side of the transcript that another device (e.g., device**100-2**) made the last move within the application, and prompting the user to make a move ("Your turn")—and message **3798** received while tic-tac-toe user interface **3782** was displayed.

[0981] FIGS. **37**BT-**37**DJ illustrate an exemplary embodiment of an interactive pizza ordering application operated within a messaging application. Operation of the interactive application causes display of an application input area on a portion of the display (e.g., a portion that is sometimes used to display a digital keyboard, application swipe tray, or application selection tray) and an interactive application object, displaying an output of the interactive application, displayed within the conversation transcript of the messaging user interface. The application input area is accessible to users of the messaging session through the interactive application object.

[0982] FIGS. **37**BT and **37**CQ illustrate exemplary user interface **3500** for a messaging application on devices **100-2** and **100-1**, respectively. User interface **3500** includes conversation transcript **3700**, message-input area **3502**, either of application expansion affordance **3702** or three activatable affordances—digital image affordance **3504**, digital canvas affordance **3506**, and application affordance **3508**—optionally, one of digital keyboard **3501** for inputting messages into message-input area **3502**, application selection tray **3654**, and application swipe tray **3892**. Conversation transcript **3700** includes messages from participants of a corresponding messaging session, including the user of the particular portable multifunction device and other users included in the messaging session. Each of the other users included in the messaging transcript are represented by an avatar (e.g., avatar **3510** for "Abe" and avatar **3511** for "Andrew").

[0983] FIGS. **37**BT-**37**CA illustrate activation of an interactive application for ordering a pizza. Three activatable affordances—digital image affordance **3504**, digital canvas affordance **3506**, and application affordance **3508**—are displayed by device **100-2** in FIG. **37**BU, in response to a tap gesture on application expansion affordance **3702**, including contact **3723** in FIG. **37**BT. The device then displays application swipe tray **3892** in FIG. **37**BW, responsive to detect-

ing a tap gesture on application affordance **3508**, including contact **3725** in FIG. **37**BV. Application swipe tray **3892** includes launch icon **3774** for an interactive tic-tac-toe application and application menu toggle affordance **3627** for switching between application swipe tray **3892** and application selection tray **3654**. After detecting a tap gesture on application menu toggle affordance **3627**, including contact **3727** in FIG. **37**BX, device **100-2** displays application selection tray **3654** in FIG. **37**BY, including a plurality of launch icons for applications'launch icon **3601** for a messaging application-specific application store, launch icon **3603** for an interactive tic-tac-toe application, launch icon **3605** for an interactive reservation application, launch icon **3607** for a search application, launch icon **3609** for a digital sticker pack, launch icon **3611** for a live video-streaming application, launch icon **3613** for an interactive pizza ordering application, and launch icon **3615** for an interactive digital music application.

[0984] A pizza ordering application is launched in FIG. **37**CA after device **100-2** detects a tap gesture on launch icon **3613** for the application, including contact **3729** in FIG. **37**BZ. The device displays input area **3731** for the pizza ordering application, which includes input affordances **3733-1**, **3733-2**, and **3733-3** for adding toppings to the pizza, removing toppings from the pizza, and ordering the pizza, respectively, and exit affordance **3694** for terminating display, in FIG. **37**CA. The device also displays pizza ordering application object **3735** in conversation transcript **3700**, which displays the status of the pizza being ordered and serves as a launch icon for the interactive session of the pizza building application within in the messaging session. In FIG. **37**CA, pizza ordering application object **3735** shows that no toppings have been added to the pizza. Device **100-2** sends information to device **100-1** that a session of the pizza ordering application was initiated within the messaging session.

[0985] Device **100-1** receives the information sent from device **100-2** and, in response, displays pizza ordering application object **3735** in conversation transcript **3700** in FIG. **37**CR. The device also displays an indication that "Abe wants to share a pizza" below application object **3735**.

[0986] Device **100-2** then detects a tap gesture on affordance **3733-1** for adding toppings to the pizza, including contact **3737** in FIG. **37**CB, and displays a drop-down menu of topping choices from affordance **3733-1** in FIG. **37**CC. Pepperoni is added to the pizza in FIG. **37**CE in response to detecting a tap gesture on the topping, including contact **3739** in FIG. **37**CD. The device displays pepperoni on the pizza in pizza ordering application object **3735** displayed at position **3735**-*a*—immediately below message **3798**—within conversation transcript **3700** in FIG. **37**CE. The device also displays an indication that "you added pepperoni" below application object **3735** in FIG. **37**CE. Device **100-2** also sends information to device **100-1** that pepperoni was added to the pizza.

[0987] Device **100-1** receives the information sent from device **100-2** and, in response, displays pepperoni on the pizza shown in pizza ordering application object **3735** in FIG. **37**CS. Digital keyboard **3501** is then activated in FIG. **37**CU by a tap gesture on message-input area, including contact **3759** in FIG. **37**CT. The device receives and posts message **3741** to the messaging session, as shown in conversation transcript **3700** in FIG. **37**CV, in response to a tap gesture on message-content posting affordance **3520** in FIG. **37**CU.

[0988] When device **100-2** receives message **3741** posted from device **100-1**, pizza ordering application object **3735** moves up on touch screen **112**, in accordance with its temporal order within the messaging session, as in FIG. **37**CF. Digital keyboard **3501** replaces input area **3731** in FIG. **37**CH after device **100-2** detects a tap gesture on message-input area **3502**, including contact **3743** in FIG. **37**CG. The device then receives and posts message **3747** to the messaging session, as shown in conversation transcript **3700** in FIG. **37**CJ, in response to a tap gesture on message-content posting affordance **3520** in FIG. **37**C**1**. However, pizza ordering application object **3735** does not move in response to placing message **3747** in conversation transcript **3700** because it has reached the top of the displayed conversation transcript **3700**. Rather, message **3741** moves up and behind pizza ordering application object **3735**, which is temporarily pinned to the top of the displayed portion of the conversation transcript, in FIG. **37**CJ.

[0989] Likewise, when device **100-1** receives message **3747** posted from device **100-2**, pizza ordering application object **3735** is pinned to the top of conversation transcript **3700** in FIG. **37**CW. Message **3741** is displayed as if sliding behind application object **3735** in FIG. **37**CW. The device then receives and posts message **3749** to the messaging session, as shown in conversation transcript **3700** in FIG. **37**CY, in response to a tap gesture on message-content posting affordance **3520** including contact **3763** in FIG. **37**CX. Pizza ordering application object **3735** remains pinned to the top of conversation transcript **3700** in FIG. **37**CY because users of the messaging session are actively creating a pizza together.

[0990] Likewise, messages posted to the messaging session continue to slide behind pizza ordering application object **3735** on device **100-2**, as shown in FIG. **37**CK when the device receives message **3749** posted by device **100-1**

[0991] Mushrooms are then added to the pizza from device **100-1**. Pizza ordering application input area **3731** is displayed on the device in response to a tap gesture on pizza ordering application object **3735** in conversation transcript **3700**, including contact **3756** in FIG. **37**CZ. Mushrooms are selected after a tap gesture on input affordance **3733-1**, including contact **3767** in FIG. **37**DB, activates a drop-down menu of pizza toppings in FIG. **37**DC. A tap gesture, including contact **3769** on "Mushrooms" in FIG. **37**DD, causes the device to display mushrooms on the pizza in pizza ordering application object **3735** in FIG. **37**DE. The device also displays an indication that "you added mushrooms" below application object **3735** in FIG. **37**DE, and sends information to device **100-2** that mushrooms were added to the pizza.

[0992] Upon receiving the information from device **100-1**, device **100-2** displays mushrooms on the pizza within pizza ordering application object **3735**, in FIG. **37**CL. The device also displays, in FIG. **37**CL, an indication that "Andrew added mushrooms" to the pizza below application object **3735** in transcript **3700**. The device then receives and posts message **3753** to the messaging session ion FIG. **37**CN, in response to detecting a tap gesture on message-content posting affordance **3520** including contact **3751** in FIG. **37**CM.

[0993] Device **100-1** receives message **3753**, as displayed in conversation transcript **3700** in FIG. **37**DF. The pizza is then ordered from a business associated with the pizza ordering application, by device **100-1**. The device detects a tap gesture on ordering affordance **3733-3**, including contact **3771** in FIG. **37**DG, and displays affordances for setting details of the order—affordance **3773-1** for selecting a payment option and affordance **3773-2** for selecting a delivery address—and for placing the order with the business (affordance **3773-3**) in pizza ordering application input area **3731**, as in FIG. **37**DH. The pizza is ordered in FIG. **37**DJ upon detecting a tap gesture on ordering affordance **3773-3**, including contact **3775** in FIG. **37**DI. In response to ordering the pizza, device **100-1** closes the pizza ordering application, displays conversation transcript **3700** in full-screen mode, un-pins pizza ordering application object **3735** and returns it to its original temporal position within conversation transcript **3700**, indicates that "Abe started building a pizza" at that time, and displays pizza ordering application archiving icon **3755** at the end of the conversation transcript, archiving the ordering event in the temporal order of the messaging session. Device **100-1** also sends information to device **100-2** that the pizza was ordered.

[0994] Upon receiving the information for device **100-1**, device **100-2** likewise displays pizza ordering application archiving icon **3755** at the end of conversation transcript **3700** in FIG. **37**CO, indicating that "Andrew ordered a pizza" at this time in the messaging session. Device **1002** also unpins pizza ordering application object **3735** from the top of the displayed portion of the conversation transcript, and displays application object at original temporal position **3735**-*a* in conversation transcript **3700**, as shown in FIG. **37**CQ. Full-screen display of transcript **3700** is activated upon detecting a downward swipe gesture including movement **3759** of contact **3757** from position **3757**-a in FIG. **37**CP to position **3757**-*b* in FIG. **37**CQ, causing the device to cease display of digital keyboard **3501**.

[0995] FIGS. **38**A-**38**AZ illustrate exemplary user interfaces for integrating applications in a messaging application in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIGS. **60**A-**60**D. For convenience of explanation, some of the embodiments will be discussed with reference to operations performed on a device with a touch-sensitive display system **112**. In such embodiments, the focus selector is, optionally: a respective finger or stylus contact, a representative point corresponding to a finger or stylus contact (e.g., a centroid of a respective contact or a point associated with a respective contact), or a centroid of two or more contacts detected on the touch-sensitive display system **112**. However, analogous operations are, optionally, performed on a device with a display **450** and a separate touch-sensitive surface **451** in response to detecting the contacts on the touch-sensitive surface **451** while displaying the user interfaces shown in the figures on the display **450**, along with a focus selector.

[0996] FIGS. **38**A-**380** and **38**R-**38**AZ illustrate an exemplary user interface **3500** for a messaging application which includes conversation transcript **3503**, message-input area **3502**, either of application expansion affordance **3702** or three activatable affordances—digital image affordance **3504**, digital canvas affordance **3506**, and application affordance **3508**—optionally, one of digital keyboard **3501**, digital image tray **3806**, digital canvas tray **3854**, application selection tray **3654**, and application swipe tray **3892**. Conversation transcript **3503** includes messages from participants of a corresponding messaging session, including the user of portable multifunction device **100-1** and other users included in the messaging session. Each of the other users included in the messaging transcript are represented by an avatar (e.g., avatar **3510** for "Abe") displayed in stack of avatars **4002**.

[0997] FIGS. **38**A-**38**Y illustrate an exemplary embodiment where digital images and a digital camera are integrated into a messaging application. FIG. **38**A illustrates user interface **3500** for a messaging application, including conversation transcript **3503**, digital image affordance **3504**, digital canvas affordance **3506**, application affordance **3508**, and message-input area **3502**, including microphone affordance **3802** for receiving speech that is translated into text for posting to the messaging session associated with conversation transcript **3503**. Device **100-1** detects a tap gesture, including contact **3804** in FIG. **38**B, on digital camera affordance **3504** and, in response, displays digital image tray **3806** in FIG. **38**C. Conversation transcript **3503** shrinks to accommodate digital image tray **3806**. Digital image tray includes live preview image **3514** from an associated digital camera, including image capture affordance **3516** and camera switching affordance **3505** for switching the live preview image between two or more associated digital cameras, and previously captured digital images **3518**.

[0998] FIGS. **38**D-**38**G illustrate an exemplary embodiment where scrolling in opposite directions on the digital image tray causes display of different affordances. Device **100-1** detects a swipe gesture including movement **3810** of contact **3808** to the left, from position **3808**-*a* in FIG. **38**D to position **3808**-*b* in FIG. **38**E. In response, the device moves digital image tray **3806** to the left, in accordance with movement **3810**, creating the appearance that live preview image **3514** slides off of the left side of touch screen **112** and additional digital images **3518-6** and **3518-7** slide onto the display from the right side of touch screen **112**, in FIG. **38**E.

[0999] The device then detects a swipe gesture including movement **3814** of contact **3812** to the right, from position **3812**-*a* in FIG. **38**F to position **3812**-*b* in FIG. **38**G. In response, the device moves digital image tray **3806** to the right, in accordance with movement **3814**, creating the appearance that digital images **3518-3**, **3518-4**, **3518-6**, and **3518-7** slide off of the right side of touch screen **112** and revealing full-screen camera affordance **3816** and photo library affordance **3818** from the left side of touch screen **112** in FIG. **38**G.

[1000] FIGS. **38**H-**38**M illustrate an exemplary embodiment where a digital image is captured and posted to the messaging session by accessing a full-screen camera live preview image from the messaging application user interface. Device **100-1** detects a tap gesture, including contact **3820** in FIG. **38**H, on full-screen camera affordance **3816** and, in response, displays digital camera user interface **3822** in FIG. **38**I. Digital camera user interface **3822** includes a full-screen display of live preview image **3514** and image capture affordance **2822**. The device then detects a tap gesture including contact **3824** on image capture affordance **3822** in FIG. **38**J. In response, device **100** captures live preview image **3514**, creating digital image **3518-5**, and places the image in message-input area **3502**, which expands to accommodate the image in FIG. **38**K. The device then detects a tap gesture including contact **3826** on message-

content posting affordance **3520** in FIG. **38**L. In response, device **100** posts captured digital image **3518-5** to the messaging session, displaying the image in conversation transcript **3503** in FIG. **38**M.

[1001] FIGS. **38**N-**38**R illustrate an exemplary embodiment where a digital image stored in a photo library is accessed and posted to the messaging session from the messaging application user interface. Full-screen camera affordance **3816** and photo library affordance **3818** are revealed in digital image tray **3806**, from the left side of touch screen **112**, in response to detecting a swipe gesture, including movement of contact **3828** to the right in FIG. **38**N. Device **100-1** then detects a tap gesture, including contact **3830** in FIG. **38**O, on photo library affordance **3818** and, in response, displays photo library user interface **3832**, in FIG. **38**P. Photo library user interface **3832** includes affordances **3834** for accessing digital image collections, from which a digital image can be posted to the messaging session. The device detects a tap gesture, including contact **3838** on canceling affordance **3836**, causing the device to return to display of messaging user interface **3500**, in FIG. **38**R, without posting a previously captured digital image to the messaging session.

[1002] FIGS. **38**R to **38**Y illustrate exemplary embodiments where display of a digital keyboard replaces display of a photo tray, and vis versa. While displaying photo tray **3806**, device **100-1** detects a tap gesture on message-input area **3502**, including contact **3840** in FIG. **38**R. In response, the device replaces photo tray **3806** with digital keyboard **3501** in FIG. **38**S. Responsive to the tap gesture, the device also expands message-input area **3502**, displaying text cursor **3842** therein, and collapses digital image affordance **3504**, digital canvas affordance **3506**, and application affordance **3508** into application expansion affordance **3702** in FIG. **38**S.

[1003] The device detects input of a message, displayed within message-input area **3502** in FIG. **38**T. Responsive to input of the message, microphone affordance **3802** is replaced by message-content posting affordance **3520** in FIG. **38**T. Responsive to detecting a tap gesture, including contact **3844** in FIG. **38**U, on message-content posting affordance **3520**, the device posts the message to the messaging session, displaying message **3846** in conversation transcript **3503**, in FIG. **38**V. The device then displays the three activatable affordances—digital image affordance **3504**, digital canvas affordance **3506**, and application affordance **3508**—in FIG. **38**W in response to detection of a tap gesture, including contact **3848** in FIG. **38**V, on application expansion affordance **3702**. Responsive to detecting a tap gesture, including contact **3850** in FIG. **38**X, on digital image affordance **3504**, the device replaces digital keyboard **3501** with digital image tray **3806**, in FIG. **38**Y.

[1004] FIGS. **38**Z-**38**AH illustrate an exemplary embodiment where a digital canvas is integrated into a messaging application. FIG. **38**Z illustrates user interface **3500** for a messaging application, including conversation transcript **3503**, digital image affordance **3504**, digital canvas affordance **3506**, application affordance **3508**, and message-input area **3502**. Device **100-1** detects a tap gesture, including contact **3852** in FIG. **38**AA, on digital canvas affordance **3506** and, in response, displays digital canvas tray **3854** in FIG. **38**AB. Digital canvas tray **3854** includes a digital canvas **3858**, expression mode affordances **3860** for enabling various modes of expression on digital canvas **3858**, and color selection affordances **3856** for setting a color for an expression on digital canvas **3858**.

[1005] FIGS. **38**AC to **38**AH illustrate exemplary embodiments where display of a digital keyboard replaces display of a digital canvas tray, and vis versa. While displaying digital canvas tray **3854**, device **100-1** detects a tap gesture on message-input area **3502**, including contact **3862** in FIG. **38**AC. In response, the device replaces digital canvas tray **3854** with digital keyboard **3501** in FIG. **38**AD. Responsive to the tap gesture, the device also expands message-input area **3502**, displaying text cursor **3842** therein, and collapses digital image affordance **3504**, digital canvas affordance **3506**, and application affordance **3508** into application expansion affordance **3702** in FIG. **38**AD.

[1006] The device then displays the three activatable affordances—digital image affordance **3504**, digital canvas affordance **3506**, and application affordance **3508**—in FIG. **38**AF in response to detection of a tap gesture, including contact **3864** in FIG. **38**AE, on application expansion affordance **3702**. Responsive to detecting a tap gesture, including contact **3866** in FIG. **38**AG, on digital canvas affordance **3506**, the device replaces digital keyboard **3501** with digital canvas tray **3858**, in FIG. **38**AH.

[1007] FIGS. **38**AI-**38**AS illustrate an exemplary embodiment where interactive applications are integrated into a messaging application. FIG. **38**AI illustrates exemplary user interface **3500** for a messaging application, including conversation transcript **3503**, digital image affordance **3504**, digital canvas affordance **3506**, application affordance **3508**, and message-input area **3502**. Device **100-1** detects a tap gesture, including contact **3868** in FIG. **38**AJ, on application affordance **3508** and, in response, displays application swipe tray **3892** including launch icon **3708** for an interactive application and application menu toggle affordance **3627**, in FIG. **38**AK. The device then detects a tap gesture, including contact **3870** in FIG. **38**AL, on application menu toggle affordance **3627** and, in response, replaces application swipe tray **3892** with application selection tray **3654**, including a plurality of launch icons for applications—launch icon **3601** for a messaging application-specific application store, launch icon **3603** for an interactive tic-tac-toe application, launch icon **3605** for an interactive reservation application, launch icon **3607** for a search application, launch icon **3609** for a digital sticker pack, launch icon **3611** for a live video-streaming application, launch icon **3613** for an interactive pizza ordering application, and launch icon **3615** for an interactive digital music application—in FIG. **38**AM.

[1008] FIGS. **38**AC to **38**AH illustrate exemplary embodiments where display of a digital keyboard replaces display of an application launch tray, and vis versa. While displaying application selection tray **3654**, device **100-1** detects a tap gesture on message-input area **3502**, including contact **3872** in FIG. **38**AN. In response, the device replaces application selection tray **3654** with digital keyboard **3501** in FIG. **38**AO. Responsive to the tap gesture, the device also expands message-input area **3502**, displaying text cursor **3842** therein, and collapses digital image affordance **3504**, digital canvas affordance **3506**, and application affordance **3508** into application expansion affordance **3702** in FIG. **38**AO.

[1009] In response to detecting a tap gesture, including contact **3874** in FIG. **38**AP, on application expansion affordance **3702**, the device then displays the three activatable affordances—digital image affordance **3504**, digital canvas

affordance **3506**, and application affordance **3508**—in FIG. **38**AQ. Responsive to detecting a tap gesture, including contact **3876** in FIG. **38**AR, on application affordance **3508**, the device replaces digital keyboard **3501** with application selection tray **3654**, in FIG. **38**AS.

[1010] FIGS. **38**AT-**38**AV illustrate an exemplary embodiment where the message transcript shrinks to accommodate display of a keyboard. FIG. **38**AT illustrates exemplary user interface **3500** for a messaging application, including conversation transcript **3503**, digital image affordance **3504**, digital canvas affordance **3506**, application affordance **3508**, and message-input area **3502**. Device **100-1** detects a tap gesture, including contact **3878** in FIG. **38**AU, on message-input area **3502** and, in response, shrinks conversation transcript **3503** to accommodate display of digital keyboard **3501** in FIG. **38**AV. Responsive to the tap gesture, the device also expands message-input area **3502**, displaying text cursor **3842** therein, and collapses digital image affordance **3504**, digital canvas affordance **3506**, and application affordance **3508** into application expansion affordance **3702** in FIG. **38**AV.

[1011] FIGS. **38**AV-**38**AZ illustrate an exemplary embodiment where the user of the device can interact with a single participant in a group messaging session through interactions with that person's avatar. FIG. **38**AV illustrates an exemplary user interface **3500** for a messaging application which includes conversation transcript **3503**, digital keyboard **3501**, message-input area **3502**, and application expansion affordance **3702**. Conversation transcript **3503** includes messages from participants of a corresponding messaging session, including the user of portable multifunction device **100-1** and other users included in the messaging session. Each of the other users included in the messaging transcript are represented by an avatar (e.g., avatar **3510** for "Abe" and avatar **4008** for "Mary Todd") displayed in stack of avatars **4002** in messaging user interface **3500**.

[1012] In one embodiment, a menu of actions for interacting with another user included in the messaging session is displayed by tapping on the user's avatar. Device **100-1** detects a tap gesture, including contact **3880** in FIG. **38**AW, on Abe's avatar **3510**. In some embodiments, the user input is a deep press gesture. In response, the device displays menu **3882** of activatable menu items **3884-1** to **3884-6** for interacting directly with Abe by a phone call, video call, individual message, e-mail, digital drawing, or payment, respectfully, in FIG. **38**AX. The device then activates a private messaging conversation transcript **3700** with Abe in FIG. **38**AZ, after detecting a tap input including contact **3886** on menu item **3884-3**, in FIG. **38**AY.

[1013] FIGS. **39**A-**39**AW illustrate exemplary user interfaces for integrating electronic stickers in a messaging application in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIGS. **62**A-**62**C and **64**A-**64**C. For convenience of explanation, some of the embodiments will be discussed with reference to operations performed on a device with a touch-sensitive display system **112**. In such embodiments, the focus selector is, optionally: a respective finger or stylus contact, a representative point corresponding to a finger or stylus contact (e.g., a centroid of a respective contact or a point associated with a respective contact), or a centroid of two or more contacts detected on the touch-sensitive display system **112**. However, analogous operations are, optionally, performed on a device with a display **450** and a separate touch-sensitive surface **451** in response to detecting the contacts on the touch-sensitive surface **451** while displaying the user interfaces shown in the figures on the display **450**, along with a focus selector.

[1014] FIGS. **39**A-**39**AW illustrate exemplary user interface **3500** for a messaging application which includes conversation transcript **3700**, message-input area **3502**, either of application expansion affordance **3702** or three activatable affordances—digital image affordance **3504**, digital canvas affordance **3506**, and application affordance **3508**—optionally, one of digital keyboard **3501**, application selection tray **3654**, and application swipe tray **3892**. Conversation transcript **3700** includes messages from participants of a corresponding messaging session, including the user of portable multifunction device **100** and other users included in the messaging session. Each of the other users included in the messaging transcript are represented by an avatar (e.g., avatar **3510** for "Abe").

[1015] FIGS. **39**A-**39**C, **39**AB-**39**AF, and **39**AU-**39**AW illustrate three exemplary embodiments for accessing an electronic sticker pack in a messaging application. Each embodiment begins from an exemplary user interface **3500** for a messaging application, including conversation transcript **3503**, digital image affordance **3504**, digital canvas affordance **3506**, application affordance **3508**, and message-input area **3502**, including microphone affordance **3802** for receiving speech that is translated into text for posting to the messaging session associated with conversation transcript **3503**, as in FIGS. **39**A, **39**AB, and **39**AU.

[1016] In a first embodiment, device **100-1** detects a tap gesture, including contact **3902** in FIG. **39**B, on application affordance **3508** and, in response, displays application swipe tray **3892**, including sticker pack **3904** with electronic stickers **3906**, **3908**, and **3910** and application menu toggle affordance **3627**, in FIG. **39**C.

[1017] In a second embodiment, device **100-1** detects a tap gesture, including contact **3934** in FIG. **39**AB, on application affordance **3508** and, in response, displays application swipe tray **3892**, including launch icon **3708** for an interactive reservation application and application menu toggle affordance **3627**, in FIG. **39**AC. The device then detects a swipe gesture to the left in application swipe tray **3892**, including movement **3938** of contact **3936** from position **3936**-*a* in FIG. **39**AD to position **3936**-*b* in FIG. **39**AE. In response, the device moves application swipe tray **3892** to the left, in accordance with movement **3936**, creating the appearance that application launch icon **3708** slides off of the left side of touch screen **112** and sticker pack **3904** slides the display from the right side of touch screen **112**, in FIG. **39**AE. After completion of the swipe gesture, the device displays sticker pack **3904** with electronic stickers **3906**, **3908**, and **3910** and application menu toggle affordance **3627**, within application slide tray **3892**, in FIG. **39**AF.

[1018] In a third embodiment, device **100-1** detects a tap gesture, including contact **3952** in FIG. **39**AU, on application affordance **3508** and, in response, displays application selection tray **3654**, including a plurality of launch icons for applications—launch icon **3601** for a messaging application-specific application store, launch icon **3603** for an interactive tic-tac-toe application, launch icon **3605** for an interactive reservation application, launch icon **3607** for a search application, launch icon **3609** for an electronic sticker pack, launch icon **3611** for a live video-streaming application, launch icon **3613** for an interactive pizza ordering

application, and launch icon **3615** for an interactive digital music application—in FIG. **38**AM. The device then detects a tap gesture, including contact **3954** in FIG. **39**AV, on launch icon **3609** for an electronic sticker pack and, in response, replaces application selection tray **3654** with sticker pack **3904**, including electronic stickers **3906**, **3908**, and **3910** and application menu toggle affordance **3627**, in FIG. **39**AW.

[1019] FIGS. **39**D-**39**P and **39**Z-**39**AA illustrate exemplary embodiments for posting an electronic sticker to a messaging session. Each embodiment begins from an exemplary user interface **3500** for a messaging application, including conversation transcript **3503**, message-input area **3502**, and electronic sticker pack **3904** with electronic stickers **3906**, **3908**, and **3910**, as in FIGS. **39**D, **39**H, **39**K, **39**N, and **39**Z.

[1020] In a first embodiment, an electronic sticker is posted to the conversation transcript through the message-input area, in response to tapping on the electronic sticker. Device **100-1** detects a tap gesture, including contact **3912** in FIG. **39**D, on snowflake sticker **3908**. In response, the device places snowflake sticker **3908** in message-input area **3502** in FIG. **39**E. The device then detects a tap gesture including contact **3914** on message-content posting affordance **3520** in FIG. **39**F. In response, device **100** posts snowflake sticker **3908** at location **3908**-*a,* corresponding to the next temporal position for a message posted in transcript **3700**, as shown in FIG. **39**G.

[1021] In a second embodiment, an electronic sticker is dragged into the conversation transcript by a drag gesture, and is posted to the messaging session at the location it was dragged to in the conversation transcript. Device **100-1** detects a drag gesture, including movement **3918** of contact **3916**, which was initiated on electronic sticker **3906**, from position **3916**-*a,* within sticker pack **3904**, in FIG. **39**H to position **3916**-*b,* within conversation transcript **3700** in FIG. **39**I. In response, snowman sticker **3906** is dragged from its initial position **3906**-*a* in the sticker pack, in FIG. **39**H, to position **3906**-*b* within the conversation transcript, in FIG. **39**I, in accordance with movement **3918**. Upon lift-off of contact **3916** within conversation transcript **3700**, snowman sticker **3906** is posted to the messaging session, as displayed at position **3906**-*b* in FIG. **39**J.

[1022] In a third embodiment, an electronic sticker is not posted to the messaging session when it is not dragged all the way into the conversation transcript. Device **100-1** detects a drag gesture, including movement **3922** of contact **3920**, which was initiated on electronic sticker **3910**, from position **3920**-*a,* within sticker pack **3904**, in FIG. **39**K to position **3920**-*b,* still within sticker pack **3904** in FIG. **39**L. In response, sled sticker **3910** is dragged from its initial position **3910**-*a* in sticker pack **3904**, in FIG. **39**K, to position **3910**-*b* still within sticker pack **3904**, in FIG. **39**L, in accordance with movement **3922**. Upon lift-off of contact **3920** within sticker pack **3904**, sled sticker **3910** is not posted to the messaging session, because it was not dragged into the conversation transcript, as displayed in its original position **3920**-*a* in FIG. **39**M.

[1023] In a fourth embodiment, an electronic sticker is dragged into the conversation transcript by a drag gesture, and is posted to the messaging session at a nearest predefined position to the location it was dragged to in the conversation transcript. Device **100-1** detects a drag gesture, including movement **3926** of contact **3924**, which was initiated on electronic sticker **3908**, from position **3924**-a, within sticker pack **3904**, in FIG. **39**N to position **3924**-*b,* within conversation transcript **3700** in FIG. **39**O. In response, snowflake sticker **3908** is dragged from its initial position **3908**-*a* in the sticker pack, in FIG. **39**N, to position **3908**-*c* within the conversation transcript, in FIG. **39**O, in accordance with movement **3926**. Upon lift-off of contact **3924** within conversation transcript **3700**, snowflake sticker **3908** is repositioned to position **3908**-*d*, which corresponds to the nearest location within a message region (e.g., message region **3749**) to the position the sticker was at when the device detected lift-off of the contact corresponding to the drag gesture (e.g., location **3908**-*c*).

[1024] In a fifth embodiment, an electronic sticker is posted directly to the messaging session, at the next temporal position for a message posted in the transcript, in response to detecting a deep press gesture. Device **100-1** detects a press gesture including contact **3932** on snowman sticker **3906** in FIG. **39**Y. Device **100-1** then detects an increase in the intensity of contact **3932** above a predefined intensity threshold (e.g., IT_L or IT_D) and, in response, posts snowman sticker directly to the messaging session, as displayed at position **3906**-*c,* corresponding to the next temporal position for a message posted in transcript **3700**, as shown in FIG. **39**AA.

[1025] FIGS. **39**P-**39**X illustrate exemplary embodiments where the electronic sticker in animated. In FIG. **39**P, snowman sticker **3906** is displayed at location **3906**-*b* in conversation transcript **3700**, as it was placed in FIGS. **39**H-**39**J. In FIGS. **39**Q-**39**T, snowman sticker **3906** cycles through animation states **3930**-*a,* **3930**-*b,* and **3930**-*c,* appearing to lift and lower his broomstick.

[1026] In FIGS. **39**U-**39**X animation **3930** of snowman sticker **3906** is previewed by deep pressing on the sticker in sticker pack **3904**. Device **100-1** detects a press gesture including contact **3928** on snowman sticker **3906** in FIG. **39**U. Device **100-1** then detects an increase in the intensity of contact **3928** above a predefined intensity threshold (e.g., IT_L or IT_D) in FIG. **39**V and, in response, cycles snowman sticker **3906** through animation states **3930**-*a,* **3930**-*b,* and **3930**-*c* in FIGS. **39**V-**39**X. In some embodiments, stickers associated with animations are continually animated when displayed in the sticker pack.

[1027] FIGS. **39**AF-**39**AT illustrate exemplary embodiments where the position, size, and/or rotation on an electronic sticker are changed.

[1028] In one embodiment, the size of an electronic sticker changes in response to the pressure of a contact on the sticker. In FIGS. **39**AG-**39**AI, snowman sticker **3906** is dragged from sticker pack **3904** into conversation transcript **3700** by a drag gesture including movement **3942** of contact **3940** from position **3940**-*a* in FIG. **39**AG, to position **3940**-*c* in FIG. **39**AI. During the drag gesture, device **100-1** detects an increase in the intensity of contact **3940** between FIGS. **39**AG and **39**AH and in between FIGS. **39**AH and **39**AI. In response, snowman sticker **3940** gets successively larger. The device then detects a decrease in the intensity of contact **3940** between FIGS. **39**AI and **39**AJ and, in response, the size of snowman sticker **3906** decreases.

[1029] In one embodiment, the rotation of an electronic sticker changes in response to a rotation gesture by a contact on the sticker. Device **100-1** detects a counter-clockwise rotation gesture including rotation **3944** of contact **3940** from position **3940**-*c* in FIG. **39**AK to position **3940**-*d* in

FIG. **39**AL. In response, snowman sticker **3906** is rotated counter-clockwise, in accordance with rotation **3944**, from position **3906**-*e* in FIG. **39**AK to position **3906**-*f* in FIG. **39**AL. In response to detecting lift-off of contact **3940** from touch screen **112**, while in conversation transcript **3700**, snowman sticker **3906** is posted to the messaging session, as displayed rotated and larger, with respect to its original appearance in the sticker pack, at position **3906**-*f* within conversation transcript **3700** in FIG. **39**AM.

[1030] In one embodiment, the position of an electronic sticker can be changed after initially placing the sticker within the conversation transcript. Device **100-1** detects a drag gesture initiating over snowman sticker **3906** in conversation transcript **3700**, after the sticker was initially placed in the transcript in FIG. **39**AM. The drag gesture includes movement **3948** of contact **3946** from position **3946**-*a* in FIG. **39**AN to position **3946**-*b* in FIG. **39**AO. In response, snowman sticker moves from position **3906**-*f* in FIG. **39**AN to position **3906**-*g*—in FIG. **39**AO, in accordance with movement **3948**.

[1031] In one embodiment, the size of an electronic sticker is changed after initially placing the sticker with the conversation transcript. As a continuation of the gesture described above, device **100-1** detects an increase in the intensity of contact **3946** between FIGS. **39**AO and **39**AP. In response, snowman sticker **3940** is displayed larger in FIG. **39**AP.

[1032] In one embodiment, the rotation of an electronic sticker is changed after initially placing the sticker with the conversation transcript. As a continuation of the gesture described above, device **100-1** detects a counter-clockwise rotation gesture including rotation **3950** of contact **3946** from position **3946**-*b* in FIG. **39**AQ to position **3946**-*c* in FIG. **39**AR. In response, snowman sticker **3906** is rotated counter-clockwise, in accordance with rotation **3944**, from position **3906**-*g* in FIG. **39**AQ to position **3906**-*h* in FIG. **39**AR. In response to detecting lift-off of contact **3946** from touch screen **112**, while in conversation transcript **3700**, snowman sticker **3906** is placed back in the transcript as displayed in FIG. **39**AS. The device sends information about the orientation of snowman sticker **3906** at position **3906**-*h* to electronic devices corresponding to other users included in the messaging session associated with conversation transcript **3700**.

[1033] In one embodiment, the position, size, and/or rotation of an electronic sticker is changed by a second user after being posted to the messaging session. Device **100-1** receives information from another device corresponding to another user included in the messaging session associated with conversation transcript **3700** (e.g., "Abe"). The information conveys that Abe changes the position, size, and rotation of snowman sticker **3906** from orientation (e.g., position) **3906**-*h*, as illustrated in FIG. **39**AS, to orientation **3906**-I, as illustrated in FIG. **39**AT. In response, device **100-1** displays snowman sticker **3906** with orientation **3906**-I in FIG. **39**AT.

[1034] FIGS. **40**A-**40**W illustrate exemplary user interfaces for interacting with other users of a messaging transcript through an avatar in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIGS. **66** and **68**A-**68**B. For convenience of explanation, some of the embodiments will be discussed with reference to operations performed on a device with a touch-sensitive display system **112**. In such embodiments, the focus selector is, optionally: a respective finger or stylus contact, a representative point corresponding to a finger or stylus contact (e.g., a centroid of a respective contact or a point associated with a respective contact), or a centroid of two or more contacts detected on the touch-sensitive display system **112**. However, analogous operations are, optionally, performed on a device with a display **450** and a separate touch-sensitive surface **451** in response to detecting the contacts on the touch-sensitive surface **451** while displaying the user interfaces shown in the figures on the display **450**, along with a focus selector.

[1035] FIGS. **40**A-**40**W illustrate an exemplary user interface **3500** for a messaging application which includes conversation transcript **3503**, message-input area **3502**, three activatable affordances—digital image affordance **3504**, digital canvas affordance **3506**, and application affordance **3508**. Conversation transcript **3503** includes messages from participants of a corresponding messaging session, including the user of portable multifunction device **100-1** and other users included in the messaging session. Each of the other users included in the messaging transcript are represented by an avatar (e.g., avatar **3510** for "Abe" and avatar **4008** for "Mary Todd") displayed in stack of avatars **4002**.

[1036] FIGS. **40**A-**40**F illustrate two exemplary embodiments for interacting with another user of a messaging session through an avatar, where the device performs different operations based on detecting different types of user inputs.

[1037] In a first embodiment, a menu of actions for interacting with another user included in the messaging session is displayed by tapping on the user's avatar. Device **100-1** detects a tap gesture, including contact **4004** in FIG. **40**B, on Abe's avatar **3510**. In response, the device displays menu **3882** of activatable menu items **3884-1** to **3884-6** for interacting directly with Abe by a phone call, video call, individual message, e-mail, digital drawing, or payment, respectfully.

[1038] In a second embodiment, the stacked avatars are cycled to display a different avatar on top of the stack by deep pressing on the stack of avatars. Device **100-1** detects a press gesture, including contact **4006** in FIG. **40**D, on stack of avatars **4002** displaying Abe's avatar **3510** on top. The device then detects an increase in the intensity of contact **4006** above a predefined intensity threshold (e.g., IT_L or IT_D) in FIG. **40**E and, in response, shuffles the stack of avatars **4002** to display Mary Todd's avatar **4008** on top, in FIGS. **40**E-**40**F.

[1039] FIGS. **40**G-**40**R illustrate an exemplary embodiment for paying another user of a messaging session through an avatar. Device **100-1** detects a press gesture, including contact **4010** in FIG. **40**G, of stack of avatars **4002** displaying Mary Todd's avatar **4008** on top. The device then detects an increase in the intensity of contact **4010** above a predefined intensity threshold (e.g., IT_L or IT_D) and, in response, displays menu **3882** of activatable menu items **3884-1** to **3884-6**, for interacting with Mary Todd directly, and blurs display of conversation transcript **3503** in FIG. **40**H. Menu **3882** remains displayed after the device detects lift-off of contact **4010** in FIG. **40**I.

[1040] Device **100-1** then detects a tap gesture, including contact **4012** in FIG. **40**J, on activatable menu item **3884-6** for a payment action. In response, the device displays payment area **4014**, including termination affordance **4016**,

execution affordance **4018**, and digital keypad **4015** for inputting payment amount, in FIG. **40**K. The device then detects input of a payment amount ($60) and, subsequently, a tap gesture including contact **4020** on message-input area **4019**, in FIG. **40**L. In response, the device replaces digital touchpad **4014** with digital keyboard **4017** in FIG. **40**M. Responsive to detecting input of message **4021**, in FIG. **40**N, and a tap gesture, including contact **4022** in FIG. **40**O, on execution affordance **4018**, the device prompts the user of device **100-1** to confirm their identity by displaying confirmation area **4024** in FIG. **40**P. In response to receiving an identity confirming input, including contact **4026** in FIG. **40**Q, the device executes payment of $**60** to Mary Todd and posts confirmation of the payment to the messaging session, displaying payment confirmation **4028** within conversation transcript **3503** in FIG. **40**R.

[1041] FIGS. **40**S-**40**W illustrate two exemplary embodiments for interacting with another user of a messaging session through an avatar, where the device performs different operations based on detecting different types of user inputs.

[1042] In a first embodiment, tapping on the stack of avatars spreads the avatars out, such that a particular avatar can be selected. Device **100-1** detects a tap gesture, including contact **4030** in FIG. **40**S, on stack of avatars **4002**. In response, the device spreads the avatars in stack of avatars **4002**—avatar **3510** for "Abe," avatar **4008** for "Mary Todd," avatar **4032** for "Chuck," avatar **4034** for "Isaac," and avatar **4036** for "Edwin"—across the top of touch screen **112** in FIG. **40**T.

[1043] In a second embodiment, which is also a continuation of the first embodiment, deep pressing on a particular avatar calls up a menu of activatable actions for interacting with the user corresponding to the avatar. Device **100-1** detects a press gesture, including contact **4038** in FIG. **40**U, on Mary Todd's avatar **4008**. The device then detects an increase in the intensity of contact **4038** above a predefined intensity threshold (e.g., IT_L or IT_D) and, in response, displays menu **3882** of activatable menu items **3884-1** to **3884-6**, for interacting with Mary Todd directly, and blurs display of conversation transcript **3503** in FIG. **40**V. Menu **3882** remains displayed after the device detects lift-off of contact **4038** in FIG. **40**W.

[1044] FIGS. **41**A-**41**H illustrate exemplary user interfaces for integrating data detectors into a messaging application in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIGS. **70**A-**70**B. For convenience of explanation, some of the embodiments will be discussed with reference to operations performed on a device with a touch-sensitive display system **112**. In such embodiments, the focus selector is, optionally: a respective finger or stylus contact, a representative point corresponding to a finger or stylus contact (e.g., a centroid of a respective contact or a point associated with a respective contact), or a centroid of two or more contacts detected on the touch-sensitive display system **112**. However, analogous operations are, optionally, performed on a device with a display **450** and a separate touch-sensitive surface **451** in response to detecting the contacts on the touch-sensitive surface **451** while displaying the user interfaces shown in the figures on the display **450**, along with a focus selector.

[1045] FIGS. **41**A-**41**H illustrate two exemplary embodiments where a first electronic device **100-1** detects a word or phrase, in a messaged received from a second electronic device associated with another user included in the messaging session, associated with additional content available on the internet. FIG. **41**A illustrates an exemplary user interface **3500** for a messaging application which includes conversation transcript **3503**, message-input area **3502**, three activatable affordances—digital image affordance **3504**, digital canvas affordance **3506**, and application affordance **3508**. Conversation transcript **3503** includes messages from participants of a corresponding messaging session, including the user of portable multifunction device **100-1** and other users included in the messaging session. Each of the other users included in the messaging transcript are represented by an avatar (e.g., avatar **4008** for "Mary Todd") displayed in stack of avatars **4002**.

[1046] In a first embodiment, the device prompts the user to view additional content associated with the identified word or phrase within the messaging user interface by displaying a selectable affordance. Device **100-1** receives message **4102** from Mary Todd, displayed in conversation transcript **3503** in FIG. **41**A. The device recognizes phrase **4101** ("Meteorite Catcher") as the name of a movie about which information is available on the internet. In response, the device displays selectable affordance **4104**, prompting the user to "See more information" about the movie. The device then detects a tap gesture, including contact **4106**, on selectable affordance **4104** in FIG. **41**B. In response, the device displays information area **4108** displaying information about the movie found on the internet, including a representation **4110** of a poster for the film and biographical information **4112** about the movie, in FIG. **41**C.

[1047] In a second embodiment, the device prompts the user to view additional content associated with the identified word or phrase in a separate search user interface by highlighting the word or phrase. Device **100-1** receives message **4114** from Abe, displayed in conversation transcript **3503** in FIG. **41**D. The device recognizes phrase **4103** ("Astron Omer") as the name of an actor about whom information is available on the internet. In response, the device displays highlighting **4116** of phrase **4103**, prompting the user to select the phrase. The device then detects a tap gesture, including contact **4118**, on phrase **4103** in FIG. **41**E. In response, the device displays search user interface **3661** displaying categorized results—new articles **3664**, **3678**, and **3680** and movie previews **3670**, **3682**, and **3684**—of an internet search of phrase **4103**, in FIG. **41**F. The device detects a tap gesture, including contact **4120** in FIG. **41**G, on movie preview **3670**. In response, the device posts movie preview **3670** to the messaging session, displaying movie preview **3670** in conversation transcript **3503** in FIG. **41**H.

[1048] FIGS. **42**A-**42**D are flow diagrams illustrating a method **4200** of capturing and posting digital images within a messaging application in accordance with some embodiments. The method **4200** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display, a touch-sensitive surface, and one or more sensors to detect intensities of contacts with the touch-sensitive surface. In some embodiments, the display is a touch-screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **4200** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1049] As described below, the method **4200** provides an intuitive way to capture and post digital images within a messaging application. The method reduces the number, extent, and/or nature of the inputs from a user when capturing and posting digital images within a messaging application, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to capture and post digital images within a messaging application faster and more efficiently conserves power and increases the time between battery charges.

[1050] The device displays (**4202**) a messaging user interface (e.g., of a messaging application) on the display (e.g., user interface **3500** on touch screen **112** in FIG. **35**A), the messaging user interface including a conversation transcript (e.g., displayed in a first area of the display; e.g., conversation transcript **3503** in FIG. **35**A) of a messaging session between a user of the electronic device and at least one other user (e.g., of another electronic device), a keyboard (e.g., displayed in a second area of the display; e.g., keyboard **3501** in FIG. **35**A), a message-input area (e.g., area **3502** in FIG. **35**A), and a digital image affordance (e.g., affordance **3504** in FIG. **35**A).

[1051] While displaying the messaging user interface, the device detects (**4204**) an input that activates the digital image affordance (e.g., for an electronic device with a touch sensitive display, detecting a tap gesture on the digital image affordance). For example, in FIG. **35**B, device **100-1** detects an input including contact **3512** on digital image affordance **3504**.

[1052] In response to detecting the input that activates the digital image affordance, the device replaces (**4206**) display of the keyboard with display of a plurality of digital images, the plurality of digital images including one or more digital images stored in the memory and a live preview image from the digital camera. For example, responsive to detecting a tap gesture including contact **3512** in FIG. **35**B, the device replaces digital keyboard **3501** in FIG. **35**B with digital image tray **3806** including live preview image **3514** and previously captured digital images **3518**.

[1053] In some embodiments, the messaging user interface is not displaying a digital keyboard prior to detecting activation of the digital image affordance (e.g., the conversation transcript is maximized and includes display of the digital image affordance). For example, in FIG. **38**B, messaging user interface **3500** is displaying a full-screen version of conversation transcript **3503** when an input including contact **3804** is detected at digital image affordance **3504**. In response, the device shrinks display of conversation transcript **3503** to accommodate display of digital image tray **3806** in FIG. **38**C.

[1054] In some embodiments, replacing display of the keyboard includes displaying the plurality of digital images over the keyboard. In some embodiments, replacing display of the keyboard includes ceasing to display the keyboard and displaying the plurality of digital images where the keyboard had been displayed (e.g., as in FIG. **35**B-**35**C).

[1055] In some embodiments, the plurality of digital images is a scrollable array of digital images. For example, in FIGS. **35**P-**35**Q, a drag gesture including movement **3538** of contact **3536** from position **3536**-*a* in FIG. **35**P to position **3536**-*b* in FIG. **35**Q scrolls digital image tray to the left, revealing additional previously captured digital images **3518-6** and **3519-7**.

[1056] In some embodiments, the plurality of digital images includes a recently shared image, a recently received image, an image including a participant in the conversation (e.g., as identified by facial recognition), a real-time image from a forward-facing digital camera in the device, or a real-time image from a backwards-facing digital camera in the device.

[1057] In some embodiments, the one or more digital images stored in the memory, and displayed in response to detecting the input that activates the digital image affordance, consist (**4208**) of digital images captured (and or posted) during the messaging session.

[1058] The device detects (**4210**) an input that selects the live image displayed within the plurality of digital images (e.g., for an electronic device with a touch sensitive display, detecting a tap gesture on the live image). For example, in FIG. **35**D, contact **3512** is detected on live preview image **3514** (e.g., on image capture affordance **3516** displayed over live preview image **3514**).

[1059] In response to detecting that input that selects the live image, the device captures (**4212**) a digital image with the digital camera, while maintaining display of the conversation transcript. For example, in response to detecting an input that includes contact **3512** in FIG. **35**D, electronic device **100-1** captures digital image **3518-5**, displayed in message-input area **3502** in FIG. **35**E.

[1060] In some embodiments, after capturing the digital image, the device displays (**4214**) the digital image captured by the digital camera in the conversation transcript and transmits a representation of the captured digital image to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the captured digital image in a conversation transcript that corresponds to the messaging session. For example, device **100-1** detects an input including contact **3522** on message-content posting affordance **3520** in FIG. **35**F and, in response, displays captured digital image **3518-5** in conversation transcript **3503** in FIG. **35**G. Device **100-1** also transmits a representation of digital image **3518-5** to other electronic device associated with other users of the messaging session, for example, "Abe."

[1061] In some embodiments, the captured image is automatically posted to the messaging session upon selection of the live image. For example, in response to detecting a deep press gesture including contact **3524** in FIGS. **35**H-**35**I, device **100-1** automatically posts captured digital image **3518-5** to the messaging session, as displayed in conversation transcript **3503** in FIG. **35**I. In some embodiments, the device detects an input (e.g., a tap, press, deep press, double tap, multi-finger tap, long-press, or input including movement of a contact) and dependent upon the type of input, the device will either place the captured digital image in the message-input area or post it directly to the messaging session (e.g., display it in the conversation transcript). For example, FIGS. **35**C-**35**I illustrate an exemplary embodiment where a tap gesture causes the device to place the captured image in the message-input area (e.g., as in FIGS. **35**D-**35**F) and a deep press (or multi-finger input) causes the device to post the image directly to the messaging session (e.g., as in FIGS. **35**H-**35**I).

[1062] In some embodiments, the captured image is displayed in the message input area and the user posts the image to the messaging session (e.g., by activating a send

icon with a tap gesture). For example, activation of message-content posting affordance **3520** in FIG. **35**F causes the device to post the captured image to the messaging session, as displayed in conversation transcript **3503** in FIG. **35**G.

[1063] In some embodiments, prior to displaying the digital image captured by the digital camera in the conversation transcript (or any previously captured image) and transmitting a representation of the captured image, the device displays the digital image captured by the digital camera (or any previously captured image) in the message input area (e.g., as illustrated in FIG. **35**V). While displaying the digital image captured by the digital camera (or any previously captured digital image) in the message input area, the device detects an input that activates an image editing mode (e.g., contact **3546** in FIG. **35**W). In response to detecting the input that activates the image editing mode, the device replaces display of the messaging user interface with display of a digital photo editing user interface (e.g., user interface **3509** in FIG. **35**X), wherein the digital image captured by the digital camera (or any previously captured digital image) is displayed in the digital photo editing user interface (e.g., digital image **3518-4** in FIG. **35**X). While displaying the digital photo editing mode, the device detects an input that edits the digital photo captured by the digital camera (or any previously captured digital image). For example, inputs causing device **100-1** to draw mustache **3562** in FIG. **35**Z, place magnification loupe **3566** in FIG. **35**AB, configure magnification loupe **3566** in FIGS. **35**AB-AF, type "Senor Snowman" **3578** in FIG. **35**AH, or add handwriting **3582** in FIG. **35**AJ. In response to detecting the input that edits the digital photo captured by the digital camera (or any previously captured digital image), the device edits (**4216**) the digital image captured by the digital camera (e.g., draws on, magnifies, types on, hand writes on, as described above). After editing the digital image captured by the digital camera, the device detects an input terminating the digital image editing mode (e.g., contact **3586** in FIG. **35**AK). In response to detecting the input terminating the digital image editing mode, the device displays the edited digital image captured by the digital camera (or any previously captured digital image) in the message input area (e.g., as illustrated in FIG. **35**AL.

[1064] In some embodiments, in response to detecting the input terminating the digital image editing mode, the device displays the edited digital image captured by the digital camera in the conversation transcript and sends a representation of the edited image to at least one other electronic device corresponding to another user included in the messaging session.

[1065] In some embodiments, any digital image (e.g., any of previously captured digital images **3518**) can be edited from the messenger application and then posted to a messaging session, in accordance with the description above.

[1066] In some embodiments, in response to detecting the input that selects the live preview image, and after capturing the digital image, the device displays the digital image in the message-input area (e.g., digital image **3518-5** displayed in message-input area **3502** in FIG. **35**K). While displaying the digital image in the message-input area, the device detects input of a message in the message input area (e.g., a text message, such as message **3530** in FIG. **35**M). After detecting input of the message in the message-input area, the device detects an input that corresponds to a request to post contents of the message-input area to the messaging session (e.g., detecting a tap gesture on a send icon, such as contact **3532** in FIG. **35**N), the contents including the digital image and the message. In response to detecting the input that corresponds to the request to post the contents of the message-input area to the messaging session, the device displays the digital image in the conversation transcript (e.g., digital image **3518-5** in conversation transcript **3503** in FIG. **35**O), and the device displays (**4218**) the message (e.g., within a message region) in the conversation transcript, wherein the message (e.g., the message region) partially overlaps the digital image in the conversation transcript. For example, message **3534** partially overlaps with digital image **3518-5** in conversation transcript **3503** in FIG. **35**O. The device also transmits a representation of the digital image and the message to one or more electronic devices that correspond to the at least one other user included in the messaging session (e.g., "Abe" in FIG. **35**O), wherein the one or more electronic devices display the representation of the digital image and the message (e.g., the message region) in a conversation transcript corresponding to the messaging session, wherein the message (e.g., the message region) partially overlaps the representation of the digital image in the conversation transcript corresponding to the messaging session.

[1067] In some embodiments, in response to detecting the input that selects the live image, in accordance with a determination that the input that selects the live image meets one or more input-area-display criteria (e.g., one or more criteria based on the motion, timing, and/or intensity of a contact in the input), the device displays (**4220**) the digital image captured by the digital camera in the message input area (e.g., as illustrated in FIGS. **35**D-**35**E, where the input-area-display criteria are met by a tap gesture including contact **3512**), and in accordance with a determination that the input that selects the live image meets one or more transcript-area-display criteria (e.g., one or more criteria based on the motion, timing, and/or intensity of a contact in the input, which are distinct from the input-area-display criteria), the device displays the digital image captured by the digital camera in the conversation transcript and sends instructions, to one or more electronic devices that correspond to the at least one other user included in the messaging session, to display the digital image captured by the digital camera in a conversation transcript corresponding to the messaging session (e.g., as illustrated in FIGS. **35**H-**35**I, where the transcript-area-display criteria are met by a press gesture including contact **3524**).

[1068] In some embodiments, the electronic device includes one or more sensors configured to detect intensities of contacts on the touch-sensitive surface. Detecting the input that selects the live image displayed within the plurality of digital images includes that the device detects (**4222**) a first contact at a location on the touch-sensitive surface that corresponds to display of the live image on the display. The one or more transcript-area-display criteria require that a characteristic intensity of the first contact on the touch-sensitive surface meet a respective intensity threshold in order for the transcript-area-display criteria to be met (e.g., transcript-area-display criteria are met in FIG. **35**I because a characteristic intensity of contact **3524** meets a predefined intensity threshold (e.g., IT_L or IT_D)). The one or more input-area-display criteria do not require that the characteristic intensity of the contact on the touch-sensitive surface meet the respective intensity threshold in order for

the selection criteria to be met (e.g., input-area-display criteria are met in Figure in FIGS. **35**D-**35**E even though a characteristic intensity of contact **3512** did not meet a predefined intensity threshold (e.g., IT_L or IT_D)).

[1069] In some embodiments, the input-area-display criteria are met when a characteristic intensity of the first contact is between a first intensity threshold and a second intensity threshold and the transcript-area-display criteria are met when a characteristic intensity of the first contact is between the second intensity threshold and a third intensity threshold. In some embodiments, the second intensity threshold is above the first intensity threshold and the third intensity threshold is above the second intensity threshold (e.g., tap to display the digital image in the message input area before posting the image to the messaging session and light press (or deep press) to post the digital image directly to the messaging session). In some embodiments, the second intensity threshold is below the first intensity threshold and the third intensity threshold is below the second intensity threshold (e.g., deep press) to display the digital image in the message input area before posting the image to the messaging session and tap to post the digital image directly to the messaging session).

[1070] In some embodiments, the one or more input-area-display criteria are met upon detection (**4224**) of a tap gesture on the touch-sensitive surface (e.g., a tap gesture including contact **3512** in FIG. **35**D).

[1071] In some embodiments, prior to detecting the input that selects the live preview image (or a previously captured digital image) displayed within the plurality of digital images, the device detects a first portion of a second input that includes detecting an increase in a characteristic intensity of a second contact, at a location that corresponds to display of a first digital image within the plurality of digital images above a preview-intensity threshold. For example, device **100-1** detects an input including contact **3540**, which increases in intensity above a predefined intensity threshold (e.g., IT_L or IT_D) between FIG. **35**R and **35**S. In some embodiments, the first digital image is the live preview image (e.g., live preview image **3514**). In some embodiments, the first digital image is a previously acquired image (e.g., previously captured digital image **3518-4** in FIG. **35**R).

[1072] In response to detecting the first portion of the second input, the device increases (**4226**) the size of the first digital image. For example, in response to detecting the increase in intensity of contact **3540**, device **100-1** displays enlarged preview **3507** of digital image **3518-4** in FIG. **35**S. In some embodiments, the size of the first digital image is increased dynamically in accordance with the increase in the characteristic intensity of the second contact. After increasing the size of the first digital image, detecting a second portion of the second input that includes detecting a decrease in the characteristic intensity of the second contact below the preview intensity threshold and, in response to detecting the second portion of the second input, decreasing the size of the first digital image. For example, device **100-1** detects a decrease in the intensity of contact **3540** between FIGS. **35**S and **35**T and, in response, shrinks image **3518-4** back to its original size in the digital image tray in FIG. **35**T.

[1073] [**001015**] In some embodiments, the device detects a user input including a first swipe gesture that starts while a focus selector is at a first location in the messaging user interface that corresponds to a first digital image in the plurality of digital images, the first swipe gesture moving the focus selector in a first direction (e.g., detects a drag gesture by a contact on a touch-sensitive surface, such as a touch sensitive display, that starts at the first digital image and moves in a first direction (e.g., towards the edge of the display), or detects a swipe gesture by a contact on a touch-sensitive surface that starts while a cursor or other pointer is at the first digital image on the display and moves the pointer in a first direction on the display). For example, device **100-1** detects a swipe gesture to the left, including movement **3538** of contact **3536** from location **3536-*a*** in FIG. **35**P to location **3536-*b*** in FIG. **35**Q.

[1074] In response to detecting the first swipe gesture, the device scrolls display (**4228**) of the plurality of digital images in the first direction on the display, wherein the scrolling display includes ceasing to display digital images in the plurality of digital images that are scrolled off a first edge of the display and displaying new digital images in the plurality of digital images from a second (e.g., opposite) edge of the display (e.g., photos are scrolled off the display in the direction of the swipe gesture and new images are brought onto the display from the opposite edge of the display). For example, in FIG. **35**Q, device **100-1** moves digital image tray **3806** to the left, in accordance with movement **3538**, creating the appearance that live preview image **3514** slides off of the left side of touch screen **112** and additional digital images **3518-6** and **3518-7** slide onto the display from the right side of touch screen **112**, in FIG. **35**Q.

[1075] In some embodiments, the device detects a user input including a second swipe gesture that starts while a focus selector is at a first location in the messaging user interface that corresponds to a first digital image in the plurality of digital images, the first swipe gesture moving the focus selector in a second direction (e.g., opposite of the first direction; e.g., the device detects a drag gesture by a contact on a touch-sensitive surface, such as a touch sensitive display, that starts at the first digital image and moves in a second direction (e.g., towards an opposite edge of the display), or detects a swipe gesture by a contact on a touch-sensitive surface that starts while a cursor or other pointer is at the first digital image on the display and moves the pointer in a second direction on the display. For example, device **100-1** detects a swipe gesture to the right, including movement of contact **3812** from position **3812-*a*** in FIG. **38**F to position **3812-*b*** in FIG. **38**G.

[1076] In response to detecting the second swipe gesture, the device displays (**4230**) (e.g., reveals from a first edge of the display) a first affordance for the digital camera and a second affordance for a photo library. For example, full-screen camera affordance **3816** and photo library affordance **3818** are revealed in digital image tray **3806**, from the left side of touch screen **112**, in response to detecting the swipe gesture including movement **3814** of contact **3812** FIG. **38**G.

[1077] In some embodiments, while displaying the first affordance for the digital camera (e.g., camera affordance **3816** in FIG. **38**H), the device detects an input that activates the first affordance for the digital camera (e.g., contact **3820** in FIG. **38**H) and, in response to detecting the input that activates the first affordance for the digital camera, the device displays (**4232**) a user interface for the digital camera over at least a portion of the messaging user interface (e.g., user interface **3822** displayed in FIG. **38**I). In some embodi-

ments, the interactive application user interface entirely replaces display of the messaging user interface (e.g., as in FIG. **38**I).

[1078] In some embodiments, while displaying the second affordance for the photo library (affordance **3818** in FIG. **38**O), the device detects an input that activates the second affordance for the photo library (e.g., contact **3830** in FIG. **38**O) and, in response to detecting the input that activates the second affordance for the photo library, the device ceases (**4234**) to display the plurality of digital images including one or more digital images stored in the memory and a live preview image from the digital camera and displays a plurality of digital images from a digital photo library (e.g., a photo library stored on the electronic device or a photo library stored remotely). For example, in response to detecting an input including contact **3830** in FIG. **38**O, device **100-1** replaces display of messenger user interface **3500** in FIG. **38**O with photo library user interface **3832** in FIG. **38**P.

[1079] While displaying the plurality of digital images from the digital photo library, the device detects an input that selects a digital image in the plurality of digital images from the digital photo library and in response to detecting the input that selects the digital image from the digital photo library, the device displays the digital image from the digital photo library in the conversation transcript. In some embodiments, the digital image is automatically posted to the messaging session upon selection of the image. In some embodiments, the digital image is displayed in the message input area and the user posts the image to the messaging session (e.g., by activating a send icon with a tap gesture). The device also transmit a representation of the digital image from the digital photo library to one or more electronic devices that correspond to the at least one other user included in the messaging session (e.g., "Abe"), where the one or more electronic devices display the representation of the digital image from the digital photo library in a conversation transcript that corresponds to the messaging session.

[1080] It should be understood that the particular order in which the operations in FIGS. **42**A-**42**D have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4400**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6400**, **6600**, **6800**, and **7000**) are also applicable in an analogous manner to method **4200** described above with respect to FIGS. **42**A-**42**D. For example, the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, and animations described above with reference to method **4200** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4400**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6400**, **6600**, **6800**, and **7000**). For brevity, these details are not repeated here.

[1081] In accordance with some embodiments, FIG. **43** shows a functional block diagram of an electronic device **4300** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. **43** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[1082] As shown in FIG. **43**, an electronic device **4300** includes a display unit **4302** configured to display user interfaces, a touch-sensitive surface unit **4304**, optional sensor unit(s) **4306**, a digital camera unit **4308** configured to capture images, a memory unit **4310**, and a processing unit **4312** coupled to the display unit **4302**, the digital camera unit **4308**, the touch-sensitive surface unit **4304**, and the memory unit **4310**. In some embodiments, the processing unit includes a display enabling unit **4314**, a detecting unit **4316**, an image capturing unit **4318**, a transmitting unit **4320**, an editing unit **4322**, and a scrolling unit **4324**.

[1083] The processing unit **4312** is configured to display (e.g., with display enabling unit **4314**) a messaging user interface on the display unit, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a keyboard, a message-input area, and a digital image affordance. The processing unit **4312** is further configured to, while displaying the messaging user interface, detect (e.g., with detecting unit **4316**) an input that activates the digital image affordance. The processing unit **4312** is further configured to, in response to detecting the input that activates the digital image affordance, replace display (e.g., with display enabling unit **4314**) of the keyboard with display of a plurality of digital images, the plurality of digital images including one or more digital images stored in the memory unit **4310** and a live preview image from the digital camera unit **4308**. The processing unit **4312** is further configured to detect (e.g., with detecting unit **4316**) an input that selects the live image displayed within the plurality of digital images. The processing unit **4312** is further configured to, in response to detecting that input that selects the live image, capture (e.g., with image capture unit **4320**) a digital image with the digital camera unit **4308**, while maintaining display of the conversation transcript.

[1084] In some embodiments, the processing unit **4312** is configured to, after capturing the digital image, display (e.g., with display enabling unit **4314**) the digital image captured by the digital camera unit **4308** in the conversation transcript, and transmit (e.g., with transmitting unit **4320**) a representation of the captured digital image to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the captured digital image in a conversation transcript that corresponds to the messaging session.

[1085] In some embodiments, the processing unit **4312** is configured to, prior to displaying the digital image captured by the digital camera unit **4308** in the conversation transcript and transmitting a representation of the captured image, display (e.g., with display enabling unit **4314**) the digital image captured by the digital camera unit **4308** in the

message input area. The processing unit **4312** is further configured to, while displaying the digital image captured by the digital camera unit **4308** in the message input area, detect (e.g., with detecting unit **4316**) an input that activates an image editing mode. The processing unit **4312** is further configured to, in response to detecting the input that activates the image editing mode, replace display (e.g., with display enabling unit **4314**) of the messaging user interface with display of a digital photo editing user interface, wherein the digital image captured by the digital camera unit **4308** is displayed in the digital photo editing user interface. The processing unit **4312** is further configured to, while displaying the digital photo editing mode, detect (e.g., with detecting unit **4316**) an input that edits the digital photo captured by the digital camera unit **4308**. The processing unit **4312** is further configured to, in response to detecting the input that edits the digital photo captured by the digital camera unit **4308**, edit (e.g., with editing unit **4322**) the digital image captured by the digital camera unit **4308**. The processing unit **4312** is further configured to, after editing the digital image captured by the digital camera unit **4308**, detect (e.g., with detecting unit **4316**) an input terminating the digital image editing mode. The processing unit **4312** is further configured to, in response to detecting the input terminating the digital image editing mode, display (e.g., with display enabling unit **4314**) the edited digital image captured by the digital camera unit **4308** in the message input area.

[1086] In some embodiments, the processing unit **4312** is configured to, in response to detecting the input that selects the live preview image, and after capturing the digital image, display (e.g., with display enabling unit **4314**) the digital image in the message-input area. The processing unit **4312** is further configured to, while displaying the digital image in the message-input area, detect (e.g., with detecting unit **4316**) input of a message in the message input area. The processing unit **4312** is further configured to, after detecting input of the message in the message-input area, detect (e.g., with detecting unit **4316**) an input that corresponds to a request to post contents of the message-input area to the messaging session, the contents including the digital image and the message. The processing unit **4312** is further configured to, in response to detecting the input that corresponds to the request to post the contents of the message-input area to the messaging session: display (e.g., with display enabling unit **4314**) the digital image in the conversation transcript, display (e.g., with display enabling unit **4314**) the message in the conversation transcript, wherein the message partially overlaps the digital image in the conversation transcript, and transmit (e.g., with transmitting unit **4320**) a representation of the digital image and the message to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the digital image and the message in a conversation transcript corresponding to the messaging session, wherein the message partially overlaps the representation of the digital image in the conversation transcript corresponding to the messaging session.

[1087] In some embodiments, the processing unit **4312** is configured to, in response to detecting the input that selects the live image, in accordance with a determination that the input that selects the live image meets one or more input-area-display, display (e.g., with display enabling unit **4314**) the digital image captured by the digital camera unit **4308** in the message input area. The processing unit **4312** is further configured to, in accordance with a determination that the input that selects the live image meets one or more transcript-area-display criteria, display (e.g., with display enabling unit **4314**) the digital image captured by the digital camera unit **4308** in the conversation transcript, and send (e.g., with transmitting unit **4320**) instructions, to one or more electronic devices that correspond to the at least one other user included in the messaging session, to display the digital image captured by the digital camera unit **4308** in a conversation transcript corresponding to the messaging session

[1088] In some embodiments, the electronic device includes one or more sensors units **4306** configured to detect intensities of contacts on the touch-sensitive surface unit **4304**. In some embodiments, detecting the input that selects the live image displayed within the plurality of digital images includes detecting a first contact at a location on the touch-sensitive surface unit **4304** that corresponds to display of the live image on the display unit. In some embodiments, the one or more transcript-area-display criteria require that a characteristic intensity of the first contact on the touch-sensitive surface unit **4304** meet a respective intensity threshold in order for the transcript-area-display criteria to be met. In some embodiments, the one or more input-area-display criteria do not require that the characteristic intensity of the contact on the touch-sensitive surface unit **4304** meet the respective intensity threshold in order for the selection criteria to be met.

[1089] In some embodiments, the one or more input-area-display criteria are met upon detection of a tap gesture on the touch-sensitive surface unit **4304**.

[1090] In some embodiments, the processing unit **4312** is configured to, prior to detecting the input that selects the live image displayed within the plurality of digital images, detect (e.g., with detecting unit **4316**) a first portion of a second input that includes detecting an increase in a characteristic intensity of a second contact, at a location that corresponds to display of a first digital image within the plurality of digital images, above a preview intensity threshold. The processing unit **4312** is further configured to, in response to detecting the first portion of the second input, increase the size of the first digital image. The processing unit **4312** is further configured to, after increasing the size of the first digital image, detect (e.g., with detecting unit **4316**) a second portion of the second input that includes detecting a decrease in the characteristic intensity of the second contact below the preview intensity threshold. The processing unit **4312** is further configured to, in response to detecting the second portion of the second input, decrease the size of the first digital image.

[1091] In some embodiments, the processing unit **4312** is configured to detect (e.g., with detecting unit **4316**) a user input including a first swipe gesture that starts while a focus selector is at a first location in the messaging user interface that corresponds to a first digital image in the plurality of digital images, the first swipe gesture moving the focus selector in a first direction. The processing unit **4312** is further configured to, in response to detecting the first swipe gesture, scroll display (e.g., with scrolling unit **4324**) of the plurality of digital images in the first direction on the display unit, wherein the scrolling display includes ceasing to display digital images in the plurality of digital images that are scrolled off a first edge of the display unit and displaying

new digital images in the plurality of digital images from a second edge of the display unit.

[1092] In some embodiments, the processing unit **4312** is configured to detect (e.g., with detecting unit **4316**) a user input including a second swipe gesture that starts while a focus selector is at a first location in the messaging user interface that corresponds to a first digital image in the plurality of digital images, the first swipe gesture moving the focus selector in a second direction. The processing unit **4312** is further configured to, in response to detecting the second swipe gesture, display (e.g., with display enabling unit **4314**) a first affordance for the digital camera unit **4308** and a second affordance for a photo library.

[1093] In some embodiments, the processing unit **4312** is configured to, while displaying the first affordance for the digital camera unit **4308**, detect (e.g., with detecting unit **4316**) an input that activates the first affordance for the digital camera unit **4308**. The processing unit **4312** is further configured to, in response to detecting the input that activates the first affordance for the digital camera unit **4308**, display (e.g., with display enabling unit **4314**) a user interface for the digital camera unit **4308** over at least a portion of the messaging user interface.

[1094] In some embodiments, the processing unit **4312** is configured to, while displaying the second affordance for the photo library, detect (e.g., with detecting unit **4316**) an input that activates the second affordance for the photo library. The processing unit **4312** is further configured to, in response to detecting the input that activates the second affordance for the photo library, cease to display (e.g., with display enabling unit **4314**) the plurality of digital images including one or more digital images stored in the memory unit **4310** and a live preview image from the digital camera unit **4308** and display a plurality of digital images from a digital photo library. The processing unit **4312** is further configured to, while displaying the plurality of digital images from the digital photo library, detect (e.g., with detecting unit **4316**) an input that selects a digital image in the plurality of digital images from the digital photo library. The processing unit **4312** is further configured to, in response to detecting the input that selects the digital image from the digital photo library, display (e.g., with display enabling unit **4314**) the digital image from the digital photo library in the conversation transcript, and transmit (e.g., with transmitting unit **4320**) a representation of the digital image from the digital photo library to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the digital image from the digital photo library in a conversation transcript that corresponds to the messaging session.

[1095] In some embodiments, the one or more digital images stored in the memory unit **4310**, and displayed in response to detecting the input that activates the digital image affordance, consist of digital images captured during the messaging session.

[1096] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[1097] The operations described above with reference to FIGS. **42**A-**42**D are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **43**. For example, detection operations **4204** and **4210** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as selection of an object on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally utilizes or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

[1098] FIGS. **44**A-**44**D are flow diagrams illustrating a method **4400** of searching for and sharing multimedia content within a messaging application in accordance with some embodiments. The method **4400** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display, a touch-sensitive surface, and one or more sensors to detect intensities of contacts with the touch-sensitive surface. In some embodiments, the display is a touch-screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **4400** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1099] As described below, the method **4400** provides an intuitive way to search for and share multimedia content within a messaging application. The method reduces the number, extent, and/or nature of the inputs from a user when searching for and sharing multimedia content within a messaging application, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to search for and share multimedia content within a messaging application faster and more efficiently conserves power and increases the time between battery charges.

[1100] The device displays (**4402**) a messaging user interface (e.g., of a messaging application, for example, user interface **3500** in FIGS. **36**A and **36**Y) on the display, the messaging user interface including a conversation transcript (e.g., displayed in a first area of the display, for example, conversation transcript **3503** in FIGS. **36**A and **36**Y) of a messaging session between a user of the electronic device and at least one other user (e.g., of another electronic device, for example "Abe," represented by avatar **3510** in FIGS. **36**A and **36**Y), and a search affordance (e.g., search affordance **3602** in FIG. **36**A or search launch icon **3607** in FIG. **36**Y). In some embodiments, the messaging user interface includes a message input area that is configured to display content ready to be posted to the messaging session (e.g., message-content input area **3502** in FIGS. **36**A and **36**Y). In some embodiments, the messaging user interface includes a

keyboard, e.g., displayed in a second area of the display (e.g., digital keyboard **3501** in FIG. **36**A).

[1101] In some embodiments, the search affordance is displayed as a launch icon for a search application in a plurality of launch icons for interactive applications within the messaging user interface (e.g., search launch icon **3607** is displayed in application selection tray **3654** with launch icons **3601**, **3603**, **3605**, **3609**, **3611**, **3613**, and **3615**). In some embodiments, the search affordance is a search application launch icon (**4404**) that is displayed with a plurality of launch icons for interactive applications within the messaging application.

[1102] In some embodiments, prior to displaying the plurality of launch icons for interactive applications in the messaging user interface, the messaging user interface included the conversation transcript (e.g., displayed in a first area of the display) of the messaging session between a user of the electronic device and at least one other user (e.g., of another electronic device), a keyboard (e.g., displayed in a second area of the display), a message-input area, and an application affordance. For example, in FIG. **36**W, user interface **3500** includes conversation transcript **3503**, keyboard **3501**, message-content input area **3502**, and application affordance **3508**. The device detects a user input that activates the application affordance (e.g., an input including contact **3652** in FIG. **36**X) and, in response to detecting the user input that activates the application affordance, the device replaces (**4406**) display of the keyboard with display of the plurality of launch icons for interactive applications (e.g., application selection tray **3654** in FIG. **36**Y replaces digital keyboard **3501** in FIG. **36**X).

[1103] In some embodiments, the messaging user interface is not displaying a digital keyboard prior to detection of the application affordance (e.g., the conversation transcript is maximized and includes display of the application affordance). For example, as illustrated in FIGS. **38**AJ-**38**AM.

[1104] In some embodiments, replacing display of the keyboard includes displaying the plurality of launch icons for interactive applications over the keyboard. In some embodiments, replacing display of the keyboard includes ceasing to display the keyboard and displaying the plurality of launch icons for interactive applications where the keyboard had been displayed.

[1105] While displaying the messaging user interface, the device detects (**4408**) an input that activates the search affordance. For example an input including contact **3602** on search affordance **3602** in FIG. **36**B or an input including contact **3656** on search application launch icon **3607** in FIG. **36**Z.

[1106] In response to detecting the input that activates the search affordance (**4410**), the device ceases to display the messaging user interface and displays a search user interface, the search user interface including a search field and a plurality of categorized content items, wherein the plurality of categorized content items includes at least a content item stored on the electronic device and a content item from the Internet. For example, in response to activating search application launch icon **3607** in FIG. **36**Z, device **100-1** ceases displaying messenger user interface **3500** and displays search user interface **3658** in FIG. **36**AA, including content items **3662**, **3664**, **3666**, **3668**, **3670**, **3672** categorized as suggested content for posting (e.g., the current location of the device **3662**, a news article **3664** being accessed from the internet, a digital recording **3666** playing on the device) and recently shared content (e.g., a news article **3668** accessed from the internet, a movie trailer **3670** accessed from the internet, and a digital image **3672**).

[1107] In some embodiments, the content items include suggested content, such as content open on the device, content recently accessed on the device (e.g., content **3662**, **3664**, and **3666** in FIG. **36**AA), content related to the messaging session (e.g., content identified as associated with any of the users of the messaging session), web content related to content open or recently opened on the device (e.g., content **3664**, **3668**, and **3670** in FIG. **36**AA), web content related to the messaging session, content related to the location of the device (e.g., content **3662** in FIG. **36**AA), recently shared content (e.g., content **3668**, **3670**, and **3672** in FIG. **36**AA), recently received content, and/or content that is trending (e.g., in a social networking application; e.g., content **3678**, **3680**, **3668**, and **3669** in FIG. **36**AE). In some embodiments, the content items are related to an input in the search field (e.g., content **3664**, **3678**, **3680**, **3670**, **3682**, and **3684** are results from a search of the word "Meteorites" in FIG. **36**F). In some embodiments, the content includes rich links, music, application links, and/or web links. In some embodiments, the plurality of categorized content items is displayed as a scrollable list of content items, arranged by content categories (e.g., additional content in FIGS. **36**AG-**36**H is accessed by scrolling the search results to the left).

[1108] While displaying the search user interface, the device detects an input that selects a first content item in the plurality of categorized content items (e.g., for an electronic device with a touch sensitive display, detecting a tap gesture on the first content item). For example, device **100-1** detects a tap gesture including contact **3674** on movie trailer **3670** in FIG. **36**AB and a tap gesture including contact **3690** on movie trailer **3684** in FIG. **36**AI.

[1109] After detecting the input that selects the first content item in the plurality of categorized content items (**4414**), the device ceases to display the searching user interface and displays the first content item in the conversation transcript within the messaging user interface. For example, in response to detecting a tap gesture including contact **3674** on movie trailer **3670** in FIG. **36**AB, device **100-1** replaces display of search user interface **3658** with display of messaging user interface **3500** in FIG. **36**AC. Similarly, in response to detecting a tap gesture including contact **3690** on movie trailer **3684** in FIG. **36**AI, device **100-1** replaces display of search user interface **3658** with display of messaging user interface **3500** in FIG. **36**AJ.

[1110] The device also transmits (**4416**) the first content item (e.g., information relating to the first content item) to one or more (e.g., second) electronic devices that correspond to the at least one other user included in the messaging session (e.g., "Abe"), where the one or more electronic devices display the first content item in a conversation transcript that corresponds to the messaging session.

[1111] In some embodiments, detecting the input that selects the first content item includes: detecting a first input while a focus selector is over the first content item, and displaying the selected first content item in a message-input area. For example, as illustrated in FIGS. **36**AI-**36**AJ. In some embodiments, while displaying the selected content item in the message-input area, the device detects a second input to post the contents of the message-input area to the conversation transcript of the messaging session. For example, device **100-1** detects a tap input including contact

3696 on send affordance **3520** in FIG. **36**AK, and posts movie trailer **3684** to the messaging session, as displayed in conversation transcript **3503** in FIG. **36**AL.

[1112] In some embodiments, the first content item is displayed in the conversation transcript of the messaging session (e.g., is directly posted to the messaging session) in response to detecting the input that selects the first content item. For example, in response to detecting a tap gesture including contact **3674** on movie trailer **3670** in FIG. **36**AB, device **100-1** posts the movie trailer directly to the messaging session, as displayed in conversation transcript **3503** in FIG. **36**AC.

[1113] In some embodiments, while displaying the search user interface, and prior to detecting the input that selects the first content item in the plurality of categorized content items, the device (**4418**) receives input of a query in the search field and, in response to receiving input of the query in the search field, updates the displayed plurality of categorized content items to display content items that satisfy the query. For example, while displaying search user interface **3658** in FIG. **36**AD, device **100-1** receives input of search query "Meterorites" in search field **3660** and, in response, displays search user interface **3661** with updated content items satisfying the query in FIG. **36**AF.

[1114] In some embodiments, in response to detecting the input that selects the first content item, the device (**4420**) displays the first content item in the message-input area, while displaying the first content item in the message-input area, receiving input of a message in the message input area (e.g., a text message). After receiving input of the message in the message-input area, the device detects an input that corresponds to a request to post the contents of the message-input area to the messaging session (e.g., detecting a tap gesture on a send icon), the contents including the first content item and the message. In response to detecting the input that corresponds to the request to post the contents of the message-input area to the messaging session, the device displays the first content item in the conversation transcript, displays the message (e.g., within a message region) in the conversation transcript, wherein the message (e.g., the message region) partially overlaps the first content item in the conversation transcript, and transmits the first content item and the message to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the first content item and the message in a conversation transcript corresponding to the messaging session, wherein the message (e.g., the message region) partially overlaps the first content item in the conversation transcript corresponding to the messaging session.

[1115] In some embodiments, in response to detecting the input that selects the first content item, the device (**4422**): in accordance with a determination that the input that selects the first content item meets one or more input-area-display criteria (e.g., one or more criteria based on the motion, timing, and/or intensity of a contact in the input), displays the first content item in the message input area (e.g., as illustrated in FIGS. **36**AI-**36**AJ), and in accordance with a determination that the input that selects the first content item meets one or more transcript-area-display criteria (e.g., one or more criteria based on the motion, timing, and/or intensity of a contact in the input, which are distinct from the input-area-display criteria) displays the first content item in the conversation transcript (e.g., as illustrated in FIGS. **36**AB-**36**AC) and transmits the first content item to one or more electronic devices that correspond to the at least one other user included in the messaging session, where the one or more electronic devices display the first content item in a conversation transcript corresponding to the messaging session.

[1116] In some embodiments, the electronic device includes one or more sensors configured to detect intensities of contacts on the touch-sensitive surface. Detecting the input that selects the first content item in the plurality of content items includes detecting a first contact at a location on the touch-sensitive surface that corresponds to display of the first content item on the display. The one or more transcript-area-display criteria require that a characteristic intensity of the first contact on the touch-sensitive surface meet a respective intensity threshold in order for the transcript-area-display criteria to be met (e.g., transcript-area-display criteria are met in FIG. **35**AB if a characteristic intensity of contact **3674** meets a predefined intensity threshold (e.g., IT_L or IT_D)). The one or more input—area-display criteria do not require that the characteristic intensity of the contact on the touch-sensitive surface meet the respective intensity threshold in order for the selection criteria to be met (e.g., input-area-display criteria are met in Figure in FIGS. **36**AI-**36**AJ even if a characteristic intensity of contact **3690** does not meet a predefined intensity threshold (e.g., IT_Lor IT_D)).

[1117] In some embodiments, (**4424**) input-area-display criteria are met when a characteristic intensity of the first contact is between a first intensity threshold and a second intensity threshold and the transcript-area-display criteria are met when a characteristic intensity of the first contact is between the second intensity threshold and a third intensity threshold. In some embodiments, the second intensity threshold is above the first intensity threshold and the third intensity threshold is above the second intensity threshold (e.g., tap to display the content item in the message input area before posting the content item to the messaging session and light press (or deep press) to post the first content item directly to the messaging session). In some embodiments, the second intensity threshold is below the first intensity threshold and the third intensity threshold is below the second intensity threshold (e.g., light press (or deep press) to display the content item in the message input area before posting the content item to the messaging session and tap to post the first content item directly to the messaging session).

[1118] In some embodiments, the one or more input-area-display criteria are met (**2426**) upon detection of a tap gesture on the touch-sensitive surface (e.g., a tap gesture including contact **3690** in FIG. **36**AI).

[1119] In some embodiments, while displaying the first content item in the conversation transcript within the messaging user interface, the device (**4428**) detects a first input by a first contact at a location that corresponds to the first content item and, in response to detecting the first input, in accordance with a determination that the first contact meets one or more expansion criteria (e.g., a tap, deep press, or long press gesture), the device displays an expanded version of content associated with the first content item. For example, device **100-1** detects a tap gesture, including contact **3636**, on news article **3634** displayed in conversation transcript **3503**, in FIG. **36**P. In response, device **100-1** accesses the web page associated with the news article in

area **3638**, displayed over portions of search tray **3629** and conversation transcript **3503**, in FIG. **36**Q. Device **100-1** then displays more of the news article from the web site, in area **3638**, responsive to detecting a swipe gesture, including movement **3642** of contact **3640** from position **3640**-*a* in FIG. **36**R to position **3640**-*b* in FIG. **36**S.

[1120] In some embodiments, the expanded version of the content is navigation to a website, display of an application preview platter displaying more content than the first content item displayed in the conversation transcript, display of a video, or opening of an interactive application within the messaging application.

[1121] In some embodiments, the device detects (**4430**), in the conversation transcript, a word or phrase associated with additional content stored on the electronic device and additional content available on the Internet (e.g., business/restaurant info, music info, movie info; insert boilerplate from Siri/ontology applications). For example, device **100-1** device recognizes phrase **4103** ("Astron Omer") as the name of an actor about whom information is available on the internet. In response, the device displays highlighting **4116** of phrase **4103** in FIG. **41**D, prompting the user to select the phrase. The device then detects a tap gesture, including contact **4118**, on phrase **4103** in FIG. **41**E. In response, the device displays search user interface **3661** displaying categorized results-new articles **3664**, **3678**, and **3680** and movie previews **3670**, **3682**, and **3684**-of an internet search of phrase **4103**, in FIG. **41**F. The device detects a tap gesture, including contact **4120** in FIG. **41**G, on movie preview **3670**. In response, the device posts movie preview **3670** to the messaging session, displaying movie preview **3670** in conversation transcript **3503** in FIG. **41**H. In some embodiments, detecting the word or phrase is done in response to detecting the input that activates the search affordance. The plurality of categorized content items displayed in the search user interface includes a content item stored on the electronic device associated with the word or phrase detected in the conversation transcript.

[1122] In some embodiments, the device detects (**4432**), in the conversation transcript, a word or phrase associated with additional content stored on the electronic device and additional content available on the Internet (e.g., business/restaurant info, music info, movie info; insert boilerplate from Siri/ontology applications). In some embodiments, detecting the word or phrase is done in in response to detecting the input that activates the search affordance. The plurality of categorized content items displayed in the search user interface includes content item from the Internet associated with the word or phrase detected in the conversation transcript.

[1123] It should be understood that the particular order in which the operations in FIGS. **44**A-**44**D have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6400**, **6600**, **6800**, and **7000**) are also applicable in an analogous manner to method **4400** described above with respect to FIGS. **44**A-**44**D. For example, the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations described above with reference to method **4400** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations described herein with reference to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6400**, **6600**, **6800**, and **7000**). For brevity, these details are not repeated here.

[1124] In accordance with some embodiments, FIG. **45** shows a functional block diagram of an electronic device **4500** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. **45** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[1125] As shown in FIG. **45**, an electronic device **4500** includes a display unit **4502** configured to display user interfaces, a touch-sensitive surface unit **4504**, and a processing unit **4506** coupled to the display unit **4502** and the touch-sensitive surface unit **4504**. In some embodiments, the processing unit includes a display enabling unit **4508**, a detecting unit **4510**, a transmitting unit **4512**, a selecting unit **4514**, and an updating unit **4316**.

[1126] The processing unit **4506** is configured to: display (e.g., with display enabling unit **4508**) a messaging user interface on the display unit **4502**, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device **4500** and at least one other user, and a search affordance. The processing unit **4506** is further configured to, while displaying the messaging user interface, detect (e.g., with detecting unit **4510**) an input that activates the search affordance. The processing unit **4506** is further configured to, in response to detecting the input that activates the search affordance: cease to display (e.g., with display enabling unit **4508**) the messaging user interface, and display a search user interface, the search user interface including a search field and a plurality of categorized content items, wherein the plurality of categorized content items includes at least a content item stored on the electronic device **4500** and a content item from the Internet. The processing unit **4506** is further configured to, while displaying the search user interface, detect (e.g., with detecting unit **4510**) an input that selects a first content item in the plurality of categorized content items. The processing unit **4506** is further configured to, after detecting the input that selects the first content item in the plurality of categorized content items: cease to display (e.g., with display enabling unit **4508**) the searching user interface, display the first content item in the conversation transcript within the messaging user interface, and transmit (e.g., with transmitting unit **4512**) the first content item to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or

more electronic devices display the first content item in a conversation transcript that corresponds to the messaging session.

[1127] In some embodiments, the processing unit **4506** is configured to, while displaying the search user interface, and prior to detecting the input that selects the first content item in the plurality of categorized content items, receive input (e.g., with receiving input unit **4518**) of a query in the search field. The processing unit **4506** is further configured to, in response to receiving input of the query in the search field, update (e.g., with updating unit **4516**) the displayed plurality of categorized content items to display content items that satisfy the query.

[1128] In some embodiments, the processing unit **4506** is configured to, in response to detecting the input that selects the first content item, display (e.g., with display enabling unit **4508**) the first content item in the message-input area. The processing unit **4506** is further configured to, while displaying the first content item in the message-input area, receive input (e.g., with receiving input unit **4518**) of a message in the message input area. The processing unit **4506** is further configured to, after receiving input of the message in the message-input area, detect an input that corresponds to a request to post the contents of the message-input area to the messaging session, the contents including the first content item and the message. The processing unit **4506** is further configured to, in response to detecting the input that corresponds to the request to post the contents of the message-input area to the messaging session, display (e.g., with display enabling unit **4508**) the first content item in the conversation transcript, display (e.g., with display enabling unit **4508**) the message in the conversation transcript, wherein the message partially overlaps the first content item in the conversation transcript, and transmit (e.g., with transmitting unit **4512**) the first content item and the message to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the first content item and the message in a conversation transcript corresponding to the messaging session, wherein the message partially overlaps the first content item in the conversation transcript corresponding to the messaging session.

[1129] In some embodiments, the processing unit **4506** is configured to, in response to detecting the input that selects the first content item, in accordance with a determination that the input that selects the first content item meets one or more input-area-display criteria, display (e.g., with display enabling unit **4508**) the first content item in the message input area. The processing unit **4506** is further configured to, in accordance with a determination that the input that selects the first content item meets one or more transcript-area-display criteria: display (e.g., with display enabling unit **4508**) the first content item in the conversation transcript, and transmit (e.g., with transmitting unit **4512**) the first content item to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the first content item in a conversation transcript corresponding to the messaging session.

[1130] In some embodiments, the electronic device **4500** includes one or more sensors units configured to detect intensities of contacts on the touch-sensitive surface unit **4504**. In some embodiments, detecting the input that selects the first content item in the plurality of content items includes detecting a first contact at a location on the touch-sensitive surface unit **4504** that corresponds to display of the first content item on the display unit **4502**. In some embodiments, the one or more transcript-area-display criteria require that a characteristic intensity of the first contact on the touch-sensitive surface unit **4504** meet a respective intensity threshold in order for the transcript-area-display criteria to be met. In some embodiments, the one or more input-area-display criteria do not require that the characteristic intensity of the contact on the touch-sensitive surface unit **4504** meet the respective intensity threshold in order for the selection criteria to be met.

[1131] In some embodiments, the one or more input-area-display criteria are met upon detection of a tap gesture on the touch-sensitive surface unit **4504**.

[1132] In some embodiments, the processing unit **4506** is configured to, while displaying the first content item in the conversation transcript within the messaging user interface, detect (e.g., with detecting unit **4510**) a first input by a first contact at a location that corresponds to the first content item. The processing unit **4506** is further configured to, in response to detecting the first input, in accordance with a determination that the first contact meets one or more expansion criteria, display (e.g., with display enabling unit **4508**) an expanded version of content associated with the first content item.

[1133] In some embodiments, the processing unit **4506** is configured to detect, in the conversation transcript, a word or phrase associated with additional content stored on the electronic device **4500** and additional content available on the Internet, wherein the plurality of categorized content items displayed in the search user interface includes a content item stored on the electronic device **4500** associated with the word or phrase detected in the conversation transcript.

[1134] In some embodiments, the processing unit **4506** is configured to, detect, in the conversation transcript, a word or phrase associated with additional content stored on the electronic device **4500** and additional content available on the Internet, wherein the plurality of categorized content items displayed in the search user interface includes content item from the Internet associated with the word or phrase detected in the conversation transcript.

[1135] In some embodiments, the search affordance is a search application launch icon that is displayed with a plurality of launch icons for interactive applications within the messaging application.

[1136] In some embodiments, the processing unit **4506** is configured to, prior to displaying the plurality of launch icons for interactive applications in the messaging user interface, the messaging user interface included the conversation transcript of the messaging session between a user of the electronic device **4500** and at least one other user, a keyboard, a message-input area, and an application affordance: detect (e.g., with detecting unit **4510**) a user input that activates the application affordance. The processing unit **4506** is further configured to, in response to detecting the user input that activates the application affordance, replace display of the keyboard with display of the plurality of launch icons for interactive applications.

[1137] The operations described above with reference to FIGS. **44**A-**44**D are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **43**. For example, detection operations **4408** and **4412** are, optionally, imple-

mented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as selection of an object on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally utilizes or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

[1138] FIGS. **46**A-**46**C are flow diagrams illustrating a method **4600** of adding an interactive application to a messaging application in accordance with some embodiments. The method **4600** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display, a touch-sensitive surface, and one or more sensors to detect intensities of contacts with the touch-sensitive surface. In some embodiments, the display is a touch-screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **4600** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1139] As described below, the method **4600** provides an intuitive way to add an interactive application to a messaging application. The method reduces the number, extent, and/or nature of the inputs from a user when adding an interactive application to a messaging application, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to add an interactive application to a messaging application faster and more efficiently conserves power and increases the time between battery charges.

[1140] The device displays (**4602**) a messaging user interface of a messaging application (e.g., messaging user interface **3500** in FIG. **38**AQ) on the display, the messaging user interface including a conversation transcript (e.g., displayed in a first area of the display, such as conversation transcript **3503** in FIG. **38**AQ) of a messaging session between a user of the electronic device and at least one other user (e.g., of another electronic device), and an application affordance (e.g., application affordance **3508** in FIG. **38**AQ). In some embodiments, the messaging user interface includes a message input area that is configured to display content ready to be posted to the messaging session (e.g., message-input area **3502** in FIG. **38**AQ). In some embodiments, the messaging user interface includes a keyboard (e.g., digital keyboard **3501** in FIG. **38**AQ), e.g., displayed in a second area of the display.

[1141] While displaying the messaging user interface, the device detects (**4604**) an input that activates the application affordance. For example, a tap gesture including contact **3876** on application affordance **3508** in FIG. **38**AR.

[1142] In response to detecting the input that activates the application affordance (e.g., while maintaining display of the conversation transcript), the device concurrently displays (**4606**) a launch icon for an application store and a plurality of launch icons for interactive applications, where activation of a respective launch icon for an interactive application launches a corresponding application that is displayed within the messaging application. For example, in response to detecting the tap gesture including contact **3876** in FIG. **38**AR, device **100-1** displays application selection tray **3654**, including launch icon **3601** for an application store and other launch icons for interactive applications—e.g., launch icon **3603** for a tic-tac-toe application, launch icon **3605** for a reservation application, launch icon **3611** for a live video-streaming application, and launch icon **3615** for a music application.

[1143] In some embodiments, the messaging user interface is not displaying a digital keyboard just prior to detecting the input that activates the application affordance (e.g., the conversation transcript is maximized and includes display of the application affordance or the keyboard is replaced by a user interface for an interactive application that is displayed within the messaging application). In some embodiments, the plurality of launch icons for interactive applications replaces display of the keyboard. In some embodiments, replacing display of the keyboard includes ceasing to display the keyboard and displaying the plurality of launch icons for interactive applications where the keyboard had been displayed.

[1144] In some embodiments, the interactive application is configured to perform (**4608**) a subset (e.g., less than all) of the functions of a corresponding application operated separate from the messaging application. For example, in some embodiments, the application store application launched in response to activation of launch icon **3601** only allows download of applications operable within a messaging application. In contrast, a corresponding application store application (e.g., as launched from a home screen on the device outside of the messaging application) allows download of applications operable within a messaging application and applications operable outside of the messaging application.

[1145] In some embodiments, the interactive application launch icon displays (**4610**) an identifier for a corresponding application operated separate from the messaging application. For example, in FIG. **38**AS, application store launch icon **3601** includes a same or similar "A" logo as an application store application operated outside of the messaging application.

[1146] In some embodiments, the interactive application displays (**4612**) a portion (e.g., less than all) of the content displayed by a corresponding application operated separate from the messaging application. For example, in some embodiments, the application store application launched in response to activation of launch icon **3601** only displays all downloadable applications that are operable within the messaging application. In contrast, a corresponding application store application (e.g., as launched from a home screen on the device outside of the messaging application) displays all downloadable applications operable within a messaging application and operable outside of the messaging application.

[1147] In some embodiments, the interactive application causes (**4614**) the device to launch a corresponding application operated separate from the messaging application

upon detection of a predefined input. For example, in response to a first input (e.g., a tap, press, deep press, long-press, or multi-finger gesture) on application store launch icon **3601** in FIG. **38**AS, the device launches an application store application within the messaging application. In response to a second (e.g., different) input (e.g., a tap, press, deep press, long-press, or multi-finger gesture) on application store launch icon **3601** in FIG. **38**AS, the device launches an application store application outside of the messaging application.

[1148] In some embodiments, the interactive application is operated (**4616**) separately from a corresponding application operated separate from the messaging application. For example, the application store application launched in response to activation of launch icon **3601** may be operated when a corresponding application store application operated outside of the application in not running.

[1149] In some embodiments, the interactive application is operated (**4618**) in conjunction with a corresponding application operated separate from the messaging application. For example, the application store application launched in response to activation of launch icon **3601** may not be operated when a corresponding application store application operated outside of the application in not running.

[1150] In some embodiments, the interactive application has a dedicated portion of the memory for temporary storage (**4620**) that is different from a dedicated portion of the memory for temporary storage for a corresponding application operated separate from the messaging application. For example, in some embodiments, records of applications downloaded using the application store application corresponding to launch icon **3601** are stored in a different portion of memory than records of applications downloaded using a corresponding application store application operated outside of the messaging application.

[1151] In some embodiments, the corresponding application operated separate from the messaging application is configured (**4622**) to access the dedicated portion of memory for temporary storage for the interactive application. For example, in some embodiments, the corresponding application store application operated outside of the messaging application can access the records of applications downloaded using the application store application corresponding to launch icon **3601**.

[1152] The device then detects (**4624**) an input that activates the launch icon for the application store. For example, device **100-1** detects a tap gesture including a contact on application store launch icon **3601** in FIG. **38**AS.

[1153] In response to detecting the input that activates the launch icon for the application store, the device (**4626**) ceases to display the messaging user interface and displays an application store user interface, including display of at least one interactive application available for download to the electronic device. For example, responsive to detecting a tap gesture including a contact on application store launch icon **3601** in FIG. **38**S, device **100-1** replaces display of messaging user interface **3500** with display of an application store user interface.

[1154] While displaying the application store user interface, the device detects (**4628**) an input that corresponds to a request to download a first interactive application that is not stored in the memory of the electronic device. For example, device **100-1** detects a tap gesture including a contact on an icon for a tic-tac-toe application not stored on the device. In some embodiments, the input is a tap gesture on a download icon, which initiates automatic downloading and installation of the first interactive application on the device (e.g., as soon as the device detects the tap gesture, the application begins downloading on the device). In some embodiments, the input is a tap gesture on a download confirmation icon, which asks the user to confirm that the user wants to download the first interactive application and which initiates automatic downloading and installation of the first interactive application on the device (e.g., in response to detecting the tap gesture, the device displays a request to confirm the download request and/or confirm the identity of the user.

[1155] In response to detecting the input that corresponds to the request to download the first interactive application, the device (**4630**) downloads the first interactive application to the memory of the electronic device, replaces display of the application store user interface with display of the messaging user interface (e.g., messaging user interface **3500** in FIG. **38**AS), the messaging user interface including the conversation transcript (e.g., conversation transcript **3503** in FIG. **38**AS) and at least some of the plurality of launch icons for interactive applications (e.g., some of the launch icons displayed in application selection tray **3654** in FIG. **38**AS). In some embodiments, the messaging user interface also includes a messaging-input area (e.g., message-input area **3502** in FIG. **38**AS. The device also adds a launch icon that corresponds to the first interactive application to the display of the plurality of launch icons for interactive applications (e.g., the device would add application launch icon **3603** for the downloading tic-tac-toe application to application selection tray **3654** in FIG. **38**AS.

[1156] In some embodiments, adding a launch icon that corresponds to the first interactive application to the display of the plurality of launch icons for interactive applications includes displaying (**4632**) an indicia (e.g. an animation indicating) that the first interactive application is being downloaded. For example, an indicia similar to indicia **3709**, indicating download of a tic-tac-toe application, in FIG. **37**BH.

[1157] In some embodiments, the indicia (e.g., the animation) indicates (**4634**) the progress of the download of the first interactive application. For example, in FIG. **37**BH, the size of the partial circle in indicia **3709** grows, in accordance with a percentage of the application that is downloaded, until the application is completely downloaded.

[1158] It should be understood that the particular order in which the operations in FIGS. **46**A-**46**C have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6400**, **6600**, **6800**, and **7000**) are also applicable in an analogous manner to method **4600** described above with respect to FIGS. **46**A-**46**C. For example, the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations described above with reference to method **4600** optionally have one or more of the characteristics of the contacts, gestures, user interface

objects, tactile outputs, intensity thresholds, focus selectors, animations described herein with reference to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6400**, **6600**, **6800**, and **7000**). For brevity, these details are not repeated here.

[1159] In accordance with some embodiments, FIG. **47** shows a functional block diagram of an electronic device **4700** configured in accordance with the principles of the invention as described above. The functional blocks of the device may be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the invention. It is understood by persons of skill in the art that the functional blocks described in FIG. **47** may be combined or separated into sub-blocks to implement the principles of the invention as described above. Therefore, the description herein may support any possible combination or separation or further definition of the functional blocks described herein.

[1160] As shown in FIG. **47**, an electronic device **4700** includes a display unit **4702** configured to display user interfaces; a touch-sensitive surface unit **4704** configured to detect contacts; and a processing unit **4706** coupled with the display unit **4702** and the touch-sensitive surface unit **4704**. In some embodiments, the processing unit **4706** includes a detecting unit **4708**, a display enabling unit **4710**, a ceasing unit **4712**, a downloading unit **4714**, a display replacing unit **4716**, and an adding unit **4718**.

[1161] The processing unit **4706** is configured to: enable display of a messaging user interface of a messaging application on the display unit **4702**, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and an application affordance (e.g., with the display enabling unit **4710**); while displaying the messaging user interface, detect an input that activates the application affordance (e.g., with the detecting unit **4708**); in response to detecting the input that activates the application affordance, concurrently enable display of a launch icon for an application store and a plurality of launch icons for interactive applications, wherein activation of a respective launch icon for an interactive application launches a corresponding application that is displayed within the messaging application (e.g., with the display enabling unit **4710**); detect an input that activates the launch icon for the application store (e.g., with the detecting unit **4708**); in response to detecting the input that activates the launch icon for the application store: cease to display the messaging user interface (e.g., with the ceasing unit **4712**), and enable display of an application store user interface, including display of at least one interactive application available for download to the electronic device (e.g., with the display enabling unit **4710**); while displaying the application store user interface, detect an input that corresponds to a request to download a first interactive application that is not stored in the memory of the electronic device (e.g., with the detecting unit **4708**); and, in response to detecting the input that corresponds to the request to download the first interactive application: download the first interactive application to the memory of the electronic device (e.g., with the downloading unit **4714**); replace display of the application store user interface with display of the messaging user interface, the messaging user interface including the conversation transcript and at least some of the plurality of launch icons for interactive applications (e.g., with the display replacing unit **4716**); and add a launch icon that corresponds to the first interactive application to the display of the plurality of launch icons for interactive applications (e.g., with the adding unit **4718**).

[1162] In some embodiments, adding a launch icon that corresponds to the first interactive application to the display of the plurality of launch icons for interactive applications includes displaying an indicia that the first interactive application is being downloaded.

[1163] In some embodiments, the indicia indicates the progress of the download of the first interactive application.

[1164] In some embodiments, the interactive application is configured to perform a subset of the functions of a corresponding application operated separate from the messaging application.

[1165] In some embodiments, the interactive application launch icon displays an identifier for a corresponding application operated separate from the messaging application.

[1166] In some embodiments, the interactive application displays a portion of the content displayed by a corresponding application operated separate from the messaging application.

[1167] In some embodiments, the interactive application causes the device to launch a corresponding application operated separate from the messaging application upon detection of a predefined input.

[1168] In some embodiments, the interactive application is operated separately from a corresponding application operated separate from the messaging application.

[1169] In some embodiments, the interactive application is operated in conjunction with a corresponding application operated separate from the messaging application.

[1170] In some embodiments, the interactive application has a dedicated portion of the memory for temporary storage that is different from a dedicated portion of the memory for temporary storage for a corresponding application operated separate from the messaging application.

[1171] In some embodiments, the corresponding application operated separate from the messaging application is configured to access the dedicated portion of memory for temporary storage for the interactive application.

[1172] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[1173] The operations described above with reference to FIGS. **46**A-**46**C are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **47**. For example, detection operations **4604** and **4624** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as selection of an object on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of

the event or sub-event. Event handler **190** optionally utilizes or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

[1174] FIGS. **48**A-**48**D are flow diagrams illustrating a method **4800** of posting messages to a messaging session from a user interface other than the user interface for the messaging application in accordance with some embodiments. The method **4800** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display, a touch-sensitive surface, and one or more sensors to detect intensities of contacts with the touch-sensitive surface. In some embodiments, the display is a touch-screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **4800** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1175] As described below, the method **4800** provides an intuitive way to post messages to a messaging session from a user interface other than the user interface for the messaging application. The method reduces the number, extent, and/or nature of the inputs from a user when posting messages to a messaging session from a user interface other than the user interface for the messaging application, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to post messages to a messaging session from a user interface other than the user interface for the messaging application faster and more efficiently conserves power and increases the time between battery charges.

[1176] The device displays (**4802**) a messaging user interface of a messaging application on the display (e.g., messaging user interface **3500** in FIGS. **37**F, **37**O, and **37**AS), the messaging user interface including a conversation transcript (e.g., displayed in a first area of the display, such as conversation transcript **3700** in FIGS. **37**F, **37**O, and **37**AS) of a messaging session between a user of the electronic device and at least one other user (e.g., of another electronic device), a first message-input area (e.g., message-input area **3502** in FIGS. **37**F, **37**O, and **37**AS), and a launch icon for an interactive application (e.g., an application operated within the messaging application than can be updated by all participants of the messaging session; e.g., launch icon **3708** for an interactive reservations application, reservations interactive application object **3728** displayed in conversation transcript **3700** in FIG. **37**O, and launch icon **3774** for an interactive tic-tac-toe application in FIG. **37**AS).

[1177] In some embodiments, once the interactive application is posted to the messaging session, any participant of the session may open the interactive application, make a change within the interactive application (e.g., change a location on a map, select a topping for a pizza, make or change an appointment, or take a turn in a game, such as tic-tac-toe), and the change is sent to all participants of the messaging session. For example, once a session of a reservations interactive application is posted to a messaging session corresponding to conversation transcript **3700**, as illustrated by display of reservation application object **3728** in transcript **3700** in FIG. **37**O, any user included in the messaging transcript can open the application session and change the time of the reservation. This is illustrated, for example, in FIGS. **37**P-**37**AC, where Abe, the operator of device **100-2**, changes the time of the reservation made by Andrew, the operator of device **100-1**, from 6:30 PM, as shown in FIG. **37**P, to 8:00 PM, as shown in FIG. **37** AC.

[1178] In some embodiments, the first message input area is configured to display text and other content ready to be posted to the messaging session. For example, after receiving input of message **3736** in FIG. **37**N, the message is posted to the messaging session, as illustrated by display of message **3736** in conversation transcript **3700** in FIG. **37**O.

[1179] In some embodiments, the launch icon for the interactive application is concurrently displayed (**4804**) with a plurality of launch icons for other interactive applications in the messaging user interface. For example, launch icon **3603** for an interactive tic-tac-toe application and launch icon **3605** for an interactive reservation application are displayed in application selection tray **3654** with other launch icons for interactive applications—e.g., application launch icon **3611** for a live video-streaming application, application launch icon **3613** for an interactive pizza ordering application, and application launch icon **3615** for an interactive music application.

[1180] In some embodiments, the interactive application launch icon displays (**4806**) an identifier for a corresponding application operated separate from the messaging application. For example, application launch icon **3708** for an interactive reservations application displays concentric circle identifiers for a corresponding reservation application operated outside of the messaging application.

[1181] While displaying the messaging user interface, the device detects (**4808**) an input that activates the launch icon for the interactive application. In some embodiments, the input is a tap gesture on the launch icon. For example, device **100-1** detects a tap gesture including contact **3710** on launch icon **3708** in FIG. **37**F, activating a corresponding interactive reservations application in FIG. **37**G. For example, device **100-2** detects a tap gesture including contact **3738** on reservations application object **3728** in FIG. **37**P, activating a corresponding interactive reservations application in FIG. **37**Q. For example, device **100-1** detects a tap gesture including contact **3776** on tic-tac-toe application launch icon **3774** in FIG. **37**AT, activating a corresponding interactive tic-tac-toe application in FIG. **37**AU.

[1182] In some embodiments, detecting the input that activates the launch icon for the interactive application includes (**4810**) detecting a first input by a first contact at a location corresponding to the launch icon for the interactive application, in response to detecting the first input, displaying a menu that includes a plurality of options for how to run the interactive application (e.g., to play tic-tac-toe as "X" or "O"; to operate the interactive application in full-screen mode or embedded within the messaging user interface), and detecting a second input that selects a first option in the plurality of options for how to run the interactive application.

[1183] For example, device **100-1** detects a tap gesture including contact **3776** on tic-tac-toe launch icon **3774** in FIG. **37**AT. In response to detecting the contact, the device displays menu **3778** including options **3780-1** and **3780-2** for playing the game as 'O' or 'X', respectively. Responsive to detecting selection of 'O' via a tap gesture on affordance

3780-1, including contact **3782** in FIG. **37**AV, device **100-1** displays tic-tac-toe user interface **3784** over a portion of messaging user interface **3500** in FIG. **37**AW.

[1184] In some embodiments, the second input is a continuation of the first input, such as, dragging a first contact to a location corresponding to the first option and lifting-off, or increasing the intensity of the first contact, to select the first option. In some embodiments, the second input is by a second contact at a location corresponding to the first option, e.g., a tap gesture on the first option. In some embodiments, the menu is displayed on top of the launch icon and/or the plurality of launch icons. In some embodiments, the menu replaces display of the interactive launch icon, which includes ceasing to display the launch icon or plurality of launch icons and displaying the menu where the launch icon(s) had been displayed. For example, menu **3778** in FIG. **37**AU replaces display of interactive launch icon **3774** in response to detecting contact **3776** in FIG. **37**AT.

[1185] In response to detecting the input that activates the launch icon for the interactive application, the device displays (**4812**) a user interface for the interactive application (e.g., an "interactive application user interface"). The interactive application user interface includes a second message-input area that is distinct from the first message-input area. For example, interactive reservation application user interface **3712** includes message-input area **3716** in FIGS. **37**G and **37**Q, which is separate from message-input area **3502** displayed in the messaging user interface **3500** in FIGS. **37**F and **37**P. Similarly, interactive tic-tac-toe application user interface **3784** includes message-input area **3716** in FIG. **37**AW, which is separate from message-input area **3502** displayed in the messaging user interface **3500**, as seen in the background of FIG. **37**AW.

[1186] In some embodiments, the interactive application user interface is displayed over at least a portion of the messaging user interface. For example, interactive tic-tac-toe application user interface **3784** is displayed over a portion of messaging user interface **3500** in FIG. **37**AW. In some embodiments, where the interactive application user interface is displayed over a portion of the messaging user interface, the messaging user interface is blurred, faded, or otherwise obscured to emphasize display of the interactive application user interface.

[1187] In some embodiments, the interactive application user interface replaces display of the messaging user interface. For example, interactive reservations application user interface **3712**, illustrated in FIG. **37**G, replaces display of messaging user interface **3500** in FIG. **37**F, upon activation.

[1188] In some embodiments, the interactive application user interface, or a portion of the interactive application user interface (e.g., where the interactive application user interface is displayed in more than one continuous area on the display) is displayed within the message transcript. For example, pizza application object **3735**, displayed within transcript **3700** in FIG. **37**CA, is a non-contiguous portion of the user interface for an interactive pizza ordering application, because it displays a current status of the pizza being ordered. For example, in response to pepperoni being added to the pizza in FIG. **37**CD, pizza ordering application object **3735** displays pepperoni on the pizza in FIG. **37**CE.

[1189] In some embodiments, the user interface for the interactive application includes (**4814**) at least one avatar, each respective avatar in the at least one avatar corresponding to a user in the at least one other user included in the messaging session. For example, user interface **3712** for an interactive reservation application displays avatar **3510** corresponding to Abe, when displayed on device **100-1** (e.g., operated by Andrew) in FIG. **37**G, and displays avatar **3511** corresponding to Andrew, when displayed on device **100-2** (e.g., operated by Abe).

[1190] In some embodiments, the user interface for the interactive application includes (**4816**) a plurality of avatars displayed as a stack of avatars (e.g., an overlapping stack of avatars, such as stack of avatars **4002** in FIG. **40**A.

[1191] In some embodiments, while displaying the interactive application user interface, the device (**4818**) detects a third input by a third contact at a location corresponding to an avatar within the user interface for the interactive application and, in response to detecting the third input, displaying a menu of actions, that are associated with the avatar (e.g., for sending to the user associated with the avatar a personal message, calling, video chatting, sending a payment, and/or sending a digital touch). In some embodiments, the menu or actions is overlaid on top of the user interface for the interactive application. For example, responsive to detecting a input including an increase in a characteristic intensity of contact **3799** from FIG. **37**AM to **37**AM, while over avatar **3510** in reservations application user interface **3712**, menu **3882** of actions **3884** is displayed in FIG. **37**AN.

[1192] In some embodiments, the interactive application is configured (**4820**) to perform a subset (e.g., less than all) of the functions of a corresponding application operated separate from the messaging application. For example, in some embodiments, an interactive reservations application operated within a messaging application is be configured to allow making reservations but not configured to allow users to comment on a restaurant. In contrast, the corresponding reservation application operable outside of the messaging application is configured to allow making reservations and commenting on a restaurant.

[1193] In some embodiments, the interactive application displays (**4822**) a portion (e.g., less than all) of the content displayed by a corresponding application operated separate from the messaging application. For example, in some embodiments, an interactive reservations application operated within a messaging application displays restaurant ratings but not user comments on a restaurant. In contrast, the corresponding reservation application operable outside of the messaging application displays both restaurant ratings and user comments on a restaurant.

[1194] In some embodiments, the interactive application causes (**4824**) the device to launch a corresponding application operated separate from the messaging application upon detection of a predefined input. For example, in response to a first input (e.g., a tap, press, deep press, long-press, or multi-finger gesture) on interactive reservations application launch icon **3708** in FIG. **37**F, the device launches the interactive reservations application within the messaging application. In response to a second (e.g., different) input (e.g., a tap, press, deep press, long-press, or multi-finger gesture) on interactive reservations application launch icon **3708** in FIG. **37**F, the device launches a reservations application outside of the messaging application.

[1195] In some embodiments, the interactive application is operated (**4826**) separately from a corresponding application operated separate from the messaging application. For example, the interactive reservations application launched in response to activation of launch icon **3708** in FIG. **37**F is

operable when a corresponding reservations application operated outside of the messaging application is not running.

[1196] In some embodiments, the interactive application is operated (**4828**) in conjunction with a corresponding application operated separate from the messaging application. For example, the interactive reservations application launched in response to activation of launch icon **3708** in FIG. **37**F is not operable when a corresponding reservations application operated outside of the messaging application is not running.

[1197] In some embodiments, the interactive application has a dedicated portion of the memory for temporary storage (**4830**) that is different from a dedicated portion of the memory for temporary storage for a corresponding application operated separate from the messaging application. For example, in some embodiments, records of reservations made using the interactive reservations application operated within the messaging application are stored in a different portion of memory than records of reservations made using a corresponding reservations application operated outside of the messaging application.

[1198] In some embodiments, the corresponding application operated separate from the messaging application is configured (**4832**) to access the dedicated portion of memory for temporary storage for the interactive application. For example, in some embodiments, the corresponding reservations application operated outside of the messaging application can access the records of reservations made using the interactive reservations application operated within the messaging application.

[1199] While displaying the interactive application user interface, the device detects (**4834**) an input of a first message in the second message-input area. For example, while displaying interactive reservations application user interface **3712**, device **100-2** detects input of message **3746** in message-input area **3716** in FIG. **37**S.

[1200] In response to detecting the input of the first message in the second message-input area, the device displays (**4836**) the first message in the second message-input area. For example, in response to detecting input of message **3746**, device **100-2** displays the message in message-input area **3716** in FIG. **37**T.

[1201] While displaying the first message in the second message-input area, the device detects (**4838**) an input that corresponds to a request to post the contents of the second message-input area to the messaging session. In some embodiments, the input is a tap gesture on a send icon. For example, device **100-2** detects an input including contact **3748** on sending affordance **3520** in FIG. **37**U.

[1202] In response to detecting the input that corresponds to the request to post the contents of the second message-input area to the messaging session, the device transmits (**4840**) the first message to one or more (e.g., second) electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the first message in a conversation transcript corresponding to the messaging session. For example, in response to detecting the input including contact **3748** on sending affordance **3520** in FIG. **37**U, device **100-2** transmits message **3746** at 9:29 AM to other device **100-1** associated with Andrew, who is included in the messaging session. Device **100-1** receives message **3746** and displays it within conversation transcript **3700** at 9:29 AM, in FIG. **37**AE.

[1203] In some embodiments, after detecting the input that corresponds to the request to post the contents of the second message-input area to the messaging session, and while displaying the user interface for the interactive application, the device detects an input terminating the interactive application (e.g., a tap on the close button; for example, a tap gesture including contact **3756** on exit affordance **3714** in FIG. **3756**) and, in response to detecting the input terminating the interactive application, the device (**4842**) ceases to display the user interface for the interactive application and displays the messaging user interface, the messaging user interface including display of the first message in the conversation transcript. For example, responsive to a tap gesture including contact **3756** on exit affordance **3714** in FIG. **3756**, device **100-2** replaces display of interactive reservations application user interface **3712** in FIG. **37**AB with display of messaging user interface **3500** in FIG. **37**AC. Message **3746**, posted while device **100-2** was displaying interactive reservations application user interface **3712** in FIGS. **37**U-**37**V, is displayed in conversation transcript **3700** in FIG. **37**AC.

[1204] In some embodiments, while displaying the user interface for the interactive application (e.g., in full-screen mode), the device (**4844**) receives a message associated with the messaging session and, in response to receiving the message associated with the messaging session, transiently displays the message overlaid on top of the user interface for the interactive application. For example, while displaying user interface **3712** for an interactive reservations application in full screen mode in FIG. **37**V, associated with a messaging session corresponding to conversation transcript **3700** in FIG. **37**P, device **100-2** receives message **3750**, associated with the messaging session corresponding to conversation transcript **3700** at 9:30 AM, and transiently displays the message over user interface **3712** in FIG. **37**W, even though conversation transcript **3700** is not displayed in user interface **3712**.

[1205] In some embodiments, messages associated with other messaging sessions are not displayed over the interactive application user interface when received. For example, message **4114**, posted at 9:28 AM, to a messaging session associated with conversation transcript **3503** in FIG. **41**D is not displayed over interactive user interface **3712** in FIGS. **37**Q-**37**T (e.g., at 9:28 AM), even though device **100-2** corresponds to user "Abe," who is also included in the messaging session associated with conversation transcript **3503**.

[1206] It should be understood that the particular order in which the operations in FIGS. **48**A-**48**D have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **50000**, **52000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6400**, **6600**, **6800**, and **7000**) are also applicable in an analogous manner to method **4800** described above with respect to FIGS. **48**A-**48**D. For example, the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations described above with reference to method **4800** optionally have one or more of the

characteristics of the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations described herein with reference to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **50000**, **52000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6400**, **6600**, **6800**, and **7000**). For brevity, these details are not repeated here.

[1207] In accordance with some embodiments, FIG. **49** shows a functional block diagram of an electronic device **4900** configured in accordance with the principles of the invention as described above. The functional blocks of the device may be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the invention. It is understood by persons of skill in the art that the functional blocks described in FIG. **49** may be combined or separated into sub-blocks to implement the principles of the invention as described above. Therefore, the description herein may support any possible combination or separation or further definition of the functional blocks described herein.

[1208] As shown in FIG. **49**, an electronic device **4900** includes a display unit **4902** configured to display user interfaces; a touch-sensitive surface unit **4904** configured to detect contacts; and a processing unit **4906** coupled with the display unit **4902** and the touch-sensitive surface unit **4904**. In some embodiments, the processing unit **4906** includes a detecting unit **4908**, a display enabling unit **4910**, a ceasing unit **4912**, a transmitting unit **4914**, and a receiving unit **4916**.

[1209] The processing unit **4906** is configured to: enable display of a messaging user interface of a messaging application on the display unit **4902** (e.g., with the display enabling unit **4910**), the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a first message-input area, and a launch icon for an interactive application; while displaying the messaging user interface, detect an input that activates the launch icon for the interactive application (e.g., with the detecting unit **4908**); in response to detecting the input that activates the launch icon for the interactive application, enable display of a user interface for the interactive application (e.g., with the display enabling unit **4910**), the interactive application user interface including a second message-input area that is distinct from the first message-input area; while displaying the interactive application user interface, detect input of a first message in the second message-input area (e.g., with the detecting unit **4908**); in response to detecting the input of the first message in the second message-input area, enable display of the first message in the second message-input area (e.g., with the display enabling unit **4910**); while displaying the first message in the second message-input area, detect an input that corresponds to a request to post the contents of the second message-input area to the messaging session (e.g., with the detecting unit **4908**); and, in response to detecting the input that corresponds to the request to post the contents of the second message-input area to the messaging session, transmit the first message to one or more electronic devices that correspond to the at least one other user included in the messaging session (e.g., with the transmitting unit **4914**), wherein the one or more electronic devices display the first message in a conversation transcript corresponding to the messaging session.

[1210] In some embodiments, the processing unit **4906** is further configured to: after detecting the input that corresponds to the request to post the contents of the second message-input area to the messaging session, and while displaying the user interface for the interactive application, detect an input terminating the interactive application (e.g., with the detecting unit **4908**); and, in response to detecting the input terminating the interactive application: cease to display the user interface for the interactive application (e.g., with the ceasing unit **4912**), and enable display of the messaging user interface (e.g., with the display enabling unit **4910**), the messaging user interface including display of the first message in the conversation transcript.

[1211] In some embodiments, the launch icon for the interactive application is concurrently displayed with a plurality of launch icons for other interactive applications in the messaging user interface.

[1212] In some embodiments, detecting the input that activates the launch icon for the interactive application includes: detecting a first input by a first contact at a location corresponding to the launch icon for the interactive application; in response to detecting the first input, displaying a menu that includes a plurality of options for how to run the interactive application; and detecting a second input that selects a first option in the plurality of options for how to run the interactive application.

[1213] In some embodiments, the user interface for the interactive application includes at least one avatar, each respective avatar in the at least one avatar corresponding to a user in the at least one other user included in the messaging session.

[1214] In some embodiments, the user interface for the interactive application includes a plurality of avatars displayed as a stack of avatars.

[1215] In some embodiments, the processing unit **4906** is further configured to: while displaying the interactive application user interface: detect a third input by a third contact at a location corresponding to an avatar within the user interface for the interactive application (e.g., with the detecting unit **4908**); and, in response to detecting the third input, enable display of a menu of actions, that are associated with the avatar (e.g., with the display enabling unit **4910**).

[1216] In some embodiments, the processing unit **4906** is further configured to: while displaying the user interface for the interactive application: receive a message associated with the messaging session (e.g., with the receiving unit **4916**); and, in response to receiving the message associated with the messaging session, transiently enable display of the message overlaid on top of the user interface for the interactive application (e.g., with the display enabling unit **4910**).

[1217] In some embodiments, the interactive application is configured to perform a subset of the functions of a corresponding application operated separate from the messaging application.

[1218] In some embodiments, the interactive application launch icon displays an identifier for a corresponding application operated separate from the messaging application.

[1219] In some embodiments, the interactive application displays a portion of the content displayed by a corresponding application operated separate from the messaging application.

[1220] In some embodiments, the interactive application causes the device to launch a corresponding application

operated separate from the messaging application upon detection of a predefined input.

[1221] In some embodiments, the interactive application is operated separately from a corresponding application operated separate from the messaging application.

[1222] In some embodiments, the interactive application is operated in conjunction with a corresponding application operated separate from the messaging application.

[1223] In some embodiments, the interactive application has a dedicated portion of the memory for temporary storage that is different from a dedicated portion of the memory for temporary storage for a corresponding application operated separate from the messaging application.

[1224] In some embodiments, the corresponding application operated separate from the messaging application is configured to access the dedicated portion of memory for temporary storage for the interactive application.

[1225] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[1226] The operations described above with reference to FIGS. **48**A-**48**D are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **49**. For example, detection operations **4808** and **4834** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as selection of an object on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally utilizes or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

[1227] FIGS. **50**A-**50**C are flow diagrams illustrating a method **50000** of using an interactive application in a messaging application in accordance with some embodiments. The method **50000** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display, a touch-sensitive surface, and one or more sensors to detect intensities of contacts with the touch-sensitive surface. In some embodiments, the display is a touch-screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **50000** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1228] As described below, the method **50000** provides an intuitive way to use an interactive application in a messaging application. The method reduces the number, extent, and/or nature of the inputs from a user when using an interactive application in a messaging application, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to use an interactive application in a messaging application faster and more efficiently conserves power and increases the time between battery charges.

[1229] The device displays (**50002**) a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript (e.g., displayed in a first area of the display) of a messaging session between a user of the electronic device and at least one other user (e.g., of another electronic device), a message-input area, and an icon for an interactive application ("interactive application icon" or "interactive application object") that is displayed within the conversation transcript.

[1230] As used herein, "interactive application icon" and "interactive application object" are used interchangeably to refer to an item, displayed in a conversation transcript of a messaging session, which is associated with an interactive application in a messaging application, and specifically with a session of the interactive application initiated within the messaging session. When activated in a messaging session, the interactive application object causes launch of a user interface for the associated interactive application, and specifically for the session of the interactive application initiated within the messaging session.

[1231] For example, messaging user interface **3500** in FIG. **37**K includes conversation transcript **3700**, message-input area **3502**, and icon (e.g., object) **3728** corresponding to an interactive reservations application. Icon **3728** includes identifier **3730**, representing that the icon is associated with the interactive reservations application. Icon **3728** also includes information about content input into the associated session of the interactive application, for example, that a reservation was made for two people at 6:45 PM at Joe's Bistro, serving American Fare.

[1232] As another example, messaging user interface **3500** in FIG. **37**BI includes conversation transcript **3700**, message-input area **3502**, and icon (e.g., object) **3705** corresponding to an interactive tic-tac-toe application. Icon **3502** includes an identifying image of a tic-tac-toe board with an X and an O that were entered by users in the messaging session.

[1233] As another example, messaging user interface **3500** in FIG. **37**CT includes conversation transcript **3700**, message-input area **3502**, and icon (e.g., object) **3735** corresponding to an interactive pizza ordering application. Icon **3502** does not include identifying information about the interactive application, but does include information about inputs made in the associated session of the interactive application, namely that pepperoni was added to the pizza being designed.

[1234] In some embodiments, further information about the state of the associated application or session of the interactive application is displayed proximal to an interactive application icon/object. For example, in FIG. **37**BF, additional information **3795** is displayed below icon **3705**, indicating that the corresponding interactive tic-tac-toe application is not stored in memory of device **100-2**. In another example, in FIG. **37**CS, additional information **3797** is displayed below icon **3735**, indicating that Abe added pepperoni to the pizza being designed in the session of the

interactive pizza ordering application associated with icon **3735** (e.g., the last change made with in the session of the application).

[1235] In some embodiments, no further information about the state of the associated application or session of the interactive application is displayed proximal to an interactive application icon/object. For example, in FIG. **37**K, no additional information about the state of the associated application of session of the interactive application is displayed proximal to interactive application icon **3728**.

[1236] In some embodiments, an interactive application launch icon displays (**50004**) an identifier for a corresponding application operated separate from the messaging application. In some embodiments interactive application icons/objects function as application launch icons by enabling launch of a user interface for the interactive application associated with the application icon/object. For example, upon activation of interactive application icon **3728**, by an input including contact **3738** in FIG. **37**P, device **100-2** displays user interface **3712** for the corresponding interactive reservations application in FIG. **37**Q. The display of icon **3728** includes identifier **3730** for a corresponding reservations application operated separate from the messaging application.

[1237] While displaying the messaging user interface, the device detects (**50006**) an input that activates the icon for the interactive application. In some embodiments, the input is a tap gesture on the icon. For example, device **100-2** detects an input including contact **3738** on icon **3728** for an interactive reservations application, in FIG. **37**P. As another example, device **100-2** detects an input including contact **3711** on icon **3705** for an interactive tic-tac-toe application, in FIG. **37**BJ. As another example, device **100-1** detects an input including contact **3765** on icon **3735** for an interactive pizza ordering application, in FIG. **37**CZ.

[1238] In response to detecting the input that activates the icon for the interactive application, the device displays (**50008**) a user interface for the interactive application ("interactive application user interface") in a first state. For example, device **100-2** displays user interface **3712** for an interactive reservations application in a first state that includes display of a 6:45 PM reservation for 2 people at Joe's Bistro, in FIG. **37**Q. As another example, device **100-2** displays user interface **3782** for an interactive tic-tac-toe application in a first state that includes display of an 'O' in the center square of tic-tac-toe board **7391** and display of no 'X' on tic-tac-toe board **3791**, in FIG. **37**BK. As another example, device **100-1** displays a non-contiguous user interface for an interactive pizza ordering application, including application input area **3731** and application object **3735** in a first state that includes display of pepperoni on the pizza displayed in application object **3735**. In some embodiments, the output display of an interactive application (e.g., the pizza displayed in application object **3735** in FIG. **37**DA) is also included in an application input area (e.g., the pizza could be displayed in a corner of input area **3731** in FIG. **37**DA.

[1239] In some embodiments, the interactive application user interface is displayed over at least a portion of the messaging user interface. For example, user interface **3782** for an interactive tic-tac-toe application is displayed over a portion of messaging user interface **3500** in FIG. **37**BK.

[1240] In some embodiments, the interactive application user interface replaces display of the messaging user interface. For example, user interface **3712** for an interactive reservations application in FIG. **37**Q replaces display of messaging user interface in FIG. **37**P.

[1241] In some embodiments, the interactive application user interface is displayed within the message transcript. For example, pizza application object **3735**, displayed within transcript **3700** in FIG. **37**CA, is a non-contiguous portion of the user interface for an interactive pizza ordering application, because it displays a current status of the pizza being ordered.

[1242] In some embodiments, the interactive application displays (**50010**) a portion (e.g., less than all) of the content displayed by a corresponding application operated separate from the messaging application. For example, in some embodiments, an interactive reservations application operated within a messaging application is be configured to allow making reservations but not configured to allow users to comment on a restaurant. In contrast, the corresponding reservation application operable outside of the messaging application is configured to allow making reservations and commenting on a restaurant.

[1243] In some embodiments, the interactive application causes (**50012**) the device to launch a corresponding application operated separate from the messaging application upon detection of a predefined input. For example, in response to a first input (e.g., a tap, press, deep press, long-press, or multi-finger gesture) on interactive reservations application icon **3728** in FIG. **37**P, the device launches the interactive reservations application within the messaging application. In response to a second, different input (e.g., a different one of a tap, press, deep press, long-press, or multi-finger gesture) on interactive reservations application icon **3728** in FIG. **37**P, the device launches a reservations application outside of the messaging application.

[1244] In some embodiments, the interactive application is operated (**50014**) separately from a corresponding application operated separate from the messaging application. For example, the interactive reservations application launched in response to activation of icon **3728** in FIG. **37**P is operable when a corresponding reservations application operated outside of the messaging application is not running.

[1245] In some embodiments, the interactive application is operated (**50016**) in conjunction with a corresponding application operated separate from the messaging application. For example, the interactive reservations application launched in response to activation of icon **3728** in FIG. **37**P is not operable when a corresponding reservations application operated outside of the messaging application is not running.

[1246] In some embodiments, the interactive application has a dedicated portion of the memory for temporary storage (**50018**) that is different from a dedicated portion of the memory for temporary storage for a corresponding application operated separate from the messaging application. For example, in some embodiments, records of reservations made using the interactive reservations application launched in response to activation of icon **3728** in FIG. **37**P and operated within the messaging application are stored in a different portion of memory than records of reservations made using a corresponding reservations application operated outside of the messaging application.

[1247] In some embodiments, the corresponding application operated separate from the messaging application is configured to access the dedicated portion of memory for

temporary storage for the interactive application. For example, in some embodiments, the corresponding reservations application operated outside of the messaging application can access the records of reservations made using the interactive reservations application launched in response to activation of icon **3728** in FIG. **37**P and operated within the messaging application.

[1248] While displaying the user interface for the interactive application, the device detects (**50022**) a first user input within the user interface for the interactive application. For example, device **100-2** detects an input in interactive reservations user interface **3712** including contacts **3752** in FIG. **37**X and **3754** in FIG. **37**Z. As another example, device **100-2** detects an input in interactive tic-tac-toe application user interface **3782** including contact **3713** in FIG. **37**BL. As another example, device **100-1** detects an input in interactive pizza ordering application user interface **3731** (e.g., application input area **3731**) including contacts **3767** in FIG. **37**DB and **3769** in FIG. **37**DD.

[1249] In response to detecting (or after detecting) the first user input within the user interface for the interactive application, the device (**50023**) changes display of the user interface for the interactive application from the first state to a second state (e.g., placing a second "**0**" on a tic-tac-toe board) and sends information (e.g., a meta-message, instructions, a representation of an indicia of the input), to the one or more (e.g., second) electronic devices that correspond to the at least one other user included in the messaging session, indicating that the first user input was made in the user interface for the interactive application, wherein the one or more electronic devices display an indicia of the first user input (e.g., indicate that the first user input was made).

[1250] For example, device **100-2** changes the time of the reservation from 6:45 PM to 8:00 PM in input affordance **3740-1** of interactive reservations application user interface **3712** in FIG. **37**AA. Device **100-2** also sends information, at 9:31 AM, to device **100-1** that the time of the reservation was changed. In response to receiving the information at 9:31 AM, device **100-1** indicates the change in the state of the session of the interactive reservations application by moving display of application icon (e.g., object) **3728** in conversation transcript **3700** from position **3728-*a*** in FIG. **37**AK to position **3728-*b*** in FIG. **37**AL and by changing the time of the reservation displayed within application icon **3728** from 6:45 PM in FIG. **37**AK to 8:00 PM in FIG. **37**AL.

[1251] In another example, device **100-2** places 'X' **3794** in the upper-right corner of tic-tac-toe board **3791** displayed in interactive tic-tac-toe application user interface **3782** in FIG. **37**BM. Device **100-2** also sends information, at 9:35 AM, to device **100-1** that the 'X' was placed on tic-tac-toe board **3791**. In response to receiving the information at 9:35 AM, device **100-1** indicates the change in the state of the session of the interactive tic-tac-toe application by displaying 'X' **3794** in the upper-right corner of tic-tac-toe board **3791** in FIG. **37**AZ, by moving display of application icon (e.g., object) **3786** in conversation transcript **3700** from position **3786-*a*** in FIG. **37**AY to position **3784-*b*** in FIG. **37**AZ, and by displaying additional information **3795** "Your turn," in conversation transcript **3700**, immediately below application icon **3786**, in FIG. **37**AZ.

[1252] In another example, device **100-1** displays mushrooms on the pizza displayed in application object **3735** in FIG. **37**DE. Device **100-1** also sends information, at 9:42 AM, to device **100-2** that mushrooms were added to the pizza. In response to receiving the information at 9:42 AM, device **100-2** indicates the change in the state of the session of the interactive pizza ordering application by displaying mushrooms on application object (e.g. icon) **3735** in FIG. **37**CL and by changing additional information **3797** below application object **3735** from "you added pepperoni" in FIG. **37**CK to "Andrew added mushrooms" in FIG. **37** CL.

[1253] In some embodiments, the information indicating that the first user input was made in the user interface for the interactive application includes (**50024**) information that causes movement of a corresponding icon for the interactive application within (e.g., to the end of and/or to an opposite side of) a conversation transcript corresponding to the messaging session.

[1254] For example, an interactive application icon is placed at a particular place in a conversation transcript according to when it was first opened in (e.g., posted to) the messaging session. Thereafter, the interactive application icon is moved to the end of the transcript when a device corresponding to a user included in the messaging session changes the state of the session of the interactive application.

[1255] For example, information sent to device **100-1** causes the device to move display of application icon (e.g., object) **3728** in conversation transcript **3700** from position **3728-*a*** in FIG. **37**AK to position **3728-*b*** in FIG. **37**AL.

[1256] In another example, information sent to device **100-1** causes the device to more display of application icon (e.g., object) **3786** in conversation transcript **3700** from position **3786-*a*** in FIG. **37**AY to position **3784-*b*** in FIG. **37**AZ.

[1257] In some embodiments, the information indicating that the first user input was made in the user interface for the interactive application includes (**50026**) information that causes movement of a corresponding icon for the interactive application from a first side of a conversation transcript corresponding to the messaging session to a second side of the conversation transcript

[1258] For example, an icon for an interactive application moves from the right side of the transcript to the left side of the transcript, to indicate that another user included in the messaging session (e.g., a device corresponding to another user) made a last input in the associated session of the interactive application (e.g., took a turn within the interactive application shared within the messaging session). In some embodiments, the information causes the one or more devices to move the icon only where the icon was already displayed on the first side (e.g., the side indicating that a post was made by the user of the electronic device, for example, the right side of conversation transcripts **3503** and **3700** displayed in messaging application user interface **3500**) (e.g., a condition precedent must be met for a device in the one or more devices to move the application object). Otherwise, where the application object was already displayed on the second side of the conversation transcript when the information was received, the device maintains display of the application object on the second side upon receiving the information (e.g., instructions).

[1259] For example, information sent to device **100-1** causes the device to move display of application icon (e.g., object) **3728** in conversation transcript **3700** from position **3728-*a*,** on the right side of conversation transcript **3700**, in FIG. **37**AK to position **3728-*b*,** on the left side of conversation transcript **3700**, in FIG. **37**AL.

[1260] In another example, information sent to device **100-1** causes the device to move display of application icon (e.g., object) **3786** in conversation transcript **3700** from position **3786**-*a,* on the right side of conversation transcript **3700**, in FIG. **37**AY to position **3784**-*b,* on the left side of conversation transcript **3700**, in FIG. **37**AZ.

[1261] In some embodiments, when the application icon/object is moved from a first to a second temporal location within the conversation transcript (e.g., to represent that a new input was received within the session of the corresponding interactive application), an archiving icon/object is placed in the conversation transcript at the first temporal location, to memorialize the previous input that caused the application icon/object to be displayed at the first location.

[1262] For example, device **100-1** receives information, at 9:31 AM that the time of a reservation was changed by device **100-2**. In response, the device moves interactive reservations application icon/object **3728** from position **3728**-*a,* corresponding to a first temporal location in transcript **3700** in FIG. **37**AK, to position **3728**-*b,* corresponding to a second temporal location in transcript **3700** in FIG. **37**AL. To memorialize that the reservation was first made at a time corresponding to the first temporal location position in transcript **3700** (e.g., position **3728**-*b*), device **100-1** displays interactive reservations application archiving icon/object **3756**, including information on the input made at the first time (e.g., that a reservation was made/suggested for 6:45 PM) and an symbol identifying the corresponding interactive application (e.g., the concentric circle symbol corresponding to the interactive reservations application). In some embodiments, the interactive application archiving icon/object includes only one of text describing the input and an application symbol. In some embodiments, the interactive application archiving icon/object includes both text describing the input and an application symbol.

[1263] In some embodiments, when an interactive application archiving icon/object is activated, additional information on the input associated with that time is displayed. In some embodiments, the information is displayed by opening a user interface for the interactive application in a state corresponding to the state of the session of the interactive application at the time the input was made (e.g., showing a particular tic-tac-toe move made at that time). In some embodiments, the information is displayed within or over the conversation transcript (e.g., as an expansion of the interactive application archiving icon/object or as a pop-up area displayed over/within the messaging user interface (e.g., over at least a portion of the conversation transcript).

[1264] In some embodiments, where messages posted to the conversation by the user and other participants of the messaging session are displayed on opposite sides of the display, the icon is always displayed on the side corresponding to the user that made the last input (e.g., wherein display of the interactive application icon at the first side of the conversation transcript indicates that a user of the electronic device made a last input in the interactive application user interface, and display of the interactive application icon at the second side of the conversation transcript indicates that another user included in the messaging session made a last input in the interactive application user interface).

[1265] In some embodiments, where the interactive application is a turn-based application, the icon for the interactive application is always displayed on the side of the transcript corresponding to the user whose turn it is to make an input (e.g., wherein display of the interactive application icon at the first side of the conversation transcript indicates that it is another user included in the messaging session's turn to make an input, and display of the interactive application launch icon at the second side of the conversation transcript indicates that it is the user's turn to make an input.

[1266] In some embodiments, the information indicating that the first user input was made in the user interface for the interactive application includes (**50028**) information that causes display of text, indicating the first user input was made, below (or above, next to, near, or proximate to), a corresponding icon for the interactive application within a conversation transcript corresponding to the messaging session.

[1267] For example, information sent to device **100-1** causes the device to display additional information **3795** "Your turn," in conversation transcript **3700**, below (e.g., directly below) application icon **3786**, in FIG. **37**AZ.

[1268] For example, information sent to device **100-2** causes the device to display additional information **3797** "Andrew added mushrooms" below (e.g., directly below) application object **3735** in FIG. **37** CL.

[1269] [**001211**] In some embodiments, displaying text includes changing (e.g., updating) text displayed near the application object prior to receiving the information. For example, information sent to device **100-2** causes the device to update additional information **3797** displayed below (e.g., directly below) application object **3735** from "You added pepperoni" in FIG. **37**CK to "Andrew added mushrooms" in FIG. **37** CL.

[1270] In some embodiments, the text indicates to the user that it is their turn to make a user input (e.g., "Your turn to play") or that it is another user's turn to make an input (e.g., "Abe's turn to play). In some embodiments, the text indicates the name of the user who made the user input (e.g., "Abe played an 'X'," or "Andrew changed the reservation").

[1271] In some embodiments, the information indicating that the first user input was made in the user interface for the interactive application includes (**50030**) information that causes change of the appearance of a corresponding icon for the interactive application.

[1272] For example, information sent to device **100-2** causes the device to change the time of the reservation displayed within application icon **3728** from 6:45 PM in FIG. **37**AK to 8:00 PM in FIG. **37**AL.

[1273] In another example, information sent to device **100-1** causes the device to display mushrooms on application object (e.g. icon) **3735** in FIG. **37**CL.

[1274] In some embodiments, the information indicating that the first user input was made in the user interface for the interactive application includes (**50032**) information that causes change of display of a corresponding user interface for the interactive application from a first state to a second state.

[1275] In some embodiments, where a corresponding interactive user interface is being displayed on another device when the first user makes an input (e.g., when the other device receives the information that the first user makes an input), the display of the other user is updated in real-time (e.g., an 'X' is placed on the tic-tac-toe board of the second user in real-time).

[1276] For example, interactive tic-tac-toe application user interface **3782** is displayed on touch screen **112** of device **100-1**, in FIG. **37**Y, when the device receives infor-

mation that 'X' **3794** was placed on corresponding tic-tac-board **3791** (e.g., displayed in corresponding tic-tac-toe application user interface **3782** associated with a messaging session corresponding to conversation transcript **3700**) on device **100-2** at 9:35 AM. In response, device **100-1** displays 'X' **3794** on tic-tac-toe board **3782** in FIG. **37**AZ (e.g., because interactive tic-tac-toe application user interface **3782** was being displayed when the device received the information.

[1277] In some embodiments, when the corresponding interactive interface is not being displayed on the other device, the corresponding interactive user interface is updated upon opening on the device.

[1278] In some embodiments, the interactive application is configured (**50034**) to perform a subset (e.g., less than all) of the functions of a corresponding application operated separate from the messaging application. For example, in some embodiments, an interactive reservations application operated within a messaging application is be configured to allow making reservations but not configured to allow users to comment on a restaurant. In contrast, the corresponding reservation application operable outside of the messaging application is configured to allow making reservations and commenting on a restaurant.

[1279] It should be understood that the particular order in which the operations in FIGS. **50**A-**50**C have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **52000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6400**, **6600**, **6800**, and **7000**) are also applicable in an analogous manner to method **50000** described above with respect to FIGS. **50**A-**50**C. For example, the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations described above with reference to method **50000** optionally have one or more of the characteristics of the [contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations] described herein with reference to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **52000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6400**, **6600**, **6800**, and **7000**). For brevity, these details are not repeated here.

[1280] In accordance with some embodiments, FIG. **51** shows a functional block diagram of an electronic device **51000** configured in accordance with the principles of the invention as described above. The functional blocks of the device may be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the invention. It is understood by persons of skill in the art that the functional blocks described in FIG. **51** may be combined or separated into sub-blocks to implement the principles of the invention as described above. Therefore, the description herein may support any possible combination or separation or further definition of the functional blocks described herein.

[1281] As shown in FIG. **51**, an electronic device **51000** includes a display unit **51002** configured to display user interfaces; a touch-sensitive surface unit **51004** configured to detect contacts; and a processing unit **51006** coupled with the display unit **51002** and the touch-sensitive surface unit **51004**. In some embodiments, the processing unit **51006** includes a detecting unit **51008**, a display enabling unit **51010**, a display changing unit **51012**, and a sending unit **51014**.

[1282] The processing unit **51006** is configured to: enable display of a messaging user interface of a messaging application on the display unit **51002** (e.g., with the display enabling unit **51010**), the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a message-input area, and an icon for an interactive application that is displayed within the conversation transcript; while displaying the messaging user interface, detect an input that activates the icon for the interactive application (e.g., with the detecting unit **51008**); in response to detecting the input that activates the icon for the interactive application, enable display of a user interface for the interactive application in a first state (e.g., with the display enabling unit **51010**); while displaying the user interface for the interactive application, detect a first user input within the user interface for the interactive application (e.g., with the detecting unit **51008**); and, in response to detecting the first user input within the user interface for the interactive application: change display of the user interface for the interactive application from the first state to a second state (e.g., with the display changing unit **51012**), and send information, to the one or more electronic devices that correspond to the at least one other user included in the messaging session, indicating that the first user input was made in the user interface for the interactive application (e.g., with the sending unit **51014**), wherein the one or more electronic devices display an indicia of the first user input.

[1283] In some embodiments, the information indicating that the first user input was made in the user interface for the interactive application includes information that causes movement of a corresponding icon for the interactive application within a conversation transcript corresponding to the messaging session.

[1284] In some embodiments, the information indicating that the first user input was made in the user interface for the interactive application includes information that causes movement of a corresponding icon for the interactive application from a first side of a conversation transcript corresponding to the messaging session to a second side of the conversation transcript.

[1285] In some embodiments, the information indicating that the first user input was made in the user interface for the interactive application includes information that causes display of text, indicating the first user input was made, below a corresponding icon for the interactive application within a conversation transcript corresponding to the messaging session.

[1286] In some embodiments, the information indicating that the first user input was made in the user interface for the interactive application includes information that causes change of the appearance of a corresponding icon for the interactive application.

[1287] In some embodiments, the information indicating that the first user input was made in the user interface for the interactive application includes information that causes

change of display of a corresponding user interface for the interactive application from a first state to a second state.

[1288] In some embodiments, the interactive application is configured to perform a subset of the functions of a corresponding application operated separate from the messaging application.

[1289] In some embodiments, the interactive application launch icon displays an identifier for a corresponding application operated separate from the messaging application.

[1290] In some embodiments, the interactive application displays a portion of the content displayed by a corresponding application operated separate from the messaging application.

[1291] In some embodiments, the interactive application causes the device to launch a corresponding application operated separate from the messaging application upon detection of a predefined input.

[1292] In some embodiments, the interactive application is operated separately from a corresponding application operated separate from the messaging application.

[1293] In some embodiments, the interactive application is operated in conjunction with a corresponding application operated separate from the messaging application.

[1294] In some embodiments, the interactive application has a dedicated portion of the memory for temporary storage that is different from a dedicated portion of the memory for temporary storage for a corresponding application operated separate from the messaging application.

[1295] In some embodiments, the corresponding application operated separate from the messaging application is configured to access the dedicated portion of memory for temporary storage for the interactive application.

[1296] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[1297] The operations described above with reference to FIGS. **50**A-**50**C are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **51**. For example, detection operations **50006** and **50022** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as selection of an object on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally utilizes or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

[1298] FIGS. **52**A-**52**C are flow diagrams illustrating a method **52000** of using an interactive application in a messaging application in accordance with some embodiments. The method **52000** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display, a touch-sensitive surface, and one or more sensors to detect intensities of contacts with the touch-sensitive surface. In some embodiments, the display is a touch-screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **52000** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1299] As described below, the method **52000** provides an intuitive way to use an interactive application in a messaging application. The method reduces the number, extent, and/or nature of the inputs from a user when using an interactive application in a messaging application, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to use an interactive application in a messaging application faster and more efficiently conserves power and increases the time between battery charges.

[1300] The device displays (**52002**) a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript (e.g., displayed in a first area of the display) of a messaging session between a user of the electronic device and at least one other user (e.g., of another electronic device), and a message-input area. For example, device **100-2** (operated by Abe) displays messaging user interface **3500** in FIGS. **37**J and **37**BD, including conversation transcript **3700** and message-input area **3502**.

[1301] While displaying the messaging user interface, the device receives (**52004**) instructions, from an (second) electronic device that corresponds to another user included in the messaging session (e.g., device **100-1** operated by Andrew in FIGS. and **37**F and **37**AV), to display an icon for an interactive application ("interactive application icon" or "interactive application object") in the conversation transcript.

[1302] In some embodiments, while displaying the messaging user interface, the device receives information (e.g., a meta-message, instructions, or a representation of an interactive application icon/object) from an (second) electronic device that corresponds to another user included in the messaging session (e.g., device **100-1** operated by Andrew in FIGS. and **37**F and **37**AV), that a session of an interactive application was initiated within the messaging session. In some embodiments, the information causes the electronic device to display an icon for the for the session of the interactive application in the conversation transcript.

[1303] For example, upon initiation of a session of an interactive reservations application, caused by detection of an input (e.g., a tap gesture) including contact **3710** on launch icon **3708** in FIG. **37**F, device **100-1** sends information to device **100-2** that a session of the interactive reservations application was initiated. Device **100-2** receives the information in FIG. **37**J. As another example, upon initiation of a session of an interactive tic-tac-toe application, device **100-2** receives information from device **100-1** in FIG. **37**BE that a session (e.g., game) of the interactive tic-tac-toe application was initiated.

[1304] In response to receiving the instructions, the device displays (**52008**) the icon (e.g., interactive application object) for the interactive application in the conversation transcript.

[1305] In some embodiments, in response to receiving the information that a session of an interactive application was initiated within the messaging session, the device displays an icon for the interactive application, that is associated with the session of the interactive application initiated within the messaging session, in the conversation transcript.

[1306] For example, in response to receiving information from device **100-2** in FIG. **37**J, device **100-1** displays interactive reservations application icon/object **3730** in conversation transcript **3700**, in FIG. **37**K. As another example, in response to receiving information from device **10012** in FIG. **37**BE, device **100-1** displays interactive tic-tac-toe application icon/object **3705** in conversation transcript **3700**, in FIG. **37**BF.

[1307] In some embodiments, the interactive application launch icon displays (**52006**) an identifier for a corresponding application operated separate from the messaging application. In some embodiments interactive application icons/objects function as application launch icons by enabling launch of a user interface for the interactive application associated with the application icon/object.

[1308] In some embodiments, the interactive application icon/object displays an identifier for a corresponding application operated separate from the messaging application. For example, in FIG. **37**K, interactive reservations application icon/object **3730** displays a concentric circle symbol that corresponds to a reservations application operated separate from the messaging application.

[1309] While displaying the icon for the interactive application in the conversation transcript, the device detects (**52012**) an input (e.g., a tap gesture) that activates the icon (e.g., launches the application) for the interactive application. For example, device **100-2** detects an input including contact **3738** on interactive application icon/object **3728**, in FIG. **37**P, that activates an interactive reservations application. In another example, device **100-2** detects an input including contact **3707** on interactive application icon/object **3705**, in FIG. **37**BG, that activates an interactive tic-tac-toe application.

[1310] In response to detecting (**52012**) the input that activates the icon for the interactive application displayed in the conversation transcript, in accordance with a determination that an interactive application that corresponds to the icon for the interactive application is stored in the memory of the electronic device, the device displays (**52014**) a user interface for the interactive application ("interactive application user interface").

[1311] For example, device **100-2** displays interactive reservations application user interface **3712**, in FIG. **37**Q, because the interactive reservations application was stored in the device when the activating input, including contact **3738** in FIG. **37**P, was detected.

[1312] In some embodiments, the interactive application user interface is displayed over at least a portion of the messaging user interface. For example, user interface **3782** for an interactive tic-tac-toe application is displayed over a portion of messaging user interface **3500** in FIG. **37**BK.

[1313] In some embodiments, the interactive application user interface replaces display of the messaging user interface. For example, user interface **3712** for an interactive reservations application in FIG. **37**Q replaces display of messaging user interface in FIG. **37**P.

[1314] In some embodiments, the interactive application user interface is displayed within the message transcript. For example, pizza application object **3735**, displayed within transcript **3700** in FIG. **37**CA, is a non-contiguous portion of the user interface for an interactive pizza ordering application, because it displays a current status of the pizza being ordered.

[1315] In response to detecting (**52012**) the input that activates the icon for the interactive application displayed in the conversation transcript, in accordance with a determination that the interactive application that corresponds to the icon for the interactive application is not stored in the memory of the electronic device, the device downloads the interactive application, from a remote server (e.g., a server that is part of an online application store that contains interactive applications for the messaging application), to the memory of the electronic device and, after downloading the interactive application from the remote server, displays the user interface for the interactive application.

[1316] For example, device **100-2** downloads an interactive tic-tac-toe application corresponding to interactive tic-tac-toe application icon/object **3705**, as indicated by download status indicia **3709** in FIG. **37**BH, because the application was not stored in memory of the device when the activating input, including contact **3707** in FIG. **37**BG, was detected.

[1317] In some embodiments, downloading the interactive application includes a permissive step where a user input indicates approval of the download of the interactive application (e.g., an object is displayed prompting the user to confirm download of the application and/or confirm their identity). In some embodiments, the downloading occurs in the background, without requiring user authorization.

[1318] In some embodiments, the downloading occurs without navigating away from the messaging user interface. In some embodiments, the downloading occurs while maintaining display of the messaging user interface.

[1319] In some embodiments, the interactive application user interface is displayed over at least a portion of the messaging user interface. For example, user interface **3782** for an interactive tic-tac-toe application is displayed over a portion of messaging user interface **3500** in FIG. **37**BK.

[1320] In some embodiments, the interactive application user interface replaces display of the messaging user interface. For example, user interface **3712** for an interactive reservations application in FIG. **37**Q replaces display of messaging user interface in FIG. **37**P.

[1321] In some embodiments, the interactive application user interface is displayed within the message transcript. For example, pizza application object **3735**, displayed within transcript **3700** in FIG. **37**CA, is a non-contiguous portion of the user interface for an interactive pizza ordering application, because it displays a current status of the pizza being ordered.

[1322] In some embodiments (**52032**), in accordance with a determination that the interactive application is not stored in the memory of the electronic device, the icon for the interactive application has a first appearance and, in accordance with a determination that the interactive application is stored in the memory of the electronic device, the icon for the interactive application has a second appearance that is different from the first appearance.

[1323] In some embodiments, in accordance with a determination that the interactive application is not stored in the memory of the electronic device, the device displays additional information near (e.g., below, above, next to, or proximate to) the icon for the interactive application, that indicates that the interactive application is not stored in the memory of the device. For example, device **100-2** displays additional information "Tap to download" below icon **3705** in FIG. **37**BF because the corresponding interactive tic-tac-toe application is not stored in memory of the device. In contrast, device **100-2** displays additional information "Your turn" below icon **3705** in FIG. **37**BI, after the corresponding interactive tic-tac-toe application was downloaded into memory of the device.

[1324] In some embodiments, the interactive application is configured (**52016**) to perform a subset (e.g., less than all) of the functions of a corresponding application operated separate from the messaging application. For example, in some embodiments, an interactive reservations application operated within a messaging application is be configured to allow making reservations but not configured to allow users to comment on a restaurant. In contrast, the corresponding reservation application operable outside of the messaging application is configured to allow making reservations and commenting on a restaurant.

[1325] In some embodiments, the interactive application displays (**52018**) a portion (e.g., less than all) of the content displayed by a corresponding application operated separate from the messaging application. For example, in some embodiments, an interactive reservations application operated within a messaging application is be configured to allow making reservations but not configured to allow users to comment on a restaurant. In contrast, the corresponding reservation application operable outside of the messaging application is configured to allow making reservations and commenting on a restaurant.

[1326] In some embodiments, the interactive application causes (**52020**) the device to launch a corresponding application operated separate from the messaging application upon detection of a predefined input. For example, in response to a first input (e.g., a tap, press, deep press, long-press, or multi-finger gesture) on interactive reservations application icon **3728** in FIG. **37**P, the device launches the interactive reservations application within the messaging application. In response to a second (e.g., different) input (e.g., a tap, press, deep press, long-press, or multi-finger gesture) on interactive reservations application icon **3728** in FIG. **37**P, the device launches a reservations application outside of the messaging application.

[1327] In some embodiments, the interactive application is operated (**52022**) separately from a corresponding application operated separate from the messaging application. For example, the interactive reservations application launched in response to activation of icon **3728** in FIG. **37**P is operable when a corresponding reservations application operated outside of the messaging application is not running.

[1328] In some embodiments, the interactive application is operated (**52024**) in conjunction with a corresponding application operated separate from the messaging application. For example, the interactive reservations application launched in response to activation of icon **3728** in FIG. **37**P is not operable when a corresponding reservations application operated outside of the messaging application is not running.

[1329] In some embodiments, the interactive application has a dedicated portion of the memory for temporary storage (**52026**) that is different from a dedicated portion of the memory for temporary storage for a corresponding application operated separate from the messaging application. For example, in some embodiments, records of reservations made using the interactive reservations application launched in response to activation of icon **3728** in FIG. **37**P and operated within the messaging application are stored in a different portion of memory than records of reservations made using a corresponding reservations application operated outside of the messaging application.

[1330] In some embodiments, the corresponding application operated separate from the messaging application is configured (**52028**) to access the dedicated portion of memory for temporary storage for the interactive application. For example, in some embodiments, the corresponding reservations application operated outside of the messaging application can access the records of reservations made using the interactive reservations application launched in response to activation of icon **3728** in FIG. **37**P and operated within the messaging application.

[1331] In some embodiments (**52032**), the device detects termination of the interactive application and, in response to detecting termination of the interactive application, ceases to display the user interface for the interactive application and displays (e.g., restoring partial or complete display) the messaging user interface including the conversation transcript, wherein the icon for the interactive application is displayed at a position within the conversation transcript.

[1332] For example, device **100-2** displays messaging user interface **3500**, including interactive reservations application icon/object **3728** within transcript **3700** in FIG. **37**AC, in response to detecting a termination input, including contact **3756** on termination (exiting) affordance **3714**, in FIG. **37**AB.

[1333] In another example, device **100-2** restores, in FIG. **37**BO, the partial display of messaging user interface **3500** that was obscured by display of interactive tic-tac-toe application user interface **3782** in FIG. **37**BN, including interactive tic-tac-toe application icon/object **3705** within transcript **3700** in FIG. **37**BO, in response to detecting a termination input, including contact **3717** on termination (exiting) affordance **3794**, in FIG. **37**BN.

[1334] In some embodiments, the position of the icon within the conversation transcript is dependent upon the temporal order in which the instructions to display the icon was received (e.g., when another user requested a session of the interactive application). In some embodiments, the position of the icon within the conversation transcript is dependent upon the temporal order in which the user terminated the interactive application (e.g., closing the application pushes the icon down in the transcript). In some embodiments, the position of the icon is dependent upon the temporal order in which the last input (e.g., by any user) was made within the interactive application.

[1335] It should be understood that the particular order in which the operations in FIGS. **52**A-**52**C have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods

described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6400**, **6600**, **6800**, and **7000**) are also applicable in an analogous manner to method **52000** described above with respect to FIGS. **52**A-**52**C. For example, the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, and animations described above with reference to method **52000** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6400**, **6600**, **6800**, and **7000**). For brevity, these details are not repeated here.

[1336] In accordance with some embodiments, FIG. **53** shows a functional block diagram of an electronic device **5300** configured in accordance with the principles of the invention as described above. The functional blocks of the device may be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the invention. It is understood by persons of skill in the art that the functional blocks described in FIG. **53** may be combined or separated into sub-blocks to implement the principles of the invention as described above. Therefore, the description herein may support any possible combination or separation or further definition of the functional blocks described herein.

[1337] As shown in FIG. **53**, an electronic device **5300** includes a display unit **5302** configured to display user interfaces; a touch-sensitive surface unit **5304** configured to detect contacts; and a processing unit **5306** coupled with the display unit **5302** and the touch-sensitive surface unit **5304**. In some embodiments, the processing unit **5306** includes a detecting unit **5308**, a display enabling unit **5310**, a ceasing unit **5312**, a downloading unit **5314**, and a receiving unit **5316**.

[1338] The processing unit **5306** is configured to: enable display of a messaging user interface of a messaging application on the display unit **5302** (e.g., with the display enabling unit **5310**), the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a message-input area; while displaying the messaging user interface, receiving information, from an electronic device that corresponds to another user included in the messaging session, that causes display of an icon for an interactive application in the conversation transcript (e.g., with the receiving unit **5316**); in response to receiving the information, enable display of the icon for the interactive application in the conversation transcript (e.g., with the display enabling unit **5310**); while displaying the icon for the interactive application in the conversation transcript, detect an input that activates the icon for the interactive application (e.g., with the detecting unit **5308**); and, in response to detecting the input that activates the icon for the interactive application displayed in the conversation transcript: in accordance with a determination that an interactive application that corresponds to the icon for the interactive application is stored in the memory of the electronic device, enable display of a user interface for the interactive application (e.g., with the display enabling unit **5310**), and in accordance with a determination that the interactive application that corresponds to the icon for the interactive application is not stored in the memory of the electronic device: download the interactive application, from a remote server, to the memory of the electronic device (e.g., with the downloading unit **5314**), and after downloading the interactive application from the remote server, enable display of the user interface for the interactive application (e.g., with the display enabling unit **5310**).

[1339] In some embodiments, the processing unit **5306** is further configured to: detect termination of the interactive application (e.g., with the detecting unit **5308**), and, in response to detecting termination of the interactive application: cease to display the user interface for the interactive application (e.g., with the ceasing unit **5312**); and enable display of the messaging user interface including the conversation transcript (e.g., with the display enabling unit **5310**), wherein the icon for the interactive application is displayed at a position within the conversation transcript.

[1340] In some embodiments, in accordance with a determination that the interactive application is not stored in the memory of the electronic device, the icon for the interactive application has a first appearance; and in accordance with a determination that the interactive application is stored in the memory of the electronic device, the icon for the interactive application has a second appearance that is different from the first appearance.

[1341] In some embodiments, the interactive application is configured to perform a subset of the functions of a corresponding application operated separate from the messaging application.

[1342] In some embodiments, the interactive application launch icon displays an identifier for a corresponding application operated separate from the messaging application.

[1343] In some embodiments, the interactive application displays a portion of the content displayed by a corresponding application operated separate from the messaging application.

[1344] In some embodiments, the interactive application causes the device to launch a corresponding application operated separate from the messaging application upon detection of a predefined input.

[1345] In some embodiments, the interactive application is operated separately from a corresponding application operated separate from the messaging application.

[1346] In some embodiments, the interactive application is operated in conjunction with a corresponding application operated separate from the messaging application.

[1347] In some embodiments, the interactive application has a dedicated portion of the memory for temporary storage that is different from a dedicated portion of the memory for temporary storage for a corresponding application operated separate from the messaging application.

[1348] In some embodiments, the corresponding application operated separate from the messaging application is configured to access the dedicated portion of memory for temporary storage for the interactive application.

[1349] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[1350] The operations described above with reference to FIGS. **52**A-**52**C are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **53**. For example, detection operations **52010** and **52034** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as selection of an object on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally utilizes or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

[1351] FIGS. **54**A-**54**C are flow diagrams illustrating a method **5400** of using an interactive application in a messaging application in accordance with some embodiments. The method **5400** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display, a touch-sensitive surface, and one or more sensors to detect intensities of contacts with the touch-sensitive surface. In some embodiments, the display is a touch-screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **5400** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1352] As described below, the method **5400** provides an intuitive way to use an interactive application in a messaging application. The method reduces the number, extent, and/or nature of the inputs from a user when using an interactive application in a messaging application, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to use an interactive application in a messaging application faster and more efficiently conserves power and increases the time between battery charges.

[1353] The device displays (**5402**) a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript, displayed in a first area of the display, of a messaging session between a user of the electronic device and at least one other user (e.g., of another electronic device), a first interactive application object displayed within the conversation transcript a message input area, and an input area for the first interactive application, distinct from the message input area, displayed in a second area of the display, the input area for the first interactive application including one or more input affordances.

[1354] For example, in FIGS. **37**CA and **37**DA, devices **100-2** and **100-1**, respectively, display messaging user interface **3500**, including conversation transcript **3700** displayed in a top portion of touch screen **112**, interactive pizza ordering application object **3735** within conversation transcript **3700**, and interactive pizza ordering application input area **3731** displayed in a bottom portion of touch screen **112**. Interactive pizza ordering input area **3731** includes input affordances **3733-1**, **3733-2**, and **3733-3** for adding toppings to a pizza being designed (e.g., for ordering), removing toppings from the pizza, and ordering the pizza, respectively.

[1355] In some embodiments, the interactive application object displays an output of the interactive application (e.g., an output of the interactive application is displayed on the interactive application object) in response to a user input. For example, in response to an input adding pepperoni to a pizza, including contacts **3737** and **3739** in FIGS. **37**CB and **37**CD, pepperoni is displayed on interactive pizza ordering application object **3737** in FIG. **37**CE.

[1356] In some embodiments, the input area for the interactive application is displayed in a second area of the display while the conversation transcript is displayed in the first area of the display.

[1357] In some embodiments, display of the input area for the first interactive application replaces display of the conversation transcript, the first interactive application object, and/or the message input area (e.g., in response to detecting an input that activates the first interactive application object).

[1358] In some embodiments, the device (**5404**) displays content posted to the messaging session within the conversation transcript according to a temporal order in which the content was posted and the interactive application object is displayed at a position within the conversation transcript associated with the temporal order in which a session of the interactive application was initiated. For example, the interactive application object is positioned relative to other objects in the conversation transcript (e.g., messages, multimedia, and other content) according to a temporal order when a user first posted a session of the interactive application to the messaging session.

[1359] For example, in FIGS. **37**CE-**37**CF, interactive tic-tac-toe application object **3735** is positioned between messages **3798** and **3741** in conversation transcript because message **3798** was posted to the messaging session first (e.g., at 9:36 in FIG. **37**BS), application object **3735** was posted second (e.g., at 9:37 PM in FIG. **37**CA), and message **3741** was posted last (e.g., at 9:39 AM in FIG. **37**CV).

[1360] In some embodiments, the device (**5406**) displays synchronous movement of content displayed in a temporal order within the conversation transcript (e.g., as new content is posted to the messaging session) towards an edge of the conversation transcript (e.g., the top of the conversation transcript), the displayed content including the first interactive application object and in accordance with a determination that the first interactive application object is within a predetermined distance from the edge of the conversation transcript, the device displays the first interactive application object at a fixed location on the display (e.g., at a top portion of the conversation transcript).

[1361] For example, in FIG. **37**CE, message **3798** and interactive tic-tac-toe application object **3735** are displayed according to the temporal order in which they were posted to the messaging session, as described above. In response to message **3741** being posted to the messaging session, device **100-2** moves message **3798** up and off of the top of touch screen **112** and interactive tic-tac-toe application object **3735** up to the top of conversation transcript **3700**, from position **3735**-*a*, in FIG. **37**CE, to position **3735**, in FIG. **37**CF.

Because interactive tic-tac-toe application object **3735** is displayed at a pre-defined position near the top of the displayed portion of the conversation transcript (e.g., at position **3735**-*b*) it does not continue to move up when message **3747** is posted to the messaging session in FIG. **37**CJ (e.g., is remains displayed at position **3735**-*b*).

[1362] In some embodiments, while displaying the first interactive application object at the fixed location on the display, the device continues (**5408**) to display synchronous movement of other content displayed in a temporal order within the conversation transcript.

[1363] For example, in FIGS. **37**CI-**37**CK, although interactive tic-tac-toe application object **3735** has a fixed display at position **3735**-*b,* message **3741** continues to scroll up on touch screen **112** as message **2747**, In FIG. **37**CJ, and message **3749**, in FIG. **37**CK, are posted to the messaging session.

[1364] In some embodiments, continuing to display synchronous movement of other content displayed in a temporal order with the conversation transcript includes that the device animates (**5410**) other content such that the other content appears to move behind the first interactive application object (e.g., the first interactive application UI appears to hover over the conversation transcript, which continues to scroll upwards as new content is posted to the messaging session).

[1365] For example, in FIGS. **37**CI-**37**CK, while interactive tic-tac-toe application object **3735** is fixed at position **3735**-*b,* message **3741** is animated to slide behind interactive tic-tac-toe application object **3735** as message **2747**, In FIG. **37**CJ, and message **3749**, in FIG. **37**CK, are posted to the messaging session.

[1366] In some embodiments, while displaying the first interactive application object at the fixed location on the display, the device (**5418**) detects a request to close the first interactive application (e.g., an input unpinning the interactive application object from the fixed position on the display) and, in response to detecting the request to close the first interactive application (or to unpin the interactive application object from the fixed position on the display), ceases to display the first interactive application object at the fixed location on the display and displays the first interactive application object at a position within the conversation transcript associated with the temporal order in which the session of the interactive application was initiated (e.g., the first interactive application UI is unpinned from the top of the conversation transcript and moves back to its original position within the transcript).

[1367] In some embodiments, the input unpinning the interactive application object from the fixed position on the display does not terminate display of an interactive application user interface (e.g., interactive pizza ordering application object **3735** may be unpinned from the fixed location on touch screen **112** without terminating display of interactive pizza ordering application input **3731**.

[1368] In some embodiments, the input unpinning the interactive application object from the fixed position on the display (e.g., the displayed portion of the conversation transcript) is a user input (e.g., detected on a touch-sensitive surface, such as touch screen **112**). For example, application object **3735** moves from fixed position **3735**-*b* in conversation transcript **3700**, in FIG. **37**DI, to original position **3735**-*a* (e.g., its original temporal position in the messaging session), in FIG. **37**DJ, in response to an input ordering the pizza (e.g., and closing the interactive pizza ordering application), including contact **3775** on ordering affordance **3773-3**, in FIG. **37**DI.

[1369] In some embodiments, the input unpinning the interactive application object from the fixed position on the display (e.g., the displayed portion of the conversation transcript) is an input (e.g., a meta-message, instruction, or information) from another electronic device that corresponds to another user included in the messaging session. For example, application object **3735** moves from fixed position **3735**-*b* in conversation transcript **3700**, in FIG. **37**CN, to original position **3735**-*a* (e.g., its original temporal position in the messaging session), in FIG. **37**CO (as evidenced in FIG. **37**CQ), on touch screen **112** of device **100-2** in response to receiving information from device **100-1** that the pizza was ordered.

[1370] In some embodiments, the input unpinning the interactive application object from the fixed position on the display (e.g., the displayed portion of the conversation transcript) is an automatically generated input (e.g., a command) generated in response to a condition precedent (e.g., a timing-out of the first interactive application).

[1371] In some embodiments, the interactive application object is a display and/or user interface for the interactive application.

[1372] In some embodiments, the interactive application object is a launch icon for a session of the interactive application initiated within the messaging session.

[1373] While displaying the messaging user interface including the input area for the first interactive application, including one or more input affordances, the device detects (**5420**) an input that activates a first input affordance in the input area for the interactive application. For example, device **100-2** detects an input to add pepperoni to the pizza being designed, including contact **3737**, in FIG. **37**CB, and contact **3739**, in FIG. **37**CD.

[1374] In some embodiments, after detecting the input that activates the first input affordance, the device (**5422**) updates the first interactive application object that corresponds to the first interactive application in accordance with the input that activates the first input affordance (e.g., adds a topping on the pizza) and sends information (e.g., a meta-message, instructions, or a representation of the updated interactive application object) to one or more (e.g., second) electronic devices that correspond to the at least one other user included in the messaging session, relating to the activation of the first input affordance (e.g., instructions to update a corresponding interactive application object that corresponds to the first interactive application displayed within a corresponding conversation transcript of the messaging session and/or information that pepperoni was added to the pizza).

[1375] For example, device **100-2** updates display of interactive pizza ordering application object **3735** by adding pepperoni on the pizza, in FIG. **37**CE, and sends information to device **100-1** that pepperoni was added to the pizza at 9:38 AM. Device **100-1** then updates display of interactive pizza ordering application object **3735** by adding pepperoni on the pizza, in FIG. **37**CS.

[1376] In some embodiments, prior to displaying the first interactive application object within the conversation transcript, the device (**5426**) displays the messaging user interface including the conversation transcript (e.g., displayed in a first area of the display) of the messaging session between

the user of the electronic device and the at least one other user (e.g., of another electronic device) and an application affordance. For example, device **100-1** displays messaging user interface **3500** including conversation transcript **3700** and application affordance **3508** in FIG. **37**AN.

[1377] While displaying the messaging user interface, the device detects an input that activates the application affordance (e.g., detecting a tap gesture at a location that corresponds to the application affordance). For example an input including contact **3768** on application affordance **3508** in FIG. **37** AO.

[1378] In response to detecting the input that activates the application affordance, the device maintains display of at least a portion of the conversation transcript in a first area of the display and displays a second interactive application icon (e.g., a launch icon for a second interactive application), which is one of a plurality of interactive application icons, in a second area of the display (e.g., in a scrollable interactive application panel). For example, device **100-1** displays interactive reservations application launch icon **3708** in application slide tray **3892** in FIG. **37**AP.

[1379] In some embodiments, where the messaging user interface includes display of an electronic keyboard prior to activating the application affordance, the display of the scrollable interactive application panel replaces display of the keyboard. For example, display of application slide tray **3892**, in FIG. **37**BW, replaces display of digital keyboard **3501**, in FIG. **37**BV.

[1380] In some embodiments, where the messaging user interface includes a full-screen display of the conversation transcript prior to activating the application affordance, the display of the scrollable interactive application panel replaces a portion of the display of the message transcript. For example, conversation transcript **3700**, displayed in full-screen mode in FIG. **37**AO, shrinks to accommodate display of application slide tray **3892** in FIG. **37**AP.

[1381] While displaying the second interactive application icon in the second area of the display, the device detects a first swipe gesture that includes horizontal movement of a first contact at a location that corresponds to the second area of the display. For example, device **100-1** detects a swipe gesture including movement **3772** of contact **3770** from position **3770** in Figure to position **3770**-*b* in FIG. **37**AR.

[1382] In accordance with a determination that the first swipe gesture satisfies one or more interactive application icon switching criteria, the device replaces display of the second interactive application icon with display of a first interactive application icon that corresponds to the first interactive application in the second area of the display. For example, device **100-1** replaces interactive reservations application launch icon **3708** in slide tray **3892**, in FIG. **37**AQ, with interactive tic-tac-toe application launch icon **3774** in slide tray **3892**, in FIG. **37** AS.

[1383] In some embodiments, the interactive application icon switching criteria includes a criterion that the magnitude of a horizontal movement of the first swipe gestures satisfies a predetermined movement threshold. In some embodiments, the predetermined movement threshold varies with the speed of the movement of the contact.

[1384] While displaying the first interactive application icon in the second area of the display, the device detects an input that activates the first interactive application icon and, in response to detecting the input that activates the first interactive application icon, the device displays a user interface for the first interactive application within the conversation transcript (e.g., displays the first interactive application object) and ceases to display the first interactive application icon (e.g., replacing display of the first interactive application icon with display of an input area for the first interactive application in the second area of the display). For example, device **100-2** displays interactive pizza ordering application object **3735** in conversation transcript **3700**, and replaces display of application selection tray **3654**, which includes interactive pizza ordering launch icon **3613**, in FIG. **37**BZ, with interactive pizza ordering application input area **3731**, in FIG. **37**CA.

[1385] In some embodiments, prior to displaying the first interactive application object within the conversation transcript, the device (**5428**) displays the messaging user interface including the conversation transcript (e.g., displayed in a first area of the display) of the messaging session between the user of the electronic device and the at least one other user (e.g., of another electronic device) and an application affordance. For example, device **100-1** displays messaging user interface **3500**, including conversation transcript **3503** and application affordance **3508**, in FIG. **38**AQ.

[1386] While displaying the messaging user interface, the device detects an input that activates the application affordance (e.g., detecting a tap gesture at a location that corresponds to the application affordance). For example an input including contact **3876** on application affordance **3508**, in FIG. **38**AR.

[1387] In response to detecting the input that activates the application affordance, the device maintains display of at least a portion of the conversation transcript in a first area of the display and displays, in a second area of the display that includes a plurality of launch icons for interactive applications, a launch icon for the first interactive application. For example, device **100-1** maintains display of conversation transcript **3503** and displays application selection tray **3654** in FIG. **38**AS.

[1388] In some embodiments, where the messaging user interface includes display of an electronic keyboard prior to detecting activation of the application affordance, the display of the plurality of launch icons for interactive applications replaces display of the keyboard. For example, application selection tray **3654**, in FIG. **38**AS, replaces digital keyboard in FIG. **38**AR.

[1389] In some embodiments, where the messaging user interface includes a full-screen display of the conversation transcript prior to detecting activation of the application affordance, the display of the plurality of launch icons for interactive applications replaces a portion of the display of the message transcript. For example, conversation transcript **3700**, displayed in full-screen mode in FIG. **37**AO, shrinks to accommodate display of application slide tray **3892** in FIG. **37**AP.

[1390] While displaying the plurality of launch icons for interactive applications, the device detects an input that activates the launch icon for the first interactive application. For example, an input including contact **3729** on pizza ordering application launch icon **3613**, in FIG. **37**BZ.

[1391] In response to detecting the input that activates the launch icon for the first interactive application (e.g., detecting a tap gesture at a location that corresponds to the launch icon for the first interactive application), the device displays a user interface for the first interactive application within the conversation transcript (e.g., displaying the first interactive

application object). For example, device **100-2** displays interactive pizza ordering application object **3735** within transcript **3700**, in FIG. **37**CA.

[1392] In some embodiments, in response to detecting the input that activates the launch icon for the first interactive application, the device replaces (**5426**) display of the plurality of launch icons for interactive applications with display of an input area for the first interactive application in the second area of the display. For example, interactive pizza ordering application input area **3731**, in FIG. **37**CA, replaces display of application selection tray **3654**, in FIG. **37**BZ.

[1393] It should be understood that the particular order in which the operations in FIGS. **54**A-**54**C have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **52000**, **5600**, **5800**, **6000**, **6200**, **6400**, **6600**, **6800**, and **7000**) are also applicable in an analogous manner to method **5400** described above with respect to FIGS. **54**A-**54**C. For example, the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations described above with reference to method **5400** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations described herein with reference to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **52000**, **5600**, **5800**, **6000**, **6200**, **6400**, **6600**, **6800**, and **7000**). For brevity, these details are not repeated here.

[1394] In accordance with some embodiments, FIG. **55** shows a functional block diagram of an electronic device **5500** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. **55** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[1395] As shown in FIG. **55**, an electronic device **5500** includes a display unit **5502**, a touch-sensitive surface unit **5504**, and a processing unit **5510** coupled with the display unit **5502** and the touch-sensitive surface unit **5504**. In some embodiments, the processing unit **5510** includes: a display enabling unit **5512**, a detecting unit **5514**, an updating unit **5516**, a sending unit **5518**, a maintaining unit **5520**, and a replacing unit **5522**.

[1396] The processing unit **5510** is configured to enable display (e.g., with the display enabling unit **5512**) of a messaging user interface of a messaging application on the display unit **5502**, the messaging user interface including: a conversation transcript, displayed in a first area of the display, of a messaging session between a user of the electronic device and at least one other user, a first interactive application object displayed within the conversation transcript that corresponds to a first interactive application, a message input area, and an input area for the first interactive application, distinct from the message input area, displayed in a second area of the display, the input area for the first interactive application including one or more input affordances. The processing unit **5510** is also configured to detect (e.g., with the detecting unit **5514**) an input that activates a first input affordance in the input area for the interactive application.

[1397] In some embodiments, the processing unit **5510** is further configured to: after detecting the input that activates the first input affordance: update (e.g., with the updating unit **5516**) the first interactive application object that corresponds to the first interactive application in accordance with the input that activates the first input affordance; and send (e.g., with the sending unit **5518**) information, to one or more electronic devices that correspond to the at least one other user included in the messaging session, that causes update (e.g., with the updating unit **5516**) of a corresponding interactive application object that corresponds to the first interactive application displayed within a corresponding conversation transcript of the messaging session.

[1398] In some embodiments, content posted to the messaging session is displayed within the conversation transcript according to a temporal order in which the content was posted, and the interactive application object is displayed at a position within the conversation transcript associated with the temporal order in which a session of the interactive application was initiated.

[1399] In some embodiments, the processing unit **5510** is further configured to: enable display (e.g., with the display enabling unit **5512**) of synchronous movement of content displayed in a temporal order within the conversation transcript towards an edge of the conversation transcript, the displayed content including the first interactive application object; in accordance with a determination that the first interactive application object is within a predetermined distance from the edge of the conversation transcript, enable display (e.g., with the display enabling unit **5512**) of the first interactive application object at a fixed location on the display unit **5502**.

[1400] In some embodiments, the processing unit **5510** is further configured to: while displaying the first interactive application object at the fixed location on the display unit **5502**, continue to display synchronous movement of other content displayed in a temporal order within the conversation transcript.

[1401] In some embodiments, continuing to display synchronous movement of other content displayed in a temporal order with the conversation transcript includes animating other content such that the other content appears to move behind the first interactive application object.

[1402] In some embodiments, the processing unit **5510** is further configured to: while displaying the first interactive application object at the fixed location on the display unit **5502**: detect (e.g., with the detecting unit **5514**) a request to close the first interactive application; and, in response to detecting the request to close the first interactive application: cease to display (e.g., with the displaying enabling unit **5512**) the first interactive application object at the fixed location on the display unit **5502**; and enable display (e.g., with the display enabling unit **5512**) of the first interactive

application object at a position within the conversation transcript associated with the temporal order in which the session of the interactive application was initiated.

[1403] In some embodiments, the processing unit **5510** is further configured to: prior to displaying the first interactive application object within the conversation transcript: enable display (e.g., with the display enabling unit **5512**) of the messaging user interface including the conversation transcript of the messaging session between the user of the electronic device and the at least one other user and an application affordance; while displaying the messaging user interface, detect (e.g., with the detecting unit **5514**) an input that activates the application affordance; in response to detecting the input that activates the application affordance, maintain (e.g., with the maintaining unit **5520**) display of at least a portion of the conversation transcript in a first area of the display, and enable display (e.g., with the display enabling unit **5512**) of a second interactive application icon, which is one of a plurality of interactive application icons, in a second area of the display; while displaying the second interactive application icon in the second area of the display, detect (e.g., with the detecting unit **5514**) a first swipe gesture that includes horizontal movement of a first contact at a location that corresponds to the second area of the display; in accordance with a determination that the first swipe gesture satisfies one or more interactive application icon switching criteria, replace (e.g., with the replacing unit **5522**) display of the second interactive application icon with display of a first interactive application icon that corresponds to the first interactive application in the second area of the display; while displaying the first interactive application icon in the second area of the display, detect (e.g., with the detecting unit **5514**) an input that activates the first interactive application icon; and, in response to detecting the input that activates the first interactive application icon, enable display (e.g., with the display enabling unit **5512**) of a user interface for the first interactive application within the conversation transcript; and cease to display (e.g., with the display enabling unit **5512**) the first interactive application icon.

[1404] In some embodiments, the processing unit **5510** is further configured to: prior to displaying the first interactive application object within the conversation transcript: enable display (e.g., with the display enabling unit **5512**) of the messaging user interface including the conversation transcript of the messaging session between the user of the electronic device and the at least one other user and an application affordance; while displaying the messaging user interface, detect (e.g., with the detecting unit **5514**) an input that activates the application affordance; in response to detecting the input that activates the application affordance, maintain (e.g., with the maintaining unit **5520**) display of at least a portion of the conversation transcript in a first area of the display, and enable display (e.g., with the displaying enabling unit **5512**) of, in a second area of the display that includes a plurality of launch icons for interactive applications, a launch icon for the first interactive application; while displaying the plurality of launch icons for interactive applications, detect (e.g., with the detecting unit **5514**) an input that activates the launch icon for the first interactive application; and, in response to detecting the input that activates the launch icon for the first interactive application, enable display (e.g., with the display enabling unit **5512**) of a user interface for the first interactive application within the conversation transcript.

[1405] In some embodiments, the processing unit **5510** is further configured to: in response to detecting the input that activates the launch icon for the first interactive application, replace (e.g., with the replacing unit **5522**) display of the plurality of launch icons for interactive applications with display of an input area for the first interactive application in the second area of the display.

[1406] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[1407] The operations described above with reference to FIGS. **54**A-**54**C are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **55**. For example, detection operation **5420** and **5428** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

[1408] FIGS. **56**A-**56**B are flow diagrams illustrating a method **5600** of using an interactive application in a messaging application in accordance with some embodiments. The method **5600** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display, a touch-sensitive surface, and one or more sensors to detect intensities of contacts with the touch-sensitive surface. In some embodiments, the display is a touch-screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **5600** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1409] As described below, the method **5600** provides an intuitive way to use an interactive application in a messaging application. The method reduces the number, extent, and/or nature of the inputs from a user when using an interactive application in a messaging application, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to use an interactive

application in a messaging application faster and more efficiently conserves power and increases the time between battery charges.

[1410] The device displays (**5602**) a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user (e.g., of another electronic device), a first interactive application object displayed within the conversation transcript (e.g., a reservation application object) that corresponds to a first interactive application (e.g., an interactive application for making reservations for a meal, a movie, a hotel, or the like), and a message input area. For example, device **100-2** displays messaging user interface **3500**, including conversation transcript **3700**, interactive reservations application object **3728**, and message input area **3502**, in FIG. **370**.

[1411] The device detects (**5604**) a first input while a focus selector is at a location on the touch-sensitive surface that corresponds to the first interactive application object displayed within the conversation transcript (e.g., detect a gesture by a contact on a touch-sensitive display at the location of the first interactive application object, or detect a gesture by a contact on a touch-sensitive surface while a cursor or other pointer is at the location of the first interactive application object). For example, device **100-2** detects an input including contact **3738** on interactive reservations application object **3728** displayed within transcript **3700**, in FIG. **37**P.

[1412] In response to detecting the first input, the device displays (**5606**) an input area for the first interactive application that is distinct from the message input area, the input area for the first interactive application including one or more input affordances (e.g., radio buttons, text input fields, check boxes, pull down lists, and/or form fields). For example, device **100-2** displays interactive reservations application user interface **3712**, including input affordances **3740-1** and **3740-2**, in FIG. **37**Q.

[1413] In some embodiments, display of the input area for the first interactive application in response to detecting the first input (e.g., in response to detecting an input that activates the first interactive application object) replaces (**5608**) display of the conversation transcript, the first interactive application object, and/or the message input area. For example, display of interactive reservations application user interface **3712** in FIG. **37**Q replaces display of messaging user interface **3500**, including conversation transcript **3700**, interactive reservations application object **3728**, and message input area **3502**, in FIG. **37**P.

[1414] While displaying an input area for the first interactive application, the device detects (**5610**) one or more inputs on the one or more input affordances. For example, device **100-2** detects inputs including contact **3752** on input affordance **3740-1**, in FIG. **37**X, and contact **3754** on input affordance **3740-1**, in FIG. **37**Z.

[1415] After detecting the one or more inputs on the one or more input affordances, the device (**5612**) updates the first interactive application (e.g., updating fields in a reservation application object in the conversation transcript), sends instructions (e.g., information, instructions, or a representation of an updated interactive application object) to one or more (e.g., second) electronic devices that correspond to the at least one other user included in the messaging session to update a corresponding user interface for the first interactive application displayed within a corresponding conversation transcript of the messaging session (e.g., updating a corresponding first interactive application object or other user interface for the first interactive application), and ceases to display of the input area for the first interactive application.

[1416] For example, device **100-2** updates the reservation time in input affordance **3740-1** in FIG. **37**AA. Device **100-2** also sends information to device **100-1** that the time of the reservation was changed to 8:00 PM, causing device **100-1** to update interactive reservations application object **3728** to show an 8:00 PM reservation time, in FIG. **37**AL, to move display of interactive reservations application object **3728** in transcript **3700** from position **3728**-*a,* in FIG. **37**AK, to position **3728**-*b* in FIG. **37**AL, and to display interactive reservations application archiving icon **3756** within transcript **3700** (e.g., at original position **3728**-*b* of interactive reservations application object **3728**). Device **100-2** also ceases to display interactive reservations application user interface in FIG. **37**AC.

[1417] In some embodiments, the conversation transcript, the first interactive application object, and/or the message input area are redisplayed (e.g., in response to detecting an input that corresponds to a request to cease displaying the input area for the first interactive application. For example, device **100-2** redisplays messaging user interface **3500**, including transcript **3700**, interactive reservations application object **3728**, and message-input area **3502**, in FIG. **37**AC.

[1418] In some embodiments, updating (**5614**) the first interactive application occurs in response to detecting an input on one of the input affordances. For example, interactive tic-tac-toe application object **3705** is updated (e.g., moves from transcript **3700** position **3705**-*a,* in FIG. **37**BL, to transcript position **3705**-*b,* in FIG. **37**BM) in response to detecting an input including contact **3713** on tic-tac-toe board **3791** (e.g., an input affordance), in FIG. **37**BL.

[1419] In some embodiments, updating (**5616**) the first interactive application occurs in response to detecting an input that corresponds to a request to cease displaying the input area for the first interactive application. For example, interactive reservations application object **3728** is updated to display an 8:00 reservation in FIG. **37**AC in response to detecting an input including contact **3756** on exit affordance **3714**, in FIG. **37**AB, which corresponds to a request to confirm the change to the reservation and close interactive reservations application user interface **3712**. In another example, the position of interactive pizza ordering application object **3735** is updated in FIG. **37**DJ in response to an input including contact **3775** on input affordance **3773-3**, in FIG. **37**DI, corresponding to a request to order the pizza and close input area **3731** for the interactive pizza ordering application.

[1420] In some embodiments, sending instructions (**5618**) (e.g., sending information, instructions, or an updated representation of an interactive application object) to one or more (e.g., second) electronic devices that correspond to the at least one other user included in the messaging session to update a corresponding user interface for the first interactive application occurs in response to detecting an input on one of the input affordances. For example, device **100-2** sends information, at 9:35 AM, that 'X' **3794** was placed on tic-tac-toe board **3791** in response to detecting an input including contact **3713** on tic-tac-toe board **3791** (e.g., an input affordance), in FIG. **37**BL. Device **100-1** receives the

information and updates interactive tic-tac-toe application user interface **3782**, at 9:35 AM, to display 'X' **3794** on corresponding tic-tac-toe board **3791**.

[1421] In some embodiments, sending instructions (**5620**) (e.g., sending information, instructions, or an updated representation of an interactive application object) to one or more (e.g., second) electronic devices that correspond to the at least one other user included in the messaging session to update a corresponding user interface for the first interactive application occurs in response to detecting an input that corresponds to a request to cease displaying the input area for the first interactive application. For example, device **100-2** sends information, at 9:31 AM, that the reservation has been changed to 8:00 to device **100-1** in response to detecting an input including contact **3756** on exit affordance **3714**, in FIG. **37**AB, which corresponds to a request to confirm the change to the reservation and close interactive reservations application user interface **3712**. Device **100-1** receives the information, and updates display of interactive reservations application object **3728**, in transcript **3700**, at 9:31 AM, in FIG. **37**AL.

[1422] In some embodiments, ceasing display (**5622**) of the input area for the first interactive application occurs in response to detecting an input on one of the input affordances. For example, device **100-1** ceases to display interactive pizza ordering application input area **3731**, in FIG. **37**DJ, in response to an input including contact **3775** on input affordance **3773-3**, in FIG. **37**DI, corresponding to a request to order the pizza.

[1423] In some embodiments, ceasing display (**5624**) of the input area for the first interactive application occurs in response to detecting an input on an exit affordance. (e.g., detecting a tap gesture on a "done," "save," or "exit" icon or on an area on the display outside of the input area for the first interactive application). For example, device **100-2** ceases to display interactive reservations application user interface **3712**, in FIG. **37**AC, in response to detecting an input including contact **3756** on exit affordance **3714**, in FIG. **37**AB.

[1424] In some embodiments, the interactive application is configured to perform a subset (e.g., less than all) of the functions of a corresponding application operated separate from the messaging application. For example, in some embodiments, an interactive reservations application operated within a messaging application is be configured to allow making reservations but not configured to allow users to comment on a restaurant. In contrast, the corresponding reservation application operable outside of the messaging application is configured to allow making reservations and commenting on a restaurant.

[1425] In some embodiments, the interactive application displays a portion (e.g., less than all) of the content displayed by a corresponding application operated separate from the messaging application. For example, in some embodiments, an interactive reservations application operated within a messaging application is be configured to allow making reservations but not configured to allow users to comment on a restaurant. In contrast, the corresponding reservation application operable outside of the messaging application is configured to allow making reservations and commenting on a restaurant.

[1426] In some embodiments, the interactive application causes the device to launch a corresponding application operated separate from the messaging application upon detection of a predefined input. For example, in response to a first input (e.g., a tap, press, deep press, long-press, or multi-finger gesture) on interactive reservations application icon **3728** in FIG. **37**P, the device launches the interactive reservations application within the messaging application. In response to a second (e.g., different) input (e.g., a tap, press, deep press, long-press, or multi-finger gesture) on interactive reservations application icon **3728** in FIG. **37**P, the device launches a reservations application outside of the messaging application.

[1427] In some embodiments, the interactive application is operated separately from a corresponding application operated separate from the messaging application. For example, the interactive reservations application launched in response to activation of icon **3728** in FIG. **37**P is operable when a corresponding reservations application operated outside of the messaging application is not running.

[1428] In some embodiments, the interactive application is operated in conjunction with a corresponding application operated separate from the messaging application. For example, the interactive reservations application launched in response to activation of icon **3728** in FIG. **37**P is not operable when a corresponding reservations application operated outside of the messaging application is not running.

[1429] In some embodiments, the interactive application has a dedicated portion of the memory for temporary storage that is different from a dedicated portion of the memory for temporary storage for a corresponding application operated separate from the messaging application. For example, in some embodiments, records of reservations made using the interactive reservations application launched in response to activation of icon **3728** in FIG. **37**P and operated within the messaging application are stored in a different portion of memory than records of reservations made using a corresponding reservations application operated outside of the messaging application.

[1430] In some embodiments, the corresponding application operated separate from the messaging application is configured to access the dedicated portion of memory for temporary storage for the interactive application. For example, in some embodiments, the corresponding reservations application operated outside of the messaging application can access the records of reservations made using the interactive reservations application launched in response to activation of icon **3728** in FIG. **37**P and operated within the messaging application.

[1431] In some embodiments, the interactive application icon/object displays an identifier for a corresponding application operated separate from the messaging application. For example, in FIG. **37**K, interactive reservations application icon/object **3730** displays a concentric circle symbol that corresponds to a reservations application operated separate from the messaging application.

[1432] It should be understood that the particular order in which the operations in FIGS. **56**A-**56**B have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **52000**, **5400**, **5800**, **6000**, **6200**,

6400, **6600**, **6800**, and **7000**) are also applicable in an analogous manner to method **5600** described above with respect to FIGS. **56**A-**56**B. For example, the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations described above with reference to method **5600** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations described herein with reference to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **52000**, **5400**, **5800**, **6000**, **6200**, **6400**, **6600**, **6800**, and **7000**). For brevity, these details are not repeated here.

[1433] In accordance with some embodiments, FIG. **57** shows a functional block diagram of an electronic device **5700** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. **57** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[1434] As shown in FIG. **57**, an electronic device **5700** includes a display unit **5702**, a touch-sensitive surface unit **5704**, and a processing unit **5710** coupled with the display unit **5702** and the touch-sensitive surface unit **5704**. In some embodiments, the processing unit **5710** includes: a display enabling unit **5712**, a detecting unit **5714**, an updating unit **5716**, a sending unit **5718**, and a replacing unit **5720**.

[1435] The processing unit **5710** is configured to enable display (e.g., with the display enabling unit **5712**) of a messaging user interface of a messaging application on the display unit **5702**, the messaging user interface including: a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a first interactive application object displayed within the conversation transcript that corresponds to a first interactive application, and a message input area. The processing unit **5710** is also configured to detect (e.g., with the detecting unit **5714**) a first input while a focus selector is at a location on the touch-sensitive surface unit **5704** that corresponds to the first interactive application object displayed within the conversation transcript. In response to detecting the first input, the processing unit **5710** is configured to enable display (e.g., with the display enabling unit **5712**) of an input area for the first interactive application that is distinct from the message input area, the input area for the first interactive application including one or more input affordances. While displaying an input area for the first interactive application, the processing unit **5710** is configured to detect (e.g., with the detecting unit **5714**) one or more inputs on the one or more input affordances. After detecting the one or more inputs on the one or more input affordances, the processing unit **5710** is configured to: update (e.g., with the updating unit **5716**) the first interactive application; send (e.g., with the sending unit **5718**) information to one or more electronic devices that correspond to the at least one other user included in the messaging session that causes updating of a corresponding user interface for the first interactive application displayed within a corresponding conversation transcript of the messaging session; and cease display (e.g., with the display enabling unit **5712**) of the input area for the first interactive application.

[1436] In some embodiments, display of the input area for the first interactive application in response to detecting the first input replaces (e.g., with the replacing unit **5720**) display of the conversation transcript, the first interactive application object, and/or the message input area.

[1437] In some embodiments, updating the first interactive application occurs in response to detecting an input on one of the input affordances.

[1438] In some embodiments, updating the first interactive application occurs in response to detecting an input that corresponds to a request to cease displaying the input area for the first interactive application.

[1439] In some embodiments, sending information to one or more electronic devices that correspond to the at least one other user included in the messaging session that causes updating of a corresponding user interface for the first interactive application occurs in response to detecting an input on one of the input affordances.

[1440] In some embodiments, sending information to one or more electronic devices that correspond to the at least one other user included in the messaging session that causes updating of a corresponding user interface for the first interactive application occurs in response to detecting an input that corresponds to a request to cease displaying of the input area for the first interactive application.

[1441] In some embodiments, ceasing display of the input area for the first interactive application occurs in response to detecting an input on one of the input affordances.

[1442] In some embodiments, ceasing display of the input area for the first interactive application occurs in response to detecting an input on an exit affordance.

[1443] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[1444] The operations described above with reference to FIGS. **56**A-**56**B are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **57**. For example, detection operations **5604** and **5610** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by

the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

[1445] FIG. **58** is a flow diagram illustrating a method **5800** of enabling use of an interactive application in a messaging application in accordance with some embodiments. The method **5800** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display, a touch-sensitive surface, and one or more sensors to detect intensities of contacts with the touch-sensitive surface. In some embodiments, the display is a touch-screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **5800** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1446] As described below, the method **5800** provides an intuitive way to enable use of an interactive application in a messaging application. The method reduces the number, extent, and/or nature of the inputs from a user when enabling use of an interactive application in a messaging application, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to enable use of an interactive application in a messaging application faster and more efficiently conserves power and increases the time between battery charges.

[1447] In some embodiments, the device has one or more processors, memory, and a display, where a messaging application and a plurality of other applications are stored in the memory, and a respective application in the plurality of other applications has a normal mode for normal operation on the electronic device (e.g., as a standalone application, separate from the messaging application) and an embedded mode for operation within the messaging application on the electronic device;

[1448] In some embodiments, the electronic device includes a touch-sensitive surface, e.g., a track-pad or touch-sensitive display. In some embodiments, the electronic device includes one or more sensors configured to detect intensities of contacts on the touch-sensitive surface.

[1449] The device (**5802**) displays a plurality of toggle affordances, where a respective toggle affordance in the plurality of toggle affordances has a corresponding application in the plurality of other applications stored in the memory, the respective toggle affordance has a first state that enables display of a respective launch icon, within the messaging application, for operation of the corresponding application in the embedded mode within the messaging application, the respective toggle affordance has a second state that prevents display of the respective launch icon, within the messaging application, to prevent operation of the corresponding application in the embedded mode within the messaging application, and the plurality of toggle affordances include a first toggle affordance for a first application that is displayed in the first state and a second toggle affordance for a second application that is displayed in the second state.

[1450] While displaying the plurality of toggle affordances, the device detects (**5804**) a first user input at a first location that corresponds to the first toggle affordance (e.g., detecting a tap or swipe gesture at a location on a touch-sensitive surface that corresponds to a location of the first toggle affordance on the display).

[1451] In response to detecting the first user input at the first location that corresponds to the first toggle affordance, the device (**5806**) changes the first toggle affordance from the first state to the second state, and prevents display of a corresponding launch icon for the first application in the messaging application.

[1452] In some embodiments, while displaying the plurality of toggle affordances, the device (**5808**) detects a second user input at a second location that corresponds to the second toggle affordance (e.g., detecting a tap or swipe gesture at a location on a touch-sensitive surface that corresponds to a location of the second toggle affordance on the display) and, in response to detecting the second user input at the second location that corresponds to the second toggle affordance, changes the second toggle affordance from the second state to the first state and enables display of a corresponding launch icon for the second application in the messaging application.

[1453] It should be understood that the particular order in which the operations in FIG. **58** have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **6000**, **6200**, **6400**, **6600**, **6800**, and **7000**) are also applicable in an analogous manner to method **5800** described above with respect to FIG. **58**. For example, the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations described above with reference to method **5800** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations described herein with reference to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **6000**, **6200**, **6400**, **6600**, **6800**, and **7000**). For brevity, these details are not repeated here.

[1454] In accordance with some embodiments, FIG. **59** shows a functional block diagram of an electronic device **5900** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. **59** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[1455] As shown in FIG. **59**, an electronic device **5900** includes a display unit **5902**, a touch-sensitive surface unit **5904**, and a processing unit **5910** coupled with the display unit **5902** and the touch-sensitive surface unit **5904**. In some embodiments, a messaging application and a plurality of

other applications are stored in memory of the electronic device **5900**, and a respective application in the plurality of other applications has a normal mode for normal operation on the electronic device **5900** and an embedded mode for operation within the messaging application on the electronic device **5900**. In some embodiments, the processing unit **5910** includes: a display enabling unit **5912**, a detecting unit **5914**, and a changing unit **5916**.

[1456] The processing unit **5910** is configured to enable display (e.g., with the display enabling unit **5912**) of a plurality of toggle affordances. In some embodiments, a respective toggle affordance in the plurality of toggle affordances has a corresponding application in the plurality of other applications stored in the memory; the respective toggle affordance has a first state that enables display of a respective launch icon, within the messaging application, for operation of the corresponding application in the embedded mode within the messaging application; the respective toggle affordance has a second state that prevents display of the respective launch icon, within the messaging application, to prevent operation of the corresponding application in the embedded mode within the messaging application; the plurality of toggle affordances include a first toggle affordance for a first application that is displayed in the first state and a second toggle affordance for a second application that is displayed in the second state. While displaying the plurality of toggle affordances, the processing unit **5910** is configured to detect (e.g., with the detecting unit **5914**) a first user input at a first location that corresponds to the first toggle affordance. In response to detecting the first user input at the first location that corresponds to the first toggle affordance, the processing unit **5910** is configured to change (e.g., with the changing unit **5916**) the first toggle affordance from the first state to the second state, and prevent display (e.g., with the display enabling unit **5912**) of a corresponding launch icon for the first application in the messaging application.

[1457] In some embodiments, while displaying the plurality of toggle affordances, the processing unit **5910** is further configured to detect (e.g., with the detecting unit **5914**) a second user input at a second location that corresponds to the second toggle affordance; and, in response to detecting the second user input at the second location that corresponds to the second toggle affordance, change (e.g., with the changing unit **5916**) the second toggle affordance from the second state to the first state, and enable display (e.g., with the display enabling unit **5912**) of a corresponding launch icon for the second application in the messaging application.

[1458] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[1459] The operations described above with reference to FIG. **58** are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **59**. For example, display operation **5802** and detection operation **5804** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

[1460] FIGS. **60**A-**60**D are flow diagrams illustrating a method **6000** of navigating within a messaging application having associated applications in accordance with some embodiments. The method **6000** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display, a touch-sensitive surface, and one or more sensors to detect intensities of contacts with the touch-sensitive surface. In some embodiments, the display is a touch-screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **6000** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1461] As described below, the method **6000** provides an intuitive way to navigate within a messaging application having associated applications. The method reduces the number, extent, and/or nature of the inputs from a user when navigating within a messaging application having associated applications, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to navigate within a messaging application having associated applications faster and more efficiently conserves power and increases the time between battery charges.

[1462] The device displays (**6002**) a messaging user interface (e.g., of a messaging application) on the display, the messaging user interface including a conversation transcript (e.g., displayed in a first area of the display) of a messaging session between a user of the electronic device and at least one other user (e.g., of another electronic device), a message-input area, a digital image affordance, a digital touch affordance, and an application affordance. In some embodiments, the messaging user interface also includes a keyboard, e.g., displayed in a second area of the display.

[1463] For example, in FIG. **38**A, device **100-1** displays messaging user interface **3500** on touch screen **112**. Messaging user interface **3500** includes conversation transcript **3503**, digital image affordance **3504**, digital canvas affordance **3506**, application affordance **3508**, and message-input area **3502**. In FIG. **38**AV, messaging user interface also includes digital keyboard **3501**.

[1464] In some embodiments, the messaging user interface also includes (**6004**) a microphone affordance, configured to enable sound recording on the electronic device upon activation. For example, microphone affordance **3802** in FIG. **38**A.

[1465] In some embodiments, the messaging user interface also includes (**6006**) at least one avatar corresponding

to a first other user included in the messaging session, configured to enable the electronic device to display a menu that contains activatable menu items associated with the at least one avatar overlaid on the messaging user interface when activated.

[1466] For example, in FIGS. **38**A and **38**AW, conversation transcript **3503** includes messages from participants of a corresponding messaging session, including the user of portable multifunction device **100-1** and other users included in the messaging session. Each of the other users included in the messaging transcript are represented by an avatar (e.g., avatar **3510** for "Abe") displayed in stack of avatars**4002**. Upon activation of Abe's avatar **3510**, by an input including contact **3880** in FIG. **38**AW, the device displays menu **3882** containing activatable menu items **3884**, in FIG. **38**AX.

[1467] In some embodiments, the menu that contains activatable menu items associated with the at least one avatar includes (**6008**) a menu item that when activated initiates a digital touch action with the first other user (e.g., menu item **3884-5** in FIG. **38**AX), a menu item that when activated initiates messaging with only the first other user (e.g., selecting a messaging menu item causes the electronic device to display a private messaging user interface between the user of the electronic device and the first other user) (e.g., menu item **3884-3** in FIG. **38**AX), a menu item that when activated initiates an email with the first other user (e.g., menu item **3884-4** in FIG. **38**AX), a menu item that when activated initiates a call with the first other user (e.g., menu item **3884-1** in FIG. **38**AX), a menu item that when activated initiates a video conference with the first other user (e.g., menu item **3884-2** in FIG. **38**AX), and/or a menu item that when activated initiates a payment action with the first other user (e.g., menu item **3884-6** in FIG. **38**AX).

[1468] While displaying the messaging user interface, the device detects (**6010**) a first input on the touch sensitive surface (e.g., for an electronic device with a touch sensitive display, detecting a tap gesture). For example an input including one of contact **3804** on digital image affordance **3504**, in FIG. **38**B, contact **3852** on digital canvas affordance **3506**, in FIG. **38**AA, and contact **3868** on application affordance **3508**, in FIG. **38**AJ.

[1469] In response to detecting the first input, the device (**6012**): in accordance with a determination that the first input is made while a focus selector is at a location in the messaging user interface that corresponds to the digital image affordance, displays a plurality of digital images within the messaging user interface (e.g., digital images **3514** and **3518** in digital image tray **3806** in FIG. **38**C); in accordance with a determination that the first input is made while a focus selector is at a location in the messaging user interface that corresponds to the digital canvas affordance, displaying a digital drawing canvas within the messaging user interface (e.g., digital drawing canvas **3858** in digital canvas tray **3854** in FIG. **38**AH); and in accordance with a determination that the first input is made while a focus selector is at a location in the messaging user interface that corresponds to the application affordance, displaying one or more launch icons for an (e.g., interactive) application within the messaging user interface (e.g., application launch icon **3708** in application swipe tray **3892** in FIG. **38**AK or application launch icons **3601**, **3603**, **3605**, **3607**, **3609**, **3611**, **3613**, and **3615** in application selection tray **3654** in FIG. **38**AN).

[1470] In some embodiments, displaying the plurality of digital images within the messaging user interface includes (**6014**): in accordance with a determination that the messaging user interface included display of a keyboard at the time the first input was detected, replacing display of the keyboard with the display of the plurality of digital images, the plurality of digital images including a live preview image from the digital camera, and in accordance with a determination that the messaging user interface did not include display of a keyboard at the time the first input was detected, displaying the conversation transcript in a first area of the display and displaying the plurality of digital images in a second area of the display, the plurality of digital images including a live preview image from the digital camera.

[1471] For example, in FIG. **38**C, the size of conversation transcript **3503** is reduced, with respect to the size of conversation transcript **3503** in FIG. **38**B, to accommodate display of digital image tray **3806**, including live preview image **3514** from optical sensor **164** and previously captured digital images **3518**.

[1472] In another example, display of digital keyboard **3501**, in FIG. **38**X, is replaced by display of digital image tray **3806**, including live preview image **3514** from optical sensor **164** and previously captured digital images **3518**, in FIG. **38**Y.

[1473] In some embodiments, replacing display of the keyboard includes displaying the plurality of digital images over the keyboard. In some embodiments, replacing display of the keyboard includes ceasing to display the keyboard and displaying the plurality of digital images where the keyboard had been displayed (e.g., as in FIGS. **38**X-**38**Y).

[1474] In some embodiments, the plurality of digital images is a scrollable array of digital images. For example, digital image tray **3806** is scrolled in FIG. **38**E to reveal additional digital images **3518-6** and **3518-7**.

[1475] In some embodiments, the plurality of digital images includes a recently shared image, a recently received image, an image including a participant in the conversation (e.g., as identified by facial recognition), a real-time image from a forward-facing digital camera in the device, or a real-time image from a backwards-facing digital camera in the device.

[1476] In some embodiments, the plurality of digital images consists of the live preview image from the digital camera (e.g., live preview image **3514** in FIG. **38**C) and a plurality of digital images captured during the messaging session.

[1477] In some embodiments, where the conversation transcript was maximized at the time the second input was detected, display of the conversation transcript is partially replaced by display of the plurality of digital images. For example, display of conversation transcript **3503** is partially replaced by digital image tray **3806** in FIG. **38**C.

[1478] In some embodiments, while displaying the plurality of digital images, the device (**6016**) detects an input that selects a digital image in the plurality of digital images (e.g., an input including contact **3512** on live preview image **3514** in FIG. **35**D) and, after detecting the input that selects a digital image in the plurality of digital images, displays the selected digital image in the conversation transcript (e.g., display of captured digital image **3518-5** in conversation transcript **3503** in FIGS. **35**G and **351**) and transmitting a representation of the selected digital image to one or more electronic devices that correspond to the at least one other

user included in the messaging session, wherein the one or more electronic devices display the representation of the selected digital image in a conversation transcript that corresponds to the messaging session.

[1479] In some embodiments, the digital image is automatically posted to the messaging session upon selection. For example, digital image **3518-5** is automatically posted to the messaging session in FIG. **35**I in response to an input including contact **3524** in FIGS. **35**H-**35**I.

[1480] In some embodiments, the digital image is displayed in the message input area and the user posts the image to the messaging session (e.g., by activating a send icon with a tap gesture). For example, digital image **3518-5** is displayed in message-input area **3502**, in FIG. **35**E, in response to detecting an input including contact **3512**, in FIG. **35**D. Digital image **3518-5** is then posted to the messaging session, in FIG. **35**G, in response to detecting an input including contact **3522** on posting affordance **3520**, in FIG. **35**F.

[1481] In some embodiments, the device (**6018**) detects an input that selects the live image displayed within the plurality of digital images (e.g., for an electronic device with a touch sensitive display, detecting a tap gesture on the live image) and, in response to detecting that input that selects the live image, captures a digital image with the digital camera, while maintaining display of the conversation transcript. For example, in response to detecting an input including contact **3512** on capture affordance **3516** displayed over live preview image **3514**, in FIG. **35**D, the device captures digital image **3518-5**, while maintaining display of conversation transcript **3503**, in FIG. **35**E.

[1482] In some embodiments, after capturing the digital image, the device (**6020**) displays the digital image captured by the digital camera in the conversation transcript and transmits a representation of the captured digital image to one or more electronic devices that correspond to the at least one other user included in the messaging session, where the one or more electronic devices display the representation of the captured digital image in a conversation transcript that corresponds to the messaging session. For example, captured image **3518-5** is displayed in conversation transcript **3503** in FIGS. **35**G and **35**I.

[1483] In some embodiments, the captured image is automatically posted to the messaging session upon selection of the live image. For example, captured digital image **3518-5** is automatically posted to the messaging session in FIG. **35**I in response to an input including contact **3524** in FIGS. **35**H-**35**I.

[1484] In some embodiments, the captured image is displayed in the message input area and the user posts the image to the messaging session (e.g., by activating a send icon with a tap gesture). For example, captured digital image **3518-5** is displayed in message-input area **3502**, in FIG. **35**E, in response to detecting an input including contact **3512**, in FIG. **35**D. Captured digital image **3518-5** is then posted to the messaging session, in FIG. **35**G, in response to detecting an input including contact **3522** on posting affordance **3520**, in FIG. **35**F.

[1485] In some embodiments, displaying the digital drawing canvas within the messaging user interface includes (**6022**), in accordance with a determination that the messaging user interface included display of a keyboard at the time the first input was detected, replacing display of the keyboard with the display of the digital drawing canvas and, in accordance with a determination that the messaging user interface did not include display of a keyboard at the time the first input was detected, displaying the conversation transcript in a first area of the display and displaying the plurality of digital touch actions in a second area of the display.

[1486] For example, in FIG. **38**AB, the size of conversation transcript **3503** is reduced, with respect to the size of conversation transcript **3503** in FIG. **38**AA, to accommodate display of digital canvas tray **3854**, including digital drawing canvas **3858**.

[1487] In another example, display of digital keyboard **3501**, in FIG. **38**G, is replaced by display of digital canvas tray **3854**, including digital drawing canvas **3858**, in FIG. **38**AH.

[1488] In some embodiments, replacing display of the keyboard includes displaying the digital drawing canvas over the keyboard. In some embodiments, replacing display of the keyboard includes ceasing to display the keyboard and displaying the digital drawing canvas where the keyboard had been displayed (e.g., as illustrated in FIGS. **38**AG-**38**AH).

[1489] In some embodiments, where the conversation transcript was maximized at the time the second input was detected, display of the conversation transcript is partially replaced by display of the digital drawing canvas (e.g., as illustrated in FIGS. **38**AA-**38**AB).

[1490] In some embodiments, displaying the one or more launch icons for an (e.g., interactive) application within the messaging user interface includes (**6024**): in accordance with a determination that the messaging user interface included display of a keyboard at the time the first input was detected, replacing display of the keyboard with the display of the one or more launch icons for an (e.g., interactive) application and, in accordance with a determination that the messaging user interface did not include display of a keyboard at the time the first input was detected, displaying the conversation transcript in a first area of the display and displaying the one or more launch icons for an (e.g., interactive) application in a second area of the display.

[1491] For example, in FIG. **38**AK, the size of conversation transcript **3503** is reduced, with respect to the size of conversation transcript **3503** in FIG. **38**AJ, to accommodate display of application swipe tray **3892**, including interactive reservations application launch icon **3708**.

[1492] In another example, display of digital keyboard **3501**, in FIG. **38**AR, is replaced by display of application selection tray **3654**, including application launch icons **3601**, **3603**, **3605**, **3607**, **3609**, **3611**, **3613**, and **3615**, in FIG. **38**AS.

[1493] In some embodiments, replacing display of the keyboard includes displaying the one or more launch icon over the keyboard. In some embodiments, replacing display of the keyboard includes ceasing to display the keyboard and displaying the one or more launch icon where the keyboard had been displayed (e.g., as illustrated in FIGS. **38**AR-**38**AS).

[1494] In some embodiments, the one or more launch icon is a single launch icon in a scrollable list of launch icons (e.g., interactive reservations application launch icon **3708** in application swipe tray **3892** in FIG. **37**AQ).

[1495] In some embodiments, the one or more launch icon is a plurality of launch icons, e.g., displayed in a mini springboard (e.g., application launch icons **3601**, **3603**,

3605, **3607**, **3609**, **3611**, **3613**, and **3615** displayed in application selection tray **3654** in FIG. **38**AN).

[1496] In some embodiments, where the conversation transcript was maximized at the time the second input was detected, display of the conversation transcript is partially replaced by display of the one or more launch icon (e.g., as illustrated in FIGS. **38**AJ-**38**AK).

[1497] In some embodiments, while displaying the one or more launch icons for an (e.g., interactive) application, the device (**6026**) detects an input that activates a launch icon in the one or more launch icons for an (e.g., interactive) application (e.g., an input including one of contact **3710** in FIG. **37**F, contact **3776** in FIG. **37**AT, and contact **3729** in FIG. **37**BZ).

[1498] In some embodiments, after detecting the input that activates the launch icon in the one or more launch icons for an (e.g., interactive) application, the device displays a first input area for an (e.g., interactive) application corresponding to the activated launch icon the (e.g., interactive) application that is distinct from the message input area, the input area for the first interactive application including one or more input affordances (e.g., radio buttons, text input fields, check boxes, pull down lists, and/or form fields. For example, interactive reservations application user interface **3712** in FIG. **37**G, interactive tic-tac-toe application input area **3778** in FIG. **37**AV, interactive tic-tac-toe application user interface **3784** FIG. **37**AW, or interactive pizza ordering application input area **3731** in FIG. **37**CA.

[1499] In some embodiments, the first input area is displayed over/replaces display of a portion of the messaging user interface. (e.g., interactive reservations application user interface **3712** in FIG. **37**G).

[1500] In some embodiments, the first input area replaces display of the one or more launch icons for an (e.g., interactive) application (e.g., interactive tic-tac-toe application input area **3778** in FIG. **37**AV or interactive pizza ordering application input area **3731** in FIG. **37**CA).

[1501] In some embodiments, the first input area is displayed over/replaces display of the entire messaging user interface (e.g., interactive reservations application user interface **3712** in FIG. **37**G or interactive tic-tac-toe application user interface **3784** FIG. **37**AW).

[1502] In some embodiments, the first input area for the (e.g., interactive) application is a menu including choices as to how to operate a session of the (e.g., interactive) application (e.g., play tic-tac-toe as X or **0**). For example, interactive tic-tac-toe application input area **3778** in FIG. **37**AV.

[1503] In some embodiments, the first input area for the (e.g., interactive) application is a user interface for the (e.g., interactive) application.

[1504] In some embodiments, the device displays a first (e.g., interactive) application object within the conversation transcript that corresponds to the (e.g., interactive) application corresponding to the activated launch icon. For example, interactive reservations application object **3728**, in FIG. **37**I, corresponding to an interactive reservations application launched from launch icon **3708**, in FIG. **37**F. Another example is interactive tic-tac-toe application object **3728**, in FIG. **37**AW, corresponding to an interactive tic-tac-toe application launched from launch icon **3774** in FIG. **37**AT. Another example is interactive pizza ordering application object **3725**, in FIG. **37**CA, corresponding to an interactive pizza ordering application launched from launch icon **3613**, in FIG. **37**BZ.

[1505] In some embodiments, where display of at least a portion of the conversation transcript is maintained while the first input area for the (e.g., interactive) application is displayed, the interactive application object is displayed immediately in the conversation transcript (e.g., interactive tic-tac-toe application object **3728**, in FIG. **37**AW and interactive pizza ordering application object **3725**, in FIG. **37**CA).

[1506] In some embodiments, where display of the first input area for the (e.g., interactive) application replaces display of the conversation transcript, the interactive application object is displayed after display of the first input area is terminated (e.g., interactive reservations application object **3728**, in FIG. **37**I).

[1507] In some embodiments, transmitting a representation of a second (e.g., interactive) application object that corresponds to the (e.g., interactive) application corresponding to the activated launch icon to one or more electronic devices that correspond to the at least one other user included in the messaging session, where the one or more electronic devices display the representation of the second (e.g., interactive) application object in a conversation transcript that corresponds to the messaging session.

[1508] For example, device **100-2** displays interactive reservations application object **3728**, in FIG. **37**K, in response to receiving information from device **100-1** that a session of the corresponding interactive reservations application was initiated within the messaging session corresponding to conversation transcript **3700**.

[1509] In another example, device **100-2** displays interactive tic-tac-toe application object **3705**, in FIG. **37**BF, in response to receiving information from device **100-1** that a session of the corresponding interactive tic-tac-toe application was initiated within the messaging session corresponding to conversation transcript **3700**.

[1510] In another example, device **100-1** displays interactive pizza ordering application object **3735**, in FIG. **37**CR, in response to receiving information from device **100-2** that a session of the corresponding pizza ordering application was initiated with the messaging session corresponding to conversation transcript **3700**.

[1511] In some embodiments, the second (e.g., interactive) application object is the same as the first (e.g., interactive) application object, e.g., for a standard messages application. In some embodiments, the second (e.g., interactive) application object is different from the first (e.g., interactive) application object, e.g., for a third party messages application that the other user may need to download to use.

[1512] In some embodiments, the interactive application is configured to perform a subset (e.g., less than all) of the functions of a corresponding application operated separate from the messaging application. For example, in some embodiments, an interactive reservations application operated within a messaging application is be configured to allow making reservations but not configured to allow users to comment on a restaurant. In contrast, the corresponding reservation application operable outside of the messaging application is configured to allow making reservations and commenting on a restaurant.

[1513] In some embodiments, the interactive application displays a portion (e.g., less than all) of the content dis-

played by a corresponding application operated separate from the messaging application. For example, in some embodiments, an interactive reservations application operated within a messaging application is be configured to allow making reservations but not configured to allow users to comment on a restaurant. In contrast, the corresponding reservation application operable outside of the messaging application is configured to allow making reservations and commenting on a restaurant.

[1514] In some embodiments, the interactive application causes the device to launch a corresponding application operated separate from the messaging application upon detection of a predefined input. For example, in response to a first input (e.g., a tap, press, deep press, long-press, or multi-finger gesture) on interactive reservations application icon **3728** in FIG. **37**P, the device launches the interactive reservations application within the messaging application. In response to a second (e.g., different) input (e.g., a tap, press, deep press, long-press, or multi-finger gesture) on interactive reservations application icon **3728** in FIG. **37**P, the device launches a reservations application outside of the messaging application.

[1515] In some embodiments, the interactive application is operated separately from a corresponding application operated separate from the messaging application. For example, the interactive reservations application launched in response to activation of icon **3728** in FIG. **37**P is operable when a corresponding reservations application operated outside of the messaging application is not running.

[1516] In some embodiments, the interactive application is operated in conjunction with a corresponding application operated separate from the messaging application. For example, the interactive reservations application launched in response to activation of icon **3728** in FIG. **37**P is not operable when a corresponding reservations application operated outside of the messaging application is not running.

[1517] In some embodiments, the interactive application has a dedicated portion of the memory for temporary storage that is different from a dedicated portion of the memory for temporary storage for a corresponding application operated separate from the messaging application. For example, in some embodiments, records of reservations made using the interactive reservations application launched in response to activation of icon **3728** in FIG. **37**P and operated within the messaging application are stored in a different portion of memory than records of reservations made using a corresponding reservations application operated outside of the messaging application.

[1518] In some embodiments, the corresponding application operated separate from the messaging application is configured to access the dedicated portion of memory for temporary storage for the interactive application. For example, in some embodiments, the corresponding reservations application operated outside of the messaging application can access the records of reservations made using the interactive reservations application launched in response to activation of icon **3728** in FIG. **37**P and operated within the messaging application.

[1519] In some embodiments, the interactive application icon/object displays an identifier for a corresponding application operated separate from the messaging application. For example, in FIG. **37**K, interactive reservations application icon/object **3730** displays a concentric circle symbol that corresponds to a reservations application operated separate from the messaging application.

[1520] In some embodiments, while displaying the message-input area, the device (**6028**) detecting a second input that activates the message-input area (e.g., an input including one of contact **3872**, in FIG. **38**AN, contact **3878**, in FIG. **38**AU, and contact **3528** in FIG. **35**L).

[1521] In some embodiments, in response to detecting the input that activates the message-input area, in accordance with a determination that the messaging user interface included display of a keyboard and did not include display of the three activatable affordances at the time the second input was detected, the device displays a prompt within the message-input area.

[1522] In some embodiments, in response to detecting the input that activates the message-input area, in accordance with a determination that the messaging user interface included display of a keyboard and the three activatable affordances at the time the second input was detected, the device: ceases to display the three activatable affordances, displays the application expansion affordance, expands display of the message input-area, and displays a prompt within the message-input area.

[1523] In some embodiments, in response to detecting the input that activates the message-input area, in accordance with a determination that the messaging user interface did not include display of a keyboard and included display of the three activatable affordances at the time the second input was detected, the device: ceases to display the three activatable affordances, displays the application expansion affordance, expands display of the message input-area, displays a prompt within the message-input area, and displays a keyboard.

[1524] In some embodiments, in response to detecting the input that activates the message-input area, in accordance with a determination that the messaging user interface did not include display of a keyboard and included display of the three activatable affordances at the time the second input was detected, the device: displays a prompt within the message-input area, and displays a keyboard.

[1525] It should be understood that the particular order in which the operations in FIGS. **60**A-**60**D have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **5800**, **6200**, **6400**, **6600**, **6800**, and **7000**) are also applicable in an analogous manner to method **6000** described above with respect to FIGS. **60**A-**60**D. For example, the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations described above with reference to method **6000** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations described herein with reference to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**,

4400, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **5800**, **6200**, **6400**, **6600**, **6800**, and **7000**). For brevity, these details are not repeated here.

[1526] In accordance with some embodiments, FIG. **61** shows a functional block diagram of an electronic device **6100** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. **61** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[1527] As shown in FIG. **61**, an electronic device **6100** includes a display unit **6102**, a touch-sensitive surface unit **6104**, a digital camera unit **6106**, and a processing unit **6110** coupled with the display unit **6102**, the touch-sensitive surface unit **6104**, and the digital camera unit **6106**. In some embodiments, the processing unit **6110** includes: a display enabling unit **6112**, a detecting unit **6114**, a replacing unit **6116**, a transmitting unit **6118**, a capturing unit **6120**, and an expanding unit **6122**.

[1528] The processing unit **6110** is configured to enable display (e.g., with the display enabling unit **6112**) of a messaging user interface on the display unit **6102**, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a message-input area, a digital image affordance, a digital touch affordance, and an application affordance. While displaying the messaging user interface, the processing unit **6110** is configured to detect (e.g., with the detecting unit **6114**) a first input on the touch sensitive surface. In response to detecting the first input, the processing unit **6110** is configured to: in accordance with a determination that the first input is made while a focus selector is at a location in the messaging user interface that corresponds to the digital image affordance, enable display (e.g., with the display enabling unit **6112**) of a plurality of digital images within the messaging user interface; in accordance with a determination that the first input is made while a focus selector is at a location in the messaging user interface that corresponds to the digital canvas affordance, enable display (e.g., with the display enabling unit **6112**) of a digital drawing canvas within the messaging user interface; and in accordance with a determination that the first input is made while a focus selector is at a location in the messaging user interface that corresponds to the application affordance, enable display (e.g., with the display enabling unit **6112**) of one or more launch icons for an application within the messaging user interface.

[1529] In some embodiments, displaying the plurality of digital images within the messaging user interface includes: in accordance with a determination that the messaging user interface included display of a keyboard at the time the first input was detected, replacing display (e.g., with the replacing unit **6116**) of the keyboard with the display of the plurality of digital images, the plurality of digital images including a live preview image from the digital camera unit **6106**; and in accordance with a determination that the messaging user interface did not include display of a keyboard at the time the first input was detected, displaying (e.g., with the display enabling unit **6112**) the conversation transcript in a first area of the display and displaying the plurality of digital images in a second area of the display, the plurality of digital images including a live preview image from the digital camera unit **6106**.

[1530] In some embodiments, while displaying the plurality of digital images, the processing unit **6110** is further configured to detect (e.g., with the detecting unit **6114**) an input that selects a digital image in the plurality of digital images; and after detecting the input that selects a digital image in the plurality of digital images: enable display (e.g., with the display enabling unit **6112**) of the selected digital image in the conversation transcript; and transmit (e.g., with the transmitting unit **6118**) a representation of the selected digital image to one or more electronic devices that correspond to the at least one other user included in the messaging session, where the one or more electronic devices display the representation of the selected digital image in a conversation transcript that corresponds to the messaging session.

[1531] In some embodiments, the processing unit **6110** is further configured to: detect (e.g., with the detecting unit **6114**) an input that selects the live image displayed within the plurality of digital images; and, in response to detecting that input that selects the live image, capture (e.g., with the capturing unit **6120**) a digital image with the digital camera unit **6106**, while maintaining display of the conversation transcript.

[1532] In some embodiments, after capturing the digital image, the processing unit **6110** is configured to: enable display (e.g., with the display enabling unit **6112**) of the digital image captured by the digital camera unit **6106** in the conversation transcript, and transmit (e.g., with the transmitting unit **6118**) a representation of the captured digital image to one or more electronic devices that correspond to the at least one other user included in the messaging session, where the one or more electronic devices display the representation of the captured digital image in a conversation transcript that corresponds to the messaging session.

[1533] In some embodiments, displaying the digital drawing canvas within the messaging user interface includes: in accordance with a determination that the messaging user interface included display of a keyboard at the time the first input was detected, replacing (e.g., with the replacing unit **6116**) display of the keyboard with the display of the digital drawing canvas; and in accordance with a determination that the messaging user interface did not include display of a keyboard at the time the first input was detected, displaying (e.g., with the display enabling unit **6112**) the conversation transcript in a first area of the display and displaying the plurality of digital touch actions in a second area of the display.

[1534] In some embodiments, displaying the one or more launch icons for an application within the messaging user interface includes: in accordance with a determination that the messaging user interface included display of a keyboard at the time the first input was detected, replacing (e.g., with the replacing unit **6116**) display of the keyboard with the display of the one or more launch icons for an application; and in accordance with a determination that the messaging user interface did not include display of a keyboard at the time the first input was detected, displaying (e.g., with the display enabling unit **6112**) the conversation transcript in a

first area of the display and displaying the one or more launch icons for an application in a second area of the display.

[1535] In some embodiments, while displaying the one or more launch icons for an application, the processing unit **6110** is further configured to detect (e.g., with the detecting unit **6114**) an input that activates a launch icon in the one or more launch icons for an application; and after detecting the input that activates the launch icon in the one or more launch icons for an application, the processing unit **6110** is configured to: enable display (e.g., with the display enabling unit **6112**) of a first input area for an application corresponding to the activated launch icon the application that is distinct from the message input area, the input area for the first interactive application including one or more input affordances; enable display (e.g., with the display enabling unit **6112**) of a first application object within the conversation transcript that corresponds to the application corresponding to the activated launch icon; and transmit (e.g., with the transmitting unit **6118**) a representation of a second application object that corresponds to the application corresponding to the activated launch icon to one or more electronic devices that correspond to the at least one other user included in the messaging session, where the one or more electronic devices display the representation of the second application object in a conversation transcript that corresponds to the messaging session.

[1536] In some embodiments, while displaying the message-input area, the processing unit **6110** is further configured to detect (e.g., with the detecting unit **6114**) a second input that activates the message-input area; and in response to detecting the input that activates the message-input area: in accordance with a determination that the messaging user interface included display of a keyboard and did not include display of the three activatable affordances at the time the second input was detected, enable display (e.g., with the display enabling unit **6112**) of a prompt within the message-input area; in accordance with a determination that the messaging user interface included display of a keyboard and the three activatable affordances at the time the second input was detected: cease to display (e.g., with the display enabling unit **6112**) the three activatable affordances, enable display (e.g., with the display enabling unit **6112**) of the application expansion affordance, expand (e.g., with the expanding unit **6122**) display of the message input-area, and enable display (e.g., with the display enabling unit **6112**) of a prompt within the message-input area; in accordance with a determination that the messaging user interface did not include display of a keyboard and included display of the three activatable affordances at the time the second input was detected: cease to display (e.g., with the display enabling unit) the three activatable affordances, enable display (e.g., with the display enabling unit **6112**) of the application expansion affordance, expand (e.g., with the expanding unit **6122**) display of the message input-area, enable display (e.g., with the display enabling unit **6112**) of a prompt within the message-input area, and enable display (e.g., with the display enabling unit **6112**) of a keyboard; and in accordance with a determination that the messaging user interface did not include display of a keyboard and did not include display of the three activatable affordances at the time the second input was detected: enable display (e.g., with the display enabling unit **6112**) of a prompt within the message-input area, and enable display (e.g., with the display enabling unit **6112**) of a keyboard.

[1537] In some embodiments, the messaging user interface also includes a microphone affordance, configured to enable sound recording on the electronic device upon activation.

[1538] In some embodiments, the messaging user interface also includes at least one avatar corresponding to a first other user included in the messaging session, configured to enable the electronic device to display a menu that contains activatable menu items associated with the at least one avatar overlaid on the messaging user interface when activated.

[1539] In some embodiments, the menu that contains activatable menu items associated with the at least one avatar includes: a menu item that when activated initiates a digital touch action with the first other user, a menu item that when activated initiates messaging with only the first other user, a menu item that when activated initiates an email with the first other user, a menu item that when activated initiates a call with the first other user, a menu item that when activated initiates a video conference with the first other user, and/or a menu item that when activated initiates a payment action with the first other user.

[1540] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[1541] The operations described above with reference to FIGS. **60**A-**60**D are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **61**. For example, display operation **6002** and detection operation **6010** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

Adding and Manipulating Stickers

[1542] FIGS. **62**A-**62**C are flow diagrams illustrating a method **6200** of adding a sticker to a messaging transcript in accordance with some embodiments. The method **6200** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display, a touch-sensitive surface, and one or more sensors

to detect intensities of contacts with the touch-sensitive surface. In some embodiments, the display is a touch-screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **6200** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1543] As described below, the method **6200** provides an intuitive way to add a sticker to a messaging transcript. The method reduces the number, extent, and/or nature of the inputs from a user when adding a sticker to a messaging transcript, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to add a sticker to a messaging transcript faster and more efficiently conserves power and increases the time between battery charges.

[1544] The device displays (**6202**) a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript (e.g., displayed in a first area of the display) of a messaging session between a user of the electronic device and at least one other user (e.g., of another electronic device), a plurality of electronic stickers (e.g., a sticker pack displayed in a second area of the display), and a message-input area. For example, in FIG. **39**C, device **100-1** displays messaging user interface **3500**, including conversation transcript **3700**, sticker pack **3904** with electronic stickers **3906**, **3908**, and **3910**, and message-input area **3502**.

[1545] While displaying the messaging user interface, the device detects (**6204**) a first drag gesture (e.g., by a first contact on a touch-sensitive surface) that starts while a focus selector is at a first location in the messaging user interface that corresponds to a first electronic sticker in the plurality of electronic stickers, the first drag gesture moving the focus selector in a first direction; (e.g., detect a drag gesture by a contact on a touch-sensitive display that starts at the first electronic sticker and moves in a first direction, or detect a drag gesture by a contact on a touch-sensitive surface that starts while a cursor or other pointer is at the first electronic sticker on the display and moves the pointer in a first direction on the display). For example, device **100-1** detects a drag gesture including movement **3918** of contact **3906** from position **3906**-*a,* over electronic snowman sticker **3906** in FIG. **39**H, to position **3906**-*b,* in FIG. **39**I. In another example, device **100-1** detects a drag gesture including movement **3922** of contact **3920** from position **3920**-*a,* over electronic sled sticker **3910** in FIG. **39**K, to position **3920**-*b,* in FIG. **39**L. In another example, device **100-1** detects a drag gesture including movement **3926** of contact **3925** from position **3924**-a, over electronic snowflake sticker **3908** in FIG. **39**N, to position **3924**-*b,* in FIG. **39**O.

[1546] The device moves (**6206**) the first electronic sticker in the first direction in accordance with the movement of the first drag gesture. For example, electronic snowman sticker moves from location **3906**-*a,* in FIG. **39**H, to position **3906**-*b,* in FIG. **39**I, in accordance with movement **3918**. In another example, electronic sled sticker **3910** moves from position **3910**-*a,* in FIG. **39**K, to position **3910**-*b,* in FIG. **39**L, in accordance with movement **3922**. In another example, electronic snowflake sticker **3908** moves from position **3908**-*a,* in FIG. **39**N, to position **3908**-*c,* in FIG. **39**O, in accordance with movement **3926**.

[1547] In some embodiments, the plurality of electronic stickers is a plurality of objects contained within a digital image (e.g., a TV or movie frame, a digital comic illustration, a frame from a digital video, or other digital image), where (**6208**): the first electronic sticker corresponds to an object displayed at the first location at the start of the first drag gesture (e.g., tapping on any object within the digital image creates a digital sticker of that object), and moving the first electronic sticker includes displaying an animation of peeling the first electronic sticker from the digital image (e.g., it appears that the user is peeling the first electronic sticker away from the digital image).

[1548] The device detects (**6210**) termination of the first drag gesture while the focus selector is at a second location in the messaging user interface (e.g., while a contact on a touch-sensitive display is at the second location, or while a cursor or other pointer is at the second location). For example, device **100-1** detects termination of a drag gesture when contact **3916** is at position **3916**-*b* in FIG. **39**I (e.g., lift-off of contact **3916**, as illustrated in FIG. **39**J). In another example, device **100-1** detects termination of a drag gesture when contact **3920** is at position **3920**-*b* in FIG. **39**L (e.g., lift-off of contact **3920**, as illustrated in FIG. **39**M). In another example, device **100-1** detects termination of a drag gesture when contact **3924** is at position **3924**-*b* in FIG. **39**O (e.g., lift-off of contact **3924**, as illustrated in FIG. **39**P).

[1549] In response to detecting termination of the first drag gesture (e.g., detecting lift-off the contact in the drag gesture), the device: in accordance with a determination that the second location is within the conversation transcript (e.g., the sticker was dragged from the tray into the conversation transcript), places (**6212**) the electronic sticker in the conversation transcript at a location based on the second location. For example, in FIG. **39**J, electronic snowman sticker **3906** is placed in conversation transcript **3700** because the drag gesture terminated within the transcript (e.g., at position **3916**-*b*). In another example, in FIG. **39**P, electronic snowflake sticker **3908** is placed in conversation transcript **3700** because the drag gesture terminated within the transcript (e.g., at position **3916**-*b*).

[1550] In response to detecting termination of the first drag gesture (e.g., detecting lift-off the contact in the drag gesture), the device: in accordance with a determination that the second location in not within the conversation transcript (e.g., the sticker was not dragged into the conversation transcript), ceases (**6212**) to display the electronic sticker at the second location on the display. E.g., when the sticker is not dragged all the way to the conversation transcript, termination of the gesture causes the sticker to return to the sticker pack. For example, in FIG. **39**M, device **100-1** ceases displaying electronic sled sticker **3910** at position **3910**-*b* in response to detecting lift-off of contact **3920** (e.g., termination of the drag gesture) while outside of conversation transcript **3700** (e.g., at position **3920**-*b*),

[1551] In some embodiments, the electronic device differentiates between an input that allows the user to place the sticker at a user-selected location in the transcript and an input that places the sticker at a default location within the transcript. For example, a drag gesture places the sticker at a user-selection location within the transcript (e.g., snowman sticker **3906** is dragged to, and placed at, position **3906**-*b* in FIGS. **39**H-**39**J, while a stationary gesture (such as a tap, light press, or deep press) places the sticker in the transcript at a default next location designated for a user message (e.g., with or without a surrounding message bubble). For example, snowflake sticker **3908** is placed in

transcript **3700** at position **3908**-*a,* in FIG. **39**G, corresponding to the next temporal position within the conversation transcript, after detecting a tap gesture on the sticker, including contact **3912** in FIG. **39**D.

[1552] In some embodiments, the device displays a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript (e.g., displayed in a first area of the display) of a messaging session between a user of the electronic device and at least one other user (e.g., of another electronic device), a plurality of electronic stickers (e.g., a sticker pack displayed in a second area of the display), and a message-input area. While displaying the messaging user interface, the device detects a first user input at a location corresponding to display of a first electronic sticker. In response to detecting the first user input: in accordance with a determination that the first user input includes a drag gesture starting at the location corresponding to display of the first electronic sticker and ending at a location corresponding to display of the conversation transcript, placing the electronic sticker in the conversation transcript (e.g., dragging the sticker into the conversation transcript). For example, snowman sticker **3906** is dragged into conversation transcript **3700** in FIGS. **39**J-**39**J. In accordance with a determination that the first user input satisfies tap gesture criteria (e.g., detection of initiation and termination of a user contact, having a characteristic intensity that does not reach a predefined intensity threshold, at a substantial same location), displaying the electronic sticker in the message-input area (e.g., which allows the user to post the sticker to the transcript at a location corresponding to the next message). For example, snowflake sticker **3908** is tapped on and placed in message-input area **3502** in FIGS. **39**D-**39**F.

[1553] In some embodiments, the location based on the second location is the second location (**6214**). For example, the sticker is placed in the transcript at the location where the drag gesture terminated (e.g., by user lift-off of the contact corresponding to the drag gesture or by timing-out of the drag gesture by maintaining a relatively stable position for a pre-defined period of time). For example, in FIG. **39**J, electronic snowman sticker **3906** is placed at position **3906**-*b* in transcript **3700**, where it was displayed when the device detected termination (e.g., lift-off) of the drag gesture including contact **3916**.

[1554] In some embodiments, the conversation transcript includes display of one or more objects posted to the messaging session (e.g., message bubbles, icons for interactive applications, and/or multimedia content), the location is based on the second location is a nearest position in a plurality of positions that are defined by the positions of the one or more objects posted to the messaging session (**6216**). For example, device **100-1** detects termination of a drag gesture including contact **3924** at position **3924**-*b* in conversation transcript, when electronic snowflake sticker **3908** is displayed at position **3908**-*c,* in FIG. **390**. In response, snowflake sticker **3908** is placed (e.g., displayed) at position **3908**-*d*, corresponding to the nearest point on a message object (e.g., message region **3749**), in FIG. **39**P.

[1555] In some embodiments, the plurality of positions include positions that are defined by the outside border of the one or more objects posted to the messaging session (e.g., every position defining the outlines of the one or more objects, a set number of positions on the outlines (e.g., horizontal and vertical mid-points on the top, bottom, right, and left borders of each object), regularly spaced positions along the outside border (e.g., every X pixels or spaced to provide Y positions on each object)).

[1556] In some embodiments, the plurality of positions include positions that are defined by the surface area of the one or more objects posted to the messaging session (e.g., every position within the border (inclusive or exclusive) of an object, a set number of positions within each object (e.g., quadrant midpoints within each object), regularly spaced positions within each object (e.g., every (X, Y) pixels or spaced to provide Z positions within each object).

[1557] In some embodiments, the plurality of positions include one or more positions that are defined by a relationship between two adjacent objects (e.g., positions defined by the mid-point between two objects).

[1558] In some embodiments, in response to detecting termination of the first drag gesture, in accordance with a determination that the second location is within the conversation transcript, the device (**6218**) transmits information that represents the electronic sticker to one or more (e.g., at least a second) electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display a corresponding representation of the electronic sticker in a corresponding location within a corresponding conversation transcript

[1559] In some embodiments, where messages sent from the user of the electronic device and messages received from other users are displayed on opposite sides of a conversation transcript, the corresponding location is a position that is a mirror image of the position at which the stick is displayed on the sending user's electronic device (e.g., a mirror image of the position or a mirror image of the position and the sticker).

[1560] In some embodiments, the device (**6220**) detects a user input while the focus selector is at a third position that corresponds to a second electronic sticker in the plurality of electronic stickers (e.g., while a contact on a touch-sensitive display is at the second electronic sticker, or while a cursor or other pointer is at the second electronic sticker). For example, an input including one of contact **3912**, in FIG. **39**D and contact **3932**, in FIG. **39**Z,

[1561] In response to detecting the user input while the focus selector is at the third position, in accordance with a determination that the user input satisfies one or more sticker-selection-criteria (e.g., which are distinct from sticker posting criteria), the device displays the second electronic sticker in the message-input area (e.g., snowflake sticker **3908** is displayed in message-input area **3502** in FIG. **39**F.

[1562] In some embodiments, the sticker selection criteria include a criterion that is configured to be met when a characteristic intensity of a contact in the input remains below a first intensity threshold.

[1563] In some embodiments, the sticker selection criteria include a criterion that is met when a characteristic intensity of a contact in the input satisfies a first intensity threshold (e.g., the sticker is displayed in the message-input area, but may be pushed-through to the transcript by pressing harder)

[1564] In some embodiments, the sticker can then be posted to the messaging session by a second user input corresponding to a request to post the content within the message-input area, such as a tap gesture at a location that corresponds to a send icon on the display. For example,

snowflake sticker **3908** is displayed in conversation transcript **3700**, in FIG. **39**G, in response to a tap gesture including contact **3914** on send affordance **3520**, in FIG. **39**F.

[1565] In response to detecting the user input while the focus selector is at the third position, in accordance with a determination that the user input satisfies one or more sticker-posting-criteria, displaying the sticker in the conversation transcript at a location that corresponds to a next message insertion point. For example, snowman sticker **3906** is directly posted to the messaging session (e.g., displayed in transcript **3700**), in FIG. **39**AA in response to detecting deep press gesture including contact **3932**.

[1566] In some embodiments, the sticker posting criteria include a criterion that is met when a characteristic intensity of a contact in the input goes above a second intensity threshold.

[1567] In some embodiments, posting the sticker to the messaging session at the position where the next messaging bubble would be located, e.g., at position **3908**-*b* in FIG. **39**G or position **3906**-*c* in FIG. **39**AA.

[1568] In some embodiments, the one or more sticker-posting-criteria require that a characteristic intensity of the first contact on the touch-sensitive surface meet a respective intensity threshold in order for the transcript-area-display criteria to be met are met when the characteristic intensity of the first contact is between the second intensity threshold and a third intensity threshold; and the one or more sticker-selection-criteria do not require that the characteristic intensity of the contact on the touch-sensitive surface meet the respective intensity threshold in order for the selection criteria to be met.

[1569] In some embodiments, the device detects (**6222**) a user input while the focus selector is at a fourth position that corresponds to a third electronic sticker in the plurality of electronic stickers (e.g., while a contact on a touch-sensitive display is at the third electronic sticker, or while a cursor or other pointer is at the third electronic sticker) wherein the third electronic sticker is associated with a sticker animation. For example, in FIGS. **39**Q-**39**X, snowman sticker **3906** is associated with an animation including movement of the snowman's broom up and down, cycling through animation states **3930**-*a,* **3930**-*b,* and **3930**-*c.* Device **100-1** detects an input including contact **3928** on snowman sticker **3906** in sticker pack **3904**.

[1570] In some embodiments, the sticker animation is displayed in a loop when the sticker is posted to the messaging session. In some embodiments, the sticker animation is displayed a pre-defined number of times after being posted to the messaging session. In some embodiments, the sticker animation is displayed upon activation by a user within a corresponding conversation transcript. In some embodiments, the sticker animation is automatically displayed in the sticker pack.

[1571] In response to detecting the user input while the focus selector is at the fourth position, in accordance with a determination that the user input satisfies one or more animation preview criteria (e.g., deep-press criteria) the device previews the sticker animation associated with the third electronic sticker (e.g., a cat sticker cries when a user presses on the cat sticker in a sticker pack). For example, device **100-1** displays a preview of the animation for snowman sticker displayed in sticker pack **3904**, in FIGS. **39**-V-**39**X.

[1572] In some embodiments, the animation preview criteria include a criterion that is met when a characteristic intensity of a contact in the input satisfies an intensity threshold. In some embodiments, a press and hold gesture satisfies animation preview criteria. In some embodiments, a deep press gesture satisfies animation preview criteria. In some embodiments, a light press does not satisfy animation preview. In some embodiments, a light press gesture causes the electronic sticker to be displayed in the message-input area, previewing the sticker animation associated with the third electronic sticker (e.g., a cat sticker cries when a user presses on the cat sticker in a sticker pack).

[1573] In some embodiments, prior to displaying the plurality of electronic stickers, the device (**6224**) displays the messaging user interface including the conversation transcript (e.g., displayed in a first area of the display) of the messaging session between the user of the electronic device and the at least one other user (e.g., of another electronic device) and an application affordance (e.g., user interface **3500** in FIG. **39**A).

[1574] While displaying the messaging user interface, the device detects an input that activates the application affordance. For example, an input including contact **3902** on application affordance **3508**, in FIG. **39**B (e.g., detecting a tap gesture at a location that corresponds to the application affordance).

[1575] In response to detecting the input that activates the application affordance, the device maintains display of at least a portion of the conversation transcript in a first area of the display (e.g., FIG. **39**C includes a portion of conversation transcript **3700** displayed in FIG. **39**C. The device displays the plurality of electronic stickers in a second area of the display (e.g., in sticker pack **3904**, in FIG. **39**C).

[1576] In some embodiments, where the messaging user interface includes display of an electronic keyboard prior to activating the application affordance, the display of the plurality of electronic stickers replaces display of the keyboard (e.g., display of sticker pack **3904** would replace display of digital keyboard **3501**).

[1577] In some embodiments, where the messaging user interface includes a full-screen display of the conversation transcript prior to activating the application affordance, the display of the plurality of electronic stickers replaces a portion of the display of the message transcript. For example, in FIG. **39**B, conversation transcript **3700** is displayed in full-screen mode. In response to activation of sticker pack **3904** by an input including contact **3902** in FIG. **39**B, display of conversation transcript **3700** is reduced to accommodate display of the sticker pack in FIG. **39**C.

[1578] In some embodiments, prior to displaying the plurality of electronic stickers: the device (**6226**) displays the messaging user interface including the conversation transcript (e.g., displayed in a first area of the display) of the messaging session between the user of the electronic device and the at least one other user (e.g., of an electronic device) and an application affordance. For example, messaging user interface **3500** in FIG. **39**AB.

[1579] While displaying the messaging user interface, the device detects an input that activates the application affordance. For example, in FIG. **39**AB, an input including contact **3934** activates application affordance **3508**.

[1580] In response to detecting the input that activates the application affordance, the device maintains display of at least a portion of the conversation transcript in a first area of

the display (e.g., device **100-1** maintains display of conversation transcript **3700** in FIG. **39**AC), and the device displays a first interactive application icon (e.g., an icon for a first interactive application), which is one of a plurality of interactive application icons, in a second area of the display (e.g., in a scrollable interactive application panel). For example, interactive reservations application launch icon **3708** displayed in application slide tray **3892**, in FIG. **39**AC.

[1581] In some embodiments, where the messaging user interface includes display of an electronic keyboard prior to activating the application affordance, the display of the scrollable interactive application panel replaces display of the keyboard (e.g., application slide tray **3892** may replace display of digital keyboard **3501**.

[1582] In some embodiments, where the messaging user interface includes a full-screen display of the conversation transcript prior to activating the application affordance, the display of the scrollable interactive application panel replaces a portion of the display of the message transcript. For example, in FIG. **39**AC, application slide tray **3892** replaces a portion of transcript **3700**, displayed in full-screen mode in FIG. **39**AB.

[1583] While displaying the first interactive application icon in the second area of the display, detecting a first swipe gesture that includes horizontal movement of a first contact at a location that corresponds to the second area of the display. For example, device **100-1** detects a swipe gesture including movement **3938** of contact **3936** from position **3936**-*a,* in FIG. **39**AD, to position **3936**-*b,* in FIG. **39**AE.

[1584] In accordance with a determination that the first swipe gesture satisfies one or more interactive application icon switching criteria, the device replaces display of the first interactive application icon with display of the plurality of electronic stickers in the second area of the display. For example, sticker pack **3904**, in FIG. **39**AF, replaces display of interactive reservations application launch icon **3708**, in FIG. **39**AD, in accordance to movement **3938** of contact **3936**.

[1585] In some embodiments, the interactive application icon switching criteria includes a criterion that the magnitude of a horizontal movement of the first swipe gesture satisfies a predetermined movement threshold. In some embodiments, the predetermined movement threshold varies with the speed of the movement of the contact.

[1586] In some embodiments, prior to displaying the plurality of electronic stickers, the device (**6228**) displays the messaging user interface including the conversation transcript (e.g., displayed in a first area of the display) of the messaging session between the user of the electronic device and the at least one other user (e.g., of another electronic device) and an application affordance (e.g., messaging user interface **3500** in FIG. **39**AU.

[1587] While displaying the messaging user interface, the device detects an input that activates the application affordance (e.g., detecting a tap gesture at a location that corresponds to the application affordance). For example, in FIG. **39**AU, an input including contact **3952** activates application affordance **3508**.

[1588] In response to detecting the input that activates the application affordance, the device maintains display of at least a portion of the conversation transcript in a first area of the display (e.g., device **100-1** maintains display of conversation transcript **3700** in FIG. **39**AV) and displays in a second area of the display that includes a plurality of application launch icons (e.g., including launch icons for one or more interactive applications; e.g., application selection tray **3654** in FIG. **39**AV), an application launch icon for a sticker pack (e.g., sticker pack launch icon **3609** in application selection tray **3654** in FIG. **39**AV.

[1589] In some embodiments, where the messaging user interface includes display of an electronic keyboard prior to detecting activation of the application affordance, the display of the plurality of application launch icons replaces display of the keyboard. For example, display of application selection tray **3654**, in FIG. **36**Y, replaces digital keyboard **3501**, in FIG. **36**X.

[1590] In some embodiments, where the messaging user interface includes a full-screen display of the conversation transcript prior to detecting activation of the application affordance, the display of the plurality of application launch icons replaces a portion of the display of the message transcript. For example, in FIG. **39**AV, application selection tray **3654** replaces a portion of transcript **3700**, displayed in full-screen mode, in FIG. **39**AU.

[1591] While displaying the plurality of application launch icons, the device detects an input that activates the application launch icon for the sticker pack. For example, device **100-1** detects an in input including contact **3954** over sticker pack launch icon **3609**, in FIG. **39**AV.

[1592] In response to a detecting the input that activates the application launch icon for the sticker pack (e.g., detecting a tap gesture at a location that corresponds to the launch icon for the sticker pack), the device replaces display of the plurality of application launch icons with display of the plurality of electronic stickers in the second area of the display. For example, in response to detecting an input including contact **3954**, in FIG. **39**AV, device **100-1** replaces display of application selection tray **3654**, in FIG. **39**AV, with display of sticker pack **3904**, in FIG. **39**AW.

[1593] It should be understood that the particular order in which the operations in FIGS. **62**A-**62**C have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **5800**, **6000**, **6400**, **6600**, **6800**, and **7000**) are also applicable in an analogous manner to method **6200** described above with respect to FIGS. **62**A-**62**C. For example, the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations described above with reference to method **6200** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations described herein with reference to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **5800**, **6000**, **6400**, **6600**, **6800**, and **7000**). For brevity, these details are not repeated here.

[1594] In accordance with some embodiments, FIG. **63** shows a functional block diagram of an electronic device **6300** configured in accordance with the principles of the various described embodiments. The functional blocks of

the device are, optionally, implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. **63** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[1595] As shown in FIG. **63**, an electronic device **6300** includes a display unit **6302** configured to display user interfaces; a touch-sensitive surface unit **6304** configured to detect contacts; and a processing unit **6306** coupled with the display unit **6302** and the touch-sensitive surface unit **6304**. The processing unit **6306** includes: an enabling unit **6308**, a detecting unit **6310**, a moving unit **6312**, a placing unit **6314**, a ceasing unit **6316**, a previewing unit **6318**, a maintaining unit **6320**, and a replacing unit **6322**. The processing unit **6306** is configured to enable display of (e.g., with enabling unit **6308**) a messaging user interface of a messaging application on the display unit **6302**, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a plurality of electronic stickers, and a message-input area. While displaying the messaging user interface, the processing unit **6306** is configured to detect (e.g., with detecting unit **6310**) a first drag gesture that starts while a focus selector is at a first location in the messaging user interface that corresponds to a first electronic sticker in the plurality of electronic stickers, the first drag gesture move the focus selector in a first direction. The processing unit **6306** is configured to move (e.g., with moving unit **6312**) the first electronic sticker in the first direction in accordance with the movement of the first drag gesture. The processing unit **6306** is configured to detect (e.g., with detecting unit **6310**) termination of the first drag gesture while the focus selector is at a second location in the messaging user interface. In response to detecting termination of the first drag gesture: in accordance with a determination that the second location is within the conversation transcript, the processing unit **6306** is configured to place (e.g., with placing unit **6314**) the electronic sticker in the conversation transcript at a location based on the second location, and in accordance with a determination that the second location in not within the conversation transcript, the processing unit **6306** is configured to cease (e.g., with ceasing unit **6316**) to display the electronic sticker at the second location on the display unit **6302**.

[1596] In some embodiments, the processing unit **6306** is further configured to: in response to detecting termination of the first drag gesture, in accordance with a determination that the second location is within the conversation transcript: transmit (e.g., with transmitting unit **6317**) information that represents the electronic sticker to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display a corresponding representation of the electronic sticker in a corresponding location within a corresponding conversation transcript.

[1597] In some embodiments, the location based on the second location is the second location.

[1598] In some embodiments, the conversation transcript includes display of one or more objects posted to the messaging session, the location based on the second location is a nearest position in a plurality of positions that are defined by the positions of the one or more objects posted to the messaging session.

[1599] In some embodiments, the processing unit **6306** is further configured to: detect (e.g., with detecting unit **6310**) a user input while the focus selector is at a third position that corresponds to a second electronic sticker in the plurality of electronic stickers. In response to detecting the user input while the focus selector is at the third position: in accordance with a determination that the user input satisfies one or more sticker-selection-criteria, enable display of (e.g., with enabling unit **6308**) the second electronic sticker in the message-input area; and in accordance with a determination that the user input satisfies one or more sticker-posting-criteria, enable display of (e.g., with enabling unit **6308**) the sticker in the conversation transcript at a location that corresponds to a next message insertion point.

[1600] In some embodiments, the processing unit **6306** is further configured to: detect (e.g., with detecting unit **6310**) a user input while the focus selector is at a fourth position that corresponds to a third electronic sticker in the plurality of electronic stickers, wherein the third electronic sticker is associated with a sticker animation. In response to detecting the user input while the focus selector is at the fourth position, in accordance with a determination that the user input satisfies one or more animation preview criteria, preview (e.g., with previewing unit **6318**) the sticker animation associated with the third electronic sticker.

[1601] In some embodiments, the processing unit **6306** is further configured to: prior to displaying the plurality of electronic stickers: enable display of (e.g., with enabling unit **6308**) the messaging user interface including the conversation transcript of the messaging session between the user of the electronic device and the at least one other user and an application affordance. While displaying the messaging user interface, the processing unit **6306** is configured to detect (e.g., with detecting unit **6310**) an input that activates the application affordance. In response to detecting the input that activates the application affordance, the processing unit **6306** is configured to: maintain display of (e.g., with maintaining unit **6320**) at least a portion of the conversation transcript in a first area of the display, and enable display of (e.g., with enabling unit **6308**) the plurality of electronic stickers in a second area of the display.

[1602] In some embodiments, the processing unit **6306** is further configured to: prior to displaying the plurality of electronic stickers: enable display of (e.g., with enabling unit **6308**) the messaging user interface including the conversation transcript of the messaging session between the user of the electronic device and the at least one other user and an application affordance. While displaying the messaging user interface, the processing unit **6306** is configured to detect (e.g., with detecting unit **6310**) an input that activates the application affordance. In response to detecting the input that activates the application affordance, the processing unit **6306** is configured to: maintain display of (e.g., with maintaining unit **6320**) at least a portion of the conversation transcript in a first area of the display, and enable display of (e.g., with enabling unit **6308**) a first interactive application icon, which is one of a plurality of interactive application icons, in a second area of the display. While displaying the first interactive application icon in the second area of the display, the processing unit **6306** is configured to

detect (e.g., with detecting unit **6310**) a first swipe gesture that includes horizontal movement of a first contact at a location that corresponds to the second area of the display. In accordance with a determination that the first swipe gesture satisfies one or more interactive application icon switching criteria, the processing unit **6306** is configured to replace display of (e.g., with replacing unit **6322**) the first interactive application icon with display of the plurality of electronic stickers in the second area of the display.

[1603] In some embodiments, the processing unit **6306** is further configured to: prior to displaying the plurality of electronic stickers: enable display of (e.g., with enabling unit **6308**) the messaging user interface including the conversation transcript of the messaging session between the user of the electronic device and the at least one other user and an application affordance. While displaying the messaging user interface, the processing unit **6306** is configured to detect (e.g., with detecting unit **6310**) an input that activates the application affordance. In response to detecting the input that activates the application affordance, the processing unit **6306** is configured to: maintain display of (e.g., with maintaining unit **6320**) at least a portion of the conversation transcript in a first area of the display, and enable display of (e.g., with enabling unit **6308**), in a second area of the display that includes a plurality of application launch icons, an application launch icon for a sticker pack. While displaying the plurality of application launch icons, the processing unit **6306** is configured to detect (e.g., with detecting unit **6310**) an input that activates the application launch icon for the sticker pack. In response to a detecting that the input that activates the application launch icon for the sticker pack, the processing unit **6306** is configured to replace display of (e.g., with replacing unit **6322**) the plurality of application launch icons with display of the plurality of electronic stickers in the second area of the display.

[1604] In some embodiments, the plurality of electronic stickers is a plurality of objects contained within a digital image, wherein: the first electronic sticker corresponds to an object displayed at the first location at the start of the first drag gesture; and moving the first electronic sticker includes displaying an animation of peeling the first electronic sticker from the digital image.

[1605] The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1**A and **3**) or application specific chips.

[1606] The operations described above with reference to FIGS. **62**A-**62**C are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **63**. For example, detection operation **6204** and move operation **6206** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

[1607] FIGS. **64**A-**64**C are flow diagrams illustrating a method **6400** of modifying display of electronic stickers in a messaging application in accordance with some embodiments. The method **6400** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display, a touch-sensitive surface, and one or more sensors to detect intensities of contacts with the touch-sensitive surface. In some embodiments, the display is a touch-screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **6400** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1608] As described below, the method **6400** provides an intuitive way to modify display of electronic stickers in a messaging application. The method reduces the number, extent, and/or nature of the inputs from a user when modifying display of electronic stickers in a messaging application, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to modify display of electronic stickers in a messaging application faster and more efficiently conserves power and increases the time between battery charges.

[1609] The device displays (**6402**) a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript (e.g., displayed in a first area of the display) of a messaging session between a user of the electronic device and at least one other user (e.g., of another electronic device), a plurality of electronic stickers (e.g., a sticker pack displayed in a second area of the display), and a message-input area. For example in FIG. **39**AF, device **100-1** displays messaging user interface **3500**, including conversation transcript **3700**, electronic sticker pack**3904**, including electronic stickers **3906**, **3908**, and **3910**, and message-input area **3502**.

[1610] While displaying the messaging user interface (e.g., user interface **3500**), the device detects (**6404**) a first user input (e.g., by a first contact on a touch-sensitive surface, such as a drag gesture or a tap gesture) while a focus selector is at a first location in the messaging user interface that corresponds to a first electronic sticker in the plurality of electronic stickers (e.g., detect a drag gesture by a contact on a touch-sensitive display that starts at the first electronic sticker and moves in a first direction, or detect a drag gesture by a contact on a touch-sensitive surface that starts while a cursor or other pointer is at the first electronic sticker on the display and moves the pointer in a first direction on the display). In some embodiments, the first electronic sticker is initially not within the conversation transcript (e.g., the first electronic sticker is in a sticker pack displayed in a second area of the display).

[1611] For example, device **100-1** detects an input including: a drag gesture, including movement **3942** of contact **3940** from position **3940**-*a,* over electronic snowman sticker **3906** displayed in sticker pack **3904**, in FIG. **39**AG, through position **3940**-*b,* in FIG. **39**AH, to position **3940**-*c,* in FIG. **39**AI; increases in a characteristic intensity of contact **3940** between FIGS. **39**AG-**39**AH and **39**AH-**39**AI, respectively; a decrease in a characteristic intensity of contact **3940** between FIG. **39**AI and FIG. **39**AJ; and a rotation gesture, including rotation **3944** of contact **3940** from orientation (e.g., position) **3940**-*c,* in FIG. **39**AK, to orientation (e.g., position) **3940**-*d,* in FIG. **39**AL.

[1612] In response to detecting the first user input, the device (**6406**) places and displays the first electronic sticker in the conversation transcript. For example, device **100-1** displays electronic sticker **3906** at position (e.g., location and orientation) **3906**-*f,* in FIG. **39**AM.

[1613] While the first electronic sticker is displayed in the conversation transcript, the device (**6408**): detects a second user input while a focus selector is at a second location in the messaging user interface that corresponds to the first electronic sticker in the conversation transcript (e.g., detect a drag gesture, a portion of a depinch gesture, or a rotate gesture by a contact on a touch-sensitive display that starts at the location of the first electronic sticker in the transcript, or detect a drag gesture, a portion of a depinch gesture, or a rotate gesture by a contact on a touch-sensitive surface that starts while a cursor or other pointer is at the location of the first electronic sticker in the transcript).

[1614] For example, device **100-1** detects an input including: movement **3948** of contact **3946**, within conversation transcript **3700**, from position **3946**-*a,* in FIG. **39**AN, to position **3946**-*b,* in FIG. **39**AO; an increase in a characteristic intensity of contact **3946** between FIG. **39**AO and FIG. **39**AP; and rotation **3950** of contact **3946** from orientation (e.g., position) **3946**-*b,* in FIG. **39**AQ, to orientation (e.g., position) **3946**-*c,* in FIG. **39**R.

[1615] In some embodiments, the first and second user inputs are first and second parts of a single continuous input, e.g., a drag gesture followed by a pinch or rotation gesture made with the same contact.

[1616] In response to detecting the second user input, the device (**6408**) changes the position, size, and/or rotation of the first electronic sticker in the conversation transcript. (e.g., while maintaining a constant display of the conversation transcript behind the first electronic sticker).

[1617] For example, device **100-1** moves electronic snowman sticker **3906** from position **3906**-*f,* in FIG. **39**AN, to position **3906**-*g,* in FIG. **39**AO. In another example, device **100-1** increases the size of electronic snowman sticker **3906**, displayed in transcript **3700**, between FIG. **39**AO and Figure AP. In another example, device **100-1** rotates electronic snowman sticker **3906** from orientation (e.g., position) **3906**-*g,* in FIG. **39**AQ, to orientation (e.g., position) **3906**-*h,* in FIG. **39**AR.

[1618] In some embodiments, the size of the first electronic sticker is reduced (**6410**) in response to detecting a pinch gesture that includes movement of a first contact towards a second contact, wherein the pinch gesture started while a focus selector was at a location in the messaging user interface that corresponds to the first electronic sticker (e.g., pinching while over the electronic sticker reduces the display size of the sticker without changing the display size of the conversation transcript).

[1619] In some embodiments, the size of the first electronic sticker is increased (**6412**) in response to detecting a depinch gesture that includes movement of a first contact away from a second contact, wherein the depinch gesture started while a focus selector was at a location in the messaging user interface that corresponds to the first electronic sticker (e.g., depinching while over the electronic sticker increases the display size of the sticker without changing the display size of the conversation transcript).

[1620] In some embodiments, the size of the first electronic sticker is increased (**6414**) in accordance with a (e.g., change in a) characteristic intensity of a contact made while a focus selector was at a location in the messaging user interface that corresponds to the first electronic sticker. For example, the size of electronic snowman sticker **3906** is increased between FIGS. **39**AG-**39**AH, **39**AH-**39**AI, and **39**AO-**39**AP, respectively.

[1621] In some embodiments, the size of the first electronic sticker is decreased in accordance with a (e.g., change in a) characteristic intensity of a contact made while a focus selector was at a location in the messaging user interface that corresponds to the first electronic sticker. For example, the size of electronic snowman sticker **3906** is decreased between FIG. **39**AI and FIG. **39**AJ.

[1622] In some embodiments, the orientation of the first electronic sticker is changed (**6416**) in response to detecting a rotation gesture that started while a focus selector was at a location in the messaging user interface that corresponds to the first electronic sticker. For example, the orientation (e.g., position) of electronic snowman sticker **3906** is rotated from orientation **3906**-*e,* in FIG. **39**AK, to orientation **3906**-*f,* in FIG. **39**AL. In another example, the orientation (e.g., position) of electronic snowman sticker **3906** is rotated from orientation **3906**-*g,* in FIG. **39**AQ, to orientation **3906**-*h,* in FIG. **39**AR.

[1623] In some embodiments, the rotation gesture includes rotation of a single user contact. In some embodiments, the rotation gesture includes rotation of a first contact relative to a second contact.

[1624] In some embodiments, after detecting the first user input, the device transmits (**6418**) information that represents the first electronic sticker to one or more (e.g., second) electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display a corresponding representation of the first electronic sticker in a corresponding location (e.g., a corresponding location, size, and rotation) within a corresponding conversation transcript (e.g., corresponding to the messaging session).

[1625] In some embodiments, information that represents the first electronic sticker is sent in response to detecting the first user input (e.g., upon detection of lift-off of contact **3940** in FIG. **39**AM), and subsequent movement, resizing, and/or rotation of the sticker causes the device to send subsequent information that represents the first electronic sticker (e.g., the position, including location, size, and/or orientation) (e.g., upon detection of lift-off of contact **3946** in FIG. **39**AS).

[1626] In some embodiments, information that represents the first electronic sticker is not sent until the user has finally positioned, sized, and/or rotated the sticker within the conversation transcript (e.g., with the second user input). For example, information is sent upon detection of lift-off of

contact **3946** in FIG. **39**AS, but not upon detection of lift-off of contact **3940** in FIG. **39**AM.

[1627] In some embodiments, once the user places, sizes, and/or rotates the electronic sticker, further modifications to the sticker in the transcript cannot be made (e.g., detection of a second input, including second contact **3946**, in FIG. **39**AN, would not cause device **100-1** to move, resize, or rotate electronic snowman sticker **3906** within conversation transcript **3700**).

[1628] In some embodiments, once the user places, sizes, and/or rotates the electronic sticker, further modifications to the sticker in the transcript can only be made within a predetermined time period (e.g., initiation of further modifications) beginning at termination of the first input, placing the sticker in the conversation transcript. For example, detection of a second input, including second contact **3946**, in FIG. **39**AN, would only cause device **100-1** to move, resize, or rotate electronic snowman sticker **3906** within conversation transcript **3700** if the second input was first detected within the predefined time period.

[1629] In some embodiments, after transmitting the information that represents the first electronic sticker to the one or more electronic devices, the device (**6420**) detects a third user input while a focus selector is at a third location in the messaging user interface that corresponds to the first electronic sticker in the conversation transcript and, in response to detecting the third user input: changes the position of the first electronic sticker in the conversation transcript for a second time, and sends information to the one or more electronic devices that correspond to the at least one other user included in the messaging session that the position of the first electronic sticker was changed in the conversation transcript, wherein the one or more electronic devices make corresponding changes to the position of the first electronic sticker within the corresponding conversation transcript (e.g., to match or mirror the changes made in the first user's conversation transcript).

[1630] In some embodiments, only the user who posted the sticker to the messaging session can change the position, size, or rotation of the sticker. In some embodiments, any user included in the messaging session can change the position, size, and/or rotation of the sticker. In some embodiments, no user can change the position, size and/or rotation of the sticker once it has been posted to the messaging session.

[1631] In some embodiments, after transmitting the information that represents the first electronic sticker to the one or more electronic devices, the device (**6422**) detects a third user input while a focus selector is at a third location in the messaging user interface that corresponds to the first electronic sticker in the conversation transcript and, in response to detecting the third user input: changes the rotation (e.g., orientation) of the first electronic sticker in the conversation transcript for a second time, and sends information to the one or more electronic devices that correspond to the at least one other user included in the messaging session that the rotation (e.g., orientation) of the first electronic sticker was changed in the conversation transcript, wherein the one or more electronic devices make corresponding changes to the rotation (e.g., orientation) of the first electronic sticker within the corresponding conversation transcript (e.g., to match or mirror the changes made in the first user's conversation transcript).

[1632] In some embodiments, only the user who posted the sticker to the messaging session can change the position, size, or rotation of the sticker. In some embodiments, any user included in the messaging session can change the position, size, and/or rotation of the sticker. In some embodiments, no user can change the position, size and/or rotation of the sticker once it has been posted to the messaging session.

[1633] In some embodiments, after transmitting the information that represents the first electronic sticker to the one or more electronic devices, the device (**6424**) detects a third user input while a focus selector is at a third location in the messaging user interface that corresponds to the first electronic sticker in the conversation transcript and, in response to detecting the third user input: changes the size of the first electronic sticker in the conversation transcript for a second time, and sends information to the one or more electronic devices that correspond to the at least one other user included in the messaging session that the size of the first electronic sticker was changed in the conversation transcript, wherein the one or more electronic devices make corresponding changes to the size of the first electronic sticker within the corresponding conversation transcript (e.g., to match or mirror the changes made in the first user's conversation transcript).

[1634] In some embodiments, only the user who posted the sticker to the messaging session can change the position, size, or rotation of the sticker. In some embodiments, any user included in the messaging session can change the position, size, and/or rotation of the sticker. In some embodiments, no user can change the position, size and/or rotation of the sticker once it has been posted to the messaging session.

[1635] In some embodiments, after transmitting the information that represents the first electronic sticker to the one or more electronic devices, the device receives information from an electronic device that corresponds to another user included in the messaging session that the position, size, and/or orientation of a corresponding representation of the first electronic sticker was changed in a corresponding conversation transcript and, in response, changes the position, size, and/or orientation of the first electronic sticker in the conversation transcript. For example, device **100-1** receives information from device **100-2** at 9:56 AM and, in response, changes the position, size, and orientation of electronic snowman sticker **3906** from location **3906-*h*,** in FIG. **39**AS, to location **3906**-i, in FIG. **39**AT.

[1636] In some embodiments, in response to detecting the first user input, the device changes (**6426**) the position, of the first electronic sticker (e.g., the size, position, and orientation of the sticker can be changes while still displayed in the sticker pack and/or while being dragged into the conversation transcript). For example, movement of electronic snowman sticker **3906** from position **3906-*a*,** in FIG. **39**AG, through position **3906-*d*,** in FIG. **39**AH, to position **3906-*e*,** in FIG. **39**AI.

[1637] In some embodiments, in response to detecting the first user input, the device changes (**6428**) the size of the first electronic sticker (e.g., the size, position, and orientation of the sticker can be changes while still displayed in the sticker pack and/or while being dragged into the conversation transcript). For example, the size of electronic snowman sticker **3906** is increased between FIGS. **39**AG-**39**AH and

39AH-**39**AI, respectively. In another example, the size of electronic snowman sticker **3906** is decreased between FIG. **39**AI and FIG. **39**AJ.

[1638] In some embodiments, in response to detecting the first user input, the device changes (**6430**) the rotation of the first electronic sticker (e.g., the size, position, and orientation of the sticker can be changes while still displayed in the sticker pack and/or while being dragged into the conversation transcript). For example, electronic snowman sticker **3906** is rotated from orientation (e.g., position) **3906**-*e,* in FIG. **39**AK, to orientation (e.g., position) **3906**-*f,* in FIG. **39**AL.

[1639] It should be understood that the particular order in which the operations in FIGS. **64**A-**64**C have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6600**, **6800**, and **7000**) are also applicable in an analogous manner to method **6400** described above with respect to FIGS. **64**A-**64**C. For example, the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, and animations described above with reference to method **6400** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6600**, **6800**, and **7000**). For brevity, these details are not repeated here.

[1640] In accordance with some embodiments, FIG. **65** shows a functional block diagram of an electronic device **6500** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. **65** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[1641] As shown in FIG. **65**, an electronic device **6500** includes a display unit **6502** configured to display user interfaces; a touch-sensitive surface unit **6504** configured to detect contacts; and a processing unit **6506** coupled with the display unit **6502** and the touch-sensitive surface unit **6504**. The processing unit **6506** including an enabling unit **6508**, a detecting unit **6510**, a placing unit **6512**, a changing unit **6514**, a transmitting unit **6516**, and a sending unit **6518**.

[1642] The processing unit **6506** is configured to: enable display of (e.g., with enabling unit **6508**) a messaging user interface of a messaging application on the display unit **6502**, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a plurality of electronic stickers, and a message-input area. While displaying the messaging user interface, the processing unit **6506** is configured to detect (e.g., with detecting unit **6510**) a first user input while a focus selector is at a first location in the messaging user interface that corresponds to a first electronic sticker in the plurality of electronic stickers. In response to detecting the first user input, the processing unit **6506** is configured to place (e.g., with placing unit **6512**) and enable display of (e.g., with enabling unit **6508**) the first electronic sticker in the conversation transcript. While the first electronic sticker is displayed in the conversation transcript: the processing unit **6506** is configured to detect (e.g., with detecting unit **6510**) a second user input while a focus selector is at a second location in the messaging user interface that corresponds to the first electronic sticker in the conversation transcript. In response to detecting the second user input, the processing unit **6506** is configured to change (e.g., with changing unit **6514**) the position, size, and/or rotation of the first electronic sticker in the conversation transcript.

[1643] In some embodiments, the processing unit **6506** is further configured to: after detecting the first user input: transmit (e.g., with transmitting unit **6516**) information that represents the first electronic sticker to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display a corresponding representation of the first electronic sticker in a corresponding location within a corresponding conversation transcript.

[1644] In some embodiments, the processing unit **6506** is further configured to: after transmitting the information that represents the first electronic sticker to the one or more electronic devices: detect (e.g., with detecting unit **6510**) a third user input while a focus selector is at a third location in the messaging user interface that corresponds to the first electronic sticker in the conversation transcript. In response to detecting the third user input, the processing unit **6506** is configured to: change (e.g., with changing unit **6514**) the position of the first electronic sticker in the conversation transcript for a second time; and send (e.g., with sending unit **6518**) information to the one or more electronic devices that correspond to the at least one other user included in the messaging session that the position of the first electronic sticker was changed in the conversation transcript, wherein the one or more electronic devices make corresponding changes to the position of the first electronic sticker within the corresponding conversation transcript.

[1645] In some embodiments, the processing unit **6506** is further configured to: after transmitting the information that represents the first electronic sticker to the one or more electronic devices: detect (e.g., with detecting unit **6510**) a third user input while a focus selector is at a third location in the messaging user interface that corresponds to the first electronic sticker in the conversation transcript; and, in response to detecting the third user input: change (e.g., with changing unit **6514**) the rotation of the first electronic sticker in the conversation transcript for a second time; and send (e.g., with sending unit **6518**) information to the one or more electronic devices that correspond to the at least one other user included in the messaging session that the rotation of the first electronic sticker was changed in the conversation transcript, wherein the one or more electronic devices make

corresponding changes to the rotation of the first electronic sticker within the corresponding conversation transcript.

[1646] In some embodiments, the processing unit **6506** is further configured to: after transmitting information that represents the first electronic sticker to the one or more electronic devices: detect (e.g., with detecting unit **6510**)a third user input while a focus selector is at a third location in the messaging user interface that corresponds to the first electronic sticker in the conversation transcript; and, in response to detecting the third user input: change (e.g., with changing unit **6514**) the size of the first electronic sticker in the conversation transcript for a second time; and send (e.g., with sending unit **6518**) information to the one or more electronic devices that correspond to the at least one other user included in the messaging session that the size of the first electronic sticker was changed in the conversation transcript, wherein the one or more electronic devices make corresponding changes to the size of the first electronic sticker within the corresponding conversation transcript.

[1647] In some embodiments, the processing unit **6506** is further configured to: in response to detecting the first user input, change (e.g., with changing unit **6514**) the position, of the first electronic sticker.

[1648] In some embodiments, the processing unit **6506** is further configured to: in response to detecting the first user input, change (e.g., with changing unit **6514**) the size of the first electronic sticker.

[1649] In some embodiments, the processing unit **6506** is further configured to: in response to detecting the first user input, change (e.g., with changing unit **6514**) the rotation of the first electronic sticker.

[1650] In some embodiments, the size of the first electronic sticker is reduced in response to detecting a pinch gesture that includes movement of a first contact towards a second contact, wherein the pinch gesture started while a focus selector was at a location in the messaging user interface that corresponds to the first electronic sticker.

[1651] In some embodiments, the size of the first electronic sticker is increased in response to detecting a depinch gesture that includes movement of a first contact away from a second contact, wherein the depinch gesture started while a focus selector was at a location in the messaging user interface that corresponds to the first electronic sticker.

[1652] In some embodiments, the size of the first electronic sticker is increased in accordance with a characteristic intensity of a contact made while a focus selector was at a location in the messaging user interface that corresponds to the first electronic sticker.

[1653] In some embodiments, the orientation of the first electronic sticker is changed in response to detecting a rotation gesture that started while a focus selector was at a location in the messaging user interface that corresponds to the first electronic sticker.

[1654] The operations described above with reference to FIGS. **64**A-**64**C are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **65**. For example, detection operations **6404** and **6408** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

Making Payments

[1655] FIG. **66** is a flow diagram illustrating a method **6600** of making payments from a messaging application in accordance with some embodiments. The method **6600** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display, a touch-sensitive surface, and one or more sensors to detect intensities of contacts with the touch-sensitive surface. In some embodiments, the display is a touch-screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **6600** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1656] As described below, the method **6600** provides an intuitive way to make payments from a messaging application. The method reduces the number, extent, and/or nature of the inputs from a user when making payments from a messaging application, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to make payments from a messaging application faster and more efficiently conserves power and increases the time between battery charges.

[1657] The device displays (**6602**) a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript (e.g., displayed in a first area of the display) of a messaging session between a user of the electronic device and at least one other user (e.g., of another electronic device) and a message-input area, wherein each of the other users included in the messaging session has a corresponding avatar (e.g., displayed in a second area of the display). For example, messaging user interface **3500**, in FIG. **40**F, includes conversation transcript **3503**, message-input area **3502**. Conversation transcript **3503** includes messages from participants of a corresponding messaging session, including the user of portable multifunction device **100-1** and other users included in the messaging session. Each of the other users included in the messaging transcript are represented by an avatar (e.g., avatar **4008** for "Mary Todd") displayed in stack of avatars **4002**, in FIG. **40**F.

[1658] While displaying the messaging user interface, the device detects (**6604**) a first user input (e.g., a tap, light press, or deep press gesture by a contact on a touch-sensitive surface) while a focus selector is at a first location in the messaging user interface that corresponds to an avatar of a first other user included in the messaging session, (e.g., detect a gesture by a contact on a touch-sensitive display at

the location of the avatar of the first other user, or detect a gesture by a contact on a touch-sensitive surface while a cursor or other pointer is at the location of the avatar of the first other user). For example, device **100-1** detects an input including contact **4010**, on Mary Todd's avatar **4010**, in FIG. **40**G.

[1659] In response to detecting the first user input, the device displays (**6006**) a menu that contains activatable menu items associated with the first other user overlaid on the messaging user interface, the displayed menu including an activatable menu item for initiating a payment action with the first other user (e.g., a menu item for paying, or requesting payment from, the first other user). For example, in response to detecting an input including an increase in a characteristic intensity of contact **4010**, meeting a predefined intensity threshold, the device displays action menu **3882** that includes activatable action **3884-6** for making a payment to another user (e.g., Mary Todd) included in the messaging session, in FIG. **40**H.

[1660] While displaying the menu that contains activatable menu items associated with the first other user (e.g., action menu **3882** in FIG. **40**J), the device detects (**6008**) a second user input (e.g., by a contact on a touch-sensitive surface, such as an input including contact **4012**, in FIG. **40**J) while a focus selector is at a second location in the messaging user interface that corresponds to the activatable menu item for initiating a payment action with the first other user (e.g., activatable menu action **3884-6** for a payment, in FIG. **40**J). For example, the device detects a gesture by a contact on a touch-sensitive display at the location of the activatable menu item for initiating a payment action with the first other user, or detects a gesture by a contact on a touch-sensitive surface while a cursor or other pointer is at the location of the activatable menu item for initiating a payment action with the first other user.

[1661] In response to detecting the second user input, the device displays (**6610**) a user interface configured to initiate sending of a payment to, and/or requesting a payment from, the first other user. For example, in response to detecting an input including contact **4012** on activatable payment action **3884-6**, in FIG. **40**J, device **100-1** displays payment user interface **4014**, in FIG. **40**K.

[1662] It should be understood that the particular order in which the operations in FIG. **66** have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6400**, **6800**, and **7000**) are also applicable in an analogous manner to method **6600** described above with respect to FIG. **66**. For example, the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, and animations described above with reference to method **6600** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6400**, **6800**, and **7000**). For brevity, these details are not repeated here.

[1663] In accordance with some embodiments, FIG. **67** shows a functional block diagram of an electronic device **6700** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. **67** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[1664] As shown in FIG. **67**, an electronic device **6700** includes a display unit **6702** configured to display user interfaces; a touch-sensitive surface unit **6704** configured to detect contacts; and a processing unit **6706** coupled with the display unit **6702** and the touch-sensitive surface unit **6704**. The processing unit **6706** includes an enabling unit **6708** and a detecting unit **6710**.

[1665] The processing unit **6706** is configured to enable display of (e.g., with enabling unit **6708**) a messaging user interface of a messaging application on the display unit **6702**, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user and a message-input area, wherein each of the other users included in the messaging session has a corresponding avatar. While displaying the messaging user interface, the processing unit **6706** is configured to detect (e.g., with detecting unit **6710**) a first user input while a focus selector is at a first location in the messaging user interface that corresponds to an avatar of a first other user included in the messaging session. In response to detecting the first user input, enable display of (e.g., with enabling unit **6708**) a menu that contains activatable menu items associated with the first other user overlaid on the messaging user interface, the displayed menu including an activatable menu item for initiating a payment action with the first other user. While displaying the menu that contains activatable menu items associated with the first other user, detect (e.g., with detecting unit **6710**) a second user input while a focus selector is at a second location in the messaging user interface that corresponds to the activatable menu item for initiating a payment action with the first other user. In response to detecting the second user input, enable display of (e.g., with enabling unit **6708**) a user interface configured to initiate sending of a payment to, and/or requesting a payment from, the first other user.

[1666] The operations described above with reference to FIG. **66** are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **67**. For example, detection operations **6604** and **6608** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the

device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

Interacting with Avatars in a Group Messaging Session

[1667] FIGS. **68**A-**68**B are flow diagrams illustrating a method **6800** of interacting with a single user included in a group messaging session in accordance with some embodiments. The method **6800** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display, a touch-sensitive surface, and one or more sensors to detect intensities of contacts with the touch-sensitive surface. In some embodiments, the display is a touch-screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **6800** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1668] As described below, the method **6800** provides an intuitive way to interact with a single user included in a group messaging session. The method reduces the number, extent, and/or nature of the inputs from a user when interacting with a single user included in a group messaging session, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to interact with a single user included in a group messaging session faster and more efficiently conserves power and increases the time between battery charges.

[1669] The device displays (**6802**) a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript (e.g., displayed in a first area of the display) of a messaging session between a user of the electronic device and a plurality of other users (e.g., of respective other electronic devices), a message-input area, and a plurality of avatars, each respective avatar in the plurality of avatars corresponding to a respective other user in the plurality of other users included in the messaging session, wherein the plurality of avatars are displayed as a stack of (e.g., overlapping) avatars, with a first avatar in the plurality of avatars displayed on the top of the stack of avatars. For example, messaging user interface **3500**, in FIG. **40**S, includes conversation transcript **3503** and message-input area **3502**. Conversation transcript **3503** includes messages from participants of a corresponding messaging session, including the user of portable multifunction device **100-1** and other users included in the messaging session. Each of the other users included in the messaging transcript are represented by an avatar (e.g., avatar **3510** for "Abe") displayed on top of stack of avatars **4002**, in FIG. **40**S.

[1670] While displaying the messaging user interface, the device detects an input by a first contact on the touch-sensitive surface while a focus selector is at a first location in the messaging user interface that corresponds to the first avatar (e.g., detect a gesture by a contact on a touch-sensitive display at the location of the first avatar, or detect a gesture by a contact on a touch-sensitive surface while a cursor or other pointer is at the location of the first avatar). For example, device **100-1** detects an input including contact **4030** on Abe's avatar (e.g., displayed on top of stack of avatars **4002**), in FIG. **40**S. In another example, device **100-1** detects an input including contact **4038** on Mary Todd's avatar **4008**, in FIG. **40**U.

[1671] In response to detecting the input by the first contact, in accordance with a determination that the input meets menu-activation-criteria, wherein the menu-activation-criteria require that a characteristic intensity of the contact on the touch-sensitive surface meet a respective intensity threshold in order for the menu-activation criteria to be met, the device displays (**6806**) a menu that contains activatable menu items associated with the first avatar overlaid on the messaging user interface. For example, in response to detecting an increase in a characteristic intensity of contact **4038** on Mary Todd's avatar **4008**, meeting a predetermined intensity threshold (e.g., IT_L or IT_D), between FIGS. **40**U and **40**V, device **100-1** displays action menu **3882**, including actions **3884** for directly interacting with Mary Todd (e.g., interacting only with Mary Todd), in FIG. **40**V.

[1672] In response to detecting the input by the first contact, in accordance with a determination that the input meets avatar-spreading-criteria, wherein the avatar-spreading-criteria do not require that a characteristic intensity of the contact on the touchscreen meet the respective intensity threshold in order for the selection criteria to be met, the device displays (**6906**) the plurality of avatars in an array (e.g., a substantially or completely non-overlapping array). For example, in response to detecting an input including contact **4030** on Abe's avatar **3510**, in FIG. **40**S, where a characteristic intensity of contact **4030** does not meet a predetermined intensity threshold (e.g., IT_L or IT_D), device **100-1** displays an array of avatars in avatar stack **4002**—e.g., Abe's avatar **3510**, Mary Todd's avatar **4008**, Chuck's avatar **4032**, Isaac's avatar **4034**, and Edwin's avatar **4036**—in FIG. **40**T.

[1673] In some embodiments, in accordance with a determination that a characteristic (e.g., a maximum) intensity of the first contact met a predefined intensity threshold (e.g., was between a first intensity threshold and a second intensity threshold), the device replaces display of the first avatar on top of the stack of avatars with display of a second avatar in the plurality of avatars on top of the stack of avatars. For example, in response to detecting an increase in a characteristic intensity of contact **4006** on Abe's avatar **3510**, meeting a predetermined intensity threshold (e.g., IT_L or IT_D), between FIGS. **40**D and **40**E, device **100-1** cycles (e.g., switches or shuffles) stack of avatars **4002** to display Mary Todd's avatar **4008** on top of stack of avatars **4002** in FIGS. **40**E-**40**F (e.g., Mary Todd's avatar **4008** replaces Abe's avatar **3510** on top of stack of avatars **4002**).

[1674] In some embodiments, in accordance with a determination that a characteristic (e.g., a maximum) intensity of the first contact did not meet a predetermined intensity threshold (e.g., was between the second intensity threshold and a third intensity threshold), the device displays a menu that contains activatable menu items associated with the first avatar overlaid on the messaging user interface. For example, in response to detecting an input including contact

4004 on Abe's avatar **3510**, in FIG. **40**B, where a characteristic intensity of contact **4004** does not meet a predetermined intensity threshold (e.g., IT_L or IT_D), device **100-1** displays action menu **3882**, including actions **3884** for directly interacting with Abe (e.g., interacting only with Abe), in FIG. **40**C.

[1675] In some embodiments, the second intensity threshold is above the first intensity threshold and the third intensity threshold is above the second intensity threshold (e.g., tap to cycle through the avatars and light press or deep press to call up a quick action menu for the avatar at the top of the stack).

[1676] In some embodiments, the second intensity threshold is below the first intensity threshold and the third intensity threshold is below the second intensity threshold (e.g., deep press or light press to cycle through the avatars and tap to call up the quick action menu for the avatar at the top of the stack).

[1677] In some embodiments, the avatar-spreading-criteria are met (**6810**) upon detection of a tap gesture on the touch-sensitive surface. For example, avatars **3510**, **4008**, **4032**, **4034**, and **4036**, in avatar stack **4002**, displayed in FIG. **40**S, are displayed as a spread array (e.g., a substantially or completely non-overlapping array), in FIG. **40**T, in response to detecting a tap gesture including contact **4030** on Abe's avatar **3510**, in FIG. **40**S.

[1678] In some embodiments, the menu that contains activatable menu items associated with the first avatar (e.g., action menu **3882** in FIG. **40**V) includes (**6812**) a menu item that when activated initiates a canvas for sharing digital drawings with the other user (e.g., digital touch action **3884-5** in FIG. **40**V).

[1679] In some embodiments, the menu that contains activatable menu items associated with the first avatar (e.g., action menu **3882** in FIG. **40**V) includes (**6814**) a menu item that when activated initiates messaging with only the first other user (e.g., message action **3884-3** in FIG. **40**V).

[1680] For example, in some embodiments, selecting a messaging menu item (e.g., activatable action **3884-3**) causes the electronic device to display a private messaging user interface between the user of the electronic device and the first other user. For example, in response to detecting an input including contact **3886** on activatable message action **3884-3**, in FIG. **38**AY, while messaging user interface **3500** is displaying conversation transcript **3503** corresponding to a messaging session between the user of device **100-1** (e.g., "Andrew") and a plurality of other users, each represented by an avatar in the stack of avatars **4002**, in FIG. **38**AY, device **100-1** replaces display of conversation transcript **3503**, in FIG. **38**AY, with conversation transcript **3700**, corresponding to a messaging session between only Abe and Andrew, in FIG. **38**AZ.

[1681] In some embodiments, the menu that contains activatable menu items associated with the first avatar (e.g., action menu **3882** in FIG. **40**V) includes (**6816**) a menu item that when activated initiates an email with the first other user (e.g., mail action **3884-4** in FIG. **40**V).

[1682] In some embodiments, the menu that contains activatable menu items associated with the first avatar (e.g., action menu **3882** in FIG. **40**V) includes (**6818**) a menu item that when activated initiates a call with the first other user (e.g., call action **3884-1** in FIG. **40**V).

[1683] In some embodiments, the menu that contains activatable menu items associated with the first avatar (e.g., action menu **3882** in FIG. **40**V) includes (**6820**) a menu item that when activated initiates a video conference with the first other user (e.g., video call action **3884-2** in FIG. **40**V).

[1684] In some embodiments, the menu that contains activatable menu items associated with the first avatar (e.g., action menu **3882** in FIG. **40**V) includes (**6822**) a menu item that when activated initiates a payment action with the first other user (e.g., payment action **3884-6** in FIG. **40**V).

[1685] It should be understood that the particular order in which the operations in FIGS. **68**A-**68**B have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6400**, **6600**, and **7000**) are also applicable in an analogous manner to method **6800** described above with respect to FIGS. **68**A-**68**B. For example, the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, and animations described above with reference to method **6800** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6400**, **6600**, and **7000**). For brevity, these details are not repeated here.

[1686] In accordance with some embodiments, FIG. **69** shows a functional block diagram of an electronic device **6900** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. **69** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[1687] As shown in FIG. **69**, an electronic device **6900** includes a display unit **6902** configured to display user interfaces; a touch-sensitive surface unit **6904** configured to detect contacts; and a processing unit **6906** coupled with the display unit **6902** and the touch-sensitive surface unit **6904**. The processing unit **6906** including: an enabling unit **6908** and detecting unit **6910**.

[1688] The processing unit **6906** is configured to: enable display of (e.g., with enabling unit **6908**) a messaging user interface of a messaging application on the display unit **6902**, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and a plurality of other users, a message-input area, and a plurality of avatars, each respective avatar in the plurality of avatars corresponding to a respective other user in the plurality of other users included in the messaging session, wherein the plurality of avatars are displayed as a

stack of avatars, with a first avatar in the plurality of avatars displayed on the top of the stack of avatars. While displaying the messaging user interface, the processing unit **6906** is configured to detect (e.g., with detecting unit **6910**) an input by a first contact on the touch-sensitive surface unit **6904** while a focus selector is at a first location in the messaging user interface that corresponds to the first avatar. In response to detecting the input by the first contact: in accordance with a determination that the input meets menu-activation-criteria, wherein the menu-activation-criteria require that a characteristic intensity of the contact on the touch-sensitive surface unit **6904** meet a respective intensity threshold in order for the menu-activation criteria to be met, the processing unit **6906** is configured to enable display of (e.g., with enabling unit **6908**) a menu that contains activatable menu items associated with the first avatar overlaid on the messaging user interface. In accordance with a determination that the input meets avatar-spreading-criteria, wherein the avatar-spreading-criteria do not require that a characteristic intensity of the contact on the touchscreen meet the respective intensity threshold in order for the selection criteria to be met, the processing unit **6906** is configured to enable display of (e.g., with enabling unit **6908**) the plurality of avatars in an array.

[1689] In some embodiments, the avatar-spreading-criteria are met upon detection of a tap gesture on the touch-sensitive surface unit.

[1690] In some embodiments, the menu that contains activatable menu items associated with the first avatar includes a menu item that when activated initiates a canvas for sharing digital drawings with the other user.

[1691] In some embodiments, the menu that contains activatable menu items associated with the first avatar includes a menu item that when activated initiates messaging with only the first other user,

[1692] In some embodiments, the menu that contains activatable menu items associated with the first avatar includes a menu item that when activated initiates an email with the first other user,

[1693] In some embodiments, the menu that contains activatable menu items associated with the first avatar includes a menu item that when activated initiates a call with the first other user,

[1694] In some embodiments, the menu that contains activatable menu items associated with the first avatar includes a menu item that when activated initiates a video conference with the first other user, and/or

[1695] In some embodiments, the menu that contains activatable menu items associated with the first avatar includes a menu item that when activated initiates a payment action with the first other user.

[1696] The operations described above with reference to FIGS. **68**A-**68**B are, optionally, implemented by components depicted in FIGS. **1**A-**1**B or FIG. **69**. For example, detection operation **6804** and display operation **6806** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

Making Suggestions in a Messaging Session

[1697] FIGS. **70**A-**70**B are flow diagrams illustrating a method **7000** of displaying additional information in a messaging session in accordance with some embodiments. The method **7000** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display, a touch-sensitive surface, and one or more sensors to detect intensities of contacts with the touch-sensitive surface. In some embodiments, the display is a touch-screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **7000** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1698] As described below, the method **7000** provides an intuitive way to display additional information in a messaging session. The method reduces the number, extent, and/or nature of the inputs from a user when displaying additional information in a messaging session, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to display additional information in a messaging session faster and more efficiently conserves power and increases the time between battery charges.

[1699] The device displays (**7002**) a messaging user interface of a messaging application on the display, the messaging user interface including a conversation transcript (e.g., displayed in a first area of the display) of a messaging session between a user of the electronic device and at least one other user (e.g., of another electronic device), and a message-input area. For example, messaging user interface **3500**, in FIGS. **41**A and **41**C, include conversation transcript **3503** and message-input area **3502**.

[1700] While displaying the messaging user interface, the device receives (**7004**) a first message within the messaging session from an (e.g., second) electronic device that corresponds to another user included in the messaging session. For example device **100-1** receives message **4102** from Mary Todd, in FIG. **41**A.

[1701] In response to receiving the first message, the device (**7006**): displays the first message within a first message region (e.g., bubble) in the conversation transcript on the display (e.g., message **4102** is displayed within a message region in transcript **3503** in FIG. **41**A),

[1702] In response to receiving the first message, the device (**7006**): detects, in the first message, a word or phrase associated with additional content available on the Internet (e.g., information about a detected business/restaurant, music, movie, television show, current event, public figure, politician, celebrity, university, athlete, sporting event, or

sports league/team). For example, device **100-1** recognizes the phrase "Meteorite Catcher" **4101** as the title of a movie, in FIG. **41**A. In some embodiments, the device uses a data detector stored in the memory of the device and/or stored remotely. In some embodiments, the device compares words/phrases in received messages to a predefined list of words and/or phrases stored within the memory or the device and/or stored remotely.

[1703] In response to detecting the word or phrase associated with additional content available on the internet, the device (**7006**): displays proximate to the first message region (e.g., bubble; for example, directly above or below the message), a selectable indication that additional content associated with the word or phrase is available (e.g., selectable text relating to the additional content, such as "see local show times," "make a reservation now"). For example, in response to recognizing the phrase "Meteorite Catcher" **4101** as the title of a movie, device **100-1** displays selectable indication **4104** ("See movie info") below message **4102**, in FIG. **41**A.

[1704] In some embodiments, the word or phrase associated with additional content available is associated (**7008**) with a movie (e.g., a movie title, a distinctive or context-identifiable character name from the movie, or a famous line from a movie, such as, "show me the money"), and the additional content includes biographical data about the movie (e.g., the name of an actor/actress, the length of the move, the year the movie was released, or the studio that produced and/or distributed the movie), information on local performances of the movie (e.g., show times, theatre information, or a link to purchase tickets), ratings information for the movie (e.g., critic or user-contributed ratings, individual or compiled), and/or multi-media content about the movie (e.g., movie clips, streaming performances, or audio clips).

[1705] In some embodiments, the word or phrase associated with additional content available is associated (**7010**) with a television show (e.g., a show title, a distinctive or context-identifiable character name from the show, or an identifiable catch phrase, such as, "don't have a cow, man"), and the additional content includes biographical data about the show (e.g., the name of an actor/actress, the length of the series, information on the network, channel, and/or time the show is broadcasted; or the network that produced the show), ratings information about the show (e.g., critic or user-contributed ratings, individual or compiled), and/or multi-media content about the show (e.g., show clips, streaming performances, or audio clips).

[1706] In some embodiments, the word or phrase associated with additional content available is associated (**7012**) with a song or album (e.g., a song or album title, an artist name, or an identifiable line from the song or album, such as, "bye, bye, Miss American Pie"), and the additional content includes biographical data about the song or album (e.g., the name of an artist, composer, or producer of the song or album, the length of the song or album, songs on the album, the year the song or album was released, or the studio that produced and/or distributed the song or album), ratings information about the song or album (e.g., critic or user-contributed ratings, individual or compiled), and/or multi-media content about the song or album (e.g., audio clips or streaming performances).

[1707] In some embodiments, the word or phrase associated with additional content available is associated (**7014**) with a business (e.g., a particular type of business, such as restaurant, store, salon, or golf course, a business name, a distinctive or context-identifiable employee/owner name, or an identifiable slogan, such as, "pizza, pizza"), and the additional content includes biographical data about the business (e.g., an address, local street map, phone number, email address, or business hours), ratings information about the business (e.g., critic or user-contributed ratings (individual or compiled), and/or interactive content about the business (e.g., a website, an interactive ordering platform, or an interactive application associated with the business). In some embodiments, the business is a particular business, e.g., a specific restaurant. In some embodiments, the business is a class of businesses, e.g., a restaurant.

[1708] In some embodiments, the device (**7016**) detects an input that activates the selectable indication (e.g., detecting a tap gesture on the selectable indication) and, in response to detecting the input that activates the selectable indication, displaying additional content within the conversation transcript (e.g., displaying a drop-down window below the message bubble with additional content from the Internet). For example, in response to detecting an input that includes contact **4106** on selectable indication **4104**, in FIG. **41**B, device **100-1** displays area **4108** including additional information (e.g., movie poster **4110** and biographical information **4112**) about the "Meteorite Catcher" movie available on the Internet (e.g., device **100-1** displays selected Internet search results relating to the detected phrase).

[1709] In some embodiments, the additional content includes a link to a web content associated with the detected word or phrase (e.g., a link to a movie website or a link to a digital video that may be viewed and/or posted within the conversation transcript).

[1710] In some embodiments, the activatable indication is a stylized display of the recognized word or phrase within display of the received message (e.g., highlighting or coloring of the recognized word or phrase).

[1711] In some embodiments, the device detects in the first message, a word or phrase associated with additional content available on the Internet (e.g., information about a detected business/restaurant, music, movie, television show, current event, public figure, politician, celebrity, university, athlete, sporting event, or sports league/team). For example, device **100-1** recognizes the phrase "Astron Omer" **4103**, in received message **4114**, as the name of an actor, in FIG. **41**D. In some embodiments, the device uses a data detector stored in the memory of the device and/or stored remotely. In some embodiments, the device compares words/phrases in received messages to a predefined list of words and/or phrases stored within the memory or the device and/or stored remotely.

[1712] In some embodiments, in response to detecting the word or phrase associated with additional content available on the internet, the device stylizes the word or phrase within the message region and enables activation of the word or phrase in the message region. For example, in response to recognizing the phrase "Astron Omer" **4103** as the name of an actor, device **100-1** displays highlighting **4116** of "Astron Omer" within message **4114**, in FIG. **41**D.

[1713] In some embodiments, the device detects an input that activates the stylized word or phrase in the message region (e.g., detecting a tap gesture on a highlighted word or phrase) and, in response, replaces display of the messaging user interface with display of an internet (and/or memory) search user interface for an internet search of the detected

word or phrase, including a plurality of (e.g., categorized) search results. For example, in response to detecting an input, including contact **4118** on stylized phrase "Astron Omer," in FIG. **41**E, device **100-1** replaces display of messaging user interface with display of internet search user interface **3661**, in FIG. **41**F, for an internet search of detected phrase "Astron Omer" **4103**. Internet search user interface **3661** including a plurality of categorized search results relating to phrase "Astron Omer" **4103** (e.g., news articles **3664**, **3678**, **3680** and movie trailers **3670**, **3682**, and **3684**).

[1714] In some embodiments, the device detects an input on a first search result in the plurality of search results in the Internet (and/or memory) search user interface and, in response, replaces display of the Internet (and/or memory) search user interface with the messaging user interface, displays a representation of the first search result in the conversation transcript of the messaging user interface, and transmits a representation of the first search result to the one or more electronic devices associated with other users of the messaging session (e.g., posts the search result to the messaging session).

[1715] For example, device **100-1** detects an input including contact **4120** on search result **3670**, in FIG. **41**G, and, in response, replaces Internet search interface **3661** with messaging user interface **3500**, including conversation transcript **3503** displaying representation of search result **3670**.

[1716] It should be understood that the particular order in which the operations in FIGS. **70**A-**70**B have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6400**, **6600**, and **6800**) are also applicable in an analogous manner to method **7000** described above with respect to FIGS. **70**A-**70**B. For example, the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, and animations described above with reference to method **7000** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein (e.g., methods **600**, **800**, **1000**, **1200**, **1400**, **1600**, **1800**, **2100**, **2400**, **2600**, **2800**, **3100**, **3300**, **4200**, **4400**, **4600**, **4800**, **50000**, **52000**, **5400**, **5600**, **5800**, **6000**, **6200**, **6400**, **6600**, and **6800**). For brevity, these details are not repeated here.

[1717] In accordance with some embodiments, FIG. **71** shows a functional block diagram of an electronic device **7100** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. **71** are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

[1718] As shown in FIG. **71**, an electronic device **7100** includes a display unit **7102** configured to display user interfaces; a touch-sensitive surface unit **7104** configured to detect contacts; and a processing unit **7106** coupled with the display unit **7102** and the touch-sensitive surface unit **7104**, the processing unit **7106** including a detecting unit **7108**, a receiving unit **7110** and a detecting unit **7112**.

[1719] The processing unit **7106** is configured to enable display of (e.g., with enabling unit **7108**) a messaging user interface of a messaging application on the display unit **7102**, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, and a message-input area. While displaying the messaging user interface, the processing unit **7106** is configured to receive (e.g., with receiving unit **7110**) a first message within the messaging session from an electronic device that corresponds to another user included in the messaging session. In response to receiving the first message: the processing unit **7106** is configured to enable display of (e.g., with enabling unit **7108**) the first message within a first message region in the conversation transcript on the display unit **7102**. The processing unit **7106** is configured to detect (e.g., with detecting unit **7112**), in the first message, a word or phrase associated with additional content available on the Internet. In response to detecting the word or phrase associated with additional content available on the internet, the processing unit **7106** is configured to enable display of (e.g., with enabling unit **7108**), proximate to the first message region, a selectable indication that additional content associated with the word or phrase is available.

[1720] In some embodiments, the processing unit **7106** is further configured to: detect (e.g., with detecting unit **7112**) an input that activates the selectable indication; in response to detecting the input that activates the selectable indication, enable display of (e.g., with enabling unit **7108**) additional content within the conversation transcript.

[1721] In some embodiments, the word or phrase associated with additional content available is associated with a movie, and the additional content includes biographical data about the movie, information on local performances of the movie, ratings information for the movie, and/or multimedia content about the movie.

[1722] In some embodiments, the word or phrase associated with additional content available is associated with a television show, and the additional content includes biographical data about the show, ratings information about the show, and/or multi-media content about the show.

[1723] In some embodiments, the word or phrase associated with additional content available is associated with a song or album, and the additional content includes biographical data about the song or album, ratings information about the song or album, and/or multi-media content about the song or album.

[1724] In some embodiments, the word or phrase associated with additional content available is associated with a business, and the additional content includes biographical data about the business, ratings information about the business, and/or interactive content about the business.

[1725] The operations described above with reference to FIGS. **70**A-**70**B are, optionally, implemented by compo-

nents depicted in FIGS. **1A-1B** or FIG. **71**. For example, detection operation **7016** is, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1A-1B**.

Navigation Between Applications in Messages

[1726] FIGS. **72A-72R** illustrate exemplary user interfaces for navigation between applications using an application user interface displayed in a messaging user interface, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIGS. **73A-73D**. For convenience of explanation, some of the embodiments will be discussed with reference to operations performed on a device with a touch-sensitive display system **112**. In such embodiments, the focus selector is, optionally: a respective finger or stylus contact, a representative point corresponding to a finger or stylus contact (e.g., a centroid of a respective contact or a point associated with a respective contact), or a centroid of two or more contacts detected on the touch-sensitive display system **112**. However, analogous operations are, optionally, performed on a device with a display **450** and a separate touch-sensitive surface **451** in response to detecting the contacts on the touch-sensitive surface **451** while displaying the user interfaces shown in the figures on the display **450**, along with a focus selector.

[1727] FIGS. **72A-72FM** illustrate exemplary user interface **7200** for a messaging application. In FIG. **72A**, user interface **7200** includes conversation transcript **7202**, message-input area **7204**, activatable digital image affordance **7206**, application affordance **7208**, and application area **7210**. Conversation transcript **7202** includes messages from participants of a corresponding messaging session, including the user of portable multifunction device **100** and another user included in the messaging session. The other user included in the messaging transcript is represented by an avatar (e.g., avatar **7218** for "Abe"). Message **7216** is a message received by device **100** from a remote device operated by a user identified as Abe and message **7214** is a message transmitted by device **100** to the remote device operated by Abe. In FIG. **72A**, application area **7210** displays a keyboard **7212**.

[1728] In FIG. **72B**, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to application affordance **7208**, as indicated by focus selector **7220**. In response to the input, keyboard **7212**, shown in the application area **7210** in FIG. **72B**, is replaced by an application input area **7222** and an application-selection area **7224**, as shown in FIG. **72C**. From FIG. **72B** to FIG. **72C**, the appearance of application affordance **7208** has changed to indicate that an application mode is active. Application-selection area **7224** includes application-configuration affordance **7226** and application-selection affordances **7228** (for selecting a tic-tac-toe application), **7230** (for the currently displayed music application), and **7232** (for selecting a sticker application). Application-configuration affordance **7226** is also referred to herein as an application-selection affordance. Application input area **7222** includes application objects **7234**, **7236**, **7238**, and **7240** (e.g., for selecting music track information to transmit to a remote device).

[1729] In FIGS. **72D-72G**, an input (e.g., a scroll input) by a contact on touch screen **112** is detected, as indicated by focus selector **7242**. As the focus selector **7242** moves along a path indicated by arrow **7244** from a first location on application-selection area **7224** (as shown in FIG. **72D**) to a second location on application-selection area **7224** (as shown in FIG. **72E**), the size of application selection objects **7228**, **7230**, and **7232** increases, and application-configuration affordance **7226** is no longer displayed in FIG. **72E**. As the focus selector **7242** continues to move across application-selection area **7224**, as shown in FIGS. **72E-72F**, application selection-affordance **7228** is no longer displayed and application-selection affordance **7246** is revealed. When the contact indicated by focus selector **7242** lifts off of touch screen **112**, the sizes of application-selection affordances are decreased, as shown in FIGS. **72F-72G**, and an additional application-selection affordance **7248** is revealed in FIG. **72G**.

[1730] In FIG. **72H**, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to application-selection affordance **7246**, as indicated by focus selector **7250**. In response to the input, application objects **7234-7240** for a music application, displayed in in application input area **7222** in FIG. **72H**, are replaced by application objects **7252** and **7254** (e.g., for selecting reservation information to transmit to a remote device) of a reservations application, as shown in FIG. **72I**.

[1731] FIGS. **72J-72L** illustrate an input (e.g., an upward drag input) by a contact on touch screen **112**, as indicated by focus selector **7256**. The focus selector **7256** moves along a path indicated by arrow **7258** from a first location that corresponds to chevron **7260**. The input drags the chevron **7260** upward, causing application input area **7222** to expand over conversation transcript **7202** as shown in FIGS. **72J-72K**, such that the application input area **7222** covers conversation transcript **7202** in FIG. **72L**. FIGS. **72M-72N** illustrate an input (e.g., an upward swipe input) by a contact on touch screen **112**, as indicated by focus selector **7262**. The input drags the chevron **7260** downward, causing the length of application input area **7222** to decrease to its original size.

[1732] In FIG. **72O**, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to application affordance **7208**, as indicated by focus selector **7264**. In response to the input, application input area **7222** and application-selection area **7224**, shown in the application area **7210** in FIG. **72O**, are replaced by keyboard **7212**, as shown in FIG. **72P**.

[1733] In FIG. **72**Q, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to application affordance **7208**, as indicated by focus selector **7266**. In response to the input, keyboard **7212**, shown in the application area **7210** in FIG. **72**Q, is replaced by application input area **7222** and application-selection area **7224**. In FIG. **72**O, application-selection affordances **7230**, **7232**, **7246**, and **7248** are displayed in application-selection area **7224**. The transition to displaying keyboard **7212**, shown in FIGS. **72**O-**72**P, followed by a transition to displaying application input area **7222** and application-selection area **7224**, shown in FIGS. **72**Q-**72**R, causes the originally displayed set of application selection affordances **7226**, **7228**, **7230** and **7232** to be redisplayed in application-selection area **7224** in FIG. **72**R.

Application Management Interfaces in Messages

[1734] FIGS. **72**S-**72**AO illustrate exemplary user interfaces for managing applications used within a messaging application, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIGS. **74**A-**74**D. For convenience of explanation, some of the embodiments will be discussed with reference to operations performed on a device with a touch-sensitive display system **112**. In such embodiments, the focus selector is, optionally: a respective finger or stylus contact, a representative point corresponding to a finger or stylus contact (e.g., a centroid of a respective contact or a point associated with a respective contact), or a centroid of two or more contacts detected on the touch-sensitive display system **112**. However, analogous operations are, optionally, performed on a device with a display **450** and a separate touch-sensitive surface **451** in response to detecting the contacts on the touch-sensitive surface **451** while displaying the user interfaces shown in the figures on the display **450**, along with a focus selector.

[1735] In FIG. **72**S, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to application-configuration affordance **7226**, as indicated by focus selector **7268**. In response to the input, a messages application installation/deletion interface **7270** is displayed, as shown in FIG. **72**T. Messages application installation/deletion interface **7270** includes application management listings for applications installed on device **100**, including application management listing **7272** that corresponds to the tic-tac-toe application represented by application-selection affordance **7228**, application management listing **7274** that corresponds to the music application represented by application-selection affordance **7230**, application management listing **7276** that corresponds to the sticker application represented by application-selection affordance **7232**, application management listing **7278** that corresponds to the reservation application represented by application-selection affordance **7246**, application management listing **7280** that corresponds to the pizza builder application represented by application-selection affordance **7248**, and additional application management listings **7282** and **7284** that correspond to selectable applications in the messaging user interface **7200**.

[1736] In FIG. **72**U, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to a deletion affordance **7273** of application listing **7272**, as indicated by focus selector **7288**. In response to the input (or in response to a second input, such as another tap input to confirm the deletion), a messaging application component of the tic-tac-toe application that corresponds to application listing **7272** is deleted, as shown in FIG. **72**V. In some embodiments, other application components of the tic-tac-toe application that corresponds to application listing **7272**, such as a watch component and/or a content sharing component, are also deleted. When the tic-tac-toe application component has been deleted, the tic-tac-toe application-selection affordance **7228** is no longer displayed in application-selection area **7224**, as shown in FIG. **72**AO.

[1737] In FIG. **72**W, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to search input area **7290** of messages application installation/deletion interface **7270**, as indicated by focus selector **7292**. In response to the input, a search interface area **7294** and keyboard **7212** are displayed in messages application installation/deletion interface **7270**, as indicated in FIG. **72**X.

[1738] In FIG. **72**Y, search input **7296** has been entered in search input area **7290**, and an input by a contact on touch screen **112** is detected at a location that corresponds to search affordance **7298**, as indicated by focus selector **72100**. In response to the input by the contact, search results **72102** (for a tiny transit application) and **72104** (for a transit maps application) are displayed in search interface area **7294**, as shown in FIG. **72**Z.

[1739] In FIG. **72**Z, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to installation affordance **72106**, as indicated by focus selector **72108**. In response to the input (or in response to a second input, such as another tap input to confirm the installation), a tiny transit application for messages is installed, messages application installation/deletion interface **7270** is redisplayed, and application management listing **72110** for the tiny transit application for messages is displayed in messages application installation/deletion interface **7270**, as shown in FIG. **72**AA.

[1740] In FIG. **72**AB, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to affordance **72112** for displaying an application modification interface **72116**, as indicated by focus selector **72114**. In response to the input, application modification interface **72116** is displayed, as shown in FIG. **72**AC. Application modification interface **72116** displays toggle controls (e.g., toggle control **72118**) and rearrangement controls (e.g., rearrangement control **72124**) for messaging applications installed on device **100**.

[1741] In FIG. **72**AD, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to toggle control **72118** for application management listing **7276**, as indicated by focus selector **72122**. In response to the input, a sticker application for messages that corresponds to the stickers application management listing **7276** is adjusted from a displayed state to a hidden state (e.g., as indicated by the altered appearance of toggle control **72118** in FIG. **72**AE. When the state of the sticker application for messages is a hidden state, the sticker application-selection affordance **7232** that corresponds to the sticker application for messages ceases to be displayed in application-selection area **7224** (e.g., as shown in FIG. **72**AO).

[1742] In FIG. **72**AF, a rearrangement input (e.g., a drag input) is detected by a contact on touch screen **112**, as indicated by focus selector **72124**. The rearrangement input

selects the application management listing **72110** (e.g., after the focus selector **72124** remains proximate to a location that corresponds to rearrangement control **72120** for a duration of time increased beyond a threshold duration) and drags the application management listing **72110** upward to a new position, as shown at FIGS. **72**AF to **72**AJ. In FIG. **72**AK, the contact indicated by focus selector **72124** lifts off of the touch screen. In response to the lift off of the contact from the touch screen **112**, in accordance with a determination that the rearrangement input met rearrangement criteria (e.g., movement of focus selector **72124** increased beyond a threshold distance), application management listing **72110** is dropped in the new position. As a result of the rearrangement input, an application-selection affordance **72126** for the tiny transit application that corresponds to application management listing **72110** is displayed in application-selection area **7224** between application selection affordance **7230** for the music application and application selection affordance **72128** for the reservations application (see, e.g., FIG. **72**AO).

[1743] In FIG. **72**AL, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to affordance **72130** for exiting application modification interface **72116**, as indicated by focus selector **72132**. In response to the input, application installation/deletion interface **7270** is redisplayed, as shown in FIG. **72**AM.

[1744] In FIG. **72**AN, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to affordance **72134** for exiting application installation/deletion interface **7270**, as indicated by focus selector **72136**. In response to the input, conversation transcript **7202** and application area **7210** are redisplayed in messaging user interface **7200**, as shown in FIG. **72**AO.

Message Translation

[1745] FIGS. **72**AP-**72**DI illustrate exemplary user interfaces for translating message content in a messaging application, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIGS. **75**A-**75**D and **76**A-**76**C. For convenience of explanation, some of the embodiments will be discussed with reference to operations performed on a device with a touch-sensitive display system **112**. In such embodiments, the focus selector is, optionally: a respective finger or stylus contact, a representative point corresponding to a finger or stylus contact (e.g., a centroid of a respective contact or a point associated with a respective contact), or a centroid of two or more contacts detected on the touch-sensitive display system **112**. However, analogous operations are, optionally, performed on a device with a display **450** and a separate touch-sensitive surface **451** in response to detecting the contacts on the touch-sensitive surface **451** while displaying the user interfaces shown in the figures on the display **450**, along with a focus selector.

[1746] In conversation transcript **7202** of the messaging user interface **7200** shown in FIG. **72**AP, message bubbles **72138**, **72142**, and **72144** have message text in a language that matches the native language setting of device **100**, and message bubble **72140** displays a message received by device **100** that includes foreign language text **72146**.

[1747] In FIG. **72**AQ, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to message bubble **72140**, as indicated by focus selector **72148**. In response to the input, foreign language text **72146** has been replaced by translation **72150** of the foreign language text in message bubble **72140**, as shown in FIG. **72**AR.

[1748] In FIG. **72**AS, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to message bubble **72140**, as indicated by focus selector **72152**. In response to the input, translation **72150** has been replaced by the original foreign language text **72146** in message bubble **72140**, as shown in FIG. **72**AT.

[1749] In FIG. **72**AU, an input (e.g., a press input) by a contact on touch screen **112** is detected at a location that corresponds to message bubble **72140**, as indicated by focus selector **72154**. In FIG. **72**AV, a characteristic intensity of the contact has increased above a deep press intensity threshold level IT_D as indicated by intensity level meter **72155**. In response to the input, a menu **72156** is displayed. Menu **72156** includes a translate option as indicated at **72158**. In FIG. **72**AW, menu **72156** remains displayed after the contact indicated by focus selector **72154** lifts off of touch screen **112**.

[1750] In FIG. **72**AX, an input (e.g., a tap input) by a contact on touch screen **112** is detected **72155** at a location that corresponds to translate option **72158**, as indicated by focus selector **72160**. In response to the input, foreign language text **72146** has been replaced by translation **72150** of the foreign language text in message bubble **72140**, as shown in FIG. **72**AY. In FIG. **72**AY, the state of the translate option **72158** in menu **72156** has toggled to an "Undo Translate" state from the "Translate" state shown in FIG. **72**AX.

[1751] In FIG. **72**AZ, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location shown by focus selector **72162** (e.g., a location that does not correspond to any of the affordances (e.g., messages, platters, and/or menus) displayed in messaging user interface **7200**). In response to the input, menu **72156** ceases to be displayed, as shown in FIG. **72**BA.

[1752] In FIG. **72**BB, an input (e.g., a press input) by a contact on touch screen **112** is detected at a location that corresponds to message bubble **72140**, as indicated by focus selector **72164**. In FIG. **72**BC, a characteristic intensity of the contact has increased above a deep press intensity threshold level IT_D as indicated by intensity level meter **72155**. In response to the input, menu **72156** is displayed with translate option **72158** in an "Undo Translate" state. In FIG. **72**BD, menu **72156** remains displayed after the contact indicated by focus selector **72164** lifts off of touch screen **112**.

[1753] In FIG. **72**BE, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to translate option **72158**, as indicated by focus selector **72166**. In response to the input, translation **72150** has been replaced by foreign language text **72146** in message bubble **72140**, as shown in FIG. **72**BF. In FIG. **72**BF, the state of the translate option **72158** in menu **72156** has toggled back to the "Translate" state.

[1754] In FIG. **72**BG, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location shown by focus selector **72168** (e.g., a location that does not correspond to any of the affordances (e.g., messages, platters, and/or menus) displayed in messaging user interface **7200**). In response to the input, menu **72156** ceases to be displayed, as shown in FIG. **72**BH.

[1755] In FIGS. **72**BI-**72**BJ an input (e.g., a press input) by a contact on touch screen **112** detected at a location that corresponds to message bubble **72142**, as indicated by focus selector **72170**. In FIG. **72**BK, a characteristic intensity of the contact has increased above a deep press intensity threshold level IT_D as indicated by intensity level meter **72155**. In response to the input, menu **72156** is displayed. Because text **72172** in message bubble **72142** does not include foreign language text, menu **72156** does not include a translate option.

[1756] In FIG. **72**BL, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location shown by focus selector **72174** (e.g., a location that does not correspond to any of the affordances (e.g., messages, platters, and/or menus) displayed in messaging user interface **7200**). In response to the input, menu **72156** ceases to be displayed, as shown in FIG. **72**BM.

[1757] In FIG. **72**BN, an input (e.g., a press input) by a contact on touch screen **112** is detected at a location that corresponds to message bubble **72140**, as indicated by focus selector **72176**. In FIG. **72**BO, a characteristic intensity of the contact has increased above a deep press intensity threshold level IT_D as indicated by intensity level meter **72155**. In response to the input, an acknowledgement platter **72178** is displayed. Acknowledgement platter **72178** includes a translate option as indicated at **72180**. In FIG. **72**BP, acknowledgement platter **72178** remains displayed after the contact indicated by focus selector **72176** lifts off of touch screen **112**.

[1758] In FIG. **72**BQ, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to translate option **72180**, as indicated by focus selector **72182**. In response to the input, foreign language text **72146** has been replaced by translation **72150** of the foreign language text in message bubble **72140**, as shown in FIG. **72**BR.

[1759] In FIG. **72**BS, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location shown by focus selector **72184** (e.g., a location that does not correspond to any of the affordances (e.g., messages, platters, and/or menus) displayed in messaging user interface **7200**). In response to the input, acknowledgement platter **72178** ceases to be displayed, as shown in FIG. **72**BT.

[1760] FIGS. **72**BU-**1** to **72**BU-**4** illustrate translation of text of message **72140** in response to a tap input. In **72**BU-**2**, at a time t=**0**, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to message bubble **72140**, as indicated by focus selector **72186**. The contact lifts off after a time t_{tap}, as indicated by FIGS. **72**BU-**3** to **72**BU-**4**. In response to the tap input, the original foreign language text **72146** is replaced by translation **72150** in message bubble **72140**, as shown in FIG. **72**BU-**4**.

[1761] FIGS. **72**BV-**1** to **72**BV-**5** illustrate display of a menu **72156** that includes a translate option **72158** in response to a long press input. In FIG. **72**BV-**2**, at a time t=0, an input (e.g., a press input) by a contact on touch screen **112** is detected at a location that corresponds to message bubble **72140**, as indicated by focus selector **72188**. The contact lifts off from touch screen **112** after a time t_{long} that is greater than t_{tap}, as shown at FIGS. **72**BV-**4** and **72**BV-**5**. When the contact has been in contact with touch screen **112** for time t_{long}, menu **72156** is displayed as shown at FIGS. **72**BV-**5**.

[1762] FIGS. **72**BW-BX illustrate translation of foreign language text **72146** in response to a hover input. In FIG. **72**BW, an input object **72192** (e.g., a finger or a stylus) is detected over the surface of touch screen **112** at a distance **72194** that exceeds a threshold hover distance. When the distance between **72192** and touch screen **112** decreases below the threshold hover distance, as shown in FIG. **72**BX (e.g., the distance **72194** between an input object **72192** and the touch screen **112** is less than the threshold hover distance), foreign language text **72146** is replaced by translation **72150** of the foreign language text in message bubble **72140**.

[1763] FIGS. **72**BY-**72**CN illustrate a "translate all" option **72196** displayed in a menu **72156**. When the translate all option **72196** is selected (e.g., by a contact **72198**), all detected foreign language text in a conversation transcript (e.g., foreign language text in message bubble **72140** and in message bubble **72198**) is simultaneously translated.

[1764] FIGS. **72**CO-**72**CS illustrate translation of a portion of foreign language text in message bubble **72140** that occurs after the portion of the foreign language text has been highlighted. In FIG. **72**CO, a highlighting input (e.g., a drag input) is detected by a contact on touch screen **112**, as indicated by focus selector **72200**. The highlighting input gradually selects a portion of text in message bubble **72140**, as indicated by highlighted region **72202**, as the contact moves (e.g., along a path that is parallel to and/or across the text being highlighted) from a first location, as shown in FIG. **72**CO, to a second location, as shown in FIG. **72**CR. As shown in FIG. **72**CS, in response to lift off of the contact from the touch sensitive surface **112**, the foreign language text that corresponds to highlighted region **72202** is replaced by translated text **72204** (while foreign language text outside of the highlighted region **72202** in message bubble **72140** remains untranslated).

[1765] FIGS. **72**CT-**72**CS illustrate translation of a portion of foreign language text in message bubble **72140** that occurs progressively as the portion of the foreign language text is highlighted. In FIGS. **72**CU-**72**CV, a highlighting input (e.g., a drag input) is detected by a contact on touch screen **112**, as indicated by focus selector **72206**. The highlighting input gradually selects a portion of text in message bubble **72140**, as indicated by highlighted region **72208**, as the contact moves (e.g., along a path that is parallel to and/or across the text being highlighted) from a first location, as shown in FIG. **72**CV, to a second location, as shown in FIG. **72**CX. As shown in FIGS. **72**CV-**72**CX, as the highlighted region **72208** expands, a translated version of the text in the highlighted region is displayed at **72210**. In FIG. **72**CV, highlighted region **72208** includes a single word, and a translation of the single word is displayed at **72210**. In FIG. **72**CW, highlighted region **72208** includes two words, and a translation of the two words is displayed at **72210**. In FIG. **72**CX, highlighted region **72208** includes a three words, and a translation of the three words is displayed at **72210**.

[1766] FIGS. **72**CY-**72**DD illustrate temporary display of translated text in response to a light press input. In FIG. **72**CZ, an input (e.g., a press input) by a contact on touch screen **112** is detected at a location that corresponds to message bubble **72140**, as indicated by focus selector **72190**. In FIG. **72**DA, a characteristic intensity of the contact has increased above a hint intensity threshold level ITH as indicated by intensity level meter **72155**. Message bubble **72140** displays foreign language text **72146** in FIGS. **72**CY-**72**DA. In FIG. **72**DB, the characteristic intensity of the

contact has increased above a light press intensity threshold level IT_L as indicated by intensity level meter **72155**. While the characteristic intensity of the contact remains above light press intensity threshold level IT_L, translation **72150** of the foreign language text is displayed in message bubble **72140**. In FIG. **72**DC, in accordance with a determination that the characteristic intensity of the contact has decreased below light press intensity threshold level IT_L, foreign language text **72146** is redisplayed in message bubble **72140**.

[1767] FIGS. **7**DD-**72**DI illustrate persistent display of translated text in response to a deep press input. In FIG. **72**DE, an input (e.g., a press input) by a contact on touch screen **112** is detected at a location that corresponds to message bubble **72140**, as indicated by focus selector **72214**. In FIG. **72**DF, a characteristic intensity of the contact has increased above a hint intensity threshold level IT_H as indicated by intensity level meter **72155**. Message bubble **72140** displays foreign language text **72146** in FIGS. **72**DD-**72**DF. In FIG. **72**DG, the characteristic intensity of the contact has increased above a light press intensity threshold level IT_L as indicated by intensity level meter **72155**. In accordance with a determination that the characteristic intensity of the contact increases above light press intensity threshold level IT_L, translation **72150** of the foreign language text is displayed in message bubble **72140**. In FIG. **72**DH, in accordance with a determination that the characteristic intensity of the contact increases above a deep press intensity threshold level IT_D as indicated by intensity level meter **72155**, translation **72150** of the foreign language text is persistently displayed in message bubble **72140** (e.g., continuing after the contact indicated by focus selector **72214** lifts off of touch screen **112**, as shown in FIG. **72**DI). Additionally, in accordance with the determination that the characteristic intensity of the contact has increased above deep press intensity threshold level IT_D, the visual appearance of the translated text **72150** is changed (e.g., compared with the visual appearance of the translated text **72150** in FIG. **72**DG) to provide an indication to the user of the persistent nature of the translation.

Bubble Connections

[1768] FIGS. **72**DJ-**72**EV illustrate exemplary user interfaces for connecting message bubbles in a messaging application, in accordance with some embodiments. For convenience of explanation, some of the embodiments will be discussed with reference to operations performed on a device with a touch-sensitive display system **112**. In such embodiments, the focus selector is, optionally: a respective finger or stylus contact, a representative point corresponding to a finger or stylus contact (e.g., a centroid of a respective contact or a point associated with a respective contact), or a centroid of two or more contacts detected on the touch-sensitive display system **112**. However, analogous operations are, optionally, performed on a device with a display **450** and a separate touch-sensitive surface **451** in response to detecting the contacts on the touch-sensitive surface **451** while displaying the user interfaces shown in the figures on the display **450**, along with a focus selector.

[1769] In FIG. **72**DJ, user interface **7200** includes conversation transcript **7202** that includes messages from participants of a corresponding messaging session, including the user of portable multifunction device **100**-A ("Riley") and a user of portable multifunction device **100**-B ("Ray") included in the messaging session. On device **100**-A, the user "Ray" is represented by an avatar **72216**. Message **72218** is a message received by device **100**-A from remote device **100**-B operated by the user identified as Ray and message **72224** is a message transmitted by device **100**-A to the remote device **100**-B operated by Riley.

[1770] FIGS. **72**DJ-**72**ED illustrate input used for grouping message content (e.g., for connecting message bubbles displayed in conversation transcript **7202**). In some embodiments, the grouping selection input groups first content (e.g., one or more received messages in the conversation transcript, one or more sent messages in the conversation transcript, and/or input content entered in a message-input area) in a messaging user interface with at least one message (e.g., one or more received messages in the conversation transcript and/or one or more sent messages in the conversation transcript) that is displayed in the messaging user interface. In response to detecting the grouping selection input, a group that includes the first content and the at least one message is created.

[1771] In some embodiments, input for connecting message bubbles includes input to put a message bubble in a grouping mode, as illustrated at FIGS. **72**DN-**72**DR and **72**DS-**72**DU. In some embodiments, input for connecting message bubbles includes input to move a message bubble, as illustrated at FIGS. **72**DO-**72**DQ and FIGS. **72**DV-**72**DY. In some embodiments, input for connecting message bubbles includes input for drawing a connection between message bubbles, as illustrated at FIGS. **72**EA-**72**ED.

[1772] In some embodiments, a grouping selection input is an input detected at a location that corresponds to the first content (e.g., message bubble **72218**) and the grouping selection input moves the first content from a first location to a second location (e.g., as shown in FIGS. **72**DO-**72**DQ) within the messaging user interface **7200**. In some embodiments, the grouping selection input drags a message in a direction (e.g., left to right or right to left) by a distance that meets one or more grouping criteria. FIGS. **72**DO-**72**DY illustrate a grouping selection input that includes dragging a first message bubble **72218** and a second message bubble **72224** to grouping positions (e.g., proximate to the center of messaging user interface **7200**).

[1773] In FIG. **72**DK, a grouping mode input (e.g., a press input) by a contact on touch screen **112** is detected at a location that corresponds to message bubble **72218**, as indicated by focus selector **72220**, and a characteristic intensity of the gradually increases, as shown in FIGS. **72**DK-**72**DM, until the characteristic intensity of the contact has increased above a deep press intensity threshold level IT_D as indicated by intensity level meter **72155**, as shown in FIG. **72**DM. In accordance with a determination that the characteristic intensity of the contact has increased above the deep press intensity threshold level IT_D, message bubble **72218** enters a grouping mode. In some embodiments, when the message bubble **72218** enters the grouping mode, the message bubble **72218** is "detached" from conversation transcript **7202** such that the message bubble **72218** is movable within conversation transcript **7202**. In some embodiments, to indicate that message bubble **72218** is in a grouping mode, the device provides an indication that the message is detached from the transcript, such as an altered background, haptic feedback, an altered transcript characteristic, and/or an altered message bubble characteristic. For example, a message bubble outline is altered (e.g., shown with a greater line weight, as shown in FIG. **72**DN), the

bubble size is increased, and/or the appearance of text in the message bubble is altered to provide a visual indication that message bubble **72218** is in a grouping mode. The input that transitions message bubble **72218** to a grouping mode allows a swipe input at a location that corresponds to message bubble **72218** to have a grouping functionality when the message bubble is in a grouping mode and an alternative functionality (e.g., horizontally dragging one or more displayed message bubbles to reveal a time that corresponds to the one or more message bubbles) when the message bubble is not in a grouping mode.

[1774] In some embodiments, grouping selection input as described herein occurs without transitioning a message bubble to a grouping mode using a grouping mode input.

[1775] In some embodiments, detecting the grouping selection input includes detecting a first input (e.g., a deep press input) at a location that corresponds to the first content and a second input (e.g., a deep press input) at a location that corresponds to the at least one message.

[1776] In FIG. **72**DO a grouping selection input (e.g., a drag input) by a contact on touch screen **112** is detected at a location that corresponds to message bubble **72218**, as indicated by focus selector **72222**. The input drags the message bubble **72218** toward a grouping position (e.g., proximate to the center of messaging user interface **7200**), as shown at FIGS. **72**DO to **72**DQ. In FIG. **72**DR, after movement of message bubble **72218** has met grouping criteria (e.g., the message bubble has moved to the grouping position), the contact indicated by focus selector **72222** lifts off of the touch screen **112**. In some embodiments, in accordance with a determination that movement of message bubble **72218** has met grouping criteria (e.g., the message bubble has moved to the grouping position), a visual appearance of message bubble **72218** is altered and/or a haptic effect occurs to indicate to the user that the message bubble has been moved to a grouping position.

[1777] In FIG. **72**DS, a grouping mode input (e.g., a press input) by a contact on touch screen **112** is detected at a location that corresponds to message bubble **72224**, as indicated by focus selector **72226**, and a characteristic intensity of the gradually increases, as shown in FIGS. **72**DS-**72**DT, until the characteristic intensity of the contact has increased above a deep press intensity threshold level IT_D as indicated by intensity level meter **72155**, as shown in FIG. **72**DT. In accordance with a determination that the characteristic intensity of the contact has increased above the deep press intensity threshold level IT_D, message bubble **72224** enters a grouping mode as shown in FIG. **72**DU.

[1778] In FIG. **72**DV a grouping selection input (e.g., a drag input) by a contact on touch screen **112** is detected at a location that corresponds to message bubble **72224**, as indicated by focus selector **72228**. The grouping selection input drags the message bubble **72224** toward a grouping position (e.g., proximate to the center of messaging user interface **7200**), as shown at FIGS. **72**DV to **72**DX. In FIG. **72**DY, after movement of message bubble **72218** has met grouping criteria (e.g., the message bubble has moved to the grouping position), the contact indicated by focus selector **72228** lifts off of the touchscreen. In some embodiments, in accordance with a determination that movement of message bubble **72224** has moved to the grouping position, a visual appearance of message bubble **72224** is altered and/or a haptic effect occurs to indicate to the user that the message bubble has been moved to a grouping position. In response to lift off of the contact, a group of message bubbles **72218** and **72224** is formed (e.g., in accordance with a determination that more than one message bubble has been dragged to a grouping position by the grouping selection input), as indicated by grouping indicator **72230**.

[1779] In some embodiments, grouping indicia are displayed at a first location that corresponds to the first content (e.g., message bubble **72218**) and at a second location that corresponds to the at least one message (e.g., message bubble **72224**). For example, grouping indicia include a line (e.g., grouping indicator **72230** or **72236**) that connects the first content with the at least one message, a region designator (e.g., a shape, such as a box, that encompasses the first content and the at least one messages), and/or a plurality of markers (e.g., a first marker displayed at a location that corresponds to the first content and a second marker displayed at a location that corresponds to the at least one message.

[1780] FIGS. **72**EA-**72**ED illustrate a grouping selection input that includes a swipe input from a first message bubble **72218** to a second message bubble **72224**. In FIG. **72**EA, a grouping selection input (e.g., a swipe input) by a contact on touch screen **112** is detected at a location that corresponds to message bubble **72218**, as indicated by focus selector **72232**. In some embodiments, the grouping selection input is detected after message bubble **72218** has transitioned to a grouping mode. As the grouping selection input is received, a line **72234** is displayed to indicate the path of the grouping selection input, as illustrated at FIGS. **72**EB-**72**EC. In FIG. **72**ED, the contact indicated by focus selector **72232** has lifted off from touch-sensitive surface **112**, an line **72234** is replaced by grouping indicator **72236**.

[1781] FIG. **72**EE shows messages **72218** and **72224** in a group (as indicated by group indicator **72236**) displayed on portable multifunction device **100**-B.

[1782] In some embodiments, a second input is detected that indicates second content to add to the created group. For example, in FIG. **72**EF, text input **72238** has been entered in message input area **72240** displayed on device **100**-B. An input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to send affordance **72242**, as indicated by focus selector **72244**. In FIG. **72**EG, text input **72238** is displayed in message bubble **72246** as a sent message in conversation transcript **7202**.

[1783] In FIG. **72**EH, message bubble **72246** is shown in a grouping mode state. For example, a grouping mode input as described with regard to FIGS. **72**DK-**72**DN is provided to transition message bubble **72246** to a grouping mode state.

[1784] In FIG. **72**EI, a grouping selection input (e.g., a drag input) by a contact on touch screen **112** is detected at a location that corresponds to message bubble **72246**, as indicated by focus selector **72248**. The grouping selection input drags the message bubble **72246** toward a grouping position (e.g., proximate to the center of messaging user interface **7200**), as shown at FIGS. **72**EI to **72**EK. In FIG. **72**EL, after movement of message bubble **72246** has met grouping criteria (e.g., the message bubble has moved to the grouping position), the contact indicated by focus selector **72248** lifts off of the touchscreen. In response to lift off of the contact, in accordance with a determination that grouping criteria have been met, message bubble **72246** is added to a group with message bubble **72218** and **72224**, as indicated by grouping indicator **72236**.

[1785] FIG. **72**EM shows messages **72218**, **72224**, and **72246** in a group (as indicated by group indicator **72236**) displayed on portable multifunction device **100**-A. Text input **72250** has been entered in message input area **7204** displayed on device **100**-A. The size of the text input in message input area **7204** causes message bubbles in the group indicated by group indicator **72236** to move upward. In order to continue to display uppermost message bubble **72218** of the group, uppermost message bubble **72218** is displayed overlapping non-group messages **72258**, **72260**, and **72262** (which are shown in a dimmed area of the display to avoid confusion between the non-group messages and the overlying group messages).

[1786] In some embodiments, the first content is input content entered in the message-input area (e.g., input received prior to transmitting a message including input content), and the grouping selection input is detected prior to a transmission input that transmits the message to another device (e.g., as illustrated at FIGS. **72**EM-**72**ER).

[1787] In FIG. **72**EN, a grouping selection input (e.g., a drag input) by a contact on touch screen **112** is detected at a location that corresponds to send affordance **72254**, as indicated by focus selector **72256**. The grouping selection input drags the message bubble **72256** toward a group member (e.g., to a location that partially overlaps a message bubble in the group), as shown at FIGS. **72**EN to **72**E**0**. In FIG. **72**EP, after movement of message bubble **72246** has met grouping criteria (e.g., the message bubble has moved a location that partially overlaps message bubble **72246**), the contact indicated by focus selector **72256** lifts off of the touch screen **112**. In FIG. **72**EQ, an input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to send affordance **72254**, as indicated by focus selector **72266**. As shown in FIG. **72**ER, in response to the input, message bubble **72264** is added to a group with message bubbles **72218**, **72224**, and **72246**, as indicated by grouping indicator **72236**.

[1788] In some embodiments, in response to lift off of the contact indicated by focus selector **72256**, in accordance with a determination that grouping criteria have been met, message bubble **72264** is added to a group with message bubbles **72218**, **72224**, and **72246**, as indicated by grouping indicator **72236**.

[1789] FIG. **72**ES indicates an input (e.g., a tap input) by a contact on touch screen **112** at a location shown by focus selector **72268** (e.g., a location that does not correspond to any of the message bubbles or affordances displayed in messaging user interface **7200**). In response to the input, the grouped messages cease to overlap the non-grouped messages (e.g., message bubble **72218** ceases to be displayed such that message bubble **72218** ceases to overlap message bubble **72258** as shown in FIG. **72**ET). FIG. **72**EU indicates an input (e.g., a tap input) by a contact on touch screen **112** at a location that corresponds to group indicator **72236**, as shown by focus selector **72270**. In response to the input, the grouped message bubbles are displayed overlapping the non-grouped messages, such that grouped message bubbles **72218**, **72224**, **72246**, and **72264** are simultaneously displayed, as shown in Figure EV.

Message Flagging

[1790] FIGS. **72**EW-**72**FM illustrate exemplary user interfaces for flagging a message bubble, in accordance with some embodiments. For example, in response to an input that designates a message bubble in a conversation transcript **7202**, the message bubble is flagged (e.g., the message bubble is displayed at a fixed location on the display, such as at the top of the conversation transcript **7202**). For convenience of explanation, some of the embodiments will be discussed with reference to operations performed on a device with a touch-sensitive display system **112**. In such embodiments, the focus selector is, optionally: a respective finger or stylus contact, a representative point corresponding to a finger or stylus contact (e.g., a centroid of a respective contact or a point associated with a respective contact), or a centroid of two or more contacts detected on the touch-sensitive display system **112**. However, analogous operations are, optionally, performed on a device with a display **450** and a separate touch-sensitive surface **451** in response to detecting the contacts on the touch-sensitive surface **451** while displaying the user interfaces shown in the figures on the display **450**, along with a focus selector.

[1791] In FIG. **72**EW, user interface **7200** includes conversation transcript **7202** that includes messages from participants of a corresponding messaging session. Conversation transcript **7202** includes a received message displayed in message bubble**72272**.

[1792] In FIG. **72**EX, a flagging mode input (e.g., a press input) by a contact on touch screen **112** is detected at a location that corresponds to message bubble **72272**, as indicated by focus selector **72274**, and a characteristic intensity of the gradually increases, as shown in FIGS. **72**EX-**72**EZ, until the characteristic intensity of the contact has increased above a deep press intensity threshold level IT_D as indicated by intensity level meter **72155**, as shown in FIG. **72**EZ. In accordance with a determination that the characteristic intensity of the contact has increased above the deep press intensity threshold level IT_D, message bubble **72272** enters a flagging mode. In some embodiments, when the message bubble **72272** enters the flagging mode, the message bubble **72272** is "detached" from conversation transcript **7202** such that the message bubble **72272** is movable within conversation transcript **7202**. In some embodiments, to indicate that message bubble **72272** is in a grouping mode, the device provides an indication that the message is detached from the transcript, such as an altered background, haptic feedback, an altered transcript characteristic, and/or an altered message bubble characteristic. For example, a message bubble outline is altered (e.g., shown with a greater line weight, as shown in FIG. **72**FA), the bubble size is increased, and/or the appearance of text in the message bubble is altered to provide a visual indication that message bubble **72272** is in a flagging mode.

[1793] In some embodiments, flagging selection input as described herein occurs without transitioning a message bubble to a flagging using a flagging mode input.

[1794] In some embodiments, in response to an input (e.g., a flagging mode input and/or a flagging selection input) that designates a message (e.g., a message in message bubble **72272**) in a conversation transcript **7202**, the message is displayed at a fixed location on the display **112**, such as at the top of the conversation transcript **7202**. In some embodiments, the input that designates the message is a tap input on the message bubble followed by selection of a menu item, a press and hold input (e.g., an input that meets predetermined duration criteria during which a contact remains in contact with touch screen **112**), and/or a press input (e.g., an input with a characteristic intensity of the contact that exceeds a

threshold intensity level, such as a light press intensity threshold level IT_L and/or a deep press intensity threshold level IT_D). In some embodiments, the input is a drag input that drags the message to the fixed location on the display. In some embodiments, when the input moves the message beyond a threshold distance, the message is "detached" from the conversation transcript **7202**. In some embodiments, in response to detecting the input, the message is detached from the conversation transcript and/or automatically moved to the fixed location on the display (e.g., an animation is shown in which the message moves from its original location on the display to the fixed location on the display).

[1795] In FIG. **72**FB, a flagging selection input (e.g., a drag input) is detected by a contact on touch screen **112**, as indicated by focus selector **72276**. The flagging selection input drags the message bubble **72272** toward the top of conversation transcript **7202**, as shown at FIGS. **72**FC to **72**FE. In some embodiments, a placeholder **72278** for message bubble **72218** is displayed in the conversation transcript **7202**. In FIG. **72**FF, the contact indicated by focus selector **72276** lifts off of the touch screen **112**. In response to the lift off of the contact from touch screen **112**, in accordance with a determination that the flagging selection input met flagging criteria (e.g., movement of the focus selector **72276** increased beyond a threshold distance), message bubble **72272** is dropped at the top of conversation transcript **7202**.

[1796] In FIG. **72**FF, message bubble **72272** is displayed in a message banner **72280** at the top of conversation transcript **7202**.

[1797] In some embodiments, a timer **72282** is displayed that indicates the elapsed time since the message was flagged.

[1798] In some embodiments, when a message that responds to the flagged message is transmitted, a flagged message is unflagged and returns to its previous location in the transcript. For example, in FIG. **72**FG, text input **72284** has been entered in message input area **7204**. An input (e.g., a tap input) by a contact on touch screen **112** is detected at a location that corresponds to send affordance **72290**, as indicated by focus selector **72286**. In FIG. **72**FH, text input **72284** is displayed in message bubble **72292** as a sent message in conversation transcript **7202**.

[1799] In some embodiments, a second input (e.g., dragging the message in a direction that is opposite to the direction in which the message was dragged to flag the message) is received that returns a flagged message to its previous position (e.g., to unflag the message). For example, in FIG. **72**FI, a flagging deselection input (e.g., a drag input) is detected by a contact on touch screen **112**, as indicated by focus selector **72294**. The flagging selection input drags the message bubble **72272** toward its original location (e.g., indicated by placeholder **72278**), as shown at FIGS. **72**FI to **72**FL. In FIG. **72**FM, the contact indicated by focus selector **72294** lifts off of the touch screen **112**. In response to the lift off of the contact from touch screen **112**, in accordance with a determination that the flagging selection input meet unflagging criteria (e.g., movement of the focus selector **72294** increased beyond a threshold distance), message bubble **72272** is dropped at its original location within conversation transcript **7202**.

[1800] In some embodiments, a flagging mode input is received (e.g., while message **72272** is displayed at the flagged position and/or prior to a flagging deselection input.

[1801] FIGS. **73**A-**73**D are flow diagrams illustrating a method **7300** for navigating between applications using an application user interface displayed in a messaging user interface, in accordance with some embodiments. The method **7300** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display and a touch-sensitive surface. In some embodiments, the display is a touch screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **7300** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1802] The device displays (**7302**), on a display (e.g., touch screen **112**), a messaging user interface (**7200**, FIG. **72**A), the messaging user interface including: a conversation transcript **7202** of a messaging session between a user of the electronic device and at least one other user, a message-input area **7204**, an application area **7210**, and an application-area-display affordance. In some embodiments, application area **7210** is a predefined area in the messaging user interface **7200**, separate from the conversation transcript **7202** and the message-input area **7204**, that is configured to display either a keyboard **7212** or activatable objects (e.g., objects **7234**-**7240**, FIG. **72**C) that correspond to one or more applications that operate within the messaging user interface **7200** of a messaging application.

[1803] While displaying the messaging user interface **7200**, the device detects (**7304**) a first input (e.g., a tap input by a contact at a location indicated by focus selector **7220**, FIG. **72**B) that activates the application-area-display affordance **7208**.

[1804] In response to detecting the first input that activates the application-area-display affordance **7208**, in accordance with a determination that the application area is displaying a keyboard **7212** at the time the first input is detected, the device replaces (**7306**) display of the keyboard **7212** in the application area with concurrent display of: an application-selection area **7224** (FIG. **72**C) that displays a plurality of scrollable application-selection affordances (e.g., **7226**-**7232**) and an application-input area **7222** that displays one or more activatable objects (e.g., **7234**-**7240**) of the first application. In some embodiments, the plurality of scrollable application-selection affordances are arranged in a single horizontal row. The plurality of scrollable application-selection affordances includes a first application-selection affordance (e.g., **7230**) that corresponds to a first application that is currently selected (e.g., the music application that includes activatable objects **7234**-**7240** displayed in application-input area **7222**). A respective application-selection affordance (e.g. application-selection affordance **7230**) has a respective first size.

[1805] While concurrently displaying the application-selection area **7224** and the application-input area **7222**, the device detects (**7308**) a second input that includes a movement of a contact on the touch-sensitive surface that corresponds to movement of a focus selector **7242** (FIG. **72**D) in a first direction in the application-selection area **7224** on the display (e.g., a horizontal drag or swipe gesture by the contact within the application-selection area on touch screen **112**).

[1806] In response to detecting the second input, the device scrolls (**7310**) the plurality of application-selection affordances in the first direction (e.g., as shown at FIGS.

72D-72G) and displays a second application-selection affordance (e.g., application-selection affordance **7426**, FIG. **72**G). In some embodiments, the second application-selection affordance was not displayed prior to the scrolling.

[1807] While displaying the second application-selection affordance and the one or more activatable objects of the first application in the messaging user interface, the device detects (**7312**) a third input (e.g., a tap input by a contact at a location indicated by focus selector **7250**, FIG. **72**H) that activates the second application-selection affordance (e.g., **7426**).

[1808] In response to detecting the third input that activates the second application-selection affordance, the device (**7314**) ceases to display the one or more activatable objects of the first application (e.g., **7234-7240**) and displays, in the application-input area, one or more activatable objects of a second application that corresponds to the second application-selection affordance (e.g., the device displays activatable objects **7252** and **7254** of a reservations application, as indicated in FIG. **72**I).

[1809] Displaying an application-selection area that displays a plurality of scrollable application-selection affordances presents a user with a limited number of initially displayed application-selection affordances while providing the user with quick access to additional application-selection affordances. Presenting a limited number of initially displayed application-selection affordances allows the user to quickly select an application (e.g., from among a short list of pre-selected and/or most used applications) and reduces the likelihood of accidental selection of an application affordance. Enabling the user to use the device more quickly and efficiently reduces power usage and improves battery life of the device.

[1810] In some embodiments, while scrolling the plurality of application-selection affordances in the first direction, for at least some of the scrolling application-selection affordances, the device increases (**7316**) the size of a respective application-selection affordance from the respective first size to a respective second size, larger than the respective first size. For example, while scrolling of application-selection affordances occurs, application-selection affordance **7230** increases from a first size, as shown in FIG. **72**C, to a second size, as shown in FIG. **72**E. In some embodiments, increasing the size of the respective application-selection affordance includes displaying an animated transition (e.g., that gradually increases the size of the respective application-selection affordance from the respective first size to the respective second size). In some embodiments, all displayed application-selection affordances increase in size temporarily during scrolling (e.g., as shown in FIG. **72**E, application-selection affordances **7232**, **7230**, and **7228** have all increased in size relative to their respective sizes in FIG. **72**C). In some embodiments, a size of the application-selection area **7224** increases temporarily during scrolling. In some embodiments, a magnitude of the increase in size of the one or more application selection affordances is dependent on a speed at which the scrolling occurs (e.g., a greater scrolling speed results in a larger (e.g., proportionally larger) increase in the size of the one or more application selection affordances). Increasing the size of the application-selection affordances during scrolling makes it easier for a user to locate the application-selection affordance that corresponds to the application that the user wants to select and use within the messaging application.

[1811] Increasing the size of a respective application-selection affordance while scrolling the plurality of scrollable application-selection affordances increases the visibility of the respective application-selection affordance. Increasing the visibility of an application-selection affordance enhances the operability of the device by making the desired application selection affordance easier for the user to select (e.g., by providing a larger selectable area that corresponds to the application-selection affordance) and reduces the likelihood of accidental selection of an application selection affordance other than the desired application selection affordance (e.g., by making an icon that corresponds to the desired application-selection affordance easier for the user to see).

[1812] In some embodiments, after scrolling the plurality of application-selection affordances in the first direction, the device decreases (**7318**) the size of the respective application-selection affordance from the respective second size to the respective first size. For example, after scrolling of application-selection affordances occurs, application-selection affordance **7230** decreases from the second size, as shown in FIG. **72**E to the its initial size, as shown in FIG. **72**G. In some embodiments, the size of the respective application-selection affordance decreases when scrolling stops, or within a predetermined time after scrolling stops. In some embodiments, decreasing the size of the respective application-selection affordance includes displaying an animated transition (e.g., that gradually decreases the size of the respective application-selection affordance from the respective second size to the respective first size).

[1813] Decreasing the size of a respective application-selection affordance after scrolling the plurality of scrollable application-selection affordances allows an increased number of application-selection affordances to be simultaneously displayed. Increasing the number of simultaneously displayed application-selection affordances makes the user-device interface more efficient (e.g., by increasing the number of application-selection affordances available for selection without further scrolling input).

[1814] In some embodiments, while scrolling the plurality of application-selection affordances in the first direction, the device reduces (**7320**) a number of application-selection affordances shown in the application-input area from a first number of application-selection affordances (e.g., the four application-selection affordances **72226**, **7228**, **7230**, and **7232** shown in FIG. **72**D) to a second number of application-selection affordances (e.g., the three application-selection affordances **7228**, **7230**, and **7232** shown in FIG. **72**E) that is less than the first number of application-selection affordances.

[1815] Reducing the number of application-selection affordances displayed while scrolling the plurality of scrollable application-selection affordances reduces the likelihood of accidental selection of an application selection affordance other than the desired application selection affordance (e.g., by increasing the distance between the centers of the application-selection affordances).

[1816] In some embodiments, after scrolling the plurality of application-selection affordances in the first direction, the device ceases (**7322**) to display at least one application-selection affordance of the plurality of scrollable application-selection affordances that was displayed prior to scrolling the plurality of application-selection affordances in the first direction. For example, application-selection affordance

7228, shown in FIG. **72**C prior to scrolling, is no longer displayed in application-selection area **7224** after scrolling, as shown in FIG. **72**G.

[1817] Ceasing to display at least one application-selection affordance after scrolling allows the user to view additional application selection affordances in the display space that is made available by ceasing to display the at least one application selection affordance. This increases the operability of the device (e.g., by increasing a number of application-selection affordances that can be viewed and selected via a scrolling process).

[1818] In some embodiments, while the application-input area **7222** is displayed at a first size, the device (**7324**) displays, in the application-input area, an application-input area expansion affordance (e.g., chevron **7260**) and detects a fourth input that activates the application-input area expansion affordance **7260**. For example, the fourth input includes movement of a contact on the touch-sensitive surface that corresponds to movement of the focus selector **7256** in a second direction (e.g., different from the first direction) that drags the application-input area expansion affordance **7260** (e.g., upwards). In some embodiments, the fourth input is a tap input on the application-input area expansion affordance **7260**. In response to detecting the fourth input, the device increases a size of the application-input area **7222** from the first size (as shown in FIG. **72**J) to a second size that is larger than the first size (e.g., as shown in FIG. **72**K or **72**L). In some embodiments, while the size of the application-input area is the second size, the conversation transcript **7202** of the messaging session (e.g., including at least one message) is at least partially displayed in the messaging user interface (e.g., as shown in FIG. **72**K).

[1819] Increasing a size of the application-input area in response to input that activates an application-input area expansion affordance allows an increased number of activatable objects of an application to be simultaneously displayed in the application-input area. Increasing a number of activatable objects of an application that are simultaneously displayed in the application-input area makes the user-device interface more efficient by reducing the number of inputs required to navigate to a desired activatable object of an application.

[1820] In some embodiments, in response to detecting the first input that activates the application-area-display affordance **7264** (e.g., a tap input by a contact at a location indicated by focus selector **7264**, FIG. **72**O), in accordance with a determination that the application area **7210** is displaying the application-selection area **7224** and the application-input area **7222** in the application area **7210** at the time the first input is detected, the device replaces (**7326**) display of the application-selection area **7224** and the application-input area **7222** in the application area with display of the keyboard **7212**, as shown in FIGS. **72**O-**72**P. In some embodiments, in response to detecting an input (e.g., a tap input) on the application-area-display affordance **7208** (or in the message-input area **7204**), in accordance with a determination that the messaging user interface is displaying the application-selection area **7224** and the application-input area **7222** at the time the input is detected, display of the application-selection area **7224** and the application-input area **7222** is replaced with display of the keyboard **7212**.

[1821] Replacing display of the application-selection area **7224** and the application-input area **7222** in the application area **7210** with display of the keyboard **7212** in response to input that activates an application-area-display affordance **7208** enhances the operability of the device by reducing the amount of display area consumed by these elements by alternatively displaying the elements. Reducing the amount of display area consumed by these elements enhances the operability of the device by increasing the display area available to display other user interface objects.

[1822] In some embodiments, while displaying, in the application-input area **7222**, the one or more activatable objects (e.g., **7252** and **7254**) of the second application, the device detects (**7328**) a fifth input (e.g., a tap input by a contact at a location indicated by focus selector **7264**, FIG. **720**) that activates the application-area-display affordance **7208**. In response to detecting the fifth input that activates the application-area-display affordance **7208**, the device replaces concurrent display of the application-selection area **7224** and the application-input area **7222** with display of the keyboard **7212** (e.g., as shown in FIGS. **72**O-**72**P). While displaying the keyboard **7212** in the application area, the device detects a sixth input (e.g., a tap input by a contact at a location indicated by focus selector **7264**, FIG. **72**Q) that activates the application-area-display affordance **7208**. In response to detecting the sixth input that activates the application area-display affordance, the device ceases to display the keyboard **7212** in the application area, and concurrently displays the application-selection area **7224** and the application-input area **7222** (e.g., as shown in FIGS. **72**Q-**72**R), wherein the application-selection area **7224** concurrently displays a pre-selected set of application-selection affordances (e.g., the set of **7226**, **7228**, **7230**, and **7232**) that includes the first application-selection affordance (e.g., **7230**). For example, the pre-selected set of application-selection affordances are a default set of application-selection affordances or a set of user-selected application selection affordances that are displayed. In some embodiments, the pre-selected set of application-selection affordances are shown each time input that activates the application area-display affordance causes the application-selection area to be displayed.

[1823] Displaying a pre-selected set of application-selection affordances (e.g., the set of **7226**, **7228**, **7230**, and **7232**) in response to an input that activates an application area-display affordance **7208** allows the user to quickly navigate to a desired activatable object that corresponds to an application (e.g., a frequently used application) in a pre-selected set of applications. For example, after scrolling the plurality of application-selection affordances, the user is enabled to return to a pre-set of most used application-selection affordances by providing an input that activates an application area-display affordance (rather than needing to reverse the scrolling of the plurality of application selection affordances). In this way, the number of inputs and/or time during which input must be provided is reduced.

[1824] It should be understood that the particular order in which the operations in FIGS. **73**A-**73**D have been described is merely one example and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein are also applicable in an analogous manner to method **7300** described above. For example, the contacts, gestures, user interface objects, inten-

sity thresholds, focus selectors, and animations described above with reference to method **7300** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein. For brevity, these details are not repeated here.

[1825] The operations described above with reference to FIGS. **73**A-**73**D are, optionally, implemented by components depicted in FIGS. **1**A-**1**B. For example, one or more of the operations are optionally implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

[1826] FIGS. **74**A-**74**D are flow diagrams illustrating a method **7400** for managing applications used within a messaging application, in accordance with some embodiments. The method **7400** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display and a touch-sensitive surface. In some embodiments, the display is a touch screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **7400** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1827] The device displays (**7402**), by a display (e.g., touch screen **112**), a messaging user interface **7200** (FIG. **72**C) of a messaging application. The messaging user interface includes a conversation transcript **7202** of a messaging session between a user of the electronic device and at least one other user; a message-input area **7204**; and an application area **7210** (e.g. a predefined area in the messaging user interface, separate from the conversation transcript and the message-input area, that is configured to display either a keyboard or activatable objects that correspond to one or more applications that are displayed within the messaging user interface of a messaging application). The application area **7210** includes an application-input area **7222** that displays one or more activatable objects (e.g., **7234-7240**) of a first application and an application-selection area **7224**. The application-selection area **7224** includes a plurality of scrollable application-selection affordances (e.g., **7228-7232**) that correspond to a plurality of applications that operate within the messaging user interface and a first application-configuration affordance (e.g., **7226**). In some embodiments, the application-selection affordances are arranged in a single horizontal row.

[1828] While displaying the application-configuration affordance **7226** in the application-selection area **7224**, the device detects (**7404**) a first input (e.g., a tap input by a contact at a location indicated by focus selector **7268**, FIG. **72**S) that activates the first application-configuration affordance **7226**.

[1829] In response to detecting the first input, the device displays (**7406**) a first application-management interface **7270** (FIG. **72**T) for the messaging application that includes a plurality of installed-application affordances (e.g., **7273**, **7275**, **7277**, **7279**, **7281**, **7283**, **7285**) that correspond to the plurality of applications that operate within the messaging user interface of the messaging application, and a second application-configuration affordance **72112** that is distinct from the first application-configuration affordance **7226**.

[1830] While displaying the first application-management interface **7270**, the device detects (**7408**) a second input (e.g., a tap input by a contact at a location indicated by focus selector **7288**, FIG. **72**U) at a location that corresponds to a first installed-application affordance **7273** of the plurality of installed-application affordances, wherein the first installed-application affordance **7273** corresponds to a first installed application on the electronic device (e.g., a tic-tac-toe application).

[1831] In response to detecting the second input, the device initiates (**7410**) a process to uninstall at least a component of the first installed application on the mobile device (e.g., a component of the first installed application that operates within one or more user interfaces, such as the messaging user interface, a watch user interface, and/or a content sharing user interface, is uninstalled). In some embodiments, at least a component of the first installed application remains installed on the device when the component of the first installed application is uninstalled. For example, a component of the application that is accessible from the device home screen remains installed.

[1832] While displaying the first application-management interface, the device detects (**7412**) a third input (e.g., a tap input by a contact at a location indicated by focus selector **72212**, FIG. **72**AB) at a location that corresponds to the second application-configuration affordance **72112**.

[1833] In response to detecting the third input, the device displays (**7414**) a second application-management interface **72116** (FIG. **72**AC) for the messaging application. The second application-management interface **72116** includes a plurality of toggles (e.g., **72117**, **72118**, **72119**, **72121**, **72123**, **72125**, **72127**) that correspond to the plurality of applications that operate within the messaging user interface of the messaging application. Activation of a respective toggle (e.g., **72118**) causes a corresponding application to toggle between a hidden state and a revealed state in the messaging user interface of the messaging application (e.g., as shown in FIGS. **72**S, **72**AD-**72**AE, and **72**AO).

[1834] Providing a first application-management interface **7270** that receives an input for initiating a process to uninstall at least a component of an installed application (e.g., as shown in FIGS. **72**U-**72**V) and providing a second application-management interface **72116** that receives input for toggling between a hidden state and a revealed state of an installed application (e.g., as shown in FIGS. **72**AD-**72**AE) provides the user with the ability to hide an application in the messaging user interface without deleting

non-messaging components of the installed application. Providing the user with the ability to limit displayed components to those that the user intends to use makes the user-device interface more efficient (e.g., by reducing clutter in the interface), allowing the user to more efficiently locate an application-selection affordance for selection without entirely removing the access to non-messaging components of an application that corresponds to component that is hidden in the messaging user interface.

[1835] In some embodiments, the first application-configuration affordance **7226** (FIG. **72**R) is located (**7416**) in a fixed position relative to the plurality of application-selection affordances (e.g., **7228**, **7230**, and **7232**) that correspond to the plurality of applications. In some embodiments, the first application-configuration affordance **7226** is always located at an end of a list of application-selection affordances (e.g., at the right end of a horizontal row of application-selection affordances).

[1836] Locating the first application-configuration affordance **7226** at a fixed position relative to the plurality of application-selection affordances allows the user to locate the application-configuration affordance **7226** quickly and consistently (e.g., because the user does not need to scroll back and forth among the plurality of application-selection affordances to locate the application configuration affordance). Reducing the number of inputs required and the time required for providing inputs to locate the application-configuration affordance makes the user-device interface more efficient.

[1837] In some embodiments, the device displays (**7418**), in the first application-management interface **7270**, a search-input area **7290** (FIG. **72**Y); receives input for the search-input area (e.g., text input **7296** or voice input); and performs a search, using the input in the search-input area, for a plurality of applications that are operable within the messaging user interface (e.g., a search of applications available for installation for use in the messaging user interface **7200**, a search of applications previously installed for use in the messaging user interface **7200**, and/or a search of installed applications that have a revealed state (e.g., as indicated by the toggles (e.g., **72117**, **72118**, **72119**, **72121**, **72123**, **72125**, **72127**) of application-management interface **72116**). For example, in response to the search input received as shown in FIG. **72**Y, applications **72102** and **72014** are displayed as search results in FIG. **72**Z.

[1838] Displaying, in the first application-management interface **7270**, a search-input area **7290** for performing a search for applications that are operable within the messaging user interface **7200**, allows the user search for such applications without the need to navigate away from the messaging user interface **7200**. As a result, the number of inputs required and the time required to locate applications that are operable within the messaging user interface **7200** is reduced, which makes the user-device interface more efficient.

[1839] In some embodiments, while displaying the second application-management interface, the device detects (**7420**) a fourth input (e.g., a tap input by a contact at a location indicated by focus selector **72122**, FIG. **72**AD) at a location that corresponds to a first toggle (e.g., **72118**, FIG. **72**AD) of the plurality of toggles. The first toggle **72118** corresponds to a second application, such as a stickers application (e.g., that is distinct from the first installed application) of the plurality of applications that operate within the messaging user interface **7200** of the messaging application. In response to detecting the fourth input, in accordance with a determination that a current state of the second application is a revealed state (e.g., as shown by the first state of first toggle **72118** in FIG. **72**AD), the device toggles the state of second application from the revealed state to the hidden state (e.g., as shown by the second state of first toggle **72118** in FIG. **72**AE). In accordance with a determination that the current state of the second application is a hidden state, the device toggles the second application from the hidden state to the revealed state. After toggling the first toggle **72118**, the device redisplays the application-selection area **7224** that includes the plurality of scrollable application-selection affordances (e.g., in response to an input (e.g., at affordance **72130**) to exit the second application-management interface **72116** followed by an input (e.g., at affordance **72134**) to exit the first application-management interface **7270**). In accordance with a determination that the second application is in the revealed state, the device displays a first application-selection affordance that corresponds to the second application in the redisplayed application-selection area, and in accordance with a determination that the second application is in the hidden state, the device foregoes displaying the first application-selection affordance that corresponds to the second application in the redisplayed application-selection area. For example, in response to the fourth input, the stickers application-selection affordance **7232** that was displayed in FIG. **72**R is no longer displayed in FIG. **72**AO.

[1840] Providing a second application-management interface that receives input for toggling between a hidden state and a revealed state of an installed application provides the user with the ability to hide an application in the messaging user interface without deleting the installed application entirely. This makes the user-device interface more efficient and enhances the operability of the device (e.g., the number of inputs required is reduced because the user does not need to provide the input required for uninstalling and/or reinstalling a device when hiding an application is sufficient for the user's needs).

[1841] In some embodiments, the device displays (**7422**), in the second application-management interface **72116**, a plurality of arrangement indicia (examples of which are arrangement controls **72120** and **72131**, Figure AF) that correspond to the plurality of applications that operate within the messaging user interface **7200** of the messaging application. The plurality of arrangement indicia include: a first arrangement indicator **72120** that corresponds to a third application (e.g. a tiny transit application, as indicated by application management listing **72110**) that operates within the messaging interface (e.g., the third application is the same as or different from the second application (see **7314**) that operates within the messaging interface), and a second arrangement indicator **72131** that corresponds to a fourth application (e.g., a reservations application, as indicated by application management listing **7278**) that operates within the messaging interface **7200**. While displaying the second application-management interface **72116**, the device detects a fifth input that includes a movement of a contact on the touch-sensitive surface from a first location (e.g., a location indicated by focus selector **72124** in FIG. **72**AF) that corresponds to the first arrangement indicator **72120** (e.g., the movement of the contact drags the first arrangement indicator such that the first arrangement indicator moves in accordance with the movement of the contact). In response

to detecting the fifth input, in accordance with a determination that movement of the contact on the touch-sensitive surface (e.g., as shown at FIGS. **72**AF-**72**AG) meets rearrangement criteria, the device changes an order of the first arrangement indicator **72120** relative to the second arrangement indicator **72131** (e.g., the order is changed as shown at Figures AF-AJ). In some embodiments, rearrangement criteria include a distance criterion that is met when the movement of the contact increases above a threshold movement distance (e.g., in at least one direction, such as an upward direction or a downward direction.

[1842] Changing an order of the first arrangement indicator relative to the second arrangement indicator in a second application management interface that is distinct from an application area makes the user-device interface more efficient (e.g., by implementing rearrangement of application selection affordances in a location that is separate from the application area, reducing the likelihood of accidental triggering of a rearrangement mode while application selection affordances are displayed in the application area.

[1843] In some embodiments, after changing the order of the first arrangement indicator relative to the second arrangement indicator (e.g., as discussed with regard to **7422** and Figures AF-AJ), the device redisplays (**7424**) the application-selection area **7224** that includes the plurality of scrollable application-selection affordances (e.g., in response to an input (e.g., at affordance **72130**) to exit the second application-management interface **72116** followed by an input (e.g., at affordance **72134**) to exit the first application-management interface **7270**). The device displays, in the redisplayed application-selection area **7224** (FIG. **72**AO) a second application-selection affordance **72126** of the plurality of scrollable application-selection affordances, wherein the second application-selection affordance **72126** corresponds to the third application that operates within the messaging interface **7200**, and a third application-selection affordance **72128** of the plurality of scrollable application-selection affordances, wherein the third application-selection affordance **72128** corresponds to the fourth application that operates within the messaging user interface. An order of the second application-selection affordance **72126** relative to the third application-selection affordance **72128** corresponds to the order of the first arrangement indicator relative to the second arrangement indicator.

[1844] Changing an order of application-selection affordances in response to input for changing the order of a first arrangement indicator relative to a second arrangement indicator gives the user the ability to make the user-device interface more efficient (e.g., by rearranging application-selection affordances to place the most frequently used application-selection affordances within or proximate to a set of pre-selected set of initially displayed application-selection affordances).

[1845] It should be understood that the particular order in which the operations in FIGS. **74**A-**74**D have been described is merely one example and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein are also applicable in an analogous manner to method **7400** described above. For example, the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described above with reference to method **7400** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein. For brevity, these details are not repeated here.

[1846] The operations described above with reference to FIGS. **74**A-**74**D are, optionally, implemented by components depicted in FIGS. **1**A-**1**B. For example, one or more of the operations are optionally implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

[1847] FIGS. **75**A-**75**D are flow diagrams illustrating a method **7500** for translating message content in a messaging application, in accordance with some embodiments. The method **7500** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display and a touch-sensitive surface. In some embodiments, the display is a touch screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **7500** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1848] The device displays (**7502**), on the display (e.g., touch screen **112**) a messaging user interface **7200** (FIG. **72**AP). The messaging user interface includes a conversation transcript **7202** of a messaging session between a user of the electronic device and at least one other user.

[1849] The device (**7504**) receives a first message (e.g., a message displayed within message bubble **72140**) within the messaging session from an electronic device that corresponds to another user included in the messaging session, wherein the first message includes foreign language text **72146** (e.g., text of a language that is different from one or more native languages indicated by one or more language settings of the device).

[1850] In response to receiving the first message, the device displays (**7506**) the first message **72140** in the conversation transcript **7202**.

[1851] The device detects (**7508**) a first input at a first location (e.g., a location indicated by focus selector **72148** of FIG. **72**AP or a location indicated by focus selector **72154**

of FIG. **72**AU) that corresponds to the foreign language text **72146** in the first message. For example, the device detects a gesture by a contact on the foreign language text **72146**, in a message bubble **72140** in which the foreign language text **72146** is displayed, or proximate to a message bubble **72140** in which the foreign language text **72146** is displayed.

[1852] In response to detecting the first input at the first location that corresponds to the foreign language text **72146**, in accordance with a determination that the first input meets translation criteria, the device displays (**7510**) a translation of the foreign language text (e.g., the device replaces display of the foreign language text **72146** with translated text **72150** as shown in FIGS. **72**AQ-**72**R). In some embodiments, all of the foreign language text in the first message is translated. In some embodiments, a portion of the foreign language text in the first message is translated. In some embodiments, the foreign language text has a display characteristic (e.g., a font size, a font color, a font style, a font effect (such as highlighting, underlining, bolding, capitalizing, and/or italicizing) and/or a background color) that is different from a display characteristic of native language text that is displayed in the conversation transcript (e.g., foreign language text **72146** is shown without boldface and translated text **72152** is shown with boldface, as shown in FIGS. **72**AQ-**72**AR). In some embodiments, the foreign language text **72146** is replaced by translated foreign language text **72152**. In some embodiments, the translation **72152** of the foreign language text is displayed alongside the foreign language text **72146**. In accordance with a determination that the first input meets option-display criteria, the device displays a plurality of activatable indicia (e.g., a plurality of activatable indicia include one or more acknowledgement options and a translation option **72180** in an acknowledgement platter **72178** (FIG. **72**BQ) and/or a plurality of activatable indicia include one or more action items in a menu **72156** (FIG. **72**BE) that includes an option **72158** which, when activated, causes display of a translation of the foreign language text **72146**. In some embodiments, in accordance with a determination that the first input does not meet the translation criteria and does not meet the option-display criteria, the electronic device continues to display the foreign language text **72146** in the first message (e.g., in message bubble **72140**). This heuristic allows input at a location that corresponds to foreign language text to either cause a translated version of message text to be displayed (e.g., without having to find and activate a translation option in a menu) or to cause a plurality of activatable indicia to be displayed (e.g., to enable access to additional actions). This heuristic for input at a location that corresponds to foreign language text enhances the operability of the device and makes the user-device interface more efficient (e.g., by providing for translation directly, as well as providing for other options) which, also reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

[1853] In some embodiments, the electronic device includes a touch-sensitive surface and one or more sensors configured to detect intensities of contacts with the touch-sensitive surface, and detecting the input at the first location that corresponds to the foreign language text includes (**7512**) detecting a contact on the touch-sensitive surface (e.g., a contact at a location indicated by focus selector **72148**, FIG. **72**AP, or at a location indicated by focus selector **72154**, FIG. **72**AU). The determination that the first input meets translation criteria includes a determination that the contact lifts off from the touch-sensitive surface before option-display criteria are met (e.g., the translation intensity criteria are met when a tap input is received, for example as shown in FIGS. **72**AR-**72**AQ). The determination that the first input meets option-display criteria includes a determination that the characteristic intensity of the contact with the touch-sensitive surface meets option-display intensity criteria (e.g., the option-display intensity criteria are met when the characteristic intensity of the contact increases above a second intensity threshold, such as a light press intensity threshold level IT_L or a deep press intensity threshold IT_D), e.g., as shown in FIGS. **72**AU-**72**AV.

[1854] Using contact intensity criteria at a location that corresponds to foreign language text to be used to either cause a translated version of a text message to be displayed (e.g., without having to find and activate a translation option in a menu) or cause a plurality of activatable indicia to be displayed (e.g., to enable access to additional actions) enhances the operability of the device and makes the user-device interface more efficient (e.g., by providing for translation directly, as well as providing for other options).

[1855] In some embodiments, the electronic device includes a touch-sensitive surface and detecting the input at the first location that corresponds to the foreign language text includes (**7514**) detecting a contact on the touch-sensitive surface (e.g., a contact at a location indicated by focus selector **72186** in FIG. **72**BU-**2** or a contact at a location indicated by focus selector **72188** in FIG. **72**BV-**2**). The determination that the first input meets translation criteria includes a determination that the contact lifts off from the touch-sensitive surface before translation duration criteria are met (e.g., the input is a tap input, for example as shown in FIGS. **72**BU-**2** to **72**BU-**4**.) The determination that the first input meets option-display criteria includes a determination that a duration of the contact on the touch-sensitive surface meets option display duration criteria (e.g., the option display duration criteria are met when the duration of the contact satisfies a duration threshold, such as a long press duration threshold, for example as shown in FIGS. **72**BV-**2** to **72**BV-**4**).

[1856] Using contact duration criteria to either cause a translated version of a text message to be displayed (e.g., without having to find and activate a translation option in a menu) or cause a plurality of activatable indicia to be displayed (e.g., to enable access to additional actions) enhances the operability of the device and makes the user-device interface more efficient (e.g., by providing for translation directly, as well as providing for other options).

[1857] In some embodiments, the electronic device includes a touch-sensitive surface **112** and one or more sensors configured to detect proximity of an input object **72192** above the touch-sensitive surface **112**, and detecting the input at the first location that corresponds to the foreign language text includes (**7516**) detecting input (e.g., input at a location indicated by focus selector **72190**, FIG. **72**BW) by the input object **72192**. The determination that the first input meets translation criteria includes a determination that the input by the input object **72192** meets hover proximity criteria. For example, the hover proximity criteria are met when the input object **72192** is within a hover proximity range above the touch-sensitive surface **112** (e.g., the distance **72196** between input object **72192** and touch screen **112** decreases below a threshold hover distance, as shown in

FIG. **72**BX), and the input object **72192** is not in contact with the touch-sensitive surface. In some embodiments, when the translation criteria include hover proximity criteria, the option-display criteria are met when the duration of a contact with the touch-sensitive surface exceeds a duration threshold (e.g., such as a tap threshold or a long press duration threshold), the characteristic intensity of the contact increases above a threshold intensity level (e.g., a light press intensity threshold IT_Lor a deep press intensity threshold IT_D); or a contact with the touch-sensitive surface lifts off, subsequently touches down at the location that corresponds to the foreign language text, and then lifts off again within a duration of time that meets double-tap criteria.

[1858] In some embodiments, the determination that the first input meets translation criteria includes a determination (**7518**) that a focus selector (e.g., focus selector **72200**, FIG. **72**CP) that corresponds to the first input moved to the first location that corresponds to the foreign language text **72146** from a second location that corresponds to another part of the foreign language text **72146** in the first message (e.g., focus selector **72200** moves from a first location as shown in FIG. **72**CP to a second location as shown in FIG. **72**CR). In some embodiments, the foreign language text between the first location and the second location is translated (e.g., less than all of the foreign language text **72146** in the first message is translated, as shown in FIG. **72**CS). In some embodiments, all of the foreign language text in the first message is translated. In some embodiments, all of a contiguous section of foreign language text (e.g., less than all of the foreign language text in the first message) at or proximate to the first location is translated. Translating text at locations that a finger (or other contact) moves over can help a user learn the foreign language text.

[1859] In some embodiments, displaying the translation of the foreign language text in accordance with the determination that the first input meets translation criteria includes displaying (**7520**) a translation of a first portion of the foreign language text (e.g., portion **72210** includes a single translated word that corresponds to portion **72208** of foreign language text **72146** as shown in FIG. **72**CV). While displaying the translation of the first portion **72210** of the foreign language text **72146**, the device detects movement of a focus selector **72206** that corresponds to the first input (e.g., a pointer input, a contact with a touch sensitive surface, or an input by an input object that meets hover proximity criteria) to a second location (e.g., as shown by focus selector **72206** in FIG. **72**CX) that corresponds to another part of the foreign language text. In response to detecting the movement of the focus selector to the second location, the device displays a translation of a second portion of the foreign language text (e.g., portion **72210** includes multiple translated words that correspond to portion **72208** of foreign language text **72146**, as shown in FIG. **72**CX). In some embodiments, the second portion includes the first portion (e.g., the translation of the foreign language text is gradually revealed as the input moves). In some embodiments, the second portion is distinct from the first portion (e.g., a portion of the translated foreign language text is temporarily revealed as the input moves).

[1860] Progressively revealing translated text in a message in response to movement of a focus selector allows a translation of a portion of foreign language text to be displayed while leaving a portion of the foreign language text untranslated if desired. Displaying the translation in this manner enhances the privacy provided by the device (e.g., by continuing to display an untranslated version of a portion of the foreign language text, which provides security when the foreign language text cannot be read by other people in the vicinity of the device.

[1861] In some embodiments, the device receives (**7522**) a second message (e.g., a message displayed within message bubble **72142**) within the messaging session. In accordance with a determination that the second message includes foreign language text and in accordance with a determination that the option-display criteria are met, the device displays, in a plurality of activatable indicia, an activatable indicator which, when activated, causes display of a translation of the foreign language text in the second message (e.g., as described with regard to **7510** and option **72158** of FIG. **72**BE). In accordance with a determination that the second message does not include foreign language text and in accordance with a determination that the option-display criteria are met, the device displays a plurality of activatable indicia, without displaying the activatable indicator (e.g., as shown in FIG. **72**BJ). In some embodiments, the electronic device determines whether a received message includes foreign language text. In some embodiments, a device that is remote from the electronic device (e.g., a server that supports messaging functions) determines whether the received message includes foreign language text.

[1862] Automatically including an activatable indicator for displaying translated foreign language text in a displayed plurality of activatable indicia (e.g., a menu or an acknowledgements platter) provides an additional control option for translation without consuming space among the plurality of activatable indicia when the translation option is not needed. This heuristic enhances the operability of the device and makes the user-device interface more efficient (e.g., by reducing display space consumed by the plurality of activatable indicia and eliminating unintended selection of a translation control when no foreign language text is present in a message.)

[1863] In some embodiments, while displaying the translation **72150** of the foreign language text (e.g., as shown in FIG. **72**DB), the device determines (**7524**) whether the translation of the foreign language text meets translation-display-cessation criteria (e.g., determining whether a characteristic intensity of the contact in the first input decreases below an first intensity threshold level (such as light press intensity threshold level IT_L) without increasing above a second intensity threshold level (such as deep press intensity threshold level IT_D) before liftoff of the contact from the touch sensitive surface, determining whether an amount of time since the translated foreign language text was displayed exceeds a threshold time limit, and/or determining whether a contact in the first input has lifted off from the touch sensitive surface). In accordance with a determination that the displayed translation of the foreign language text meets the translation-display-cessation criteria (e.g., as shown in FIGS. **72**DB-**72**DC), the device ceases to display the translation of the foreign language text and re-displaying the corresponding foreign language text. In accordance with a determination that the displayed translation of the foreign language text does not meet the translation-display-cessation criteria, the device continues to display the translation of the foreign language text (e.g., as shown in Figures DE-DI).

[1864] In some embodiments, translated foreign language text is displayed in response to an input by a contact that meets characteristic intensity criteria and/or contact duration criteria, and the translated foreign language text ceases to be displayed when the contact lifts off of the touch-sensitive surface. For example, when translation of messages is used for language learning, a user may wish to redisplay an untranslated version of the foreign language text to facilitate learning the connection between the translated and untranslated text.

[1865] In some embodiments, the one or more activatable indicia include an option to display the translated foreign language text for a predefined duration of time. In some embodiments, in accordance with a determination that the option to display the translated foreign language text for a predefined duration of time is selected, the translated foreign language text is displayed, and after the predefined duration of time, the translated foreign language text reverts to untranslated foreign language text.

[1866] Automatically re-displaying the foreign language text when translation-display-cessation criteria are met allows the untranslated foreign language text to be re-displayed without requiring further user input following the input that displayed the translation. Automatically re-displaying untranslated foreign language text without requiring additional user input makes the user-device interface more efficient by reducing the number of inputs required to operate the device.}

[1867] In some embodiments, while displaying the translation **72146** of the foreign language text, the device detects (**7526**) a second input (e.g., by a contact at a location indicated by focus selector **72148**, as shown in FIG. **72**AS) at a third location that corresponds to the translation **72150** of the foreign language text (e.g., a location that is the same as the first location, the same as the second location, or distinct from the first location and the second location). In response to detecting the second input at the third location that corresponds to the translated foreign language text **72150**, in accordance with a determination that the second input meets re-display criteria, the device ceases to display the translation **72150** of the foreign language text and re-displays the corresponding foreign language text **72146** (e.g., as shown in FIGS. **72**AS-**72**AT. In some embodiments, the same type of input used for displaying the translation of the foreign language text is used to re-display the original, untranslated foreign language text. In some embodiments, displaying the translation of the foreign language text is irreversible.

[1868] In some embodiments, while displaying the translation of the foreign language text, the device detects (**7528**) a third input at a fourth location (e.g., a location indicated by focus selector **72164** of FIG. **72**BC) that corresponds to the translation **72150** of the foreign language text (e.g., a location that is the same as the first location, the same as the second location, the same as the third location, or distinct from the first, second, and third locations). In response to detecting the third input at the fourth location that corresponds to the translation **72150** of the foreign language text, in accordance with a determination that the third input meets the option-display criteria, displaying a plurality of activatable indicia (e.g., the action items displayed in menu **72156**), wherein the plurality of activatable indicia include an activatable indicator **72158** which, when activated, causes re-display of the original, un-translated foreign language text **72146** (e.g., as shown in FIGS. **72**BB-**72**BF.

[1869] Displaying an activatable indicator for re-displaying the foreign language text in response to user input allows the un-translated foreign language text to be re-displayed with controls that are displayed as needed, without ongoing display of additional controls for undoing a previously performed translation. This enhances the operability of the device and makes the user-device interface more efficient (e.g., by providing added functionality to a messaging user interface without reducing space available to display message content in the messaging user interface).

[1870] It should be understood that the particular order in which the operations in FIGS. **75**A-**75**D have been described is merely one example and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein are also applicable in an analogous manner to method **7500** described above. For example, the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described above with reference to method **7500** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein. For brevity, these details are not repeated here.

[1871] The operations described above with reference to FIGS. **75**A-**75**D are, optionally, implemented by components depicted in FIGS. **1**A-**1**B. For example, one or more of the operations are optionally implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

[1872] FIGS. **76**A-**76**C are flow diagrams illustrating a method **7600** for translating message content in a messaging application, in accordance with some embodiments. The method **7600** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1**A) with a display and a touch-sensitive surface. In some embodiments, the display is a touch screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from

the touch-sensitive surface. Some operations in method **7600** are, optionally, combined and/or the order of some operations is, optionally, changed.

[1873] The device displays (**7602**), by a display (e.g., touch screen **112**), a messaging user interface **7200** (FIG. **72**AP) on the display. The messaging user interface includes a conversation transcript **7202** of a messaging session between a user of the electronic device and at least one other user.

[1874] The device receives (**7604**) a first message (e.g., a message displayed within message bubble **72140**) within the messaging session from an electronic device that corresponds to another user included in the messaging session, wherein the first message includes foreign language text **72146** (e.g., text of a language that is different from one or more native languages indicated by one or more language settings of the device).

[1875] In response to receiving the first message, the device displays (**7606**) the first message **72140** in the conversation transcript **7202**.

[1876] The device detects (**7608**) a first input at a location (e.g., a location indicated by focus selector **72148** of FIG. **72**AP or a location indicated by focus selector **72154** of FIG. **72**AU) that corresponds to the foreign language text **72146** in the first message. For example, the device detects a gesture by a contact on the foreign language text **72146**, in a message bubble **72140** in which the foreign language text **72146** is displayed, or proximate to a message bubble **72140** in which the foreign language text **72146** is displayed.

[1877] In response to detecting the first input at the location that corresponds to the foreign language text **72146**, in accordance with a determination that the first input meets translation criteria, the device performs (**7610**) a foreign-language-text-translation action (e.g., displaying a menu **72156** (FIG. **72**BE) or platter **72178** (FIG. **72**BQ) that includes an activatable option (e.g., option **72158** of menu **72156** or option **72180** of platter **72178**) to translate the foreign language text, translating the foreign language text **72146**, and/or displaying the translation **72150** of the foreign language text). In accordance with a determination that the first input does not meet the translation criteria, the device forgoes performance of the foreign-language-text-translation action.

[1878] Translating and/or displaying foreign language text in response to user input received at a location that corresponds to foreign language text in a received message allows translated text to be displayed without displaying additional controls for obtaining the translation. Providing an activatable option to translate foreign language text without ongoing display of additional controls for translation enhances the operability of the device and makes the user-device interface more efficient (e.g., by providing added functionality to a messaging user interface without constantly reducing the space available to display message content in the messaging user interface), which also reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

[1879] In some embodiments, the electronic device includes (**7612**) a touch-sensitive surface **112** and one or more sensors configured to detect intensities of contacts with the touch-sensitive surface **112**. In some embodiments, detecting the first input at the first location (e.g., a location indicated by focus selector **72190**, FIG. **72**DC) that corresponds to the foreign language text **72146** includes detecting a contact on the touch-sensitive surface. In accordance with a determination that the first input meets temporary-translation-display criteria (e.g., criteria that are met when a characteristic intensity of the contact in the first input decreases below an first intensity threshold level (such as light press intensity threshold level IT_L) without increasing above a second intensity threshold level (such as deep press intensity threshold level IT_D) before liftoff of the contact from the touch sensitive surface) performing the foreign-language-text-translation action includes temporarily displaying a translation of the foreign language text (e.g., as shown in FIGS. **72**DA-**72**DC). In some embodiments, when temporary-translation-display criteria are met, the translated foreign language text **72150** is displayed temporarily (e.g., for a predetermined amount of time, until a subsequent input meeting foreign language text re-display criteria is received, or until a contact lifts off) after which the original, untranslated foreign language text **72146** is re-displayed.

[1880] In some embodiments, in accordance with a determination that the first input meets fixed-translation-display criteria, performing the foreign-language-text-translation action includes (**7614**) fixedly replacing display of the foreign language text **72146** with the translation **72150** of the foreign language text (e.g., as shown at FIGS. **72**DD-**72**DI). In some embodiments, the translated foreign language text is displayed fixedly (e.g., for the subsequent time during which the first message is displayed in the messaging session). In some embodiments, contact intensity criteria are used to determine whether the input meets temporary-translation-display criteria and the translation is displayed temporarily, or whether the input meets fixed-translation-display criteria and the translation is displayed fixedly. For example, the translation is displayed temporarily in response to a light press (e.g., as shown at FIGS. **72**CY-**72**DD) and the translation is displayed fixedly in response to a deep press (e.g., as shown at FIGS. **72**DD-**72**DI), or vice versa.

[1881] Using contact intensity criteria to determine whether to temporarily or fixedly display a translation of foreign language text in a message allows a single input by a contact to be used for either temporary display or fixed display of a translation. Enabling multiple possible operations in response to a single input by a contact enhances the operability of the device and makes the user-device interface more efficient, which also reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

[1882] In some embodiments, the determination that the first input meets the fixed-translation-display criteria includes (**7616**) a determination that a characteristic intensity of the contact on the touch-sensitive surface meets fixed translation intensity criteria (e.g., as described with regard to FIGS. **72**DD-**72**DI). In some embodiments, the fixed translation intensity criteria are met when the characteristic intensity of the contact increases above a second intensity threshold, such as a deep press intensity threshold IT_D.

[1883] In some embodiments, the determination that the first input meets the fixed-translation-display criteria includes (**7618**) a determination that the duration of the contact on the touch-sensitive surface meets fixed translation duration criteria. In some embodiments, the fixed translation duration criteria are met when the duration of the contact increases above a time threshold, such as a long press duration threshold.

[1884] In some embodiments, performing the foreign-language-text-translation action includes (**7620**): displaying a translation **72150** of the foreign language text; determining whether lift-off of the contact from the touch-sensitive surface has occurred; and, in response to detecting lift-off of the contact from the touch-sensitive surface, ceasing to display the translation **72150** of the foreign language text (and, in some embodiments, re-displaying foreign language text **72146**).

[1885] Ceasing to display translated foreign language text in response to detecting lift-off of the contact from the touch-sensitive surface provides an additional control option without cluttering the messaging user interface with additional displayed controls. Providing additional control options without cluttering the messaging UI enhances the operability of the device and makes the user-device interface more efficient (e.g., by providing added functionality to a messaging user interface without reducing space available to display message content in the messaging user interface.)

[1886] In some embodiments, performing the foreign-language-text-translation action includes displaying (**7622**), over the conversation transcript, (e.g., in a location that corresponds to the displayed first message, such as partially overlaying the first message or proximate to the first message) a platter **72178** (FIG. **72**BQ) that includes a plurality of activatable indicia (e.g., an acknowledgement options menu for responding to a received message, with options such as a heart, thumbs up, and thumbs down), wherein the plurality of activatable indicia includes a translation indicator **72180** which, when activated, causes display of a translation for at least a portion of the foreign language text.

[1887] Displaying an activatable indicator for translating at least a portion of the foreign language text in response to user input allows translated foreign language text to be displayed with controls that are displayed as needed, without ongoing display of additional controls for performing a translation. Providing an activatable option to translate foreign language text without ongoing display of additional controls for translation enhances the operability of the device and makes the user-device interface more efficient (e.g., by providing added functionality to a messaging user interface without constantly reducing space available to display message content in the messaging user interface).}

[1888] In some embodiments, the electronic device includes (**7624**) a touch-sensitive surface **112** and one or more sensors configured to detect proximity of an input object **72192** above the touch-sensitive surface **112** (e.g., as shown in FIGS. **72**BW-**72**BX), detecting the input at the first location (e.g., a location indicated by focus selector **72190**) that corresponds to the foreign language text **72146** includes detecting input by the input object **72192**; and the determination that the first input meets translation criteria includes a determination that the input by the input object meets hover proximity criteria (e.g., the distance between **72192** and touch screen **112** decreases below the threshold hover distance, as shown in FIG. **72**BX). In some embodiments, the hover proximity criteria are met when the input object is within a threshold hover distance above the touch-sensitive surface and is not in contact with the touch-sensitive surface **112**.

[1889] In some embodiments, the determination that the first input meets translation criteria includes (**7626**) a determination that a focus selector (e.g., focus selector **72200**, FIG. **72**CP) that corresponds to the first input moved to the first location that corresponds to the foreign language text **72146** from a second location that corresponds to another part of the foreign language text **72146** (e.g., focus selector **72200** moves from a first location as shown in FIG. **72**CP to a second location as shown in FIG. **72**CR). In some embodiments, the foreign language text between the first location and the second location is translated (e.g., less than all of the foreign language text in the first message is translated). In some embodiments, all of the foreign language text in the first message is translated. In some embodiments, all of a contiguous section of foreign language text (e.g., less than all of the foreign language text in the first message) at or proximate to the first location is translated. Translating text at locations that a finger (or other contact) moves over can help a user learn the foreign language text.

[1890] In some embodiments, displaying the translation of the foreign language text in accordance with the determination that the first input meets translation criteria includes displaying (**7628**) a translation of a first portion of the foreign language text (e.g., portion **72210** includes a single translated word that corresponds to portion **72208** of foreign language text **72146** as shown in FIG. **72**CV). While displaying the translation of the first portion **72210** of the foreign language text **72146**, the device detects (**7628**) movement of a focus selector **72206** that corresponds to the first input (e.g., a pointer input, a contact with a touch sensitive surface, or an input by an input object that meets hover proximity criteria) to a second location (e.g., as shown by focus selector **72206** in FIG. **72**CX) that corresponds to another part of the foreign language text. In response to detecting the movement of the focus selector to the second location, the device displays a translation of a second portion of the foreign language text (e.g., portion **72210** includes multiple translated words that correspond to portion **72208** of foreign language text **72146**, as shown in FIG. **72**CX). In some embodiments, the second portion includes the first portion (e.g., the translation of the foreign language text is gradually revealed as the input moves). In some embodiments, the second portion is distinct from the first portion (e.g., the translated foreign language text is temporarily revealed as the input moves).

[1891] Progressively revealing translated text in a message in response to movement of a focus selector allows a translation of a portion of foreign language text to be displayed while leaving a portion of the foreign language text untranslated if desired. Displaying the translation in this manner enhances the privacy provided by the device (e.g., by continuing to display an untranslated version of a portion of the foreign language text, which provides security when the foreign language text cannot be read by other people in the vicinity of the device.)

[1892] It should be understood that the particular order in which the operations in FIGS. **76**A-**76**C have been described is merely one example and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein are also applicable in an analogous manner to method **7600** described above. For example, the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described above with reference to method **7600** optionally have one or more of the character-

istics of the contacts, gestures, user interface objects, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein. For brevity, these details are not repeated here.

[1893] The operations described above with reference to FIGS. **76**A-**76**D are, optionally, implemented by components depicted in FIGS. **1**A-**1**B. For example, one or more of the operations are optionally implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1**A-**1**B.

[1894] The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. However, the illustrative discussions above are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the invention and its practical applications, to thereby enable others skilled in the art to best use the invention and various described embodiments with various modifications as are suited to the particular use contemplated.

What is claimed is:

1. A method, comprising:

at an electronic device having one or more processors, memory, a touch-sensitive surface, a digital camera, and a display:

displaying a messaging user interface on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a message-input area, at least one avatar corresponding to a first other user included in the messaging session, and an application affordance;

while displaying the messaging user interface, detecting a first input on the touch sensitive surface;

in response to detecting the first input:

in accordance with a determination that the first input corresponds to selection of the at least one avatar displayed in the messaging user interface, displaying a menu that contains a plurality of activatable menu items associated with the at least one avatar overlaid on the messaging user interface; and

in accordance with a determination that the first input corresponds to selection of the application affordance, displaying a plurality of application launch icons for a plurality of corresponding applications within the messaging user interface, wherein activation of a respective application launch icon in the plurality of application launch icons causes a corresponding application to be displayed within the messaging user interface, and wherein displaying the plurality of application launch icons for the plurality of corresponding applications within the messaging user interface includes:

in accordance with a determination that the messaging user interface included display of a keyboard at the time the first input was detected, displaying the plurality of application launch icons while maintaining display of the message-input area at a location at which it was displayed prior to detecting the first input; and

in accordance with a determination that the messaging user interface did not include display of a keyboard at the time the first input was detected, displaying the conversation transcript in a first area of the display and shifting the message-input area in a first direction in order to display the plurality of application launch icons in a second area of the display, distinct from the first area.

2. The method of claim **1**, wherein in response to detecting the first input:

in accordance with a determination that the first input corresponds to selection of a digital image affordance, displaying a plurality of digital images within the messaging user interface, wherein displaying the plurality of digital images within the messaging user interface includes:

in accordance with a determination that the messaging user interface included display of a keyboard at the time the first input was detected, replacing display of the keyboard with the display of the plurality of digital images; and

in accordance with a determination that the messaging user interface did not include display of a keyboard at the time the first input was detected, displaying the conversation transcript in a first area of the display and displaying the plurality of digital images in a second area of the display.

3. The method of claim **2**, including:

while displaying the plurality of digital images, detecting an input that selects a digital image in the plurality of digital images; and

after detecting the input that selects a digital image in the plurality of digital images:

displaying the selected digital image in the conversation transcript; and

transmitting a representation of the selected digital image to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the selected digital image in a conversation transcript that corresponds to the messaging session.

4. The method of claim **1**, wherein in response to detecting the first input:

in accordance with a determination that the first input corresponds to selection of a digital canvas affordance, displaying a digital drawing canvas within the messaging user interface.

5. The method of claim **1**, including:

while displaying the plurality of application launch icons for the plurality of corresponding applications, detecting an input that activates a launch icon in the plurality of application launch icons for the plurality of corresponding applications; and

after detecting the input that activates the launch icon in the plurality of application launch icons for the plurality of corresponding applications:

displaying a first input area for an application corresponding to the activated launch icon that is distinct from the message input area, the first input area including one or more input affordances;

displaying a first application object within the conversation transcript that corresponds to the application corresponding to the activated launch icon; and

transmitting a representation of a second application object that corresponds to the application corresponding to the activated launch icon to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the second application object in a conversation transcript that corresponds to the messaging session.

6. The method of claim **1**, wherein the messaging user interface also includes a microphone affordance, configured to enable sound recording on the electronic device upon activation.

7. The method of claim **1**, wherein the menu that contains activatable menu items associated with the at least one avatar includes:

a menu item that when activated initiates a digital touch action with the first other user,

a menu item that when activated initiates messaging with only the first other user,

a menu item that when activated initiates an email with the first other user,

a menu item that when activated initiates a call with the first other user,

a menu item that when activated initiates a video conference with the first other user, and/or

a menu item that when activated initiates a payment action with the first other user.

8. The method of claim **2**, including:

detecting a first swipe gesture that starts while a focus selector is at a first location in the messaging user interface that corresponds to a first digital image in the plurality of digital images, the first swipe gesture moving the focus selector in a first direction;

in response to detecting the first swipe gesture, scrolling display of the plurality of digital images in the first direction on the display;

detecting a second swipe gesture that starts while a focus selector is at a second location in the messaging user interface that corresponds to a second digital image in the plurality of digital images, the second swipe gesture moving the focus selector in a second direction, opposite the first direction; and

in response to detecting the second swipe gesture, displaying a first affordance for the digital camera and a second affordance for a photo library.

9. The method of claim **8**, including:

while displaying the first affordance for the digital camera:

detecting an input that activates the first affordance for the digital camera; and,

in response to detecting the input that activates the first affordance for the digital camera, displaying a user interface for the digital camera over at least a portion of the messaging user interface.

10. The method of claim **8**, including:

while displaying the second affordance for the photo library:

detecting an input that activates the second affordance for the photo library; and

in response to detecting the input that activates the second affordance for the photo library:

ceasing to display the plurality of digital images including one or more digital images stored in the memory and a live preview image from the digital camera and

displaying a plurality of digital images from a digital photo library; and

while displaying the plurality of digital images from the digital photo library:

detecting an input that selects a digital image in the plurality of digital images from the digital photo library; and

in response to detecting the input that selects the digital image from the digital photo library:

displaying the digital image from the digital photo library in the conversation transcript, and

transmitting a representation of the digital image from the digital photo library to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the digital image from the digital photo library in a conversation transcript that corresponds to the messaging session.

11. An electronic device, comprising:

a display;

a touch-sensitive surface;

one or more processors;

memory; and

one or more programs, wherein the one or more programs are stored in the memory and configured to be executed by the one or more processors, the one or more programs including instructions for:

displaying a messaging user interface on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a message-input area, at least one avatar corresponding to a first other user included in the messaging session, and an application affordance;

while displaying the messaging user interface, detecting a first input on the touch sensitive surface;

in response to detecting the first input:

in accordance with a determination that the first input corresponds to selection of the at least one avatar displayed in the messaging user interface, displaying a menu that contains a plurality of activatable

menu items associated with the at least one avatar overlaid on the messaging user interface; and

in accordance with a determination that the first input corresponds to selection of the application affordance, displaying a plurality of application launch icons for a plurality of corresponding applications within the messaging user interface, wherein activation of a respective application launch icon in the plurality of application launch icons causes a corresponding application to be displayed within the messaging user interface, and wherein displaying the plurality of application launch icons for the plurality of corresponding applications within the messaging user interface includes:

in accordance with a determination that the messaging user interface included display of a keyboard at the time the first input was detected, displaying the plurality of application launch icons while maintaining display of the message-input area at a location at which it was displayed prior to detecting the first input; and

in accordance with a determination that the messaging user interface did not include display of a keyboard at the time the first input was detected, displaying the conversation transcript in a first area of the display and shifting the message-input area in a first direction in order to display the plurality of application launch icons in a second area of the display, distinct from the first area.

12. The electronic device of claim **11**, wherein the one or more programs include instructions for, in response to detecting the first input:

in accordance with a determination that the first input corresponds to selection of a digital image affordance, displaying a plurality of digital images within the messaging user interface, wherein displaying the plurality of digital images within the messaging user interface includes:

in accordance with a determination that the messaging user interface included display of a keyboard at the time the first input was detected, replacing display of the keyboard with the display of the plurality of digital images; and

in accordance with a determination that the messaging user interface did not include display of a keyboard at the time the first input was detected, displaying the conversation transcript in a first area of the display and displaying the plurality of digital images in a second area of the display.

13. The electronic device of claim **12**, wherein the one or more programs include instructions for:

while displaying the plurality of digital images, detecting an input that selects a digital image in the plurality of digital images; and

after detecting the input that selects a digital image in the plurality of digital images:

displaying the selected digital image in the conversation transcript; and

transmitting a representation of the selected digital image to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the selected digital image in a conversation transcript that corresponds to the messaging session.

14. The electronic device of claim **11**, wherein the one or more programs include instructions for, in response to detecting the first input:

in accordance with a determination that the first input corresponds to selection of a digital canvas affordance, displaying a digital drawing canvas within the messaging user interface.

15. The electronic device of claim **11**, wherein the one or more programs include instructions for:

while displaying the plurality of application launch icons for the plurality of corresponding applications, detecting an input that activates a launch icon in the plurality of application launch icons for the plurality of corresponding applications; and

after detecting the input that activates the launch icon in the plurality of application launch icons for the plurality of corresponding applications:

displaying a first input area for an application corresponding to the activated launch icon that is distinct from the message input area, the first input area including one or more input affordances;

displaying a first application object within the conversation transcript that corresponds to the application corresponding to the activated launch icon; and

transmitting a representation of a second application object that corresponds to the application corresponding to the activated launch icon to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the second application object in a conversation transcript that corresponds to the messaging session.

16. The electronic device of claim **11**, wherein the messaging user interface also includes a microphone affordance, configured to enable sound recording on the electronic device upon activation.

17. The electronic device of claim **11**, wherein the menu that contains activatable menu items associated with the at least one avatar includes:

a menu item that when activated initiates a digital touch action with the first other user,

a menu item that when activated initiates messaging with only the first other user,

a menu item that when activated initiates an email with the first other user,

a menu item that when activated initiates a call with the first other user,

a menu item that when activated initiates a video conference with the first other user, and/or

a menu item that when activated initiates a payment action with the first other user.

18. The electronic device of claim **12**, wherein the one or more programs include instructions for:

detecting a first swipe gesture that starts while a focus selector is at a first location in the messaging user interface that corresponds to a first digital image in the plurality of digital images, the first swipe gesture moving the focus selector in a first direction;

in response to detecting the first swipe gesture, scrolling display of the plurality of digital images in the first direction on the display;

detecting a second swipe gesture that starts while a focus selector is at a second location in the messaging user interface that corresponds to a second digital image in the plurality of digital images, the second swipe gesture moving the focus selector in a second direction, opposite the first direction; and

in response to detecting the second swipe gesture, displaying a first affordance for the digital camera and a second affordance for a photo library.

19. The electronic device of claim **18**, wherein the one or more programs include instructions for:

while displaying the first affordance for the digital camera:

detecting an input that activates the first affordance for the digital camera; and,

in response to detecting the input that activates the first affordance for the digital camera, displaying a user interface for the digital camera over at least a portion of the messaging user interface.

20. The electronic device of claim **18**, wherein the one or more programs include instructions for:

while displaying the second affordance for the photo library:

detecting an input that activates the second affordance for the photo library; and

in response to detecting the input that activates the second affordance for the photo library:

ceasing to display the plurality of digital images including one or more digital images stored in the memory and a live preview image from the digital camera and

displaying a plurality of digital images from a digital photo library; and

while displaying the plurality of digital images from the digital photo library:

detecting an input that selects a digital image in the plurality of digital images from the digital photo library; and

in response to detecting the input that selects the digital image from the digital photo library:

displaying the digital image from the digital photo library in the conversation transcript, and

transmitting a representation of the digital image from the digital photo library to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the digital image from the digital photo library in a conversation transcript that corresponds to the messaging session.

21. A non-transitory computer readable storage medium storing one or more programs, the one or more programs comprising instructions, which when executed by an electronic device with a display and a touch-sensitive surface, cause the device to:

display a messaging user interface on the display, the messaging user interface including a conversation transcript of a messaging session between a user of the electronic device and at least one other user, a message-input area, a digital image affordance, a digital touch affordance, and an application affordance;

while displaying the messaging user interface, detect a first input on the touch sensitive surface;

in response to detecting the first input:

in accordance with a determination that the first input corresponds to selection of the at least one avatar displayed in the messaging user interface, displaying a menu that contains a plurality of activatable menu items associated with the at least one avatar overlaid on the messaging user interface; and

in accordance with a determination that the first input corresponds to selection of the application affordance, displaying a plurality of application launch icons for a plurality of corresponding applications within the messaging user interface, wherein activation of a respective application launch icon in the plurality of application launch icons causes a corresponding application to be displayed within the messaging user interface, and wherein displaying the plurality of application launch icons for the plurality of corresponding applications within the messaging user interface includes:

in accordance with a determination that the messaging user interface included display of a keyboard at the time the first input was detected, displaying the plurality of application launch icons while maintaining display of the message-input area at a location at which it was displayed prior to detecting the first input; and

in accordance with a determination that the messaging user interface did not include display of a keyboard at the time the first input was detected, displaying the conversation transcript in a first area of the display and shifting the message-input area in a first direction in order to display the plurality of application launch icons in a second area of the display, distinct from the first area.

22. The non-transitory computer readable storage medium of claim **21**, wherein the one or more programs comprise instructions that cause the device to, in response to detecting the first input:

in accordance with a determination that the first input corresponds to selection of a digital image affordance, displaying a plurality of digital images within the messaging user interface, wherein displaying the plurality of digital images within the messaging user interface includes:

in accordance with a determination that the messaging user interface included display of a keyboard at the time the first input was detected, replacing display of the keyboard with the display of the plurality of digital images; and

in accordance with a determination that the messaging user interface did not include display of a keyboard at the time the first input was detected, displaying the conversation transcript in a first area of the display and displaying the plurality of digital images in a second area of the display.

23. The non-transitory computer readable storage medium of claim **22**, wherein the one or more programs comprise instructions that cause the device to:

while displaying the plurality of digital images, detect an input that selects a digital image in the plurality of digital images; and

after detecting the input that selects a digital image in the plurality of digital images:

display the selected digital image in the conversation transcript; and

transmit a representation of the selected digital image to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the selected digital image in a conversation transcript that corresponds to the messaging session.

24. The non-transitory computer readable storage medium of claim **21**, wherein the one or more programs comprise instructions that cause the device to, in response to detecting the first input:

in accordance with a determination that the first input corresponds to selection of a digital canvas affordance, display a digital drawing canvas within the messaging user interface.

25. The non-transitory computer readable storage medium of claim **21**, wherein the one or more programs comprise instructions that cause the device to:

detect an input that activates a launch icon in the plurality of application launch icons for the plurality of corresponding applications while displaying the plurality of application launch icons for the plurality of corresponding applications; and

after detecting the input that activates the launch icon in the plurality of application launch icons for the plurality of corresponding applications:

display a first input area for an application corresponding to the activated launch icon that is distinct from the message input area, the first input area including one or more input affordances;

display a first application object within the conversation transcript that corresponds to the application corresponding to the activated launch icon; and

transmit a representation of a second application object that corresponds to the application corresponding to the activated launch icon to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the second application object in a conversation transcript that corresponds to the messaging session.

26. The non-transitory computer readable storage medium of claim **21**, wherein the messaging user interface also includes a microphone affordance, configured to enable sound recording on the electronic device upon activation.

27. The non-transitory computer readable storage medium of claim **21**, wherein the menu that contains activatable menu items associated with the at least one avatar includes:

a menu item that when activated initiates a digital touch action with the first other user,

a menu item that when activated initiates messaging with only the first other user,

a menu item that when activated initiates an email with the first other user,

a menu item that when activated initiates a call with the first other user,

a menu item that when activated initiates a video conference with the first other user, and/or

a menu item that when activated initiates a payment action with the first other user.

28. The non-transitory computer readable storage medium of claim **22**, wherein the one or more programs comprise instructions that cause the device to:

detect a first swipe gesture that starts while a focus selector is at a first location in the messaging user interface that corresponds to a first digital image in the plurality of digital images, the first swipe gesture moving the focus selector in a first direction;

in response to detecting the first swipe gesture, scroll display of the plurality of digital images in the first direction on the display;

detect a second swipe gesture that starts while a focus selector is at a second location in the messaging user interface that corresponds to a second digital image in the plurality of digital images, the second swipe gesture moving the focus selector in a second direction, opposite the first direction; and

in response to detecting the second swipe gesture, display a first affordance for the digital camera and a second affordance for a photo library.

29. The non-transitory computer readable storage medium of claim **28**, wherein the one or more programs comprise instructions that cause the device to:

detect an input that activates the first affordance for the digital camera while displaying the first affordance for the digital camera; and,

in response to detecting the input that activates the first affordance for the digital camera, display a user interface for the digital camera over at least a portion of the messaging user interface.

30. The non-transitory computer readable storage medium of claim **28**, wherein the one or more programs comprise instructions that cause the device to:

detect an input that activates the second affordance for the photo library while displaying the second affordance for the photo library; and

in response to detecting the input that activates the second affordance for the photo library:

cease to display the plurality of digital images including one or more digital images stored in the memory and a live preview image from the digital camera and

display a plurality of digital images from a digital photo library; and

while displaying the plurality of digital images from the digital photo library:

detect an input that selects a digital image in the plurality of digital images from the digital photo library; and

in response to detecting the input that selects the digital image from the digital photo library:

display the digital image from the digital photo library in the conversation transcript, and

transmit a representation of the digital image from the digital photo library to one or more electronic devices that correspond to the at least one other user included in the messaging session, wherein the one or more electronic devices display the representation of the digital image from the digital photo library in a conversation transcript that corresponds to the messaging session.

* * * * *